

Task 1

FavoritesHistoryWorkspacesAdmin

Client Script - Task 1

Application scope: Global
Update set: Default (Global)

Client Script
Task 1

UpdateDelete

New client-scripts are run in strict mode, with direct DOM access disabled. Access to jQuery, prototype and the window object are likewise disabled. To disable this on a per-script basis, configure this form and add the "Isolate script" field. To disable this feature for all new globally-scoped client-side scripts set the system property "glide.script.block.client.globals" to false.

NameTask 1

TableRestaurant Order [u_restaurant_order]

UI TypeAll

TypeonChange

Field nameQuantity

ApplicationGlobal

Active☒

Inherited☐

Global☒

DescriptionQuantity is available

Messages

Script

```
1 function onChange(control, oldValue, newValue, isLoading, isTemplate) {
2   if (isLoading || newValue === '') {
3     return;
4   }
5   var availableStock = g_form.getValue('u_available');
6   var qty = parseFloat(newValue);
7   var stock = parseFloat(availableStock);
8   if (qty > stock) {
9     g_form.setValue('u_integer_1', '');
10    g_form.showFieldMsg('u_integer_1', 'Quantity exceeded the stock!', 'error');
11  }
12 }
```

Isolate script☒

UpdateDelete

Related Links

Run Print Scan

Task 2

servicenow

All

Client Script - Task 2

Application scope: Global
Update set: Default [Global]

Update

Delete

Client Script
Task 2

Update

Delete

New client-scripts are run in strict mode, with direct DOM access disabled. Access to jQuery, prototype and the window object are likewise disabled. To disable this on a per-script basis, configure this form and add the "Isolate script" field. To disable this feature for all new globally-scoped client-side scripts set the system property "glide.script.block.client.globals" to false.

Name

Task 2

Application

Global

Table

Restaurant Order [u_rest...

Active

☒

UI Type

All

Inherited

☐

Type

onChange

Global

☒

Field name

Dish Name

Description

Messages

Script

```
1 function onChange(control, oldValue, newValue, isLoading, isTemplate) {
2     if (isLoading || newValue === '') {
3         return;
4     }
5     switch (newValue) {
6         case 'pizza':
7             g_form.setValue('u_cuisine', 'italian');
8             break;
9         case 'noodles':
10            g_form.setValue('u_cuisine', 'japanese');
11            break;
12         case 'burger':
13            g_form.setValue('u_cuisine', 'fast food');
14            break;
15         default:
16            break;
17     }
18 }
```

Task 3

servicenow

All

Restaurant Order - ...

Ap...
Up...

<

Order Info
New record

?

...

Submit

* Dish Name

Quantity

1

State

Open

Assigned Waiter

cuisine

-- None --

available

20

Customer Info

Payment

Customer Name

Phone Number

Submit

servicenow

All

Restaurant Order - ...

Ap...
Up...

<

Order Info
New record

Submit

* Dish Nameindian

Quantity1

StateOpen

Assigned Waiter

available20

spice levellow

Customer InfoPayment

Customer Name

Phone Number

Submit

servicenow

All

Restaurant Order - ...

Ap...
Up...

<

Order Info
New record

Submit

* Dish Namethai

Quantity1

StateOpen

Assigned Waiter

available20

spice levelmedium

Customer InfoPayment

Customer Name

Phone Number

Submit

Task 4

servicenow

All

Client Script - Task 4

Ap... Up... 🔍 🌐 🗨️ 📄 ? 🛡️

< ☰

Client Script Task 4

🔗 ? ✚ ⚙️ ⋮

Update Delete

↑ ↓

New client-scripts are run in strict mode, with direct DOM access disabled. Access to jQuery, prototype and the window object are likewise disabled. To disable this on a per-script basis, configure this form and add the "Isolate script" field. To disable this feature for all new globally-scoped client-side scripts set the system property "glide.script.block.client.globals" to false.

NameTask 4

ApplicationGlobal ⓘ

TableRestaurant Order [u_rest... ▼]

Active☒

UI TypeAll ▼

Inherited☐

TypeonSubmit ▼

Global☒

Description ⓘ <>

Messages ⓘ <>

Script ⓘ <> ⌚ ⚙️ 🗨️ 📄 ⌨️ 🔍 🍷 ⬆️ 📄 ? 📄 🔄

```
1 function onSubmit() {
2   var qty = g_form.getValue('u_integer_1');
3   var qtyNum = parseFloat(qty);
4   if (qty === '' || isNaN(qtyNum) || qtyNum <= 0) {
5     g_form.hideFieldMsg('u_integer_1');
6     g_form.showFieldMsg('u_integer_1', 'Quantity must
7     be greater than 0 and not empty.', 'error');
8   }
9 }
```

Isolate script ☒

Update Delete

Related Links

[Run Point Scan](#)

Task 5

servicenow

All

Client Script - Task 5

Ap... Up...

?

+

≡

...

Update

Delete

<

≡

Client Script Task 5

New client-scripts are run in strict mode, with direct DOM access disabled. Access to jQuery, prototype and the window object are likewise disabled. To disable this on a per-script basis, configure this form and add the "Isolate script" field. To disable this feature for all new globally-scoped client-side scripts set the system property "glide.script.block.client.globals" to false.

NameTask 5

ApplicationGlobal ⓘ

TableRestaurant Order [u_rest... ▼

Active☒

UI TypeAll ▼

Inherited☐

TypeonChange ▼

Global☒

Field nameQuantity ▼

Description ⓘ <>

Messages ⓘ <>

Script ⓘ <>

1

function onChange(control, oldValue, newValue, isLoading, isTemplate) {

2

if (isLoading || newValue === '') {

3

return;

4

}

5

var total= newValue * g_form.getValue('u_dish_price');

6

g_form.setValue('u_total_amount', total);

7

}

Isolate script☒

Update

Delete

Related Links

[Run Point Scan](#)