

JAVASERVER FACES COURSE

EXERCISE

HANDLING OF COMPONENTS IN JSF




JAVASERVER FACES COURSE

www.globalmentoring.com.mx

EXERCISE OBJECTIVE

The objective of this exercise is to implement some of the Components of those available in JSF. We will convert the City field from h: inputText to h: selectOneMenu. The result will be similar to the following:




The screenshot shows a web browser window with the title 'Job Agency V7' and the URL 'localhost:8080/JobAgencyV7/faces/index.xhtml'. The form contains the following fields:

- Name:
- Last Name:
- Desired Salary:
- Birthdate:
- Zip Code:
- City:

A yellow arrow points from the Zip Code field to the City dropdown. Below the form are a [Show](#) link and a button.


1. OPEN THE PROJECT

We open the JobAgencyV6 project, just in case we do not have it open:



1. OPEN THE PROJECT

We open the JobAgencyV6 project, just in case we do not have it open:




JAVASERVER FACES COURSE

www.globalmentoring.com.mx


2. COPY THE PROJECT

We copy the JobAgencyV6 project:




2. COPY THE PROJECT

We copy the JobAgencyV6 project, we rename it to JobAgencyV7 and deposit it in the new path shown:




3. CLOSE THE PROJECT

We closed the previous project, and left only the new one open:




4. RENAME THE PROJECT

Change the name of the project to JobAgencyV7:



4. RENAME THE PROJECT

Change the name of the project to JobAgencyV7:



Rename Project

Rename Project "JobAgencyV6"

☒ Change Display Name: JobAgencyV7

☒ Change ArtifactID: JobAgencyV7

☐ Rename Folder: JobAgencyV7

OK Cancel

JAVASERVER FACES COURSE

www.globalmentoring.com.mx

5. MODIFY THE JAVA CLASS

Open the Candidate.java class and perform the following actions :

- Remove the city property
- Remove the getCity () method
- Remove the setCity () method

Add the following property:

```
private long cityId;
```

Generate the getter and setter methods for this new property

5. MODIFY THE CODE

Candidate.java:

[Click to download](#)

```
package beans.model;

import java.util.Date;
import javax.inject.Named;
import javax.enterprise.context.RequestScoped;
import org.apache.logging.log4j.*;

@Named
@RequestScoped
public class Candidate {

    Logger log = LogManager.getRootLogger();

    private String name;
    private String lastName;
    private int desiredSalary;
    private Date birthdate;
    private String zipCode;
    private String cityId;
    private String comment;

    public Candidate() {
        log.info("Creating the Candidate object");
        this.setName("Introduce your name");
    }

    public String getName() {
        return name;
    }
}
```


5. MODIFY THE CODE

Candidate.java:

[Click to download](#)

```
public void setName(String name) {
    this.name = name;
}

public String getLastName() {
    return lastName;
}

public void setLastName(String lastName) {
    this.lastName = lastName;
}

public int getDesiredSalary() {
    return desiredSalary;
}

public void setDesiredSalary(int desiredSalary) {
    this.desiredSalary = desiredSalary;
}

public Date getBirthdate() {
    return birthdate;
}

public void setBirthdate(Date birthdate) {
    this.birthdate = birthdate;
}

public String getZipCode() {
    return zipCode;
}
```

5. MODIFY THE CODE

[Candidate.java:](#)

[Click to download](#)

```
public void setZipCode(String zipCode) {  
    this.zipCode = zipCode;  
}  
  
public String getCityId() {  
    return cityId;  
}  
  
public void setCityId(String cityId) {  
    this.cityId = cityId;  
}  
  
public String getComment() {  
    return comment;  
}  
  
public void setComment(String comment) {  
    this.comment = comment;  
}  
}
```

JAVASERVER FACES COURSE

www.globalmentoring.com.mx

6. MODIFY THE PROPERTIES FILE

Open the messages.properties file and make the following changes:

Delete the following field:

```
vacanteForm.city=City
```

Add the new fields

```
vacanteForm.cityId=City  
vacanteForm.select=-- Select --
```

Make the same changes in the messages_es.properties file in the corresponding language.

6. MODIFY THE CODE

[messages.properties:](#)

[Click to download](#)

```
vacantForm.name=Name  
vacantForm.lastName=Last Name  
vacantForm.desiredSalary=Desired Salary  
vacantForm.birthdate=Birthdate  
vacantForm.zipCode=Zip Code  
vacantForm.send=Send  
vacantForm.comment=Comment  
vacantForm.show=Show  
vacantForm.hide=Hide  
vacantForm.cityId=City  
vacantForm.select=-- Select --
```

JAVASERVER FACES COURSE

www.globalmentoring.com.mx

7. MODIFY THE CODE

[messages_es.properties:](#)

[Click to download](#)

```
vacantForm.name=Nombre  
vacantForm.lastName=Apellido  
vacantForm.desiredSalary=Sueldo Deseado  
vacantForm.birthdate=Fecha de nacimiento  
vacantForm.zipCode=Codigo Postal  
vacantForm.send=Enviar  
vacantForm.comment=Comentario  
vacantForm.show=Mostrar  
vacantForm.hide=Ocultar  
vacantForm.cityId=Ciudad  
vacantForm.select=-- Seleccionar --
```

JAVASERVER FACES COURSE

www.globalmentoring.com.mx

8. MODIFY THE XHTML FILE

Modify the index.xhtml file. We are going to make several changes:

1) Remove the following tag:

```
<td><h:inputText id="city" required="true" value="#{candidate.city}" /></td>
```

2) Insert the following code instead of the one we have removed:

```
<td>
    <h:selectOneMenu id="cityId" required="true" value="#{candidate.cityId}">
        <f:selectItem itemLabel="#{msgs['vacanteForm.select']}" itemValue="" />
        <f:selectItem itemLabel="Phoenix" itemValue="1" />
        <f:selectItem itemLabel="Little Rock" itemValue="2" />
        <f:selectItem itemLabel="Huntsville" itemValue="3" />
    </h:selectOneMenu>
</td>
```


8. MODIFY THE XHTML

Search for h: outputLabel for the cityId field and make the following changes:

Change the h: ouputLabel from:

```
<h:outputLabel for="city" value="#{msgs['vacantForm.city']}"
```

By the following:

```
<h:outputLabel for="cityId" value="#{msgs['vacantForm.cityId']}" />
```

8. MODIFY THE XHTML FILE

Change the h: message from :

```
<h:message for="city" />
```

By the following :

```
<h:message for="cityId" />
```

The index.xhtml file should be as follows:

8. MODIFY THE FILE

[index.xhtml:](#)

[Click to download](#)

```
<!DOCTYPE html>
<html xmlns="http://www.w3.org/1999/xhtml"
      xmlns:h="http://java.sun.com/jsf/html"
      xmlns:f="http://xmlns.jcp.org/jsf/core">
  <h:head>
    <title>Job Agency V7</title>
  </h:head>
  <h:body>
    <h:form id="vacantForm">

      <h:messages globalOnly="true" ></h:messages>

      <table>
        <tr>
          <td><h:outputLabel for="name" value="#{msgs['vacantForm.name']}" /></td>
          <td><h:inputText id="name" required="true" value="#{candidate.name}" /></td>
          <td><h:message for="name" /></td>
        </tr>
        <tr>
          <td><h:outputLabel for="lastName" value="#{msgs['vacantForm.lastName']}" /></td>
          <td><h:inputText id="lastName" required="true" value="#{candidate.lastName}" /></td>
          <td><h:message for="lastName" /></td>
        </tr>
      </table>
    </h:form>
  </h:body>
</html>
```

JAVASERVER FACES COURSE

www.globalmentoring.com.mx

8. MODIFY THE FILE

[index.xhtml:](#)

[Click to download](#)

```
<tr>
  <td><h:outputLabel for="desiredSalary" value="#{msgs['vacantForm.desiredSalary']}" /></td>
  <td><h:inputText id="desiredSalary" required="true"
    value="#{candidate.desiredSalary}">
    <f:validateLongRange minimum="500" maximum="5000"/>
  </h:inputText></td>
  <td><h:message for="desiredSalary" /></td>
</tr>
<tr>
  <td><h:outputLabel for="birthdate" value="#{msgs['vacantForm.birthdate']}" /></td>
  <td><h:inputText id="birthdate" required="true"
    value="#{candidate.birthdate}">
    <f:convertDateTime pattern="MM/dd/yyyy" />
  </h:inputText></td>
  <td><h:message for="birthdate" /></td>
</tr>
<tr>
  <td><h:outputLabel for="zipCode" value="#{msgs['vacantForm.zipCode']}" /></td>
  <td><h:inputText id="zipCode" immediate="true"
    onchange="this.form.submit()" required="true"
    value="#{candidate.zipCode}"
    valueChangeListener="#{vacantForm.zipCodeListener}" /></td>
  <td><h:message for="zipCode" /></td>
</tr>
```

JAVASERVER FACES COURSE

www.globalmentoring.com.mx

8. MODIFY THE FILE

[index.xhtml:](#)

[Click to download](#)

```
<tr>
  <td><h:outputLabel for="cityId" value="#{msgs['vacantForm.cityId']}" /></td>
  <td>
    <h:selectOneMenu id="cityId" required="true" value="#{candidate.cityId}">
      <f:selectItem itemLabel="#{msgs['vacantForm.select']}" itemValue="" />
      <f:selectItem itemLabel="Phoenix" itemValue="1" />
      <f:selectItem itemLabel="Little Rock" itemValue="2" />
      <f:selectItem itemLabel="Huntsville" itemValue="3" />
    </h:selectOneMenu>
  </td>

  <td><h:message for="cityId" /></td>
</tr>
</table>
<table>
  <tr>
    <td>
      <h:commandLink actionListener="#{vacantForm.hideComment}"
        immediate="true" rendered="#{!vacantForm.commentSent}"
        value="#{msgs['vacantForm.show']}" />
      <h:commandLink actionListener="#{vacantForm.hideComment}"
        immediate="true" rendered="#{vacantForm.commentSent}"
        value="#{msgs['vacantForm.hide']}" />
    </td>
  </tr>
</table>
```

8. MODIFY THE FILE

index.xhtml:

Click to download

```
<h:panelGroup rendered="#{vacantForm.commentSent}">
  <table>
    <tr>
      <td><h:outputLabel for="comment" value="#{msgs['vacantForm.comment']}" /></td>
    </tr>
    <tr>
      <td><h:inputTextarea id="comment" cols="50" rows="10" value="#{candidate.comment}" /></td>
    </tr>
  </table>
</h:panelGroup>
<h:commandButton action="#{vacantForm.send}" value="#{msgs['vacantForm.send']}" />
</h:form>
</h:body>
</html>
```

JAVASERVER FACES COURSE

www.globalmentoring.com.mx

9. MODIFY THE JAVA FILE

Modify the VacanteForm.java file.

Replace the code of the zipCodeListener ():

```
UIInput cityInputText = (UIInput) uiViewRoot.findComponent("vacanteForm:city");  
String city = "Phoenix";  
cityInputText.setValue(city);  
cityInputText.setSubmittedValue(city);
```

By the following:

```
UIInput cityInputText = (UIInput) uiViewRoot.findComponent("vacanteForm:cityId");  
Long cityId = 1L;  
cityInputText.setValue(cityId);  
cityInputText.setSubmittedValue(Long.toString(cityId));
```

9. MODIFY THE CODE

VacanteForm.java:

[Click to download](#)

```
package beans.backing;

import beans.model.Candidate;
import javax.inject.*;
import javax.enterprise.context.RequestScoped;
import javax.faces.application.FacesMessage;
import javax.faces.component.*;
import javax.faces.context.FacesContext;
import javax.faces.event.*;
import org.apache.logging.log4j.*;

@Named
@RequestScoped
public class VacantForm {

    Logger log = LogManager.getRootLogger();

    @Inject
    private Candidate candidate;

    private boolean commentSent = false;

    public VacantForm() {
        log.info("Creating VacantForm object");
    }

    public void setCandidate(Candidate candidate) {
        this.candidate = candidate;
    }
}
```

9. MODIFY THE CODE

VacanteForm.java:

[Click to download](#)

```
public String send() {
    log.info("send() Name=" + this.candidate.getName());
    log.info("send() Desired Salary=" + this.candidate.getDesiredSalary());

    if (this.candidate.getName().equals("John")) {

        if (this.candidate.getLastName().equals("Smith")) {
            String msg = "Thanks, but John Smith is already working with us.";
            FacesMessage facesMessage = new FacesMessage(FacesMessage.SEVERITY_ERROR, msg, msg);
            FacesContext facesContext = FacesContext.getCurrentInstance();
            String componentId = null; //This is a global message
            facesContext.addMessage(componentId, facesMessage);
            return "index";
        }
        return "success";//success.xhtml
    } else {
        return "failure"; //failure.xhtml
    }
}
```

JAVASERVER FACES COURSE

www.globalmentoring.com.mx

9. MODIFY THE CODE

VacanteForm.java:

[Click to download](#)

```
//Method of type Value Change Listener
public void zipCodeListener(ValueChangeEvent valueChangeEvent) {
    FacesContext facesContext = FacesContext.getCurrentInstance();
    UIViewRoot uiViewRoot = facesContext.getViewRoot();
    String newZipCode = (String) valueChangeEvent.getNewValue();
    if ("85001".equals(newZipCode)) {
        log.info("Modify the city value dynamically with ValueChangeListener");
        //We use the name of the form of index.xhtml to find the component
        UIInput cityInputText = (UIInput) uiViewRoot.findComponent("vacantForm:cityId");
        Long cityId = 1L;
        cityInputText.setValue(cityId);
        cityInputText.setSubmittedValue(Long.toString(cityId));
        //Return the response
        facesContext.renderResponse();
    }
}

public void hideComment(ActionEvent actionEvent) {
    this.setCommentSent(!this.commentSent);
    log.info("Executing actionEvent hideComment");
}
```

JAVASERVER FACES COURSE

www.globalmentoring.com.mx

9. MODIFY THE CODE

VacanteForm.java:

[Click to download](#)


```
public boolean isCommentSent() {  
    return commentSent;  
}  
  
public void setCommentSent(boolean commentSent) {  
    this.commentSent = commentSent;  
}  
}
```

JAVASERVER FACES COURSE

www.globalmentoring.com.mx


10. EXECUTE THE PROJECT

Execute the project:



10. EXECUTE THE PROJECT

Execute the project:



The screenshot shows a web browser window with the title 'Job Agency V7'. The address bar displays 'localhost:8080/JobAgencyV7/faces/index.xhtml'. The form contains the following fields and controls:

- Name:
- Last Name:
- Desired Salary:
- Birthdate:
- Zip Code:
- City:
- [Show](#)
-

A yellow arrow points to the City dropdown menu.

JAVASERVER FACES COURSE

www.globalmentoring.com.mx

EXERCISE CONCLUSION

With this exercise we put into practice the concept of components in JSF.

We use the SelectItem component, which will be one of the components that we will use the most in our JSF forms.

One of the great advantages of using JSF components is that many of the components are just as simple to apply or use once having the basics of handling JSF components.



JAVASERVER FACES COURSE

www.globalmentoring.com.mx

ONLINE COURSE

JAVASERVER FACES (JSF)

By: Eng. Ubaldo Acosta



JAVASERVER FACES COURSE

www.globalmentoring.com.mx