

STRUTS FRAMEWORK COURSE

INTERNATIONALIZATION WITH STRUTS 2 FRAMEWORK



By the expert: Ubaldo Acosta




STRUTS FRAMEWORK COURSE

www.globalmentoring.com.mx

EXERCISE OBJECTIVE

Create an application to implement the use of internationalization with Struts 2. At the end we must observe the following:



EXERCISE REQUIREMENT

In this project we are going to put into practice the concept of Internationalization in Struts 2.

Although we have already used the concept of message handling, in this exercise we will see how to handle different languages, using the concept of internationalization or localization.

Let's see how our exercise is:




STRUTS FRAMEWORK COURSE

www.globalmentoring.com.mx


CLOSE PROJECTS THAT WE NO LONGER USE

- We close any other project that we no longer use, if we wish :




1. CREATE A NEW PROJECT

- We create the new project as shown below:



1. CREATE A NEW PROJECT

- We create the new project as shown below:



1. CREATE A NEW PROJECT

- We create the new project as shown below :

New Web Application

Steps

1. Choose Project
- 2. Name and Location**
3. Settings

Name and Location

Project Name:

Project Location:

Project Folder:

Artifact Id:

Group Id:

Version:

Package: (Optional)

STRUTS FRAMEWORK COURSE

www.globalmentoring.com.mx

1. CREATE A NEW PROJECT

- We select the values shown:

New Web Application

Steps

1. Choose Project
2. Name and Location
3. **Settings**

Settings


Server: Add...

Java EE Version:

< Back Next > **Finish** Cancel Help


2. OPEN MAVEN'S POM.XML FILE

- The maven pom.xml file manages the Java libraries we will use :



2. OPEN MAVEN'S POM.XML FILE

- Once opened, we will modify the information completely of this file, with the information provided below:



3. MODIFY THE CODE

[pom.xml:](#)

[Click to download](#)

```
<?xml version="1.0" encoding="UTF-8"?>
<project xmlns="http://maven.apache.org/POM/4.0.0" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="http://maven.apache.org/POM/4.0.0 http://maven.apache.org/xsd/maven-4.0.0.xsd">
    <modelVersion>4.0.0</modelVersion>

    <groupId>web</groupId>
    <artifactId>InternationalizationStruts</artifactId>
    <version>1</version>
    <packaging>war</packaging>

    <name>InternationalizationStruts</name>

    <properties>
        <project.build.sourceEncoding>UTF-8</project.build.sourceEncoding>
    </properties>

    <dependencies>
        <dependency>
            <groupId>javax</groupId>
            <artifactId>javaee-web-api</artifactId>
            <version>8.0</version>
            <scope>provided</scope>
        </dependency>
        <dependency>
            <groupId>org.apache.struts</groupId>
            <artifactId>struts2-core</artifactId>
            <version>2.5.17</version>
        </dependency>
    </dependencies>
</project>
```


3. MODIFY THE CODE

[pom.xml:](#)

[Click to download](#)

```
<dependency>
  <groupId>org.apache.logging.log4j</groupId>
  <artifactId>log4j-api</artifactId>
  <version>2.11.1</version>
</dependency>
<dependency>
  <groupId>org.apache.logging.log4j</groupId>
  <artifactId>log4j-core</artifactId>
  <version>2.11.1</version>
</dependency>
<dependency>
  <groupId>org.apache.struts</groupId>
  <artifactId>struts2-convention-plugin</artifactId>
  <version>2.5.17</version>
</dependency>
</dependencies>
```

CURSO DE JAVA CON JDBC

www.globalmentoring.com.mx

3. MODIFY THE CODE

[pom.xml:](#)

[Click to download](#)

```
<build>
  <plugins>
    <plugin>
      <groupId>org.apache.maven.plugins</groupId>
      <artifactId>maven-war-plugin</artifactId>
      <version>2.3</version>
      <configuration>
        <failOnMissingWebXml>false</failOnMissingWebXml>
      </configuration>
    </plugin>
    <plugin>
      <groupId>org.apache.maven.plugins</groupId>
      <artifactId>maven-compiler-plugin</artifactId>
      <version>3.7.0</version>
      <configuration>
        <source>1.8</source>
        <target>1.8</target>
      </configuration>
    </plugin>
  </plugins>
</build>


</project>
```

CURSO DE JAVA CON JDBC

www.globalmentoring.com.mx


4. STOP GLASSFISH IF IT WAS STARTED

- Before doing Clean & Build of the project to download the new libraries, we verify that the Glassfish server is not started as there may be problems to do the Clean & build process if the server is started. This step is only verification :



5. EXECUTE CLEAN & BUILD

- In order to download the new libraries, we make Clean & Build the project. If for some reason this process fails, you must disable any software such as antivirus, Windows defender or firewall during this process so that the download of Java .jar files is not prevented. Once finished, these services can be activated again. This process may take several minutes depending on your internet speed:



5. EXECUTE CLEAN & BUILD

- If you no longer had to download any library because you could already have all downloaded, the process is faster. In the end we should observe the following:

```
Output - Build (InternationalizationStruts) X
--- maven-war-plugin:2.3:war (default-war) @ InternationalizationStruts ---
Packaging webapp
Assembling webapp [InternationalizationStruts] in [C:\Courses\Struts\Lesson10\InternationalizationStruts\target\Inte
Processing war project
Copying webapp resources [C:\Courses\Struts\Lesson10\InternationalizationStruts\src\main\webapp]
Webapp assembled in [25 msecs]
Building war: C:\Courses\Struts\Lesson10\InternationalizationStruts\target\InternationalizationStruts-1.war
--- maven-install-plugin:2.3.1:install (default-install) @ InternationalizationStruts ---
Installing C:\Courses\Struts\Lesson10\InternationalizationStruts\target\InternationalizationStruts-1.war to C:\Users
Installing C:\Courses\Struts\Lesson10\InternationalizationStruts\pom.xml to C:\Users\user\.m2\repository\web\Intern
-----
BUILD SUCCESS
-----
Total time: 5.870s
Finished at: Thu Aug 30 14:00:52
Final Memory: 15M/489M
-----
```

STRUTS FRAMEWORK COURSE

www.globalmentoring.com.mx

6. CREATE AN XML FILE

We are going to create the web.xml file below

This file is what allows us to join a Java Web application with the Struts framework, configuring the Struts filter in the web.xml file.




STRUTS FRAMEWORK COURSE

www.globalmentoring.com.mx

6. CREATE AN XML FILE

- We create the web.xml file and add it to the WEB-INF folder as shown:



6. CREATE AN XML FILE

- The name of the file is web, it is not necessary to add the extension, it adds it in automatic the IDE since it is an XML type document. Finally we provide the path shown:

New XML Document

Steps

1. Choose File Type
- 2. Name and Location**
3. Select Document Type
4. ...

Name and Location

File Name:

Project:

Folder:

Created File:

6. CREATE AN XML FILE

- We select the indicated type and click on finish:

The screenshot shows a 'New File' dialog box with a 'Steps' list on the left and a 'Select Document Type' section on the right. The 'Steps' list includes: 1. Choose File Type, 2. Name and Location, 3. Select Document Type (highlighted with a red circle containing the number 1), and 4. ... The 'Select Document Type' section has a text prompt: 'Select the type of XML document you want to create based on your document structure, data types, and namespace requirements.' Below this, there are three radio button options: 'Well-formed Document' (selected and highlighted with a red circle), 'DTD-Constrained Document', and 'XML Schema-Constrained Document'. At the bottom of the dialog, there are four buttons: '< Back', 'Next >', 'Finish' (highlighted with a red circle containing the number 2 and a red arrow pointing to it), and 'Cancel'. A 'Help' button is also present.

New File

Steps

1. Choose File Type
2. Name and Location
3. **Select Document Type**
4. ...

Select Document Type

Select the type of XML document you want to create based on your document structure, data types, and namespace requirements.

☒ Well-formed Document

☐ DTD-Constrained Document

☐ XML Schema-Constrained Document

< Back Next > **Finish** Cancel Help

7. MODIFY THE CODE

web.xml:

[Click to download](#)

```
<?xml version="1.0" encoding="UTF-8"?>
<web-app version="4.0"
  xmlns="http://xmlns.jcp.org/xml/ns/javaee"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://xmlns.jcp.org/xml/ns/javaee
http://xmlns.jcp.org/xml/ns/javaee/web-app_4_0.xsd">

  <filter>
    <filter-name>struts2</filter-name>
    <filter-class>org.apache.struts2.dispatcher.filter.StrutsPrepareAndExecuteFilter</filter-class>
  </filter>
  <filter-mapping>
    <filter-name>struts2</filter-name>
    <url-pattern>/*</url-pattern>
  </filter-mapping>

</web-app>
```

STRUTS FRAMEWORK COURSE

www.globalmentoring.com.mx

8. MODIFY THE INDEX.HTML FILE

In automatic the IDE adds a file called index.html. However, if this file is not created we must add it to the project at the root level of Web Pages.

The index.html file really is not yet part of the Struts framework, however it will be the entry point for the Struts framework to be executed, since from this file we will indicate which action we want to execute.

In this exercise the path that we will use will be: [messages](#)




STRUTS FRAMEWORK COURSE

www.globalmentoring.com.mx

8. MODIFY THE INDEX.HTML FILE

- Modify the index.html file. In case this file does not exist at the root level of the Web Pages folder, we create it, as shown:



8. MODIFY THE FILE

[index.html:](#)

[Click to download](#)

```
<!DOCTYPE html>
<html>
  <head>
    <title>Home</title>
    <meta charset="UTF-8">
  </head>
  <body>
    <a href="messages">Go to the system</a>
  </body>
</html>
```

STRUTS FRAMEWORK COURSE

www.globalmentoring.com.mx

9. CREATE A NEW JAVA CLASS

The class MessagesAction.java that we are going to create next will act as Controller (Action) and Model (Bean).

We will extend the ActionSupport class and overwrite the execute method.

We are going to apply the internationalization topic, so in order to change the language our Action class must receive the request_locale parameter from the respective view and in this way the interceptor of Struts 2 that is responsible for managing the concept of internationalization will be the one that will select the resource bundle (property file with messages in the corresponding language) according to the specified language.

Let's see how our class is.




STRUTS FRAMEWORK COURSE

www.globalmentoring.com.mx

9. CREATE A NEW JAVA CLASS

- We create the MessagesAction.java class:



STRUTS FRAMEWORK COURSE

www.globalmentoring.com.mx

9. CREATE A NEW JAVA CLASS

- We create the MessagesAction.java class:

New Java Class

Steps

1. Choose File Type
2. **Name and Location**

Name and Location

Class Name: MessagesAction

Project: InternationalizationStruts

Location: Source Packages

Package: web.actions

Created File: C:\Courses\Struts\Lesson10\InternationalizationStruts\src\main\java\web\actions\MessagesAction.java

< Back Next > **Finish** Cancel Help

10. MODIFY THE CODE

MessagesAction.java:

[Click to download](#)

```
package web.actions;

import com.opensymphony.xwork2.ActionSupport;
import org.apache.logging.log4j.*;

public class MessagesAction extends ActionSupport {

    Logger log = LogManager.getLogger(MessagesAction.class);

    private String name;

    @Override
    public String execute() {
        log.info("Name value:" + name);
        return SUCCESS;
    }

    public String getName() {
        return name;
    }

    public void setName(String name) {
        this.name = name;
    }
}
```

11. CREATE A PROPERTIES FILE

We will create two properties files, the first will have the messages of the application in English (en), and the second will have the messages in Spanish (es) according to the i18n standard.

Let's see how our file is.




STRUTS FRAMEWORK COURSE

www.globalmentoring.com.mx

11. CREATE A PROPERTIES FILE

- We created the MessagesAction_en.properties file:



STRUTS FRAMEWORK COURSE

www.globalmentoring.com.mx

11. CREATE A PROPERTIES FILE

- We created the MessagesAction_en.properties file :

New Properties File [X]

Steps

1. Choose File Type
2. **Name and Location**

Name and Location

File Name:

Project:

Folder:

Created File:

< Back Next > **Finish** Cancel Help

12. MODIFY THE FILE

[MessagesAction_en.properties:](#)

[Click to download](#)

```
title=Struts 2 Localization  
name=Name  
send=Send  
name.send=Sent name is:  
idiom.english=English  
idiom.spanish=Spanish
```


13. CREATE A PROPERTIES FILE

We are now going to create the second properties file, which will contain the messages in Spanish (es) according to the i18n standard.

Let's see how our file is.




STRUTS FRAMEWORK COURSE

www.globalmentoring.com.mx

13. CREATE A PROPERTIES FILE

- We created the MessagesAction_es.properties file:



STRUTS FRAMEWORK COURSE

www.globalmentoring.com.mx

13. CREATE A PROPERTIES FILE

- We created the MessagesAction_es.properties file:

New Properties File [X]

Steps

1. Choose File Type
2. **Name and Location**

Name and Location

File Name:

Project:

Folder:

Created File:

< Back Next > **Finish** Cancel Help

14. MODIFY THE FILE

[MessagesAction_es.properties:](#)

[Click to download](#)

```
title=Internacionalización con Struts  
name=Nombre  
send=Enviar  
name.send=Nombre proporcionado:  
idiom.english=Inglés  
idiom.spanish=Español
```

15. CREATE A NEW JSP FILE

Now we create the file: messages.jsp. Remember that this name corresponds to the path that will be used to call the corresponding action MessagesAction.java

We must also deposit this JSP in the folder [/WEB-INF/content](#) as we have seen in the Struts 2 conventions topic.




STRUTS FRAMEWORK COURSE

www.globalmentoring.com.mx

15. CREATE A NEW JSP FILE

- We create the messages.jsp file:



15. CREATE A NEW JSP FILE

- We created the messages.jsp file in the path shown :

New JSP

Steps

1. Choose File Type
2. **Name and Location**

Name and Location

File Name:

Project:

Location:

Folder:

Created File:

Options:

☒ JSP File (Standard Syntax) ☐ Create as a JSP Segment

☐ JSP Document (XML Syntax)

Description:

16. MODIFY THE FILE

[messages.jsp:](#)

[Click to download](#)

```
<%@page contentType="text/html" pageEncoding="UTF-8"%>
<%@taglib prefix="s" uri="/struts-tags" %>
<!DOCTYPE html>
<html>
  <head>
    <title><s:text name="title" /></title>
    <s:head />
  </head>
  <body>
    <h1><s:text name="title" /></h1>
    <s:form>
      <s:textfield key="name" name="name" />
      <s:submit key="send"/>
    </s:form>

    <s:if test='name!=null && !"".equals(name.trim())'>
      <s:text name="name.send" /> <s:property value="name" />
    </s:if>
```

16. MODIFY THE FILE

[messages.jsp:](#)

[Click to download](#)

```
<br/>
<br/>
<!-- Create the URL-->
<s:url var="localeEN" action="messages" >
  <s:param name="request_locale" >en</s:param>
</s:url>
<s:url var="localeES" action="messages" >
  <s:param name="request_locale" >es</s:param>
</s:url>

<!-- We use the URLs. The request_locale parameter changes language -->
<s:a href="%{localeEN}" ><s:text name="idiom.english" /></s:a>
|
<s:a href="%{localeES}" ><s:text name="idiom.spanish" /></s:a>
</body>
</html>
```


17. CREATE THE LOG4J2.XML FILE

We create a log4j2.xml file. The log4j API allows us to manage the log or log of a Java application in a simpler way.

We place this file in the resource path of the maven project. If maven is not used then the file must be deposited at the root level of the Java code src.




STRUTS FRAMEWORK COURSE

www.globalmentoring.com.mx

17. CREATE THE LOG4J2.XML FILE

- We create the log4j2.xml file as follows:



17. CREATE THE LOG4J2.XML FILE

- We deposit the file in the resources folder as shown:

New XML Document

Steps

1. Choose File Type
2. **Name and Location**
3. Select Document Type
4. ...

Name and Location

File Name:


Project:

Folder:

Created File:

17. CREATE THE LOG4J2.XML FILE

- We select the option shown:



STRUTS FRAMEWORK COURSE

www.globalmentoring.com.mx

18. MODIFY THE FILE

log4j2.xml:

[Click to download](#)


```
<?xml version="1.0" encoding="UTF-8"?>
<Configuration>
  <Appenders>
    <Console name="STDOUT" target="SYSTEM_OUT">
      <PatternLayout pattern="%F:%L) - %m%n"/>
    </Console>
  </Appenders>
  <Loggers>
    <Logger name="com.opensymphony.xwork2" level="info"/>
    <Logger name="org.apache.struts2" level="info"/>
    <Root level="info">
      <AppenderRef ref="STDOUT"/>
    </Root>
  </Loggers>
</Configuration>
```

STRUTS FRAMEWORK COURSE

www.globalmentoring.com.mx

19. EXECUTE CLEAN & BUILD

- We execute the Clean & Build command as shown, to obtain the latest version of each file:




STRUTS FRAMEWORK COURSE

www.globalmentoring.com.mx

19. EXECUTE CLEAN & BUILD


- We must observe a result similar to the following:



```
Output - Build (InternationalizationStruts) X
--- maven-war-plugin:2.3:war (default-war) @ InternationalizationStruts ---
Packaging webapp
Assembling webapp [InternationalizationStruts] in [C:\Courses\Struts\Lesson10\InternationalizationStruts\target\Inte
Processing war project
Copying webapp resources [C:\Courses\Struts\Lesson10\InternationalizationStruts\src\main\webapp]
Webapp assembled in [409 msecs]
Building war: C:\Courses\Struts\Lesson10\InternationalizationStruts\target\InternationalizationStruts-1.war
--- maven-install-plugin:2.3.1:install (default-install) @ InternationalizationStruts ---
Installing C:\Courses\Struts\Lesson10\InternationalizationStruts\target\InternationalizationStruts-1.war to C:\Users
Installing C:\Courses\Struts\Lesson10\InternationalizationStruts\pom.xml to C:\Users\user\.m2\repository\web\Interna
-----
BUILD SUCCESS
-----
Total time: 6.429s
Finished at: Thu Aug 30 17:35:27
Final Memory: 19M/295M
-----
```


20. EXECUTE THE APPLICATION

- We run the application as follows:




20. EXECUTE THE APPLICATION

- We run the application as follows:



20. EXECUTE THE APPLICATION

- Fill the form and click on Send, in this case it first appears in English, but the default language depends on the configuration of our Web browser :



Ubaldo

Struts 2 Localization

localhost:8080/InternationalizationStruts/messages.action

Struts 2 Localization


Name:

Sent name is: John

[English](#) | [Spanish](#)

20. EXECUTE THE APPLICATION

- If we want to change the language, we click on the desired language, eg. Spanish. We can see that the `request_locale=es` is sent in, and with this it is enough to change the language:



20. EXECUTE THE APPLICATION

- We note that the properties file has now been loaded in the Spanish language (es):



20. EXECUTE THE APPLICATION

- Finally, to return again to the English language, just click on the respective option and send the parameter `request_locale=en`



FINAL RECOMMENDATIONS

If for some reason the exercise fails, several things can be done to correct it:

1. Stop the Glassfish server
2. Make a Clean & Build project to have the most recent version compiled
3. Restart the project (deploy the project to the server again)

If the above does not work, you can try loading the resolved project which is 100% functional and rule out configuration problems in your environment or any other code error.



STRUTS FRAMEWORK COURSE

www.globalmentoring.com.mx

EXERCISE CONCLUSION

With this exercise we put into practice the concept of internationalization with Struts 2.

Although in this project we could have applied more features such as validations, error handling, etc., we left it as something optional so that you can put it into practice yourself. In this exercise we have left this project as simple as possible so that the use of Internationalization is clear when we work with Struts 2.

This topic as we have seen is an extension of the handling of Messages with Struts 2, and just by extending the ActionSupport class and working with the default implementation of Struts, we have access to this feature automatically.

With this we conclude the message topic and Internationalization with Struts 2.

ONLINE COURSE

STRUTS 2 FRAMEWORK

By: Eng. Ubaldo Acosta



STRUTS FRAMEWORK COURSE

www.globalmentoring.com.mx