

# KUBERNETES ZERO TO HERO

## APPLICATION

```
cd /mnt/c/users/hafsa/downloads
mv fixed-k8s.sh ~
mv minikube-reset-script.sh ~
./ fixed-k8s.sh
cd /home/hafsa_027/k8s-master-app
./scripts/deploy.sh
cd /mnt/c/users/hafsa/downloads
mv deploy-no-validate.sh /k8s-master-app/scripts
./deploy-no-validate.sh
./scripts/deploy.sh
```

IsADirectoryError: [Errno 21] Is a directory: '/logs'

FIX IT:-

If **LOG\_PATH** is set (**/logs**), it appends **'app.log'**, resulting in **/logs/app.log**

code .

minikube service k8s-master-app -n k8s-demo(open the link in the browser)

## FLOWCHART of deploy.sh:-

**Start**

| **1**

**Check prerequisites**

(minikube, kubectl, docker installed)

| **2**

**Start Minikube** (if not running)

minikube status,

minikube start --cpus=2 --memory=4096 --disk-size=20g

minikube start --driver=docker

| 3

**Enable Addons** (dashboard [img1])

| 4

**Configure Docker** `eval $(minikube docker-env)`

| 5

**Build Docker Image**

`docker build --network=host -t k8s-master-app:latest .`

| 6

**Apply Kubernetes manifests**

Namespace Creation: `kubectl apply -f k8s/base/namespace.yaml`

ConfigMap and Volume Setup: `kubectl apply -f k8s/volumes/volumes.yaml`

Application Settings ConfigMap: `kubectl apply -f k8s/config/configmap.yaml`

Secrets Management: `kubectl apply -f k8s/config/secret.yaml`

Deployment Creation: `kubectl apply -f k8s/base/deployment.yaml`

Service Exposure: `kubectl apply -f k8s/networking/service.yaml`

Horizontal Pod Autoscaler (HPA): `kubectl apply -f k8s/monitoring/hpa.yaml`

| 7

**Wait for Deploy (check rollout)**

`kubectl -n k8s-demo get pods`

`kubectl -n k8s-demo rollout status deployment/k8s-master-app`

`--timeout=180s`

| 8

**Setup Port Forward**

|

`pgrep -f "kubectl.*port-forward.*k8s-demo" > /dev/null`

`pkill -f "kubectl.*port-forward.*k8s-demo"`

`kubectl -n k8s-demo port-forward svc/k8s-master-app 8080:80 &`

**Show Access URLs**

| 9

✓ **Method 1:** Port Forwarding

<http://localhost:8080>

✓ **Method 2:** NodePort (Minikube)

`MINIKUBE_IP=$(minikube ip)`

`" http://\$MINIKUBE\_IP:30080"`

### ✓ **Method 3:** Minikube Service URL

minikube service k8s-master-app -n k8s-demo

#### **Show Useful Cmds**

| 10

minikube dashboard # Open the Kubernetes dashboard in the browser

kubectl -n k8s-demo logs -l app=k8s-master # View logs of pods with label

kubectl -n k8s-demo get pods -l app=k8s-master -o name | head -1) --

/bin/bash # Get a shell into a pod

kubectl -n k8s-demo get all # View all resources in the k8s-demo namespace

kubectl -n k8s-demo top pods # Check pod resource usage (if metrics-server is enabled)

./scripts/cleanup.sh # Run cleanup script to remove all resources

|  
Success ✓

←→↻①127.0.0.1:34327

Kubernetes Zero to Hero

v1.0.0

A comprehensive Kubernetes demonstration application

Pod Information

Instance ID: fdc792ae

Hostname: k8s-master-app-869578d457-p4hrh

Environment: demo

Request count: 5

Platform: Linux-5.15.167.4-microsoft-standard-WSL2-x86\_64-with-glibc2.36

Uptime: 3677.0 seconds

Resource Usage

CPU Usage

43.1%

Memory

70.5%

Disk

1.5%

Requests

5

Mounted Volumes

Data Volume

Path: /data

Status: Successfully mounted

Files:

hello.txt

View

info.txt

View

firstexample.txt

View

sample-config.txt

View

Config Volume

Path: /config

Status: Mounted but empty

Logs Volume

Logs Volume

Path: /logs

Status: Successfully mounted

Files:	
init.log	<a href="#">View</a>
app.log	<a href="#">View</a>
container.log	<a href="#">View</a>
file_operations.log	<a href="#">View</a>



Actions

- Create a File
- API Info
- Health Check
- Metrics

Environment Variables

- APP\_NAME: Kubernetes Zero to Hero
- APP\_VERSION: 1.0.0
- ENVIRONMENT: demo
- DATA\_PATH: /data
- CONFIG\_PATH: /config
- LOG\_PATH: /logs
- SECRET\_KEY: dev-sec...

```
hafsa_027@Dell:~$ minikube addons list
```

ADDON NAME	PROFILE	STATUS	MAINTAINER
ambassador	minikube	disabled	3rd party (Ambassador)
amd-gpu-device-plugin	minikube	disabled	3rd party (AMD)
auto-pause	minikube	disabled	minikube
cloud-spanner	minikube	disabled	Google
csi-hostpath-driver	minikube	disabled	Kubernetes
dashboard	minikube	enabled 	Kubernetes
default-storageclass	minikube	enabled 	Kubernetes
efk	minikube	disabled	3rd party (Elastic)
freshpod	minikube	disabled	Google
gcp-auth	minikube	disabled	Google
gvisor	minikube	disabled	minikube

```
hafsa_027@Dell:~$ minikube docker-env
```

```
export DOCKER_TLS_VERIFY="1"
```

```
export DOCKER_HOST="tcp://127.0.0.1:32774"
```

```
export DOCKER_CERT_PATH="/home/hafsa_027/.minikube/certs"
```

```
export MINIKUBE_ACTIVE_DOCKERD="minikube"
```

```
# To point your shell to minikube's docker-daemon, run:
```

```
# eval $(minikube -p minikube docker-env)
```