Fault Propagation and Recovery in a Multi-Agent LLM Workflow — Phase 1

1. Problem

Multi-agent LLM systems pass intermediate results between agents and act on the world through tools. When one result is wrong, through an accidental error or an attack, we do not know how far the error travels, how soon it causes a side effect that cannot be undone, or whether simple recovery repairs it. Phase 1 measures this causally and evaluates the recovery baselines that Phase 2's selective recovery must beat.

2. System, data and method

- **Workflow.** A researcher (read-only tools, structured claims with sources), a planner (steps that cite claims) and an executor (write tools) on 14 AgentDojo v1.2.2 tasks (banking, workspace, slack). Results are handed off either inside the next prompt or through a versioned shared blackboard. Every state write is versioned; external effects (money sent, emails, posts) go to a log that is never rolled back, and each tool is labeled reversible, compensable or irreversible.
- **Faults.** 18 conditions at 7 injection points (researcher tool returns and output, planner output, blackboard, executor tool returns). Accidental: wrong, stale or missing facts, timeouts. Adversarial: prompt injection, impersonation, byzantine corrections, injected plan steps, poisoned notes. Controls: a wrong noncritical fact, a benign paraphrase, and a positive control that forces a wrong argument.
- **Causal measurement.** Each branch replays the clean prefix from an LLM cache (0 replay misses), then continues either with the fault or clean, with the same seeds. Effect Δ = P(bad | fault) − P(bad | clean continuation). Counterfactual dependence (an artifact no clean continuation produced) is the ground truth for scoring three dependency graphs: declared citations, observed data flow, and value taint.
- **Recovery baselines** under identical fault schedules: R0 none, R1 full restart (prior external effects stay), R3 verify-all (verifiers on findings, plan and every write).
- **Released data.** 13,433 runs with full traces (Qwen3-8B, vLLM on one RTX 5070 Ti): main 3,080, R3 3,080, R1 2,010, plus a harder-task set, a T=0 noise floor, a CPU latency sample and a cross-family check. All tables and figures are generated by scripts from `data/`; a fresh clone passes `uv sync && pytest`.
- **Validation** (pre-registered, `docs/preregistration.md`). Three blind trace audits of 36 branches each against the raw traces; labels were fixed twice and the final labels pass the 0.90 agreement threshold on the third, unseen sample (`data/audit/`). Artifact equivalence checked under three definitions (`data/tables/validation_main/`).

3. Results (95% cluster-bootstrap CIs over 14 tasks; Holm-adjusted over 14 headline comparisons)

	Accidental	Adversarial
Δ bad outcome, message (n = 560 / 335)	+0.41 [0.26, 0.55]	+0.68 [0.59, 0.76]
P(reaches outcome | used), message / state	0.47 / 0.59	0.85 / 0.79
Used but outcome unaffected, by stage	0.17–0.48	0.00–0.29
Fault-caused irreversible effect, P.out and E.tool faults	0.00–0.10	0.76–1.00, median 3–4 steps
Recall of taint / declared `U` taint vs. counterfactual dependence	0.62 / 0.73	0.55 / 0.72
R1 − R0 utility	+0.27 [0.13, 0.40]	+0.01 [−0.17, 0.18], n.s.
R3 − R0 residual harm	−0.03 [−0.06, 0.00], n.s.	−0.39 [−0.45, −0.34]

n.s.: not distinguishable after Holm adjustment (`data/tables/stats/headline_comparisons.csv`). Excluding `banking.user_task_9`, whose checker accepts an unchanged environment, gives the same eight distinguishable comparisons.

1. **Propagation by family.** Once used, adversarial payloads reached the outcome in 0.85 [0.77, 0.92] (message) and 0.79 [0.72, 0.86] (state) of branches; accidental faults in 0.47 [0.33, 0.61] and 0.59 [0.43, 0.74]. Difference +0.38 [0.25, 0.49] and +0.20 [0.08, 0.33]. This holds for these payloads; adversarial payloads are written to be acted on, which is an alternative explanation we cannot rule out.
2. **Time to an irreversible effect.** Plan- and executor-level attacks produced a fault-caused irreversible or compensable effect in 0.76–1.00 of branches, median 3–4 steps after injection; researcher-level attacks in 0.42–0.52, median 8–24 steps.
3. **Read is not used.** Every injected fault reached an agent's prompt. Poisoned blackboard notes were read but not used in 0.83 of branches (n = 70). The control conditions (wrong noncritical fact, benign paraphrase) have Δ +0.09 [−0.03, 0.24] (message) and −0.03 [−0.12, 0.02] (state).
4. **Dependency graphs against counterfactual dependence.** Taint precision is 0.98–0.99 and recall 0.55–0.62; declared `U` taint recall is 0.72–0.73. These values change by ≤ 0.02 across three artifact-equivalence definitions; recall changes by ≤ 0.008 between 5 and 10 clean continuations per branch point (pre-registered

threshold 0.05), and declared ∪ taint recall is 0.73–0.74 on Qwen3-14B.

5. **Recovery.** R1 raised accidental utility by +0.27 and did not change adversarial residual harm (+0.02 [0.00, 0.04], n.s.); it re-executed an earlier action in 16–24% of branches. R3 reduced adversarial residual harm by 0.39 for +11% tokens; its utility differences are not distinguishable from 0, and clean success fell from 0.86 to 0.77 (message) and 0.79 to 0.69 (state). No existing prompt-injection defense was compared, so we do not claim that only verification helps.




Figure 1. (a) Share of injected branches with a fault-caused irreversible or compensable external effect before any recovery, by injection stage. (b, c) Utility and residual harm under no recovery (R0), full restart (R1) and verify-all (R3). Bars: 95% cluster-bootstrap CIs over 14 tasks.

4. Limitations and next step

- **Task selection.** The 14 tasks are the candidates with clean pass rate ≥ 0.5 for this model (33 candidates; 4 at 1/3 run separately; 15 below). On the 4 excluded tasks clean failure is 0.43–0.54 and adversarial Δ is 0.22 [−0.06, 0.54], so Δ on selected tasks is an upper-end estimate.
- **One prefix per task and mode.** Branches replay the reference prefix of seed 0. On two more prefixes (core conditions, 1,988 runs) all family-level Δ and propagation estimates fall inside the seed-0 CIs, a low-power check. Per-condition results (18 conditions) are exploratory.
- **Models.** Qwen3-8B is the primary model. On Qwen3-4B (`data/tables/main_qwen3-4b/`), findings 2 and 5 have the same direction; finding 1 holds in message mode (0.78 vs 0.51) but not in state mode (0.82 [0.77, 0.86] vs 0.71 [0.57, 0.84]). Qwen3-14B gives the same direction for findings 1, 2 and 5 in both modes. Four 8B models from three other families did not pass the clean-success gate (best 0.36–0.39), so cross-family generality is not shown.
- **Audit and simulator.** The trace audits were automated and blind, not human; a human audit is planned. The simulator accepts some invalid arguments (e.g. a malformed IBAN), and three selected tasks fail in 0.42–0.65 of clean runs, so many bad outcomes on them are not fault-caused (Δ subtracts this rate).
- **Phase 2** will test whether probing the uncertain edges of the dependency graph recovers the missed dependencies at a fraction of restart cost, with thresholds fixed in advance (`docs/revised_plan.md`).

Appendix A. Timeline and milestones

Phase 1 milestones

Milestone	Deliverable and acceptance test	Status
M0 Setup	vLLM serving Qwen3-8B FP8, tool call with thinking off, repo and hooks	done
M1–M3 Workflow, tracing, faults	3 agents on MockLLM; snapshot restore exact; replay with 0 live calls; each fault injects and is detected downstream	done
M4 Runner	matrix expansion, identical fault/clean prefixes, resume without duplicates, 64 concurrent episodes	done
M5 Real runs	screening 33 → 14 tasks, pilot go/no-go, primary matrix, cross-family check	done
W1 Main matrix	18 conditions × 5 seeds × 2 modes, full traces (3,080 runs)	done
W2–W3 Recovery baselines	R3 verify-all (3,080 runs), R1 restart (2,010 runs)	done
W4–W5 Analysis	counterfactual dependence, graph accuracy, irreversibility, recovery, all figures with CIs	done
W6 Robustness	harder tasks, T=0 noise floor, CPU vs GPU latency, cross-family recovery	done
W7 Submission	README, report, data export, fresh-clone check	done
W8 Breadth	full matrix on Qwen3-4B and Qwen3-14B; four 8B models of other families screened, none passed the clean-success gate	done
W9 Validation	pre-registration, 3 blind label audits, equivalence, k = 10 and prefix checks, statistics, task-selection record	done

Phase 2 (planned; details and pre-registered thresholds in `docs/revised_plan.md`)

Week of	Milestone	Done means
Nov 9	Tool relabeling; R2 rollback; spotlighting and tool-output filter baselines; cross-model verifier	baselines run on the main fault schedule; MockLLM acceptance tests pass
Nov 16	Selective recovery with counterfactual probing of uncertain edges, per-object restore, compensation	MockLLM acceptance tests; zero duplicated effects on mock
Nov 23	Real runs: recall–cost frontier, ablations, all baselines	runs complete; 10% of branches spot-checked against traces
Nov 30	Analysis and label audit of Phase 2 labels	pre-registered criteria evaluated as passed or failed
Dec 7	Final report (4–6 pages)	every number traced to a table, script and run subset