

Actual Final Exam

测验, 13 个问题

12
points

1.

Check a box if and only if it is an accurate description of Racket.

- ☐ `(define (f x y) e)` is syntactic sugar for the curried function definition `(define f (lambda (x) (lambda (y) e)))`.
- ☒ Without `let*-expressions`, Racket programmers could just use nested `let-expressions`, but the result would have more parentheses.
- ☐ It is a run-time error for the first argument to an `if-expression` not to be a boolean.
- ☒ A struct definition for a struct with n (immutable) fields adds $n+2$ functions to the environment.
- ☐ A struct definition is syntactic sugar for introducing several functions that operate over Racket lists.
- ☒ A function call always evaluates each argument exactly once, but a macro use may not evaluate each argument exactly once.

4
points

2.

This incorrect Racket code is supposed to bind to **longer-strings** a stream where the N^{th} element of the stream is the string containing the character A N times.

```
1 (define longer-strings
2   (lambda ()
3     (letrec ([f (lambda(s)
4                   (cons s (f (string-append "A" s))))])
5       (f "A"))))
6 What is wrong with this code?
7
```

- ☐ **longer-strings** is bound to a function, but it should be bound to a pair.
- ☒ Calls to **longer-strings** will never terminate because there is too little thunking.
- ☐ Calls to **longer-strings** will never terminate because the function bound to **f** needs a conditional.
- ☐

Calls to **longer-strings** will never terminate because the function bound to **f** is returning a procedure somewhere where it needs to return a call to the procedure.

Actual Final Exam

测验, 13 个问题

4
points

3.

Which statement below accurately describes the function bound to **mystery** in this Racket code?

```
1 (define (mystery s)
2   (lambda ()
3     (let ([pr (s)])
4       (if (car pr)
5           (cons (car pr) (mystery (cdr pr)))
6           ((mystery (cdr pr)))))))
```

- ☐ It takes a stream and generates all its elements, causing an infinite loop for any call to **mystery**.
- ☐ It takes a stream and generates a list of its elements up to the first **#f** in the stream.
- ☐ It takes a list and returns a stream that repeatedly generates the elements in the list in order.
- ☒ It takes a stream and returns a stream that is like the stream it takes except all **#f** elements are removed.

5
points

4.

What is the difference between these two pieces of Racket code? (Here we assume **e1** and **e2** are arbitrary, unspecified Racket expressions. We also assume **e1** does not contain a use of **y**.)

```
1 (define f (let ([x e1]) (lambda (y) e2))) ; call this code A
2
3 (define f (lambda (y) (let ([x e1]) e2))) ; call this code B
```

- ☒ Code A evaluates **e1** once whereas Code B evaluates **e1** once every time the function bound to **f** is called.
- ☐ Code B evaluates **e1** once whereas Code A evaluates **e1** once every time the function bound to **f** is called.
- ☐ Code A evaluates **e1** only if, at run-time, **e2** uses the variable **x**, but Code B always evaluates **e1** assuming **f** is used at least once.
- ☐ Code B evaluates **e1** only if, at run-time, **e2** uses the variable **x**, but Code A always evaluates **e1** assuming **f** is used at least once.



There is no semantic difference: although the order of the code is different, code A and code B are equivalent for any **e1** and **e2**.

Actual Final Exam

测验, 13 个问题

4
points

5.

In this question, RUPL is like the language MUPL except it is really small, containing only integers, variables, additions, and let-expressions. What is wrong with this implementation?

```

1 (struct var (string) #:transparent) ;; a variable, e.g., (var "foo")
2 (struct int (num) #:transparent) ;; a number, e.g., (int 17)
3 (struct add (e1 e2) #:transparent) ;; add two expressions
4 (struct mlet (var e body) #:transparent) ;; a local binding
5                                     ;; (let var = e in body)
6
7 (define (envlookup env str)
8   (cond [(null? env) (error "unbound variable" str)]
9         [(equal? (car (car env)) str) (cdr (car env))]
10        [#t (envlookup (cdr env) str)]))
11
12 (define (eval-under-env e env)
13   (cond [(var? e) (envlookup env (var-string e))]
14         [(int? e) e]
15         [(add? e)
16          (let ([v1 (eval-under-env (add-e1 e) env)]
17                [v2 (eval-under-env (add-e2 e) env)])
18            (if (and (int? v1)
19                     (int? v2))
20                (int (+ (int-num v1)
21                        (int-num v2)))
21                (error "RUPL addition applied to non-number")))]
22         [(mlet? e)
23          (let ([v (eval-under-env (mlet-e e) env)])
24            (eval-under-env (mlet-body e) env))]
25         [#t (error "bad RUPL expression")]))
26
27
28 (define (eval-exp e)
29   (eval-under-env e null))

```



The case for variables is wrong because we should recursively call **eval-under-env** in this case.



The case for integer expressions is wrong: we should return **(int-num e)**.



The case for addition expressions is wrong: we should write **e1** and **e2** where we have **(add-e1 e)** and **(add-e2 e)**.



The case for **mlet**-expressions is wrong: we do not use the correct environment to evaluate the let-expression body.

12
points

6.

Actual Final Exam

测验, 13 个问题

In this question, we consider what would happen if we ported (i.e., rewrote) Racket code to ML. Assume we write the code by only changing the syntax as follows: Racket functions become ML functions, Racket conditionals become ML conditionals, Racket addition becomes ML addition, Racket `car` becomes ML `hd`, and Racket `null` becomes ML `[]`.

For each function below, check the box if and only if the ML rewrite of the function would type-check (with some type). (Always assume we port the code so that the ML code parses correctly.)

- ☒ `(define (f1 x) (if x 37 42))`
- ☒ `(define (f2 x) (if x x x))`
- ☐ `(define (f3 x) (if x 42 x))`
- ☒ `(define (f4 x) (car null))`
- ☒ `(define (f5 x) (+ (car x) 42))`
- ☐ `(define (f6 x) (car (+ x 42)))`

10
points

7.

For each of the following, check the box if and only if it is an accurate description of an advantage of static typing over dynamic typing.

- ☒ Static typing catches some simple bugs without having to test your code.
- ☒ Static typing can produce faster code because the language implementation does not need to perform type tests at run time.
- ☐ Static typing lets you change the type of a function as its requirements evolve without ever having to change any of the function's callers.
- ☐ Static typing is necessary to avoid the security and reliability problems of weak typing.
- ☐ Static typing does not make sense for OOP.

9
points

8.

This question uses this Ruby class definition:

Actual Final Exam

测验, 13 个问题

```

1 class A
2   attr_accessor :x
3   def m1
4     @x = 4
5   end
6   def m2
7     m1
8     @x > 4
9   end
10  def m3
11    @x = 4
12    @x > 4
13  end
14  def m4
15    self.x = 4
16    @x > 4
17  end
18 end

```

For each statement below, check the box if and only if the statement is true. In all cases, consider only a definition of class B, not code that makes any changes to class A.

- ☒ It is possible to define a class B such that evaluating **B.new.m2** causes the method **m2** defined in class A (not an override of **m2**) to return **true**.
- ☐ It is possible to define a class B such that evaluating **B.new.m3** causes the method **m3** defined in class A (not an override of **m3**) to return **true**.
- ☒ It is possible to define a class B such that evaluating **B.new.m4** causes the method **m4** defined in class A (not an override of **m4**) to return **true**.

4
points

9.

This problem uses this Ruby class definition, which includes a mixin:

```

1 class MyRange
2   include Enumerable
3   def initialize(low,high)
4     @low = low
5     @high = high
6   end
7   def each
8     i=@low
9     while i <= @high
10      yield i
11      i=i+1
12    end
13  end
14 end

```

Given this definition, the expression **MyRange.new(4,2).any? {|i| i <= 4}** evaluates to **false**. Why?

- ☐ Because instances of **MyRange** do not have a method **any?**.
- ☒ Because the **each** method for the object created by **MyRange.new(4,2)** never calls its block.
- ☐ Because the superclass of **MyRange** is **Object**, which has an **any?** method that always returns **false**.
- ☐

Because the **each** method in **MyRange** implicitly returns **nil** and in Ruby **nil** is like **false**.

Actual Final Exam

测验, 13 个问题

14
points

10.

Check the box if and only if the statement is true.

- ☐ In Ruby, it is a run-time error to create an array holding instances of different classes.
 - ☒ In Ruby, you cannot store a block in an array, but you can pass a block to **lambda** and store the result in an array.
 - ☐ It does not make sense to consider adding multiple inheritance to a dynamically typed language because the purpose of multiple inheritance is to make type-checking less restrictive.
 - ☐ In Ruby, **is_a?** and **instance_of?** are synonyms: the two methods are defined for every object and always compute the same result.
 - ☒ In Ruby, anything returned by a method is an object.
 - ☐ Double dispatch is special to Ruby -- it is a programming pattern that does not work in most other OOP languages.
 - ☒ A Ruby mixin method included in a class can get and set instance variables of **self**.
-

4
points

11.

This problem and the next problem relate to this Ruby code:

Actual Final Exam

测验, 13 个问题

```

1 class A
2   def initialize a
3     @arr = a
4   end
5   def get i
6     @arr[i]
7   end
8   def sum
9     @arr.inject(0) {|acc,x| acc + x}
10  end
11 end
12
13 class B < A
14   def initialize a
15     super
16     @ans = false
17   end
18   def sum
19     if !@ans
20       @ans = @arr.inject(0) {|acc,x| acc + x}
21     end
22     @ans
23   end
24 end

```

Which technique that we studied is mostly closely related to the code in class B?

- ☐ Thunking
- ☒ Memoization
- ☐ Mixins
- ☐ Double dispatch

4
points

12.

This problem uses the code in the previous problem. Class A and class B are not equivalent. In particular, there are ways to fill in the ... in the code below so that **s3** and **s4** hold different numbers. Which change would make the two classes equivalent?

```

1 v = [4,19,74]
2 a = A.new v
3 b = B.new v
4 s1 = a.sum
5 s2 = b.sum
6 ...
7 s3 = a.sum
8 s4 = b.sum

```

- ☒ Have the initialize method in class A store a copy of its argument in **@arr**.
- ☐ Remove the method **get** from class A.
- ☐ Change the **sum** method in both classes to use an explicit loop instead of **inject** and a block.
- ☐ Change class A to use a class variable **@@arr** in place of the instance variable **@arr**.

14

points

Actual Final Exam

测验, 13 个问题

13.

This problem uses the made-up language from the lectures for studying subtyping.
Recall:

- The language has records with mutable fields.
- We write types for records and functions like in ML.
- Records have width and permutation subtyping.
- Function subtyping has contravariant arguments and covariant results.

Assume these bindings for functions exist and have given types:

```
1 val f1 : {a:int, b:int} -> {a:int, b:int};
2 val f2 : {a:int, c:{x:int, y:int}, b:int} -> {a:int, b:int};
3 val f3 : int -> {a:int,b:int,c:int};
4 val f4 : ({a:int,b:int,c:int} -> {a:int,b:int}) -> int;
```

For example, **f1** is bound to a function that takes a record of type **{a:int, b:int}** and returns a record of the same type.

For each call below, check the box if and only if the call type-checks.

- ☒ **f1 {a=3, b=4, c=5}**
- ☐ **f2 {a=3, c={x=4, y=5, z=6}, b=7}**
- ☒ **f1 (f3 4) (* call f1 with result of call (f3 4) *)**
- ☐ **f2 (f3 4) (* call f2 with result of call (f3 4) *)**
- ☒ **f4 f1**
- ☐ **f4 f2**
- ☐ **f4 f3**

☐ 我 (**Feitao YI**) 了解提交不是我自己完成的作业 将永远不会通过此课程或导致我的 Coursera 帐号被关闭。 了解荣誉准则的更多信息

Submit Quiz

