










# Constraint Satisfaction

Student:



Student:









Taking classes:



Student:



Taking classes:


















Exam slots:









Monday








Tuesday

Wednesday

















































# Constraint Satisfaction Problem

- Set of variables  $\{X_1, X_2, \dots, X_n\}$
- Set of domains for each variable  $\{D_1, D_2, \dots, D_n\}$
- Set of constraints  $C$

5	3			7				
6			1	9	5			
	9	8					6	
8				6				3
4			8		3			1
7				2				6
	6					2	8	
			4	1	9			5
				8			7	9

## Variables

$\{(0, 2), (1, 1), (1, 2), (2, 0), \dots\}$

## Domains


$\{1, 2, 3, 4, 5, 6, 7, 8, 9\}$

for each variable

## Constraints

$\{(0, 2) \neq (1, 1) \neq (1, 2) \neq (2, 0), \dots\}$





## Variables

$\{A, B, C, D, E, F, G\}$

## Domains

$\{Monday, Tuesday, Wednesday\}$

for each variable

## Constraints


$\{A \neq B, A \neq C, B \neq C, B \neq D, B \neq E, C \neq E, C \neq F, D \neq E, E \neq F, E \neq G, F \neq G\}$

# hard constraints

constraints that must be satisfied in a correct solution

# soft constraints

constraints that express some notion of which solutions are preferred over others



# unary constraint

constraint involving only one variable

# unary constraint

$$\{A \neq \textit{Monday}\}$$

# binary constraint

constraint involving two variables

# binary constraint

$$\{A \neq B\}$$



# node consistency


when all the values in a variable's domain satisfy the variable's unary constraints



$\{Mon, Tue, Wed\}$

$\{Mon, Tue, Wed\}$


$\{A \neq Mon, B \neq Tue, B \neq Mon, A \neq B\}$




$\{Mon, Tue, Wed\}$

$\{Mon, Tue, Wed\}$


$\{A \neq Mon, B \neq Tue, B \neq Mon, A \neq B\}$




$$\{A \neq Mon, B \neq Tue, B \neq Mon, A \neq B\}$$




$$\{A \neq Mon, B \neq Tue, B \neq Mon, A \neq B\}$$



$$\{A \neq Mon, B \neq Tue, B \neq Mon, A \neq B\}$$




$$\{A \neq Mon, B \neq Tue, B \neq Mon, A \neq B\}$$



$$\{A \neq Mon, B \neq Tue, B \neq Mon, A \neq B\}$$






$$\{A \neq Mon, B \neq Tue, B \neq Mon, A \neq B\}$$

# arc consistency


when all the values in a variable's domain satisfy the variable's binary constraints

# arc consistency


To make  $X$  arc-consistent with respect to  $Y$ ,  
remove elements from  $X$ 's domain until every  
choice for  $X$  has a possible choice for  $Y$




$$\{A \neq Mon, B \neq Tue, B \neq Mon, A \neq B\}$$



$$\{A \neq Mon, B \neq Tue, B \neq Mon, A \neq B\}$$



$\{A \neq Mon, B \neq Tue, B \neq Mon, A \neq B\}$



$$\{A \neq Mon, B \neq Tue, B \neq Mon, A \neq B\}$$

# Arc Consistency

```
function REVISE(csp, X, Y):  
    revised = false  
    for x in X.domain:  
        if no y in Y.domain satisfies constraint for (X, Y):  
            delete x from X.domain  
            revised = true  
    return revised
```



# Arc Consistency

function AC-3( $csp$ ):

$queue =$  all arcs in  $csp$

    while  $queue$  non-empty:

$(X, Y) =$  DEQUEUE( $queue$ )

        if REVISE( $csp, X, Y$ ):


            if size of  $X.domain == 0$ :


                return *false*

            for each  $Z$  in  $X.neighbors - \{Y\}$ :

                ENQUEUE( $queue, (Z, X)$ )

    return *true*





# Search Problems

- initial state
- actions
- transition model
- goal test
- path cost function


# CSPs as Search Problems

- initial state: empty assignment (no variables)
- actions: add a  $\{variable = value\}$  to assignment
- transition model: shows how adding an assignment changes the assignment
- goal test: check if all variables assigned and constraints all satisfied
- path cost function: all paths have same cost


# Backtracking Search


# Backtracking Search


```
function BACKTRACK(assignment, csp):  
    if assignment complete: return assignment  
    var = SELECT-UNASSIGNED-VAR(assignment, csp)  
    for value in DOMAIN-VALUES(var, assignment, csp):  
        if value consistent with assignment:  
            add {var = value} to assignment  
            result = BACKTRACK(assignment, csp)  
            if result ≠ failure: return result  
        remove {var = value} from assignment  
    return failure
```


























































































































# Inference





























# **maintaining arc-consistency**

algorithm for enforcing arc-consistency  
every time we make a new assignment



# maintaining arc-consistency

When we make a new assignment to  $X$ , call  
AC-3, starting with a queue of all arcs  $(Y, X)$   
where  $Y$  is a neighbor of  $X$


```
function BACKTRACK(assignment, csp):  
  if assignment complete: return assignment  
  var = SELECT-UNASSIGNED-VAR(assignment, csp)  
  for value in DOMAIN-VALUES(var, assignment, csp):  
    if value consistent with assignment:  
      add {var = value} to assignment  
      inferences = INFERENCE(assignment, csp)  
      if inferences ≠ failure: add inferences to assignment  
      result = BACKTRACK(assignment, csp)  
      if result ≠ failure: return result  
      remove {var = value} and inferences from assignment  
  return failure
```


```
function BACKTRACK(assignment, csp):  
  if assignment complete: return assignment  
  var = SELECT-UNASSIGNED-VAR(assignment, csp)  
  for value in DOMAIN-VALUES(var, assignment, csp):  
    if value consistent with assignment:  
      add {var = value} to assignment  
      inferences = INFERENCE(assignment, csp)  
      if inferences ≠ failure: add inferences to assignment  
      result = BACKTRACK(assignment, csp)  
      if result ≠ failure: return result  
      remove {var = value} and inferences from assignment  
  return failure
```


```
function BACKTRACK(assignment, csp):  
  if assignment complete: return assignment  
  var = SELECT-UNASSIGNED-VAR(assignment, csp)  
  for value in DOMAIN-VALUES(var, assignment, csp):  
    if value consistent with assignment:  
      add {var = value} to assignment  
      inferences = INFERENCE(assignment, csp)  
      if inferences ≠ failure: add inferences to assignment  
      result = BACKTRACK(assignment, csp)  
      if result ≠ failure: return result  
    remove {var = value} and inferences from assignment  
  return failure
```

# SELECT-UNASSIGNED-VAR


- **minimum remaining values (MRV)** heuristic: select the variable that has the smallest domain
- **degree** heuristic: select the variable that has the highest degree













```
function BACKTRACK(assignment, csp):  
  if assignment complete: return assignment  
  var = SELECT-UNASSIGNED-VAR(assignment, csp)  
  for value in DOMAIN-VALUES(var, assignment, csp):  
    if value consistent with assignment:  
      add {var = value} to assignment  
      inferences = INFERENCE(assignment, csp)  
      if inferences ≠ failure: add inferences to assignment  
      result = BACKTRACK(assignment, csp)  
      if result ≠ failure: return result  
      remove {var = value} and inferences from assignment  
  return failure
```


```
function BACKTRACK(assignment, csp):  
  if assignment complete: return assignment  
  var = SELECT-UNASSIGNED-VAR(assignment, csp)  
  for value in DOMAIN-VALUES(var, assignment, csp):  
    if value consistent with assignment:  
      add {var = value} to assignment  
      inferences = INFERENCE(assignment, csp)  
      if inferences ≠ failure: add inferences to assignment  
      result = BACKTRACK(assignment, csp)  
      if result ≠ failure: return result  
      remove {var = value} and inferences from assignment  
  return failure
```

# DOMAIN-VALUES


- **least-constraining values** heuristic: return variables in order by number of choices that are ruled out for neighboring variables
  - try least-constraining values first








# Problem Formulation



Local  
Search

$$\begin{aligned} &50x_1 + 80x_2 \\ &5x_1 + 2x_2 \leq 20 \\ &(-10x_1) + (-12x_2) \leq -90 \end{aligned}$$

Linear  
Programming



Constraint  
Satisfaction



# Optimization

Introduction to  
**Artificial Intelligence**  
with Python