

Fastcampus

Computer Science SCHOOL

Network Basic (2)


2017.2.15

Civilization



Web Programming

Web architecture




웹 개발 패턴의 변화

- 1991 ~ 1999: Sir Timothy John "Tim" Berners-Lee가 하이퍼텍스트 기반의 프로젝트를 제안한 이후 정적인 콘텐츠를 중심으로 한 웹 기술이 발달
- 1999 ~ 2009: Linux, Apache, Mysql, Php 중심의 동적인 서버, 정적인 클라이언트 모델이 지속됨
- 2010 ~ 현재: JavaScript!! (Dynamic Web Client)

Web Browser


Mosaic(1993)



Netscape(1994)




Internet Explorer(1995)



FireFox(2004)



Chrome(2008)



웹 개발의 현재

JavaScript

Client-side

- HTML/CSS, javaScript
- jQuery, AJAX
- Front-end Web Framework
 - AngularJS
 - React.js
 - Vue.js
- CSS Framework
 - Bootstrap
 - Foundation

Server-side

- Depends on Language
 - PHP: Laravel
 - JavaScript: Node.js(Express.js)
 - Java: Spring
 - C++, C#: [ASP.net](#)
 - Python: Django, Flask
 - Golang: itself
 - Ruby: Ruby on Rails

Database

- RDBMS
 - MySQL
 - PostgreSQL
 - MariaDB
- noSQL
 - MongoDB
 - CouchDB
 - Redis

etc

- celery (for Distributed Task Queue)
- github, Bitbucket, gitlab (for SCM)
- travis CI or jenkins (for Continuous Integration)
- slack, trello

URI, URL, URN

URI

- Uniform Resource Information
- `https://www.example.com/post/how-to-make-url`

URL

- Uniform Resource Locator
- `https://www.example.com/post/`

URN

- Uniform Resource Name
- `www.example.com/post/how-to-make-url`

REST API

RE presentational S tate T ransfer

A pplication P rogramming I nterface

Resource - URI

Verb - HTTP method

Representations - 표현

CRUD

Create

Read

Update

Delete

REST API 설계시 주의할 점

- 버전관리 <https://api.foo.com/v1/bar>
- 명사형 사용 <https://foo.com/showid/> --> <https://foo.com/user/>
- 반응형 <https://foo.com/m/user/>, <https://m.foo.com/user/> (x)
- 언어코드 <https://foo.com/kr/>, <https://kr.foo.com/> (x)
- 응답상태 코드 (200, 400, 500)

HTTP Response code

[wikipedia](#)

200, 201 - Success

400, 404 - Not found

500 - Server error



Simple Server Framework: Flask

```
$ pip install flask
```

```
from flask import Flask

app = Flask(__name__)

@app.route('/')
def index():
    return 'hello world!'

if __name__ == '__main__':
    app.run(host='0.0.0.0')
```

c9.io

```
from flask import Flask
import os

app = Flask(__name__)

@app.route('/')
def index():
    return 'hello world!'

app.run(host=os.getenv('IP', '0.0.0.0'), port=int(os.getenv('PORT', 5000)))
```


Simple Server Framework: Flask

```
from flask import Flask, render_template

app = Flask(__name__)

@app.route('/')
def index(name=None):
    return render_template('index.html', name=name)

@app.route('/about')
def about(name=None):
    return render_template('about.html', name=name)

if __name__ == '__main__':
    app.run(host='0.0.0.0')
```

Simple Server Framework: Flask


```
/
  simpleserver.py
  /templates
    index.html
    about.html
```

Flask with **socket.io**

Web Crawling with Python


Scraping vs Crawling vs Parsing

Scraping: 데이터를 수집하는 행위



Scraping vs Crawling vs Parsing

Crawling: 조직적 자동화된 방법으로 월드 와이드 웹을 탐색하는 것



Scraping vs Crawling vs Parsing

Parsing: 문장 혹은 문서를 구성 성분으로 분해하고 위계관계를 분석하여 문장의 구조를 결정하는 것



Caution!!

저작권 침해 위반 소지

- 웹사이트 운영자의 크롤링 금지 룰을 어길경우
- 월권하여 데이터베이스에 접근
- 타인의 경제적 이익을 침해할 경우
- 개인정보를 수집할 경우(전화번호, 주소, ..)

Beautiful Soup

Web Scraping with Beautiful Soup

```
$ pip install beautifulsoup4
```

```
$ pip install beautifulsoup4
```

```
Collecting beautifulsoup4
```

```
  Downloading beautifulsoup4-4.5.1-py3-none-any.whl (83kB)
```

```
    100% |██████████████████████████████████████████████████████████████████████████████| 92kB 153kB/s
```

```
Installing collected packages: beautifulsoup4
```

```
Successfully installed beautifulsoup4-4.5.1
```

Web Scraping with BeautifulSoup

```
$ pip list
DEPRECATION: The default format will switch to
the [list] section) to disable this warning.
beautifulsoup4 (4.5.1)
pip (9.0.1)
setuptools (20.10.1)
urllib3 (1.19.1)
```

Web Scraping with BeautifulSoup

```
>>> import urllib
>>> from bs4 import BeautifulSoup
>>> html = """
... <html><head><title>The Dormouse's story</title></head>
... <body>
... <p class="title"><b>The Dormouse's story</b></p>
...
... <p class="story">Once upon a time there were three little sisters; and their names were
... <a href="http://example.com/elsie" class="sister" id="link1">Elsie</a>,
... <a href="http://example.com/lacie" class="sister" id="link2">Lacie</a> and
... <a href="http://example.com/tillie" class="sister" id="link3">Tillie</a>;
... and they lived at the bottom of a well.</p>
...
... <p class="story">...</p>
... """
>>> soup = BeautifulSoup(html, 'html.parser')
>>> print(soup.prettify())
```

Web Scraping with BeautifulSoup

```
import urllib
from bs4 import BeautifulSoup
html = """

uglified html code

"""
soup = BeautifulSoup(html, "html.parser")
print(soup.prettify())
```

Web Scrapping with BeautifulSoup

```
curl https://www.rottentomatoes.com
```

```
import urllib.request
from bs4 import BeautifulSoup

url = "https://www.rottentomatoes.com"
html = urllib.request.urlopen(url)
source = html.read()
html.close()

soup = BeautifulSoup(source, "html.parser")
print(soup)

table = soup.find(id="Top-Box-Office")
print(table)
```

Web Scrapping with BeautifulSoup

```
all_tr = table.find_all("tr")

for tr in all_tr:
    all_td = tr.find_all("td")
    score = all_td[0].find("span", attrs={"class": "tMeterScore"})
    movie_name = all_td[1].a.text
    amount = all_td[2].a.text
    print(score, movie_name, amount)
```

Web Scraping with BeautifulSoup

```
>>> import urllib.request
>>> from bs4 import BeautifulSoup
>>> url = "https://www.rottentomatoes.com"
>>> html = urllib.request.urlopen(url)
>>> source = html.read()
>>> html.close()
>>> soup = BeautifulSoup(source, "html.parser")
>>> table = soup.find(id="Top-Box-Office")
>>> all_tr = table.find_all("tr")
>>> for tr in all_tr:
...     all_td = tr.find_all("td")
...     score = all_td[0].find("span", attrs={"class": "tMeterScore"}).text
...     movie_name = all_td[1].a.text
...     amount = all_td[2].a.text
...     print(score, movie_name, amount)
```


Web Scrapping with BeautifulSoup

```
...
69% Sing
                                $41.5M

95% Fences
                                $10.2M

40% Why Him?
                                $10.1M

16% Assassin's Creed
                                $8.1M

12% Collateral Beauty
                                $4.1M

73% Fantastic Beasts and Where to Find Them
                                $4.0M
```

So, Let's Scrap Naver