

Transformations and correlations among some clay parameters — the global database

Jianye Ching and Kok-Kwang Phoon

Abstract: This study compiles a large database of 10 clay parameters (labeled as CLAY/10/7490) from 251 studies, covering clay data from 30 regions or countries worldwide. Hence, the range of data covered by this “global” database is broader than that underlying the calibration of existing transformation models in the literature. These transformation models relate test measurements (e.g., cone tip resistance) to appropriate design parameters (e.g., undrained shear strength). The correlation behaviours exhibited by the database among the 10 clay parameters are consistent with those exhibited by existing transformation models in the literature. The biases and transformation uncertainties of these transformation models with respect to the global database are calibrated. It is found that more recent transformation models are less biased and that the transformation uncertainties are typically fairly large. Such large transformation uncertainties are further reduced by incorporating secondary input parameters, such as plasticity index or sensitivity. In a companion paper written by the same authors, a 10-dimensional multivariate probability distribution coupling these clay parameters is constructed from CLAY/10/7490 and a useful application involving updating the entire bivariate probability distribution of two design parameters from three separate measurements is presented.

Key words: clay properties, correlations, transformation models, database, statistics.

Résumé : Cette étude compile une grande base de données de 10 paramètres d'argile (appelée CLAY/10/7490) provenant de 251 études, couvrant des données d'argile de 30 régions ou pays à travers le monde. Ainsi, la gamme de données couverte par cette base de données « globale » est plus vaste que celle utilisée pour calibrer les modèles de transformation existants dans la littérature. Ces modèles de transformation relient des mesures d'essais (par exemple la résistance à la pointe du cône) aux paramètres de conception appropriés (par exemple la résistance au cisaillement non drainé). Les comportements de corrélation démontrés par la base de données pour les 10 paramètres de l'argile sont consistants avec ceux démontrés par les modèles de transformation dans la littérature. Les biais et les incertitudes de transformation de ces modèles par rapport à la base de données globale sont calibrés. Il est démontré que les modèles de transformation plus récents sont moins biaisés et que les incertitudes de transformation sont généralement relativement grandes. De telles incertitudes de transformation sont encore plus réduites par l'ajout de paramètres d'entrée secondaires, comme l'indice de plasticité ou la sensibilité. Dans un article compagnon écrit par les mêmes auteurs, une distribution de probabilité multivariées à 10 dimensions couplée aux paramètres de l'argile est construite à partir de la base de données CLAY 10/7490. De plus, on présente une application intéressante impliquant la mise à jour de la distribution de probabilité bivariable pour deux paramètres de conception à partir de trois mesures séparées. [Traduit par la Rédaction]

Mots-clés : propriétés de l'argile, corrélations, modèles de transformation, base de données, statistiques.

Introduction

Geotechnical variability is a complex attribute that needs careful evaluation. Phoon and Kulhawy (1999a) demonstrated using fairly extensive soil statistics that geotechnical variability depends on the site condition, measurement error associated with a field test, and quality of the correlation model adopted to relate the field test to a design property. The first component refers to inherent soil variability, which is customarily categorized as aleatoric in nature because it cannot be reduced by performing more tests. The second and third components, namely measurement error inevitably introduced in a test procedure and data scatter about a mean correlation trend (typically in the form of a linear regression equation), are customarily categorized epistemic in nature. They can be reduced by gathering more data or building better models. While there are merits to categorizing uncertainties as aleatoric or epistemic, one should be mindful that this

demarcation is in part a modeler's choice (Der Kiureghian and Ditlevsen 2007). From a practical perspective, it is perhaps more important to align statistical characterization to the property evaluation procedure already embedded in our geotechnical engineering practice. In recognition of the need to respect sound geotechnical engineering practice, Phoon and Kulhawy (1999b) presented guidelines for coefficients of variation (COVs) of some soil properties as a function of the test method, correlation equation, and soil type. The key conclusion in this study is that it is not possible to assign a single coefficient of variation (COV) to a design property, such as the undrained shear strength. Geotechnical reliability-based design (RBD) equations that are calibrated using this single COV assumption are too simplistic, because diverse methodologies in estimating soil properties are ignored. This diversity is actually good practice, because there is a need to accommodate diverse site conditions. Phoon and Kulhawy (1999a, 1999b) advocated that the calibration of geotechnical RBD equations

Received 18 July 2013. Accepted 11 April 2014.

J. Ching. Department of Civil Engineering, National Taiwan University, Taiwan.

K.-K. Phoon. Department of Civil and Environmental Engineering, National University of Singapore, Singapore.

Corresponding author: Jianye Ching (e-mail: jyching@gmail.com).

should be carried out in explicit recognition of property variability and in full compliance with how soil properties are physically evaluated in practice. The framework recommended by Phoon and Kulhawy (1999a, 1999b) and the ensuing three-tier classification scheme of soil property variability (Phoon and Kulhawy 2008) should be viewed as the *minimum* requirements in variability characterization. The third edition of ISO 2394 (*General principles on reliability for structures*; to be published in 2015) includes a new Annex D on “Reliability of geotechnical structures” where the importance of respecting sound geotechnical engineering practices in variability characterization and reliability calibration is strongly emphasized.

The characterization of geotechnical variability is far from being a mature area in research. An astute practitioner would readily point out that multiple tests are commonly conducted in a site investigation and it is common practice to estimate a design property from these tests, either by straightforward averaging or picking a credible worst-case value from the range of values produced by different tests. The information collected in a site investigation programme is fundamentally multivariate in nature and this aspect has not been considered in the earlier studies mentioned above. The purpose of this paper is to develop unbiased transformation models and to quantify their associated uncertainties for 10 common clay parameters. A companion paper (Ching and Phoon 2014) develops a multivariate probability model coupling these clay parameters. The supporting database contains information from multiple tests that are collected in close proximity. In other words, each data point records soil information at a specific location and depth, i.e., at a specific sampling point. Note that measurement error is present, but it is not possible to isolate measurement error from transformation uncertainty in conventional site investigation programs. Hence, the transformation uncertainties presented in this study include some measurement errors, but these errors are relatively minor for cone penetration testing with pore pressure measurement (CPTU) (Phoon and Kulhawy 1999a). Inherent soil variability is clearly not considered in this study. In principle, inherent soil variability can be incorporated by extending the multivariate probability model (which applies to a sampling “point”) to a vector random field covering the three-dimensional (3D) spatial domain of the entire site. The outcomes of this study are thus incomplete in this sense, but they can be viewed as paving the way for characterization of geotechnical variability to advance beyond univariate data and to achieve closer alignment to how soil properties are estimated in actual practice from site investigation programs.

As noted by Phoon and Kulhawy (1999a), the measurement from a geotechnical test is typically not directly applicable to design. Instead, a transformation model is needed to relate the test measurement to an appropriate design parameter. Most transformation models in geotechnical engineering are obtained by empirical or semi-empirical data-fitting using regression analyses. These transformation models are widely adopted in geotechnical engineering practice as a matter of practical expediency. Useful compilations of these models (mostly pairwise correlations) are available in the literature (e.g., Kulhawy and Mayne 1990; Mayne et al. 2001). A cursory review of these compilations would reveal a rather bewildering variety and number of models. Most models were developed for a specific geomaterial type and (or) a specific locale.

It is not judicious to apply these models indiscriminately to other sites without a proper appreciation of geomaterial behaviour and geology. This “site-specific” limitation is a distinctive and fundamental feature of geotechnical engineering practice. Geotechnical design must take cognizance of this limitation to avoid gross oversimplification of “ground truths.” As opposed to site-specific models, Ching and Phoon (2012a) demonstrated the construction of “global” models. Global models are calibrated from global databases covering many sites and geomaterial types. Ching and Phoon (2012a) observed that site-specific models are

Table 1. Databases compiled by the authors.

Database	Reference	Parameters of interest	Range of properties				
			No. of data points	No. of sites or studies	OCR	PI	S _t
CLAY/5/345	Ching and Phoon (2012b)	LI, s _u , s _u ^{re} , σ _p ^r , σ _v ^r	345	37 sites	1~4	—	Sensitive to quick clays
CLAY/6/535	Ching et al. (2014)	s _u /σ _v ^r , OCR, (q _t - s _u)/σ _v ^r , (q _t - u ₀)/σ _v ^r , B _q	535	40 sites	1~6	Low to very high plasticity	Insensitive to quick clays
CLAY/7/6310	Ching and Phoon (2013)	s _u under seven different s _u test types	6310	164 studies	1~10	Low to very high plasticity	Insensitive to quick clays
CLAY/10/7490	This paper	LI, PI, LI, σ _v ^r /p _a , σ _p ^r /p _a , s _u /σ _v ^r , S _t , (q _t - σ _v)/σ _v ^r , (q _t - u ₀)/σ _v ^r , B _q	7490	251 studies	1~10	Low to very high plasticity	Insensitive to quick clays

Fig. 1. (a) Plasticity chart; (b) Robertson's (1990) CPTU soil classification chart. B_q , pore pressure ratio; CH, high-plasticity clay; CL, low-plasticity clay; MH, high-plasticity silt; ML, low-plasticity silt; q_t , corrected cone tip resistance; u_0 , hydrostatic pore pressure; u_2 , pore pressure behind the cone; σ'_v , total effective stress; σ'_v , vertical effective stress.




Table 2. Transformation models for $s_u(\text{mob})$.

Available s_u information	Transformation model	Reference
FV	$s_u(\text{mob}) \approx s_u(\text{field}) \approx [s_u(\text{FV})]\mu$	Bjerrum (1972)
UC	$s_u(\text{mob}) \approx s_u(\text{UC})$	Mesri and Huvaj (2007)
UU	$s_u(\text{mob})/\sigma'_v \approx s_u(\text{UC})/\sigma'_v \approx -0.073 + 1.018s_u(\text{UU})/\sigma'_v$	Chen and Kulhawy (1993); Mesri and Huvaj (2007)
CIUC	$s_u(\text{mob})/\sigma'_v \approx s_u(\text{UC})/\sigma'_v \approx -0.278 + 1.172s_u(\text{CIUC})/\sigma'_v$	Chen and Kulhawy (1993); Mesri and Huvaj (2007)
CK ₀ UC, DSS, CK ₀ UE	$s_u(\text{mob}) \approx \{[s_u(\text{CK}_0\text{UC}) + s_u(\text{DSS}) + [s_u(\text{CK}_0\text{UE})]/3]\mu_t\}$	Mesri and Huvaj (2007); Kulhawy and Mayne (1990)
CK ₀ UC, CK ₀ UE	$s_u(\text{mob}) \approx \{[s_u(\text{CK}_0\text{UC}) + s_u(\text{CK}_0\text{UE})]/2\}\mu_t^*$	Mesri and Huvaj (2007); Kulhawy and Mayne (1990)
DSS	$s_u(\text{mob}) \approx [s_u(\text{DSS})]\mu_t^*$	Mesri and Huvaj (2007); Kulhawy and Mayne (1990)
CK ₀ UC	$s_u(\text{mob}) \approx [s_u(\text{DSS})]\mu_t \approx [s_u(\text{CK}_0\text{UC})][0.67\mu_t]$	Mesri and Huvaj (2007); Kulhawy and Mayne (1990)
CK ₀ UE	$s_u(\text{mob}) \approx [s_u(\text{DSS})]\mu_t \approx [s_u(\text{CK}_0\text{UE})][1.53^*(\mu_t)]$	Mesri and Huvaj (2007); Kulhawy and Mayne (1990)

Note: FV, field vane; UC, unconfined compression; UU, unconsolidated undrained compression; CIUC, isotropically consolidated undrained compression; CK₀UC, K₀-consolidated undrained compression; DSS, direct simple shear; CK₀UE, K₀-consolidated undrained extension; μ , PI-dependent correction factor for $s_u(\text{FV})$ proposed in Bjerrum (1972); μ_t , PI-dependent strain rate correction factor proposed in Terzaghi et al. (1996).

*These equations are based on the following two facts: (i) $s_u(\text{mob}) \approx [s_u(\text{CK}_0\text{UC}) + s_u(\text{DSS}) + s_u(\text{CK}_0\text{UE})]/3\mu_t$ and (ii) $s_u(\text{DSS})$ is roughly the average of $s_u(\text{CK}_0\text{UC})$ and $s_u(\text{CK}_0\text{UE})$ (Kulhawy and Mayne 1990).

*This constant of 1.53 is based on the following two facts: (i) $s_u(\text{DSS}) \approx 0.67s_u(\text{CK}_0\text{UC})$ (Kulhawy and Mayne 1990) and (ii) $s_u(\text{DSS})$ is roughly the average of $s_u(\text{CK}_0\text{UC})$ and $s_u(\text{CK}_0\text{UE})$.

Table 3. Statistics of the data points in the database.

Variable	n	Mean	COV	Min	Max
LL	3822	67.7	0.80	18.1	515
PI	4265	39.7	1.08	1.9	363
LI	3661	1.01	0.78	-0.75	6.45
σ'_v/P_a	3370	1.80	1.47	4.13E-3	38.74
σ'_p/P_a	2028	4.37	2.31	0.094	193.30
s_u/σ'_v	3532	0.51	1.25	3.68E-3	7.78
s_t	1589	35.0	2.88	1	1467
B_q	1016	0.58	0.35	0.01	1.17
$(q_t - \sigma'_v)/\sigma'_v$	862	8.90	1.17	0.48	95.98
$(q_t - u_2)/\sigma'_v$	668	5.34	1.37	0.61	108.20
s_u/σ'_p	1467	0.23	0.55	3.68E-3	1.34
OCR	3531	3.85	1.56	1.0	60.23
s_u^{re}/P_a	1143	0.075	2.86	9.67E-5	2.47

Table 4. Sample percentiles of the data points in the database.

Variable	2.5%	5%	25%	50% (median)	75%	95%	97.5%
LL	23.6	26.2	39.0	54.3	76.0	149.1	200.0
PI	5.8	8.0	18.5	29.3	46.0	91.4	135.0
LI	-8.6E-2	4.7E-3	0.54	0.87	1.32	2.51	3.00
σ'_v/P_a	0.11	0.14	0.43	0.94	2.03	6.27	8.37
σ'_p/P_a	0.26	0.33	0.80	1.71	3.69	19.57	29.19
s_u/σ'_v	0.080	0.11	0.21	0.31	0.56	1.46	2.25
s_t	1.7	2.3	5.0	8.0	23.0	140.8	217.6
B_q	0.15	0.23	0.45	0.57	0.72	0.91	0.99
$(q_t - \sigma'_v)/\sigma'_v$	1.92	2.43	4.15	5.79	8.77	27.57	44.07
$(q_t - u_2)/\sigma'_v$	1.28	1.51	2.42	3.63	5.67	14.97	18.55
s_u/σ'_p	6.30E-2	8.38E-2	0.15	0.21	0.27	0.44	0.56
OCR	1.0	1.0	1.04	1.73	3.57	15.79	24.00
s_u^{re}/P_a	5.14E-4	8.05E-4	6.48E-3	0.021	0.062	0.26	0.54

generally more precise than global models, but they can be significantly biased when applied to another site. On the contrary, global models are less precise than site-specific models, but they are less biased. Their observations are already well appreciated by engineers. The key contribution from Ching and Phoon (2012a)

was to demonstrate these observations with statistical rigor using a sizeable global database.

Because most transformation models were built based on their own databases, their ranges of application are, in principle,

Table 5. The transformation models in literature and their calibration results.

Type	Relationship	Literature	n	Transformation model	Remarks	Comparison to the global database	Calibration results		
						Figure	Fit to the trend?	Bias factor, <i>b</i>	COV of $\varepsilon = \delta$ (value in literature)
A	LI- s_u^{re}/P_a	Wroth and Wood (1978)	899	$s_u^{re}/P_a \approx 1.7 \exp(-4.6LI)$	Based on modified Cam Clay model	Figure 2	No	—	—
		Locat and Demers (1988)	899	$s_u^{re}/P_a \approx 0.0144LI^{-2.44}$	—	Figure 2	Yes	1.92	1.25 (n/a)
	LI- S_t	Bjerrum (1954)	1279	$S_t \approx 10^{0.8LI}$	Norwegian marine clays	Figure 3	Yes	2.06	1.09 (n/a)
		Ching and Phoon (2012b)	1279	$S_t \approx 20.726LI^{1.910}$	Structured clays with $S_t = 2 \sim 1000$ and OCR = 1~4	Figure 3	Yes	0.88	1.28 (1.19)
B	LI- $\sigma'_v/P_a - S_t$	Mitchell (1993)	694	—	Graphical curves	Figure 4	No	—	—
	LI- $\sigma'_p/P_a - S_t$	NAVFAC (1982)	492	—	Graphical curves	Figure 5	No	—	—
		Stas and Kulhawy (1984)	249	$\sigma'_p/P_a \approx 10^{1.11-1.62LI}$ (for $S_t < 10$ only)	—	Figure 6	Yes	2.94	1.90 (0.34)
		Ching and Phoon (2012b)	489	$\sigma'_p/P_a \approx 0.235LI^{-1.319}S_t^{0.536}$	Structured clays with $S_t = 2 \sim 1000$ and OCR = 1~4	Figure 7	Yes	1.32	0.78 (0.73)
C	LI- s_u/σ'_p	Bjerrum and Simons (1960)	1072	—	Graphical curves; Norwegian NC clays	Figure 8	No	—	—
	PI- s_u/σ'_p	Mesri (1975, 1989)	1155	$s_u(\text{mob})/\sigma'_p \approx 0.22$	—	Figure 9	Yes	1.04	0.55 (n/a)
	OCR- s_u/σ'_v	Jamiolkowski et al. (1985)	1402	$s_u(\text{mob})/\sigma'_v \approx 0.23(\text{OCR})^{0.8}$	—	Figure 10	Yes	1.11	0.53 (n/a)
	OCR- $s_u/\sigma'_v - S_t$	Ching and Phoon (2012b)	395	$s_u(\text{mob})/\sigma'_v \approx 0.229(\text{OCR})^{0.823}S_t^{0.121}$	Structured clays with $S_t = 2 \sim 1000$ and OCR = 1~4	Figure 11	Yes	0.84	0.34 (0.34)
D	CPTU- s_u/σ'_v	Ching and Phoon (2012a)	423	$[(q_t - \sigma_v)/\sigma'_v]/[s_u(\text{mob})/\sigma'_v] \approx 29.1 \exp(-0.513B_q)$	—	Figure 12	Yes	0.95	0.49 (0.31)
			428	$[(q_t - u_2)/\sigma'_v]/[s_u(\text{mob})/\sigma'_v] \approx 34.6 \exp(-2.049B_q)$	—	Figure 12	Yes	1.11	0.57 (0.34)
			423	$[(u_2 - u_0)/\sigma'_v]/[s_u(\text{mob})/\sigma'_v] \approx 21.5B_q$	—	Figure 12	Yes	0.94	0.49 (0.32)
	CPTU-OCR	Chen and Mayne (1996)	690	$\text{OCR} \approx 0.259[(q_t - \sigma_v)/\sigma'_v]^{1.107}$	—	Figure 13	Yes	1.01	0.42 (n/a)
			542	$\text{OCR} \approx 0.545[(q_t - u_2)/\sigma'_v]^{0.969}$	—	Figure 13	Yes	1.06	0.57 (n/a)
			779	$\text{OCR} \approx 1.026B_q^{-1.077}$	—	Figure 13	Yes	1.28	0.86 (n/a)
			690	$\text{OCR} \approx 0.32(q_t - \sigma_v)/\sigma'_v$	—	Figure 13	Yes	1.00	0.39 (≈ 0.25)
			690	$\sigma'_p/P_a \approx 0.227[(q_t - \sigma_v)/P_a]^{1.200}$	—	Figure 14	Yes	0.99	0.42 (n/a)
	CPTU- σ'_p/P_a	Chen and Mayne (1996)	542	$\sigma'_p/P_a \approx 0.490[(q_t - u_2)/P_a]^{1.053}$	—	Figure 14	Yes	1.08	0.61 (n/a)
			690	$\sigma'_p/P_a \approx 1.274 + 0.761(u_2 - u_0)/P_a$	—	Figure 14	No	0.49	0.59 (n/a)
			690	$\sigma'_p/P_a \approx 0.33(q_t - \sigma_v)/P_a$	—	Figure 14	Yes	0.97	0.39 (≈ 0.2)
			690	$\sigma'_p/P_a \approx 0.54(u_2 - u_0)/P_a$	—	Figure 14	Yes	1.18	0.75 (≈ 0.25)
		Kulhawy and Mayne (1990)	690	$\sigma'_p/P_a \approx 0.33(q_t - \sigma_v)/P_a$	—	Figure 14	Yes	0.97	0.39 (≈ 0.2)
			690	$\sigma'_p/P_a \approx 0.54(u_2 - u_0)/P_a$	—	Figure 14	Yes	1.18	0.75 (≈ 0.25)

limited to the range of characteristics contained in the databases, e.g., certain soil types, certain range of soil properties (e.g., insensitive clays), and certain geographic locations. It is important to assess their biases and the uncertainties when these models are applied globally (i.e., applying these models outside their range of calibration). In the current paper, a global clay database is compiled and presented. This database consists of data points from 251 studies, covering clay data from 30 regions or countries world-wide. Hence, the range of data covered by this “global” database is broader than that underlying the calibration of existing transformation models in the literature. Ten parameters of clays are of main interest, including three index properties (i.e., Atterberg’s limits); four parameters for effective stresses, shear strength, and sensitivity; and three parameters from piezocone tests (CPTU). This global database is the largest database compiled by the authors thus far in terms of number of data points and number of parameters of interest. Table 1 shows the databases compiled by the authors, labeled as (soil type)/(number of parameters of interest)/(number of data points). The current global database is CLAY/10/7490. The first purpose of this paper is to present this large database and verify whether the correlation behaviours in the data points are consistent with those exhibited by existing transformation models in the literature. Most of these models are site-specific models. The biases and uncertainties in these models will be estimated using the global database. The site-specific models can be applied to a wider range of conditions when their biases are corrected and their transformation uncertainties are suitably revised.

The uncertainties of the resulting global models are inevitably large because they are required to accommodate a broader range of clays, e.g., insensitive, sensitive, and quick clays. It is possible to reduce the transformation uncertainty by considering soil index properties (such as plasticity index and sensitivity) as secondary input (explanatory) parameters. Most of the existing transformation models do not include such secondary parameters. Nonetheless, with the global database compiled in this study, it is possible to augment the existing transformation models with secondary input parameters. The resulting models will still be global, but with less uncertainties. This is the second purpose of this paper. In a companion paper (Ching and Phoon 2014), a 10-dimensional multivariate probability distribution coupling these clay parameters is constructed from CLAY/10/7490 and a useful application involving updating the entire bivariate probability distribution of two design parameters from three separate measurements is presented.

Database CLAY/10/7490

This study compiles a clay database (CLAY/10/7490) from the literature consisting of a large number of data points. This database consists of data points from 251 studies. The number of data points associated with each study varies from 1 to 419 with an average 30 data points per study. The geographical regions cover Australia, Austria, Brazil, Canada, China, England, Finland, France, Germany, Hong Kong, India, Iraq, Italy, Japan, Korea, Malaysia, Mexico, New Zealand, Northern Ireland, Norway, Poland, Singapore, South Africa, Spain, Sweden, Taiwan, Thailand, United Kingdom, United States, and Venezuela. The clay properties cover a wide range of overconsolidation ratio (OCR) values (but mostly 1–10), a wide range of sensitivity (S_t) values (sites with $S_t = 1$ –tens or hundreds are fairly typical), and a wide range of plasticity index (PI) values (but mostly 8–100). Figure 1 shows the plasticity chart and Robertson’s CPTU soil classification chart (Robertson 1990) of all data points in the database — most data points are classified as clays (some are sensitive or organic clays). Some data points are classified as clayey silts or silt mixtures, and a few are classified as sand mixtures or sands. The details of this database are shown in Appendix A.

Fig. 2. $LI-(s_u^{re}/P_a)$ models proposed by Wroth and Wood (1978) and Locat and Demers (1988).





Fig. 3. $LI-S_t$ models proposed by Bjerrum (1954) and Ching and Phoon (2012b).




Ten dimensionless parameters of clays are of primary interest. They are categorized into three groups:

1. Index properties, including liquid limit (LL), plasticity index (PI), and liquidity index (LI).
2. Stresses and strengths, including normalized vertical effective stress (σ'_v/P_a , where P_a is one atmosphere pressure ($= 101.3 \text{ kN/m}^2$)), normalized preconsolidation stress (σ'_p/P_a), normalized undrained shear strength (s_u/σ'_v), and sensitivity ($S_t = s_u/s_u^{re}$, where s_u^{re} is the remoulded undrained shear strength).

The s_u values in the literature were obtained based on various types of tests, including isotropically consolidated undrained compression (CIUC), K_0 -consolidated undrained compression (CK_0UC), K_0 -consolidated undrained extension (CK_0UE), direct simple shear (DSS), unconsolidated undrained compression (UU), unconfined compression (UC), and field vane (FV). These values cannot be compared directly because s_u depends on stress state, strain rate, and sampling distur-

Fig. 4. $LI-(\sigma'_v/P_a)-S_t$ model proposed by Mitchell (1993).



bance. By following the recommendations made by Bjerrum (1972), Kulhawy and Mayne (1990), and Mesri and Huvaj (2007), these s_u values are all converted to the “mobilized” s_u values, denoted by $s_{u(mob)}$, which is defined as the in situ undrained shear strength mobilized in embankment and slope failures (Mesri and Huvaj 2007). The transformation models used to convert undrained shear strengths derived from different test types to the reference $s_{u(mob)}$ are given in Table 2.

- Parameters from the piezocone test (CPTU), including pore pressure ratio $B_q = (u_2 - u_0)/(q_t - \sigma_v)$, where u_2 is the pore pressure behind the cone, u_0 is the hydrostatic pore pressure, q_t is the corrected cone tip resistance, and σ_v is the total effective stress; normalized cone tip resistance $(q_t - \sigma_v)/\sigma'_v$; and normalized effective cone tip resistance $(q_t - u_2)/\sigma'_v$.

The CPTU data are nearly continuous with depth. However, only a few data points in a CPTU profile are adopted into the database at the depths where other clay parameters (such as s_u and PI) are also known. As a result, the vertical interval of the adopted CPTU data points at the same site is about 1 to 3 m. Note that the point data at the appropriate depths are adopted. A possible refinement involving averaging along the length of the undisturbed sample was not considered.


Some other dimensionless parameters of interest, such as s_u/σ'_p , OCR, and s_u^{re}/P_a , can be derived from the above 10 parameters. The basic statistics of all these parameters (10 basic parameters together with s_u/σ'_p , OCR, and s_u^{re}/P_a) are listed in Table 3. The numbers of available data points (n) are shown in the second column. The statistics are the mean value, coefficient of variation (COV), minimum value (min), and maximum value (max). Their percentiles are listed in Table 4, where the median values (50% percentiles) are shaded. It is worth mentioning that the statistical uncertainty is higher for the lower and higher percentiles.

Calibration of existing transformation models

In the database, there are data points where two or more clay parameters are simultaneously known. For instance, a disturbed clay sample is extracted to determine PI, and an undisturbed clay sample is extracted at a nearby borehole at the same depth to determine s_u . In this case, PI and s_u are simultaneously known. These data points can be compared with transformation models proposed in literature as a rough check for consistency. Twenty-four transformation models shown in Table 5 are considered. Most of these models were developed based on certain clay databases, but these databases may not be global in the sense that the data are limited to certain clay types or certain geographic locations. In other words, they are typically site-specific models. It is recommended that the basic statistics of the database supporting the development of transformation models should be explicitly reported in the form of Table 3 and (or) Table 4. The characteristics of the databases underlying numerous existing transformation models are not known and this complicates comparisons with other databases such as the one presented in this study. These characteristics are of interest, because engineers can make a more informed decision on the applicability of a particular transformation model to his or her design scenario at hand.

In the section below, the global database is compared with existing transformation models to assess the quality of the data compiled for this study. The global database is considered to be satisfactory if there is broad agreement with the transformation models published in the literature. Some differences are to be expected. In the absence of detailed information on the databases supporting published transformation models, it is assumed in this study that the differences arose because our global database covers a broader range of clays. As a result, correcting published transformation models will broaden the range of their applicability. The correction is undertaken by calibrating the bias factors

Fig. 5. $LI-(\sigma'_p/P_a)-S_t$ model proposed by NAVFAC (1982).



and uncertainties for these models against the global database compiled in this study.

These 24 transformation models are labeled using the template: (primary input parameter)–(target parameter)–(secondary input parameter). They are categorized into four types (see Table 5):

1. Type A — Models for S_t , including two $LI-(s_u^{\text{re}}/P_a)$ models and two $LI-S_t$ models.
2. Type B — Models for effective stress, including one $LI-(\sigma'_v/P_a)-S_t$ model and three $LI-(\sigma'_p/P_a)-S_t$ models.
3. Type C — Models for shear strength, including one $LI-(s_u/\sigma'_p)$ model, one $PI-(s_u/\sigma'_p)$ model, one $OCR-(s_u/\sigma'_v)$ model, and one $OCR-(s_u/\sigma'_v)-S_t$ model.


In the $LI-(s_u/\sigma'_p)$ model proposed by Bjerrum and Simons (1960) for normally consolidated (NC) clays, the s_u/σ'_p values are obtained from CIUC tests. For NC clays, $s_u(\text{CIUC})/\sigma'_p$ is estimated to be 0.37, whereas $s_u(\text{mob})/\sigma'_p$ is about 0.22 (Mesri 1975, 1989). As a result, the s_u/σ'_p value in the original $LI-(s_u/\sigma'_p)$ model by Bjerrum and Simons (1960) is multiplied by $0.22/0.37 = 0.59$.

4. Type D — Models relevant to CPTU, including three $CPTU-(s_u/\sigma'_v)$ models, four $CPTU-OCR$ models, and five $CPTU-(\sigma'_p/P_a)$ models.


Note that for the $CPTU-(s_u/\sigma'_v)$ models by Ching and Phoon (2012a), the target parameters are actually the cone factors (namely $(q_t - \sigma_v)/s_u$, $(q_t - u_2)/s_u$, and $(u_2 - u_0)/s_u$). In these models, the s_u values are obtained from CIUC tests. Therefore, the cone factors in these models are divided by the same factor of 0.59.

Most of these 24 transformation models are derived empirically using regression analyses. The only exception is the $LI-(s_u^{\text{re}}/P_a)$ model by Wroth and Wood (1978), which is derived theoretically from the modified Cam Clay model. Most models are not constructed for a specific type of clay. The exceptions are: (i) the $LI-$

Fig. 6. $LI-(\sigma'_p/P_a)-S_t$ model proposed by Stas and Kulhawy (1984).



$(\sigma'_p/P_a)-S_t$ and $OCR-(s_u/\sigma'_v)-S_t$ models by Ching and Phoon (2012b), constructed primarily from sensitive (structured) clay data (database CLAY/5/535 in Table 1); (ii) the $LI-S_t$ model by Bjerrum (1954), constructed from Norwegian marine clay data only; and (iii) the $LI-(s_u/\sigma'_p)$ model by Bjerrum and Simons (1960), constructed from Norwegian NC clay data. Some transformation models are presented as graphical curves only: (i) the $LI-(\sigma'_v/P_a)-S_t$ model by Mitchell (1993), (ii) the $LI-(\sigma'_p/P_a)-S_t$ by NAVFAC (1982), and (iii) the $LI-(s_u/\sigma'_p)$ model by Bjerrum and Simons (1960). No equations were reported by the original authors.

Fig. 7. $LI-(\sigma'_p/P_a)-S_t$ model proposed by Ching and Phoon (2012b).


The comparison results between the transformation models and the database are shown in Figs. 2–14. For the models with a secondary input parameter S_t , data points in our database are divided into four groups according to their S_t values, and four subplots are presented to compare with the transformation models. The four groups are obtained based on $S_t < 4$, $4 < S_t < 10$, $10 < S_t < 20$, and $S_t > 20$. Figures 2–14 show that the global data follow similar trends to most transformation models reported in the literature. The exceptions are the following six models:

1. The $LI-(s_u^{\text{re}}/P_a)$ model proposed by Wroth and Wood (1978). This model was developed based on the modified Cam Clay model. It provides a reasonable average fit to the data for $LI < 1$ as shown in Fig. 2. However, it deviates significantly from the data points in our global database for $LI > 1.5$.
2. The $LI-(\sigma'_v/P_a)-S_t$ model proposed by Mitchell (1993). Despite the wide scatter as shown in Fig. 4, there is general agreement between this model and the global data for data points with $4 < S_t < 20$. However, for data with small S_t values ($S_t < 4$) or with large S_t values ($S_t > 20$), the agreement is poor. It is possible that this model was developed with most data points falling between $4 < S_t < 20$. In other words, the empirical support for small and large S_t values may be weak.
3. The $LI-(\sigma'_p/P_a)-S_t$ model proposed by NAVFAC (1982). The observations here are similar to those for the Mitchell's model: there is a reasonably good agreement between the model and the global data for data points with $4 < S_t < 20$ (see Fig. 5). The agreement is poor outside this range of S_t . One may venture to guess that the empirical support for small and large S_t values is also weak for this model.
4. The $LI-(\sigma'_p/P_a)-S_t$ model proposed by Ching and Phoon (2012b). The agreement between this model and the global data are reasonable for data points with large S_t values ($S_t > 20$) as shown in Fig. 7. However, this model does not fit data with small S_t values ($S_t < 4$). This is because the database CLAY5/345

used to develop this $LI-(\sigma'_p/P_a)-S_t$ model contains only structured clays.

5. The $LI-(s_u^{\text{re}}/P_a)$ model proposed by Bjerrum and Simons (1960). In Fig. 8, only data points with $OCR < 1.2$ (nearly NC clays) in the global database are plotted. Nonetheless, the discrepancy between the model and the data is clear. Note that this model was developed based on Norwegian NC clays only. It is most likely that this site-specific model fits to the Norwegian data, but not to the global data from diverse geographic origins.
6. One of the $CPTU-(\sigma'_p/P_a)$ models proposed by Chen and Mayne (1996) (the third model that relates σ'_p/P_a to $(u_2 - u_0)/P_a$ in Table 5). The discrepancy between this model and our global data is apparent. However, the first two models developed by Chen and Mayne (1996) (the two models that relate σ'_p/P_a to $(q_t - \sigma_v)/P_a$ and $(q_t - u_2)/P_a$) provide reasonable fits to our global data. We are unable to explain this anomaly.

Biases and uncertainties of the existing transformation models

The bias factors and coefficients of variation (COVs) of all models with respect to the global database are calibrated, except the three models that are only presented as graphical curves in the literature. The bias factor is denoted by b , and the COV is denoted by δ . Basically, b is the sample mean of (actual target value)/(predicted target value) for the global data points, and δ is the sample COV of (actual target value)/(predicted target value). For instance, for the $LI-(s_u^{\text{re}}/P_a)$ model proposed by Locat and Demers (1988), the actual target value is the s_u^{re}/P_a value in the global database, and the predicted target value is $0.0144LI^{-2.44}$. For each data point with simultaneous knowledge of (LI, s_u^{re}) , (actual target value)/(predicted target value) = $(s_u^{\text{re}}/P_a)/(0.0144LI^{-2.44})$ can be computed. The histogram of the ratio $(s_u^{\text{re}}/P_a)/(0.0144LI^{-2.44})$ is plotted in Fig. 15. The sample mean of this ratio is equal to 1.92, which is equal to b .

Fig. 8. $LI-(s_u/\sigma'_p)$ model proposed by Bjerrum and Simons (1960).





Fig. 9. $PI-(s_u/\sigma'_p)$ model proposed by Mesri (1975, 1989).




The sample COV of this ratio is 1.25, which is equal to δ . To be specific,

$$(1) \quad \text{Actual target value} = \text{predicted target value} \times b \times \varepsilon$$

where b is the bias factor ($b = 1$ means unbiased) and ε is the variability term with mean = 1 and COV = δ . If $\delta = 0$, there is no data scatter about the transformation model, i.e., the prediction is single-valued or deterministic, rather than a distribution. The $LI-(s_u^{\text{re}}/P_a)$ model proposed by Locat and Demers (1988) is biased because the bias factor (b) is around 1.92, and the COV of this model is around 1.25. This model basically underpredicts the actual value by a factor of about 2 (conservative model). The uncertainty underlying this prediction when it is made to cover the wide range of conditions in the global database is considerable given that the COV exceeds 100%. The calibrated bias factors and COVs for all models are shown in the last two columns of Table 5. The number of data points “ n ” used for each calibration is listed in the table.

Fig. 10. $OCR-(s_u/\sigma'_v)$ model proposed by Jamiolkowski et al. (1985).



It is evident that models published in more recent studies, such as Kulhawy and Mayne (1990), Chen and Mayne (1996), and Ching and Phoon (2012a, 2012b) mostly have bias factors $b \approx 1$ (less biased). These recent studies compiled fairly large databases as well. It is also evident that the COVs (δ) calibrated by the global database in this study are typically higher than those reported in the literature (see the numbers in the parentheses in the rightmost column in Table 5). The exceptions are the $LI-S_t$, $LI-(\sigma'_p/P_a)-S_t$, and $OCR-(s_u/\sigma'_v)-S_t$ models developed in Ching and Phoon (2012b): COVs for these three models are close to those reported in Ching and Phoon (2012b). The statistics of the database used by Ching and Phoon (2012b) are given in the “Remarks” column in Table 5.

The bias factors in Table 5 still deviate somewhat from unity for two possible reasons:

1. The bias factors in Table 5 are calibrated using the global database in this study that contains broader types of clays, typically broader than the databases used to develop the transformation models in the literature. For instance, Ching and Phoon (2012b) only considered structured clays.
2. All s_u data points in the global database are converted to $s_u(\text{mob})$ (see Table 2). Such a conversion step may introduce an extra bias.

The COVs in Table 5 are typically larger than those reported in the literature for three possible reasons:

1. These COVs are calibrated using the global database that contains broader types of clays.
2. The conversion of the s_u data points to a reference strength, $s_u(\text{mob})$, would introduce transformation uncertainty. It is noteworthy that the COVs can be even larger without this conversion, because s_u varies significantly with the test type (Ladd et al. 1977).
3. The COVs summarized in Ching and Phoon (2012a) for the CPTU- (s_u/σ'_v) transformation models do not include measurement errors.

By definition, the models calibrated by the global database are unbiased with respect to the global database in this study. For instance, for the $LI-s_u^{\text{re}}/P_a$ model by Locat and Demers (1988), the predicted value for s_u^{re}/P_a is $0.0144LI^{-2.44}$. This model has a bias factor $b = 1.92$, calibrated by the global database. As a result, the calibrated model $s_u^{\text{re}}/P_a \approx b(0.0144)LI^{-2.44} = 1.92(0.0144)LI^{-2.44}$ is an

Fig. 11. OCR–(s_u/σ'_v)– S_t model proposed by Ching and Phoon (2012b).





Fig. 12. CPTU– s_u/σ'_v models proposed by Ching and Phoon (2012a).



“unbiased prediction” with respect to the global database. This means that this calibrated model can capture the mean trend of the global database, and the calibrated COV can adequately capture the data scatter around the mean trend. However, the COV is typically quite large to capture the data scatter. In the next section, the possibility of incorporating secondary input parameters to reduce the COV is addressed.

Secondary input parameters

A possible reason for the significant data scatter around the mean trend is that additional explanatory variables are not incorporated into the transformation model. As a result, the variation in these hidden explanatory variables, which is inevitable in a database, is added to the transformation uncertainty. A good example is the OCR–(s_u/σ'_v) model by Jamiolkowski et al. (1985). The COV with respect to the global database is 0.53 for this model (see Table 5). This means that the standard deviation of the data scatter

is about 53% of the mean trend. A possible hidden explanatory variable is the sensitivity S_t — it is known that the “stress history and normalized soil engineering properties” SHANSEP parameters for sensitive (structured) clays are different from those for insensitive clays. In fact, by incorporating S_t as a secondary input parameter, the OCR–(s_u/σ'_v)– S_t model by Ching and Phoon (2012b) carries a significantly smaller COV of 0.34 (see Table 5). It is widely known that parameters such as PI and S_t can be applied as secondary explanatory variables for some correlations. It is of interest to see whether the incorporation of these secondary input parameters can reduce COV significantly. If the COV reduction is significant, it is of interest to re-calibrate the transformation models to further update the bias factors and the COVs in Table 5. This is the main objective of this section.

Correlation between ε and (PI, S_t)

Let us recall from eq. (1) that the variability term ε for a transformation model can be expressed as

Fig. 13. CPTU-OCR models proposed by Chen and Mayne (1996) and Kulhawy and Mayne (1990).




Fig. 14. CPTU- σ'_p/P_a models proposed by Chen and Mayne (1996) and Kulhawy and Mayne (1990).





Fig. 15. Histogram of $(s_u^{re}/P_a)/(0.0144LI^{-2.44})$.



$$(2) \quad \varepsilon = \frac{\text{actual target value}}{b \times \text{predicted target value}} = \frac{\text{actual target value}}{\text{unbiased prediction}}$$


where the unbiased prediction = $b \times$ predicted target value. The variability term ε quantifies the deviation between the actual value and the unbiased prediction. It has mean value of 1 and COV equal to the calibrated COV (δ). Equivalently,

$$(3) \quad \ln(\varepsilon) = \ln(\text{actual target value}) - \ln(\text{unbiased prediction})$$

In essence, $\ln(\varepsilon)$ is the component that cannot be explained away by the primary input parameter. More precisely, $\ln(\varepsilon)$ should be uncorrelated to the primary input parameter. The reason why the natural logarithm is taken will be explained later. For instance, $\ln(\varepsilon)$ for the OCR- (s_u/σ'_v) model proposed by Jamiolkowski et al. (1985) is indeed nearly uncorrelated to the primary input parameter $\ln(\text{OCR})$, shown in Fig. 16a. Incidentally, the correlation between $\ln(\varepsilon)$ and $\ln(P_i)$ is also nearly zero (Fig. 16b). However, $\ln(\varepsilon)$ and $\ln(S_t)$ show some slight positive correlation (Fig. 16c). In this case, it may be possible to adopt S_t as the secondary input parameter for Jamiolkowski et al.'s model to reduce its COV.

In this section, the correlation between $\ln(\varepsilon)$ and the natural logarithm of the secondary input parameter (P_i or S_t) will be studied. The correlation with respect to $\ln(P_i)$ will be studied for all

Fig. 16. (a) $\ln(\varepsilon)$ – $\ln(\text{OCR})$, (b) $\ln(\varepsilon)$ – $\ln(\text{PI})$, and (c) $\ln(\varepsilon)$ – $\ln(S_t)$ plots for the model proposed by Jamiolkowski et al. (1985). ρ , correlation coefficient.



models except the $\text{PI}-(s_u/\sigma'_p)$ model proposed by Mesri (1975, 1989), because PI is already the primary input parameter. Similarly, the correlation with respect to $\ln(S_t)$ will not be studied for models whose primary inputs already involve S_t . The correlation with respect to $\ln(S_t)$ will not be studied for models whose target is s_u^{re} , because soil structure is supposed to be destroyed in the remoulded state and hence, it does not make much sense to infer s_u^{re} using S_t .

The correlation between $\ln(\varepsilon)$ and the natural logarithm of the secondary input parameter (PI or S_t) is quantified by the Pearson product moment correlation coefficient (ρ). The correlation coefficient for the $\ln(\varepsilon)$ – $\ln(\text{PI})$ and $\ln(\varepsilon)$ – $\ln(S_t)$ correlations are shown in Table 6. The parameter n shown in Table 6 is the number of data points used to estimate each correlation. It is clear that the $\ln(\varepsilon)$ – $\ln(\text{PI})$ data points are abundant ($n > 300$), whereas the $\ln(\varepsilon)$ – $\ln(S_t)$ data points are less abundant. It is also evident that the $\ln(\varepsilon)$ – $\ln(S_t)$ correlations seem stronger (ρ is farther away from zero) than the $\ln(\varepsilon)$ – $\ln(\text{PI})$ correlations.

Re-calibrate the existing transformation models – inference using PI and S_t

For the inference using PI, it is possible to express ε as a function of PI

$$(4) \quad \varepsilon = [\alpha(\text{PI}/20)^\beta] \varepsilon'$$

where ε' is the (updated) variability term that cannot be explained away by PI, and $\text{PI} = 20$ is a reference PI value (median plasticity). The mean value of ε' is still 1 and its (updated) COV is denoted by δ' , which should be less than δ if $\ln(\varepsilon)$ and $\ln(\text{PI})$ are correlated. The coefficients α and β can be estimated using linear regression on the $\ln(\varepsilon)$ – $\ln(\text{PI})$ data points. Namely, the following regression model is used:

$$(5) \quad \ln(\varepsilon) \approx \ln(\alpha) + \beta \ln(\text{PI}/20)$$

where $\ln(\varepsilon)$ is the known output and $\ln(\text{PI}/20)$ is the known input, whereas $\ln(\alpha)$ and β are the intercept and gradient, respectively, to be estimated by the least squares method. The natural logarithm is taken for ε and PI because traditional linear regression requires normality. Figure 17 shows the histograms of ε and $\ln(\varepsilon)$ for the $\text{OCR}-(s_u/\sigma'_v)$ model proposed by Jamiolkowski et al. (1985) — $\ln(\varepsilon)$ is more normal than ε . In fact, $\ln(\text{PI})$ is also more normal than PI (not shown). Hence, it is more appropriate to do regression on the $\ln(\varepsilon)$ – $\ln(\text{PI})$ data points. Once the least-squares estimates for α and β are obtained, eq. (1) can be expressed as

$$(6) \quad \begin{aligned} \text{Actual value} &= \text{predicted value} \times b \times [\alpha \times (\text{PI}/20)^\beta] \times \varepsilon' \\ &= \text{predicted value} \times b' \times \varepsilon' \end{aligned}$$

where b' is the updated bias factor and can be expressed as the product of the original bias b and a correction term $\alpha \times (\text{PI}/20)^\beta$

$$(7) \quad b' = b \times [\alpha \times (\text{PI}/20)^\beta] = b \times (\text{bias correction factor})$$

The term $\alpha \times (\text{PI}/20)^\beta$ is called the bias correction factor (BCF). In Table 6, the updated bias factors b' are shown in the format of $b' = (\text{original } b) \times [\text{BCF}]$. The sample COV of ε' (the updated variability term) is denoted by δ' . In Table 6, δ' values are shown in the format of $\delta' = (\text{original } \delta) \times (\text{CCF}\%)$, where CCF denotes the COV correction factor.

It is apparent that when the target parameter is σ'_p/P_a or OCR, the BCFs are always decreasing functions of PI ($\beta < 0$). This implies that clays with larger PI values tend to have lower σ'_p/P_a and OCR values. For the CPTU– (s_u/σ'_v) model proposed by Ching and Phoon (2012a), the target parameter is the CPTU cone factors (namely $(q_t - \sigma_v)/s_u$, $(q_t - u_2)/s_u$, and $(u_2 - u_0)/s_u$), the BCFs are increasing functions of PI ($\beta > 0$). This implies that clays with larger PI tend to have larger cone factors, hence smaller s_u . This observation is known (Aas et al. 1986; Marsland and Powell 1988; Powell and Quarterman 1988) although it has not been established with statistical rigor using such a large database. The CCFs are fairly close to 100%, indicating that the inference using PI does not significantly reduce the transformation uncertainties.

For the inference using PI and S_t , it is possible to express ε as

$$(8) \quad \varepsilon = [\alpha \times (\text{PI}/20)^\beta \times S_t^\gamma] \varepsilon'$$

The coefficients α , β , and γ can be estimated using linear regression on the $\ln(\varepsilon)$ – $\ln(\text{PI})$ – $\ln(S_t)$ data points. Namely, the following regression model is used:


$$(9) \quad \ln(\varepsilon) \approx \ln(\alpha) + \beta \ln(\text{PI}/20) + \gamma \ln(S_t)$$

where $\ln(\varepsilon)$ is the known output, and $\ln(\text{PI}/20)$ and $\ln(S_t)$ are the known inputs, whereas $\ln(\alpha)$, β , and γ are the intercept and gradients to be estimated by the least-squares method. Once the least-squares estimates for α , β , and γ are obtained, the term $\alpha \times (\text{PI}/20)^\beta \times S_t^\gamma$ is now the BCF. Table 6 shows the updated bias factors b' in the format of $b' = (\text{original } b) \times [\text{BCF}]$ and the updated δ' in the format of $\delta' = (\text{original } \delta) \times (\text{CCF}\%)$ for the inference using PI and S_t . It is apparent

Table 6. Analysis results for $\ln(\varepsilon)$ - $\ln(\text{PI})$ and $\ln(\varepsilon)$ - $\ln(S_t)$ correlations and inference results.

Relationship	Literature	Correlation coefficient				Updated model	Inference results			
		ε -PI		ε - S_t			Inference based PI only		Inference based on PI and S_t	
		n	ρ	n	ρ		$b' = b \times [\text{BCF}]$	$\delta' = \delta \times (\text{CCF}\%)$	$b' = b \times [\text{BCF}]$	$\delta' = \delta \times (\text{CCF}\%)$
LI- (s_u^{re}/P_a)	Locat and Demers (1988)	887	-0.24	—	—	$s_u^{\text{re}}/P_a = 0.0144\text{LI}^{-2.44}b'\varepsilon'$	$1.92 \times [1.11(\text{PI}/20)^{-0.258}]$	$1.25 \times (94\%)$	—	—
LI- S_t	Bjerrum (1954)	1137	0.18	—	—	$S_t = 10^{0.8\text{LI}}b'\varepsilon'$	$2.05 \times [0.92(\text{PI}/20)^{0.251}]$	$1.09 \times (104\%)$	—	—
	Ching and Phoon (2012b)	1137	-0.02	—	—	$S_t = 20.726\text{LI}^{1.910}b'\varepsilon'$	$0.88 \times [1.01(\text{PI}/20)^{-0.025}]$	$1.28 \times (99\%)$	—	—
	Stas and Kulhawy (1984) (for $S_t < 10$ only)	257	-0.37	—	—	$\frac{\sigma'_p}{P_a} = 10^{1.11-1.62\text{LI}}b'\varepsilon'$	$2.94 \times [1.25(\text{PI}/20)^{-0.478}]$	$1.90 \times (85\%)$	—	—
LI- σ'_p/P_a - S_t	Ching and Phoon (2012b)	487	-0.35	—	—	$\frac{\sigma'_p}{P_a} = 0.235\text{LI}^{-1.319}S_t^{0.536}b'\varepsilon'$	$1.32 \times [1.24(\text{PI}/20)^{-0.444}]$	$0.78 \times (93\%)$	—	—
PI- s_u/σ'_p	Mesri (1975, 1989)	—	—	433	0.43	$s_u(\text{mob})/\sigma'_p = 0.22b'\varepsilon'$	—	—	$1.04 \times [0.76S_t^{0.136}]$	$0.55 \times (63\%)$
OCR- s_u/σ'_v	Jamiolkowski et al. (1985)	1091	-0.06	395	0.34	$s_u(\text{mob})/\sigma'_v = 0.23\text{OCR}^{0.8}b'\varepsilon'$	$1.11 \times [1.10(\text{PI}/20)^{-0.050}]$	$0.53 \times (94\%)$	$1.11 \times [0.71(\text{PI}/20)^{0.133}S_t^{0.123}]$	$0.53 \times (67\%)$
OCR- $s_u\sigma'_v$ - S_t	Ching and Phoon (2012b)	391	0.21	—	—	$\frac{s_u(\text{mob})}{\sigma'_v} = 0.229\text{OCR}^{0.823}S_t^{0.121}b'\varepsilon'$	$0.84 \times [0.93(\text{PI}/20)^{0.131}]$	$0.34 \times (102\%)$	—	—
CPTU- s_u/σ'_v	Ching and Phoon (2012a)	387	0.38	81	-0.24	$\frac{(q_t - \sigma_v)/\sigma'_v}{s_u(\text{mob})/\sigma'_v} = 29.1[\exp(-0.513B_q)]b'\varepsilon'$	$0.95 \times [0.80(\text{PI}/20)^{0.348}]$	$0.49 \times (100\%)$	$0.95 \times [1.17(\text{PI}/20)^{0.241}S_t^{-0.198}]$	$0.49 \times (77\%)$
		392	0.29	78	-0.39	$\frac{(q_t - u_2)/\sigma'_v}{s_u(\text{mob})/\sigma'_v} = 34.6[\exp(-2.049B_q)]b'\varepsilon'$	$1.11 \times [0.78(\text{PI}/20)^{0.275}]$	$0.57 \times (90\%)$	$1.11 \times [1.40(\text{PI}/20)^{0.189}S_t^{-0.263}]$	$0.57 \times (72\%)$
		387	0.38	81	-0.25	$\frac{(u_2 - u_0)/\sigma'_v}{s_u(\text{mob})/\sigma'_v} = 21.5B_qb'\varepsilon'$	$0.94 \times [0.80(\text{PI}/20)^{0.335}]$	$0.49 \times (101\%)$	$0.94 \times [1.22(\text{PI}/20)^{0.275}S_t^{-0.216}]$	$0.49 \times (78\%)$
CPTU-OCR	Chen and Mayne (1996)	497	-0.09	163	0.12	$\text{OCR} = 0.259[(q_t - \sigma_v)/\sigma'_v]^{1.107}b'\varepsilon'$	$1.01 \times [1.01(\text{PI}/20)^{-0.073}]$	$0.42 \times (110\%)$	$1.01 \times [1.09(\text{PI}/20)^{-0.206}S_t^{0.002}]$	$0.42 \times (73\%)$
		466	-0.11	123	0.27	$\text{OCR} = 0.545[(q_t - u_2)/\sigma'_v]^{0.969}b'\varepsilon'$	$1.06 \times [1.10(\text{PI}/20)^{-0.105}]$	$0.57 \times (99\%)$	$1.06 \times [0.79(\text{PI}/20)^{-0.273}S_t^{0.102}]$	$0.57 \times (69\%)$
		545	-0.17	173	0.12	$\text{OCR} = 1.026B_q^{-1.077}b'\varepsilon'$	$1.28 \times [1.05(\text{PI}/20)^{-0.196}]$	$0.86 \times (91\%)$	$1.28 \times [0.63(\text{PI}/20)^{-0.079}S_t^{-0.057}]$	$0.86 \times (52\%)$
CPTU- σ'_p/P_a	Kulhawy and Mayne (1990)	497	-0.11	163	0.14	$\text{OCR} = 0.32[(q_t - \sigma_v)/\sigma'_v]b'\varepsilon'$	$1.00 \times [1.01(\text{PI}/20)^{-0.084}]$	$0.39 \times (108\%)$	$1.00 \times [1.04(\text{PI}/20)^{-0.188}S_t^{0.010}]$	$0.39 \times (71\%)$
	Chen and Mayne (1996)	497	-0.04	163	0.15	$\sigma'_p/P_a = 0.227[(q_t - \sigma_v)/P_a]^{1.200}b'\varepsilon'$	$0.99 \times [1.02(\text{PI}/20)^{-0.028}]$	$0.42 \times (105\%)$	$0.99 \times [1.07(\text{PI}/20)^{-0.124}S_t^{0.002}]$	$0.42 \times (70\%)$
		466	-0.09	123	0.28	$\sigma'_p/P_a = 0.490[(q_t - u_2)/P_a]^{1.053}b'\varepsilon'$	$1.08 \times [1.09(\text{PI}/20)^{-0.087}]$	$0.61 \times (99\%)$	$1.08 \times [0.78(\text{PI}/20)^{-0.268}S_t^{0.105}]$	$0.61 \times (68\%)$
		498	-0.25	163	0.04	$\sigma'_p/P_a = \left[1.274 + 0.761\frac{(u_2 - u_0)}{P_a}\right]b'\varepsilon'$	$0.49 \times [0.99(\text{PI}/20)^{-0.235}]$	$0.59 \times (89\%)$	$0.49 \times [0.94(\text{PI}/20)^{-0.262}S_t^{0.026}]$	$0.59 \times (60\%)$
	Kulhawy and Mayne (1990)	497	-0.11	163	0.14	$\sigma'_p/P_a = 0.33[(q_t - \sigma_v)/P_a]b'\varepsilon'$	$0.97 \times [1.01(\text{PI}/20)^{-0.084}]$	$0.39 \times (108\%)$	$0.97 \times [1.04(\text{PI}/20)^{-0.188}S_t^{0.010}]$	$0.39 \times (71\%)$
		497	-0.12	162	-0.01	$\sigma'_p/P_a = 0.54[(u_2 - u_0)/P_a]b'\varepsilon'$	$1.18 \times [0.96(\text{PI}/20)^{-0.114}]$	$0.75 \times (93\%)$	$1.18 \times [1.04(\text{PI}/20)^{-0.114}S_t^{-0.069}]$	$0.75 \times (61\%)$

Fig. 17. Histograms of ε and $\ln(\varepsilon)$ for the OCR- (s_u/σ'_v) model proposed by Jamiolkowski et al. (1985).



that when the target parameter is s_u/σ'_v or s_u/σ'_p , these BCFs are always increasing functions of S_t ($\gamma > 0$), implying that clays with larger S_t values tend to have larger s_u/σ'_v and s_u/σ'_p values. When the target parameter is CPTU cone factors, these BCFs are decreasing functions of S_t ($\gamma < 0$). This implies that clays with larger S_t values tend to have smaller cone factors, hence larger s_u values. The updated COV (δ') is typically noticeably less than the original δ value in Table 5. There are two possible explanations for such uncertainty reduction:

1. The uncertainty is indeed effectively reduced with the inclusion of S_t as a secondary explanatory variable.
2. The number of $\ln(\varepsilon)-\ln(\text{PI})-\ln(S_t)$ data points is substantially less than the number of $\ln(\varepsilon)-\ln(\text{PI})$ data points (see the “ n ” column in Table 5). The former n is typically around 100 to 200, except two models where n is around 400, while the latter n is about 2 to 5 times more. These relatively small numbers of the $\ln(\varepsilon)-\ln(S_t)$ data points may not represent a “global” dataset. Hence, the resulting δ' may look small.

Implementation

Tables 5 and 6 are useful for obtaining first-order estimates of the mean and COV of a clay parameter of interest (e.g., s_u or σ'_p) based on the test index at hand. These mean and COV estimates are essential for RBD. First of all, it is imperative to determine whether a transformation model is consistent with the CLAY/10/7490 database by checking the column “Comparison to the global database” and subcolumn “Fit to the trend?”. It is recommended to only adopt models that fit to the CLAY/10/7490 database. Using the well-known model developed by Jamiolkowski et al. (1985) as an example, suppose OCR = 2 is known, and the goal is to determine the mean and COV of $s_u(\text{mob})/\sigma'_v$. According to Table 5, this model fits well to the CLAY/10/7490 database and this fit is shown in Fig. 10. The second step is to extract the bias factor $b = 1.11$ and COV = 0.53 from the column “Calibration results”. Then, the mean of $s_u(\text{mob})/\sigma'_v$ is computed as $b \times 0.23 \times \text{OCR}^{0.8} = 1.11 \times 0.23 \times 2^{0.8} = 0.44$ and the data scatter around the mean is quantified by COV = 0.53.

In the case where PI = 15 and $S_t = 10$ information is also available, one can extract the bias correction factor (BCF) and COV correction factor (CCF) from the column “Inference results” and subcolumn “Inference based on PI and S_t ” in Table 6. Thus, $\text{BCF} = 0.71 \times (\text{PI}/20)^{0.133} \times S_t^{0.123} = 0.71 \times (15/20)^{0.133} \times 10^{0.123} = 0.907$ and $\text{CCF} = 67\%$. As a result, the mean for $s_u(\text{mob})/\sigma'_v$ becomes $0.44 \times 0.907 = 0.403$ and the COV becomes $0.53 \times 67\% = 0.36$. Updating the mean and COV of $s_u(\text{mob})/\sigma'_v$ based on other measured pieces of information (for example, PI, S_t , $(q_t - \sigma_v)/\sigma'_v$, and B_q may have been

simultaneously measured in close proximity at the same depth in a site investigation report) is possible once the multivariate probability distribution among these clay parameters is established. This is addressed in a companion paper (Ching and Phoon 2014).

Conclusions

In this paper, a global clay database is presented, and 24 transformation models among clay parameters in the literature are investigated. This database contains clays with a wide range of S_t , OCR, and PI values and from a wide range of geographical locales. It is found that most of the 24 models fit to the data trends of the global database. There are few exceptions, and it is believed that the poor fit is due to the fact that these models were developed by databases with a limited range of clay types (e.g., no quick clays are in the database or only clays of a single region were in the database).

The global database is further used to calibrate the biases and uncertainties for the models in literature. It is found that more recent models tend to have smaller biases. Also, the uncertainties calibrated by the global database are mostly larger than the uncertainties reported in the literature. The large uncertainties may be reduced by considering PI and S_t as secondary input parameters for the models. The biases are also updated after incorporating PI and S_t .

References

- Aas, G., Lacasse, S., Lunne, T., and Hoeg, K. 1986. Use of in-situ tests for foundation design on clay. In *Use of in-situ tests in geotechnical engineering (GSP6)*. Edited by S.P. Clemence. ASCE, New York, pp. 1–30.
- Bjerrum, L. 1954. Geotechnical properties of Norwegian marine clays. *Géotechnique*, 4(2): 49–69. doi:10.1680/geot.1954.4.2.49.
- Bjerrum, L. 1972. Embankments on soft ground. In *Proceedings, ASCE Specialty Conference on Performance of Earth and Earth-Supported Structures*, Purdue University, Lafayette, Ind. ASCE, Vol. 2, pp. 1–54.
- Bjerrum, L., and Simons, N.E. 1960. Comparison of shear strength characteristics of normally consolidated clays. In *Proceedings of the Research Conference on Shear Strength of Cohesive Soils*, Boulder, ASCE, pp. 711–726.
- Chen, B.S.Y., and Mayne, P.W. 1996. Statistical relationships between piezocone measurements and stress history of clays. *Canadian Geotechnical Journal*, 33(3): 488–498. doi:10.1139/t96-070.
- Chen, Y.-J., and Kulhawy, F.H. 1993. Undrained strength interrelationships among CIUC, UU, and UC tests. *Journal of Geotechnical Engineering*, 119(11): 1732–1750. doi:10.1061/(ASCE)0733-9410(1993)119:11(1732).
- Ching, J., and Phoon, K.-K. 2012a. Establishment of generic transformations for geotechnical design parameters. *Structural Safety*, 35: 52–62. doi:10.1016/j.strusafe.2011.12.003.
- Ching, J., and Phoon, K.-K. 2012b. Modeling parameters of structured clays as a multivariate normal distribution. *Canadian Geotechnical Journal*, 49(5): 522–545. doi:10.1139/t2012-015.
- Ching, J., and Phoon, K.-K. 2013. Multivariate distribution for undrained shear strengths under various test procedures. *Canadian Geotechnical Journal*, 50(9): 907–923. doi:10.1139/cgj-2013-0002.

- Ching, J., and Phoon, K.-K. 2014. Correlations among some clay parameters — the multivariate distribution. *Canadian Geotechnical Journal*, **51**. [This issue.] doi:10.1139/cgj-2013-0353.
- Ching, J., Phoon, K.-K., and Chen, C.-H. 2014. Modeling piezocone cone penetration (CPTU) parameters of clays as a multivariate normal distribution. *Canadian Geotechnical Journal*, **51**(1): 77–91. doi:10.1139/cgj-2012-0259.
- Der Kiureghian, A., and Ditlevsen, O. 2007. Epistemic or aleatory? Does it matter? In *Proceedings of the Special Workshop on Risk Acceptance and Risk Communication*, Stanford University, Calif. Available at http://www.rapid.ethz.ch/Paper/DerKiureghian_paper.pdf.
- Jamiolkowski, M., Ladd, C.C., Germain, J.T., and Lancellotta, R. 1985. New developments in field and laboratory testing of soils. In *Proceedings of the 11th International Conference on Soil Mechanics and Foundation Engineering*, San Francisco. Vol. 1, pp. 57–153.
- Kulhawy, F.H., and Mayne, P.W. 1990. Manual on estimating soil properties for foundation design. Report EL-6800 by Cornell University, prepared for Electric Power Research Institute, Palo Alto.
- Land, C.C., Foott, R., Ishihara, K., Schlosser, F., and Poulos, H.G. 1977. Stress deformation and strength characteristics. In *Proceedings of the 9th International Conference on Soil Mechanics and Foundation Engineering*, Tokyo. Vol. 2, pp. 421–494.
- Locat, J., and Demers, D. 1988. Viscosity, yield stress, remolded strength, and liquidity index relationships for sensitive clays. *Canadian Geotechnical Journal*, **25**(4): 799–806. doi:10.1139/t88-088.
- Marsland, S., and Powell, J.J.M. 1988. Investigation of cone penetration tests in British clays carried out by the Building Research Establishment 1962–1987. In *Proceedings of the Geotechnical Conference: Penetration Testing*, Birmingham, UK. Thomas Telford, London. pp. 209–214.
- Mayne, P.W., Christopher, B.R., and DeJong, J. 2001. Manual on Subsurface Investigations. National Highway Institute Publication No. FHWA NHI-01-031. Federal Highway Administration, Washington, D.C.
- Mesri, G. 1975. Discussion on “New design procedure for stability of soft clays”. *Journal of the Geotechnical Engineering Division, ASCE*, **101**(4): 409–412.
- Mesri, G. 1989. A re-evaluation of $s_{u(mob)} = 0.22 \sigma'_p$ using laboratory shear tests. *Canadian Geotechnical Journal*, **26**(1): 162164. doi:10.1139/t89-017.
- Mesri, G., and Huvaj, N. 2007. Shear strength mobilized in undrained failure of soft clay and silt deposits. In *Advances in measurement and modeling of soil behaviour (GSP 173)*. Edited by D.J. DeGroot et al. ASCE. pp. 1–22.
- Mitchell, J.K. 1993. *Fundamentals of soil behaviour*. 2nd ed. John Wiley and Sons, New York.
- NAVFAC. 1982. *Soil mechanics DM7.1*. Naval Facilities Engineering Command, Alexandria.
- Phoon, K.-K., and Kulhawy, F.H. 1999a. Characterization of geotechnical variability. *Canadian Geotechnical Journal*, **36**(4): 612–624. doi:10.1139/t99-038.
- Phoon, K.-K., and Kulhawy, F.H. 1999b. Evaluation of geotechnical property variability. *Canadian Geotechnical Journal*, **36**(4): 625–639. doi:10.1139/t99-039.
- Phoon, K.-K., and Kulhawy, F.H. 2008. Serviceability limit state reliability-based design. In *Reliability-based design in geotechnical engineering: computations and applications*. Taylor and Francis, UK. pp. 344–383.
- Powell, J.J.M., and Quarterman, R.S.T. 1988. The interpretation of cone penetration tests in clays, with particular reference to rate effects. In *Proceedings of Penetration Testing 1988*, Balkema, Rotterdam, Vol. 2, pp. 903–909.
- Robertson, P.K. 1990. Soil classification using the cone penetration test. *Canadian Geotechnical Journal*, **27**(1): 151–158. doi:10.1139/t90-014.
- Stas, C.V., and Kulhawy, F.H. 1984. Critical evaluation of design methods for foundations under axial uplift and compressive loading. Electric Power Research Institute, Palo Alto, Calif. Report EL-3771.
- Terzaghi, K., Peck, R.B., and Mesri, G. 1996. *Soil mechanics in engineering practice*, 3rd ed. John Wiley & Sons, New York.
- Wroth, C.P., and Wood, D.M. 1978. The correlation of index properties with some basic engineering properties of soils. *Canadian Geotechnical Journal*, **15**(2): 137–145. doi:10.1139/t78-014.

Appendix A. Summary of database CLAY/10/7490

Table A1. Basic information of the database CLAY/10/7490.

Reference	Country	n	PI	LI	OCR	S_t	$s_{u(mob)}/\sigma'_v$	CPTU
Aas et al. (1986)	Norway	12	—	—	1.5~10.0	—	—	—
Aas (1980)	Norway	2	—	—	—	—	0.30~0.33	—
Agarwal (1967)	UK	22	—	—	—	—	0.09~0.61	—
Akai and Adachi (1965)	Japan	6	27	0.54	—	—	—	—
Alberro and Santoyo (1973)	Mexico	85	284~363	0.71~1.19	—	—	0.03~0.68	—
Amerasinghe and Parry (1975)	UK	28	—	—	—	—	0.29~4.57	—
Anderson et al. (1982)	Brazil	16	47~102	1.09~1.63	1.6~7.4	2~5	0.31~5.44	—
Andersen et al. (1980)	Norway	11	—	—	1.0~50.0	—	0.04~7.78	—
Andresen and Bjerrum (1957)	Norway	18	12~32	0.48~0.95	—	2~5	—	—
Andersen and Stenhamar (1982)	Norway	3	—	—	1.6~40.0	—	—	—
Azzouz and Lutz (1986)	USA	33	29~69	0.18~0.47	1.0~1.4	—	0.04~0.20	Y
Azzouz et al. (1983)	Venezuela	10	42~57	0.45~0.78	1.1~3.3	—	0.14~0.20	Y
Balasubramanian and Chaudhry (1976)	Thailand	10	82	—	—	—	0.07~0.87	—
Baligh et al. (1980)	USA	20	13~72	0.23~1.48	1.1~5.4	—	0.22~1.40	Y
Banerjee and Stipho (1978)	UK	2	26	0.36~0.38	1.0~1.2	—	0.15~0.22	—
Baracos et al. (1980)	Canada	9	36~64	-0.01~0.60	2.8~9.2	—	0.09~4.43	—
Battaglio et al. (1986)	Italy	15	—	—	21.0~36.4	—	—	Y
Berre and Bjerrum (1973)	Norway	14	10~88	0.61~1.04	1.0~1.8	5~11	0.19~0.41	—
Bishop (1971)	UK	14	39	0.06~0.21	2.1~16.0	1~2	0.39~4.89	—
Bishop et al. (1965)	UK	6	36~43	-0.14~-0.04	—	—	—	—
Bjerrum (1954)	Norway	246	3~33	-0.05~4.70	—	3~500	5.40	—
Bjerrum and Simons (1960)	—	35	7~92	0.28~3.43	—	2~100	—	—
Bjerrum and Lo (1963)	Norway	68	22~32	0.60~0.81	—	5	0.22~45.02	—
Bjerrum (1967)	Norway	89	4~41	0.61~3.22	—	2~300	0.05~0.25	—
Bjerrum (1969)	Norway	14	13~27	1.46~2.12	—	—	—	—
Bjerrum (1972)	—	6	11~85	0.3~1.1	—	—	—	—
Bjerrum (1973)	Norway	6	3~31	0.75~5.3	—	8~100	0.16~0.30	—
Bozozuk and Leonards (1972)	Canada	19	20~34	1.18~2.49	1.3~2.0	8~100	0.13~0.55	—
Broms and Ratnam (1963)	Norway	3	—	—	3.5~13.0	—	—	—
Burland et al. (1977)	UK	14	19~46	-0.19~-0.01	—	—	0.59~2.43	—
Cadling and Odenstad (1950)	Sweden	136	22~88	0.77~1.24	—	2~167	0.06~0.29	—
Calabresi and Manfredini (1973)	Italy	1	33	0.24	—	—	—	—
Campanella et al. (1988)	Canada	20	—	—	1.0~4.5	12~25	—	Y
Cancelli (1981)	Italy	13	20~39	0.03~0.26	—	—	0.14~1.79	—
Cancelli and Cividini (1984)	Italy	5	31~39	0.04~0.44	1.0~26.7	—	0.23~4.00	Y
Carrier and Beckman (1984)	USA	14	110~165	0.5~1.43	—	—	—	—

Table A1 (continued).

Reference	Country	n	PI	LI	OCR	S_t	$s_u(\text{mob})/\sigma'_v$	CPTU
Carter and Bentley (1991)	UK	24	—	-0.11~1.90	—	1~141	—	—
Chandler (1969)	UK	1	10	-0.75	—	—	—	—
Chandler (1988)	—	22	4~100	0.47~4	1~6.3	2~80	0.15~0.36	—
Chang (1991)	Singapore	13	18~87	0.33~0.95	0.8~1.9	3.1	0.10~0.62	Y
	Malaysia	11	33~79	0.51~1.77	1.3~3.5	3.6~5.0	0.26~0.63	Y
Chen and Hsieh (1996)	Taiwan	23	11~24	0.64~1.36	1.1~1.5	4~5	—	Y
Chen (2001)	Taiwan	12	—	—	—	—	—	—
Chen and Kulhawy (1993)	—	195	9~85	-0.44~2.40	1.0~39.0	3~128	0.03~2.48	—
Chin and Liu (1997)	Taiwan	12	—	—	1.0~4.1	—	0.18~0.90	—
Chin et al. (1989)	Taiwan	32	8~26	—	1.0~8.0	—	—	—
Clough and Denby (1980)	China	29	35~52	0.51~1.95	—	—	0.09~0.23	—
Colling and Skempton (1942)	UK	113	36~67	-0.03~0.06	—	—	—	—
Coutinho (2007)	Brazil	12	27~168	0.50~2.23	0.9~2.2	5~14	0.24~0.91	Y
Cox et al. (1979)	USA	51	10~69	0.05~0.80	—	—	—	—
Crawford (1959)	Canada	3	14~27	0.53~1.21	—	3~6	—	—
Crawford (1964)	Canada	9	—	—	—	—	—	—
Crawford and Campanella (1991)	Canada	8	—	—	1.4~3.8	20~122	—	Y
Crawford and Eden (1965)	Canada	10	14~36	0.9~2.5	1.5~7.9	10~500	0.31~2.63	—
Croce et al. (1969)	Italy	14	23~47	-0.11~0.55	1.5~4.7	1~8	0.07~1.30	—
Crooks (1981)	Northern Ireland	15	—	—	1.4~2.8	—	0.31~0.71	—
Crooks and Graham (1976)	Canada	22	22~63	0.61~1.37	0.9~1.7	4~10	—	—
Cummings et al. (1950)	USA	10	4~18	0.20~0.97	—	—	—	—
D'Appolonia et al. (1971)	USA	1	17	0.7	9.3	—	0.77	—
D'Appolonia and Saada (1972)	Norway	104	—	—	1.0~37.5	—	—	—
Da Cruz (1963)	Brazil	15	—	—	0.6~3.4	—	—	—
Dascal and Tournier (1975)	Canada	11	9~12	1.11~3.89	1.4~35.8	—	0.28~0.85	—
Degroot and Lutenegeger (2003)	USA	64	11~30	0.04~2.87	1.4~9.5	6~43	0.17~1.25	—
De Lory and Salvas (1967)	Canada	40	19~59	0.84~1.31	—	—	0.13~1.84	—
De Lory and Salvas (1969)	Canada	33	17~46	0.50~1.94	—	—	0.13~0.32	—
DiBiagio and Stenhamar (1976)	Norway	6	5~11	1.68~3.71	—	18~74	—	—
Donaghe and Townsend (1978)	USA	28	—	—	—	—	0.02~1.05	—
Duncan and Seed (1966)	USA	10	—	—	3.0~18.0	—	0.33~1.35	—
Eden and Bozozuk (1962)	Canada	9	15~40	1.32~2.12	1.2~1.9	8~18	0.31~0.38	—
Eden and Crawford (1957)	Canada	36	5~56	0.81~4.13	1.6~4.4	36~1467	0.49~1.46	—
Eden and Hamilton (1957)	Canada	49	5~56	0.63~4.4	1.0~3.5	4~1160	0.26~2.64	—
Eden and Kubota (1961)	Canada	113	—	0.66~3.10	—	1~307	—	—
Eden and Law (1980)	Canada	5	28~46	—	2.0~3.0	—	0.53~1.03	Y
Eden and Poorooshasb (1968)	Canada	12	18~26	0.57~2.90	—	—	—	—
Egashira and Ohtsubo (1982)	Japan	14	8~96	0.48~3.63	—	19~970	—	—
Eide and Holmberg (1972)	Thailand	9	83~108	0.76~0.93	1.6~2.2	6~10	0.33~0.47	—
Endley et al. (1979)	USA	24	13~56	-0.10~0.69	—	—	—	—
Esu and Calabresi (1969)	Italy	3	44~51	0.1~0.16	—	—	—	—
Feyling-Hanssen (1957)	Norway	10	8~26	-0.20~0.88	—	—	—	—
Finno (1989)	USA	17	15~21	0.20~2.59	0.8~4.2	2~3	—	Y
Flaate and Preber (1974)	Norway	18	6~33	0.09~0.48	—	—	0.06~0.91	—
Focht and Drash (1991)	Mexico	108	8~41	-0.52~3.95	—	—	0.07~27.75	—
Gregersen (1979)	Norway	19	6~13	0.56~2.67	—	13	—	—
Gregersen and Løken (1979)	Norway	37	—	0.14~2.46	—	2~185	—	—
Hansen and Clough (1980)	—	8	10~105	0.65~1.04	—	5~11	—	—
Hanzawa (1977a)	Iraq	11	34~36	0.62~0.73	—	—	0.83~2.35	—
Hanzawa (1977b)	Iraq	31	11~31	0.65~1.10	1.0	—	0.09~0.37	—
Hanzawa (1979)	Japan	60	—	—	—	—	—	—
Hanzawa et al. (1979)	Iraq	12	35~38	0.63~0.66	1.3~5.7	—	0.32~0.92	—
Hanzawa (1981)	Japan	3	—	—	—	—	0.20~0.23	—
Hara et al. (1974)	Japan	182	10~92	—	1.0~3.0	—	—	—
Harris et al. (1995)	France	67	—	0.33~1.66	—	—	—	—
Helenelund (1977)	Sweden	36	22~94	—	—	—	0.15~0.31	—
Henkel and Sowa (1963)	England	59	—	—	—	—	—	—
Henry and Henry (1957)	Hong Kong	22	—	—	—	—	—	—
Hight et al. (1992)	UK	9	24~44	—	1.3~1.6	—	0.38~0.64	Y
Holmberg (1977)	Thailand	52	57~105	0.63~1.16	1.4~2.5	5~15	0.20~4.72	—
Holtz and Baker (1972)	USA	22	10~16	-0.45~0.45	—	—	—	—
Holtz and Holm (1979)	Sweden	13	74~114	0.66~0.99	1.3~3.0	—	—	—
Hong et al. (2010)	Korea	17	—	—	—	—	0.17~0.27	Y
Horn and Lambe (1964)	USA	12	14~31	0.37~0.81	0.8~4.0	4~10	0.07~0.50	—
Hutchinson (1969)	UK	2	31~51	-0.16~0.02	—	—	—	—

Table A1 (continued).

Reference	Country	<i>n</i>	PI	LI	OCR	<i>S_t</i>	<i>s_u(mob)/σ'_v</i>	CPTU
Jamiolkowski et al. (1988)	Italy	17	—	—	7.9~20.7	—	—	—
Janbu et al. (1977)	Norway	7	3~11	-0.25~0.71	—	3~14	—	—
Jardine et al. (2003)	UK	13	41~95	0.44~0.98	—	1~11	—	—
Karlsrud and Myrvoll (1976)	Norway	25	20~27	0.60~3.60	—	—	0.17~0.64	—
Karlsson and Pusch (1967)	Sweden	11	24~42	0.34~2.75	—	14~307	0.23~1.37	—
Kenney (1966)	Norway	40	10~36	0.52~2.86	—	3~60	0.02~2.71	—
Kinner and Ladd (1970)	USA	62	—	—	1.0~24	—	0.05~2.07	—
Kitago et al. (1976)	Japan	4	—	—	—	—	—	—
Kjekstad and Lunne (1981)	Norway	29	19~34	-0.15~0.28	—	—	0.26~1.64	—
Konrad and Law (1987a)	Canada	29	3~37	0.50~4.51	1.0~4.9	7~35	0.34~1.66	Y
Konrad and Law (1987b)	Canada	17	—	—	1.0~2.6	—	—	Y
Koumoto (1990)	Japan	58	43~298	0.16~1.24	—	—	—	—
Koumoto and Houlsby (2001)	Japan	74	14~293	0.00~1.45	—	—	—	—
Koutsoftas and Fischer (1976)	USA	95	13~50	0.28~1.14	1.0~29.5	108~414	0.19~2.55	—
Koutsoftas (1978)	USA	21	13~41	0.66~1.17	1.0~4.0	—	—	—
Koutsoftas (1981)	USA	19	—	—	1.0~11.7	—	0.20~1.72	—
Koutsoftas and Ladd (1985)	USA	20	—	—	1.0~7.7	—	0.23~1.16	—
Koutsoftas et al. (1987)	Hong Kong	13	12~66	0.19~1.82	1.9~3.8	5.5	0.33~1.13	Y
Kulhawy and Mayne (1990)	—	159	9~80	-0.44~2.4	1.0	—	0.14~0.27	—
Kulkarani et al. (1967)	India	5	39~65	0.57~1.00	0.7~1.0	3~4	0.12~0.23	—
Lacasse et al. (1977)	Canada	20	—	—	1.0~2.9	—	—	—
	USA	7	—	—	1.0~4.8	—	—	—
Lacasse et al. (1981)	Norway	11	—	—	1.1~2.7	—	0.19~0.45	—
Lacasse et al. (1985)	Norway	17	4~43	0.94~5.50	1.4~7.1	—	0.24~0.65	—
Ladd (1964)	USA	22	—	—	5.7~6.2	—	0.09~2.07	—
Ladd (1965)	USA	8	—	—	—	—	0.21~0.67	—
Ladd (1967)	USA	16	—	—	—	—	—	—
Ladd (1972)	USA	43	8~29	0.60~2.52	1.3~7.8	—	0.23~1.84	—
Ladd (1973)	USA	12	—	—	—	—	—	—
Ladd (1981)	USA	7	20~55	—	—	—	0.11~0.22	—
Ladd (1991)	USA	100	5~85	1.08~2.32	1.0~16.4	4~8	0.07~0.81	—
Ladd et al. (1971)	USA	6	45	1.04	1.0~8.1	8	0.20~0.94	—
Ladd et al. (1972)	USA	14	7~23	0.78~2.52	1.3~2.8	7~10	0.20~1.50	—
Ladd et al. (1977)	—	10	—	—	3.0~18.2	—	—	—
Ladd and Azzouz (1983)	Venezuela	75	12~57	-0.67~0.67	1.0~2.7	—	0.16~0.57	—
Ladd and Edgers (1971)	USA	108	7~88	—	1.0~12.1	5~100	0~1.60	—
Ladd and Foott (1974)	USA	22	10~39	0.57~2.68	1.0~4.9	—	0.17~4.37	—
Ladd and Lambe (1963)	—	39	8~80	—	1.0~3.0	5~10	0.07~0.61	—
Laflleur et al. (1988)	Canada	10	33~47	1.21~1.72	1.1~6.1	14	0.26~1.42	Y
Lacasse and Lunne (1982)	Norway	109	16~72	0.28~1.87	1.0~13.5	3~7	0.05~1.95	Y
Lambe (1964)	Venezuela	10	—	—	—	—	0.06~0.24	—
La Rochelle et al. (1974)	Canada	23	8~35	1.14~3.25	2.0~5.2	—	0.52~0.98	—
La Rochelle et al. (1988)	Canada	3	15~44	1.39~1.69	1.1~3.5	—	0.24~0.53	Y
Larsson (1980)	Norway	4	7~53	—	—	—	0.19~0.25	—
Larsson and Mulabdic (1991)	Sweden	50	29~86	0.84~1.49	1.1~4.2	—	0.20~0.67	Y
Landva et al. (1988)	Canada	26	6~21	0.74~2.63	2.2~4.0	—	—	—
Leathers and Ladd (1978)	USA	7	32~46	0.66~1.00	1.1~9.9	—	0.28~0.94	—
Lefebvre and LeBoeuf (1987)	Canada	26	—	—	—	—	0.19~0.25	—
Lembo-Fazio et al. (1984)	Italy	1	28	-0.25	—	—	—	—
Leon and Alberro (1977)	Mexico	7	—	—	—	—	—	—
Leroueil et al. (1983)	Canada	10	20~43	1.11~2.87	1.4~2.6	—	0.37~0.76	—
Lew (1981)	Canada	6	—	—	—	—	0.04~0.15	—
Liu (1999)	Taiwan	53	6~26	—	—	—	0.18~0.37	—
Lo and Stermac (1963)	Canada	13	49~55	—	—	—	—	—
Locat and Demers (1988)	Canada	49	11~37	0.59~2.44	—	8~82	—	—
Long and Menkiti (2007)	UK	2	—	—	—	—	—	—
Lowe and Karafiath (1960)	Venezuela	11	—	—	—	—	0.42~2.22	—
Lumb and Holt (1968)	Hong Kong	25	57~117	0.70~1.11	—	—	0.15~1.81	—
Lunne et al. (1981)	UK	91	10~40	-0.71~1.08	1.7~55.6	—	—	—
Lunne et al. (1985)	Norway	39	15~29	0.08~0.37	—	—	0.13~1.87	Y
	Norway	188	10~36	-0.12~1.42	1.3~6.8	—	0.06~2.02	—
Lunne et al. (1986)	Norway	9	13~39	0.66~0.86	1.2~15.5	—	0.34~1.75	Y
Mahar and O'Neill (1983)	USA	4	6~29	0.19~0.72	3.7~5.0	—	0.65~2.85	Y
Massarch et al. (1975)	Sweden	41	22~128	0.50~2.77	0.9~2.7	8~36	0.14~0.74	—
Massarch and Broms (1976)	Sweden	17	35~62	0.51~1.53	1.1~2.7	11~36	0.25~0.73	—
Mayne (1980)	USA	7	—	—	1.0~21.1	—	—	—

Table A1 (continued).

Reference	Country	n	PI	LI	OCR	S _t	s _u (mob)/σ' _v	CPTU
Mayne (1985a)	USA	64	—	—	1.0~75.0	—	0.24~0.33	—
Mayne (1985b)	—	87	2~105	—	1.0	—	0.12~0.54	—
Mayne (1988)	—	419	—	—	0.9~60.2	—	0.12~7.20	—
Mayne (1989)	USA	13	—	—	2.3~9.3	—	—	Y
Mayne (1991)	USA	19	—	—	1.7~3.5	—	—	Y
Mayne (2008)	—	43	—	—	1.3~4.3	—	—	Y
Mayne and Holtz (1985)	USA	66	—	—	—	—	0.16~0.54	—
Mitchell et al. (1972)	Canada	12	6~61	0.63~6.45	—	6~310	—	—
Mitachi and Kitago (1976)	Japan	21	—	—	—	—	—	—
Mitchell (1956)	USA	4	—	—	1.0~7.7	—	—	—
Mishtak (1964)	Canada	1	74	0.44	—	—	—	—
Moh et al. (1969)	Thailand	9	37~59	0.08~0.84	1.2~24.0	2~5	0.74~4.78	—
Morin et al. (1983)	Canada	57	10~43	0.67~2.22	1.1~54.2	—	0.28~6.75	—
Moum and Rosenqvist (1961)	USA	12	27~261	0.18~0.97	—	3~9	0.13~0.46	—
Nakase and Kamei (1983)	Japan	40	11~29	—	—	—	0.24~0.67	—
Nakase and Kamei (1986)	Japan	18	—	—	—	—	0.22~0.45	—
Nakase and Kamei (1988)	Japan	12	11~56	—	—	—	0.26~0.30	—
Newland and Allely (1957)	New Zealand	16	—	0.04~1.21	—	—	—	—
Ng and Lo (1985)	Canada	30	19~51	—	1.2~2.0	4~9	0.17~0.44	—
Niazi et al. (2010)	UK	9	—	—	2.9~11.5	—	0.62~1.95	Y
Ohtsubo et al. (1982)	Japan	19	—	0.39~3.41	—	13~759	0.52~4.15	—
Ohtsubo et al. (1995)	Japan	18	41~102	1.06~2.62	0.8~2.5	11~34	—	—
Ohtsubo et al. (2007)	Japan	9	16~96	0.89~1.55	0.8~5.1	4~1000	0.27~0.67	—
Olsen et al. (1986)	USA	73	11~33	0.65~2.70	1.0	—	0.15~1.44	—
O'Riordan et al. (1982)	UK	14	9~96	—	—	—	—	—
Ou and Hsiao (1994)	Taiwan	37	—	0.73~2.22	1.0~5.9	—	0.22~0.45	—
Parry (1960)	England	14	—	—	1.0~24.5	—	0.31~1.22	—
Parry (1968)	Australia	68	93~106	—	—	2	0.02~1.33	—
Parry and Nadarajah (1974)	UK	17	—	0.74~1.21	—	—	0.35~0.46	—
Parry and Wroth (1981)	Canada	8	14~23	—	1.1~3.9	10~115	0.05~0.74	—
Phoon (2013)	Singapore	12	13~52	0.86~2.83	1.2~26.2	—	0.16~4.39	Y
Powell and Quarterman (1988)	UK	42	24~57	0.10~1.17	1.4~3	—	0.21~4.14	Y
Prevost and Hoeg (1977)	Norway	11	29~85	0.57~1.02	1~4	—	0.42~0.99	—
Prevost (1979)	—	3	18~85	—	—	—	0.26~0.63	—
Quiros and Young (1988)	USA	8	—	—	1.0~6.2	—	0.19~0.65	—
Rad and Lunne (1988)	—	79	4~87	—	1.2~12	—	0.04~1.37	Y
Ramalho-Ortigao et al. (1983)	Brazil	35	48~92	0.17~5.75	—	1~6	—	—
Raymond (1973)	Canada	11	8~49	1.22~1.64	1.0~2.5	2~11	—	—
Raymond et al. (1971)	Canada	31	20~57	0.10~0.98	—	5~22	0.20~0.35	—
Rocha-Filho and Alencar (1985)	Brazil	8	44~63	0.66~2.60	1.6~2.1	2~8	—	Y
Roy et al. (1982)	Canada	19	10~37	0.03~2.08	2.3~6.1	—	0.28~1.12	—
Sanchez et al. (1979)	UK	10	—	—	1.0~2.0	—	0.13~0.38	—
Schofield and Wroth (1968)	UK	36	11~145	—	—	—	0.08~0.99	—
Schwab and Broms (1976)	Sweden	34	86~103	0.68~1.03	—	—	—	—
Seed and Reese (1957)	USA	26	—	—	—	—	—	—
Senneset and Janbu (1985)	Norway	13	4~10	0.40~2.69	—	—	0.08~0.63	Y
Senneset et al. (1988)	Norway	18	—	—	1.0~2.4	—	—	Y
Sherif et al. (1972)	USA	46	—	—	1.0~32.0	—	—	—
Silvestri and Aubertin (1988)	Canada	9	39~48	0.64~1.41	2.9~7.2	6~24	0.71~1.41	—
Simons (1960)	Norway	12	12~20	—	—	3~20	0.05~0.13	—
Simons (1976)	UK	7	11~85	—	—	—	0.18~0.47	—
Skempton (1948a)	UK	17	39~77	0.26~1.04	0.8~1.4	1~4	—	—
Skempton (1948b)	UK	17	18~34	0.42~0.90	—	2~3	0.46~55.61	—
Skempton (1950)	South Africa	8	61~83	0.31~0.44	2.1~2.3	4~5	—	—
Skempton (1957)	Hong Kong	28	9~59	-0.11~0.77	—	—	0.29~2.53	—
Skempton (1961)	UK	23	57~70	-0.11~0.06	1.4~44.0	—	0.43~1.34	—
Skempton and Bishop (1954)	—	14	13~75	-0.16~0.76	1.0	1~8	0.10~0.21	—
Skempton and Henkel (1953)	UK	26	15~118	0.13~0.87	0.9~2.8	2~7	0.20~2.30	—
Skempton and Northey (1953)	—	23	13~61	0.48~1.3	—	1~19	—	—
Skempton and Sowa (1963)	UK	51	—	—	—	—	0.09~0.97	—
Strachan (1960)	New Zealand	4	8~14	-0.08~0.33	1.2~1.4	—	—	—
Stille and Fredriksson (1979)	Sweden	15	15~33	1.02~1.54	—	4~22	0.15~0.26	—
Tan et al. (2003)	Singapore	43	20~73	0.27~0.68	—	—	0.08~0.16	—
Tanaka and Sakagami (1989)	Japan	7	66~79	0.25~0.53	0.5~0.8	—	—	Y
Tanaka et al. (2003)	Japan	14	36~45	0.63~1.52	—	—	0.52~2.57	—
Tani and Craig (1995)	Japan	5	—	—	—	—	—	—

Table A1 (concluded).

Reference	Country	<i>n</i>	PI	LI	OCR	<i>S_t</i>	<i>s_u(mob)/σ'_v</i>	CPTU
Tavenas et al. (1975)	Canada	15	10~37	1.43~4.14	1.8~2.2	—	0.62~1.10	—
Tavenas et al. (1978)	Canada	20	25~52	0.62~1.30	—	—	—	—
Tavenas and Leroueil (1977)	Canada	7	—	—	—	—	0.16~3.17	—
Tschuschke and Waliński (2005)	Poland	8	19~29	0.66~1.67	—	—	—	Y
Tschuschke (2010)	Poland	16	—	—	—	—	—	Y
Tsuchida et al. (1999)	Japan	44	22	0.49~4.08	—	—	—	—
Tumay and Acar (1985)	USA	7	32~80	0.24~0.74	1.1~1.8	—	—	—
Vaid et al. (1979)	Canada	1	16	1.38	—	100	—	—
Ward et al. (1959)	UK	7	40~52	-0.03~-0.19	—	—	—	—
Wei and Pant (2010)	USA	14	31~68	0.27~0.61	—	—	0.05~7.22	Y
Windle and Wroth (1977)	UK	8	—	—	—	—	—	—
Wroth and Houlsby (1985)	USA	15	12~41	0.59~1.31	1.0~5.6	—	0.19~0.90	—
Wu (1958)	USA	70	7~32	0.13~1.25	0.8~3.0	2~50	0.10~0.84	—
Wu et al. (1962)	USA	16	—	—	—	2~8	0.13~0.16	—
Wu et al. (1963)	USA	23	—	—	—	—	0.20~0.38	—
Wu et al. (1975)	USA	17	—	—	1.3~15.4	—	0.26~1.06	—
Wu et al. (1978)	USA	12	—	—	1.0~3.3	—	0.18~0.55	—
Yasuhara et al. (1982)	Japan	9	—	—	—	—	0.13~0.44	—
Zreik et al. (1995)	USA	12	20	0.48~5.63	—	—	—	—

References

- Aas, G. 1980. Evaluation of slope stability. Norwegian Geotechnical Institute Pub, 132, pp. 21–30.
- Aas, G., Lacasse, S., Lunne, T., and Hoeg, K. 1986. Use of in-situ tests for foundation design on clay. In *Use of in-situ tests in geotechnical engineering (GSP6)*. Edited by S.P. Clemence. ASCE, New York, pp. 1–30.
- Agarwal, K.B. 1967. The influence of size and orientation of sample on the undrained strength of London clay. Ph.D. thesis, University of London.
- Akai, K., and Adachi, T. 1965. Study on the one-dimensional consolidation and the shear strength characteristics of fully saturated clay, in terms of effective stress. In *Proceedings 6th International Conference on Soil Mechanics and Foundation Engineering*, Vol. 1, pp. 146–150.
- Alberro, J., and Santoyo, E. 1973. Long term behaviour of Mexico City clay. In *Proceedings of the 8th International Conference on Soil Mechanics and Foundation Engineering*, Moscow, Vol. 1, pp. 1–9.
- Amerasinghe, S.F., and Parry, R.H.G. 1975. Anisotropy in heavily overconsolidated kaolin. *Journal of the Geotechnical Engineering Division, ASCE*, 101(12): 1277–1293.
- Andersen, K.H., and Stenhamar, P. 1982. Static plate loading tests on overconsolidated clay. *Journal of the Geotechnical Engineering Division, ASCE*, 108(7): 918–934. doi:10.1016/0148-9062(83)91655-8.
- Andersen, K.H., Pool, J.H., Brown, S.F., and Rosenbrand, W.F. 1980. Cyclic and static laboratory tests on Drammen clay. *Journal of the Geotechnical Engineering Division, ASCE*, 106: 499–529. doi:10.1016/0148-9062(81)90316-8.
- Anderson, T.C., Koutsoftas, D.C., Ramalho-Ortigao, J.A., and Costa-Filho, L.M. 1982. Discussion to Cam-clay predictions of undrained strength. *Journal of the Geotechnical Engineering Division, ASCE*, 108(1): 176–183.
- Andresen, A., and Bjerrum, L. 1957. Discussion contributions from Scandinavia. *Vane Testing in Norway*. ASTM STP 193, 54–60.
- Azzouz, A.S., and Lutz, D.G. 1986. Shaft behavior of a model pile in plastic Empire clays. *Journal of Geotechnical Engineering, ASCE*, 112(4): 389–406. doi:10.1061/(ASCE)0733-9410(1986)112:4(389).
- Azzouz, A., Baligh, M., and Ladd, C.C. 1983. Cone penetration and engineering properties of soft Orinoco clay. In *Proceedings of the 3rd International Conference on the Behaviour of Offshore Structures*, Massachusetts Institute of Technology, Cambridge, Vol. 1, pp. 161–180.
- Balasubramanian, A.S., and Chaudhry, A.R. 1976. Stress-strain behaviour of soft Bangkok clay. In *Proceedings of the 2th International Conference on Numerical Methods in Geomechanics*, Blacksburg, Va. Vol. 1, pp. 390–401.
- Baligh, M.M., Vivatrat, V., and Ladd, C.C. 1980. Cone penetration in soil profiling. *Journal of the Geotechnical Engineering Division, ASCE*, 106(4): 447–461.
- Banerjee, P.K., and Stipho, A.S. 1978. Associated and non-associated constitutive relations for undrained behaviour of isotropic soft clays. *International Journal for Numerical and Analytical Methods in Geomechanics*, 2: 35–56. doi: 10.1002/nag.1610020104.
- Baracos, A., Graham, J., and Domaschuk, L. 1980. Yielding and rupture in a Lacustrine clay. *Canadian Geotechnical Journal*, 17(4): 559–573. doi:10.1139/t80-063.
- Battaglio, M., Bruzzi, D., Jamiolkowski, M., and Lancellotta, R. 1986. Interpretation of CPT's and CPTU's. In *Proceedings of the 4th International Geotechnical Seminar Field Instrumentation and In-Situ Measurements*, pp. 25–27.
- Berre, T., and Bjerrum, L. 1973. Shear strength of normally consolidated clays. In *Proceedings of the 8th International Conference on Soil Mechanics and Foundation Engineering*, Moscow, Vol. 1, pp. 39–49.
- Bishop, A.W. 1971. Shear strength parameters for undisturbed and remoulded soils specimens. In *Stress-Strain Behaviour of Soils: Proceedings of the Roscoe Memorial Symposium*. Foulis and Company, pp. 3–139.
- Bishop, A.W., Webb, D.L., and Lewin, P.I. 1965. Undisturbed samples of London clay from the Ashford Common shaft: strength-effective stress relationships. *Géotechnique*, 15(1): 1–31. doi:10.1680/geot.1965.15.1.1.
- Bjerrum, L. 1954. Geotechnical properties of Norwegian marine clays. *Géotechnique*, 4(2): 49–69. doi:10.1680/geot.1954.4.2.49.
- Bjerrum, L. 1967. Engineering geology of Norwegian normally-consolidated marine clays as related to the settlement of buildings. *Géotechnique*, 17(2): 81–118. doi:10.1680/geot.1967.17.2.83.
- Bjerrum, L. 1969. Discussion of main session 5: stability of natural slopes and embankment foundations. In *Proceedings of the 7th International Conference on Soil Mechanics and Foundation Engineering*, Mexico City, Vol. 3, pp. 377–414.
- Bjerrum, L. 1972. Embankments on soft ground. In *Proceedings of the ASCE Specialty Conference on Performance of Earth and Earth-Supported Structures*, Purdue University, Lafayette, Ind. ASCE, Vol. 2, pp. 1–54.
- Bjerrum, L. 1973. Problems of soil mechanics and construction on soft clays and structurally unstable soils (collapsible, expansive and others). In *Proceedings of the 8th International Conference on Soil Mechanics and Foundation Engineering*, Moscow, Vol. 3, pp. 111–159.
- Bjerrum, L., and Lo, K.Y. 1963. Effect of aging on the shear-strength properties of a normally consolidated clay. *Géotechnique*, 13: 147–157.
- Bjerrum, L., and Simons, N.E. 1960. Comparison of shear strength characteristics of normally consolidated clays. In *Proceedings of Research Conference on Shear Strength of Cohesive Soils*, Boulder, Colo. ASCE, pp. 711–726.
- Bozozuk, M., and Leonards, G.A. 1972. The Gloucester test fill. In *Proceedings of the ASCE Specialty Conference on Performance of Earth and Earth-Supported Structures*, Vol. 1, Part 1, pp. 299–317.
- Broms, B.B., and Ratnam, A.M. 1963. Shear strength of an anisotropically consolidated clay. *Journal of the Soil Mechanics and Foundations Division, ASCE*, 89(6): 1–26.
- Burland, J.B., Longworth, T.I., and Moore, J.F.A. 1977. A study of ground movement and progressive failure caused by a deep excavation in Oxford clay. *Géotechnique*, 27(4): 557–591. doi:10.1680/geot.1977.27.4.557.
- Cadling, L., and Odenstad, S. 1950. The vane borer. In *Proceedings of the Royal Swedish Geotechnical Institute*, Stockholm, Vol. 2.
- Calabresi, G., and Manfredini, G. 1973. Shear strength characteristics of jointed clay of S. Barbara. *Géotechnique*, 23(2): 233–244. doi:10.1680/geot.1973.23.2.233.
- Campanella, R.G., Sully, J.P., and Robertson, P.K. 1988. Interpretation of piezocone soundings in clay - a case history. In *Penetration Testing in the UK*. Thomas Telford, London, pp. 203–208.
- Cancelli, A. 1981. Evaluation of slopes in overconsolidated clays. In *Proceedings of the 10th ICSMFE*, Vol. 3, pp. 377–380.
- Cancelli, A., and Cividini, A. 1984. An embankment on soft clays with sand drains: numerical characterization of the parameters from in-situ measurements. In *Proceedings of the International Conference on Case Histories in Geotechnical Engineering*, pp. 637–643.
- Carrier, W.D., and Beckman, J.F. 1984. Correlations between index tests and the properties of remoulded clays. *Géotechnique*, 34(2): 211–228. doi:10.1680/geot.1984.34.2.211.

- Carter, M., and Bentley, S.P. 1991. Correlations of soil properties. Pentech Press, London.
- Chandler, R.J. 1969. The effect of weathering on the shear strength properties of Keuper Marl. *Géotechnique*, **19**(3): 321–334. doi:10.1680/geot.1969.19.3.321.
- Chandler, R.J. 1988. The in-situ measurement of the undrained shear strength of clays using the field vane. In *Vane shear strength testing in soils: field and laboratory studies*. STP 1014. ASTM, Philadelphia. pp. 13–44.
- Chang, M.F. 1991. Interpretation of overconsolidation ratio from *in situ* tests in recent clay deposits in Singapore and Malaysia. *Canadian Geotechnical Journal*, **28**(2): 210–225. doi:10.1139/t91-028.
- Chen, D.S. 2001. Design and construction of highrise building foundations (IV) - fault and geotechnical investigation for the 101-story Taipei international financial center site. *Sino-Geotechnics*, **84**: 29–48. [In Chinese.]
- Chen, H.M., and Hsieh, B.J. 1996. Geotechnical properties of the clay deposits from in-situ test on Keelung River reclaimed land. *Sino-Geotechnics*, **54**: 55–66. [In Chinese.]
- Chen, Y.-J., and Kulhawy, F.H. 1993. Undrained strength interrelationships among CIUC, UU, and UC tests. *Journal of Geotechnical Engineering*, **119**(11): 1732–1750. doi:10.1061/(ASCE)0733-9410(1993)119:11(1732).
- Chin, C.T., and Liu, C.C. 1997. Volumetric and undrained behaviours of Taipei silty clay. *Journal of the Chinese Institute of Civil and Hydraulic Engineering*, **9**(4): 665–678. [In Chinese.]
- Chin, C.T., Cheng, T.Y., and Liu, C.C. 1989. Relationship between undrained shear strength and overconsolidation ratio of Taipei silt. *Journal of the Chinese Institute of Civil and Hydraulic Engineering*, **1**(3): 245–250. [In Chinese.]
- Clough, G.W., and Denby, G.M. 1980. Self-boring pressuremeter study of San Francisco Bay mud. *Journal of the Geotechnical Engineering Division, ASCE*, **106**: 45–63.
- Colling, L.F., and Skempton, A.W. 1942. A laboratory study of London clay. *Journal of the Institution of Civil Engineers*, **17**(3): 251–276. doi:10.1680/jjoti.1942.13754.
- Coutinho, R.Q. 2007. Characterization and engineering properties of Recife soft clays - Brazil. In *Characterisation and Engineering Properties of Natural Soil: Proceedings of the International Workshop*, Singapore. pp. 2049–2099.
- Cox, W.R., Kraft, L.M., and Vermer, E.A. 1979. Axial load tests on 14-inch pipe piles in clay. In *Proceedings of the 11th Offshore Technology Conference*, Houston. Vol. 2, pp. 1147–1158.
- Crawford, C.B. 1959. The influence of rate of strain on effective stresses in sensitive clay. In *STP 254. ASTM International*. pp. 36–61. doi:10.1520/STP443045.
- Crawford, C.B. 1964. Some characteristics of Winnipeg clay. *Canadian Geotechnical Journal*, **1**(4): 227–235. doi:10.1139/t64-018.
- Crawford, C.B., and Campanella, R.G. 1991. Comparison of field consolidation with laboratory and *in situ* tests. *Canadian Geotechnical Journal*, **28**(1): 103–112. doi:10.1139/t91-011.
- Crawford, C.B., and Eden, W.J. 1965. A comparison of laboratory results with in-situ properties of Leda clay. In *Proceedings of the 6th International Conference on Soil Mechanics and Foundation Engineering*. Vol. 1, pp. 31–35.
- Croce, A., Japelli, R., Pellegrino, A., and Viggiani, C. 1969. Compressibility and strength of stiff intact clays. In *Proceedings of the 7th International Conference on Soil Mechanics and Foundation Engineering*. Vol. 1, pp. 81–89.
- Crooks, J.H.A. 1981. A qualitative stress-strain (time) model for soft clays. In *Laboratory shear strength of soil*. STP 740. ASTM. pp. 685–699.
- Crooks, J.H.A., and Graham, J. 1976. Geotechnical properties of the Belfast estuarine deposits. *Géotechnique*, **26**(2): 293–315. doi:10.1680/geot.1976.26.2.293.
- Cummings, A.E.K., Kerkhoff, G.O., and Peck, R.B. 1950. Effect of driving piles into soft clay. *Transactions of the American Society of Civil Engineers, ASCE*, **115**: 275–285.
- Da Cruz, P.T. 1963. Shear strength characteristics of some residual compacted clays. In *Proceedings of the 2nd Panamerican Conference on Soil Mechanics and Foundation Engineering*. Vol. 1, pp. 73–102.
- D'Appolonia, D.J., and Saada, A.S. 1972. Bearing capacity of anisotropic cohesive soil. *Journal of the Soil Mechanics and Foundation Division, ASCE*, **98**(1): 126–135.
- D'Appolonia, D.J., Lambe, T.W., and Poulos, H.G. 1971. Evaluation of pore pressures beneath an embankment. *Journal of the Soil Mechanics and Foundations Division, ASCE*, **97**(6): 881–897.
- Dascal, O., and Tournier, J.P. 1975. Embankments on soft and sensitive clay foundations. *Journal of the Geotechnical Engineering Division, ASCE*, **101**(3): 297–314.
- De Lory, F.A., and Salvat, R.J. 1967. An investigation of discrepancies in undrained shear strength test results in clay. Ontario Joint Highway Research Programme. Reports University of Toronto. Vol. 45, pp. 1–64.
- De Lory, F.A., and Salvat, R.J. 1969. Some observations on the undrained shearing strength used to analyze a failure. *Canadian Geotechnical Journal*, **6**(2): 97–110. doi:10.1139/t69-010.
- Degroot, D.J., and Lutenecker, A.J. 2003. Geology and engineering properties of Connecticut Valley varved clay. In *Characterisation and engineering properties of natural soils*. Vol. 1, pp. 695–724.
- DiBiagio, E., and Stenhamar, P. 1976. Test fill to failure on soft clay. In *Publication 110. Norwegian Geotechnical Institute*. pp. 9–14.
- Donaghe, R.T., and Townsend, F.C. 1978. Effects of anisotropic versus isotropic consolidation in consolidated-undrained triaxial compression tests of cohesive soils. *Geotechnical Testing Journal*, **1**(4): 173–189. doi:10.1520/GTJ10868J.
- Duncan, J.M., and Seed, H.B. 1966. Anisotropy and stress reorientation in clay. *Journal of the Soil Mechanics and Foundations Division, ASCE*, **92**(5): 21–50.
- Eden, W.J., and Bozozuk, M. 1962. Foundation failure of a silo on varved clay. *The Engineering Journal*, **45**(9): 54–57.
- Eden, W.J., and Crawford, C.B. 1957. Geotechnical properties of Leda clay in the Ottawa area. In *Proceedings of the 4th International Conference on Soil Mechanics and Foundation Engineering*, London. Vol. 1, pp. 22–27.
- Eden, W.J., and Hamilton, J.J. 1957. The use of a field vane apparatus in sensitive clay. In *Proceedings of the Symposium on In-Place Shear Testing of Soil by The Vane Method*. STP 193. ASTM. pp. 41–53.
- Eden, W.J., and Kubota, J.K. 1961. Some observations on the measurement of sensitivity of clays. In *Proceedings of the ASTM*. Vol. 61, pp. 1239–1249.
- Eden, W.J., and Law, K.T. 1980. Comparison of undrained shear strength results obtained by different test methods in soft clays. *Canadian Geotechnical Journal*, **17**(3): 369–381. doi:10.1139/t80-044.
- Eden, W.J., and Poorooshasb, H. 1968. Settlement observations at Kars Bridge. *Canadian Geotechnical Journal*, **5**(1): 28–45. doi:10.1139/t68-003.
- Egashira, K., and Ohtsubo, M. 1982. Smectite in marine quick-clays of Japan. *Clays and Clay Minerals*, **30**(4): 275–280. doi:10.1346/CCMN.1982.0300404.
- Eide, O., and Holmberg, S. 1972. Test fills to failure on the soft Bangkok clay. In *Proceedings of the ASCE Conference on the Performance of Earth and Earth Supported Structures*, Vol. 1. Part 1, pp. 158–180.
- Endley, S.N., Ulrich, E.J.J., and Gray, J.B. 1979. A study of axial pile load tests. In *Proceedings of the Symposium on Deep Foundations*. pp. 101–121.
- Esu, F., and Calabresi, G. 1969. Slope stability in an overconsolidated clay. In *Proceedings of the 7th ICSMFE*. Vol. 2, pp. 555–563.
- Feyling-Hanssen, R.W. 1957. Micropaleontology applied to soil mechanics in Norway. I kommisjon hos Aschehoug, Oslo. Norges geologiske undersøkelse, nr. 197.
- Finno, R.J. 1989. Subsurface conditions and pile installation data: 1989 foundation engineering congress test section. In *Predicted and observed axial behaviour of piles: results of a pile prediction symposium*. Geotechnical Special Publication 23. ASCE, New York. pp. 1–14.
- Flaate, K., and Preber, T. 1974. Stability of road embankments in soft clay. *Canadian Geotechnical Journal*, **11**(1): 72–88. doi:10.1139/t74-006.
- Focht, J.A., and Drash, C.J. 1991. Behaviour of drilled piers in layered soils on Texas Barrier Islands. In *Drilled piers and caissons II. Edited by Clyde N. Baker*. American Society of Civil Engineers (ASCE), Geotechnical Engineering Division. pp. 76–98.
- Gregersen, O. 1979. Kvikkleireskredet i Rissa. (The quick clay slide in Rissa.) *Nordiska geoteknikermøtet. Helsinki, Foredrag och artiklar*. pp. 535–548. [Also published in Norwegian Geotechnical Institute, Oslo, Publication 132, pp. 31–42.]
- Gregersen, O., and Løken, T. 1979. The quick-clay slide at Baastad, Norway, 1974. *Engineering Geology*, **14**: 183–196. doi:10.1016/0013-7952(79)90084-X.
- Hansen, L.A., and Clough, G.W. 1980. Characterization of undrained anisotropy of clays. In *Proceedings, Symposium on Limit Equilibrium, Plasticity, and Generalized Stress Strain Applications in Geotechnical Engineering*. Edited by R.N. Yong and E.T. Selig. ASCE, New York. pp. 253–276.
- Hanzawa, H. 1977a. Field and laboratory behaviour of Khor Al-Zubair clay, Iraq. *Soils and Foundations*, **17**(4): 17–30. doi:10.3208/sandf1972.17.4.17.
- Hanzawa, H. 1977b. Geotechnical properties of normally consolidated Fao clay, Iraq. *Soils and Foundations*, **17**(5): 1–15. doi:10.3208/sandf1972.17.4.1.
- Hanzawa, H. 1979. Undrained strength characteristics of an alluvial marine clay in the Tokyo Bay. *Soils and Foundations*, **19**(4): 69–84. doi:10.3208/sandf1972.19.4.69.
- Hanzawa, H. 1981. Improvement of a quick sand. In *Proceedings of the 10th International Conference on Soil Mechanics and Foundation Engineering*, Stockholm. Vol. 3, pp. 683–686.
- Hanzawa, H., Matsuno, T., and Tsuji, K. 1979. Undrained strength and stability analysis of soft Iraqi clays. *Soils and Foundations*, **19**(2): 1–14. doi:10.3208/sandf1972.19.2.1.
- Hara, A., Ohta, T., Niwa, M., Tanaka, S., and Banno, T. 1974. Shear modulus and shear strength of cohesive soils. *Soils and Foundations*, **14**(3): 1–12. doi:10.3208/sandf1972.14.3.1.
- Harris, C., Davies, M.C.R., and Coutard, J.P. 1995. Laboratory simulation of periglacial solifluction: significance of porewater pressures, moisture contents and undrained shear strengths during soil thawing. *Permafrost and Periglacial Processes*, **6**: 293–311. doi:10.1002/ppp.3430060403.
- Helenelund, K.V. 1977. Methods for reducing undrained shear strength of soft clay. In *Report (3). Swedish Geotechnical Institute*. pp. 1–59.
- Henkel, D.J., and Sowa, V.A. 1963. The influence of stress history on stress paths in undrained triaxial tests on clay. In *Laboratory shear testing of soils*. STP 361. ASTM International. pp. 280–294.
- Henry, G.S.M., and Henry, J.K.M. 1957. The planning and design of new Hong Kong airport. In *Proceedings of the Airport Engineering Division Meeting*. pp. 275–305.
- Hight, D.W., Bond, A.J., and Legge, J.D. 1992. Characterization of the Bothken-naar clay: an overview. *Géotechnique*, **42**(2): 303–347. doi:10.1680/geot.1992.42.2.303.
- Holmberg, S. 1977. Some engineering properties of soft Bangkok clay. *Geotechnical Engineering*, **8**(1): 1–19.

- Holtz, R.D., and Baker, C.N., Jr. 1972. Some load transfer data on caissons in hard Chicago clay. In *Proceedings of the ASCE Specialty Conference on Performance of Earth and Earth-Supported Structures*, West Lafayette, Ind. Vol. I, Part 2, pp. 1223-1242.
- Holtz, R.D., and Holm, B.G. 1979. Test embankment on an organic silty clay. In *Proceedings of the Seventh ECSMFE*, Brighton. Vol. 3, pp. 79-86.
- Hong, S.J., Lee, M.J., Kim, J.J., and Lee, W.J. 2010. Evaluation of undrained shear strength of Busan clay using CPT. In *Proceedings of the 2nd International Symposium on Cone Penetration Testing*, CPT'10. [Online.] Available at <http://www.cpt10.com/cpt10pdfpapers.html>.
- Horn, H.M., and Lambe, T.W. 1964. Settlement of buildings on the MIT campus. In *Design of foundations for control of settlement*. ASCE. pp. 215-229.
- Hutchinson, J.N. 1969. A reconsideration of the coastal landslides at Folkestone Warren, Kent. *Géotechnique*, 19(1): 6-38. doi:10.1680/geot.1969.19.1.6.
- Jamiolkowski, M., Ghionna, V.N., Lancellotta, R., and Pasqualini, E. 1988. New correlations of penetration tests for design practice. In *Proceedings of the First International Symposium on Penetration Testing*, ISOPT-1. pp. 263-296.
- Janbu, N., Kjekstad, O., and Senneset, K. 1977. Slide in overconsolidated clay below embankment. In *Proceedings of the 9th International Conference on Soil Mechanics and Foundation Engineering*. Vol. 2, pp. 95-102.
- Jardine, R.J., Smith, P.R., and Micholson, D.P. 2003. Properties of the soft holocene thames estuary clay from Queenborough, Kent. In *Characterisation and engineering properties of natural soils*. Vol. 1, pp. 599-643.
- Karlsrud, K., and Myrvioll, F. 1976. Performance of a strutted excavation in quick-clay. In *Proceedings of the 6th European Conference on Soil Mechanics and Foundation Engineering*, Vienna. Vol. 1, pp. 157-164.
- Karlsson, R., and Pusch, R. 1967. Shear strength parameters and microstructure characteristics of a quick clay of extremely high water content. In *Proceedings of the Geotechnical Conference*, Norwegian Geotechnical Institute. Vol. 1, pp. 35-42.
- Kenney, T.C. 1966. Shear resistance of natural quick clays. PhD. thesis, University of London.
- Kinner, E.B., and Ladd, C.C. 1970. Load-deformation behaviour of saturated clays during undrained shear. Research in Earth Physics Phase Report. Massachusetts Institute of Technology, Department of Civil and Environmental Engineering. Research Report R70-27, 13.
- Kitago, S., Mitachi, T., and Kamiya, M. 1976. Strength properties of saturated clay in undrained triaxial extension. In *Proceedings of the 11th Annual Meeting of JSSMFE*. pp. 239-242. [In Japanese.]
- Kjekstad, O., and Lunne, T. 1981. Soil parameters used for design of gravity platforms in the North Sea. *Applied Ocean Research*, 3(2): 50-58. doi:10.1016/0141-1187(81)90001-8.
- Konrad, J.-M., and Law, K.T. 1987a. Undrained shear strength from piezocone tests. *Canadian Geotechnical Journal*, 24(3): 392-405. doi:10.1139/t87-050.
- Konrad, J.-M., and Law, K.T. 1987b. Preconsolidation pressure from piezocone tests in marine clays. *Géotechnique*, 37(2): 177-190. doi:10.1680/geot.1987.37.2.177.
- Koumoto, T. 1990. Determination of both liquid and plastic limits of clays by the fall cone test. *Transactions of the Japanese Society of Irrigation, Drainage and Reclamation Engineering*, 146: 95-100.
- Koumoto, T., and Houlsby, G.T. 2001. Theory and practice of the fall cone test. *Géotechnique*, 51(8): 701-712. doi:10.1680/geot.2001.51.8.701.
- Koutsoftas, D.C. 1978. Effect of cyclic loads on undrained strength of two marine clays. *Journal of the Geotechnical Engineering Division, ASCE*, 104(5): 609-620.
- Koutsoftas, D.C. 1981. Undrained shear behaviour of a Marine clay. In *Proceedings of the Symposium on Laboratory Shear Strength of Soil*. STP740. ASTM International. pp. 254-276.
- Koutsoftas, D.C., and Fischer, J.A. 1976. In-situ undrained shear strength of two marine clays. *Journal of the Geotechnical Engineering Division, ASCE*, 102(9): 989-1005.
- Koutsoftas, D.C., and Ladd, C.C. 1985. Design strengths for an offshore clay. *Journal of Geotechnical Engineering*, 111(3): 337-355. doi:10.1061/(ASCE)0733-9410(1985)111:3(337).
- Koutsoftas, D.C., Fottt, R., and Handfelt, L.D. 1987. Geotechnical investigations offshore Hong Kong. *Journal of Geotechnical Engineering*, 113(2): 87-105. doi:10.1061/(ASCE)0733-9410(1987)113:2(87).
- Kulhawy, F.H., and Mayne, P.W. 1990. Manual on estimating soil properties for foundation design. Report EL-6800 prepared by Cornell University for Electric Power Research Institute, Palo Alto, Calif.
- Kulkarni, K.R., Katti, A.P., and Patel, A.N. 1967. A study of the properties of Bombay marine clay deposits in relation to certain foundation problems. In *Proceedings of the 3th Asian Regional Conference on Soil Mechanics and Foundation Engineering*. Jerusalem Academic Press, Haifa, Israel. Vol. 1, pp. 210-214.
- La Rochelle, P., Trak, F., Tavenas, F., and Roy, M. 1974. Failure of a test embankment on a sensitive Champlain clay deposit. *Canadian Geotechnical Journal*, 11(1): 142-164. doi:10.1139/t74-009.
- La Rochelle, P., Zebdi, M., Leroueil, S., Tavenas, F., and Virely, D. 1988. Piezocone tests in sensitive clays of eastern Canada. In *Proceedings of the 1st International Symposium on Penetration Testing*, Orlando. Vol. 2, pp. 831-841.
- Lacasse, M.S., Ladd, C.C., and Barsvary, A.K. 1977. Undrained behavior of embankments on New Liskeard varved clay. *Canadian Geotechnical Journal*, 14(3): 367-388. doi:10.1139/t77-041.
- Lacasse, S., and Lunne, T. 1982. Penetration tests in two Norwegian clays. In *Proceedings of the 2nd European Symposium on Penetration Testing*, Amsterdam. pp. 661-669.
- Lacasse, S., Jamiolkowski, M., Lancellotta, R., and Lunne, T. 1981. In situ characteristics of two Norwegian clays. In *Proceedings of the 10th International Conference on Soil Mechanics and Foundation Engineering*. Vol. 2, pp. 507-511.
- Lacasse, S., Berre, T., and Lefebvre, G. 1985. Block sampling of sensitive clays. In *Proceedings of the 11th International Conference on Soil Mechanics and Foundation Engineering*. Vol. 2, pp. 887-892.
- Ladd, C.C. 1964. Stress-strain modulus of clay in undrained shear. *Journal of the Soil Mechanics and Foundation Division, ASCE*, 90(5): 103-132.
- Ladd, C.C. 1965. Stress-strain behaviour of anisotropically consolidated clays during undrained shear. In *Proceedings of the 6th International Conference on Soil Mechanics and Foundation Engineering*, Montréal. Vol. 1, pp. 282-286.
- Ladd, C.C. 1967. Discussion on shear strength of soft clay. In *Proceedings of the Geotechnical Conference*, Oslo. Vol. 2, pp. 112-115.
- Ladd, C.C. 1972. Test embankment on sensitive clay. In *Proceedings of the ASCE Specialty Conference on Performance of Earth and Earth-Supported Structures*, Purdue University. Vol. 1, Part 1, pp. 101-128.
- Ladd, C.C. 1973. Problems of soil mechanics and construction on soft clays and structurally unstable soils (collapsible, expansive and others). In *Proceedings of the 8th International Conference on Soil Mechanics and Foundation Engineering*. Vol. 4, pp. 108-115.
- Ladd, C.C. 1981. Discussion on laboratory shear devices. In *Laboratory shear strength of soil*. ASTM STP 740. pp. 643-652.
- Ladd, C.C. 1991. Stability evaluation during staged construction. *Journal of Geotechnical Engineering*, 117(4): 540-615. doi:10.1061/(ASCE)0733-9410(1991)117:4(540).
- Ladd, C.C., and Azzouz, A.S. 1983. Stress history and strength of stiff offshore clays. In *Proceedings of the Conference on Geotechnical Practice in Offshore Engineering*. ASCE. pp. 65-80.
- Ladd, C.C., and Edgers, L. 1971. Consolidated-undrained direct-simple shear tests on saturated clays. Research in Earth Physics Phase Report No. 16.
- Ladd, C.C., and Fottt, R. 1974. New design procedure for stability in soft clays. *Journal of the Geotechnical Engineering Division, ASCE*, 100(7): 763-786.
- Ladd, C.C., and Lambe, T.W. 1963. The strength of "undisturbed" clay determined from undrained tests. In *Proceedings of the Symposium on Laboratory Shear Testing of Soils*. STP 361. ASTM. pp. 342-371.
- Ladd, C.C., Bovee, R.B., Edger, L., and Rixner, J.J. 1971. Consolidated-undrained plane strain shear tests on Boston Blue Clay. Dept. of Civil Engineering, Massachusetts Institute of Technology, Cambridge. Res. Report R71-13, No. 273.
- Ladd, C.C., Rixner, J.J., and Gifford, D.G. 1972. Performance of embankments with sand drains on sensitive clay. In *Proceedings of the ASCE Specialty Conference on Performance of Earth and Earth-Supported Structures*, Purdue University, Lafayette, Ind. Vol. 1, Part 1, 211-242.
- Ladd, C.C., Fottt, R., Schlosser, F., and Poulos, H.G. 1977. Stress deformation and strength characteristics. In *Proceedings of the 9th International Conference on Soil Mechanics and Foundation Engineering*, Tokyo. Vol. 2, pp. 421-494.
- Lafleur, J., Silvestri, V., Asselin, R., and Soulié, M. 1988. Behaviour of a test excavation in soft Champlain Sea clay. *Canadian Geotechnical Journal*, 25(4): 705-715. doi:10.1139/t88-081.
- Lambe, T.W. 1964. Methods of estimating settlement. *Journal of the Soil Mechanics and Foundations Division, ASCE*, 90(5): 43-67.
- Landva, A.O., Valsangkar, A.J., Alkins, J.C., and Charalambous, P.D. 1988. Performance of a raft foundation supporting a multistorey structure. *Canadian Geotechnical Journal*, 25(1): 138-149. doi:10.1139/t88-014.
- Larsson, R. 1980. Undrained shear strength in stability calculation of embankments and foundations on soft clays. *Canadian Geotechnical Journal*, 17(4): 591-602. doi:10.1139/t80-066.
- Larsson, R., and Mulabdic, M. 1991. Piezocone tests in clay. Swedish Geotechnical Institute, Linköping, Sweden. Report No.42.
- Leathers, F.D., and Ladd, C.C. 1978. Behavior of an embankment on New York varved clay. *Canadian Geotechnical Journal*, 15(2): 250-268. doi:10.1139/t78-023.
- Lefebvre, G., and LeBoeuf, D. 1987. Rate effects and cyclic loading of sensitive clays. *Journal of Geotechnical Engineering*, 113(5): 476-489. doi:10.1061/(ASCE)0733-9410(1987)113:5(476).
- Lembo-Fazio, A., Manfredini, G., Ribacchi, R., and Sciotti, M. 1984. Slope failure and cliff instability in the Orvieto hill. In *Proceedings of the 4th International Symposium on Landslides*. University of Toronto Press, Toronto, Ont. Vol. 2, pp. 115-120.
- Leon, J.L., and Alberro, J. 1977. Extension and compression tests on Mexico City clay. In *Proceedings of the 9th International Conference on Soil Mechanics and Foundation Engineering*, Tokyo. Vol. 1, pp. 193-196.
- Leroueil, S., Samson, L., and Bozozuk, M. 1983. Laboratory and field determination of preconsolidation pressures at Gloucester. *Canadian Geotechnical Journal*, 20(3): 477-490. doi:10.1139/t83-056.
- Lew, K.V. 1981. Yielding criteria and limit state in a Winnipeg clay. M.Sc. thesis, University of Manitoba.
- Liu, Q.C. 1999. The effective stress model of Taipei clay. Ph.D. thesis, National Taiwan University of Science and Technology.

- Lo, K.Y., and Stermac, A.G. 1963. Some case records of embankment failure. Materials and Research Division, Department of Highways Ontario. Technical Report No. 34, pp. 1–26.
- Locat, J., and Demers, D. 1988. Viscosity, yield stress, remolded strength, and liquidity index relationships for sensitive clays. *Canadian Geotechnical Journal*, **25**(9): 799–806. doi:10.1139/t88-088.
- Long, M., and Menkiti, C.O. 2007. Characterisation and engineering properties of Dublin boulder clay. In *Characterisation and engineering properties of natural soils*. Vol. 3, pp. 2003–2045.
- Lowe, J., and Karafiath, L. 1960. Effect of anisotropic consolidation on the undrained shear strength of compacted clays. In *Proceedings of the Research Conference on Shear Strength of Cohesive Soils*, pp. 837–858.
- Lumb, P., and Holt, J.K. 1968. The undrained shear strength of a soft marine clay from Hong Kong. *Géotechnique*, **18**(1): 25–36. doi:10.1680/geot.1968.18.1.25.
- Lunne, T., Myrvooll, F., and Kjekstad, O. 1981. Observed settlements of five North Sea gravity platforms. In *Proceedings of the 13th Offshore Technology Conference*. OTC 4146. Vol. 4, pp. 305–317.
- Lunne, T., Christoffersen, H.P., and Tjelta, T.I. 1985. Engineering use of piezocone data in North Sea clays. In *Proceedings of the 11th International Conference on Soil Mechanics and Foundation Engineering*, San Francisco. Vol. 2, pp. 907–912.
- Lunne, T., Eidsmoen, T., Gillespie, D., and Howland, J.D. 1986. Laboratory and field evaluation of cone penetrometers. In *Cone penetrometers evaluation*, pp. 714–729.
- Mahar, L.J., and O'Neill, M.W. 1983. Geotechnical characterization of desiccated clay. *Journal of Geotechnical Engineering*, **109**(1): 56–71. doi:10.1061/(ASCE)0733-9410(1983)109:1(56).
- Massarch, K.R., and Broms, B.B. 1976. Lateral earth pressure at rest in soft clay. *Journal of the Geotechnical Engineering Division, ASCE*, **2**: 1041–1047.
- Massarch, K.R., Holtz, R.D., Holm, B.G., and Fredriksson, A. 1975. Measurements of horizontal in-situ stress. In *Proceedings of the Conference on Design of Foundation for Control of Settlement*. ASCE. Vol. 1, pp. 266–286.
- Mayne, P.W. 1980. Cam clay predictions of undrained strength. *Journal of the Geotechnical Engineering Division, ASCE*, **106**(11): 1219–1242.
- Mayne, P.W. 1985a. Stress anisotropy effects on clay strength. *Journal of Geotechnical Engineering*, **111**(3): 356–366. doi:10.1061/(ASCE)0733-9410(1985)111:3(356).
- Mayne, P.W. 1985b. A review of undrained strength in direct simple shear. *Soils and Foundations*, **25**(3): 64–72. doi:10.3208/sandf1972.25.3.64.
- Mayne, P.W. 1988. Determining OCR in clays from laboratory strength. *Journal of Geotechnical Engineering*, **114**(1): 76–92. doi:10.1061/(ASCE)0733-9410(1988)114:1(76).
- Mayne, P.W. 1989. Site characterization of Yorktown formation for new accelerator. In *Foundation engineering: Current principles and practices*. GSP 22. Edited by F.H. Kulhawy. ASCE. pp. 1–15.
- Mayne, P.W. 1991. Determination of OCR in clays by piezocone tests using cavity expansion and critical state concepts. *Soils and Foundations*, **31**(2): 65–76. doi:10.3208/sandf1972.31.2.65.
- Mayne, P.W. 2008. Piezocone profiling of clays for maritime site investigations. In *Proceedings of the 11th Baltic Sea Geotechnical Conference, Geotechnics in Maritime Engineering*, Poland.
- Mayne, P.W., and Holtz, R.D. 1985. Effect of principal stress rotation on clay strength. In *Proceedings of the 11th International Conference on Soil Mechanics and Foundation Engineering*. Vol. 2, pp. 579–582.
- Mishtak, J. 1964. Soil mechanics aspects of the red river floodway. *Canadian Geotechnical Journal*, **1**(3): 133–146. doi:10.1139/t64-008.
- Mitachi, T., and Kitago, S. 1976. Change in undrained shear strength characteristics of saturated remolded clay due to swelling. *Soils and Foundations*, **16**(1): 45–58. doi:10.3208/sandf1972.16.45.
- Mitchell, J.K. 1956. The fabric of natural clays and its relation to engineering properties. *Proceedings of the Highway Research Board*, **35**: 693–713.
- Mitchell, R.J., Sangrey, D.A., and Webb, G.S. 1972. Foundation in the crust of sensitive clay deposit. In *Proceedings of the ASCE Specialty Conference on Performance of Earth and Earth Supported Structures*, Vol. 1, Part 2, pp. 1051–1072.
- Moh, Z.C., Nelson, J.D., and Brand, E.W. 1969. The strength and deformation behaviour of Bangkok clay. In *Proceedings of the 7th International Conference on Soil Mechanics and Foundation Engineering*. Vol. 102, Part 10, pp. 287–295.
- Morin, P., Leroueil, S., and Samson, L. 1983. Preconsolidation pressure of Champlain clays. Part I. In-situ determination. *Canadian Geotechnical Journal*, **20**(4): 782–802. doi:10.1139/t83-083.
- Moum, J., and Rosenqvist, I.Th. 1961. The mechanical properties of Montmorillonitic and Illitic clays related to the electrolytes of the pore water. In *Proceedings of the 5th International Conference on Soil Mechanics and Foundation Engineering*. Vol. 1, pp. 263–267.
- Nakase, A., and Kamei, T. 1983. In situ shear strength of soft organic soils. *Soils and Foundations*, **23**(1): 91–101.
- Nakase, A., and Kamei, T. 1986. Influence of strain rate on undrained shear characteristics of K_0 -consolidated cohesive soils. *Soils and Foundations*, **26**(1): 85–95. doi:10.3208/sandf1972.26.85.
- Nakase, A., and Kamei, T. 1988. Undrained shear strength of remoulded marine clays. *Soils and Foundations*, **28**(1): 29–40. doi:10.3208/sandf1972.28.29.
- Newland, P.L., and Allely, B.H. 1957. A study of the sensitivity resulting from consolidation of a remoulded clay. In *Proceedings of the 4th International Conference on Soil Mechanics and Foundation Engineering*. Vol. 1, pp. 83–86.
- Ng, R.M.C., and Lo, K.Y. 1985. The measurements of soil parameters relevant to tunnelling in clays. *Canadian Geotechnical Journal*, **22**(3): 375–391. doi:10.1139/t85-049.
- Niazi, F.S., Mayne, P.W., and Woeller, D.J. 2010. Case history of axial pile capacity and load-settlement response by SCPTu. In *Proceedings of the 2nd International Symposium on Cone Penetration Testing*, Huntington Beach, Calif.
- Ohtsubo, M., Takayama, M., and Egashira, K. 1982. Marine quick clays from Ariake Bay area, Japan. *Soils and Foundations*, **22**(4): 71–80. doi:10.3208/sandf1972.22.4.71.
- Ohtsubo, M., Egashira, K., and Kashima, K. 1995. Depositional and post-depositional geochemistry, and its correlation with the geotechnical properties of marine clays in Ariake Bay, Japan. *Géotechnique*, **45**: 509–523. doi:10.1680/geot.1995.45.3.509.
- Ohtsubo, M., Higashi, T., Kanayama, M., and Takayama, M. 2007. Depositional geochemistry and geotechnical properties of marine clays in the Ariake Bay area, Japan. *Characterization and Engineering Properties of Natural Soils*, **3**: 1893–1937.
- Olsen, H.W., Rice, T.L., Mayne, P.W., and Singh, R.D. 1986. Piston core properties and disturbance effects. *Journal of Geotechnical Engineering*, **112**(6): 608–625. doi:10.1061/(ASCE)0733-9410(1986)112:6(608).
- O'Riordan, N.J., Davies, J.A., and Dauncey, P.C. 1982. The interpretation of static cone penetrometer tests in soft clays of low plasticity. In *Proceedings of the 2nd European Symposium on Penetration Testing*, pp. 755–760.
- Ou, C.Y., and Hsiao, W.T. 1994. The properties of shear strength and consolidation of Taipei silty clay with plane strain condition. *Journal of the Chinese Institute of Civil and Hydraulic Engineering*, **6**(4): 383–388. [In Chinese.]
- Parry, R.H.G. 1960. Triaxial compression and extension tests on remoulded saturated clay. *Géotechnique*, **10**(4): 166–180. doi:10.1680/geot.1960.10.4.166.
- Parry, R.H.G. 1968. Field and laboratory behaviour of a lightly overconsolidated clay. *Géotechnique*, **18**(2): 151–171. doi:10.1680/geot.1968.18.2.151.
- Parry, R.H.G., and Nadarajah, V. 1974. Observations on laboratory prepared, lightly overconsolidated specimens of kaolin. *Géotechnique*, **24**(3): 345–357. doi:10.1680/geot.1974.24.3.345.
- Parry, R.H.G., and Wroth, C.P. 1981. Shear stress-strain properties of soft clay. In *Soft clay engineering*. Elsevier. pp. 311–364.
- Phoon, K.K. 2013. Personal communication.
- Powell, J.J.M., and Quarterman, R.S.T. 1988. The interpretation of cone penetration tests in clays, with particular reference to rate effects. In *Proceedings of the Conference on Penetration Testing 1988*. Balkema, Rotterdam. Vol. 2, pp. 903–909.
- Prevost, J.H. 1979. Undrained shear tests on clays. *Journal of the Geotechnical Engineering Division, ASCE*, **105**(1): 49–64.
- Prevost, J.H., and Hoeg, K. 1977. Plasticity model for undrained stress-strain behaviour. *Norwegian Geotechnical Institute, Norway*. Vol. 1, pp. 255–261.
- Quiros, G.W., and Young, A.G. 1988. Comparison of field vane, CPT, and laboratory strength data at Santa Barbara Channel site. In *Vane shear strength testing in soils: field and laboratory studies*. STP 1014. ASTM International. pp. 306–317.
- Rad, N.S., and Lunne, T. 1988. Direct correlations between piezocone test results and undrained shear strength of clay. In *Proceedings of the 1st International Symposium on Penetration Testing*, Orlando. Vol. 2, pp. 911–917.
- Ramallo-Ortigão, J.A., Werneck, L.G., and Lacerda, W.A. 1983. Embankment failure on clay near Rio De Janeiro. *Journal of Geotechnical Engineering*, **109**(11): 1460–1479. doi:10.1061/(ASCE)0733-9410(1983)109:11(1460).
- Raymond, G.P. 1973. Foundation failure of New Liskeard embankment. *Highway Research Board Bulletin*, **463**: 1–17.
- Raymond, G.P., Townsend, D.L., and Lojkasek, M.J. 1971. The effect of sampling on the undrained soil properties of a Leda soil. *Canadian Geotechnical Journal*, **8**(4): 546–557. doi:10.1139/t71-056.
- Rocha-Filho, P., and Alencar, J.A. 1985. Piezocone tests in the Rio De Janeiro soft clay deposit. In *Proceedings of the 11th International Conference on Soil Mechanics and Foundation Engineering*, San Francisco. Vol. 2, pp. 859–862.
- Roy, M., Tremblay, M., Tavenas, F., and La Rochelle, P. 1982. Development of a quasi-static piezocone apparatus. *Canadian Geotechnical Journal*, **19**(2): 180–188. doi:10.1139/t82-020.
- Sanchez, J.M., Sagaseta, C., and Ballester, F. 1979. Influence of stress history on undrained behaviour of soft clays. In *Proceedings of the 7th European Conference on Soil Mechanics and Foundation Engineering*. Vol. 1, pp. 257–261.
- Schofield, A.N., and Wroth, C.P. 1968. *Critical state soil mechanics*. McGraw-Hill, London, UK.
- Schwab, E.F., and Broms, B.B. 1976. Bottom heave in soft soils. In *Proceedings of the 6th European Conference on Soil Mechanics and Foundation Engineering*, Wien. pp. 647–650.
- Seed, H.B., and Reese, L.C. 1957. The action of soft clay along friction piles. *Transactions of the American Society of Civil Engineers*, **122**(1): 731–754.
- Senneset, K., and Janbu, N. 1985. Shear strength parameters obtained from static cone penetration tests. In *Proceedings of the ASCE Symposium*, Philadelphia, pp. 41–54.

- Senneset, K., Sandven, R., Lunne, T., By, T., and Amundsen, T. 1988. Piezocone tests in silty soils. In *Proceedings of Penetration Testing, ISOPT-1*, Vol. 2, pp. 955–966.
- Sherif, M.A., Wu, M.J., and Bostrom, R.C. 1972. Reduction in soil strength due to dynamic loading. In *Proceedings of the Microzonation Conference*. National Science Foundation and ASCE. Vol. 2, pp. 439–454.
- Silvestri, V., and Aubertin, M. 1988. Anisotropy and in-situ vane tests. In *Vane shear strength testing in soils*. STP 1014. ASTM Philadelphia. pp. 88–103.
- Simons, N.E. 1960. Comprehensive investigations of the shear strength of an undisturbed Drammen clay. In *Proceedings of the Research Conference on Shear Strength of Cohesive Soils*, Colo. pp. 727–745.
- Simons, N.E. 1976. Field studies of the stability of embankments on clay foundations. In *Proceedings of the Laurits Bjerrum Memorial Lecture*. Norwegian Geotechnical Institute. pp. 183–209.
- Skempton, A.W. 1948a. The geotechnical properties of a deep stratum of post-glacial clay at Gosport. In *Proceedings of the 2nd International Conference on Soil Mechanics and Foundation Engineering*. Vol. 1, pp. 145–150.
- Skempton, A.W. 1948b. Vane tests in the alluvial plain of the river forth near Grangemouth. *Géotechnique*, 1: 111–124. doi:10.1680/geot.1948.1.2.111.
- Skempton, A.W. 1950. Discussion on “Effect of driving piles into soft clay”. *Transactions of the American Society of Civil Engineers, ASCE*, 115: 304–309.
- Skempton, A.W. 1957. Discussion on planning and design of new Hong Kong airport. *Proceedings, Institution of Civil Engineers*, 7: 305–307.
- Skempton, A.W. 1961. Horizontal stresses in an overconsolidated Eocene clay. In *Proceedings of the 5th International Conference on Soil Mechanics and Foundation Engineering*. Vol. 1, pp. 351–357.
- Skempton, A.W., and Bishop, A.W. 1954. Building materials: their elasticity and inelasticity. Edited by M. Reiner. North Holland Publishing Co., Amsterdam. pp. 417–482.
- Skempton, A.W., and Henkel, D.J. 1953. The post-glacial clays of the Thames Estuary at Tilbury and Shellhaven. In *Proceedings of the 3rd International Conference on Soil Mechanics and Foundation Engineering*. Vol. 1, pp. 302–308.
- Skempton, A.W., and Northey, R.D. 1953. The sensitivity of clays. *Géotechnique*, 3(3): 30–53. doi:10.1680/geot.1952.3.1.30.
- Skempton, A.W., and Sowa, V.A. 1963. The behaviour of saturated clays during sampling and testing. *Géotechnique*, 13: 269–290. doi:10.1680/geot.1963.13.4.269.
- Stille, H., and Fredriksson, A. 1979. Field measurements of an anchored sheet pile wall in clay. In *Proceedings of the 7th European Conference on Soil Mechanics and Foundation Engineering*. Vol. 3, pp. 285–290.
- Strachan, C.M. 1960. Preconsolidation of foundation soils, Wellington, NZ. In *Proceedings of the 3rd Australia-New Zealand Conference on Soil Mechanics and Foundation Engineering*, Sydney. pp. 135–139.
- Tan, T.S., Phoon, K.K., Lee, F.H., Tanaka, H., Locat, J., and Chong, P.T. 2003. A characterisation study of Singapore Lower Marine clay. In *Characterisation and engineering properties of natural soils*. Vol. 1, pp. 428–464.
- Tanaka, H., Ritoh, F., and Omukai, N. 2003. Geotechnical properties of clay deposits of the Osaka Basin. In *Characterisation and engineering properties of natural soils*. Vol. 1, pp. 455–474.
- Tanaka, Y., and Sakagami, T. 1989. Piezocone testing in underconsolidated clay. *Canadian Geotechnical Journal*, 26: 563–567. doi:10.1139/t89-069.
- Tani, K., and Craig, W.H. 1995. Development of centrifuge cone penetration test to evaluate the undrained shear strength profile of a model clay bed. *Soils and Foundations*, 35(2): 37–47. doi:10.3208/sandf1972.35.2.37.
- Tavenas, F., and Leroueil, S. 1977. The effect of stresses and time on yielding of clays. In *Proceedings of the 9th International Conference on Soil Mechanics and Foundation Engineering*. Vol. 1, pp. 319–326.
- Tavenas, F.A., Blanchette, G., Leroueil, S., Roy, M., and Rochelle, P.L. 1975. Difficulties in the in-situ determination of K_0 in soft sensitive clays. In *Proceedings of the Conference on In situ Measurement of Soil Properties*. Vol. 1, pp. 450–476.
- Tavenas, F., Blanchet, R., Garneau, R., and Leroueil, S. 1978. The stability of stage-constructed embankments on soft clays. *Canadian Geotechnical Journal*, 15(2): 283–305. doi:10.1139/t78-025.
- Tschuschke, W. 2010. Assessment of strength parameters of copper ore post-flotation deposit based on CPTU. In *Proceedings of the 2nd International Symposium on Cone Penetration Testing, ISSMGE*. pp. 3–36.
- Tschuschke, W., and Waliński, M. 2005. CPTU in soft post-flotation sediments. *Studia Geotechnical et Mechanica*, XXVII(3–4): 121–132.
- Tsuchida, T., Hong, Z., Wataba, Y., and Ogawa, F. 1999. Relationship of undrained shear strength versus normalized water content for remoulded clay soils. In *Proceedings of the 34th JSGE*. Vol. 1, pp. 543–544.
- Tumay, M.T., and Acar, Y.B. 1985. Piezocone penetration testing in soft cohesive soil. In *Strength testing of marine sediments: laboratory and in-situ measurements*. STP 883. ASTM, Philadelphia. pp. 72–82.
- Vaid, Y.P., Robertson, P.K., and Campanella, R.G. 1979. Strain rate behaviour of Saint-Jean-Vianney clay. *Canadian Geotechnical Journal*, 16(1): 34–42. doi:10.1139/t79-004.
- Ward, W.H., Samuels, S.G., and Butler, M.E. 1959. Further studies of the properties of London clay. *Géotechnique*, 9(2): 33–58. doi:10.1680/geot.1959.9.2.33.
- Wei, L., and Pant, R. 2010. Evaluation of undrained shear strength of soft New Orleans clay using piezocone. In *Proceedings of the 2nd International Symposium on Cone Penetration Testing, ISSMGE*. pp. 2–12.
- Windle, D., and Wroth, C.P. 1977. The use of a self-boring pressuremeter to determine the undrained properties of clays. *Ground Engineering*, pp. 37–46.
- Wroth, C.P., and Houlsby, G.T. 1985. Soil mechanics-property characterization and analysis procedures. In *Proceedings of the 11th International Conference on Soil Mechanics and Foundation Engineering*, San Francisco. Vol. 1, pp. 1–55.
- Wu, T.H. 1958. Geotechnical properties of Glacial Lake clays. *Journal of the Soil Mechanics and Foundations Division, ASCE*, 84(3): 1–34.
- Wu, T.H., Douglas, A.G., and Goughnour, R.D. 1962. Friction and cohesion of saturated clays. *Journal of the Soil Mechanics and Foundations Division, ASCE*, 88(3): 1–32.
- Wu, T.H., Loh, A.K., and Malvern, L.E. 1963. Study of failure envelopes of soils. *Journal of the Soil Mechanics and Foundation Division, ASCE*, 80(3): 145–181.
- Wu, T.H., Thayer, W.B., and Lin, S.S. 1975. Stability of embankment on clay. *Journal of the Geotechnical Engineering Division, ASCE*, 101(9): 913–932.
- Wu, T.H., Chang, N.Y., and Ali, E.M. 1978. Consolidation and strength properties of a clay. *Journal of the Geotechnical Engineering Division, ASCE*, 104(7): 889–905.
- Yasuhara, K., Yamanouchi, T., and Hirao, K. 1982. Cyclic strength and deformation of normally consolidated clay. *Soils and Foundations*, 22(3): 77–91. doi:10.3208/sandf1972.22.3.77.
- Zreik, D.A., Ladd, C.C., and Germaine, J.T. 1995. A new fall cone device for measuring the undrained strength of very weak cohesive soils. *Geotechnical Testing Journal*, 18(4): 472–482. doi:10.1520/GTJ11022J.