A Scale-Invariant Baseline Can Miss a Broken Deep Model: Grouped-Normalisation Collapse in Learned Trajectory Screening

Harsha Vardan M Sakamuri[a], Rohit Michael Raj[a], Valarmathi P.[a,*]

[a] *School of Computer Science and Engineering (SCOPE), Vellore Institute of Technology, Vandalur–Kelambakkam Road, Melakottaiyur, Chennai, 600127, Tamil Nadu, India*

Abstract

A single feature scaler is often used among a set of data. We show that it can quietly harm a sequence model while two otherwise sensible checks—a mixed-group validation score and the particular scale-invariant XGBoost baseline tested here—remain healthy. A Transformer trained with a scaler averaged over a target group ceases to react to the input on Venus (3.11e-05 prediction standard deviation on unseen missions, 0.6037 validation area under the ROC curve (AUC)). The same transformed arrays remain almost perfectly separable by XGBoost, whose AUC varies by at most 0.0002 across the three normalisation settings. This is a narrow invariance result, not a claim that tree models generally cannot diagnose preprocessing errors. The failure is selective: 1 of 4 targets collapses; the remaining targets lose between 0.0003 and 0.0925 AUC while continuing to discriminate. Across five seeds the same preprocessing produces collapse on 4 runs, so five seeds do not establish universal reliability. Our AI contribution is a controlled test of when pooled normalisation breaks this sequence model, a label-free prediction-spread statistic that exposes the observed failure, and a second failure where the model misses a rare class that a tree finds in the same input. The engineering application is screening simulated spacecraft trajectories to save compute; operational integration is proposed, not flight-demonstrated.

Keywords: feature normalisation, shortcut learning, model diagnostics,

*Corresponding author

Email address: valarmathi.sudhakar@vit.ac.in (Valarmathi P.)

simulation screening, trajectory analysis, negative results

1. Introduction

In Monte Carlo trajectory campaigns, the majority of the compute is used on runs that were already sure to fail when they left the parking orbit. These campaigns are a regular occurrence at flight facilities, such as the large dispersion campaign that TESS used to set its trajectory design (Nickel et al., 2016). Not only is this expensive, a body of work has been developed to make each propagation even less expensive (Massari et al., 2017; Jia and Xin, 2022). Another, and obvious, approach is to steer clear of these runs: track the first part of a trajectory and cancel out the ones that will fail. It's a screen we have made. It revealed two failures that we believe are much more than astrodynamics related, and one bad result regarding the screen.

This paper will deal with the first failure. Grouped data was used for training the model and a single feature scaler was fitted for the entire group. It ended up emitting a single constant per group. It's not the surprising part that it happened. What's most interesting is the length of time it took to be noticed. With a mixed validation set it looked fine, since a model can score well if it differentiates groups but cannot differentiate anything within the groups, and validation AUC remained high. A baseline run was executed with a gradient boosted model, with almost perfect results, because the trees divide on the actual values and the scaling on which the network depends is not important to them. Both of the tests we would have used would have told us that the pipeline was healthy.

This isn't, of course, comfortable, as running a simple baseline is good advice. It is common practice for tabular and physical data to be checked by tree ensembles and they are often a strong choice (Chen and Guestrin, 2016; Grinsztajn et al., 2022; Shwartz-Ziv and Armon, 2022). In our controlled comparison, the particular XGBoost baseline is invariant to the monotone rescaling that damages the network, so its success does not test whether this network can use the compressed signal. Other tree-based checks, other feature audits, or trees exposed to a non-monotone or information-destroying preprocessing error could diagnose other failures; our evidence does not say otherwise.

We make three contributions. It is first a controlled decomposition of the collapse, which distinguishes pooling over time from pooling across groups,

and shows only the latter to be deadly. Second, a demonstration that a scale-invariant baseline actually approves of the broken configuration, as well as an inexpensive diagnostic that does notice it. Third, another failure of the same kind: the model has no access to a rare class that can be recovered from its own input. We also report something that limits how much the first two matter in practice, which is that the application that inspired them doesn't need a sequence model at all.

This paper is based on scripts in the attached repository that generate all the numbers, which are written to machine-readable artefacts. Those artefacts are then used to create the paper containing tables and figures.

2. Related Work

Normalisation is crucial for training deep networks, and there are standard layers (batch, layer, group, instance) that solve a version of the problem (Ioffe and Szegedy, 2015; Ba et al., 2016; Wu and He, 2018; Ulyanov et al., 2016; Huang et al., 2023). It has been long known that the ability of a network to train, and not merely the rate at which it trains, depends on the scaling of the inputs (Sola and Sevilla, 1997). These layers also make some assumptions about the input that they're given. They assume that the feature statistics are stationary, or that they're comparable within each pooling axis. When more than one set of data is measured on the same scaler, but the range of the data is very different, that assumption is already broken before the first layer runs. What we add is a controlled decomposition that shows us that it is not the pooling in general that does the damage, but only the pooling across the groups, and then an observation that the resulting model is not a weak model, but a constant model.

When a shortcut is there, a network will easily learn the easy signals and take the shortcut over the intended structure (Geirhos et al., 2020; Shah et al., 2020). Previous research on Clever-Hans behaviour demonstrates that the models achieve good scores for reasons that are not related to the task (Lapuschkin et al., 2019). If the scales are grouped and are not homogenous, there is an exceptionally clean shortcut, the distance between the group centroids. This type of model simply memorizes the difference, and has validation AUC of >0.95 but performs no better inside individual groups. That's what we saw. Here, our contribution is a diagnostic (spread of the predictions within a group) which does not need any label and is quite different from the common underfitting. It is also not a modelling problem, but a pipeline level

problem, like many which can be found in the shared preprocessing code that no single model owns (Chaudhary et al., 2018).

Tree ensembles perform well on tabular and physical data, and often perform with the same or better results than deep models (Chen and Guestrin, 2016; Grinsztajn et al., 2022; Shwartz-Ziv and Armon, 2022; Ke et al., 2017; Pasaribu et al., 2024), and many practitioners turn to a tree as a baseline for that reason. Their splits are axis-aligned and threshold-based, so a monotone rescaling can preserve the available ordering. That useful invariance is why the tested XGBoost baseline misses this particular cross-group scaling failure when it receives the same transformed arrays; it does not imply that tree baselines are generally unable to identify preprocessing errors.

The standard ways to overcome a serious imbalance are reweighting, focal loss or resampling (Buda et al., 2018; Lin et al., 2017; Cui et al., 2019), and the effect of imbalance on the actual learning of a deep classifier is explored in great detail (Dong et al., 2025). The two model families have different reactions to it, which is a reason why it is worthwhile to make a comparison at all (Wu et al., 2021). In Section 6 we report a case in which none of that is the issue: oversampling a rare failure mode by a factor of 19.2 doesn't move its recall at all, but a tree on the same window separates it almost perfectly. It's the same with the evidence in the space domain. The ESA anomaly benchmark shows that current sequence models still struggle with the rare but important events in real satellite telemetry (Kotowski et al., 2024), and rare anomaly detection there is still active enough to need uncertainty-aware methods (Sadr et al., 2022). This is a type of data that carefully designed LSTM pipelines are able to perform well on when the data is correctly processed in all channels (Hundman et al., 2018). It's not the model class, it's the engineering that makes the difference.

The word 'collapse' also needs disambiguation. Neural collapse conventionally describes the terminal-phase geometry of within-class representations and classifiers after training error vanishes (Papyan et al., 2020); our outcome is different: predictions over distinct missions become nearly constant after cross-group scaling. Work on predictive uncertainty under shift shows that confidence and calibration can deteriorate when the deployment distribution changes (Ovadia et al., 2019), while two-sample tests can detect changes between reference and incoming feature distributions without target labels (Rabanser et al., 2019). Production-readiness rubrics likewise call for data, model, and serving-pipeline monitors rather than relying on a single held-out score (Breck et al., 2017). Table 1 makes these boundaries explicit.

Table 1: Comparison with adjacent diagnostics. Label-free inference does not remove the need for development-time threshold calibration and evaluation.

Prior method	Failure detected	Label requirement	Dependence on a reference model	Limitation addressed by our approach
Neural-collapse geometry (Papyan et al., 2020)	Terminal class-feature geometry	Class labels; internal activations	No external model	Targets output constancy from grouped preprocessing, not terminal-phase geometry.
Predictive uncertainty (Ovadia et al., 2019)	Uncertainty and calibration under shift	Labels for evaluation	Method-dependent; often ensembles	Directly tests a distinct output degeneracy.
Dataset-shift tests (Rabanser et al., 2019)	Source–target distribution change	No target labels for alarm	Reference distribution; sometimes a domain classifier	Tests within-group model outputs, not only input shift.
ML pipeline validation (Breck et al., 2017)	Broad data, training, serving regressions	Test-dependent	Schema, baseline, or prior version	Supplies a concrete group-level output invariant.
This work	Near-constant within-group predictions	None to compute; labels to calibrate/evaluate	None for spread; optional XGBoost triage	Isolates cross-target pooling and separates collapse from low AUC.

Networks have been successfully applied in astrodynamics for trajectory optimization, approximation of optimal control (Izzo et al., 2019a, 2024; Sánchez-Sánchez and Izzo, 2018), cost estimation without complete propagation (Li et al., 2020b; Izzo et al., 2019b) and learning of a robust low thrust policy with certification via Monte Carlo (Zavoli and Federici, 2021). Learned models also correct orbit predictions from sparse tracking (Li et al., 2020a), stand in for Monte Carlo when propagating orbit uncertainty forward (Zhou et al., 2024), and are used for anomaly and fault detection in spacecraft telemetry (Ibrahim et al., 2019; Naik et al., 2020), where the same family of attention architectures is used as here (Jiang et al., 2023). Screening specifically, by means of a learned model selecting which of a very large number of candidate cases get full analysis, is already recognized: an ESA competition on real conjunction data (Uriot et al., 2020; Acciarini et al., 2021), and a benchmark of deep approaches against the classical filters they would replace (Stevenson et al., 2023). The final one is the most similar setting, a screening task on a deterministic astrodynamics simulator, measured against non-deep baselines. We could not find an article in this literature that considers early termination of individual Monte Carlo trajectory runs as we do in Section 7. The closest work decreases the cost of each propaga-

tion rather than deciding which propagations to start (Massari et al., 2017; Jia and Xin, 2022). The general idea is to use a learned surrogate instead of part of an expensive simulation (Yin et al., 2022).

3. Setup

In total, we developed 70,000 missions that leave the Earth, 10,000 missions to each of seven interplanetary targets (Mercury, Venus, Mars, Jupiter, Saturn, Uranus and Neptune), using NASA's General Mission Analysis Tool. It has an extensively verified two and three body propagator (Hughes et al., 2014), and is deterministic. Each mission has six injection offsets, which are the components of the trans orbit insertion burn (`dv_V`, `dv_N`, `dv_B`), and the RAAN, AOP and INC of the parking orbit from which the mission departs. Each is classified as success or failure, and failed ones are further sub-categorised as surface impact, orbit too high, missed target and a few others.

The interplanetary transfers are sampled at a fixed rate of 54,000 s (15 hours) and downsampled to about 100 steps for each mission. This is so that the sequences produced by targets with flight times that vary by 2 orders of magnitude are comparable. Thirteen features are recorded for each step, and include position in the synodic frame, specific orbital energy, flight path angle, normalised target distance and eccentricity. An eighth target was created (the Moon), and is intentionally left out of the study. It is a 6 day transfer inside Earth's neighbourhood, sampled at 60 s, and it doesn't have a cost structure similar to Section 7, or a heliocentric dynamical regime.

The screening task is to observe the first 40% of the mission's flight path and decide whether or not to abort. Splits are mission based 70/15/15, deterministic in (n, seed). The experiments are all based on a single definition in the repository, so no model is ever scored using data that was used for model selection. It is not a theoretical question. Two of the previous analyses in this project shuffled the same number of missions using the same seed, and in those analyses the same set of missions ended up in both 'test' sets.

The sequence model is a Pre-LN Transformer encoder, `d_model` 128, 8 heads, 4 layers and CLS token pooling, and 2 heads are connected to a single trunk (one for mission outcome and one for failure mode). It is trained on random length prefixes, so that its predictions are not only at the 40% mark in the stream but at any point in the stream. The baseline is XGBoost, 300 trees at depth 5, fitted to the same normalised prefix, flattened. It is




Figure 1: The three normalisation modes, and the only difference between them: from what part of the data does the scaler get its median and IQR? Everything else in training is the same. Each cell is all the missions of one target at one timestep index, and the shaded cells are the ones the median and IQR are estimated from.

important to note that the baseline is not working from a feature set derived separately, but from the same view the network sees, which is what 'the same input' means throughout this paper. That detail carries most of the argument and we're very rigid with it.

The three conditions are the following sets of normalisations, which only vary in how the feature statistics are combined. All use the same architecture, seed, split, optimiser and epoch budget.

per timestep: every one takes its statistics from the distribution of features at that timestep index, over the missions of one target (Fig. 1). This is the configuration the working system uses.

global: one RobustScaler (median and IQR) per target, pooled across that target's own timesteps.

grouped: one RobustScaler pooled across all timesteps of all targets in a regime group (inner: Mercury, Venus, Mars; outer: Jupiter, Saturn, Uranus, Neptune). This is the setting that was not successful in production.

The third setting isn't a straw man, and here's why. You get a single RobustScaler from nearly all the standard pipeline tutorials, applied to a concatenated training set. No warning is issued and it looks like a normalised array.

4. Grouped-Normalisation Collapse

A mission's features sweep a wide range as they fly, and the range other targets occupy varies by orders of magnitude. A scaler applied to a set of pooled data will then scale the data on the scale of the largest source of variation in the set. What the screen should be able to tell apart is neither of those things. It is the spread between missions at a particular point in the flight, which by comparison is small. Pooling divides that spread by an arbitrary denominator, which drives the level of the useful signal towards zero and has no effect on the structure between groups. The network is then tasked with learning a difference that is close to the limit of what gradient descent can detect, and Pre-LN layer normalisation filters out a lot of it.

This is used as the signal ratio, defined as the average of the standard deviation of the normalised features across missions, calculated only in the observed window. It's not a limitation you would expect but it does matter. The metric is totally useless averaged over the entire flight, because late timesteps have a huge spread across missions, as the missions that fail have physically diverged by that time, and that spread swamps the early signal so that all conditions appear healthy. The model commits at 40%, so what's important is the range within the prefix the model observes.

The first result is the decomposition that is controlled. The network is able to operate with the signal being reduced by up to a factor of 23 by pooling across time in a single target. It works on all 4 targets, with a loss of a few thousandths of AUC at most. Another kettle of fish is the pooling of a group. On Venus, the output standard deviation is 3.11e-05, which is one number for every mission, and the AUC drops from 0.9999 to 0.6037.

The term 'collapse' is used instead of 'underfitting' because of Fig. 2. A low AUC on its own doesn't mean much, because that is what you would get if the model learned something poor or wrong. A distribution on unseen missions that is three ten-thousandths wide is not ambiguous at all. The network is no longer under the control of its input.

The second result is that the collapse is selective, and we report that alongside the case that breaks. In the remaining 3 targets the same manipulation leaves the output still varying, and costs between 0.0003 and 0.0925 AUC. The signal ratio is not a measure of severity either. Jupiter compresses its signal to 0.0247, whereas Mercury compresses its signal to 0.0484, and yet Jupiter loses 0.0003 AUC whilst Mercury loses 0.0925 AUC. This is because Jupiter's task is nicely split up so that even a very weak signal is sufficient.

Compression is necessary for the collapse but not sufficient; how hard the underlying task is modulates it. We are not claiming that these data support a rule of the form 'it collapses when the ratio is below X'. The counter example is visible in Fig. 3.

One note on scope. This ablation isolates normalisation and no other component of the model, so only the statistics are pooled, with one model trained for each target. The production failure also shared a single trunk across the group, which compounds the problem, since one trunk then has to serve targets whose inputs have all been flattened in the same direction, towards a constant. These numbers therefore represent a minimum damage level of the configuration. They show that pooled normalisation is sufficient on its own to destroy a target, and not that this is a complete reconstruction of the original incident.

Under the grouped setting the tested XGBoost configuration reports AUC 1.0000 on Venus, the target where the network has collapsed to a constant at AUC 0.6037. Its AUC changes by at most 0.0002 across settings on all targets, which implies that this normalization choice is not visible to this baseline. It therefore establishes that discriminative ordering remains in the transformed arrays, but it does not establish that the deep model can exploit the remaining magnitude of variation.

This is the methodological part and it's crucial to pay attention to the exact claim. The information is there and this tree can use it. This particular baseline comparison is not informative on the question that has to be answered, which is 'can the network use the compressed signal?'. Its invariance to this rescaling makes this check orthogonal to this defect. That statement is deliberately narrower than claiming that tree baselines cannot diagnose preprocessing errors in general.

Accuracy on a mixed validation set does not catch the collapse, because a per group constant ranks the groups correctly and a pooled metric rewards that. It's picked up by two checks.

Prediction spread within a group. For group g with a batch of n_g predictions, we compute $s_g = \mathrm{sd}\{P(\text{fail} \mid x_i) : i \in g\}$. This statistic is label-free at inference: it uses predictions and group membership, not outcomes. Labels are nevertheless needed during development to decide which low-spread states are harmful, calibrate an alert level, and estimate false alarms and missed detections.

Tested XGBoost against the network under the same preprocessing. If XGBoost has a big lead with both fed the same array, then usable ordering

remains for that model while the network has failed to exploit the compressed signal.

Both are inexpensive and neither necessitates that one predicts this exact defect beforehand. In the reported experiments, 'collapsed' was assigned when $s_g < 10^{-3}$. This rule was written into the experiment before the additional multi-seed replication, but after the original single-run incident; it was a heuristic definition, not a threshold optimized on labelled validation cases. Test labels and test AUC were not used to choose it, although held-out predictions were used to report the spread. The resulting state labels therefore cannot also serve as independent ground truth for sensitivity or specificity: doing so would be circular. The evidence supports the statistic as a conspicuous signature in this experiment, not 10^{-3} as a universal operating threshold.

4.1. Mission-assurance interpretation and operational use

Demonstrated result. Within the GMAT experiment, the group-level output statistic exposes four near-constant Venus runs that a pooled AUC and the tested XGBoost comparison do not identify. Because it checks the behaviour at the preprocessing–model interface, the same form of invariant can supplement verification and validation in other simulation-screening pipelines: it tests whether changing candidate inputs still changes the learned screen. It does not validate the trajectory propagator, prove physical correctness, certify flight software, or establish a threshold outside the evaluated configuration.

Operational implication. If an analogous collapse remained undetected in a mission-design campaign, the screen could assign nearly the same disposition to materially different candidates. Depending on that constant and the decision threshold, it could discard viable trajectories, retain expensive failures, distort estimates of feasible-region size, and bias trade studies or robustness margins. A healthy aggregate score from other target groups could conceal the affected group and create false confidence in the campaign. These consequences are failure analyses, not outcomes measured in a flight campaign.

Proposed pipeline. During development, the team would generate labelled working, degraded, and intentionally fault-injected validation states for each dataset–architecture–target-group–preprocessing version. It would calibrate a group-specific spread threshold and a minimum batch size on those validation states, freeze both before the untouched test evaluation,

Table 2: Normalisation ablation. Identical architecture, seed and split; only the pooling differs. 'sig' is the mean within timestep standard deviation of the normalised features in the observed window. 'std' is the standard deviation of P(fail) on unseen missions, the quantity that identifies a collapse, as against a model that is merely inaccurate.

	per-timestep			global			grouped		
Target	sig	AUC	std	sig	AUC	std	sig	AUC	std
Venus	0.7681	0.9999	4.72e-01	0.0518	0.9947	4.50e-01	0.0023	0.6037	3.11e-05
Mars	1.0829	0.9994	4.33e-01	0.0472	0.9972	4.00e-01	0.8005	0.9422	4.06e-01
Mercury	0.7686	0.9994	4.27e-01	0.1321	0.9970	4.23e-01	0.0484	0.9069	4.25e-01
Jupiter	0.7708	1.0000	4.78e-01	0.0763	1.0000	4.78e-01	0.0247	0.9997	4.75e-01

Table 3: The tested XGBoost model on the same normalised window for each setting. Its AUC is nearly invariant to the particular rescaling that destroys the network.

Target	per-timestep	global	grouped	spread
Venus	1.0000	1.0000	1.0000	0.0000
Mars	0.9996	0.9998	0.9998	0.0002
Mercury	0.9997	0.9998	0.9998	0.0001
Jupiter	1.0000	1.0000	1.0000	0.0000

and record false-alarm and miss rates with uncertainty. At runtime, each screening batch would log model, scaler, data, and group versions; compute s_g alongside robust spread, input-signal, and feature-shift checks; and compare only with the matching frozen limits. An alarm would quarantine the learned screen, preserve all candidates, and fall back to the full-fidelity propagation rather than aborting trajectories. An XGBoost comparison can aid offline triage by asking whether information remains in the same arrays, but is not required to compute the inference-time statistic. Once delayed outcomes are available, they would support periodic re-evaluation and versioned recalibration—never silent transfer of a threshold from another domain.

5. Does It Reproduce Across Seeds?

Is it spread by seed? All of the above is problematic in that it's one run deep. A bad initialisation could result in an AUC of only 0.6037. Thus, we redo the whole ablation in 5 different seeds, in each of which we redraw the train/validation/test partition and the initialisation.




Figure 2: P(fail) on Venus, split out for each setting. Per timestep and global normalisation put the two populations at opposite ends of the axis. Under grouped normalisation every mission gets essentially the same number. Panel (d) magnifies that spike and shows the full range covers about three ten-thousandths. This is what makes a collapse different from a merely bad model.

Compression is not dependent on seed. The signal ratio for Venus under grouped normalisation lands between 0.00222 and 0.00232 across all 5 runs, a spread of 5% against the compression of 335x itself. The healthy condition is stable too. The difference in per timestep AUC between two different seeds is at most 0.0010. There is no seed on which Mars, Mercury or Jupiter collapse.

It depends on the seed whether the network escapes or not. Venus meets the pre-specified experimental rule $s_g < 10^{-3}$ on 4 of 5 seeds, with prediction spread on unseen missions ranging from 1.57e-05 to 4.84e-05, which is 4 orders of magnitude lower than the 4.66e-01 obtained by correct normalisation. On the remaining seed it doesn't meet the collapse rule, and it doesn't recover either: prediction spread 3.64e-02, still an order of magnitude short, at AUC 0.9305 against a healthy 0.9999. The observed recurrence is 4/5, with a 95% Wilson interval of 0.376–0.964. That wide interval describes recurrence of the defined state under these seeds; it is not a confidence interval for detector sensitivity and does not support universal reliability.

This is the real reason for the prediction spread diagnostic above. The range of grouped AUC for Venus over these runs is 0.5338 to 0.9305, which overlaps that of a merely weakened target. Mercury sits inside that range on every seed while still telling missions apart. AUC is thus unable to distinguish the two states. Prediction spread can. There are orders of magnitude between the collapsed runs and all the healthy runs. If you have to keep tabs on one




Figure 3: Signal ratio against validation AUC. These points would lie on a curve if the collapse was only due to compression. Jupiter has a lower signal ratio than Mercury and still loses very little.

number for this failure, watch that one.

The same invariance appears across the replication. Across 5 seeds, 4 targets and three normalisation settings, which is 60 fitted XGBoost models in total, AUC stays within 0.9989–1.0000, and within each seed and target the AUC difference is at most 0.0003 between settings. Thus this tested baseline does not distinguish these normalization conditions. This is evidence about one baseline–failure pairing, not all tree-based diagnostics.

6. Failing to Reach a Signal That Is Present

If the normalisation is correct, but the model doesn't pick up a signal that is there, the second failure appears. The failure mode `surface_impact` makes up 91 of the 4,639 failures in training. A tree on the same normalised




Figure 4: Both models under grouped normalisation on the same arrays. The tested XGBoost model is at the ceiling on every target, including the one where the network is just above chance.

40 step window separates that mode from success at AUC 1.0000, recall 1.0000. The recall of the sequence model at its operating point is 0.0000.

The information is there in both models and one of them splits the classes appropriately, so it is not an information limit, it's an optimisation limit in the sequence model. Resampling doesn't resolve the problem, which eliminates the most obvious explanation. We're not sure whether it is the loss landscape, or the CLS pooling discarding a cue that is localised in time, or the binary head being dominated by the majority mode. If we probe the representation of the trunk for linear separability of the rare mode it will narrow it down, and that's the next experiment, not a result we have.

This number can easily be quoted misleadingly, since it has two denominators. The rare mode is oversampled by about 45 times at the strongest setting, compared to the majority failure mode. The factor is 19.23x relative

Table 4: Validation AUC across 5 seeds, mean and standard deviation, and the number of seeds on which the grouped run collapsed to a constant output.

Target	per-timestep AUC	grouped AUC	collapsed
Venus	0.9998 ± 0.0001	0.6912 ± 0.1530	4/5
Mars	0.9992 ± 0.0004	0.9457 ± 0.0093	0/5
Mercury	0.9997 ± 0.0002	0.9118 ± 0.0036	0/5
Jupiter	0.9999 ± 0.0002	0.9997 ± 0.0003	0/5

Table 5: Oversampling sweep on the rare mode on Uranus. Turning up the sampling weight on the rare mode does not recover it, and does not disturb anything else either.

alpha	resample	test F1	all modes	rare mode
0.00	1.0x	0.9938	0.9877	0.0000
0.50	5.1x	0.9938	0.9877	0.0000
1.00	19.2x	0.9938	0.9877	0.0000

to uniform sampling over the training set, which is what the sampler actually applies. The latter is reported since it is what the optimiser saw.

The sweep was repeated on 5 seeds, which also redraw the split and therefore the rare mode itself. The gap replicates and the extremes do not. Sequence recall on the rare mode runs from 0.0000 to 0.1429 across all the seeds and sampling weights, against a tree on the same window at recall 0.9333 to 1.0000 and AUC 0.9997 to 1.0000. The sampling weight makes no difference on any one run at all: recall is the same at all three levels within a seed, so the flat line in the figure is not a property of a single run.

7. Where the Screen Belongs

If it has been thoroughly done on the sequence model, the real answer is that it should not be used. The six feature classifier, which is evaluated prior to any propagation whatsoever, saves 64.5% of compute against the telemetry model's 38.3%, at a similar cost in good missions destroyed. There is also a levelling off of accuracy between 10% and 40% observed. The problem is not a modelling fault. The simulator is deterministic, the outcome is a fixed function of the injection offsets, and the trajectory is an integral of the offsets. It can't transport information that the parameters don't have.




Figure 5: Every seed plotted on its own rather than summarised as an interval. With n = 5 the spread of the raw points is the honest summary.

This is not to imply that the task is trivial. Logistic regression on the same 6 features achieves 0.4824 to 0.5410 AUC on all of the targets, which is chance, so the mapping between the parameters and the outcome is very non-linear and requires a learned model. A temporal one is not really necessary. The sequential screen is only worth applying if the outcome is not known at injection: mid flight stochasticity, unmodelled dynamics, sensor noise, or campaigns where the launch parameters are not known. That is exactly the setting reinforcement learning trajectory work needs when it certifies policies through dispersed Monte Carlo campaigns (Zavoli and Federici, 2021).

This section is included since it sets the scope of the practical significance of all the preceding material. The methodological findings are valid for any grouped pipeline that models sequences. In the application that produced




Figure 6: Recall against oversampling weight. The horizontal line is a tree on the same window. The curve for the rare mode does not move.

the findings, a sequence model was not needed at all. A reviewer who works that out alone is in a worse position than one who is told.

Two methodological remarks on this table, just before the conclusion we derive. The previous version was produced under two selection biases: the thresholds were optimised on the test labels, and the evaluation set contained the validation split of the sequence model. Both of them flattered T40, the screen that this section opposes. The headline moved by no more than 0.1 percentage points when they were removed. A negative result that survives its own correction is the strongest form the claim can take.

For the T0 screen, an additional five-split analysis (seeds 0–4) gives compute saved $64.50\% \pm 0.61$ percentage points, good missions lost $1.24\% \pm 0.24$ percentage points, and failure recall $98.99\% \pm 0.18$ percentage points (mean $\pm$ standard deviation across five splits). The T40 and cascade rows in Table 6 remain single seed-42 estimates and are not presented with an interval. The multi-seed T0 result narrows sampling uncertainty for that screen, but five

Table 6: Screening economics. Compute is charged in propagation days, which span about a 100x range across the seven targets. Thresholds are fitted on validation and reported on the untouched test split, so the recall column is measured out of sample rather than achieved by construction.

Screen	Compute saved	Good missions lost	Failure recall
T0: six launch parameters, before propagating	64.5%	0.76%	99.06%
T40: telemetry Transformer at 40%	38.3%	0.21%	98.87%
Cascade: T0 where confident, else T40	65.0%	1.62%	99.94%




Figure 7: (a) What each screening point buys and what it costs. (b) Why the weighting is not uniform: the cost of propagating one mission spans two orders of magnitude, so the value of a screen is dominated by the outer targets.

correlated resplits of one synthetic corpus do not measure cross-campaign or cross-domain uncertainty.

8. Limitations

- Seeds. Replication is limited to 5 seeds. The observed 4/5 recurrence has a wide 95% Wilson interval (0.376–0.964), and detector sensitivity or specificity cannot be estimated because the same spread rule defines the reported states. Five seeds exclude neither an unknown controlling factor nor substantial uncertainty.

- Threshold scope. The $s_g < 10^{-3}$ rule was fixed before the multi-seed

extension and was not selected using test labels or test AUC, but it followed the original incident and was not calibrated on an independent library of working and collapsed states. It is not expected to transfer unchanged to another dataset, model architecture, output calibration, target group, prevalence, or batch size. A new operational context needs labelled development experiments for calibration and an untouched test for evaluation; the runtime statistic itself can then remain label-free.

- One corpus. The collapse and its rule are shown on one synthetic GMAT corpus. No cross-domain transfer experiment is included in the auditable artifacts for this paper. We outline a mechanism in terms of a variance ratio, but do not claim a universal compression or prediction-spread threshold.

- Four targets in the ablation. 1 of 4 targets collapses, and all collapsed runs are Venus. Additional target combinations and alternative group definitions are required to estimate sensitivity to group composition. The four targets agree only that the tested XGBoost AUC is nearly invariant across these normalization settings.

- Architecture scope. An LSTM control on the ordinary, correctly preprocessed screening task reaches test AUC 0.9928 versus 0.9958 for the Transformer, showing that the base task is not unique to one sequence architecture. The LSTM was not run under grouped normalization, so whether this collapse generalises beyond the Transformer configuration remains open.

- Severity range. The present rule detects exact or near-exact constancy. We have not constructed graded signal compression, near-constant outputs, or mildly degraded discrimination with independent state labels, and therefore do not report false alarms or missed detections over that broader range.

- Synthetic and deterministic. There are no execution errors, no unmodelled accelerations, no sensor noise and all missions of a target have a common time base. This common time base is what makes standardisation per timestep possible at all and it is not a property of a real campaign, but of the generator.

- No real mission data. This is the most serious issue of external validity. There are now available real satellite telemetry public benchmarks (Kotowski et al., 2024; Hundman et al., 2018) and they are the natural next benchmarks for the diagnostic.

9. Conclusion

When one scaler is pooled across groups with different scales, the tested Transformer can become a per-group constant while the tested scale-invariant XGBoost baseline still finds the same arrays separable. None of the pieces here are exotic: the defect enters through preprocessing and survives pooled validation. The exact conclusion is not that trees cannot diagnose preprocessing, but that a diagnostic invariant to this transformation cannot answer whether a magnitude-sensitive network can use the compressed signal.

We don't claim the fix, normalisation per group, to be new. The detection lesson is to monitor group-level output behaviour in addition to pooled scores and baselines. Computing prediction spread requires no inference-time labels, but turning it into a go/no-go alarm requires version-specific calibration and independent labelled evaluation during development. Our experiment demonstrates a conspicuous signature and a failure mechanism; the mission-assurance workflow, threshold transfer study, broader severity sweep, and fall-back policy are operational implications still to be validated.

10. Code and Data Availability

All the scripts for the experiments, the JSON artifacts that each number is read from, the code for the figures and the source of this document are at `https://github.com/Haise-727/gmat-pred`. A short map of where things are:

`src/ml/` holds the experiments. `norm_ablation.py` produces Table 2, `baseline_invariance.py` Table 3, `rare_mode_sweep.py` Table 5, `prune_economics.py` Table 6, and `multi_seed_economics.py` the T0 uncertainty summary. All share the same definition of the train/validation/test partition in `splits.py`.

`src/ml/model.py` is the Transformer, and `planet_config.py` holds the target list, the cadences and the recorded reason the Moon is excluded.

`reports/` holds the measured artifacts. Every reported number comes from one of those JSON files; `multiseed_paper/` holds the runs behind

Table 4, and `prune_economics_multiseed.json` holds the additional T0 split-seed analysis.

`docs/RESEARCH_LEDGER.md` is the complete decision history, including two analyses that were invalidated by a positional join and the corrections that replaced them. `docs/LIMITATIONS.md` states what the results do not support.

The JSON creates the tables and figures in this manuscript and not the other way round. No number was typed into the manuscript by hand.

The experiments read per target `.npz` files of roughly 70 MB each, which are derived from a 71 GB mission table that is too large to store in the repository. The scripts below regenerate the artifacts from those extracts. `ORBITGUARD_DATA` points at the full table, and the economics analysis is the only experiment that needs it.

```
export ORBITGUARD_DATA=/path/to/dataset

# Primary results, seed 42
python -m src.ml.norm_ablation          # Table 1
python -m src.ml.baseline_invariance    # Table 2
python -m src.ml.rare_mode_sweep        # Table 4
python -m src.ml.prune_economics        # Table 5

# Replication, one pass per seed (Table 3, Section 5)
for S in 0 1 2 3; do
  python -m src.ml.norm_ablation --seed $S \
      --out reports/multiseed_paper/normalisation_ablation_seed$S.json
  python -m src.ml.baseline_invariance --seed $S \
      --out reports/multiseed_paper/baseline_invariance_seed$S.json
  python -m src.ml.rare_mode_sweep --seed $S \
      --out reports/multiseed_paper/rare_mode_sweep_seed$S.json
done

# The document
python docs/paper/build/collect_traces.py   # Fig. 2 data
python docs/paper/build/figures.py          # all figures
python docs/paper/build/render_latex.py     # this document
```

Declaration of competing interest

The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

CRediT authorship contribution statement

Harsha Vardan M Sakamuri: Conceptualization, Methodology, Software, Validation, Formal analysis, Investigation, Data curation, Writing –

original draft, Writing – review & editing, Visualization, Project administration, Resources. **Rohit Michael Raj:** Conceptualization, Methodology, Software, Validation, Formal analysis, Investigation, Data curation, Writing – original draft, Writing – review & editing, Visualization, Project administration, Resources. **Valarmathi P.:** Supervision.

Funding

This research did not receive any specific grant from funding agencies in the public, commercial, or not-for-profit sectors.

Declaration of Generative AI and AI-assisted technologies in the writing process

During the preparation of this work the authors used Claude (Anthropic) in order to write and debug code, draft parts of the text, and check references. After using this tool, the authors reviewed and edited the content as needed and take full responsibility for the content of the publication.

References

Acciarini, G., Pinto, F., Letizia, F., Martinez-Heras, J.A., Merz, K., Bridges, C., Baydin, A.G., 2021. Kessler: A machine learning library for spacecraft collision avoidance, in: 8th European Conference on Space Debris.

Ba, J.L., Kiros, J.R., Hinton, G.E., 2016. Layer normalization. arXiv preprint arXiv:1607.06450 doi:10.48550/arXiv.1607.06450.

Breck, E., Cai, S., Nielsen, E., Salib, M., Sculley, D., 2017. The ML test score: A rubric for ML production readiness and technical debt reduction, in: 2017 IEEE International Conference on Big Data, pp. 1123–1132. doi:10.1109/BigData.2017.8258038.

Buda, M., Maki, A., Mazurowski, M.A., 2018. A systematic study of the class imbalance problem in convolutional neural networks. Neural Networks 106, 249–259. doi:10.1016/j.neunet.2018.07.011.

Chaudhary, D.K., Srivastava, S., Kumar, V., 2018. A review on hidden debts in machine learning systems, in: Second International Conference on Green Computing and Internet of Things (ICGCIoT). doi:10.1109/ICGCIOT.2018.8753081.

Chen, T., Guestrin, C., 2016. XGBoost: A scalable tree boosting system, in: Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining, pp. 785–794. doi:10.1145/2939672.2939785.

Cui, Y., Jia, M., Lin, T., Song, Y., Belongie, S., 2019. Class-balanced loss based on effective number of samples, in: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), pp. 9268–9277. doi:10.1109/CVPR.2019.00949.

Dong, J., Jiang, Z., Pan, D., Chen, Z., Guan, Q., Zhang, H., Gui, G., Gui, W., 2025. A survey on confidence calibration of deep learning-based classification models under class imbalance data. IEEE Transactions on Neural Networks and Learning Systems 36, 15664–15684. doi:10.1109/TNNLS.2025.3565159.

Geirhos, R., Jacobsen, J.H., Michaelis, C., Zemel, R., Brendel, W., Bethge, M., Wichmann, F.A., 2020. Shortcut learning in deep neural networks. Nature Machine Intelligence 2, 665–673. doi:10.1038/s42256-020-00257-z.

Grinsztajn, L., Oyallon, E., Varoquaux, G., 2022. Why do tree-based models still outperform deep learning on tabular data?, in: Advances in Neural Information Processing Systems (NeurIPS), pp. 507–520. doi:10.48550/arXiv.2207.08815.

Huang, L., Qin, J., Zhou, Y., Zhu, F., Liu, L., Shao, L., 2023. Normalization techniques in training DNNs: Methodology, analysis and application. IEEE Transactions on Pattern Analysis and Machine Intelligence 45, 10173–10196. doi:10.1109/TPAMI.2023.3250241.

Hughes, S.P., Qureshi, R.H., Cooley, D.S., Parker, J.J.K., 2014. Verification and validation of the general mission analysis tool (GMAT), in: AIAA/AAS Astrodynamics Specialist Conference. doi:10.2514/6.2014-4151.

Hundman, K., Constantinou, V., Laporte, C., Colwell, I., Söderström, T., 2018. Detecting spacecraft anomalies using LSTMs and nonparametric dynamic thresholding, in: Proceedings of the 24th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining, pp. 387–395. doi:10.1145/3219819.3219845.

Ibrahim, S.K., Ahmed, A., Zeidan, M.A.E., Ziedan, I.E., 2019. Machine learning methods for spacecraft telemetry mining. IEEE Transactions on Aerospace and Electronic Systems 55, 1816–1827. doi:10.1109/TAES.2018.2876586.

Ioffe, S., Szegedy, C., 2015. Batch normalization: Accelerating deep network training by reducing internal covariate shift, in: International Conference on Machine Learning (ICML), pp. 448–456. doi:10.48550/arXiv.1502.03167.

Izzo, D., Blazquez, E., Ferede, R., Origer, S., De Wagter, C., de Croon, G.C.H.E., 2024. Optimality principles in spacecraft neural guidance and control. Science Robotics 9, eadi6421. doi:10.1126/scirobotics.adi6421.

Izzo, D., Märtens, M., Pan, B., 2019a. A survey on artificial intelligence trends in spacecraft guidance dynamics and control. Astrodynamics 3, 287–299. doi:10.1007/s42064-018-0053-6.

Izzo, D., Sprague, C., Tailor, D., 2019b. Machine learning and evolutionary techniques in interplanetary trajectory design, in: Optimization in Space Engineering. doi:10.1007/978-3-030-10501-3_8.

Jia, B., Xin, M., 2022. Data-driven surrogate model and admissible-region-based orbital uncertainty propagation. Journal of Aerospace Information Systems 19. doi:10.2514/1.I011107.

Jiang, S., Jiang, Y., Wang, Y., Zhang, X., Zhang, Z., 2023. Anomaly detection in spacecraft telemetry data based on transformer-LSTM, in: International Conference on Intelligent Communication and Networking (ICN). doi:10.1109/ICN60549.2023.10426290.

Ke, G., Meng, Q., Finley, T., Wang, T., Chen, W., Ma, W., Ye, Q., Liu, T.Y., 2017. LightGBM: A highly efficient gradient boosting decision tree, in: Advances in Neural Information Processing Systems (NeurIPS), pp. 3146–3154.

Kotowski, K., Haskamp, C., Andrzejewski, J., Ruszczak, B., Nalepa, J., Lakey, D., Collins, P., Kolmas, A., Bartesaghi, M., Martínez-Heras, J.,

De Canio, G., 2024. European space agency benchmark for anomaly detection in satellite telemetry. arXiv preprint arXiv:2406.17826 doi:10.48550/arXiv.2406.17826.

Lapuschkin, S., Wäldchen, S., Binder, A., Montavon, G., Samek, W., Müller, K., 2019. Unmasking clever hans predictors and assessing what machines really learn. Nature Communications 10, 1096. doi:10.1038/s41467-019-08987-4.

Li, B., Huang, J., Feng, Y., Wang, F., Sang, J., 2020a. A machine learning-based approach for improved orbit predictions of LEO space debris with sparse tracking data from a single station. IEEE Transactions on Aerospace and Electronic Systems 56, 4253–4268. doi:10.1109/TAES.2020.2989067.

Li, H., Chen, S., Izzo, D., Baoyin, H., 2020b. Deep networks as approximators of optimal low-thrust and multi-impulse cost in multitarget missions. Acta Astronautica 166, 469–481. doi:10.1016/j.actaastro.2019.09.023.

Lin, T., Goyal, P., Girshick, R., He, K., Dollár, P., 2017. Focal loss for dense object detection, in: Proceedings of the IEEE International Conference on Computer Vision (ICCV), pp. 2980–2988. doi:10.1109/ICCV.2017.324.

Massari, M., Di Lizia, P., Rasotto, M., 2017. Nonlinear uncertainty propagation in astrodynamics using differential algebra and graphics processing units. Journal of Aerospace Information Systems 14, 493–503. doi:10.2514/1.I010535.

Naik, K.R., Holmgren, A., Kenworthy, J., 2020. Using machine learning to automatically detect anomalous spacecraft behavior from telemetry data, in: IEEE Aerospace Conference. doi:10.1109/AERO47225.2020.9172726.

Nickel, C., Dichmann, D.J., Lebois, R., Lutz, S., Parker, J.J.K., 2016. Monte carlo analysis as a trajectory design driver for the TESS mission, in: AIAA/AAS Astrodynamics Specialist Conference. doi:10.2514/6.2016-5665.

Ovadia, Y., Fertig, E., Ren, J., Nado, Z., Sculley, D., Nowozin, S., Dillon, J.V., Lakshminarayanan, B., Snoek, J., 2019. Can you trust your model's uncertainty? evaluating predictive uncertainty under dataset shift, in: Advances in Neural Information Processing Systems (NeurIPS), pp. 13969–13980.

Papyan, V., Han, X.Y., Donoho, D.L., 2020. Prevalence of neural collapse during the terminal phase of deep learning training. Proceedings of the National Academy of Sciences 117, 24652–24663. doi:10.1073/pnas.2015509117.

Pasaribu, J., Yudistira, N., Mahmudy, W.F., 2024. Tabular data classification and regression: XGBoost or deep learning with retrieval-augmented generation. IEEE Access 12, 191719–191732. doi:10.1109/ACCESS.2024.3518205.

Rabanser, S., G"unnemann, S., Lipton, Z.C., 2019. Failing loudly: An empirical study of methods for detecting dataset shift, in: Advances in Neural Information Processing Systems (NeurIPS), pp. 1394–1406.

Sadr, M.A.M., Zhu, Y., Hu, P., 2022. An anomaly detection method for satellites using monte carlo dropout. IEEE Transactions on Aerospace and Electronic Systems 59, 2044–2052. doi:10.1109/TAES.2022.3206257.

Sánchez-Sánchez, C., Izzo, D., 2018. Real-time optimal control via deep neural networks: Study on landing problems. Journal of Guidance, Control, and Dynamics 41, 1122–1135. doi:10.2514/1.G002357.

Shah, H., Tamuly, K., Raghunathan, A., Jain, P., Netrapalli, P., 2020. The pitfalls of simplicity bias in neural networks, in: Advances in Neural Information Processing Systems (NeurIPS), pp. 9573–9585.

Shwartz-Ziv, R., Armon, A., 2022. Tabular data: Deep learning is not all you need. Information Fusion 81, 84–90. doi:10.1016/j.inffus.2021.11.011.

Sola, J., Sevilla, J., 1997. Importance of input data normalization for the application of neural networks to complex industrial problems. IEEE Transactions on Nuclear Science 44, 1464–1468. doi:10.1109/23.589532.

Stevenson, E., Rodríguez-Fernández, V., Urrutxua, H., Camacho, D., 2023. Benchmarking deep learning approaches for all-vs-all conjunction screening. Advances in Space Research 72, 2660–2675. doi:10.1016/j.asr.2023.01.036.

Ulyanov, D., Vedaldi, A., Lempitsky, V., 2016. Instance normalization: The missing ingredient for fast stylization. arXiv preprint arXiv:1607.08022 doi:10.48550/arXiv.1607.08022.

Uriot, T., Izzo, D., Simões, L.F., Abay, R., Einecke, N., Rebhan, S., Martinez-Heras, J., Letizia, F., Siminski, J., Merz, K., 2020. Spacecraft collision avoidance challenge: design and results of a machine learning competition. arXiv preprint arXiv:2008.03069 doi:10.48550/arXiv.2008.03069.

Wu, J., Li, Y., Ma, Y., 2021. Comparison of XGBoost and the neural network model on the class-balanced datasets, in: IEEE 3rd International Conference on Frontiers Technology of Information and Computer (ICFTIC). doi:10.1109/ICFTIC54370.2021.9647373.

Wu, Y., He, K., 2018. Group normalization, in: Proceedings of the European Conference on Computer Vision (ECCV), pp. 3–19. doi:10.48550/arXiv.1803.08494.

Yin, J., Wang, F., Shankar, M., 2022. Strategies for integrating deep learning surrogate models with HPC simulation applications, in: IEEE International Parallel and Distributed Processing Symposium Workshops (IPDPSW). doi:10.1109/IPDPSW55747.2022.00222.

Zavoli, A., Federici, L., 2021. Reinforcement learning for robust trajectory design of interplanetary missions. Journal of Guidance, Control, and Dynamics 44, 1440–1453. doi:10.2514/1.G005794.

Zhou, X., Qiao, D., Li, X., 2024. Neural network-based method for orbit uncertainty propagation and estimation. IEEE Transactions on Aerospace and Electronic Systems 60, 1176–1193. doi:10.1109/TAES.2023.3332566.