

(http://www.techplayon.com/)

HOME (HTTP://WWW.TECHPLAYON.COM/)

Search ...

PRODUCTS (HTTP://WWW.TECHPLAYON.COM/INTERVIEWS/)

5G/NR (HTTP://WWW.TECHPLAYON.COM/5GNR/)

LTE (HTTP://WWW.TECHPLAYON.COM/LTE-A-LTE/)

RF DESIGN & TEST (HTTP://WWW.TECHPLAYON.COM/RF-DESIGN/)

IOT (HTTP://WWW.TECHPLAYON.COM/INTERNET-OF-THING-IOT/)

WHITE PAPER & VIDEO (HTTP://WWW.TECHPLAYON.COM/WHITE-PAPERS/)

TELCO CLOUD (HTTP://WWW.TECHPLAYON.COM/TELCO-CLOUD/)

5G NR Reference Signals (DMRS, PTRS, SRS and CSI-RS)

- September 26, 2018 (http://www.techplayon.com/5g-nr-reference-signals-dmrs-ptrssrs-and-csi-rs/)
 - admin (http://www.techplayon.com/author/admin/)
 - 5G (http://www.techplayon.com/category/5g/), Future Network Optimization (http://www.techplayon.com/category/future-network-optimization/), Interviews (http://www.techplayon.com/category/interviews/), LTE (http://www.techplayon.com/category/lte/), New Radio (http://www.techplayon.com/category/new-radio/), NR (http://www.techplayon.com/category/nr/), Tech Fundas (http://www.techplayon.com/category/tech-fundas/)


To increase protocol efficiency, and to keep Thainsweibsitensseem caincled switchtile lieves little or beam without having to depend on other slots and see airces. No Paintal or depend on other slots and see airces. No Paintal or depend on other slots and see airces. No Paintal or depend on other slots and see airces. reference signals. your use of this site is shared public. By

using this site, you agree to its use of cookie.

- Demodulation Reference Signal (DMRS) Phase Tracking Reference Signal (PTRS)

 (http://livetrafficfeed.com/gdpr)
- Sounding Reference Signal (SRS)
- Channel State Information Reference Signal (CSI-RS) Got it!

Reference Signals Mapping with associated with different physical channel is depicted in following figure.



What's new in NR compare to LTE

- In NR, there is not Cell specific Reference Signal (C-RS)
- New Reference Signal PTRS has been introduced for Time/Frequency tracking
- DMRS has been introduced for both downlink and uplink channels
- In NR, reference signals are transmitted only when it is necessary where as in LTE constantly exchanging reference signals to manage the link.

Detailed explanation

Demodulation Reference Signal (DMRS)

The DMRS is specific for specific UE, and used to estimate the radio channel. The system can beamform the DMRS, keep it within a scheduled resource, and transmit it only when necessary in either DL or UL. Additionally, multiple orthogonal DMRSs can be allocated to support MIMO transmission. The network presents users with DMRS information early on for the initial decoding requirement that low-latency applications need, but it only occasionally presents this information for low-speed scenarios in which the channel shows little change. In high-mobility scenarios to track fast changes in channel, it might increase the rate of transmission of DMRS signal (called "additional DMRS").

This website uses cookies to deliver its

- DMRS refers to demodulation references ignices, to analyze traffic. Infomation about
- It is used by a receiver for radio channel stimation fars defined of the physical channel using this site, you agree to its use of cookie.
- DMRS design and mapping is specific to each Downlink and Uplink NR channels vize NR-PBCH, NR-PDCCH, NR-PDSCH, NR-PUSCH, NR-PUSCH
- DMRS is specific for specific UE, and transmitted on demand

- DMRS can be beamform the DMRS, kept within a scheduled resource, and transmit it only when necessary in either DL or UL
- Multiple orthogonal DMRSs can be allocated to support MIMO transmission.

Phase Tracking Reference Signal (PTRS)

The phase noise of a transmitter increases as the frequency of operation increases. The PTRS plays a crucial role especially at mmWave frequencies to minimize the effect of the oscillator phase noise on system performance. One of the main problems that phase noise introduces into an OFDM signal appears as a common phase rotation of all the sub-carriers, known as common phase error (CPE).

- PTRS stands for Phase Tracking Reference signal
- It's main function is to track phase of the Local Oscillator at transmitter and receiver.
- PTRS enables suppression of phase noise and common phase error specially at higher mmwave frequencies.
- It is present both in uplink (in NR-PUSCH) and downlink (in NR-PDSCH) channels.
- Due to phase noise properties, PTRS has low density in frequency domain and high density in time domain.
- PTRS is associated with one DMRS port during transmission. Moreover it is confined to scheduled BW and duration used for NR-PDSCH/NR-PUSCH
- The NR system typically maps the PTRS information to a few subcarriers per symbol because the phase rotation affects all sub-carriers within an OFDM symbol equally but shows low correlation from symbol to symbol
- The system configures the PTRS depending on the quality of the oscillators, carrier frequency, Sub Carrier Spacing, and modulation and coding schemes that the transmission uses

Sounding Reference Signal (SRS)

As a UL-only signal, the SRS is transmitted by the UE to help the **gNB** obtain the channel state information (CSI) for each user. Channel State Information describes how the NR signal propagates from the UE to the gNB and represents the combined effect of scattering, fading, and power decay with distance. The system uses the SRS for resource scheduling, link adaptation, Massive MIMO, and beam management.

- SRS refers to Sounding Reference signal and uplink only signal.
- It is configured specific to UE
- In time domain, it spans 1/2/4 consecutive symbols which are mapped within last six symbols of the slot
- Multiple SRS symbols allow coverage extensionally increased in
- The design of SRS and its frequency hopping mechanisms frame as the section Labout

Channel State Information Reference Signarp (CSPRS) this site is shared public. By using this site, you agree to its use of cookie.

As a DL-only signal, the CSI-RS the UE receives is used to testimate the channel and report channel quality information back to the gNB. During MIMO operations, NR uses different antenna approaches based on the carrier frequency. At lower frequencies, the system uses a Got it!

modest number of active antennas for MU-MIMO and adds FDD operations. In this case, the UE needs the CSI-RS to calculate the CSI and report it back in the UL direction.

- CSI-RS refers to channel state information reference signal and these signals are downlink only signal.
- It is used for DL CSI acquisition.
- Used for RSRP measurements used during mobility and beam management
- Also used for frequency/time tracking, demodulation and UL reciprocity based precoding
- CSI-RS is configured specific to UE, but multiple users can also share the same resource
- 5G NR standard allows high level of flexibility in CSI-RS configurations, a resource can be configured with up to 32 ports.
- CSI-RS resource may start at any OFDM symbol of the slot and it usually occupies 1/2/4 OFDM symbols depending upon configured number of ports.
- CSI-RS can be periodic, semi-persistent or aperiodic (due to DCI triggering)
- For time/frequency tracking, CSI-RS can either be periodic or aperiodic. It is transmitted in bursts of two or four symbols which are spread across one or two slots

References:

3GPP TS 38.211, TS 38.212, TS 38.213

3GPP Release 15 (http://www.techplayon.com/tag/3gpp-release-15/) Tagged

5G (http://www.techplayon.com/tag/5g/)

5G Access (http://www.techplayon.com/tag/5g-access/)

5G and 4G Comparison (http://www.techplayon.com/tag/5g-and-4g-comparison/)

5G Course (http://www.techplayon.com/tag/5g-course/)

5G NR Physical Channels (http://www.techplayon.com/tag/5g-nr-physical-channels/)

5G NR Reference Signals (http://www.techplayon.com/tag/5g-nr-reference-signals/)

Interview Questions (http://www.techplayon.com/tag/interview-questions/)

New Radio (http://www.techplayon.com/tag/new-radio/)

← Accent Systems Solution: IOT Tracker with 5G NR Bandwidth Part (BWP) services, to analyze traffic. Infomation about LTE and Beacon Technologies (http://www.techplayon.com/accent-systemssolution-iot-tracker-with-lte-and-beacontechnologies/)

This website uses cookies to deliver its your use of this site is shared public. By using this site, you agree to its use of cookie.

Learn more (http://livetrafficfeed.com/gdpr)

HIT COUNTER



(//livetrafficfeed.com/live/techplayon.com)

SUBSCRIBE TO OUR NEWSLETTER

Email *		

Subscribe!

FOLLOW US ON LINKEDIN



LIVE TRAFFIC

Live Traffic Feed



This website uses cookies to deliver its services, to analyze traffic. Infomation about your use of this site is shared public. By using this site, you agree to its use of cookie.

Learn more (http://livetrafficfeed.com/gdpr)



Radios- Self Interference Cancellat (http://www.techplayon.com/5g-full-duplex-radios-self-interference-cancellation/)' 3 mins ago

A visitor from **Dhahran**, **Ash sharqiyah** viewed '5G NR Terminologies - Subcarrier Spacing, Fram-Sub

(http://www.techplayon.com/understa nding-basic-5g-nr-terminologiessubcarrier-spacing-frame-andsubframe-slot-and-ofdm-symbols/)' 4 mins ago

Real-time

OTHER POST

5G Master Information Block (NR-MIB) (http://www.techplayon.com/5g-nr-master-information-block-nr-mib/)

RSSI (Received Signal Strength Indicator) (http://www.techplayon.com/rssi/)

Smart Antennas and Beam-forming, Understanding with GNU: Part 3

(http://www.techplayon.com/smart-antennas-beam-forming-understanding-gnu-part-3/)

Vendor Agnostic SON solution for Hyper Dense Wi-Fi Deployments

(http://www.techplayon.com/hybrid-vendor-agnostic-son-solution-wi-fi/)

VoLTE Cell Capacity- Calculating Packet Size, PRBs and No. of Users (http://www.techplayon.com/2286-2/)

Insights of Mobile Virtual Network Operator (MVNO) with Allan Rasmussen (http://www.techplayon.com/insights-mobile-virtual-network-operator-mvno-allan-rasmussen/)

KPI Requirements for Next Generation Access Technologies

(http://www.techplayon.com/kpi-requirements-for-next-generation-access-technologies/)

LTE Base Station Classifications (http://www.techplayon.com/base-station-classifications/)

5G NR BWP Types and BWP Operations (http://www.techplayon.com/5g-nr-bwp-types-and-bwp-operations/)

Network-2020: Discussing Role of LTE-U/LAA,Indoor Small Cells and IOT with Mr. Oscar Bexell (http://www.techplayon.com/network-2020-discussing-role-of-lte-ulaaindoor-small-cells-and-iot-with-mr-oscar-bexell/)

This website uses cookies to deliver its

Proudly powered by WordPress (http://wordpress.org/permices, to analyze traffic. Infomation about your use of this site is shared public. By

(http://athemes.com/theme/newsanchor) by aThemes.using this site, you agree to its use of cookie.

Learn more (http://livetrafficfeed.com/gdpr)