

Operation Contracts

Table of Contents:

SSD: Login	4
SSD: Registration	5
Verify Account	6
SSD: Browsing Message Board	10
SSD: Posting a Message	15
SDD: Browsing Account	19
SSD: Change Settings	20
SSD: Recover Password	22
SSD: Delete Account	27
SSD : Leave Review	28
SSD: Cancel Trip	29
SSD: Edit Trip	30
C.D. Message	31
C.D. Trip	32
C.D. User	34
C.D. Vehicle	35
C.D. Message Table	36
C.D. User Table	38
C.D. Control Panel	40
C.D. Message TableController	41
C.D. Panel Controller	45
C.D. IOBuffers	46
C.D. Shutdown	47
C.D. User TableController	48
C.D. Driver_VehicleInfoGUI	50
C.D. HomePage GUI	51

C.D. LoginGUI	52
C.D. MessageBoard GUI	53
C.D. Message GUI	54
C.D. Register GUI	55
C.D. User GUI	56

SSD: Login

Operation: 1: Login Attempt

Cross References: Use Cases: Login

Preconditions: - There was a Login Attempt underway

Postconditions: - A Login Attempt instance was associated with the current Login

- The Client Software received a Login Attempt request

Operation: 2: Login Info

Cross References: Use Cases: Login

Preconditions: - There was a Login Attempt underway

- The Client Software received a Login Attempt request

Postconditions: - The Client Software received the User's Login Information

Operation: 2.2 Login Request

Cross References: Use Cases: Login

Preconditions: - There was a Login Attempt underway

- The Client Software received Login Information

Postconditions: - The Server received the Login Request and Login Information

SSD: Registration

Operation:	3: Registration Attempt
Cross References:	Use Cases: Registration
Preconditions:	- There was a current Registration Attempt underway
Postconditions:	- A new Registration Attempt was created and associated with the current Registration - A Registration Attempt request was received by the Client Software
Operation:	3.1: Registration Form
Cross References:	Use Cases: Login
Preconditions:	- There was a Login Attempt underway - A Registration Attempt request was received by the Client Software
Postconditions:	- The Client Software displayed Registration Form
Operation:	4: Registration Info
Cross References:	Use Cases: Login
Preconditions:	- There was a Login Attempt underway - The Client Software received a Registration Attempt
Postconditions:	- Registration Information was received by the Client Software

Operation:	4.1: Invalid Info
Cross References:	Use Cases: Registration
Preconditions:	<ul style="list-style-type: none"> - There was a current Registration Underway - The Client Software received the Registration Attempt state
Postconditions:	<ul style="list-style-type: none"> - The current Registration Attempt instance was deleted - A new Registration Attempt instance was created and was associated with Registration - Registration Page was reloaded

Verify Account

Operation:	4.2: Verify Email
Cross References:	Use Cases: Registration, Re-Verify Account
Preconditions:	<ul style="list-style-type: none"> - There was a current Registration Underway - Server received Registration Attempt request
Postconditions:	<ul style="list-style-type: none"> - SMTP received a request to Verify Email

Operation:	4.3: Listen {5 min}
Cross References:	Use Cases: Registration, Re-Verify Account
Preconditions:	<ul style="list-style-type: none"> - There was a current Registration Underway - SMTP requested email verification
Postconditions:	<ul style="list-style-type: none"> - POP3 Listened for communication for 5 minutes

Operation: 5: Valid Reply

Cross References: Use Cases: Registration, Re-Verify Account

Preconditions: - There was a current Registration Underway
- POP3 received communication

Postconditions: - Server received Valid Reply from POP3

Operation: 5.1: Registration Request

Cross References: Use Cases: Registration, Re-Verify Account

Preconditions: - There was a current Registration Underway
- Client Software received Registration Attempt request

Postconditions: - Server had received Registration Attempt request

Operation: 5.2: Registration Success

Cross References: Use Cases: Registration, Re-Verify Account

Preconditions: - There was a current Registration Underway
- Server received Valid Reply from POP3

Postconditions: - Registration Attempt was set to Success
- Client Software received Registration Attempt state

Operation: 5.3: Report Success

Cross References: Use Cases: Registration, Re-Verify Account

Preconditions: - There was a current Registration Underway
- The Client Software received Registration Attempt state

Postconditions: - Registration Successful notification was displayed

Operation: 5.3: Registration Failure

Cross References: Use Cases: Registration, Re-Verify Account

Preconditions:

- There was a current Registration Underway
- Server received No Valid Reply from POP3

Postconditions:

- Registration Attempt state was set to failure
- Client Software received Registration Attempt state

Operation: 5.3.1: Report Failure

Cross References: Use Cases: Registration, Re-Verify Account

Preconditions:

- There was a current Registration Underway
- Client Software received Registration Attempt state

Postconditions:

- Registration Failed notification was displayed
- Registration Page was reloaded

Operation: 6: No Valid Reply

Cross References: Use Cases: Registration, Re-Verify Account

Preconditions:

- There was a current Registration Underway
- POP3 did not receive a reply

Postconditions:

- Server received No Valid Reply from POP3

Operation: 6.1: Registration Failure

Cross References: Use Cases: Registration, Re-Verify Account

Preconditions:

- There was a current Registration Underway
- Server received No Valid Reply from POP3

Postconditions:

- Registration Attempt state was set to failure
- Client Software received Registration Attempt state

Operation: 6.1.1: Report Failure

Cross References: Use Cases: Registration, Re-Verify Account

Preconditions:

- There was a current Registration Underway
- Client Software received Registration Attempt state

Postconditions:

- Registration Failed notification was displayed
- Registration Page was reloaded

SSD: Browsing Message Board

Operation:	7: Load Board
Cross References:	Use Cases: Browsing Message Board
Preconditions:	- User browsed the Message Board
Postconditions:	- The Load Board instance was associated with the current Message Board - Client Software received request to Load Board
Operation:	7.1: Request Board
Cross References:	Use Cases: Browsing Message Board
Preconditions:	- User browsed the Message Board - Client Software received request to Load Board
Postconditions:	- Server received Request Board request
Operation:	7.2: Message Board
Cross References:	Use Cases: Browsing Message Board
Preconditions:	- User browsed the Message Board - Server received Request Board request
Postconditions:	- A Message Board state was returned to the Client Software

Operation: 7.3: Drawn Message Board

Cross References: Use Cases: Browsing Message Board

Preconditions:

- User browsed the Message Board
- Client Software received Request Board request

Postconditions:

- The Board's Messages were loaded according to the Messages' Headers

Operation: 8: Sort/Filter Board

Cross References: Use Cases: Browsing Message Board

Preconditions:

- User browsed the Message Board

Postconditions:

- The Client Software received request to Sort/Filter Board

Operation: 8.1: Board's Messages' Headers

Cross References: Use Cases: Browsing Message Board

Preconditions:

- User browsed the Message Board
- The Client Software received a request to Sort/Filter the Board

Postconditions:

- The Board's Messages were loaded according to the Messages' Headers and the sort method

Operation: 9: Load Message

Cross References: Use Cases: Browsing Message Board

Preconditions:

- User browsed the Message Board

Postconditions:

- Client Software got the request to Load Message

Operation:	9.1: Drawn Message
Cross References:	Use Cases: Browsing Message Board
Preconditions:	<ul style="list-style-type: none">- User browsed the Message Board- Client Software gets request to Load Message
Postconditions:	<ul style="list-style-type: none">- The Client Software implemented the MessageHeaders to display Post on screen
Operation:	10: Accept Trip
Cross References:	Use Cases: Browsing Message Board
Preconditions:	<ul style="list-style-type: none">- There was a Board Request was underway
Postconditions:	<ul style="list-style-type: none">- The Client Software got the request to Accept Offer
Operation:	10.1: Sign Up for Trip
Cross References:	Use Cases: Browsing Message Board
Preconditions:	<ul style="list-style-type: none">- User browsed the Message Board- The Client Software got the request to Accept Trip
Postconditions:	<ul style="list-style-type: none">- The Server received request to Accept Offer- A new Sign Up instance was created and associated with the Message Board

Operation: 10.2: Success

Cross References: Use Cases: Browsing Message Board

Preconditions: - User browsed the Message Board

Postconditions: - Sign Up state was assigned Success
- Client Software received Sign Up State

Operation: 10.3: Report Success

Cross References: Use Cases: Browsing Message Board

Preconditions: - User browsed the Message Board

Postconditions: - Client Software displayed Successful Signup notification

Operation: 10.3: Failure

Cross References: Use Cases: Browsing Message Board

Preconditions: - User browsed the Message Board

Postconditions: - Sign Up State was assigned Failure
- Client Software received Sign up state

Operation: 10.3.1 Report Failure

Cross References: Use Cases: Browsing Message Board

Preconditions: - User browsed the Message Board
- Client Software received Sign up state

Postconditions: - Client Software displayed Signup Failed notification

Operation: 10.3.2: Request Board

Cross References: Use Cases: Browsing Message Board

Preconditions: - User browsed the Message Board

Postconditions: - Client Software requested board instance

Operation: 10.3.3: Message Board

Cross References: Use Cases: Browsing Message Board

Preconditions: - User browsed the Message Board

- Client Software requests board instance

Postconditions: - Board Instance was received by the Client Software

SSD: Posting a Message

Operation:	11: Post a Message
Cross References:	Use Cases: Posting a Message, Posting Offer, Posting Request, Posting Service, Accepting Offer, Accepting Request, Accepting Service
Preconditions:	- There was a Post a Message Request underway
Postconditions:	- The Client Software received a Post a Message request
Operation:	11.1: Trip Form
Cross References:	Use Cases: Posting a Message, Posting Offer, Posting Request, Posting Service, Accepting Offer, Accepting Request, Accepting Service
Preconditions:	- There was a Post a Message Request underway - The Client Software received a Post a Message request
Postconditions:	- A Trip Form was displayed on screen
Operation:	12: Trip Info
Cross References:	Use Cases: Posting a Message, Posting Offer, Posting Request, Posting Service, Accepting Offer, Accepting Request, Accepting Service
Preconditions:	- There was a Post a Message Request underway
Postconditions:	- The Client Software received Trip Information

Operation:	12.1: Invalid Info
Cross References:	Use Cases: Posting a Message, Posting Offer, Posting Request, Posting Service, Accepting Offer, Accepting Request, Accepting Service
Preconditions:	<ul style="list-style-type: none">- There was a Post a Message Request underway- The Client Software received Trip Information
Postconditions:	<ul style="list-style-type: none">- The Post a Message request was deleted- A new instance of Post a Message request was created and associated with Post a Message- Trip Form was reloaded- Invalid Info error was displayed
Operation:	12.2: Add Message
Cross References:	Use Cases: Posting a Message, Posting Offer, Posting Request, Posting Service, Accepting Offer, Accepting Request, Accepting Service
Preconditions:	<ul style="list-style-type: none">- There was a Post a Message Request underway- The Client Software received Trip Info
Postconditions:	<ul style="list-style-type: none">- The Server received Trip Info

Operation:	12.3: Success
Cross References:	Use Cases: Posting a Message, Posting Offer, Posting Request, Posting Service, Accepting Offer, Accepting Request, Accepting Service
Preconditions:	<ul style="list-style-type: none">- There was a Post a Message Request underway- The Server received Trip Info
Postconditions:	<ul style="list-style-type: none">- Trip Info was recorded by Server and added to the Message Board
Operation:	12.4: Report Success
Cross References:	Use Cases: Posting a Message, Posting Offer, Posting Request, Posting Service, Accepting Offer, Accepting Request, Accepting Service
Preconditions:	<ul style="list-style-type: none">- There was a Post a Message Request underway- The Client Software received Post a Message success state
Postconditions:	<ul style="list-style-type: none">- The Client Software reported Success
Operation:	12.4: Failure
Cross References:	Use Cases: Posting a Message, Posting Offer, Posting Request, Posting Service, Accepting Offer, Accepting Request, Accepting Service
Preconditions:	<ul style="list-style-type: none">- There was a Post a Message Request underway- The Server received Trip Info
Postconditions:	<ul style="list-style-type: none">- The Server failed to add Trip Info to the Message Board

Operation:	12.4.1: Report Failure
Cross References:	Use Cases: Posting a Message, Posting Offer, Posting Request, Posting Service, Accepting Offer, Accepting Request, Accepting Service
Preconditions:	<ul style="list-style-type: none">- There was a Post a Message Request underway- The Client Software received Post a Message Failure state
Postconditions:	<ul style="list-style-type: none">- The Client Software reported Failure

SDD: Browsing Account

Operation:	13: Check User's Profile
Cross References:	Use Cases: Browsing Account
Preconditions:	- A User was Browsing their Account
Postconditions:	- The Client Software received request to Check Profile
Operation:	13.2 Request User
Cross References:	Use Cases: Browsing Account
Preconditions:	- A User was Browsing their Account - The Client Software received request to Check Profile
Postconditions:	- The Server received request to return User
Operation:	13.2: User
Cross References:	Use Cases: Browsing Account
Preconditions:	- A User was Browsing their Account - The Server received request to return User
Postconditions:	- The Server returned User to the Client Software
Operation:	13.3: Draw Profile
Cross References:	Use Cases: Browsing Account
Preconditions:	- A User was Browsing their Account - The Server returned User to the Client Software
Postconditions:	- The Client Software displayed the User's profile on screen

SSD: Change Settings

Operation:	14: Change Settings
Cross References:	Use Cases: Change Settings
Preconditions:	- There was a Change Setting request underway
Postconditions:	- The Client Software received a request to Change Settings
Operation:	14.1: Settings Form
Cross References:	Use Cases: Change Settings
Preconditions:	- There was a Change Setting request underway - The Client Software received a request to Change Settings
Postconditions:	- The Client Software displayed Setting Form to the screen
Operation:	15: Settings Info
Cross References:	Use Cases: Change Settings
Preconditions:	- There was a Change Setting request underway - The Client Software displayed Setting Form to the screen
Postconditions:	- The Client Software received Settings Info from Setting Form

Operation: 15.1: Invalid Info

Cross References: Use Cases: Change Settings

Preconditions: - There was a Change Setting request underway

Postconditions: - The Change Settings request was deleted

- A new Changes Settings request was created and associated with the current Settings

- Settings Form was displayed

- Failed to change settings error displayed

Operation: 12.4.1: Report Success

Cross References: Use Cases: Change Settings

Preconditions: - There was a Change Setting request underway

Postconditions: - The Client Software reported Success state to User

SSD: Recover Password

Operation:	16: Recover Password
Cross References:	Use Cases: Recover Password
Preconditions:	- There was a Recover Password request underway
Postconditions:	- The Client Software got a request to Recover Password
Operation:	16.1: Verify Email
Cross References:	Use Cases: Recover Password
Preconditions:	- There was a Recover Password request underway - The Client Software got a request to Recover Password
Postconditions:	- SMTP sent out Verification Email
Operation:	16.2: Listen
Cross References:	Use Cases: Recover Password
Preconditions:	- There was a Recover Password request underway - SMTP sent out Verification Email
Postconditions:	- POP3 listened for a reply

Operation: 17: Valid Reply

Cross References: Use Cases: Recover Password

Preconditions: - There was a Recover Password request underway
- POP3 Heard a reply

Postconditions: - POP3 sent Valid Reply state to Client Software

Operation: 17.1: Password Reset Form

Cross References: Use Cases: Recover Password

Preconditions: - There was a Recover Password request underway

Postconditions: - The Client Software displayed the Password Reset Form to screen

Operation: 18: Password info

Cross References: Use Cases: Recover Password

Preconditions: - There was a Recover Password request underway

Postconditions: - The Client Software received Password Reset Information

Operation: 18.1: Invalid Info

Cross References: Use Cases: Recover Password

Preconditions:

- There was a Recover Password request underway
- The Client Software received Password Reset Information

Postconditions:

- The current Password Reset request was deleted
- A new instance of Password Reset request was created and associated with the current Password Reset
- User profile was displayed
- Failure to Reset Password was displayed

Operation: 18.2: Change PassHash

Cross References: Use Cases: Recover Password

Preconditions:

- There was a Recover Password request underway

Postconditions:

- The Server received a new PassHash for the current User
- User PassHash updated

Operation: 18.3: Success

Cross References: Use Cases: Recover Password

Preconditions:

- There was a Recover Password request underway

Postconditions:

- The Client Software received Password Reset Success state

Operation: 18.4: Report Success

Cross References: Use Cases: Recover Password

Preconditions:

- There was a Recover Password request underway
- The Client Software received Password Reset Success state

Postconditions:

- The Client Software reported Password Reset Success to the User

Operation: 18.4: Failure

Cross References: Use Cases: Recover Password

Preconditions:

- There was a Recover Password request underway

Postconditions:

- The Client Software received Password Reset Fail state

Operation:

Cross References: Use Cases: Recover Password

Preconditions:

- There was a Recover Password request underway
- The Client Software received Password Reset Fail state

Postconditions:

- The Client Software reported Password Reset Failure to the User

Operation: 19: Invalid Reply

Cross References: Use Cases: Recover Password

Preconditions:

- There was a Recover Password request underway
- SMTP sent out a email
- POP3 Hears nothing

Postconditions:

- POP3 reported Invalid Reply to Server

Operation: 19.1: Failure

Cross References: Use Cases: Recover Password

Preconditions:

- There was a Recover Password request underway
- POP3 reports Invalid Reply to Server

Postconditions:

- The Client Software received the Reset Password fail state

Operation: 19.1.1: Report Failure

Cross References: Use Cases: Recover Password

Preconditions:

- There was a Recover Password request underway
- The Client Software received the Reset Password fail state

Postconditions:

- The Client Software displayed Reset Password Failure to screen
- The current Reset Password request was deleted
- The User's page was loaded

SSD: Delete Account

Operation: 20: Delete Account

Cross References: Use Cases: Delete Account

Preconditions: - The Client Software received a Delete Account Request

Postconditions: - The Server received a Delete Account Request

Operation: 21: Confirm

Cross References: Use Cases: Delete Account

Preconditions: - The Client Software received a Delete Account request

Postconditions: - A confirmation window appeared on screen

Operation: 21.1: Delete Account

Cross References: Use Cases: Delete Account

Preconditions: - A User account with UUID exists
- A UserTable is Initialized

Postconditions: - A User with a UUID was removed from the UserTable

SSD : Leave Review

Operation:	Add Rating
Cross References:	Use Cases: Leave Review
Preconditions:	- The User requests to add a Rating
Postconditions:	- The Client Software received the Add Rating request
Operation:	Insert Rating
Cross References:	Use Cases: Leave Review
Preconditions:	- The Client Software received the Add Rating request
Postconditions:	- The Server had received the Add Rating request

SSD: Cancel Trip

Operation: Cancel Trip

Cross References: Use Cases: Cancel Trip

Preconditions: - User requests to Cancel Trip

Postconditions: - Client Software received request to Cancel Trip

Operation: Confirm

Cross References: Use Cases: Cancel Trip

Preconditions: - Client Software received request to Cancel Trip

Postconditions: - A Confirm Cancel window was displayed to the screen

Operation: Cancel Trip

Cross References: Use Cases: Cancel Trip

Preconditions: - Client Software requests to Cancel Trip

Postconditions: - Server received the request to cancel trip

- Trip was canceled

SSD: Edit Trip

Operation:	Edit a Message
Cross References:	Use Cases: Edit Trip
Preconditions:	- The User requests to Edit a Message
Postconditions:	- The Client Software received a request to Edit a Message
Operation:	Message info
Cross References:	Use Cases: Edit Trip
Preconditions:	- The Client Software received a request to Edit a Message
Postconditions:	- New Message info was sent to the Client Software
Operation:	Overwrite Message
Cross References:	Use Cases: Edit Trip
Preconditions:	- The Client Software received a request to Edit a Message
Postconditions:	- The Server Overwrites the Message with the new one provided by the Client Software

C.D. Message

Operation:	Message(creator: User)
Cross References:	Use Cases: Message
Preconditions:	- Void
Postconditions:	- A new instance of Message was created

C.D. Trip

Operation: Trip(driver: User, message: Message, originTime: Date,
passengerCount: Integer)

Cross References: Use Cases: Trip

Preconditions: - Void

Postconditions: - A new instance of Trip was created

Operation: insertRider(user: User)

Cross References: Use Cases: Trip

Preconditions: - Void

Postconditions: - rider was inserted into riders, if successful true was returned
otherwise false

Operation: insertRequirement(requirement: String)

Cross References: Use Cases: Trip

Preconditions: - Void

Postconditions: - requirement was inserted into requirements

Operation: removeRider(user: User)

Cross References: Use Cases: Trip

Preconditions: - riders was initialized

Postconditions: - rider was removed from riders if it was there

Operation: `removeRequirement(requirement: String)`

Cross References: Use Cases: Trip

Preconditions: - requirements was initialized

Postconditions: - requirement was removed from requirements if it was there

C.D. User

Operation: User(email: String, password: String)

Cross References: Use Cases: User

Preconditions: - Void

Postconditions: - a new User instance was initialized
- email and password were updated

Operation: insertRating(rating: Integer)

Cross References: Use Cases: User

Preconditions: A User exists

Postconditions: The User's rating is changed

Operation: insertNotification(notification: Message)

Cross References: Use Cases: User

Preconditions: A User exists

Postconditions: The User now has a notification

Operation: removeNotification(notification: Message)

Cross References: Use Cases: User

Preconditions: A User exists and has a notification

Postconditions: The User no longer has a notification

C.D. Vehicle

Operation: Vehicle(model: String, passengerCap: Integer)

Cross References: Use Cases: Vehicle

Preconditions: A Vehicle does not exist

Postconditions: A Vehicle exists

C.D. Message Table

Operation:	MessageTable()
Cross References:	Use Cases: Message Table
Preconditions:	- Void
Postconditions:	- a new MessageBoard instance was initialized
Operation:	insert(message: Message)
Cross References:	Use Cases: Message Table
Preconditions:	- messageBoard was initialized
Postconditions:	- message was inserted into MessageBoard if it was not there
Operation:	removeAll(user: User)
Cross References:	Use Cases: Message Table
Preconditions:	- A Message Table exists
Postconditions:	- the corresponding messages were removed from message table
Operation:	remove(message: Message)
Cross References:	Use Cases: Message Table
Preconditions:	A Message Table exists
Postconditions:	the corresponding message was removed from the message table

Operation: checkFor(message: Message)

Cross References: Use Cases: Message Board

Preconditions: - messageBoard was initialized

Postconditions: - true was returned if the corresponding message was there, false otherwise

Operation: fromUser(user: User)

Cross References: Use Cases: Message Board

Preconditions: - messageBoard was initialized

Postconditions: - a Collection of the messages with the user was returned

Operation: pushReminders(date, Date)

Cross References: Use Cases: Message Table

Preconditions: A Message Table exists

Postconditions: Reminders are pushed to each user

C.D. User Table

Operation:	UserTable()
Cross References:	Use Cases: User Table
Preconditions:	- Void
Postconditions:	- a new UserTable instance was initialized
Operation:	insert(user: User)
Cross References:	Use Cases: User Table
Preconditions:	- user was initialized
Postconditions:	- user was inserted into the UserTable if it was not already there
Operation:	remove(user: User)
Cross References:	Use Cases: User Table
Preconditions:	- UserTable was initialized
Postconditions:	- A User was removed from the UserTable
Operation:	checkFor(UUID: String)
Cross References:	Use Cases: User Table
Preconditions:	- UserTable was initialized
Postconditions:	- If User with UUID was in UserTable true was returned otherwise false

Operation:	login(UUID: String, password: String)
Cross References:	Use Cases: User Table
Preconditions:	- void
Postconditions:	- a User object was returned if there was such a UUID and password was correct
Operation:	authenticate(user: User)
Cross References:	Use Cases: User Table
Preconditions:	- A User exists within the UserTable
Postconditions:	- The User is authenticated to be contained within the UserTable
Operation:	logout(user: User)
Cross References:	Use Cases: User Table
Preconditions:	- A User is logged in
Postconditions:	- A User is logged out
Operation:	generateToken()
Cross References:	Use Cases: User Table
Preconditions:	- A User does not have a UUID token
Postconditions:	- A User now has a random UUID token

C.D. Control Panel

Operation:	ControlPanel(file: File)
Cross References:	Use Cases: Control Panel
Preconditions:	- Void
Postconditions:	- A Control Panel was initialized

C.D. Message TableController

Operation: drawBoard(board: MessageBoard)

Cross References: Use Cases: UserTableInterface

Preconditions: - MessageBoard was initialized

Postconditions: - MessageBoard was drawn onto screen

Operation: drawReview(board: MessageBoard, header: MessageHeader)

Cross References: Use Cases: UserTableInterface

Preconditions: - MessageBoard and MessageHeader were initialized

Postconditions: - Review was drawn onto screen

Operation: drawReminder(board: MessageBoard, header: MessageHeader)

Cross References: Use Cases: UserTableInterface

Preconditions: - MessageBoard and MessageHeader were initialized

Postconditions: - Reminder was drawn onto screen

Operation: drawRequest(board: MessageBoard, header: MessageHeader)

Cross References: Use Cases: UserTableInterface

Preconditions: - MessageBoard and MessageHeader were initialized

Postconditions: - Request was drawn onto screen

Operation: drawOffer(board: MessageBoard, header: MessageHeader)

Cross References: Use Cases: UserTableInterface

Preconditions: - MessageBoard and MessageHeader were initialized

Postconditions: - Offer was drawn onto screen

Operation: drawService(board: MessageBoard, header: MessageHeader)

Cross References: Use Cases: UserTableInterface

Preconditions: - MessageBoard and MessageHeader were initialized

Postconditions: - Service was drawn onto screen

Operation: postReview(board: MessageBoard)

Cross References: Use Cases: UserTableInterface

Preconditions: - MessageBoard was initialized

Postconditions: - Review was stored into MessageBoard

Operation: postRequest(board: MessageBoard)

Cross References: Use Cases: UserTableInterface

Preconditions: - MessageBoard was initialized

Postconditions: - Request was stored into MessageBoard

Operation: postOffer(board: MessageBoard)

Cross References: Use Cases: UserTableInterface

Preconditions: - MessageBoard was initialized

Postconditions: - Offer was stored into MessageBoard

Operation: postService(board: MessageBoard)

Cross References: Use Cases: UserTableInterface

Preconditions: - MessageBoard was initialized

Postconditions: - Service was stored into MessageBoard

Operation: acceptRequest(board: MessageBoard, header: MessageHeader)

Cross References: Use Cases: UserTableInterface

Preconditions: - MessageBoard and MessageHeader were initialized

Postconditions: - Request of MessageHeader was accepted and stored into MessageBoard

Operation: acceptOffer(board: MessageBoard, header: MessageHeader)

Cross References: Use Cases: UserTableInterface

Preconditions: - MessageBoard and MessageHeader were initialized

Postconditions: - Offer of MessageHeader was accepted and stored into MessageBoard

Operation: acceptService(board: MessageBoard, header: MessageHeader)

Cross References: Use Cases: UserTableInterface

Preconditions: - MessageBoard and MessageHeader were initialized

Postconditions: - Service of MessageHeader was accepted and stored into MessageBoard

Operation:	pushReminders()
Cross References:	Use Cases: UserTableInterface
Preconditions:	- MessageBoard was initialized
Postconditions:	- For each person attending a Trip, a Reminder is sent to their email
Operation:	filterByUser(board: MessageBoard, UUID: String)
Cross References:	Use Cases: UserTableInterface
Preconditions:	- MessageBoard was initialized
Postconditions:	- MessageBoard is filtered by UUID of all existing Users
Operation:	removeFinished()
Cross References:	Use Cases: UserTableInterface
Preconditions:	- MessageBoard was initialized
Postconditions:	- If a Trip is completed the trip is removed from the MessageBoard

C.D. Panel Controller

Operation:	PanelController()
Cross References:	Use Cases: Panel Controller
Preconditions:	- Void
Postconditions:	- A Panel Controller was initialized
Operation:	changeFrame(newFrame: JPanel)
Cross References:	Use Cases: Control Panel
Preconditions:	- A Panel Controller exists
Postconditions:	- The current GUI frame was changed to newFrame
Operation:	closeFrame()
Cross References:	Use Cases: Control Panel
Preconditions:	- A Frame is open
Postconditions:	- Shuts a Frame down and removes it from the Panel Controller

C.D. IOBuffers

Operation:	IOBuffers(File file)
Cross References:	Use Cases: IOBuffers
Preconditions:	- An IOBuffers object does not exist
Postconditions:	- An IOBuffers object has been initialized

C.D. Shutdown

Operation: Shutdown()

Cross References: Use Cases: Shutdown

Preconditions: - An Shutdown object does not exist

Postconditions: - An Shutdown object has been initialized

C.D. User TableController

Operation: login(table: UserTable)

Cross References: Use Cases: UserTableInterface

Preconditions: - Table was initialized

Postconditions: - UserTableInterface was initialized

Operation: register(table: UserTable)

Cross References: Use Cases: UserTableInterface

Preconditions: - UserTable was initialized

Postconditions: - A User was Registered with a UUID, email, password, and profile
Picture into the UserTable

Operation: remove(table: UserTable, user: User)

Cross References: Use Cases: UserTableInterface

Preconditions: - UserTable was initialized

Postconditions: - A User with a UUID was removed from the UserTable

Operation: recoverPassword(table: UserTable, user: User)

Cross References: Use Cases: UserTableInterface

Preconditions: - UserTable was initialized

Postconditions: - A User with a UUID was sent a recover password email

Operation: reverifyAll(table: UserTable)

Cross References: Use Cases: UserTableInterface

Preconditions: - UserTable was initialized

Postconditions: - Verification emails were sent to all existing Users

Operation: drawProfile(table: UserTable. UUID: String)

Cross References: Use Cases: UserTableInterface

Preconditions: - UserTable is was initialized

Postconditions: - User Profile of a User with a UUID was loaded onto the screen

C.D. Driver_VehicleInfoGUI

Operation: Driver_VehicleInfoGUI(cp: ControlPanel)

Cross References: Use Cases: Driver_VehicleInfoGUI

Preconditions: - A ControlPanel exists, a Driver_VehicleInfoGUI does not exist

Postconditions: - A Driver_VehicleInfoGUI was initialized

Operation: initComponents()

Cross References: Use Cases: Driver_VehicleInfoGUI

Preconditions: - A Driver_VehicleInfoGUI exists with no values

Postconditions: - A Driver_VehicleInfoGUI exists with values

C.D. HomePage GUI

Operation:	HomePageGUI()
Cross References:	Use Cases: HomePage GUI
Preconditions:	- A HomePage GUI does not exist
Postconditions:	- A HomePage GUI exists
Operation:	initComponents()
Cross References:	Use Cases: HomePage GUI
Preconditions:	- A HomePage GUI exists with no values
Postconditions:	- A HomePage GUI exists with values

C.D. LoginGUI

Operation: LoginGUI()
Cross References: Use Cases: LoginGUI
Preconditions: - A LoginGUI does not exist
Postconditions: - A LoginGUI exists

Operation: initComponents()
Cross References: Use Cases: LoginGUI
Preconditions: - A LoginGUI exists with no values
Postconditions: - A LoginGUI exists with values

C.D. MessageBoard GUI

Operation:	MessageBoardGUI()
Cross References:	Use Cases: MessageBoard GUI
Preconditions:	- A Message Board GUI does not exist
Postconditions:	- A Message Board GUI exists
Operation:	initComponents()
Cross References:	Use Cases: MessageBoard GUI
Preconditions:	- A Message Board GUI exists with no values
Postconditions:	- A Message Board GUI exists with values

C.D. Message GUI

Operation:	MessageGUI()
Cross References:	Use Cases: Message GUI
Preconditions:	- A Message GUI does not exist
Postconditions:	- A Message GUI exists
Operation:	initComponents()
Cross References:	Use Cases: Message GUI
Preconditions:	- A Message GUI exists with no values
Postconditions:	- A Message GUI exists with values

C.D. Register GUI

Operation:	RegisterGUI()
Cross References:	Use Cases: Register GUI
Preconditions:	- A Register GUI does not exist
Postconditions:	- A Register GUI exists
Operation:	initComponents()
Cross References:	Use Cases: Register GUI
Preconditions:	- A Register GUI exists with no values
Postconditions:	- A Register GUI exists with values

C.D. User GUI

Operation: UserGUI()

Cross References: Use Cases: User GUI

Preconditions: - A User GUI does not exist

Postconditions: - A User GUI exists

Operation: initComponents()

Cross References: Use Cases: User GUI

Preconditions: - A User GUI exists with no values

Postconditions: - A User GUI exists with values