

A thick black L-shaped frame is positioned around the text. It starts at the top-left, goes right, then down, then right again, forming a partial rectangular border around the central text.

INTRODUCTION TO JAVA PROGRAMMING VIII

CSI-3130



JDBC CONNECT JAVA TO SQL DB

<https://docs.oracle.com/javase/tutorial/essential/io/index.html>



JDBC

- The JDBC API is a Java API that can access any kind of tabular data, especially data stored in a Relational Databases
- A database is a means of storing information in such a way that information can be retrieved from it.

JDBC

- In simplest terms, a relational database shows information in tables with rows & columns.
- A **table** is referred to as a **relation**
 - *in the sense that it is a collection of objects of the same type (rows).*
- Data in a table can be related according to common keys or concepts, and the ability to retrieve related data from a table is the basis for the term relational database.
- A Database Management System (DBMS)
 - *handles the way data is stored, maintained, and retrieved.*
- Relational Database Mgmt System (RDBMS)

Architecture



- JDBC helps you to write Java applications that manage these 3 programming activities:
 1. Connect to a data source, like a database
 2. Send queries and update statements to the database
 3. Retrieve and process the results received from the database in answer to your query

Example

```
public void connectToAndQueryDatabase(String username, String password) {  
  
    Class.forName("xx.xx.Driver"); //egister driver;specific for given DB  
    Connection con = DriverManager.getConnection(  
        "jdbc:myDriver:myDatabase",  
        username, password);  
  
    Statement stmt = con.createStatement();  
    ResultSet rs = stmt.executeQuery("SELECT colA, colB FROM Table");  
  
    while (rs.next()) {  
        int x = rs.getInt("a");  
        String s = rs.getString("b");  
        float f = rs.getFloat("c");  
    }  
}
```

Many Database providers

- Divided responsibility
 1. *Java API – JDBC*
 2. *Database specialties – Driver*
 - *Custom driver.jar per a particular database*

Sample database table

■ Employee

```
table Employee (  
  Employee_Number int primary key,  
  Fistname varchar(255),  
  Lastname varchar(255),  
  Date_of_Birth date,  
  Car_Number int foreign key  
)
```

```
class Employee {  
  int employeeNumber;  
  String fistname;  
  String lastname;  
  Date dob;  
  int carNumber;  
}
```

Employee_Number	First_name	Last_Name	Date_of_Birth	Car_Number
10001	Axel	Washington	28-Aug-43	5
10083	Arvid	Sharma	24-Nov-54	null
10120	Jonas	Ginsberg	01-Jan-69	null
10005	Florence	Wojokowski	04-Jul-71	12
10099	Sean	Washington	21-Sep-66	null
10035	Elizabeth	Yamaguchi	24-Dec-59	null

SQL

- Structured Query Language (SQL) is a domain-specific language used in programming and designed for managing data held in a relational database management system (RDBMS)
 - *SELECT [columns] FROM [table] WHERE [condition]*
 - *SELECT [columns] FROM [table1] INNER JOIN [table2] ON (cond.)..*
 - *INSERT INTO [table] VALUES ([values])*
 - *UPDATE [table] SET [column1 = value1,..] WHERE [condition]*
 - *DELETE FROM [table] WHERE [condition]*

Lets apply SQL

■ Employee

```
table Employee (  
  Employee_Number int primary key,  
  Fistname varchar(255),  
  Lastname varchar(255),  
  Date_of_Birth date,  
  Car_Number int foreign key  
)
```

```
class Employee {  
  int employeeNumber;  
  String fistname;  
  String lastname;  
  Date dob;  
  int carNumber;  
}
```

Employee_Number	First_name	Last_Name	Date_of_Birth	Car_Number
10001	Axel	Washington	28-Aug-43	5
10083	Arvid	Sharma	24-Nov-54	null
10120	Jonas	Ginsberg	01-Jan-69	null
10005	Florence	Wojokowski	04-Jul-71	12
10099	Sean	Washington	21-Sep-66	null
10035	Elizabeth	Yamaguchi	24-Dec-59	null

SQL Select Statement

```
SELECT * FROM Employees
```

■ Results:

Employee_Number	First_name	Last_Name	Date_of_Birth	Car_Number
10001	Axel	Washington	28-Aug-43	5
10083	Arvid	Sharma	24-Nov-54	null
10120	Jonas	Ginsberg	01-Jan-69	null
10005	Florence	Wojokowski	04-Jul-71	12
10099	Sean	Washington	21-Sep-66	null
10035	Elizabeth	Yamaguchi	24-Dec-59	null

SQL

- Why do not we do it in Java?
- Too slow
- Java is programming language
 - *not a retrieval/modification/processing language*
- SQL more efficient
- Mathematical model
- FAST!
- Does not know the concept of objects/polymorphism ☹️

Select Statement

```
SELECT First_Name, Last_Name  
FROM Employees  
WHERE Car_Number IS NOT NULL
```

■ Results:

FIRST_NAME	LAST_NAME
Axel	Washington
Florence	Wojokowski

Original data:

Employee_Number	First_name	Last_Name	Date_of_Birth	Car_Number
10001	Axel	Washington	28-Aug-43	5
10083	Arvid	Sharma	24-Nov-54	null
10120	Jonas	Ginsberg	01-Jan-69	null
10005	Florence	Wojokowski	04-Jul-71	12
10099	Sean	Washington	21-Sep-66	null
10035	Elizabeth	Yamaguchi	24-Dec-59	null

Select Statement

```
SELECT First_Name, Last_Name  
FROM Employees  
WHERE Last_Name LIKE 'Washington%'
```

■ Results:

FIRST_NAME	LAST_NAME
Axel	Washington
Sean	Washington

Original data:

Employee_Number	First_name	Last_Name	Date_of_Birth	Car_Number
10001	Axel	Washington	28-Aug-43	5
10083	Arvid	Sharma	24-Nov-54	null
10120	Jonas	Ginsberg	01-Jan-69	null
10005	Florence	Wojokowski	04-Jul-71	12
10099	Sean	Washington	21-Sep-66	null
10035	Elizabeth	Yamaguchi	24-Dec-59	null

Select Statement

```
SELECT First_Name, Last_Name  
FROM Employees  
WHERE Car_Number = 12
```

■ Results:

FIRST_NAME	LAST_NAME
Florence	Wojokowski

Original data:

Employee_Number	First_name	Last_Name	Date_of_Birth	Car_Number
10001	Axel	Washington	28-Aug-43	5
10083	Arvid	Sharma	24-Nov-54	null
10120	Jonas	Ginsberg	01-Jan-69	null
10005	Florence	Wojokowski	04-Jul-71	12
10099	Sean	Washington	21-Sep-66	null
10035	Elizabeth	Yamaguchi	24-Dec-59	null

Join – connect two tables (over ID)

■ Cars:

Car_Number	Make	Model	Year
5	Honda	Civic DX	1996
12	Toyota	Corolla	1999

Employee:

Employee_Number	First_name	Last_Name	Date_of_Birth	Car_Number
10001	Axel	Washington	28-Aug-43	5
10083	Arvid	Sharma	24-Nov-54	null
10120	Jonas	Ginsberg	01-Jan-69	null
10005	Florence	Wojokowski	04-Jul-71	12
10099	Sean	Washington	21-Sep-66	null
10035	Elizabeth	Yamaguchi	24-Dec-59	null


```
SELECT Employees.First_Name,
       Employees.Last_Name, Cars.Make,
       Cars.Model, Cars.Year FROM Employees, Cars
WHERE Employees.Car_Number = Cars.Car_Number
```

■ Cars:

Car_Number	Make	Model	Year
5	Honda	Civic DX	1996
12	Toyota	Corolla	1999

FIRST_NAME	LAST_NAME	MAKE	MODEL	YEAR
Axel	Washington	Honda	Civic DX	1996
Florence	Wojokowski	Toyota	Corolla	1999

Employee:

Employee_Number	First_name	Last_Name	Date_of_Birth	Car_Number
10001	Axel	Washington	28-Aug-43	5
10083	Arvid	Sharma	24-Nov-54	null
10120	Jonas	Ginsberg	01-Jan-69	null
10005	Florence	Wojokowski	04-Jul-71	12
10099	Sean	Washington	21-Sep-66	null
10035	Elizabeth	Yamaguchi	24-Dec-59	null

```
SELECT Employees.First_Name,
       Employees.Last_Name, Cars.Make,
       Cars.Model, Cars.Year FROM Employees JOIN Cars
ON (Employees.Car_Number = Cars.Car_Number)
WHERE Cars.Make like 'Hon%'
```

■ Cars:

Car_Number	Make	Model	Year
5	Honda	Civic DX	1996
12	Toyota	Corolla	1999

FIRST_NAME	LAST_NAME	MAKE	MODEL	YEAR
Axel	Washington	Honda	Civic DX	1996

Employee:

Employee_Number	First_name	Last_Name	Date_of_Birth	Car_Number
10001	Axel	Washington	28-Aug-43	5
10083	Arvid	Sharma	24-Nov-54	null
10120	Jonas	Ginsberg	01-Jan-69	null
10005	Florence	Wojokowski	04-Jul-71	12
10099	Sean	Washington	21-Sep-66	null
10035	Elizabeth	Yamaguchi	24-Dec-59	null

Common SQL commands

- **Data Modification:**
- **SELECT** — used to query and display data from a database. The SELECT statement specifies which columns to include in the result set. The vast majority of the SQL commands used in applications are SELECT statements.
- **INSERT** — adds new rows to a table. INSERT is used to populate a newly created table or to add a new row (or rows) to an already-existing table.
- **DELETE** — removes a specified row or set of rows from a table
- **UPDATE** — changes an existing value in a column or group of columns in a table

Common SQL commands

- **Data Definition:**
- **CREATE TABLE** — creates a table with the column names the user provides. The user also needs to specify a type for the data in each column. Data types vary. CREATE TABLE is normally used less often than the data manipulation commands because a table is created only once, whereas adding or deleting rows or changing individual values generally occurs more frequently.
- **DROP TABLE** — deletes all rows and removes the table definition from the database.
- **ALTER TABLE** — adds or removes a column from a table. It also adds or drops table constraints and alters column attributes

JDBC structures

■ Result Sets

- *The rows that satisfy the conditions of a query are called the result set.*
- *The number of rows returned in a result set can be zero, one, or many.*

■ Cursors

- *A user can access the data in a result set one row at a time, and a cursor provides the means to do that.*
- *A cursor can be thought of as a pointer into a file that contains the rows of the result set, and that pointer has the ability to keep track of which row is currently being accessed.*

Example

```
public void connectToAndQueryDatabase(String username, String password) {  
  
    Connection con = DriverManager.getConnection(  
        "jdbc:mysql:myDatabase",  
        username,  
        password);  
  
    Statement stmt = con.createStatement();  
    ResultSet rs = stmt.executeQuery("SELECT a, b, c FROM Table1");  
  
    while (rs.next()) {  
        int x = rs.getInt("a");  
        String s = rs.getString("b");  
        float f = rs.getFloat("c");  
    }  
}
```

```

public static void viewTable(Connection con, String dbName) throws SQLException {
    Statement stmt = null;
    String query = "select COF_NAME, SUP_ID, PRICE, SALES, TOTAL "
        + "from " + dbName + ".COFFEES";
    try{
        stmt = con.createStatement();
        ResultSet rs = stmt.executeQuery(query);
        while (rs.next()) {
            String coffeeName = rs.getString("COF_NAME");
            int supplierID = rs.getInt("SUP_ID");
            float price = rs.getFloat("PRICE");
            int sales = rs.getInt("SALES");
            int total = rs.getInt("TOTAL");
            System.out.println(coffeeName + "\t" + supplierID +
                "\t" + price + "\t" + sales + "\t" + total);
        }
    } catch (SQLException e ) {
        JDBCUtilities.printSQLException(e);
    } finally {
        if (stmt != null){ stmt.close();}
    }
}

```

JDBC execute a query

- To execute a query, call an execute method from Statement such as the following:
- `executeQuery`: **Returns one ResultSet object.**
- `executeUpdate`: Returns an integer representing the number of rows affected by the SQL statement. Use this method if you are using **INSERT, DELETE, or UPDATE** SQL statements.
- `execute`: Returns true if the first object that the query returns is a ResultSet object. False if an int value or no value is returned. Any kind of statement.

JDBC result set

```
String query = "select COF_NAME, SUP_ID, PRICE, SALES, TOTAL "
               + "from " + dbName + ".COFFEES";

try {
    stmt = con.createStatement();
    ResultSet rs = stmt.executeQuery(query);
    while (rs.next()) {
        String coffeeName = rs.getString("COF_NAME");
        int supplierID = rs.getInt("SUP_ID");
        float price = rs.getFloat("PRICE");
        int sales = rs.getInt("SALES");
        int total = rs.getInt("TOTAL");
        System.out.println(coffeeName + "\t" + supplierID +
                           "\t" + price + "\t" + sales + "\t" + total);
    }
}
```

JDBC clean up – close the connection

```
} finally {  
    if (stmt != null) { stmt.close(); }  
}
```

```

public static void viewTable(Connection con) throws SQLException {

    String query = "select COF_NAME, SUP_ID, PRICE, " +
                   "SALES, TOTAL " + "from COFFEES";

    try (Statement stmt = con.createStatement()) {

        ResultSet rs = stmt.executeQuery(query);

        while (rs.next()) {
            String coffeeName = rs.getString("COF_NAME");
            int supplierID = rs.getInt("SUP_ID");
            float price = rs.getFloat("PRICE");
            int sales = rs.getInt("SALES");
            int total = rs.getInt("TOTAL");
            System.out.println(coffeeName + ", " + supplierID +
                               ", " + price + ", " + sales + ", " + total);
        }
    } catch (SQLException e) {
        JDBCTutorialUtilities.printStackTrace(e);
    }
}

```

Create a table

```
-- SQL
```

```
create table SUPPLIERS (  
    SUP_ID integer NOT NULL,  
    SUP_NAME varchar(40) NOT NULL,  
    STREET varchar(40) NOT NULL,  
    CITY varchar(20) NOT NULL,  
    STATE char(2) NOT NULL,  
    ZIP char(5),  
    PRIMARY KEY (SUP_ID));
```

```
public void createTable() throws  
SQLException {  
    String createString =  
        "create table " + dbName +  
        ".SUPPLIERS " +  
        "(SUP_ID integer NOT NULL, " +  
        "SUP_NAME varchar(40) NOT NULL, " +  
        "STREET varchar(40) NOT NULL, " +  
        "CITY varchar(20) NOT NULL, " +  
        "STATE char(2) NOT NULL, " +  
        "ZIP char(5), " +  
        "PRIMARY KEY (SUP_ID))";  
  
    Statement stmt = null;  
    try {  
        stmt = con.createStatement();  
        stmt.executeUpdate(createString);  
    } catch (SQLException e) {  
        JDBCUtilities.  
            printSQLException(e);  
    } finally {  
        if (stmt != null) { stmt.close(); }  
    }  
}
```

Populate table

```
insert into SUPPLIERS values(
    49, 'Superior Coffee',
    '1 Party Place', 'Mendocino',
    'CA', '95460');
insert into SUPPLIERS values(
    101, 'Acme, Inc.',
    '99 Market Street', 'Grosville',
    'CA', '95199');
```

```
public void populateTable() throws Exception {
    Statement stmt = null;
    try{
        stmt = con.createStatement();
        stmt.executeUpdate(
            "insert into " + dbName +
            ".SUPPLIERS " +
            "values(49, 'Superior Coffee', " +
            "'1 Party Place', " +
            "'Mendocino', 'CA', '95460')");

        stmt.executeUpdate(
            "insert into " + dbName +
            ".SUPPLIERS " +
            "values(101, 'Acme, Inc.', " +
            "'99 Market Street', " +
            "'Groundsville', 'CA', '95199')");
    } catch (SQLException e) {
        JDBCUtilities
            .printSQLException(e);
    } finally {
        if (stmt != null) { stmt.close(); }
    }
}
```

Update

```
public void updatePrice(float price, String cofName,
                        String username, String password)
    throws SQLException{

    Connection con;
    PreparedStatement pstmt;
    try {
        con = ds.getConnection(username, password);
        con.setAutoCommit(false);
        pstmt = con.prepareStatement("UPDATE COFFEES "
                                     + "SET PRICE = ? " + "WHERE COF_NAME = ?");
        pstmt.setFloat(1, price);
        pstmt.setString(2, cofName);
        pstmt.executeUpdate();

        con.commit();
        pstmt.close();

    } finally {
        if (con != null) {con.close();}
    }
}
```

Delete

```
stmt = conn.createStatement();  
String sql = "DELETE FROM Registration " + "WHERE id = 101";  
stmt.executeUpdate(sql);
```

Apache Derby



- The most simple file-based SQL database!
- Good for practice or standalone apps with a single connection
- Embedded driver does not support multiple connections!
- open source relational database implemented entirely in Java
- Derby has a small footprint -- about 3.5 megabytes
- Derby is based on the Java, JDBC, and SQL standards.
- Derby is easy to install, deploy, and use.

Apache Derby


- Consider dbDemo app from canvas
 - *run*
- Ex1Connect
- Ex1Connect2
- Explain what was the issue
- Run
- Ex2CreateTable
- Ex3InsertRow

Eclipse

- Menu Window
- Perspective | Open Perspective | Other...
- Pick Databased development
- Right Click Database connections | New... | Derby | Next
- Add driver
 - *pick Embedded latest | call it DerbyDriver |*
 - *| tab JAR list | add JAR : ./lib/derby.jar*
 - *remove any preexisting JAR | hit OK*
- Database location | pick your DB
 - *(e.g. /Users/cerny/Documents/workspace5324/dbDemo/ex1connect)*
- Leave user/pass empty | Next | Finish



Remember to
disconnect!!!!



Example

Remember to
disconnect!!!!

- Try to call again Ex3InsertRow
- What is the issue?
- Call Ex4Select
- Call Ex5Update and again Ex4Select
- Call Ex6Delete and again Ex4Select