

1 List of empty values:

a has the following values:

1. 2
2. 3
3. 4

b has the following values:

1. 6
2. 7
3. 8
4. 9

c has the following values:

1. 11
2. 12
3. 13
4. 14

d has the following values:

1. 16
2. 17
3. 18
4. 19

e has the following values:

1. 21
2. 22
3. 23

4. 24

5. 25

2 List of nonempty values:

1. a has the following values: – 1
skip 2, skip 3, skip 4,
2. b has the following values: – 5
skip 6, skip 7, skip 8, skip 9,
3. c has the following values: – 10
skip 11, skip 12, skip 13, skip 14,
4. d has the following values: – 15
skip 16, skip 17, skip 18, skip 19,
5. e has the following values: – 20
skip 21, skip 22, skip 23, skip 24, skip 25,

3 Dorecurse alternative and while loop using

- A. a has the following values: – 1
skip 2, skip 3, skip 4,
- B. b has the following values: – 5
skip 6, skip 7, skip 8, skip 9,
- C. c has the following values: – 10
skip 11, skip 12, skip 13, skip 14,
- D. d has the following values: – 15
skip 16, skip 17, skip 18, skip 19,
- E. e has the following values: – 20
skip 21, skip 22, skip 23, skip 24, skip 25,