

Report showses the modifications made during the implementation stages

Models and arrangement of project files:

- I created the first model for perfume and split it into two parts: the glass part and plastic part but this model was changed to new models in which the glass part is a complete bottle but lower plastic part created by split by slice plane and check split option .
- I created two packages in different shapes and animated them according to their shapes.
- I created a curtain and animated it .

- I created a petal model and used it in the first scene but to make render time fast , I used petal texture on the plane and depend on opacity to hide the background of petals.
- All scenes were in a single 3d max file but after advice from our trainer ,I separated four scenes into four files resulting in work becoming easier especially when working with light and render.

Lighting and background:

- Used Arnold light type :
 - quad (plane light) to make studio lighting consist of key light , fill light and rim light and I added light above models in the fourth scene .
 - Photometric type and upload a file of light to it in the first scene.

- Background is plane then converted into editable poly and work on edge and make chamfer for middle edge and increase segment to make it curvature and smoothing it.

Animation:

- Keyframes by work directly on timeline were applied in all four scenes, in addition to animation path constraint for animating petals around perfume in scene 2 and using helix in spline as path for this animation.
Added cloth modifier and used simulate and create keys to add this simulation as keyframes on timeline for curtain in first scene .
- Used PF source in particle system to make petals fall down from top to down and POmniFlect in deflectors in space wraps to make petals stand on ground when they fall down in the fourth scene.

- Total keyframes for four scenes: 1299 frames.
- Time configuration setting for animation:
 - Frame rate is 30FPS .
 - NTSC

Camera:

- Used physical camera in standard camera.
- Used four cameras where each scene contains one physical camera.

Renderer : is Arnold

- Used ActiveShade Mode for testing material and lighting.
- Used Production Rendering Mode and resolution is 1902*1080 for Render output.

