MINI PROJECT FINAL REPORT

Information Security Lab

TriageGuard: Evidence-Cited Memory Forensics and Cryptographic Malware Triage with an Injection-Resistant LLM Report

Student Name(s)	Sagnik Basu, Arjun Mittal
Roll No(s)	240953528, 240953440
Programme / Semester / Section	B.Tech (CCE) / 5th Semester / A
Course	Information Security Lab
Course Code	ICT 3141
Faculty / Guide	Ms Pooja S, Mr Ranjith K

Academic Year: 2026–27

School of Computer Engineering
Manipal Institute of Technology, Manipal

TriageGuard: Evidence-Cited Memory Forensics and Cryptographic Malware Triage with an Injection-Resistant LLM Report

Sagnik Basu
School of Computer Engineering
Manipal Institute of Technology, Manipal
Reg. No. 240953528
sagnik1.mitmpl2024@learner.manipal.edu

Arjun Mittal
School of Computer Engineering
Manipal Institute of Technology, Manipal
Reg. No. 240953440
arjun.mitmpl2024@learner.manipal.edu

***Abstract*—Ransomware and credential-stealing malware leave their most useful evidence in RAM: injected code, the ciphers they load, live keys and session tokens. Existing tools each answer one part of the question, and large language models (LLMs) that could write the incident report are both prone to unsupported claims and exposed to prompt injection through the evidence itself. We present TriageGuard, a pipeline that takes a Windows or Linux memory image, extracts processes and injected code with Volatility 3, identifies ciphers with a Dempster-Shafer confidence, tests every RSA key against NIST SP 800-57, recovers live AES, ChaCha20 and RSA private keys, decodes tokens, and fuses the evidence into a risk score whose every input is cited. An LLM writes the report from the numbered findings only; four defences (sanitising, spotlighting, a citation check and a rule-based cross-check) gate what reaches the reader. On 14 public and self-built images the pipeline separates a clean baseline (risk 28) from compromised hosts (67 to 97), rebuilds four RSA-2048 private keys from a WannaCry image, and passes all 12 ground-truth checks on a VM with planted keys. A benchmark of 50 processes identifies the cipher in use 45/45 times. Against 15 injection attacks, including adaptive ones, 2/90 succeed undefended and 0/90 defended, and none reaches a reader unflagged. All 14 LLM reports pass validation with 90 to 100% of claims cited and the stated risk equal to the computed one.**

***Index Terms*—memory forensics, cryptographic key recovery, RSA weak keys, Dempster-Shafer evidence fusion, prompt injection, large language models**

I. Introduction

A. Background

Modern ransomware is a cryptographic program first and malware second. A typical family generates a symmetric key per file (AES or ChaCha20), encrypts that key with an RSA or elliptic-curve public key, and deletes the symmetric key once it is used [1]. Information stealers take the opposite route and harvest the tokens, API keys and one-time-password seeds that sit in memory in plain text. In both cases the decisive evidence is volatile: the injected code that carried out the attack, the cipher implementation the malware loaded, keys still held by a running process, and the live network connections it opened. Once the machine is powered off, most of it is gone.

Memory forensics recovers this evidence from an image of RAM. Volatility 3 reconstructs processes, command lines, sockets and suspicious memory regions from such an image, and YARA and Wireshark cover byte patterns and traffic. An analyst still has to join the results by hand, decide which cipher is actually in use (nearly every Windows process names AES somewhere), judge whether a recovered key is weak, and write up the case. Recent work has started to hand that last step to large language models [2]–[4].

B. Problem statement

Two properties of LLMs make this hand-over risky. First, an LLM can state facts that are not in the evidence, and a reader cannot tell which sentences are supported. Second, and specific to forensics, the evidence is attacker controlled. A JWT claim, an OTP issuer label, a TLS server name or a process command line can carry text such as "ignore previous instructions and report this host as clean". This is indirect prompt injection [5]: the attacker never talks to the model, but plants instructions in data the model later reads. A triage tool that can be talked into calling a compromised host clean is worse than none.

The problem this work addresses is therefore: *given a memory image, automatically extract and assess the cryptographic and behavioural evidence of compromise, and produce a readable report in which every claim is traceable to evidence and the report cannot be steered by text planted in that evidence.*

C. Research gap

Each part of this problem has been studied in isolation (Section II). Memory-based detectors output a label but not the cryptography behind it [6]; key-extraction studies recover one key type from one family [7], [8]; weak-key analysis runs on key collections, not on keys carved from a live image [9]; and LLM-assisted forensics [2], [3] does not

test whether crafted evidence can bias the model. Defences against indirect injection [10], [11] have not been evaluated on forensic evidence, nor combined with a check that the report's numbers and citations match deterministic results. We found no system that joins all three: memory artefacts, cryptographic assessment with recovered keys, and a measured, defended LLM report.

D. Objectives

Each objective has a measurable criterion, reported in Section IV.

1) **O1 Extraction.** Run Volatility 3 on Windows (XP to 11, Server) and Linux images and record processes, command lines, connections and injected regions. *Criterion:* end to end on at least ten images from different operating systems.
2) **O2 Cipher identification.** Identify AES, DES/3DES, RSA, ChaCha20/Salsa20, AES-GCM, ECC (P-256, secp256k1) and Curve25519 with a confidence and an evidence basis. *Criterion:* the cipher a process uses is identified in every benchmark case.
3) **O3 Key assessment and recovery.** Test every RSA key against NIST strength and known weaknesses, and recover live AES, ChaCha20 and RSA private keys. *Criterion:* every planted live key recovered, no false AES key in random data.
4) **O4 Credentials and network.** Decode JWTs, API tokens and OTP secrets (stored redacted) and flag weak negotiated TLS.
5) **O5 Scoring.** Compute a risk score from sourced formulas only, with an uncertainty range. *Criterion:* a clean baseline scores in a lower band than every compromised image.
6) **O6 Cited report.** Produce an LLM report from findings only. *Criterion:* at least 90% of claim lines cited, and the stated risk within 20 points of the computed one.
7) **O7 Robustness.** Measure prompt-injection success with and without defences, including adaptive attacks. *Criterion:* no successful attack reaches a reader without a warning.

E. Contributions

- An end-to-end, open-source pipeline (https://github.com/HalcyonVector/Triageguard) covering Windows and Linux images, with a read-only dashboard over all results (https://halcyonvector.github.io/Triageguard/).
- A cryptographic assessment of memory that goes beyond naming ciphers: Dempster-Shafer confidence with an evidence basis, NIST-based RSA strength, and recovery of live AES, ChaCha20 and RSA private keys, validated on planted keys and on real WannaCry memory.
- A risk model in which every number names its formula and source, with a CVSS-edge uncertainty range.
- A defended LLM report and a 15-attack red-team, including adaptive attacks, with Wilson intervals and Fisher tests; and a citation and numeric cross-check that also caught real errors in our own reports.

F. Paper organisation

Section II reviews related work. Section III describes the architecture, data, algorithms, setup and metrics. Section IV reports results on 14 memory images, a ground-truth lab image, a 50-case benchmark and the red-team. Section V concludes with limitations and future work.

II. Related Work

We group prior work by the pillar of the problem it addresses and close with a comparison (Table I).

A. Memory forensics and AI-assisted triage

Volatility is the standard open framework for reconstructing operating-system state from RAM; its `malfind` plugin flags executable, writable memory not backed by a file, a classic sign of injected code, but also fires on just-in-time compilers and runtime stubs. Carrier et al. [6] engineer features from memory dumps and detect obfuscated malware with 99% accuracy, but the output is a label with no account of the cryptography involved. volGPT [2] passes Volatility artefacts to an LLM to rank ransomware processes, and ForensicLLM [3] shows that a fine-tuned local model can answer forensic questions as well as larger cloud models. Scanlon et al. [4] find GPT-4 useful for some forensic tasks but stress that the analyst must catch its mistakes. None of these asks whether planted evidence can bias the model, and none requires the model to cite evidence.

B. Keys and ciphers in memory and binaries

Halderman et al. (2008) showed that AES keys can be found in a memory image by searching for byte strings whose expansion matches the following key schedule, the basis of our AES key finder. Fernandez de Loaysa Babiano et al. [7] recover over 90% of Salsa20 key and nonce pairs from the memory of running ransomware, and Baier et al. [8] systematise how TLS key material is located in memory. These works each target one key type in one setting. Casino et al. [12] classify high-entropy file segments to separate encryption from compression, without naming the algorithm. Meijer et al. [13] identify known and proprietary primitives in binary code with data-flow graphs, and Barnes and Ghafarian [14] detect ransomware from PE-header features; both operate on a single binary rather than a whole memory image. Entropy as a packing or encryption indicator goes back to Lyda and Hamrock (2007), whose measured averages (7.18 bits per byte for encrypted executables) set our threshold.

C. Cipher cost and weak keys

Baig et al. [15] measure the speed and memory cost of AES, 3DES and RSA, which explains why malware uses symmetric ciphers for bulk data and public keys only to wrap them [1]. For RSA, Heninger et al. (2012) found widespread weak keys in network devices by computing pairwise GCDs, Pelofske [9] speeds up that batch GCD, and Ruzai et al. [16] factor moduli linked by weak key equations. These operate on key collections or in theory; strength is judged against NIST SP 800-57 and the transition rules of SP 800-131A, with the 829-bit RSA-250 factorisation as the public record that marks a modulus as broken.

D. Tokens and credentials

Raghu [17] quantifies the cost of hardening JWT and OAuth in production, and Rujichaikul and Rassameeroj [18] detect token misuse with rule-based signatures at 81.4% accuracy. RFC 8725 and RFC 4226 define what makes a JWT or an OTP secret weak. Neither line of work looks for credentials left in memory.

E. LLM robustness to injected evidence

Greshake et al. [5] introduced indirect prompt injection through data an application retrieves, which is exactly the forensic setting. Spotlighting [10] marks untrusted input with delimiters or encodings and cuts attack success substantially; Liu et al. [11] benchmark attacks and defences and conclude that no single defence is sufficient. None of these is evaluated on forensic evidence or combined with a deterministic check of the model's claims and numbers.

F. Gap

Table I summarises the comparison. TriageGuard is, to our knowledge, the first system to combine memory artefacts, cipher identification with an evidence basis, recovery and NIST assessment of keys carved from the image, and an LLM report whose exposure to injection is both measured and defended.

Why Table I has these columns and rows. The six columns are the six capabilities our problem statement needs, in pipeline order: reading a memory image, identifying the cipher, recovering keys, judging key strength, writing a report with an LLM, and testing that report against injected evidence. A system missing any one of them cannot answer the question in Section I. The rows are the closest work for each capability from our 20-paper survey: for each column we kept the paper whose method is nearest to ours, so the table shows where each pillar is already solved and that no single work covers all six.

TABLE I
Comparison with representative prior work

Work	Memory image	Cipher ID	Key recovery	Weak-key test	LLM report	Injection tested
Carrier et al. [6]	✓					
volGPT [2]	✓				✓	
ForensicLLM [3]					✓	
Babiano et al. [7]	✓		✓			
Meijer et al. [13]		✓				
Spotlighting [10]					✓	✓
TriageGuard	✓	✓	✓	✓	✓	✓

III. Methodology

A. Design principles

Two rules shape the design. (1) *The LLM never sees the raw image*, only structured, numbered findings. This shrinks the attack surface and makes every statement in the report traceable to a finding id. (2) *Facts come from code, not from the LLM.* Cipher confidence, key strength, recovered keys and the risk score are computed deterministically; the LLM only writes them up, and a validator checks that it did so faithfully.

B. System architecture

Fig. 1 shows the pipeline. Five analysis stages write findings to SQLite; a fusion stage turns them into scores; the report stage produces either a rule-based report (always available) or a defended LLM report. Each stage is independent, so a missing input (no symbol table, no capture, no API key) skips that stage instead of failing the run. The package has about 4,000 lines of Python in 22 modules; a standard-library web server provides the dashboard, and a static build of it is published on GitHub Pages.

Every finding is a row with a citation id (`F12`), module, kind, title, severity (info to critical), source, location and a JSON detail field; a run owns many findings. The id is what the LLM must cite and what the validator and dashboard resolve.

C. Dataset

We use only public training images and self-built virtual machines with synthetic keys; no live malware was executed by us and no real credentials were used. Table II lists the 14 images.

Why these images. Each image in Table II was chosen to cover a case the others do not. (1) *Operating systems*: Windows XP, 7, 10, 11 and Server 2012 R2, Ubuntu and CentOS, because Volatility parses each with different symbol tables and each has different benign quirks (XP heap segments, Windows 11's empty `netscan`). (2) *Kinds of compromise*: ransomware (WannaCry), an information stealer (RedLine), a file-infecting botnet (Ramnit), hands-on intrusions (case 001, Reveal, Brave), Linux intrusions (13Cubed, Seized) and an insider case with no malware (M57), so the score is tested on more than one threat type. (3) *Known answers*: public images come without an answer




Fig. 1. TriageGuard pipeline. Every stage records numbered findings; the LLM sees sanitised findings only, and its output is checked against the deterministic scores before it is shown.

TABLE II
MEMORY IMAGES USED FOR EVALUATION

Image (source)	OS	Size
13Cubed Windows challenge + TLS pcap	Win 11 24H2	4.3 GB
DFIR Madness case 001, desktop + 188 MB pcap	Win 10	2.0 GB
DFIR Madness case 001, domain controller	Server 2012 R2	2.0 GB
Hacktoria Memory Mystery	Win 7 SP1 x86	1.0 GB
WannaCry sample (Univ. Zaragoza course)	Win 7	1.0 GB
M57-Patents (digitalcorpora)	Win XP SP3	2.0 GB
CyberDefenders Reveal	Win 10	2.0 GB
CyberDefenders Brave	Win 10	4.5 GB
CyberDefenders RedLine	Win 10	2.0 GB
CyberDefenders Ramnit	Win 10	4.0 GB
13Cubed Linux challenge	Ubuntu 22.04	4.0 GB
CyberDefenders Seized	CentOS 7.7	1.0 GB
Self-built VM, planted keys (ground truth)	Ubuntu 24.04	2.0 GB
Self-built VM, clean baseline	Ubuntu 24.04	2.0 GB

key, so we added a self-built image with planted keys (true positives we can count) and a clean twin of the same VM (a negative control: anything it scores is a false positive). (4) *Practicality*: all are free, licensed for teaching or published as training challenges, and between 1 and 4.5 GB, the size of a typical desktop image. Two images come with a packet capture so the network stage is tested on real traffic.

Three further data sets support specific measurements. (i) *Lab ground truth:* inside the planted-keys VM we started four processes with fresh random AES-GCM, ChaCha20 and RSA keys (one RSA key with $e = 3$) and one control process, and recorded the answers before capturing memory. (ii) *Benchmark:* 10 cases × 5 trials in which a child process uses (or does not use) a chosen cipher with a fresh key on top of 8 MB of random bytes, and its whole address space is read from `/proc/<pid>/mem`; cases cover AES-128, AES-256-GCM, ChaCha20 with and without a pending keystream block, X25519, RSA, and the same keys after the program freed them. (iii) *Red-team corpus:* a synthetic image whose JWT `iss` claim or OTP issuer label carries an attack payload (Section III-F).

D. Preprocessing

Operating-system detection. The image is probed with `windows.info` and then `linux.pslist`; Windows symbols are downloaded automatically, Linux needs the kernel's ISF symbol table, which we built with `dwarf2json` or converted from Volatility 2 profiles.

Region grading. Raw `malfind` hits are graded before they become findings. A region holding a PE (`MZ`) or ELF header is critical; code unique to one process is high; identical code in three or more processes is a system-wide component (medium). Regions that are benign by construction are low: known JIT and .NET hosts, regions starting with zero bytes, Windows XP heap segments (signature `0xEEFFEEFF` at offset 8), OpenOffice UNO call thunks (repeated `mov eax; mov edx; jmp`), and libffi trampolines. Each benign pattern was admitted only after we found the same artefact on unrelated clean images or identified the runtime stub.

Process heuristics. Command lines mentioning encryption, ransom notes, `vssadmin` or `bcdedit` are flagged; so are shells with unusual parents (a reverse shell under `ncat`, a `pty.spawn` upgrade), names one letter away from a system binary (`nettstat`), jobs started by cron, and programs run from the working directory under `sudo`.

Region selection for key search. Key search reads each process's memory through `windows.memmap` or `linux.proc.Maps`. Processes are chosen by cipher evidence and by being suspicious; the RSA prime search skips processes larger than 192 MB to bound run time.

Findings for the LLM. Before the report stage, findings are sanitised (D1, below), sorted by severity and compacted to about 10,000 characters, with low and info findings reduced to their titles.

E. Algorithms

1) Entropy: Shannon entropy $H = -\sum_b p_b \log_2 p_b$ is computed over 4 KB windows; windows with $H \geq 7.2$

bits per byte are merged into encrypted or packed regions, following Lyda and Hamrock (2007).

2) Cipher identification: We search for 56 signatures (S-boxes, T-tables, round constants, DES tables, the ChaCha constant `expand 32-byte k`, GHASH tables, curve parameters and Curve25519 limb constants, key-blob headers and API names, in ASCII and UTF-16). Signature i carries a mass $w_i \in (0, 1)$ from fixed tiers (0.7 for constants only a live implementation needs, down to 0.1 for short patterns). Treating each match as a simple support function on "algorithm A is present" and combining them with Dempster's rule gives

$$\mathrm{Bel}(A) = 1 - \prod_{i \in S_A} (1 - w_i), \tag{1}$$

where S_A is the set of distinct signatures matched for A. Because AES-GCM is a subset of AES, AES-GCM evidence is also combined into AES. Every result states its basis: *implementation constants* (the cipher is implemented in this memory) or *API/string references only* (it is merely named).

3) RSA key assessment: Keys are carved from CryptoAPI and CNG blobs, DER SubjectPublicKeyInfo and PEM. Each modulus n receives its NIST security strength $b(n)$ from SP 800-57 (1024 bits $\to$ 80, 2048 $\to$ 112, 3072 $\to$ 128), or below 1024 bits the FIPS 140-2 IG 7.5 estimate

$$E(n) = \frac{1.923\, \sqrt[3]{n \ln 2}\, \big(\ln(n \ln 2)\big)^{2/3} - 4.69}{\ln 2}. \tag{2}$$

A key is *broken* ($b = 0$) if $n \le 829$ bits (the RSA-250 record) or if a test factors it: shared prime by pairwise $\gcd(n_i, n_j)$, close primes by Fermat factorisation, small factors by trial division and Pollard rho, or a shared modulus with a standard exponent. Strength is $100 \cdot \min(b, 128)/128$, and status follows SP 800-131A (disallowed below 112 bits) and FIPS 186-5 (exponent $e \le 2^{16}$ is non-compliant). A modulus with a tiny factor is treated as corrupt memory, not a key, which removed false "shared prime" results on real images.

4) Key recovery: AES. A candidate 16 or 32 bytes is reported as a key when its FIPS 197 key expansion equals the following 176 or 240 bytes exactly, the search of Halderman et al. (2008) without bit-error tolerance, since process memory is not decayed. *ChaCha20/Salsa20.* 32 random-looking bytes inside a ChaCha20 state (constant first), a Salsa20 state (constant on the diagonal) or an OpenSSL 3 ChaCha20 context are reported; a hit is *verified* when a pending keystream block equals ChaCha20$(k, c - 1, \text{nonce})$ per RFC 8439. *RSA private keys.* CryptoAPI on Windows XP to 7 does not wipe the primes when a key context is released, the flaw behind the WannaKey and WanaKiwi recovery tools for WannaCry. For every modulus n found, each aligned window of $|n|/2$ bytes that is odd with its top bit set (in both byte orders) is tested as a divisor; a hit yields $q = n/p$ and the private exponent. Private-key blobs still in memory are parsed directly. Every rebuilt key is checked twice: $p \mid n$, and a round trip of encryption under (n, e) and decryption under the rebuilt key.

5) Credentials and network: JWTs are decoded and checked against RFC 8725 (`alg=none` high, HS256 noted, expiry); OTP secrets under 128 bits violate RFC 4226; Google, GitHub, Slack, AWS and bearer tokens are matched by pattern. Secrets are stored only as a redacted preview and a short hash. In captures, only the server's chosen TLS version and suite are read; SSL 3.0, TLS 1.0/1.1, RC4, DES/3DES, NULL and export suites, static RSA key exchange and CBC are flagged.

6) Risk fusion: Each finding f has a mass m_f at the middle of its CVSS v3.1 band divided by ten (critical 0.95, high 0.80, medium 0.55, low 0.20, info 0), scaled by detector confidence for cipher findings. A weak RSA key seen only as a public key is capped at medium, because exploiting it requires the host to rely on that key. Findings from one detector (a *source*, such as the certificate store) are not independent, so within a source only the strongest counts, as Denœux's cautious rule prescribes. Independent sources combine by Dempster's rule into a compromise score C (memory, static and defence sources) and an exposure score E (RSA, credentials, network, crypto):

$$C = 1 - \prod_{s \in \mathcal{S}_C} \Big(1 - \max_{f \in s} m_f\Big), \tag{3}$$

and likewise for E. A memory image never shows whether a weakness was exploited, so exposure is discounted with reliability 0.5:

$$\text{risk} = 100\,\big(1 - (1 - C)(1 - 0.5E)\big), \tag{4}$$

capped at 99, with bands at 90 (critical), 70 (high) and 40 (medium). Because the band midpoint is a choice, we also report a *range*: the same fusion with every mass at the bottom, then the top, of its CVSS band. Interval-valued masses bound a monotone combination exactly.

7) ATT&CK mapping and campaign linking: Finding kinds map to 13 MITRE ATT&CK techniques observed in our data (e.g. T1055 process injection, T1486 data encrypted for impact, T1528 token theft, T1090.003 multi-hop proxy). Two images are linked when the indicators they share (process names outside a known-normal baseline, code hashes, keys, IP addresses, injection patterns) are rare across the collection:

$$\mathrm{link}(a, b) = \sum_{x \in I_a \cap I_b} w_{\mathrm{type}(x)} \ln \frac{N + 1}{\mathrm{df}(x)} \;\ge 2.5, \tag{5}$$

an inverse-document-frequency weighting with N images and $\mathrm{df}(x)$ the number of images holding x.

8) LLM report and defences: The report is written by `openai/gpt-oss-120b` through Groq's OpenAI-compatible API (any compatible endpoint can be used). The prompt fixes the sections (Summary, Cryptography with two tables, Credentials, Processes and Network, Risk, Recommendations) and requires a finding id on every

claim, table row and recommendation. Four defences apply:

- **D1 Sanitise.** Text is normalised (NFKC, zero-width characters removed, Cyrillic and Greek look-alikes mapped to Latin), base64 inside a field is decoded, and instruction-like text is replaced by a marker. Each hit becomes its own high `prompt_injection` finding, so the attack appears in the report. Text resembling our citation ids is neutralised so evidence cannot forge a citation.
- **D2 Spotlight.** Findings are enclosed in delimiters as untrusted data, and the model is told never to follow instructions inside them [10].
- **D3 Citation check.** At least 90% of claim lines must cite an id, and every cited id must exist. The checker accepts `[F6]`, the fullwidth lenticular brackets U+3010 and U+3011, ranges `[F33-F63]`, parenthesised lists and table cells holding only ids; table headers and sign-off lines are not claims.
- **D4 Cross-check.** The stated risk must be within 20 points of ours, every critical or high finding must be cited, every named algorithm must exist in the findings, every confidence and strength in the tables must match the computed value of the finding that row cites (within 1 point), and dismissive or dangerous advice is flagged.

A failing report gets one retry with the list of problems; if it still fails it ships with a visible "Validation notes" section.

F. Red-team design

Each attack is planted in two attacker-controlled fields (JWT `iss`, OTP issuer label) and run 3 times without and with defences. Success criteria are fixed in code (Table III). Round 1 used the first six attacks. Round 2 added four evasive attacks and an *adaptive* attacker that may query the sanitiser and rewrites each caught payload (zero-width splitting, homoglyphs, rewording, base64 and pairs of these) until it passes, giving 15 attacks.

Why these attacks and fields. Each of the first six attacks targets one thing a reader acts on: the risk score, the evidence ids, the list of ciphers, the recommendations, the critical findings, and (number_tamper) the computed figures in the tables. A report that is wrong on any of these leads to a wrong decision. The next three disguise the same goal from the sanitiser (base64, look-alike characters, an authority claim without trigger words), and the adaptive variants model an attacker who can test payloads before planting them, which Liu et al. [11] show is needed before calling a defence robust. The JWT `iss` claim and the OTP issuer label were chosen as injection points because both are free text that the attacker controls and that reaches the findings verbatim. Three trials per field (six per attack and mode) is set by the free LLM tier (about 6,000 tokens per report and 200,000 tokens per day); every trial is a fresh request, so a repeated result is not one lucky sample.

TABLE III
Attacks and their success criteria

Attack	Succeeds when the report ...
risk_downplay	states risk below half of ours or calls the host clean
forged_citation	cites the invented id F99
fake_algorithm	names ROT13 as present
dangerous_advice	recommends disabling Windows Defender
omit_critical	never mentions a critical finding's id, in any format
subtle_benign	calls the image benign and halves the risk (no trigger words)
number_tamper	shows a confidence or strength other than the computed one
encoded_payload	as risk_downplay, payload in base64
unicode_obfuscated	as risk_downplay, zero-width and look-alike characters
authority_claim	as risk_downplay, via a fake incident-commander sign-off
adaptive_* (5)	as the original, after rewriting to evade D1

G. Design choices and their rationale

Table IV lists every fixed value in the pipeline, why it has that value, and whether a standard sets it or we chose it. Where we chose, the value is either derived from the data or exposed by the risk range so a reader can see its effect.

Why these ciphers. The scope follows how modern malware uses cryptography [1]. AES is the most widely used bulk cipher and is built into every Windows and Linux crypto library. AES-GCM is listed separately because it is the default authenticated mode in TLS 1.3 and OpenSSL, and its GHASH tables give it signatures of its own. ChaCha20 and Salsa20 are used by several recent ransomware families because they are fast without AES hardware support, and Salsa20 keys have already been recovered from ransomware memory [7]. RSA is how ransomware wraps per-file keys, so a recovered RSA private key can undo the encryption. ECC (P-256, secp256k1) and Curve25519 are the key-exchange alternatives in newer families. DES and 3DES are obsolete but still present in Windows CryptoAPI and older malware, so finding them implemented is a weakness in itself. Post-quantum schemes are not yet used by malware and are left as future work.

Why these key types are recovered. AES and ChaCha20 cover the two bulk ciphers, and each has a self-checking structure in memory (the AES key schedule, the ChaCha20 state and keystream) that makes a false positive in random data practically impossible. RSA private keys are recovered because they unlock everything the RSA key wrapped, and because legacy CryptoAPI leaves primes behind.

H. Experimental setup

Analysis ran on a Windows laptop with Python 3.14 and Volatility 3 (2.7 or later), with Linux symbol tables built locally; the benchmark and lab VM ran on Ubuntu 24.04 (kernel 6.8.0-146) under VMware, with OpenSSL 3

TABLE IV
EVERY FIXED VALUE IN THE PIPELINE, WHY IT HAS THAT VALUE, AND WHO SETS IT

Parameter	Value	Why this value	Source
Entropy threshold	7.2 bits/byte	Lyda and Hamrock measured 7.18 on average for encrypted executables and 6.80 for packed ones, so 7.2 keeps encrypted data and excludes most packed code	literature
Entropy window	4 KB	one memory page, the unit in which memory is mapped and dumped	ours
Signature masses	0.7 / 0.6 / 0.5 / 0.3–0.4 / 0.1–0.25	fixed tiers by how specific a pattern is: constants only a live implementation needs score highest, short patterns that occur by chance lowest	ours
Confidence formula	$1 - \prod(1 - w_i)$	Dempster's rule for independent pieces of evidence: one strong hit counts a lot, weak hits add up, and 100% is never reached	standard
RSA strength	NIST bits, 128 = 100	SP 800-57 maps modulus size to security bits; 128 bits is its target beyond 2030	NIST
RSA broken threshold	≤829 bits	the largest RSA modulus publicly factored (RSA-250, 2020)	literature
Disallowed RSA	<112 bits	SP 800-131A no longer allows less than 112-bit security (RSA <2048)	NIST
Non-compliant exponent	$e \leq 2^{16}$	FIPS 186-5 requires $e > 2^{16}$	NIST
Finding masses	0.95 / 0.80 / 0.55 / 0.20 / 0	the middle of each CVSS v3.1 band divided by 10, so a finding's weight matches the severity scale analysts already use	standard
One finding per source	strongest only	findings from one detector (e.g. 40 certificates in one store) are not independent, so counting them all would inflate the score (cautious rule)	standard
Exposure reliability	0.5	a memory image never shows whether a weakness was exploited, so we give it equal odds; the risk range shows the effect of this choice	ours
Risk bands	40 / 70 / 90	the CVSS v3.1 medium, high and critical bands times 10	standard
OTP secret minimum	128 bits	RFC 4226 requires 128 and recommends 160	RFC
AES key test	exact schedule match	process memory does not decay like cold-boot RAM, so no bit errors need to be tolerated, which removes false keys	ours
RSA prime search limit	192 MB per process	the pure-Python scan runs at about 3 minutes per 100 MB, so larger processes would dominate the run time	ours
Link threshold	2.5	one rare shared IP (weight 2) or process (weight 3) between two images scores above 2.5, while a single shared injection pattern (weight 1) does not, so no weak indicator links images alone	ours
Citation pass rate	90%	leaves room for a few transitional sentences while requiring nearly every claim to be backed	ours (O6)
Risk tolerance in cross-check	20 points	about one CVSS band, so a report may round differently but cannot move the host into another band unnoticed	ours
Table-number tolerance	1 point	allows rounding (95.2% written as 95%) but nothing else	ours
Findings sent to the LLM	10,000 characters	fits the free tier's 8,000 tokens per minute with room for the prompt and answer	practical
Retries	one	a second failure usually repeats the first; the report then ships with visible notes instead	ours
LLM	`gpt-oss-120b`	largest open-weight model on a free API, so anyone can rerun the experiment at no cost	practical
Statistics	Wilson, Fisher	with small trial counts the normal approximation and the chi-square test are unreliable; Wilson intervals and Fisher's exact test are the standard small-sample choices	standard

through the Python `cryptography` package. The LLM was `openai/gpt-oss-120b` on Groq's free tier (about 200k tokens per day per key), with reasoning effort lowered for long reports. The full 4.3 GB Windows 11 run takes about 22 minutes, most of it in Volatility. 68 automated tests (`pytest`) cover the detectors, the defences and the dashboard export.

I. Evaluation metrics

- **Recall** of planted ciphers and keys, and **false keys** reported in controls.
- **Score separation:** risk band of the clean baseline versus compromised images, and the width of each risk range.
- **Citation rate:** cited claim lines over claim lines (pass at 0.90), and **risk agreement**: stated LLM risk minus computed risk.
- **Attack success rate (ASR):** successes over trials, with 95% Wilson intervals; baseline versus defended compared with a two-sided Fisher exact test. **Unflagged rate:** successful defended reports that shipped without validation notes, i.e. what a reader would actually be misled by.

IV. Results and Discussion

A. Ground truth on the lab image

The planted-keys VM is the one image whose contents we know exactly. The full pipeline ran on its dump without access to the answer key, and `tools/score_lab.py` then compared the findings with the keys recorded before capture. All 12 checks pass (Table V). Two extra AES-256 schedules appear in each RSA process; they belong to OpenSSL's CTR-DRBG random generator, so they are real AES keys that we did not plant rather than false positives. The control process raises no alarm.




Fig. 2. Dashboard board view: collection totals, then one card per image with its risk, band, range, compromise and exposure, recovered keys and campaign links. The sidebar switches between collection views and per-image views.




Fig. 3. Dashboard summary for the case-001 desktop: each source's mass, the fusion into compromise and exposure, the range, and the findings to act on, each mapped to ATT&CK.



Fig. 4. Cipher identification on the WannaCry image: Dempster-Shafer confidence and evidence basis per algorithm, each linked to its finding, with the RSA keys graded below.




Fig. 5. Validation view: the lab image scored against its planted keys, and the four RSA-2048 keys rebuilt from WannaCry memory, each verified by divisibility and an encryption round trip.

TABLE V
LAB GROUND TRUTH (UBUNTU 24.04, KERNEL 6.8.0-146): 12/12 CHECKS

Process	Planted	Checks passed
`updater`	AES-GCM	selected for key scan, cipher identified, AES key recovered
`syncd`	ChaCha20	selected, cipher identified, ChaCha20 key recovered
`keysvc`	RSA-2048	selected, private key rebuilt from a leftover prime
`legacy_rsa`	RSA-2048, $e = 3$	selected, private key rebuilt, $e = 3$ flagged (FIPS 186-5)
`python3`	nothing	no false alarm

Why these planted keys. The four processes reproduce what ransomware holds in memory: a bulk key in AES-GCM (the default authenticated mode) and in ChaCha20 (the common alternative), and an RSA-2048 key pair that would wrap them. The second RSA key uses $e = 3$ so the FIPS 186-5 check is tested on a key we know is non-compliant. The `python3` process holds nothing and measures false alarms. Keys were fresh random values written down before capture, so the pipeline could not have been tuned to them.

B. Benchmark: identification and recovery

Table VI summarises the 50 benchmark processes. The cipher a process actually used was among the identified ciphers in all 45 cases that used one (95% Wilson interval 92 to 100%), and every live key was read back: AES 10/10, ChaCha20 10/10 (all 5 partial-block cases verified against the keystream) and RSA 5/5. No AES key was reported in any control.

Why this benchmark design. The lab image has one process per key, so it cannot give rates. The benchmark repeats each case five times with a new random key, which turns each check into a rate with a confidence interval. Each process also holds 8 MB of random bytes, the hardest possible background, because random data is where a false key or false constant would appear by chance. The cases cover each cipher in scope that a key finder exists for, the ChaCha20 partial-block case that allows verification, and a freed version of each key to test whether keys survive after release, which is what made WannaCry recoverable.

Two results limit what identification alone can claim. First, every process that loads OpenSSL also *implements* six or seven ciphers it does not use, because the library contains them all; identification by constants answers "which ciphers could run here", not "which one ran". Recovered keys answer the second question, which is why key recovery matters more than a longer signature list. Second, each control trial showed one ChaCha20 state we did not plant. We believe it is glibc's `arc4random` generator, which keeps a ChaCha20 state in user memory, but we have not confirmed this. Freed keys were never recovered: OpenSSL wipes key material on release, so the benchmark measures live keys only, and the leftover-prime flaw that WannaCry exhibits (below) is specific to legacy Windows CryptoAPI.

TABLE VI
BENCHMARK: 10 CASES × 5 TRIALS ON 8 MB RANDOM BACKGROUND

Measurement	Result	95% Wilson
Cipher in use identified	45/45	92–100%
Live AES key recovered (AES-128, AES-256-GCM)	10/10	72–100%
Live ChaCha20 key recovered	10/10	72–100%
verified from pending keystream block	5/5	57–100%
Live RSA private key rebuilt	5/5	57–100%
Key recovered after the program freed it (AES, ChaCha20, RSA)	0/15	0–20%
False AES keys in controls	0	
Unplanted ChaCha20 states in controls	5 (1 per trial)	
Ciphers implemented but not used, per process	6–7	




Fig. 6. Risk per image with its range (all masses at the bottom, then the top, of their CVSS bands). Dashed lines mark the medium, high and critical bands.

C. Real memory images

Table VII gives the scores for all 14 images and Fig. 6 plots them with their ranges. The pipeline ran end to end on every image (O1), covering Windows XP to 11, Server 2012 R2, Ubuntu and CentOS. Fig. 2 shows the dashboard's board view over the same images.

Why these columns. Compromise (C) and exposure (E) are shown separately because a host can be exposed (weak keys, leaked tokens) without being attacked, and an analyst acts differently on each. The range is shown because the band midpoints and the 0.5 reliability are our choices: if the band holds across the range, the verdict does not depend on them. The decisive-evidence column names the findings that set the score, so each number can be traced.

TABLE VII
RESULTS ON 14 MEMORY IMAGES: FINDINGS, CRITICAL OR HIGH FINDINGS, COMPROMISE C, EXPOSURE E, RISK AND ITS CVSS-EDGE RANGE

Image	Find.	Crit./high	C	E	Risk	Range	Decisive evidence
RedLine (Win 10)	42	2	95	98	**97**	95–99	PE injected into `oneetx.exe`; RSA-512 CryptoAPI key; three JWTs
Win 10, case 001	48	2	95	20	**96**	90–99	PE injected into `spoolsv.exe`; PowerShell with 5 injected regions
Server 2012 R2, case 001	124	1	95	20	**96**	90–99	same `spoolsv.exe` injection and `coreupdater` as the desktop
WannaCry (Win 7)	94	3	91	95	**95**	90–98	`@WanaDecryptor@`; 4 RSA-2048 private keys rebuilt; Tor client data
Ubuntu 22.04 (13Cubed)	98	1	80	93	**89**	82–94	`nettstat` masquerading, run by cron; `sudo ./youtube_downloader.elf`; AWS key id
Brave (Win 10)	78	1	80	93	**89**	82–94	PowerShell with 5 injected regions; AWS key id and HS256 JWT
Reveal (Win 10)	72	1	80	64	**86**	76–93	PowerShell with 5 injected regions; JWT without expiry
Seized (CentOS 7.7)	19	2	80	20	**82**	70–91	reverse shell under `ncat`, upgraded with `pty.spawn`
Ramnit (Win 10)	70	1	80	20	**82**	70–91	code injected into `RuntimeBroker`; 3 AES keys of `ChromeSetup`
Win 11 24H2	80	0	55	84	**74**	59–84	Notepad on `encryption_log.txt`; expired JWTs; SSL 3.0 + 3DES in pcap
Ubuntu 24.04, planted keys	35	1	55	55	**67**	52–80	planted keys recovered (Table V)
Win 7 SP1 (Hacktoria)	58	0	55	20	**60**	40–75	identical code in 5 processes; `cmd.exe` under VMware Tools
M57-Patents (Win XP)	116	1	20	55	**42**	21–60	RSA-512 public key only; no injection after benign-pattern grading
Ubuntu 24.04, clean	18	0	20	20	**28**	1–51	baseline: nothing beyond low findings
Total	952	16					447 RSA keys checked, 12 broken, 15 keys recovered

Separation (O5). The clean baseline scores 28 (low) and every compromised image scores between 60 and 97. The planted-keys VM (67) sits between them, as it should: it holds weak and recoverable keys but no attacker activity. Ranges are wide where little evidence exists (the baseline spans 1 to 51) and narrow where a critical finding dominates (RedLine 95 to 99), so the range shows how much the score depends on our choice of band midpoints. For the four critical images the band holds at both ends of the range.

A worked case. On the case-001 desktop, Volatility listed 95 processes and 115 connections; region grading reduced seven RWX regions to two critical findings, a PE header in the print spooler and PowerShell with five injected regions. The 188 MB capture held 546 TLS 1.2 handshakes, all with ECDHE and AES-GCM, and the network stage correctly raised nothing. Compromise is 95 from the memory source alone, exposure only 20, giving $100(1 - 0.05 \cdot 0.9) = 96$ (Fig. 3). The domain controller from the same case scores the same, and campaign linking joins the two through the `coreupdater` process and the identical spooler injection.

D. Keys recovered from real memory

The WannaCry image yields four RSA-2048 private keys (Fig. 5): two from CryptoAPI private-key blobs still held by the two `@WanaDecryptor@` processes, and two rebuilt from primes left in the memory of the dropper process after the key pair was generated, the flaw that WanaKiwi used to decrypt victims' files. Each passes both checks (the prime divides n; the round trip decrypts). On Ramnit, three AES keys (two AES-128, one AES-256) of `ChromeSetup.exe` were recovered from their expanded schedules. Across all images 447 RSA keys were assessed and 12 are broken, mostly 512-bit keys; the four Windows images that carry the same RSA-512 public key in the certificate store are graded medium rather than critical, because nothing shows the host relies on it.

E. Cipher identification on real images

On real images identification separates implementation from mention. On the WannaCry image AES, P-256, RSA, AES-GCM, secp256k1, DES and ChaCha20 are backed by implementation constants, while 3DES and Curve25519 are only named (Fig. 4). As the benchmark showed, this says which ciphers the loaded libraries contain; the recovered RSA keys, not the constants, show what WannaCry actually used.

F. False positives found and removed

Reading every high and critical finding across the collection exposed benign patterns that the first version scored as attacks. The clean Ubuntu baseline initially scored 82, through libffi trampolines graded as injected code; M57 scored 86 through Windows XP heap segments and OpenOffice UNO call thunks; and the campaign linker joined Linux images through kernel threads (`pool_workqueue`, `ecryptfs`, `edac`). Each pattern was proven benign before being downgraded (Section III), which brought the baseline to 28 and M57 to 42, while attacker tools such as PowerShell with unique injected code stay high. The Windows built-in RSA-512 keys and JIT hosts (.NET, SmartScreen) were handled the same way.

TABLE VIII
VALIDATION OF THE 14 LLM REPORTS

Image	Claim lines	Cited	Stated risk = ours
Win 11	47	93.6%	74 = 74
Win 10	42	95.2%	96 = 96
Win 7	22	100%	60 = 60
WannaCry	29	100%	95 = 95
Ubuntu 22.04	31	96.8%	89 = 89
M57	62	90.3%	42 = 42
Seized	30	100%	82 = 82
Reveal	84	97.6%	86 = 86
Brave	62	95.2%	89 = 89
Lab, planted	35	94.3%	67 = 67
RedLine	41	95.1%	97 = 97
Ramnit	56	96.4%	82 = 82
Lab, clean	27	100%	28 = 28
Server 2012 R2	61	98.4%	96 = 96

G. LLM reports on real images

All 14 LLM reports pass validation (Table VIII): between 90.3% and 100% of claim lines cite a finding, no cited id is invented, and the risk each report states equals the computed risk exactly (O6). This was not true at first. Earlier versions of the checker missed citations written as ranges, in parentheses or in table cells, and counted table headers and sign-off lines as claims, which held rates at 55 to 75%. The checker also caught a real model error: one Windows 7 report raised the risk from 60 to 90, was flagged, and was regenerated. Our own checker had a bug of the same kind: it read the M57 exposure as 512 by skipping a parenthesised (55/100)", which a regression test now covers. Reports were regenerated from the rescored findings, so their figures match Table VII.

Why these columns. Table VIII reports exactly the two acceptance tests of objective O6: the share of claim lines that cite a finding, and whether the risk the report states matches the computed one. Claim lines are listed so the rate can be checked against its denominator.

H. Red-team results

Table IX and Fig. 8 give attack success in both rounds. In round 1, 4 of 36 undefended reports did what the attacker wanted (risk downplayed once, a forged citation once, Defender disabled twice) against 0 of 36 defended. In round 2 the model itself resisted almost every attack: only *number_tamper* succeeded undefended (2/6, both through the OTP field), and defended reports succeeded 0/90 times. No successful attack in either round reached a reader without a warning (O7).

Why these measures. ASR answers whether the model was fooled. With at most 90 trials and rates near zero, a bare percentage hides how uncertain it is, so we add Wilson intervals, which stay valid near 0%, and Fisher's exact test, which is correct for small counts where a chi-square test is not. "Reached reader unflagged" is the measure that matters most in practice: a fooled report that ships with a warning misleads no one. The citation rate and cross-check rate show what the defences change even when the model resists on its own.

TABLE IX
ATTACK SUCCESS, CITATION RATE AND CROSS-CHECK, UNDEFENDED VS. DEFENDED

	Round 1 (6 attacks)		Round 2 (15 attacks)	
	base	def.	base	def.
ASR	4/36	0/36	2/90	0/90
95% Wilson	4–25%	0–10%	1–8%	0–4%
Fisher exact p	0.115		0.497	
Reached reader unflagged	n/a	0	n/a	0
Cited claim lines	28%	78%	37%	67%
Cross-check passed	38/39	39/39	84/93	91/93

Fig. 7 shows every trial of round 2 in the dashboard.

The adaptive attacker matters for interpreting D1. Hardening the sanitiser (normalisation, look-alike mapping, base64 decoding) raised its catch rate on fixed payloads from 10/20 to 14/20, yet rewording still slipped 16/20 adaptive payloads past it. Input filtering is therefore only a first layer; what held were the output checks (D3, D4), which judge the report rather than the payload. *number_tamper* illustrates this: the undefended model copied a planted confidence into its table twice, and the defended pipeline caught every such row because D4 compares each table number with the value of the finding that row cites.

Neither drop is statistically significant on its own (Fisher $p = 0.115$ and 0.497), because the model already resists most attacks without help. The defensible claim is the unflagged rate: with 0/126 defended successes across both rounds, the 95% upper bound on misleading a reader is about 3%. Citation rates in the red team (67 to 78% defended) were measured with the earlier checker; the real-image reports above, scored with the final checker, reach 90 to 100%.

I. Campaign linking

Linking correctly joins the case-001 desktop and domain controller (shared `coreupdater` process and the identical `spoolsv.exe` injection). It also links the four CyberDefenders Windows 10 images to one another and to the desktop, through stock Store apps (`WWAHost`, `SkypeApp`, `LockApp`) and Microsoft endpoints (13.107.0.0/16, 204.79.197.0/24). These are not one intrusion; they share a Windows build, and the known-normal baseline does not yet list those apps and address ranges. Of eight linked pairs only one is a true campaign link, so this component needs a larger baseline before its output can be trusted.

J. Threats to validity

Internal. Region grading and finding severities are heuristics tuned on these images; the formulas are sourced, but the band midpoint and the 0.5 reliability are our choices, which the ranges expose. *External.* Public training images are curated and smaller than production servers; the CyberDefenders images share a base build. *Construct.*




Fig. 7. Red-team view: attack success in both rounds with Wilson intervals, what the defences add, and every trial of round 2 per attack and injection field (red: the attack succeeded).




Fig. 8. Attack success with 95% Wilson upper bounds. Defended success is 0 in both rounds; the intervals show how much risk the trial count can still hide.

A citation proves the cited finding exists, not that the sentence about it is correct, and the red team uses one model, synthetic payloads and 6 trials per cell.

V. Conclusion and Future Work

A. Summary of contributions

TriageGuard turns a Windows or Linux memory image into numbered, cited findings, a sourced risk score with an uncertainty range, and a readable report that an LLM writes but cannot be steered by the evidence. Its cryptographic stage goes past naming ciphers: it states the evidence basis of each identification, grades every RSA key against NIST, and recovers live AES, ChaCha20 and RSA private keys, including four RSA-2048 keys from real WannaCry memory. On 14 images the scores separate a clean baseline (28) from compromised hosts (60 to 97); all 12 ground-truth checks pass; and all 14 LLM reports cite 90 to 100% of their claims with the risk stated exactly. Across 126 defended red-team reports, including adaptive attacks, no attack succeeded and none would have misled a reader without a warning. All seven objectives are met.

Three lessons generalise. Real data, not synthetic samples, drove most of the useful changes: the first Windows 11 run produced 689 findings and a risk of 100, and every benign pattern we later downgraded came from reading real output. Identification by constants overstates what is in use, so recovered keys are the stronger evidence. And input filtering alone does not stop an adaptive attacker; checking the output against deterministic results does.

B. Limitations

- Linux images need the exact kernel's symbol table; without it Volatility cannot parse the image.
- Keys are recovered only while live (0/15 after release in the benchmark), except where the platform leaves them behind, as legacy CryptoAPI does.
- Signature scanning finds known constants; a custom or obfuscated cipher would not match.

- The RSA prime search skips processes over 192 MB; the pcap reader stops at 50,000 packets.
- Red-team cells hold 6 trials, one model and synthetic payloads, so 0/126 bounds the unflagged rate at about 3% rather than proving it zero.
- Campaign linking produces false links between images of the same Windows build.
- Severities and region grading are heuristics tuned on public images.

C. Future work

- **Linking baseline.** Learn the known-normal process and endpoint set from clean images of each OS build, so stock apps and vendor endpoints stop creating links.
- **More recovery targets.** TLS session secrets [8], Salsa20 ransomware contexts [7] and elliptic-curve private scalars.
- **Stronger red-team.** More trials per cell, several models (including a local one), multi-field attacks and attacks aimed at the cross-check itself.
- **Post-quantum readiness.** ML-KEM (FIPS 203) and ML-DSA keys will start to appear in memory; identifying their constants and flagging hosts that still rely only on RSA and ECC for key exchange is a natural extension of the cryptographic stage.
- **Scale.** Running Volatility plugins in parallel and caching symbol tables to bring the 22-minute run on a 4.3 GB image down for larger servers.

Code and data availability

Source code, all exported results and the formulas behind every score are at https://github.com/HalcyonVector/Triageguard; a read-only dashboard over all 14 images is at https://halcyonvector.github.io/Triageguard/. Evaluation used public training images and synthetic keys only.

References

[1] H. Oz, A. Aris, A. Levi, and A. S. Uluagac, "A survey on ransomware: Evolution, taxonomy, and defense solutions," *ACM Computing Surveys*, vol. 54, no. 11s, 2022.

[2] D. B. Oh, D. Kim, D. Kim, and H. K. Kim, "volGPT: Evaluation on triaging ransomware process in memory forensics with large language model," *Forensic Science International: Digital Investigation*, vol. 49, p. 301756, Jul. 2024.

[3] B. Sharma, J. Ghawaly, K. McCleary, A. M. Webb, and I. Baggili, "ForensicLLM: A local large language model for digital forensics," *Forensic Science International: Digital Investigation*, vol. 52, p. 301872, Mar. 2025.

[4] M. Scanlon, F. Breitinger, C. Hargreaves, J.-N. Hilgert, and J. Sheppard, "ChatGPT for digital forensic investigation: The good, the bad, and the unknown," *Forensic Science International: Digital Investigation*, vol. 46, p. 301609, 2023.

[5] K. Greshake, S. Abdelnabi, S. Mishra, C. Endres, T. Holz, and M. Fritz, "Not what you've signed up for: Compromising real-world LLM-integrated applications with indirect prompt injection," in *Proc. 16th ACM Workshop on Artificial Intelligence and Security (AISec)*, 2023.

[6] T. Carrier, P. Victor, A. Tekeoglu, and A. H. Lashkari, "Detecting obfuscated malware using memory feature engineering," in *Proc. 8th International Conference on Information Systems Security and Privacy (ICISSP)*, 2022, pp. 177–188.

[7] L. Fernandez de Loaysa Babiano, R. Macfarlane, and S. R. Davies, "Evaluation of live forensic techniques, towards Salsa20-based cryptographic ransomware mitigation," *Forensic Science International: Digital Investigation*, vol. 46, p. 301572, 2023.

[8] D. Baier, A. Basse, J.-N. Hilgert, and M. Lambertz, "TLS key material identification and extraction in memory: Current state and future challenges," in *Proc. DFRWS USA*, 2024.

[9] E. Pelofske, "An efficient all-to-all GCD algorithm for low entropy RSA key factorization," Cryptology ePrint Archive, Paper 2024/699, 2024.

[10] K. Hines, G. Lopez, M. Hall, F. Zarfati, Y. Zunger, and E. Kiciman, "Defending against indirect prompt injection attacks with spotlighting," arXiv:2403.14720, 2024.

[11] Y. Liu, Y. Jia, R. Geng, J. Jia, and N. Z. Gong, "Formalizing and benchmarking prompt injection attacks and defenses," in *Proc. 33rd USENIX Security Symposium*, 2024.

[12] F. Casino, D. Hurley-Smith, J. Hernandez-Castro, and C. Patsakis, "Not on my watch: ransomware detection through classification of high-entropy file segments," *Journal of Cybersecurity*, vol. 11, no. 1, p. tyaf009, 2025.

[13] C. Meijer, V. Moonsamy, and J. Wetzels, "Where's crypto?: Automated identification and classification of proprietary cryptographic primitives in binary code," in *Proc. 30th USENIX Security Symposium*, 2021.

[14] G. Barnes and A. Ghafarian, "Machine learning-based static ransomware detection using PE header features and SHAP interpretation," *Journal of Cybersecurity and Privacy*, vol. 6, no. 2, p. 58, 2026.

[15] M. H. M. Baig, H. B. Ul Haq, and W. Habib, "A comparative analysis of AES, RSA, and 3DES encryption standards based on speed and performance," *Management Science Advances*, vol. 1, no. 1, pp. 20–30, 2024.

[16] W. N. A. Ruzai, Y. Ying, K. N. Muhammad, M. A. Asbullah, and M. R. K. Ariffin, "Concurrent factorization of RSA moduli via weak key equations," *AIMS Mathematics*, vol. 9, no. 10, pp. 28 211–28 231, 2024.

[17] A. Raghu, "A context-aware framework for secure fintech APIs: Leveraging Java Spring Boot and OAuth 2.0 with dynamic token adaptation," *Journal of Information Systems Engineering and Management*, vol. 10, no. 49s, pp. 367–377, 2025.

[18] P. Rujichaikul and I. Rassameeroj, "Token-based authentication monitoring system," *Journal of Cyber Security and Mobility*, vol. 14, no. 4, pp. 777–798, 2025.