

Question 1:

What is the output of the following code?

```
print(list(range(5, 0)))
```

A. RangeError

B. []

C. [0,1,2,3,4,5]

D. [5,4,3,2,1]

Answer: B. []

Question 2:

What will be printed by the following code?

```
def my_func(a_list, a_num=0, a_string="):
```

```
    print(a_list, a_num, a_string)
```

```
my_func(a_num=5, a_list=['cat','dog'])
```

A. ['cat','dog'], ", 5

B. Error

C. 5, ['cat','dog'], "

D. ['cat','dog'], 5, "

Answer: D. ['cat','dog'], 5, "

Question 3:

What is the output?

```
class Team:
```

```
    def __init__(self, members):
```

```
        self._members = members
```

```
    print('Jen' in Team(['Jen','Bob']))
```

A. False

B. TypeError

C. True

D. Jen

Answer: B. TypeError

Question 4:

Which demonstrates the Container Protocol?

A. 5 in range(10)

B. print(list(range(0,10,2)))

C. for x in range(5)

D. len([1,2,3])

Answer: A. 5 in range(10)

Question 5:

What is the output?

```
def print_message(message=[]):  
    message.append('Hi')  
    print(message)  
    print_message()  
    print_message()
```

- A. ['Hi'], ['Hi']
- B. ['Hi'], ['Hi', 'Hi']
- C. ['Hi'], ['Hi', 'Hi', 'Hi']
- D. ['Hi', 'Hi'], ['Hi', 'Hi', 'Hi']

Answer: B. ['Hi'], ['Hi', 'Hi']

Question 6:

Which method implements sized protocol?

- A. `__iter__`
- B. `__contains__`
- C. `__len__`
- D. `__size__`

Answer: C. `__len__`