


> Mark Smith, N6MTS

Who am I?




Mark Smith, N6MTS

- Head Cheese, Halibut Electronics: https://electronics.halibut.com/
- A host of the Ham Radio Workbench Podcast: https://www.hamradioworkbench.com/
- Twitter and YouTube: @SmittyHalibut
- Mastodon/Fediverse: @smitty@halibut.com




Who am I?

• Ham: Active ham since 1992.



- Work: ~30 years in IT, Network and Unix Systems Engineering, and Information Security.
- All Three: Left IT in 2021, started Halibut Electronics to make Ham Radio and Audiophile electronics.
- First big product, SOAR: Satellite Optimized Amateur Radio. Available late 2022.









• **Open**: Any individual or company may make devices compliant with this standard, with no obligation.



- **Open**: Any individual or company may make devices compliant with this standard, with no obligation.
- **Headset**: Describes the signaling commonly found between a user and a radio: Microphone, Headphones, and Push To Talk.



- **Open**: Any individual or company may make devices compliant with this standard, with no obligation.
- **Headset**: Describes the signaling commonly found between a user and a radio: Microphone, Headphones, and Push To Talk.
- Interconnect: Describes both the physical and electrical connection of those signals between the user and radio.



- **Open**: Any individual or company may make devices compliant with this standard, with no obligation.
- **Headset**: Describes the signaling commonly found between a user and a radio: Microphone, Headphones, and Push To Talk.
- Interconnect: Describes both the physical and electrical connection of those signals between the user and radio.
- **Standard**: Devices built to this standard will work with other devices built to the same standard.



Electrical Standards


We have electrical standards (defined, or defacto) for things like RF and Power:



Electrical Standards

We have electrical standards (defined, or defacto) for things like RF and Power:

• RF: 50 ohm impedance coax, 450 ohm twin lead





Electrical Standards

We have electrical standards (defined, or defacto) for things like RF and Power:

• RF: 50 ohm impedance coax, 450 ohm twin lead



• Power: +13.8vDC +/- 15%



Physical Standards

And one, or a few, physical standards that are easy to convert between:



Physical Standards

And one, or a few, physical standards that are easy to convert between:

• RF: PL-259, Type N, BNC, etc









Physical Standards

And one, or a few, physical standards that are easy to convert between:

• RF: PL-259, Type N, BNC, etc









• Power: Powerpole, 6-pin "Molex", "T" blades, etc





No such electrical standards exist for the User to Radio interface:



No such electrical standards exist for the User to Radio interface:

 Microphone: Dynamic, Electret, or Carbon? Balanced or single ended?



No such electrical standards exist for the User to Radio interface:

- Microphone: Dynamic, Electret, or Carbon? Balanced or single ended?
- Audio out: Line level, headphone level, or speaker level? Ground referenced or push-pull? Mono or stereo?



No such electrical standards exist for the User to Radio interface:

- Microphone: Dynamic, Electret, or Carbon? Balanced or single ended?
- Audio out: Line level, headphone level, or speaker level? Ground referenced or push-pull? Mono or stereo?
- PTT: GPIO style contact closure to ground, or completing the mic circuit?



There are even more physical options to choose from!



There are even more physical options to choose from!

• **Microphone**: 3.5mm TS/TRS? ¼" TS/TRS? XLR? "8-pin round" Aviation? 8 pin modular? 6 pin modular? What pinout?



There are even more physical options to choose from!

- **Microphone**: 3.5mm TS/TRS? ¼" TS/TRS? XLR? "8-pin round" Aviation? 8 pin modular? 6 pin modular? What pinout?
- Audio out: 3.5mm TS/TRS? 1/4" TS/TRS? RCA?




There are even more physical options to choose from!

- **Microphone**: 3.5mm TS/TRS? ¼" TS/TRS? XLR? "8-pin round" Aviation? 8 pin modular? 6 pin modular? What pinout?
- Audio out: 3.5mm TS/TRS? 1/4" TS/TRS? RCA?
- PTT: On the mic connector? 3.5mm TS? 1/4" TS?




The problem is...

Heil Pro 7 Headset:



Yaesu FT-920 Microphone pinout:



The solution?

Heil AD-1-Y Adapter:

Heil Pro 7 Headset:





rophone pinout:


MIC

- D UP
- ② +5V
- ③ DOWN
- ④ FAST
- 5) GND
- B) PTT
- ⑦ MIC GND
- B) MIC


as viewed from front panel

But, I've got a Kenwood too.

Kenwood TS-890S Microphone pinout:




Yaesu FT-920 Microphone pinout:




But, I've got a Kenwood too.

Heil Pro 7 Headset:



Kenwood TS-890S Microphone pinout:



Bob has me covered...

Heil Pro 7 Headset:

Heil AD-1-K Adapter:



Microphone pinout:

— (8) GND (STBY)

____ (7) GND (MIC)

- 6 NC

— ⑤ 8V (10mA max)


Connector ront Panel)

What about Icom?

Heil Pro 7 Headset:




Icom IC-7300 Microphone pinout:




Same connect-- oh... Never mind...


Yaesu FT-920 Microphone pinout:



Kenwood TS-890S Microphone pinout:



Icom IC-7300 Microphone pinout:




What about Icom?

Heil Pro 7 Headset:



Icom IC-7300 Microphone pinout:



Bob still has me covered...

Heil Pro 7 Head:




Heil AD-1-iC Adapter:



none pinout:

AF output



Squelch line output

But, wait a minute...

Heil AD-1-iC Adapter: Heil Pro 7 Head: Heil P7-IC-ELEM Microphone Element: Mono Pro 7
Headset Cartridge Plug able

none pinout:

AF output

(Microphone ground)


6 GND (PTT ground)

5 PTT


Squelch line output

Another headset,

CTIA "PC Gaming Headset" or "Mobile Phone" pinout:



Yaesu FT-920 Microphone pinout:




Another headset, 3 more adapters...

CTIA "PC Gaming Headset" Yaesu FT-920 Microphone pinout: or "Mobile Phone" pinout: MIC Kenwood TS-890S Microphone pinout: UP +5V (8) GND (STBY) DOWN MIC FAST GND (MIC) GND Icom IC-7300 Microphone pinout: PTT MIC GND 6 NC (8) AF output MIC - (5) 8V (10mA max) 1 Microphone input as viewed from front panel GND (Microphone ground) 2 +8 V DC output-6 GND (PTT ground) onnector ont Panel) 3 Microphone key (5) PTT input (up/down) Video Squelch line output

"Your audio is distorted!"


CTIA "PC Gaming Headset" or "Mobile Phone" pinout:

Yaesu FT-920 Microphone pinout:



Which 3.5mm TRRS was that?


CTIA "PC Gaming Headset" or "Mobile Phone" pinout:





Which 3.5mm TRRS was that?

CTIA "PC Gaming Headset" or "Mobile Phone" pinout:





Your Adapter Game is strong.

This is quickly getting out of hand.

It's a full mesh of adapters, from every different headset to every different radio.




Your Adapter Game is strong.


This is quickly getting out of hand.

It's a full mesh of adapters, from every different headset to every different radio.


How do we address this?








• **User** side adapter: Specific to the headset, stays with the headset.



- **User** side adapter: Specific to the headset, stays with the headset.
- Radio side adapter: Specific to the radio, stays with the radio.





- User side adapter: Specific to the headset, stays with the headset.
- Radio side adapter: Specific to the radio, stays with the radio.
- Open Headset Interconnect Standard is the connection between them.



Electrical:



Electrical:

• **Microphone**: Electret level. +5vDC bias provided by Radio.



Electrical:

- **Microphone**: Electret level. +5vDC bias provided by Radio.
- Audio Out: Ground referenced, "Headphone" level, stereo.



Electrical:

- **Microphone**: Electret level. +5vDC bias provided by Radio.
- Audio Out: Ground referenced, "Headphone" level, stereo.
- PTT: Simple contact closure to ground.



Electrical:

- **Microphone**: Electret level. +5vDC bias provided by Radio.
- Audio Out: Ground referenced, "Headphone" level, stereo.
- PTT: Simple contact closure to ground.
- **Power**: +5vDC 200mA provided by Radio for audio amplifiers, LED indicators, signal processing, etc.



Physical:



Physical:

• Connector: 8P8C Modular. (Commonly, but incorrectly, known as RJ-45.)



Physical:

- Connector: 8P8C Modular. (Commonly, but incorrectly, known as RJ-45.)
- Cable: Cat5 or better. Shielded is preferred but not required.



Physical:

- Connector: 8P8C Modular. (Commonly, but incorrectly, known as RJ-45.)
- Cable: Cat5 or better. Shielded is preferred but not required.
- Wiring: TIA-568A or 568B. Which pins are pairs is important.




Physical:

- Connector: 8P8C Modular. (Commonly, but incorrectly, known as RJ-45.)
- Cable: Cat5 or better. Shielded is preferred but not required.
- Wiring: TIA-568A or 568B. Which pins are pairs is important.


Allows the use of common off-the-shelf Ethernet cables.



Pin-out:




Pin-out:



Dynamic Mic Pre-Amp

Part of the open standard, freely available for use.



Technical Details...

See the QR codes at the end of this presentation for the Standard Document, the Groups.io email list, and GitHub repository.





When you have several different radios and headsets.



- When you have several different radios and headsets.
- When you operate in a shared environment and users have their own (different) headsets.



- When you have several different radios and headsets.
- When you operate in a shared environment and users have their own (different) headsets.
 - Examples: Field Day, club shack, or an Emergency Operations Center.



- When you have several different radios and headsets.
- When you operate in a shared environment and users have their own (different) headsets.
 - Examples: Field Day, club shack, or an Emergency Operations Center.
- When you want to design and sell a device that goes between the User and the Radio, and have it work everywhere without overly complex input and output interfacing.



- When you have several different radios and headsets.
- When you operate in a shared environment and users have their own (different) headsets.
 - Examples: Field Day, club shack, or an Emergency Operations Center.
- When you want to design and sell a device that goes between the User and the Radio, and have it work everywhere without overly complex input and output interfacing.





 When you only have one radio, or one headset, or any situation where the "full mesh" problem doesn't apply.



- When you only have one radio, or one headset, or any situation where the "full mesh" problem doesn't apply.
- When you already have all the adapters you need.



- When you only have one radio, or one headset, or any situation where the "full mesh" problem doesn't apply.
- When you already have all the adapters you need.
- When you prefer the simplicity of a single adapter between you and your radio.





Open is how we get out of this mess.



- Open is how we get out of this mess.
- Halibut Electronics needed to solve this problem for future products, and I am not Gillette.



- Open is how we get out of this mess.
- Halibut Electronics needed to solve this problem for future products, and I am not Gillette.
- This is a good DIY project, and I love DIY projects



Learn more



The Standard document:

https://halibut-electronics.github.io/Open-Headset-Interconnect-Standard/Open-Headset-Interconnect-Standard.pdf



GitHub repository:

https://github.com/Halibut-Electronics/Open-Headset-Interconnect-Standard



Groups.io mailing list:

https://halibut-electronics.groups.io/open-headset-interconnect-standard/



Questions and Answers

Beginning now



Slide Title

Slide Content

