4G · GNSS · BLUETOOTH · RFID

# HB-A1M

## 4G Explosion-Proof Electronic Lock

A compact, secure and smart lock

CE ATEX IP67




### About the HB-A1M

HB-A1M is a 4G-connected, explosion-proof (ATEX) electronic lock built for logistics and industrial use. Its compact size, light weight, long standby time and smart alarms give you a high level of security and control.

### Where it is used

- Containers
- Tankers
- Logistics vehicles
- Steel safes
- Fuel tank caps

### Key features

- Extra-long standby time (20 days)
- Small and lightweight design
- Multi-lock cascading
- IP67 waterproof
- Smart alarm system and Ex-proof housing

# Specifications

| Physical | |
|---|---|
| Dimensions | 124 × 95 × 47 mm |
| Weight | 544 g |
| Shackle strength | 1,000 kg |

| GNSS positioning | |
|---|---|
| Acquisition / tracking sensitivity | −147 dBm / −166 dBm |
| Tracking accuracy | 1.5 m |
| Time to first fix | Hot 1 s · Warm 25 s · Cold 28 s |

| Connectivity | |
|---|---|
| Network | 4G LTE / WCDMA / GSM |
| Data protocols | TCP / FTP / SMS |

| Unlocking modes | |
|---|---|
| RFID | 2.5 cm |
| Bluetooth | BLE 4.0 (range 20 m) |
| GPRS / SMS | No distance limit |

| Power / battery | |
|---|---|
| Main battery | 2,950 mAh Li-ion · 3.7 V · 10.9 Wh |
| USB charging | 5 V DC 2 A |
| Charging time | 6 hours |
| Standby time | 22 days (reporting every 10 minutes) |

| Operating environment | |
|---|---|
| Operating / storage | −30 °C to +70 °C |
| Charging temperature | 0 °C to +45 °C |
| Mounting | Magnetic attachment |

# Certifications and standards

## CE

Complies with safety and environmental protection standards.

## ATEX

Suitable for use in explosive atmospheres.

## IP67

Rated for protection against dust and water ingress.