

# E-R model, Relational model, SQL

Hogeschool Rotterdam  
Rotterdam, Netherlands

## Lecture topics

- E-R model.
- Relational model.
- SQL, and examples.

E-R model,  
Relational  
model, SQL

Introduction

Data models

E-R model

Relational  
model

SQL

## database design process

- Requirements analysis

## database design process

- Requirements analysis
- Conceptual database design using E-R models

## database design process

- Requirements analysis
- Conceptual database design using E-R models
- Logical database design (sometimes conceptual and logical are merged into one step)

## database design process

- Requirements analysis
- Conceptual database design using E-R models
- Logical database design (sometimes conceptual and logical are merged into one step)
- Schema refinement through normalization

## database design process

- Requirements analysis
- Conceptual database design using E-R models
- Logical database design (sometimes conceptual and logical are merged into one step)
- Schema refinement through normalization
- Physical database design

## database design process

- Requirements analysis
- Conceptual database design using E-R models
- Logical database design (sometimes conceptual and logical are merged into one step)
- Schema refinement through normalization
- Physical database design
- Application and Security Design



## Overview

- Highest level of database modelling.
- Model the conceptual aspect of the database.
- Far from the physical representation in the DBMS.

## Entity

- Anything which can exist on its own on the database
- Consider a database for a space shooter game
- Starships, asteroids are entities, they have a meaning on their own

## Attributes

- They model characteristics of the entity.
- **Starship:** velocity, shield, armour, weapon, [...]
- **Asteroid:** velocity, mass, integrity, [...]

## Relations

- They describe the associations among entities (two or more).
- They have a cardinality: number of participants for each side.

## Relations - 1 : 1

- Entity modelling a pilot and one modelling a starship.
- Related by “drives”.
- The cardinality is 1:1 : one pilot drives at most one starship, and one starship can contain only one pilot.

## Relations - 1 : N

- Entity modelling a starship and one modelling a weapon.
- Related by “mounted”
- The cardinality is 1:N : a weapon can be mounted only on one starship, but a starship can mount more than one weapon.

## Relations - N : M

- Entity modelling a starship and one modelling an asteroid.
- Related by “collides with”
- The cardinality is N : M : several starships can collide with several asteroids.

## Keys

- A way to uniquely identify an entity.
- A key is a set of attributes that have unique values among entities.
- **Starship:** id number.



## Weak entities

- Entities which do not have a key attribute.
- **Asteroids:** There can be two asteroids with the same position, same mass, velocity, etc.

## Overview

- Halfway between a conceptual model and the physical model.
- Contain an abstraction of physical elements.
- Can be easily mapped to a physical implementation in a DBMS.
- There are mapping rules from E-R model to the relational model.

## Relation

- A relation is a collection of tuples.
- Each element of a tuple is a value taken from an attribute set.
- Each attribute set is identified by a name

| Ships     |      |         |        |           |
|-----------|------|---------|--------|-----------|
| <u>id</u> | name | shields | armour | integrity |

(38258269, "Battlestar Galactica", 3000, 5000, 1.0)

## Keys

- A *Primary key* is a set of attributes with unique values in each tuple.
- A *Candidate key* is the smallest set of attributes which form a superkey.

### Example:

**Primary key:** (id, name, shield)

**Candidate key:** (id)

## Keys

- A *Primary key* is the chosen key for a relation among all the candidate keys.
- A *Foreign key* is a set of attributes in one relation which is a primary key in another relation.

### Example (Foreign key):

| Mounts        |                   |
|---------------|-------------------|
| <u>shipid</u> | <u>weaponName</u> |

| Ships     |      |         |        |           |
|-----------|------|---------|--------|-----------|
| <u>id</u> | name | shields | armour | integrity |

In the relation Mounts the attribute shipid is a foreign key to Ships.

## Overview

- Used to create relations (tables).
- Used to insert/modify/extract data from relations (tables).
- Declarative language (“What” not “How”).

| Ships     |      |         |        |           |
|-----------|------|---------|--------|-----------|
| <u>id</u> | name | shields | armour | integrity |

**Select all ships from the game**

| Ships     |      |         |        |           |
|-----------|------|---------|--------|-----------|
| <u>id</u> | name | shields | armour | integrity |

Select all ships from the game

```
SELECT *  
FROM Ships
```



| Ships     |      |         |        |           |
|-----------|------|---------|--------|-----------|
| <u>id</u> | name | shields | armour | integrity |

**Select all ships in the game whose pilot is “William Adama”**

| Ships     |      |         |        |           |
|-----------|------|---------|--------|-----------|
| <u>id</u> | name | shields | armour | integrity |

**Select all ships in the game whose pilot is “William Adama”**

```
SELECT *  
FROM Ships s  
WHERE s.pilot = 'William_Adama'
```

| Ships     |      |         |        |           |
|-----------|------|---------|--------|-----------|
| <u>id</u> | name | shields | armour | integrity |

**Find the name of the ships whose pilot is “Starbucks”**

| Ships     |      |         |        |           |
|-----------|------|---------|--------|-----------|
| <u>id</u> | name | shields | armour | integrity |

**Find the name of the ships whose pilot is “Starbucks”**

```
SELECT s.name  
FROM Ship s  
where s.pilot = 'Starbucks'
```

| Ships     |      |         |        |           |
|-----------|------|---------|--------|-----------|
| <u>id</u> | name | shields | armour | integrity |

| Mounts        |                   |
|---------------|-------------------|
| <u>shipid</u> | <u>weaponName</u> |

| Weapons     |        |      |
|-------------|--------|------|
| <u>name</u> | damage | type |

**Find the id of the ships mounting the weapon  
“Stealthblade MKII”**

| Ships     |      |         |        |           |
|-----------|------|---------|--------|-----------|
| <u>id</u> | name | shields | armour | integrity |

| Mounts        |                   |
|---------------|-------------------|
| <u>shipid</u> | <u>weaponName</u> |

| Weapons     |        |      |
|-------------|--------|------|
| <u>name</u> | damage | type |

**Find the id of the ships mounting the weapon  
“Stealthblade MKII”**

```
SELECT s.id
FROM Ship s, Mounts m
WHERE s.id = m.shipid AND
      m.weaponName = 'StealthBlade MKII'
```

| Ships     |      |         |        |           |
|-----------|------|---------|--------|-----------|
| <u>id</u> | name | shields | armour | integrity |

| Mounts        |                   |
|---------------|-------------------|
| <u>shipid</u> | <u>weaponName</u> |

| Weapons     |        |      |
|-------------|--------|------|
| <u>name</u> | damage | type |

**Find the name of all the weapons mounted in the ships  
flown by “Apollo”**

| Ships     |      |         |        |           |
|-----------|------|---------|--------|-----------|
| <u>id</u> | name | shields | armour | integrity |

| Mounts        |                   |
|---------------|-------------------|
| <u>shipid</u> | <u>weaponName</u> |

| Weapons     |        |      |
|-------------|--------|------|
| <u>name</u> | damage | type |

**Find the name of all the weapons mounted in the ships  
flown by “Apollo”**

```
SELECT w.name
FROM Ship s, Mounts m, Weapon w
WHERE s.id = m.Shipid AND
      m.weaponName = w.name AND
      s.pilot = 'Apollo'
```



| Ship          |      |       |         |        |           |
|---------------|------|-------|---------|--------|-----------|
| <u>Serial</u> | Name | Pilot | Shields | Armour | Integrity |

| Mounts            |                   |       |
|-------------------|-------------------|-------|
| <u>ShipSerial</u> | <u>WeaponName</u> | Count |

| Weapons     |        |      |
|-------------|--------|------|
| <u>name</u> | damage | type |

**Find the total damage output of the ships flown by  
“Athena”**

| Ship          |      |       |         |        |           |
|---------------|------|-------|---------|--------|-----------|
| <u>Serial</u> | Name | Pilot | Shields | Armour | Integrity |

| Mounts            |                   |       |
|-------------------|-------------------|-------|
| <u>ShipSerial</u> | <u>WeaponName</u> | Count |

| Weapons     |        |      |
|-------------|--------|------|
| <u>name</u> | damage | type |

**Find the total damage output of the ships flown by  
"Athena"**

```
SELECT SUM(w.damage) AS damage
FROM Ship s, Mounts m, Weapon w
WHERE s.id = m.shipid AND
      m.weaponName = w.name AND
      s.pilot = 'Athena'
```

| Ships     |      |         |        |           |
|-----------|------|---------|--------|-----------|
| <u>id</u> | name | shields | armour | integrity |

| Mounts        |                   |
|---------------|-------------------|
| <u>shipid</u> | <u>weaponName</u> |

| Weapon      |        |      |
|-------------|--------|------|
| <u>name</u> | damage | type |

**Count all the ships having more than 3 weapons**

| Ships     |      |         |        |           |
|-----------|------|---------|--------|-----------|
| <u>id</u> | name | shields | armour | integrity |

| Mounts        |                   |
|---------------|-------------------|
| <u>shipid</u> | <u>weaponName</u> |

| Weapon      |        |      |
|-------------|--------|------|
| <u>name</u> | damage | type |

**Count all the ships having more than 3 weapons**

```
SELECT COUNT(*)  
FROM (  
  SELECT COUNT(*) AS ShipCount  
  FROM Ship s, Mounts m, Weapon w  
  WHERE s.id = m.shipid AND  
         m.weaponName = w.Name  
  GROUP BY s.id  
  HAVING COUNT(*) > 3)
```