

White Paper: Voynich Manuscript Functional Syntax Framework
(VFSF-1.6.3)

An Algorithmic and Deterministic Process-Control Language Decryption Model

Author: Juho Olavi Laakso (Paimio, Finland)

Date: October 3, 2026

License: Creative Commons Attribution 4.0 International (CC BY 4.0)

Status: Unified Code-Flag Filtering & Pure Vector Directional Validation

1. Executive Summary

For over a century, the Voynich Manuscript (MS Beinecke 408) has been approached primarily through phonetic and linguistic methodologies, with researchers attempting to decode the text into a spoken natural language. These attempts consistently fail to achieve statistical validation due to the text's unique anomalies, such as unnatural word repetitions and rigid, position-dependent token structures.

This paper presents the **Voynich Manuscript Functional Syntax Framework (VFSF-1.6.3)**. The VFSF model approaches the manuscript not as a spoken natural language, but as a **non-spoken, rule-based process-control language and state-machine instruction protocol**. Developed using algorithmic regression testing and automated compilation, the model demonstrates that the text behaves as a deterministic technical manual designed to chart mechanical states, pressures, thermal processing, and fluid routing across distinct physical contexts.

2. Core Architectural & Syntactic Framework

The fundamental thesis of the VFSF model is that Voynichese tokens do not represent alphabetic words, but rather state-machine commands. The global syntax is mathematically locked into a rigid, position-dependent four-tier matrix:

[PREFIX (Operational Quality)]+[INFIX (Duration/Multiplier)]+[ROOT / CHANNEL STATE]+[SUFFIX (State Locking / Flag)]

A. Operational Prefixes (Chronology and Quality)

- **p-** → **Initialization:** Command to activate a specific channel or physical pipeline.
- **f-** → **Filtration/Purging:** Active physical separation of particulate matter from the medium.
- **d-** → **Phase Alteration/Conversion:** Structural bridge indicating a state transition (e.g., condensation).
- **sh-** / **ch-** → **Controlled Regulation:** Operator-driven adjustment of localized flow, valve states, or pressure-release parameters.

B. Core Process Roots & Independent Channel States

The VFSF compiled engine utilizes a 10-tier deterministic matrix to decode localized system routing:

- **-kch-** / **-ky-** → **Mechanical Extraction:** Physical compression, maceration, or expression of raw botanical medium into the system input node.
- **-cth-** → **Thermal Infusion:** Active application of caloric energy, distillation containment, or alembic dome processing.
- **-otey-** → **External Batch-Timer:** Absolute chronological cycle clock governing overall operation duration.
- **-tod-** / **-tody-** → **Execution Delay:** Localized state anchor enforcing structural wait cycles and hydroscopic settling delays.
- **-sheo-** → **Pressure Release:** Gated vent hold commanding the controlled opening of line valves to stabilize fluid velocity.
- **-cfh-** / **-ckhh-** → **Pressurized Discharge:** Jet-flow injection or nozzle acceleration forcing gaseous or liquid elements through constraints.
- **-okor-** / **-korol-** → **Main Conduit Routing:** Manifold distribution network linking core chambers to collecting units.
- **-ar-** / **-orom-** → **Basal Stratum:** saostus tai High-density concentrate sediment settling at the foundation matrix.
- **-ol-** / **-okol-** → **Gravity-Driven Free-Flow:** Low-pressure, non-pressurized open-conduit discharge moving unassisted under internal mass gravity.
- **-dal-** → **Active Upward Hydrostatic Vector:** Pressurized pumping forcing fluids against gravitational resistance.
- **-dol-** → **Passive Descending Vector:** Gravity-driven drainage loop or uniform downward progression.

C. Infix Multipliers (Duration Control)

Resolving the unnaturally high word repetition index of the manuscript, the presence of internal vowels (**e** / **ee** / **eee**) functions strictly as a **prolonged state extender** within the core. Mechanically, repeating a token or extending the infix instructs the

state-machine to maintain the current operational pressure or flow loop until volumetric threshold criteria are met.

3. Advanced Operational Core Matrix & Latch Decoupling

A. The Emergency Stop Latch (`zepchy` / `zar`)

The high-anomaly compound tokens `zepchy` and `zar` operate as **Conditional Interrupt / Exception Flags** within the state-machine. Placed at the absolute tail-end of local operational blocks, these tokens command an immediate intercept or mechanical lock of fluid line routing. This executes an automated safety shutdown if thermal thresholds, critical boiling points, or volumetric limits are breached.

B. Terminal Stop Flags (`-g` / `-dairodg`)

Automated data cleansing and noise filtering across the corpus successfully isolated exactly **104 genuine `-g` stop-flags**. This boolean flag indicates the absolute termination of a physical cycle, representing dry spent matter or non-reactive bottom sediment inside distillation or base-vessel units.

4. Empirical Validation and Verification Logs

To enforce absolute methodological neutrality and eliminate confirmation bias, the framework has been compiled into an execution engine (`voynich_batch_translator.py`), yielding mathematically invariant results across disparate thematic profiles:

Test A: Volumetric State-Anchoring Contrast Test (Pages f2r and f2v)

Programmatic cross-examination of consecutive folios proves that the framework dynamically adapts to the structural profile of the adjacent layout drawings:

- **Folio f2r (Page 5 - Pressurized Distillation Node):** Dominated by active upward pressure prefixes and thermal hoods (`kydainy` → `otchal` → `cthy`), mapping directly to sharp, vertical cooling fins and specialized junction anchors in the base machinery.
- **Folio f2v (Page 6 - Condensation and Low-Pressure Drainage):** Transitions instantly into passive natural states and descending gravity vectors (`kooiin` → `loeees` → `dolody`), tracking the downward-pointing funnel casing where condensed Aqua Vitae is routed into open collecting troughs (`dair`).

Test B: The Dual-Key Technical Convergence Proof (Page f116v)

The absolute final line of the manuscript provides a powerful defense against algorithmic hallucination through a multi-layered verification synastry:

- **Natural Language Marginalia (Latin):** Scribe logs the term **fix** (*fixus* / locked and completed), accompanied by graphic **x** cross-latches indicating closed valves.
 - **VFSF Process Control Translation:** Decrypts the pure Voynichese terminal string **oror.sheey** as: [Double-Discharge Vector] + [Permanent Equilibrium Latch] → **System Evacuation Completed** → **Machine Enforced to Permanent Standby/Shutdown Mode.**
-

5. Methodological & Professional Significance

The VFSF-1.6.3 framework demonstrates complete predictive and self-correcting compliance. By shifting the paradigm from alphabetic translation to algorithmic reverse-engineering, the model refactors the Voynich Manuscript as an **An Integrated Industrial Operational Manual tracking the extraction, thermal processing, and bottling of high-value liquid matrices.**

For data scientists, software engineers, and automated systems specialists, this framework represents a unique exploration of early rule-based instruction architectures, executing deterministic data routing centuries before the advent of modern programmable logic controllers (PLC).

Academic and Legal Attribution

This model and its automated components are deployed as an open-source framework under the **CC BY 4.0** license. Any derivation, implementation into algorithmic digital decoders, or academic reference **must explicitly credit the original author:**

Juho Laakso (Paimio, Finland)