

White Paper: Voynich Manuscript Functional Syntax Framework (VFSF-1.6.7)

An Algorithmic and Deterministic Process-Control Language Decryption Model

Author: Juho Olavi Laakso (Paimio, Finland)

Date: October 4, 2026

License: Creative Commons Attribution 4.0 International (CC BY 4.0)

Status: Unified Code-Flag Filtering & Pure Vector Directional Validation

1. Executive Summary

For over a century, the Voynich Manuscript (MS Beinecke 408) has been approached primarily through phonetic and linguistic methodologies, with researchers attempting to decode the text into a spoken natural language. These attempts consistently fail to achieve statistical validation due to the text's unique anomalies, such as unnatural word repetitions and rigid, position-dependent token structures.

This paper presents the **Voynich Manuscript Functional Syntax Framework (VFSF-1.6.7)**. The VFSF model approaches the manuscript not as a spoken natural language, but as a **non-spoken, rule-based process-control language and state-machine instruction protocol**. Developed using algorithmic regression testing and automated compilation, the model demonstrates that the text behaves as a deterministic technical manual designed to chart mechanical states, pressures, thermal processing, and fluid routing across distinct physical contexts.

2. Core Architectural & Syntactic Framework

The fundamental thesis of the VFSF model is that Voynichese tokens do not represent alphabetic words, but rather state-machine commands. The global syntax is mathematically locked into a rigid, position-dependent four-tier matrix:

[*PREFIX (Operational Quality)*] + [*INFIX (Duration/Multiplier)*] + [*ROOT / CHANNEL STATE*]

A. Operational Prefixes (Chronology and Quality)

- **p-** → **Initialization:** Command to activate a specific channel or physical pipeline.
- **f-** → **Filtration/Purging:** Active physical separation of particulate matter from the medium.
- **d-** → **Phase Alteration/Conversion:** Structural bridge indicating a state transition (e.g., condensation).
- **sh-** / **ch-** → **Controlled Regulation:** Operator-driven adjustment of localized flow, valve states, or pressure-release parameters.

B. Core Process Roots & Independent Channel States

The VFSF compiled engine utilizes a 10-tier deterministic matrix to decode localized system routing:

- **-kch-** / **-ky-** → **Mechanical Extraction:** Physical compression, maceration, or expression of raw botanical medium into the system input node.
- **-cth-** → **Thermal Infusion:** Active application of caloric energy, distillation containment, or alembic dome processing.
- **-otey-** → **External Batch-Timer:** Absolute chronological cycle clock governing overall operation duration.
- **-tod-** / **-tody-** → **Execution Delay:** Localized state anchor enforcing structural wait cycles and hydroscopic settling delays.
- **-sheo-** → **Pressure Release:** Gated vent hold commanding the controlled opening of line valves to stabilize fluid velocity.
- **-cfh-** / **-ckhh-** → **Pressurized Discharge:** Jet-flow injection or nozzle acceleration forcing gaseous or liquid elements through constraints [source: 1.1, 7].
- **-okor-** / **-korol-** → **Main Conduit Routing:** Manifold distribution network linking core chambers to collecting units.
- **-ar-** / **-orom-** → **Basal Stratum:** High-density concentrate sediment settling at the foundation matrix.
- **-ol-** / **-okol-** → **Gravity-Driven Free-Flow:** Low-pressure, non-pressurized open-conduit discharge moving unassisted under internal mass gravity.
- **-dal-** → **Active Upward Hydrostatic Vector:** Pressurized pumping forcing fluids against gravitational resistance.
- **-dol-** → **Passive Descending Vector:** Gravity-driven drainage loop or uniform downward progression.

C. Infix Multipliers (Duration Control)

Resolving the unnaturally high word repetition index of the manuscript, the presence of internal vowels (**e** / **ee** / **eee**) functions strictly as a **prolonged state extender** within the core. Mechanically, repeating a token or extending the infix instructs the

state-machine to maintain the current operational pressure or flow loop until volumetric threshold criteria are met.

D. Pictographic Sign-Form Verification and Opcode Atomism

Cross-referencing the structural syntax with original technical brushstrokes demonstrates that individual graphemes function as independent **symbolic opcodes** or graphic schematics tracking mechanical hardware status rather than phonemes [source: 1.6.1]:

- **Gallows Characters (*k* vs *t*):** Vertically rising stroke features represent physical valve stems or pistons [source: 1.6.1]. Single-looped open-right profiles (*k*) command an **Open Junction (Valve Inflow)** permitting low-resistance passage to the next terminal node [source: 1.6.1, 2]. Single-looped self-terminating profiles (*t*) command a **Closed Latch (Pressure Latch)** designed to restrict output and accrue hydrostatic pressure [source: 1, 1.6.1].
- **Bench Characters (*ch* vs *sh*):** Horizontal strokes depict structural conduit contours [source: 1.6.1]. Short, level horizontal alignments (*ch*) indicate an **Unrestricted Open-Conduit** for free fluid conveyance [source: 1.6.1]. Prolonged, step-stepped horizontal alignments (*sh*) signify a **Throttled Velocity Conduit** executing structural constraint to accelerate flow or alter line resistance prior to intercept units [source: 1.1, 7].
- **Loop Control Characters (*o* vs *a*):** Intraline circular geometries govern loop execution paths. Symmetrical, fully closed circular geometries (*o*) command a **Closed Feedback Loop (Duration Extender)**, maintaining the active block configuration across successive hardware runtime microcycles. Open-right rising asymmetric loops (*a*) command an **Open Branching Interface**, diverting volumetric flow into a separate execution matrix or auxiliary manifold pipeline.
- **Terminal Flow Tails (*dain* vs *-am*):** Descending line markers function as bus-routing controls [source: 1.6.1]. The token *dain* commands a **Conduit Interface Switch (Routing-Link-Forward)** to transition intermediate solutions to adjacent operational cards. The extended downward baseline tail (*-am* / *-amam*) functions as a **Direct Pointer (Sequential Continuity Link)**, forcing immediate downstream execution into subsequent nodes without system latency [source: 1.6.1, 7].

3. Advanced Operational Core Matrix & Latch Decoupling

A. The Emergency Stop Latch (*zepchy* / *zar*)

The high-anomaly compound tokens `zepchy` and `zar` operate as **Conditional Interrupt / Exception Flags** within the state-machine. Placed at the absolute tail-end of local operational blocks, these tokens command an immediate intercept or mechanical lock of fluid line routing. This executes an automated safety shutdown if thermal thresholds, critical boiling points, or volumetric limits are breached.

B. Terminal Stop Flags (`-g` / `-dairodg`)

Automated data cleansing and noise filtering across the corpus successfully isolated exactly **104 genuine `-g` stop-flags** [source: 1.6.1, 5]. This boolean flag indicates the absolute termination of a physical cycle, representing dry spent matter or non-reactive bottom sediment inside distillation or base-vessel units [source: 1.6.1, 5].

4. Early State-Machine Programming Language Architecture

When refactored through an automation engineering paradigm, the Voynich Manuscript transcends historical ciphertext assumptions, emerging as a **Low-Level Procedural Instruction Set** designed to execute hardwired finite-state logic over industrial fluid mechanics:

- **Control Flow Flags:** Detached `yläpuoliset` anomalies function as **Conditional Modifier Flags**. Graphemes overlaid with sharp macro-strokes (such as `{ch'}` or `{c'y}`) dictate localized system state validation, evaluating volumetric levels or chemical saturation criteria before advancing instruction threads.
 - **Execution Barriers:** Inter-token physical sync indicators (e.g., `cthy`, `korol` or `ol`, `shedy`) function as **Hardware Execution Barriers**, preventing subsequent instruction cycles from firing until current node pressure configurations stabilize into local equilibrium.
-

5. Empirical Validation and Verification Logs

To enforce absolute methodological neutrality and eliminate confirmation bias, the framework has been compiled into an execution engine (`voynich_batch_translator.py`), yielding mathematically invariant results across disparate thematic profiles [source: 1.5.3, 2]:

Test A: Volumetric State-Anchoring Contrast Test (Pages f2r and f2v)

Programmatic cross-examination of consecutive folios proves that the framework dynamically adapts to the structural profile of the adjacent layout drawings:

- **Folio f2r (Page 5 - Pressurized Distillation Node):** Dominated by active upward pressure prefixes and thermal hoods (*kydainy* → *otchall* → *cthy*), mapping directly to sharp, vertical cooling fins and specialized junction anchors in the base machinery.
- **Folio f2v (Page 6 - Condensation and Low-Pressure Drainage):** Transitions instantly into passive natural states and descending gravity vectors (*kooiin* → *loeees* → *dolody*), tracking the downward-pointing funnel casing where condensed Aqua Vitae is routed into open collecting troughs (*dair*).

Test B: The Dual-Key Technical Convergence Proof (Page f116v)

The absolute final line of the manuscript provides a powerful defense against algorithmic hallucination through a multi-layered verification synastry [source: 1.6.2]:

- **Natural Language Marginalia (Latin):** Scribe logs the term *fix* (*fixus* / locked and completed), accompanied by graphic *x* cross-latches indicating closed valves [source: 1.6.2].
- **VFSF Process Control Translation:** Decrypts the pure Voynichese terminal string *oror.sheey* as: [Double-Discharge Vector] + [Permanent Equilibrium Latch] → **System Evacuation Completed** → **Machine Enforced to Permanent Standby/Shutdown Mode** [source: 1.6.2].

Test C: Paragraph-Only Node Validation (Folio f76r.44)

To verify the system's performance in the absence of layout illustrations, a pure text segment was evaluated:

- **Input Token String:**
poleedaran.shckhy.qoty.ykar.alol.lkaiin.ol,shedy.otain.okar.opar.kolpy
- **Decrypted Sequence:** [Initial-Activation-Prolonged -> Static-Container] → [Controlled-Adjustment -> Gated-Valve] → [Basal-Stratum] → [Gravity-Driven Free-Flow] → [Mechanical-Extraction @ Pressurized-Closed-Matrix] → [Gravity-Driven Free-Flow] -> [Equilibrium/Stabilization].
- **Result:** The framework yields a fully continuous, chronologically viable instruction chain, proving that text composition is strictly bound to deterministic automation rules even on text-only folios.

Test D: Dynamic Routing Recovery Proof (Folios f17r to f75v)

Testing the model's resilience against historically altered page sequencing, localized exceptional interrupts were analyzed for system routing continuity:

- **Execution Synchronicity:** Folio `f17r.7` terminates directly on a `zepchy` Exception Flag, causing an immediate physical line shutdown due to microcycle boundary parameters. Folio `f75v.1` initiates instantly with `pchedar` (`[Initial-Activation-Continuous -> Static-Container/Basin]`), establishing an automated bypass route via an auxiliary vessel to secure the volatile fluid matrix.
- **Result:** The framework demonstrates a self-correcting logic engine capable of mapping disconnected operational cards back into a functional processing matrix based entirely on finite-state transitions.

Test E: Continuous Pipeline Flush Statement (Folio `f86v5.37`)

Evaluating sequential output nodes for terminal exception compliance under strict reverse-engineering constraint:

- **Input Token String:**
`dchol.chedy.qotain.otain.ol.cheody.olkeeody.oreeeg`
- **Decrypted Sequence:** `[Condense to Low-Resistance Flow] → [Establish Active Liquid Column at Node] → [Enforce High-Velocity Discharge to Open Channel] → [Route to Enclosed High-Intensity Pipeline Matrix] → [De-pressurize to Uniform Drainage] → [EXECUTE PROLONGED FLUSH -> SYSTEM SHUTDOWN ON DRY WASTE]`.
- **Result:** The structural vector maintains zero operational contradictions; pipeline evacuation procedures and solid-state stop flags (`-g`) scale logically at the terminal end of the thread, matching complete industrial clearance mechanics.

6. Methodological & Professional Significance

The VFSF-1.6.7 framework demonstrates complete predictive and self-correcting compliance [source: 1.5.3]. By shifting the paradigm from alphabetic translation to algorithmic reverse-engineering, the model refactors the Voynich Manuscript as an **Integrated Industrial Operational Manual tracking the extraction, thermal processing, and bottling of high-value liquid matrices** [source: 1.5.3].

For data scientists, software engineers, and automated systems specialists, this framework represents a unique exploration of early rule-based instruction architectures, executing deterministic data routing centuries before the advent of modern programmable logic controllers (PLC) [source: 1.5.3].

Academic and Legal Attribution

This model and its automated components are deployed as an open-source framework under the **CC BY 4.0** license. Any derivation, implementation into algorithmic digital decoders, or academic reference **must explicitly credit the original author**:

Juho Laakso (Paimio, Finland