

```
In[ ]:= (* Mathematica code for Modell of Eshra et al. eLife 2021 *)  
      (* Stefan Hallermann and Hartmut Schmidt Aug 2021 *)
```

Import

general

```
In[ ]:= (* imported data all Ca in uM, all times in ms,  
      all amplitudes and Nv in vesicles *)  
  
      CmToVesConversionFactor = (1/90.12) * (1/70*^-18);  
      (* explained in methods *)  
  
In[ ]:= rrp = 10; (* pool of release-ready vesicles per connection *)  
  
In[ ]:= dir = NotebookDirectory[];  
      SetDirectory[dir];  
      dataFolder = "../data to fit/";
```

tau1 Cm 5kHz

```
In[ ]:= data = Import[dataFolder <> "all_t1_v02_C5.txt", "Table"];
```

```

In[ ]:= dataT1C5Ca = 0.001 * data[[All, 1]];
dataT1C5RelRate = 1000. * data[[All, 2]];
dataT1C5Delay = data[[All, 3]];
dataT1C5ChiRatio = data[[All, 4]];
dataT1C5Amplitude = CmToVesConversionFactor data[[All, 5]];

dataT1C5Nv = Table[0, {7}];
tmp1 = 1;
tmp2 = 6;
dataT1C5Nv[[tmp1]] = CmToVesConversionFactor data[[All, tmp2]];
tmp1 += 1;
tmp2 += 1;
dataT1C5Nv[[tmp1]] = CmToVesConversionFactor data[[All, tmp2]];
tmp1 += 1;
tmp2 += 1;
dataT1C5Nv[[tmp1]] = CmToVesConversionFactor data[[All, tmp2]];
tmp1 += 1;
tmp2 += 1;
dataT1C5Nv[[tmp1]] = CmToVesConversionFactor data[[All, tmp2]];
tmp1 += 1;
tmp2 += 1;
dataT1C5Nv[[tmp1]] = CmToVesConversionFactor data[[All, tmp2]];
tmp1 += 1;
tmp2 += 1;
dataT1C5Nv[[tmp1]] = CmToVesConversionFactor data[[All, tmp2]];
tmp1 += 1;
tmp2 += 1;
dataT1C5Nv[[tmp1]] = CmToVesConversionFactor data[[All, tmp2]];

```

tau1 Cm 10kHz

```

In[ ]:= data = Import[dataFolder <> "all_t1_v02_C10.txt", "Table"];

```

```

In[ ]:= dataT1C10Ca = 0.001 * data[[All, 1]];
dataT1C10RelRate = 1000. * data[[All, 2]];
dataT1C10Delay = data[[All, 3]];
dataT1C10ChiRatio = data[[All, 4]];
dataT1C10Amplitude = CmToVesConversionFactor data[[All, 5]];

dataT1C10Nv = Table[0, {7}];
tmp1 = 1;
tmp2 = 6;
dataT1C10Nv[[tmp1]] = CmToVesConversionFactor data[[All, tmp2]];
tmp1 += 1;
tmp2 += 1;
dataT1C10Nv[[tmp1]] = CmToVesConversionFactor data[[All, tmp2]];
tmp1 += 1;
tmp2 += 1;
dataT1C10Nv[[tmp1]] = CmToVesConversionFactor data[[All, tmp2]];
tmp1 += 1;
tmp2 += 1;
dataT1C10Nv[[tmp1]] = CmToVesConversionFactor data[[All, tmp2]];
tmp1 += 1;
tmp2 += 1;
dataT1C10Nv[[tmp1]] = CmToVesConversionFactor data[[All, tmp2]];
tmp1 += 1;
tmp2 += 1;
dataT1C10Nv[[tmp1]] = CmToVesConversionFactor data[[All, tmp2]];
tmp1 += 1;
tmp2 += 1;
dataT1C10Nv[[tmp1]] = CmToVesConversionFactor data[[All, tmp2]];

```

tau1 Deconv

```

In[ ]:= data = Import[dataFolder <> "all_t1_v02_D.txt", "Table"];

```

```

In[ ]:= dataT1DCa = 0.001 * data[[All, 1]];
dataT1DRelRate = 1000. * data[[All, 2]];
dataT1DDelay = data[[All, 3]];
dataT1DChiRatio = data[[All, 4]];
dataT1DAmplitude = data[[All, 5]];

dataT1Dnv = Table[0, {7}];
tmp1 = 1; tmp2 = 6; dataT1Dnv[[tmp1]] = data[[All, tmp2]];
tmp1 += 1; tmp2 += 1; dataT1Dnv[[tmp1]] = data[[All, tmp2]];
tmp1 += 1; tmp2 += 1; dataT1Dnv[[tmp1]] = data[[All, tmp2]];
tmp1 += 1; tmp2 += 1; dataT1Dnv[[tmp1]] = data[[All, tmp2]];
tmp1 += 1; tmp2 += 1; dataT1Dnv[[tmp1]] = data[[All, tmp2]];
tmp1 += 1; tmp2 += 1; dataT1Dnv[[tmp1]] = data[[All, tmp2]];
tmp1 += 1; tmp2 += 1; dataT1Dnv[[tmp1]] = data[[All, tmp2]];

```

tau2 Cm 5kHz

```

In[ ]:= data = Import[dataFolder <> "all_t2_v02_C5.txt", "Table"];

In[ ]:= dataT2C5Ca = 0.001 * data[[All, 1]];
dataT2C5RelRate = 1000. * data[[All, 2]];
dataT2C5Amplitude2 = CmToVesConversionFactor data[[All, 3]];
dataT2C5Amplitude1 = CmToVesConversionFactor data[[All, 4]];

```

tau2 Cm 10kHz

```

In[ ]:= data = Import[dataFolder <> "all_t2_v02_C10.txt", "Table"];

In[ ]:= dataT2C10Ca = 0.001 * data[[All, 1]];
dataT2C10RelRate = 1000. * data[[All, 2]];
dataT2C10Amplitude2 = CmToVesConversionFactor data[[All, 3]];
dataT2C10Amplitude1 = CmToVesConversionFactor data[[All, 4]];

```

tau2 Deconv

```


In[ ]:= data = Import[dataFolder <> "all_t2_v02_D.txt", "Table"];

In[ ]:= dataT2DCa = 0.001 * data[[All, 1]];
dataT2DRelRate = 1000. * data[[All, 2]];
dataT2DAmplitude2 = data[[All, 3]];
dataT2DAmplitude1 = data[[All, 4]];

```

local Ca

```
In[ ]:= data = Import[dataFolder <> "local Ca at 20 nm in uM and ms.txt", "Table"];  
dataLocalCa = 1*^-6 data[[All, 1]];  
dataLocalCaTime = 1*^-3 data[[All, 2]];  
ListPlot[Transpose[{dataLocalCaTime, dataLocalCa}], PlotRange -> All]
```



General parameters and definitions

general stuff

```

In[ ]:= (* for calculations: time in s, Ca in M *)
        numberOfFitParamToBeSaved = 16;
        (*
        1 max release

        Mono
        2 chi2Mono
        3 delayMono
        4 ampMono
        5 1/tau1Mono

        Bi
        6 chi2Mono/chi2Bi
        7 delay
        8 amp
        9 amp1 (=amp*relative amp1)
        10 1/tau1
        11 1/tau2

        merge
        12 delay
        13 amp
        14 amp1
        15 1/tau1
        16 1/tau2
        *)
        cursorStart = -0.002; (*s*)
        cursorEnd = 0.01; (*s*)
        cursorEndLong = 0.061; (*s*)
        timeOfNv = {0.0001, 0.0002, 0.001, 0.005, 0.01, 0.1, 0.4};
        SeedRandom[1];
        myMaxIterations = 100;

In[ ]:= timeStart = AbsoluteTime[]
Out[ ]:= 3.839313680412683 × 109

```

noiseRepeats

```
In[ ]:= noiseRepeats = 3;
      (* should be increased to 50 for a full dataset *)
      myQuantile1 = 0.25;
      myQuantile2 = 0.75;
```

export parameters

```
In[ ]:= dtOfPlotsForExport = 20*^-5;
      exportYes = 1;
```

sampling and myNoise

```
In[ ]:= samplingOfDataInKHzC5 = 5;
      myNoiseC5 = CmToVesConversionFactor * 1.36937*^-14 / rrp(*cannot be 0*)
      signalToNoiseRatioC5 = 1.;(*minimum s-to-n-ratio to attempt fitting*)
      dtOfDataC5 = (1 / (1000 * samplingOfDataInKHzC5));

      samplingOfDataInKHzC10 = 10;
      myNoiseC10 = CmToVesConversionFactor * 1.67583*^-14 / rrp(*cannot be 0*)
      signalToNoiseRatioC10 = 1.;(*minimum s-to-n-ratio to attempt fitting*)
      dtOfDataC10 = (1 / (1000 * samplingOfDataInKHzC10));

      samplingOfDataInKHzD = 10;
      myNoiseD = 0.367584 / rrp(*cannot be 0*)
      signalToNoiseRatioD = 1.;(*minimum s-to-n-ratio to attempt fitting*)
      dtOfDataD = (1 / (1000 * samplingOfDataInKHzD));

      samplingOfDataInKHzLong = 1;
      myNoiseLong = myNoiseC5;(*cannot be 0*)
      dtOfDataLong = (1 / (1000 * samplingOfDataInKHzLong));
```

```
Out[ ]:= 0.217071
```

```
Out[ ]:= 0.265651
```

```
Out[ ]:= 0.0367584
```

number of simulations per DMN

```
In[*]:= aNumberDMN05 = 2;
        aNumberDMN2 = 2;
        aNumberDMN10 = 2;

        (* for full dataset: *)
        (*
        aNumberDMN05=2*20;
        aNumberDMN2=2*17;
        aNumberDMN10=2*10;
        *)
```

Exp fit function

```
In[*]:= myFitMono[t_] :=
        If[t <= delayMono, 0, ampMono (1 - Exp[-(t - delayMono) / tau1Mono])];

myFitBi[t_] := If[t <= delay, 0,
        amp (1 - amp1 Exp[-(t - delay) / tau1] - (1 - amp1) Exp[-(t - delay) / tau2])];

(*guess for 10 uM; will be changed according to a power of 1 law*)(*in s*)
ampGuess = 2.;(*each pool has size 1.0*)
tau1Guess = 0.001;(*in s*)
delayGuess = 0.0005;(*in s*)
amp1Guess = 0.5;
```

Calculate Ca transients

First, the resting conditions are numerically calculated. Subsequently, the resulting values are used as initial conditions for the main simulations of the flash-evoked Ca^{2+} transitions. All calculations are repeated in a loop with increasing uncaging efficacy for three different DMN concentrations. The resulting free Ca^{2+} concentration is later used to drive the release schemes.

General definitions for all DMN conc.

```
In[*]:= CaListReal = CaListDye = {};
```

0.5 mM DMN

general parameters

```
In[ ]:= TimeWindow = 0.006; (*End of simulation*)
        tflash = 0.0; (*Time of flash*)
        PlStart = 0.; (*Plot start*)

        af = 0.67; (*fast uncaging fraction; Faas et al*)

        (*Select dye*)
        OGB1 = 0;
        OGB5N = 0;
        OGB6F = 0;
        Fluo5F = 1;

        CaRest = 227. * 10^-9; (*Free pre-flash resting Ca;
        equilibrates with all buffers and DM*)
        MgT = 0.5 * 10^-3; (*total Mg in pipette*)
        γ = 0.; (*Pump rate*)

        (*Concentrations of dye, buffers, DM*)
        OGtotal = 50. * 10^-6;
        ATPtotal = 5. * 10^-3;
        MBtotal = 480. * 10^-6; (*(*Delvendahl, PNAS, 2015*)*)

        DMT = 0.5 * 10^-3; (*total concentration of DMn *)
        (*uncaging efficiency*)
        aStartDMN05 = 0.08;
        aEndDMN05 = 0.5;
```

definitions and loop

```
In[ ]:= (*Dye*)
        If[OGB1 == 1,
            kOnOG = 4.3 * 10^8;
            kOffOG = 103.;]

        If[OGB5N == 1,
            kOnOG = 2.5 * 10^8;
            kOffOG = 6000.;]

        If[OGB6F == 1,
            kOnOG = 3. * 10^8;
            kOffOG = 900.;]

        If[Fluo5F == 1,
```

```

kOnOG = 3. * 108;
kOffOG = 249.;] (*Delvendahl PNAS; before: 432*)

KdOG = kOffOG / kOnOG;
kappaOG = OGtotal / KdOG;

(*ATP*)
kOnATP = 5. * 108;
kOffATP = 100 000.;
kOnMgATP = 1. * 107; (*Bollmann Dissertation S. 59; *)
kOffMgATP = 1000.;

KdATP = kOffATP / kOnATP;
kappaATP = ATPtotal / KdATP;
KdMgATP = kOffMgATP / kOnMgATP;

(*DM*)
If[MgT == 0.,
  kOnDM = 1.98 * 107; (*Faas Plos Biol, 2007*)
  kOffDM = 0.14;
,
  kOnDM = 2.9 * 107; (*Faas Biophys J, 2005*)
  kOffDM = 0.19;
]

(*Mg binding constants for DMn, DMf, DMs*)
kOnMg = 1.3 * 105; (*all values for Mg are from Faas et al., 2005*)
kOffMg = 0.2;

(*Ca binding constants for PP*)
kOnPP2 = kOnPP1 = kOnDM;
kOffPP2 = 3.6 * 103;
If[MgT == 0.,
  kOffPP1 = 7. * 104;;
  kOffPP1 = 6.9 * 104; ]

(*Mg binding constants for PP1,PP2*)
kOffMgPP = 3. * 102; (*for PP1,PP2*)
konMgPP = kOnMg; (*koMgPP not used in below diff. eq., only kOnMg*)

(*Equilibrium constants (not complete)*)
KdDM = kOffDM / kOnDM;
KdPP1 = kOffPP1 / kOnPP1;
KdMg = kOffMg / kOnMg;
kappaDM = DMT / KdDM;

```

```

(*Endogenous buffer*)
kOnMB = 5 * 108; (*DeIvendahl, PNAS, 2015*)
kOffMB = 16 000;
KdMB = kOffMB / kOnMB;

TRest = 1000.;

(*----- Loop -----
-----*)
(*----- Loop -----
-----*)
(*----- Loop -----
-----*)

For[aCount = 1, aCount ≤ aNumberDMN05, aCount += 1,
  a = 10^(Log10[aStartDMN05] +
    (aCount - 1) * (Log10[aEndDMN05] - Log10[aStartDMN05]) / (aNumberDMN05 - 1));

  (*----- Resting
  Equations -----*)

  (*Dye*)
  OGRest := {

    OG[0] == OGtotal,
    CaOG[0] == 0,

    OG'[tt] == -kOnOG * CaRest * OG[tt] + kOffOG * CaOG[tt],
    CaOG'[tt] == kOnOG * CaRest * OG[tt] - kOffOG * CaOG[tt]
  }
;

  (*ATP*)
  ATPRest := {

    ATP[0] == ATPtotal,
    CaATP[0] == 0,
    MgATP[0] == 0,

    ATP'[tt] == -kOnATP * CaRest * ATP[tt] + kOffATP * CaATP[tt] -
      kOnMgATP * Mg[tt] * ATP[tt] + kOffMgATP * MgATP[tt],
    CaATP'[tt] == kOnATP * CaRest * ATP[tt] - kOffATP * CaATP[tt],
    MgATP'[tt] == kOnMgATP * Mg[tt] * ATP[tt] - kOffMgATP * MgATP[tt]
  }

```

```

;

(*DM nitrophenene*)
DMnRest := {

  DMn[0] == (1 - a) * DMT,
  CaDMn[0] == 0.,
  MgDMn[0] == 0.,

  DMn'[tt] == -kOnDM * CaRest * DMn[tt] +
    kOffDM * CaDMn[tt] - kOnMg * Mg[tt] * DMn[tt] + kOffMg * MgDMn[tt],
  CaDMn'[tt] == kOnDM * CaRest * DMn[tt] - kOffDM * CaDMn[tt],
  MgDMn'[tt] == kOnMg * Mg[tt] * DMn[tt] - kOffMg * MgDMn[tt]
}

;
DMfRest := {

  DMf[0] == a * af * DMT,
  CaDMf[0] == 0.,
  MgDMf[0] == 0.,

  DMf'[tt] == -kOnDM * CaRest * DMf[tt] +
    kOffDM * CaDMf[tt] - kOnMg * Mg[tt] * DMf[tt] + kOffMg * MgDMf[tt],
  CaDMf'[tt] == kOnDM * CaRest * DMf[tt] - kOffDM * CaDMf[tt],
  MgDMf'[tt] == kOnMg * Mg[tt] * DMf[tt] - kOffMg * MgDMf[tt]
}

;
DMsRest := {

  DMs[0] == a * (1 - af) * DMT,
  CaDMs[0] == 0.,
  MgDMs[0] == 0.,

  DMs'[tt] == -kOnDM * CaRest * DMs[tt] +
    kOffDM * CaDMs[tt] - kOnMg * Mg[tt] * DMs[tt] + kOffMg * MgDMs[tt],
  CaDMs'[tt] == kOnDM * CaRest * DMs[tt] - kOffDM * CaDMs[tt],
  MgDMs'[tt] == kOnMg * Mg[tt] * DMs[tt] - kOffMg * MgDMs[tt]
}

;

(*Endogeneous buffer*)
MBRest := {

  MB[0] == MBtotal,

```

```

CaMB[0] == 0,

MB'[tt] == -kOnMB * CaRest * MB[tt] + kOffMB * CaMB[tt],
CaMB'[tt] == kOnMB * CaRest * MB[tt] - kOffMB * CaMB[tt]
}

;

(*Free Mg*)
MgfRest := {
  Mg[0] == MgT,

  Mg'[tt] ==
    -kOnMgATP * Mg[tt] * ATP[tt] + kOffMgATP * MgATP[tt]
    - kOnMg * Mg[tt] * DMn[tt] + kOffMg * MgDMn[tt]
    - kOnMg * Mg[tt] * DMf[tt] + kOffMg * MgDMf[tt]
    - kOnMg * Mg[tt] * DMs[tt] + kOffMg * MgDMs[tt]
}

;

EqRest := {ATPRest, MgfRest, OGRest, DMnRest, DMfRest, DMsRest, MBRest};
VarsRest := {ATP, Mg, CaATP, MgATP, CaOG, OG, DMn,
  CaDMn, MgDMn, DMf, CaDMf, MgDMf, DMs, CaDMs, MgDMs, MB, CaMB}
;
solr := NDSolve[EqRest, VarsRest, {tt, 0, TRest}]
;

Ca0 = CaRest;
Mg0 = Extract[Mg[TRest] /. solr, 1];
ATP0 = Extract[ATP[TRest] /. solr, 1];
CaATP0 = Extract[CaATP[TRest] /. solr, 1];
MgATP0 = Extract[MgATP[TRest] /. solr, 1];
OG0 = Extract[OG[TRest] /. solr, 1];
CaOG0 = Extract[CaOG[TRest] /. solr, 1];
DMn0 = Extract[DMn[TRest] /. solr, 1];
CaDMn0 = Extract[CaDMn[TRest] /. solr, 1];
MgDMn0 = Extract[MgDMn[TRest] /. solr, 1];
DMf0 = Extract[DMf[TRest] /. solr, 1];
CaDMf0 = Extract[CaDMf[TRest] /. solr, 1];
MgDMf0 = Extract[MgDMf[TRest] /. solr, 1];
DMs0 = Extract[DMs[TRest] /. solr, 1];
CaDMs0 = Extract[CaDMs[TRest] /. solr, 1];
MgDMs0 = Extract[MgDMs[TRest] /. solr, 1];
MB0 = Extract[MB[TRest] /. solr, 1];
CaMB0 = Extract[CaMB[TRest] /. solr, 1];

```

```

ClearAll[EqRest, VarsRest];

(*----- Flash
Equations -----*)

(*Dye*)
BufferOG := {

  OG[0] == OG0,
  CaOG[0] == CaOG0,

  OG'[tt] == -kOnOG * Ca[tt] * OG[tt] + kOffOG * CaOG[tt],
  CaOG'[tt] == kOnOG * Ca[tt] * OG[tt] - kOffOG * CaOG[tt]}
;

(*ATP*)
BufferATP := {

  ATP[0] == ATP0,
  CaATP[0] == CaATP0,
  MgATP[0] == MgATP0,

  ATP'[tt] == -kOnATP * Ca[tt] * ATP[tt] + kOffATP * CaATP[tt] -
    kOnMgATP * Mg[tt] * ATP[tt] + kOffMgATP * MgATP[tt],
  CaATP'[tt] == kOnATP * Ca[tt] * ATP[tt] - kOffATP * CaATP[tt],
  MgATP'[tt] == kOnMgATP * Mg[tt] * ATP[tt] - kOffMgATP * MgATP[tt]
}
;

(*fast (tauf) and slow (taus) time constants for uncageing;
Faas et al., 2005,2007*)
If[MgT == 0.,
  tauf = 15.2 * 10^-6; (*Faas, 2007*)
  taus = 1.9 * 10^-3;
,
  tauf = 15. * 10^-6; (*Faas,2005*)
  taus = 2. * 10^-3; ]

;

(*The differential equations*)
(*non uncaging fraction of DMn*)
BufferDMn := {

  DMn[0] == DMn0,
  CaDMn[0] == CaDMn0,

```

```

MgDMn[0] == MgDMn0,

DMn'[tt] == -kOnDM * Ca[tt] * DMn[tt] +
  kOffDM * CaDMn[tt] - kOnMg * Mg[tt] * DMn[tt] + kOffMg * MgDMn[tt],
CaDMn'[tt] == kOnDM * Ca[tt] * DMn[tt] - kOffDM * CaDMn[tt],
MgDMn'[tt] == kOnMg * Mg[tt] * DMn[tt] - kOffMg * MgDMn[tt]
}
;

(*fast uncaging fraction of DMn*)
BufferDMf := {

  DMf[0] == DMf0,
  CaDMf[0] == CaDMf0,
  MgDMf[0] == MgDMf0,

  DMf'[tt] == -kOnDM * Ca[tt] * DMf[tt] + kOffDM * CaDMf[tt] - kOnMg * Mg[tt] *
    DMf[tt] + kOffMg * MgDMf[tt] - 1/tauf * DMf[tt] * UnitStep[tt - tflash],
  CaDMf'[tt] == kOnDM * Ca[tt] * DMf[tt] - kOffDM * CaDMf[tt] -
    1/tauf * CaDMf[tt] * UnitStep[tt - tflash],
  MgDMf'[tt] == kOnMg * Mg[tt] * DMf[tt] - kOffMg * MgDMf[tt] -
    1/tauf * MgDMf[tt] * UnitStep[tt - tflash]
}

;

(*slow uncaging fraction of DMn*)
BufferDMS := {

  DMS[0] == DMS0,
  CaDMS[0] == CaDMS0,
  MgDMS[0] == MgDMS0,

  DMS'[tt] == -kOnDM * Ca[tt] * DMS[tt] + kOffDM * CaDMS[tt] - kOnMg * Mg[tt] *
    DMS[tt] + kOffMg * MgDMS[tt] - 1/taus * DMS[tt] * UnitStep[tt - tflash],
  CaDMS'[tt] == kOnDM * Ca[tt] * DMS[tt] - kOffDM * CaDMS[tt] -
    1/taus * CaDMS[tt] * UnitStep[tt - tflash],
  MgDMS'[tt] == kOnMg * Mg[tt] * DMS[tt] - kOffMg * MgDMS[tt] -
    1/taus * MgDMS[tt] * UnitStep[tt - tflash]
}

;

(*Photoproducts*)
(*PP2: comes from DMf,DMS and MgDMf,MgDMS; but also binds Ca*)
BufferPP2 := {

  PP2[0] == 0,
  CaPP2[0] == 0,

```

```

MgPP2[0] == 0,

PP2'[tt] == -kOnPP2 * Ca[tt] * PP2[tt] + kOffPP2 * CaPP2[tt] -
  kOnMg * Mg[tt] * PP2[tt] + kOffMgPP * MgPP2[tt] + 2 * (1 / tauf * DMf[tt] *
    UnitStep[tt - tflash] + 1 / taus * DMs[tt] * UnitStep[tt - tflash])
  + 1 / tauf * MgDMf[tt] * UnitStep[tt - tflash] +
  1 / taus * MgDMs[tt] * UnitStep[tt - tflash],

CaPP2'[tt] == kOnPP2 * Ca[tt] * PP2[tt] - kOffPP2 * CaPP2[tt],

MgPP2'[tt] == kOnMg * Mg[tt] * PP2[tt] - kOffMgPP * MgPP2[tt] + 1 / tauf *
  MgDMf[tt] * UnitStep[tt - tflash] + 1 / taus * MgDMs[tt] * UnitStep[tt - tflash]
}
;

(*PP1: Comes from CaDMf,CaDMs and binds Ca and Mg*)
BufferPP1 := {

  PP1[0] == 0,
  CaPP1[0] == 0,
  MgPP1[0] == 0,

  PP1'[tt] == -kOnPP1 * Ca[tt] * PP1[tt] +
    kOffPP1 * CaPP1[tt] - kOnMg * Mg[tt] * PP1[tt] + kOffMgPP * MgPP1[tt]
    + 1 / tauf * CaDMf[tt] * UnitStep[tt - tflash] +
    1 / taus * CaDMs[tt] * UnitStep[tt - tflash],

  CaPP1'[tt] == kOnPP1 * Ca[tt] * PP1[tt] -
    kOffPP1 * CaPP1[tt] + 1 / tauf * CaDMf[tt] * UnitStep[tt - tflash] +
    1 / taus * CaDMs[tt] * UnitStep[tt - tflash],

  MgPP1'[tt] == kOnMg * Mg[tt] * PP1[tt] - kOffMgPP * MgPP1[tt]

}
;

(*Endogeneous Buffer*)
BufferMB := {

  MB[0] == MB0,
  CaMB[0] == CaMB0,

  MB'[tt] == -kOnMB * Ca[tt] * MB[tt] + kOffMB * CaMB[tt],
  CaMB'[tt] == kOnMB * Ca[tt] * MB[tt] - kOffMB * CaMB[tt]}

;

```



```

(*Clear[Eqns,Vars,sol]*)

(*Free Ca*)
FreeCa := {
  Ca[0] == Ca0,

  Ca'[tt] == -γ * (Ca[tt] - CaRest)
  (*DMn*)
  - kOnPP1 * Ca[tt] * PP1[tt] + kOffPP1 * CaPP1[tt]
  - kOnPP2 * Ca[tt] * PP2[tt] + kOffPP2 * CaPP2[tt]
  - kOnDM * Ca[tt] * DMn[tt] + kOffDM * CaDMn[tt]
  - kOnDM * Ca[tt] * DMf[tt] + kOffDM * CaDMf[tt]
  - kOnDM * Ca[tt] * DMS[tt] + kOffDM * CaDMS[tt]
  (*buffers*)
  - kOnATP * Ca[tt] * ATP[tt] + kOffATP * CaATP[tt]
  - kOnMB * Ca[tt] * MB[tt] + kOffMB * CaMB[tt]
  (*dye*)
  - kOnOG * Ca[tt] * OG[tt] + kOffOG * CaOG[tt]
}
;

(*Free Mg*)
FreeMg := {
  Mg[0] == Mg0,

  Mg'[tt] ==
  - kOnMgATP * Mg[tt] * ATP[tt] + kOffMgATP * MgATP[tt]
  - kOnMg * Mg[tt] * DMn[tt] + kOffMg * MgDMn[tt]
  - kOnMg * Mg[tt] * DMf[tt] + kOffMg * MgDMf[tt]
  - kOnMg * Mg[tt] * DMS[tt] + kOffMg * MgDMS[tt]
  - kOnMg * Mg[tt] * PP2[tt] + kOffMgPP * MgPP2[tt]
  - kOnMg * Mg[tt] * PP1[tt] + kOffMgPP * MgPP1[tt]
}
;

Eqns := {BufferDMn, BufferDMf, BufferDMS, BufferATP,
  BufferPP1, BufferPP2, FreeCa, FreeMg, BufferMB, BufferOG}
;
Vars := {ATP, CaATP, MgATP, Ca, Mg, CaDMn, DMn, CaDMf, DMf, CaDMS,
  DMS, CaPP1, PP1, CaPP2, PP2, MgPP2, MgPP1, MB, CaMB, OG, CaOG}
;
sol := NDSolve[Eqns, Vars, {tt, 0., TimeWindow}
  (*,Method->{"EquationSimplification"->"Solve"}*)]
;
CafP = Extract[Ca[TimeWindow] /. sol, 1];
CafOG = KdOG * CaOG[tt] / OG[tt];

```

```

AppendTo[CaListReal, Evaluate[{Ca[tt]} /. sol]];
AppendTo[CaListDye, Evaluate[{Caf0G} /. sol]];

];

```

2 mM DMN

general parameters

```

In[ ]:= TimeWindow = 0.006; (*End of simulation*)
tflash = 0.0; (*Time of flash*)
PlStart = 0.; (*Plot start*)

af = 0.67; (*fast uncaging fraction; Faas et al*)

(*Select dye*)
OGB1 = 0;
OGB5N = 1;
OGB6F = 0;
Fluo5F = 0;

CaRest = 227. * 10^-9; (*Free pre-flash resting Ca;
equilibrates with all buffers and DM*)
MgT = 0.5 * 10^-3; (*total Mg in pipette*)
γ = 0.; (*Pump rate*)

(*Concentrations of dye, buffers, DM*)
OGtotal = 200. * 10^-6;
ATPtotal = 5. * 10^-3;
MBtotal = 480. * 10^-6; (*(*Delvendahl, PNAS, 2015*)*)

DMT = 2. * 10^-3; (*total concentration of DMn *)
(*uncaging efficiency*)
aStartDMN2 = 0.15;
aEndDMN2 = 0.55;

```

definitions and loop

```

In[ ]:= (*Dye*)
If[OGB1 == 1,
  kOnOG = 4.3 * 10^8;
  kOffOG = 103.;]

```

```

If[OGB5N == 1,
  kOnOG = 2.5 * 108;
  kOffOG = 6000.;]

If[OGB6F == 1,
  kOnOG = 3. * 108;
  kOffOG = 900.;]

If[Fluo5F == 1,
  kOnOG = 3. * 108;
  kOffOG = 249.;] (*Delvendahl PNAS; before: 432*)

KdOG = kOffOG / kOnOG;
kappaOG = OGtotal / KdOG;

(*ATP*)
kOnATP = 5. * 108;
kOffATP = 100 000.;
kOnMgATP = 1. * 107; (*Bollmann Dissertation S. 59; *)
kOffMgATP = 1000.;

KdATP = kOffATP / kOnATP;
kappaATP = ATPtotal / KdATP;
KdMgATP = kOffMgATP / kOnMgATP;

(*DM*)
If[MgT == 0.,
  kOnDM = 1.98 * 107; (*Faas Plos Biol, 2007*)
  kOffDM = 0.14;
  ,
  kOnDM = 2.9 * 107; (*Faas Biophys J, 2005*)
  kOffDM = 0.19;
]

(*Mg binding constants for DMn, DMf, DMs*)
kOnMg = 1.3 * 105; (*all values for Mg are from Faas et al., 2005*)
kOffMg = 0.2;

(*Ca binding constants for PP*)
kOnPP2 = kOnPP1 = kOnDM;
kOffPP2 = 3.6 * 103;
If[MgT == 0.,
  kOffPP1 = 7. * 104;;
  kOffPP1 = 6.9 * 104; ]

(*Mg binding constants for PP1,PP2*)

```

```

kOffMgPP = 3. * 10^2; (*for PP1,PP2*)
konMgPP = kOnMg; (*koMgPP not used in below diff. eq., only kOnMg*)

(*Equilibrium constants (not complete)*)
KdDM = kOffDM / kOnDM;
KdPP1 = kOffPP1 / kOnPP1;
KdMg = kOffMg / kOnMg;
kappaDM = DMT / KdDM;

(*Endogenous buffer*)
kOnMB = 5 * 10^8; (*Delvendahl, PNAS, 2015*)
kOffMB = 16000;
KdMB = kOffMB / kOnMB;

TRest = 1000.;

(*----- Loop -----
-----*)
(*----- Loop -----
-----*)
(*----- Loop -----
-----*)

For[aCount = 1, aCount ≤ aNumberDMN2, aCount += 1,
  a = 10^ (Log10[aStartDMN2] +
    (aCount - 1) * (Log10[aEndDMN2] - Log10[aStartDMN2]) / (aNumberDMN2 - 1));

  (*----- Resting
  Equations -----*)

  (*Dye*)
  OGRest := {

    OG[0] == OGtotal,
    CaOG[0] == 0,

    OG'[tt] == -kOnOG * CaRest * OG[tt] + kOffOG * CaOG[tt],
    CaOG'[tt] == kOnOG * CaRest * OG[tt] - kOffOG * CaOG[tt]
  }
;

  (*ATP*)
  ATPRest := {

    ATP[0] == ATPtotal,
    CaATP[0] == 0,

```

```

MgATP[0] == 0,

ATP'[tt] == -kOnATP * CaRest * ATP[tt] + kOffATP * CaATP[tt] -
  kOnMgATP * Mg[tt] * ATP[tt] + kOffMgATP * MgATP[tt],
CaATP'[tt] == kOnATP * CaRest * ATP[tt] - kOffATP * CaATP[tt],
MgATP'[tt] == kOnMgATP * Mg[tt] * ATP[tt] - kOffMgATP * MgATP[tt]

}

;

(*DM nitrophenene*)
DMnRest := {

  DMn[0] == (1 - a) * DMT,
  CaDMn[0] == 0.,
  MgDMn[0] == 0.,

  DMn'[tt] == -kOnDM * CaRest * DMn[tt] +
    kOffDM * CaDMn[tt] - kOnMg * Mg[tt] * DMn[tt] + kOffMg * MgDMn[tt],
  CaDMn'[tt] == kOnDM * CaRest * DMn[tt] - kOffDM * CaDMn[tt],
  MgDMn'[tt] == kOnMg * Mg[tt] * DMn[tt] - kOffMg * MgDMn[tt]

}

;

DMfRest := {

  DMf[0] == a * af * DMT,
  CaDMf[0] == 0.,
  MgDMf[0] == 0.,

  DMf'[tt] == -kOnDM * CaRest * DMf[tt] +
    kOffDM * CaDMf[tt] - kOnMg * Mg[tt] * DMf[tt] + kOffMg * MgDMf[tt],
  CaDMf'[tt] == kOnDM * CaRest * DMf[tt] - kOffDM * CaDMf[tt],
  MgDMf'[tt] == kOnMg * Mg[tt] * DMf[tt] - kOffMg * MgDMf[tt]

}

;

DMsRest := {

  DMs[0] == a * (1 - af) * DMT,
  CaDMs[0] == 0.,
  MgDMs[0] == 0.,

  DMs'[tt] == -kOnDM * CaRest * DMs[tt] +
    kOffDM * CaDMs[tt] - kOnMg * Mg[tt] * DMs[tt] + kOffMg * MgDMs[tt],
  CaDMs'[tt] == kOnDM * CaRest * DMs[tt] - kOffDM * CaDMs[tt],

```

```

    MgDMs'[tt] == kOnMg * Mg[tt] * DMs[tt] - kOffMg * MgDMs[tt]
  }
;

(*Endogeneous buffer*)
MBRest := {

  MB[0] == MBtotal,
  CaMB[0] == 0,

  MB'[tt] == -kOnMB * CaRest * MB[tt] + kOffMB * CaMB[tt],
  CaMB'[tt] == kOnMB * CaRest * MB[tt] - kOffMB * CaMB[tt]
}

;

(*Free Mg*)
MgfRest := {
  Mg[0] == MgT,

  Mg'[tt] ==
    -kOnMgATP * Mg[tt] * ATP[tt] + kOffMgATP * MgATP[tt]
    - kOnMg * Mg[tt] * DMn[tt] + kOffMg * MgDMn[tt]
    - kOnMg * Mg[tt] * DMf[tt] + kOffMg * MgDMf[tt]
    - kOnMg * Mg[tt] * DMs[tt] + kOffMg * MgDMs[tt]
}

;
EqRest := {ATPrest, MgfRest, OGRest, DMnRest, DMfRest, DMsRest, MBRest};
VarsRest := {ATP, Mg, CaATP, MgATP, CaOG, OG, DMn,
  CaDMn, MgDMn, DMf, CaDMf, MgDMf, DMs, CaDMs, MgDMs, MB, CaMB}
;
solr := NDSolve[EqRest, VarsRest, {tt, 0, TRest}]
;

Ca0 = CaRest;
Mg0 = Extract[Mg[TRest] /. solr, 1];
ATP0 = Extract[ATP[TRest] /. solr, 1];
CaATP0 = Extract[CaATP[TRest] /. solr, 1];
MgATP0 = Extract[MgATP[TRest] /. solr, 1];
OG0 = Extract[OG[TRest] /. solr, 1];
CaOG0 = Extract[CaOG[TRest] /. solr, 1];
DMn0 = Extract[DMn[TRest] /. solr, 1];
CaDMn0 = Extract[CaDMn[TRest] /. solr, 1];
MgDMn0 = Extract[MgDMn[TRest] /. solr, 1];
DMf0 = Extract[DMf[TRest] /. solr, 1];
CaDMf0 = Extract[CaDMf[TRest] /. solr, 1];

```

```

MgDMf0 = Extract[MgDMf[TRest] /. solr, 1];
DMs0 = Extract[DMs[TRest] /. solr, 1];
CaDMs0 = Extract[CaDMs[TRest] /. solr, 1];
MgDMs0 = Extract[MgDMs[TRest] /. solr, 1];
MB0 = Extract[MB[TRest] /. solr, 1];
CaMB0 = Extract[CaMB[TRest] /. solr, 1];

ClearAll[EqRest, VarsRest];

(*----- Flash
Equations -----*)

(*Dye*)
BufferOG := {

  OG[0] == OG0,
  CaOG[0] == CaOG0,

  OG'[tt] == -kOnOG * Ca[tt] * OG[tt] + kOffOG * CaOG[tt],
  CaOG'[tt] == kOnOG * Ca[tt] * OG[tt] - kOffOG * CaOG[tt]
};

(*ATP*)
BufferATP := {

  ATP[0] == ATP0,
  CaATP[0] == CaATP0,
  MgATP[0] == MgATP0,

  ATP'[tt] == -kOnATP * Ca[tt] * ATP[tt] + kOffATP * CaATP[tt] -
    kOnMgATP * Mg[tt] * ATP[tt] + kOffMgATP * MgATP[tt],
  CaATP'[tt] == kOnATP * Ca[tt] * ATP[tt] - kOffATP * CaATP[tt],
  MgATP'[tt] == kOnMgATP * Mg[tt] * ATP[tt] - kOffMgATP * MgATP[tt]
};

(*fast (tauf) and slow (taus) time constants for uncageing;
Faas et al., 2005,2007*)
If[MgT == 0.,
  tauf = 15.2 * 10^-6; (*Faas, 2007*)
  taus = 1.9 * 10^-3;
,
  tauf = 15. * 10^-6; (*Faas,2005*)
  taus = 2. * 10^-3; ]

```

```

;

(*The differential equations*)
(*non uncaging fraction of DMn*)
BufferDMn := {

  DMn[0] == DMn0,
  CaDMn[0] == CaDMn0,
  MgDMn[0] == MgDMn0,

  DMn'[tt] == -kOnDM * Ca[tt] * DMn[tt] +
    kOffDM * CaDMn[tt] - kOnMg * Mg[tt] * DMn[tt] + kOffMg * MgDMn[tt],
  CaDMn'[tt] == kOnDM * Ca[tt] * DMn[tt] - kOffDM * CaDMn[tt],
  MgDMn'[tt] == kOnMg * Mg[tt] * DMn[tt] - kOffMg * MgDMn[tt]
}

;

(*fast uncaging fraction of DMn*)
BufferDMf := {

  DMf[0] == DMf0,
  CaDMf[0] == CaDMf0,
  MgDMf[0] == MgDMf0,

  DMf'[tt] == -kOnDM * Ca[tt] * DMf[tt] + kOffDM * CaDMf[tt] - kOnMg * Mg[tt] *
    DMf[tt] + kOffMg * MgDMf[tt] - 1/tauf * DMf[tt] * UnitStep[tt - tflash],
  CaDMf'[tt] == kOnDM * Ca[tt] * DMf[tt] - kOffDM * CaDMf[tt] -
    1/tauf * CaDMf[tt] * UnitStep[tt - tflash],
  MgDMf'[tt] == kOnMg * Mg[tt] * DMf[tt] - kOffMg * MgDMf[tt] -
    1/tauf * MgDMf[tt] * UnitStep[tt - tflash]
}

;

(*slow uncaging fraction of DMn*)
BufferDMS := {

  DMS[0] == DMS0,
  CaDMS[0] == CaDMS0,
  MgDMS[0] == MgDMS0,

  DMS'[tt] == -kOnDM * Ca[tt] * DMS[tt] + kOffDM * CaDMS[tt] - kOnMg * Mg[tt] *
    DMS[tt] + kOffMg * MgDMS[tt] - 1/taus * DMS[tt] * UnitStep[tt - tflash],
  CaDMS'[tt] == kOnDM * Ca[tt] * DMS[tt] - kOffDM * CaDMS[tt] -
    1/taus * CaDMS[tt] * UnitStep[tt - tflash],
  MgDMS'[tt] == kOnMg * Mg[tt] * DMS[tt] - kOffMg * MgDMS[tt] -
    1/taus * MgDMS[tt] * UnitStep[tt - tflash]
}

```


;

(*Photoproducts*)

(*PP2: comes from DMf,DMS and MgDMf,MgDMS; but also binds Ca*)

BufferPP2 := {

PP2[0] == 0,

CaPP2[0] == 0,

MgPP2[0] == 0,

PP2'[tt] == -kOnPP2 * Ca[tt] * PP2[tt] + kOffPP2 * CaPP2[tt] -
 kOnMg * Mg[tt] * PP2[tt] + kOffMgPP * MgPP2[tt] + 2 * (1 / tauf * DMf[tt] *
 UnitStep[tt - tflash] + 1 / taus * DMS[tt] * UnitStep[tt - tflash])
 + 1 / tauf * MgDMf[tt] * UnitStep[tt - tflash] +
 1 / taus * MgDMS[tt] * UnitStep[tt - tflash],

CaPP2'[tt] == kOnPP2 * Ca[tt] * PP2[tt] - kOffPP2 * CaPP2[tt],

MgPP2'[tt] == kOnMg * Mg[tt] * PP2[tt] - kOffMgPP * MgPP2[tt] + 1 / tauf *
 MgDMf[tt] * UnitStep[tt - tflash] + 1 / taus * MgDMS[tt] * UnitStep[tt - tflash]

}

;

(*PP1: Comes from CaDMf,CaDMS and binds Ca and Mg*)

BufferPP1 := {

PP1[0] == 0,

CaPP1[0] == 0,

MgPP1[0] == 0,

PP1'[tt] == -kOnPP1 * Ca[tt] * PP1[tt] +
 kOffPP1 * CaPP1[tt] - kOnMg * Mg[tt] * PP1[tt] + kOffMgPP * MgPP1[tt]
 + 1 / tauf * CaDMf[tt] * UnitStep[tt - tflash] +
 1 / taus * CaDMS[tt] * UnitStep[tt - tflash],

CaPP1'[tt] == kOnPP1 * Ca[tt] * PP1[tt] -
 kOffPP1 * CaPP1[tt] + 1 / tauf * CaDMf[tt] * UnitStep[tt - tflash] +
 1 / taus * CaDMS[tt] * UnitStep[tt - tflash],

MgPP1'[tt] == kOnMg * Mg[tt] * PP1[tt] - kOffMgPP * MgPP1[tt]

}

;

(*Endogeneous Buffer*)

BufferMB := {

```

MB[0] == MB0,
CaMB[0] == CaMB0,

MB'[tt] == -kOnMB * Ca[tt] * MB[tt] + kOffMB * CaMB[tt],
CaMB'[tt] == kOnMB * Ca[tt] * MB[tt] - kOffMB * CaMB[tt]

```

```
;
```

```
(*Clear[Eqns,Vars,sol]*)
```

```
(*Free Ca*)
```

```
FreeCa := {
```

```
Ca[0] == Ca0,
```

```
Ca'[tt] == -γ * (Ca[tt] - CaRest)
```

```
(*DMn*)
```

```
- kOnPP1 * Ca[tt] * PP1[tt] + kOffPP1 * CaPP1[tt]
```

```
- kOnPP2 * Ca[tt] * PP2[tt] + kOffPP2 * CaPP2[tt]
```

```
- kOnDM * Ca[tt] * DMn[tt] + kOffDM * CaDMn[tt]
```

```
- kOnDM * Ca[tt] * DMf[tt] + kOffDM * CaDMf[tt]
```

```
- kOnDM * Ca[tt] * DMs[tt] + kOffDM * CaDMs[tt]
```

```
(*buffers*)
```

```
- kOnATP * Ca[tt] * ATP[tt] + kOffATP * CaATP[tt]
```

```
- kOnMB * Ca[tt] * MB[tt] + kOffMB * CaMB[tt]
```

```
(*dye*)
```

```
- kOnOG * Ca[tt] * OG[tt] + kOffOG * CaOG[tt]
```

```
}
```

```
;
```

```
(*Free Mg*)
```

```
FreeMg := {
```

```
Mg[0] == Mg0,
```

```
Mg'[tt] ==
```

```
- kOnMgATP * Mg[tt] * ATP[tt] + kOffMgATP * MgATP[tt]
```

```
- kOnMg * Mg[tt] * DMn[tt] + kOffMg * MgDMn[tt]
```

```
- kOnMg * Mg[tt] * DMf[tt] + kOffMg * MgDMf[tt]
```

```
- kOnMg * Mg[tt] * DMs[tt] + kOffMg * MgDMs[tt]
```

```
- kOnMg * Mg[tt] * PP2[tt] + kOffMgPP * MgPP2[tt]
```

```
- kOnMg * Mg[tt] * PP1[tt] + kOffMgPP * MgPP1[tt]
```

```
}
```

```
;
```

```
Eqns := {BufferDMn, BufferDMf, BufferDMs, BufferATP,
```

```
BufferPP1, BufferPP2, FreeCa, FreeMg, BufferMB, BufferOG}
```

```
;
```

```

Vars := {ATP, CaATP, MgATP, Ca, Mg, CaDMn, DMn, CaDMf, DMf, CaDMs,
  DMs, CaPP1, PP1, CaPP2, PP2, MgPP2, MgPP1, MB, CaMB, OG, CaOG}
;
sol := NDSolve[Eqns, Vars, {tt, 0., TimeWindow}
  (*,Method->{"EquationSimplification"->"Solve"}*)]
;
CafP = Extract[Ca[TimeWindow] /. sol, 1];
CafOG = KdOG * CaOG[tt] / OG[tt];

AppendTo[CaListReal, Evaluate[{Ca[tt]} /. sol]];
AppendTo[CaListDye, Evaluate[{CafOG} /. sol]];

];

```

10 mM DMN

general parameters

```

In[ ]:= TimeWindow = 0.006; (*End of simulation*)
tflash = 0.0; (*Time of flash*)
PlStart = 0.; (*Plot start*)

af = 0.67; (*fast uncaging fraction; Faas et al*)

(*Select dye*)
OGB1 = 0;
OGB5N = 1;
OGB6F = 0;
Fluo5F = 0;

CaRest = 227. * 10-9; (*Free pre-flash resting Ca;
  equilibrates with all buffers and DM*)
MgT = 0.5 * 10-3; (*total Mg in pipette*)
γ = 0.; (*Pump rate*)

(*Concentrations of dye, buffers, DM*)
OGtotal = 200. * 10-6;
ATPtotal = 5. * 10-3;
MBtotal = 480. * 10-6; (*(*Delvendahl, PNAS, 2015*)*)

DMT = 10. * 10-3; (*total concentration of DMn *)
(*uncaging efficiency*)
aStartDMN10 = 0.14;
aEndDMN10 = 0.25;

```

definitions and loop

```

In[ ]:= (*Dye*)
  If[OGB1 == 1,
    kOnOG =  $4.3 * 10^8$ ;
    kOffOG = 103.;]

  If[OGB5N == 1,
    kOnOG =  $2.5 * 10^8$ ;
    kOffOG = 6000.;]

  If[OGB6F == 1,
    kOnOG =  $3. * 10^8$ ;
    kOffOG = 900.;]

  If[Fluo5F == 1,
    kOnOG =  $3. * 10^8$ ;
    kOffOG = 249.;] (*Delvendahl PNAS; before: 432*)

  KdOG = kOffOG / kOnOG;
  kappaOG = OGtotal / KdOG;

  (*ATP*)
  kOnATP =  $5. * 10^8$ ;
  kOffATP = 100000.;
  kOnMgATP =  $1. * 10^7$ ; (*Bollmann Dissertation S. 59; *)
  kOffMgATP = 1000.;

  KdATP = kOffATP / kOnATP;
  kappaATP = ATPtotal / KdATP;
  KdMgATP = kOffMgATP / kOnMgATP;

  (*DM*)
  If[MgT == 0.,
    kOnDM =  $1.98 * 10^7$ ; (*Faas Plos Biol, 2007*)
    kOffDM = 0.14;
    ,
    kOnDM =  $2.9 * 10^7$ ; (*Faas Biophys J, 2005*)
    kOffDM = 0.19;
  ]

  (*Mg binding constants for DMn, DMf, DMs*)
  kOnMg =  $1.3 * 10^5$ ; (*all values for Mg are from Faas et al., 2005*)
  kOffMg = 0.2;

```

```

(*Ca binding constants for PP*)
kOnPP2 = kOnPP1 = kOnDM;
kOffPP2 = 3.6 * 10^3;
If[MgT == 0.,
  kOffPP1 = 7. * 10^4;,
  kOffPP1 = 6.9 * 10^4; ]

(*Mg binding constants for PP1,PP2*)
kOffMgPP = 3. * 10^2; (*for PP1,PP2*)
konMgPP = kOnMg; (*koMgPP not used in below diff. eq., only kOnMg*)

(*Equilibrium constants (not complete)*)
KdDM = kOffDM / kOnDM;
KdPP1 = kOffPP1 / kOnPP1;
KdMg = kOffMg / kOnMg;
kappaDM = DMT / KdDM;

(*Endogenous buffer*)
kOnMB = 5 * 10^8; (*Delvendahl, PNAS, 2015*)
kOffMB = 16 000;
KdMB = kOffMB / kOnMB;

TRest = 1000.;

(*----- Loop -----
-----*)
(*----- Loop -----
-----*)
(*----- Loop -----
-----*)

For[aCount = 1, aCount ≤ aNumberDMN10, aCount += 1,
  a = 10^ (Log10[aStartDMN10] +
    (aCount - 1) * (Log10[aEndDMN10] - Log10[aStartDMN10]) / (aNumberDMN10 - 1));

  (*----- Resting
  Equations -----*)

  (*Dye*)
  OGRest := {

    OG[0] == OGtotal,
    CaOG[0] == 0,

    OG'[tt] == -kOnOG * CaRest * OG[tt] + kOffOG * CaOG[tt],
    CaOG'[tt] == kOnOG * CaRest * OG[tt] - kOffOG * CaOG[tt]
  }

```

```

    }
;

(*ATP*)
ATPrest := {

    ATP[0] == ATPtotal,
    CaATP[0] == 0,
    MgATP[0] == 0,

    ATP'[tt] == -kOnATP * CaRest * ATP[tt] + kOffATP * CaATP[tt] -
        kOnMgATP * Mg[tt] * ATP[tt] + kOffMgATP * MgATP[tt],
    CaATP'[tt] == kOnATP * CaRest * ATP[tt] - kOffATP * CaATP[tt],
    MgATP'[tt] == kOnMgATP * Mg[tt] * ATP[tt] - kOffMgATP * MgATP[tt]

}

;

(*DM nitrophenes*)
DMnRest := {

    DMn[0] == (1 - a) * DMT,
    CaDMn[0] == 0.,
    MgDMn[0] == 0.,

    DMn'[tt] == -kOnDM * CaRest * DMn[tt] +
        kOffDM * CaDMn[tt] - kOnMg * Mg[tt] * DMn[tt] + kOffMg * MgDMn[tt],
    CaDMn'[tt] == kOnDM * CaRest * DMn[tt] - kOffDM * CaDMn[tt],
    MgDMn'[tt] == kOnMg * Mg[tt] * DMn[tt] - kOffMg * MgDMn[tt]

}

;

DMfRest := {

    DMf[0] == a * af * DMT,
    CaDMf[0] == 0.,
    MgDMf[0] == 0.,

    DMf'[tt] == -kOnDM * CaRest * DMf[tt] +
        kOffDM * CaDMf[tt] - kOnMg * Mg[tt] * DMf[tt] + kOffMg * MgDMf[tt],
    CaDMf'[tt] == kOnDM * CaRest * DMf[tt] - kOffDM * CaDMf[tt],
    MgDMf'[tt] == kOnMg * Mg[tt] * DMf[tt] - kOffMg * MgDMf[tt]

}

;

DMsRest := {

```

```

DMS[0] == a * (1 - af) * DMT,
CaDMs[0] == 0.,
MgDMs[0] == 0.,

DMS'[tt] == -kOnDM * CaRest * DMS[tt] +
  kOffDM * CaDMs[tt] - kOnMg * Mg[tt] * DMS[tt] + kOffMg * MgDMs[tt],
CaDMs'[tt] == kOnDM * CaRest * DMS[tt] - kOffDM * CaDMs[tt],
MgDMs'[tt] == kOnMg * Mg[tt] * DMS[tt] - kOffMg * MgDMs[tt]
}
;

(*Endogeneous buffer*)
MBRest := {

  MB[0] == MBtotal,
  CaMB[0] == 0,

  MB'[tt] == -kOnMB * CaRest * MB[tt] + kOffMB * CaMB[tt],
  CaMB'[tt] == kOnMB * CaRest * MB[tt] - kOffMB * CaMB[tt]
}

;

(*Free Mg*)
MgfRest := {
  Mg[0] == MgT,

  Mg'[tt] ==
    -kOnMgATP * Mg[tt] * ATP[tt] + kOffMgATP * MgATP[tt]
    - kOnMg * Mg[tt] * DMn[tt] + kOffMg * MgDMn[tt]
    - kOnMg * Mg[tt] * DMf[tt] + kOffMg * MgDMf[tt]
    - kOnMg * Mg[tt] * DMS[tt] + kOffMg * MgDMs[tt]
}

;
EqRest := {ATPrest, MgfRest, OGRest, DMnRest, DMfRest, DMSrest, MBRest};
VarsRest := {ATP, Mg, CaATP, MgATP, CaOG, OG, DMn,
  CaDMn, MgDMn, DMf, CaDMf, MgDMf, DMS, CaDMs, MgDMs, MB, CaMB}
;
solr := NDSolve[EqRest, VarsRest, {tt, 0, TRest}]
;

Ca0 = CaRest;
Mg0 = Extract[Mg[TRest] /. solr, 1];
ATP0 = Extract[ATP[TRest] /. solr, 1];
CaATP0 = Extract[CaATP[TRest] /. solr, 1];

```

```

MgATP0 = Extract[MgATP[TRest] /. solr, 1];
OG0 = Extract[OG[TRest] /. solr, 1];
CaOG0 = Extract[CaOG[TRest] /. solr, 1];
DMn0 = Extract[DMn[TRest] /. solr, 1];
CaDMn0 = Extract[CaDMn[TRest] /. solr, 1];
MgDMn0 = Extract[MgDMn[TRest] /. solr, 1];
DMf0 = Extract[DMf[TRest] /. solr, 1];
CaDMf0 = Extract[CaDMf[TRest] /. solr, 1];
MgDMf0 = Extract[MgDMf[TRest] /. solr, 1];
DMs0 = Extract[DMs[TRest] /. solr, 1];
CaDMs0 = Extract[CaDMs[TRest] /. solr, 1];
MgDMs0 = Extract[MgDMs[TRest] /. solr, 1];
MB0 = Extract[MB[TRest] /. solr, 1];
CaMB0 = Extract[CaMB[TRest] /. solr, 1];

ClearAll[EqRest, VarsRest];

(*----- Flash
Equations -----*)

(*Dye*)
BufferOG := {

  OG[0] == OG0,
  CaOG[0] == CaOG0,

  OG'[tt] == -kOnOG * Ca[tt] * OG[tt] + kOffOG * CaOG[tt],
  CaOG'[tt] == kOnOG * Ca[tt] * OG[tt] - kOffOG * CaOG[tt]}
;

(*ATP*)
BufferATP := {

  ATP[0] == ATP0,
  CaATP[0] == CaATP0,
  MgATP[0] == MgATP0,

  ATP'[tt] == -kOnATP * Ca[tt] * ATP[tt] + kOffATP * CaATP[tt] -
    kOnMgATP * Mg[tt] * ATP[tt] + kOffMgATP * MgATP[tt],
  CaATP'[tt] == kOnATP * Ca[tt] * ATP[tt] - kOffATP * CaATP[tt],
  MgATP'[tt] == kOnMgATP * Mg[tt] * ATP[tt] - kOffMgATP * MgATP[tt]
}
;

(*fast (tauf) and slow (taus) time constants for uncageing;

```



```

Faas et al., 2005,2007*)
If[MgT == 0.,
  tauf = 15.2 * 10^-6; (*Faas, 2007*)
  taus = 1.9 * 10^-3;
,
  tauf = 15. * 10^-6; (*Faas,2005*)
  taus = 2. * 10^-3; ]

;

(*The differential equations*)
(*non uncaging fraction of DMn*)
BufferDMn := {

  DMn[0] == DMn0,
  CaDMn[0] == CaDMn0,
  MgDMn[0] == MgDMn0,

  DMn'[tt] == -kOnDM * Ca[tt] * DMn[tt] +
    kOffDM * CaDMn[tt] - kOnMg * Mg[tt] * DMn[tt] + kOffMg * MgDMn[tt],
  CaDMn'[tt] == kOnDM * Ca[tt] * DMn[tt] - kOffDM * CaDMn[tt],
  MgDMn'[tt] == kOnMg * Mg[tt] * DMn[tt] - kOffMg * MgDMn[tt]
}

;

(*fast uncaging fraction of DMn*)
BufferDMf := {

  DMf[0] == DMf0,
  CaDMf[0] == CaDMf0,
  MgDMf[0] == MgDMf0,

  DMf'[tt] == -kOnDM * Ca[tt] * DMf[tt] + kOffDM * CaDMf[tt] - kOnMg * Mg[tt] *
    DMf[tt] + kOffMg * MgDMf[tt] - 1/tauf * DMf[tt] * UnitStep[tt - tflash],
  CaDMf'[tt] == kOnDM * Ca[tt] * DMf[tt] - kOffDM * CaDMf[tt] -
    1/tauf * CaDMf[tt] * UnitStep[tt - tflash],
  MgDMf'[tt] == kOnMg * Mg[tt] * DMf[tt] - kOffMg * MgDMf[tt] -
    1/tauf * MgDMf[tt] * UnitStep[tt - tflash]
}

;

(*slow uncaging fraction of DMn*)
BufferDMS := {

  DMS[0] == DMS0,
  CaDMS[0] == CaDMS0,
  MgDMS[0] == MgDMS0,

```

```

DMS'[tt] == -kOnDM * Ca[tt] * DMS[tt] + kOffDM * CaDMS[tt] - kOnMg * Mg[tt] *
  DMS[tt] + kOffMg * MgDMS[tt] - 1 / taus * DMS[tt] * UnitStep[tt - tflash],
CaDMS'[tt] == kOnDM * Ca[tt] * DMS[tt] - kOffDM * CaDMS[tt] -
  1 / taus * CaDMS[tt] * UnitStep[tt - tflash],
MgDMS'[tt] == kOnMg * Mg[tt] * DMS[tt] - kOffMg * MgDMS[tt] -
  1 / taus * MgDMS[tt] * UnitStep[tt - tflash]
}
;

(*Photoproducts*)
(*PP2: comes from DMf,DMS and MgDMf,MgDMS; but also binds Ca*)
BufferPP2 := {

  PP2[0] == 0,
  CaPP2[0] == 0,
  MgPP2[0] == 0,

  PP2'[tt] == -kOnPP2 * Ca[tt] * PP2[tt] + kOffPP2 * CaPP2[tt] -
    kOnMg * Mg[tt] * PP2[tt] + kOffMgPP * MgPP2[tt] + 2 * (1 / tauF * DMf[tt] *
      UnitStep[tt - tflash] + 1 / taus * DMS[tt] * UnitStep[tt - tflash])
    + 1 / tauF * MgDMf[tt] * UnitStep[tt - tflash] +
    1 / taus * MgDMS[tt] * UnitStep[tt - tflash],

  CaPP2'[tt] == kOnPP2 * Ca[tt] * PP2[tt] - kOffPP2 * CaPP2[tt],

  MgPP2'[tt] == kOnMg * Mg[tt] * PP2[tt] - kOffMgPP * MgPP2[tt] + 1 / tauF *
    MgDMf[tt] * UnitStep[tt - tflash] + 1 / taus * MgDMS[tt] * UnitStep[tt - tflash]
}
;

(*PP1: Comes from CaDMf,CaDMS and binds Ca and Mg*)
BufferPP1 := {

  PP1[0] == 0,
  CaPP1[0] == 0,
  MgPP1[0] == 0,

  PP1'[tt] == -kOnPP1 * Ca[tt] * PP1[tt] +
    kOffPP1 * CaPP1[tt] - kOnMg * Mg[tt] * PP1[tt] + kOffMgPP * MgPP1[tt]
    + 1 / tauF * CaDMf[tt] * UnitStep[tt - tflash] +
    1 / taus * CaDMS[tt] * UnitStep[tt - tflash],

  CaPP1'[tt] == kOnPP1 * Ca[tt] * PP1[tt] -
    kOffPP1 * CaPP1[tt] + 1 / tauF * CaDMf[tt] * UnitStep[tt - tflash] +
    1 / taus * CaDMS[tt] * UnitStep[tt - tflash],

```

```

MgPP1'[tt] == kOnMg * Mg[tt] * PP1[tt] - kOffMgPP * MgPP1[tt]

}
;

(*Endogeneous Buffer*)
BufferMB := {

  MB[0] == MB0,
  CaMB[0] == CaMB0,

  MB'[tt] == -kOnMB * Ca[tt] * MB[tt] + kOffMB * CaMB[tt],
  CaMB'[tt] == kOnMB * Ca[tt] * MB[tt] - kOffMB * CaMB[tt]

}

;

(*Clear[Eqns,Vars,sol]*)

(*Free Ca*)
FreeCa := {
  Ca[0] == Ca0,

  Ca'[tt] == -γ * (Ca[tt] - CaRest)
  (*DMn*)
  - kOnPP1 * Ca[tt] * PP1[tt] + kOffPP1 * CaPP1[tt]
  - kOnPP2 * Ca[tt] * PP2[tt] + kOffPP2 * CaPP2[tt]
  - kOnDM * Ca[tt] * DMn[tt] + kOffDM * CaDMn[tt]
  - kOnDM * Ca[tt] * DMf[tt] + kOffDM * CaDMf[tt]
  - kOnDM * Ca[tt] * DMs[tt] + kOffDM * CaDMs[tt]
  (*buffers*)
  - kOnATP * Ca[tt] * ATP[tt] + kOffATP * CaATP[tt]
  - kOnMB * Ca[tt] * MB[tt] + kOffMB * CaMB[tt]
  (*dye*)
  - kOnOG * Ca[tt] * OG[tt] + kOffOG * CaOG[tt]
}
;

(*Free Mg*)
FreeMg := {
  Mg[0] == Mg0,

  Mg'[tt] ==
  - kOnMgATP * Mg[tt] * ATP[tt] + kOffMgATP * MgATP[tt]
  - kOnMg * Mg[tt] * DMn[tt] + kOffMg * MgDMn[tt]
  - kOnMg * Mg[tt] * DMf[tt] + kOffMg * MgDMf[tt]
  - kOnMg * Mg[tt] * DMs[tt] + kOffMg * MgDMs[tt]
  - kOnMg * Mg[tt] * PP2[tt] + kOffMgPP * MgPP2[tt]
}

```

```

      - kOnMg * Mg[tt] * PP1[tt] + kOffMgPP * MgPP1[tt]
    }

;

Eqns := {BufferDMn, BufferDMf, BufferDMs, BufferATP,
        BufferPP1, BufferPP2, FreeCa, FreeMg, BufferMB, BufferOG}
;
Vars := {ATP, CaATP, MgATP, Ca, Mg, CaDMn, DMn, CaDMf, DMf, CaDMs,
        DMs, CaPP1, PP1, CaPP2, PP2, MgPP2, MgPP1, MB, CaMB, OG, CaOG}
;
sol := NDSolve[Eqns, Vars, {tt, 0., TimeWindow}
  (*, Method->{"EquationSimplification"->"Solve"}*)]
;
CafP = Extract[Ca[TimeWindow] /. sol, 1];
CafOG = KdOG * CaOG[tt] / OG[tt];

AppendTo[CaListReal, Evaluate[{Ca[tt]} /. sol]];
AppendTo[CaListDye, Evaluate[{CafOG} /. sol]];
];




```


Plot and further processing

```

In[ ]:= Plot[10^6 * CaListReal, {tt, 0, TimeWindow}, PlotLabel -> "Real free Ca (μM)"]
Plot[10^6 * CaListDye, {tt, 0, TimeWindow},
  PlotLabel -> "Free Ca reported by dye (μM)"]
LogPlot[10^6 * CaListReal, {tt, 0, TimeWindow}, PlotLabel -> "Real free Ca (μM)"]
LogPlot[10^6 * CaListDye, {tt, 0, TimeWindow},
  PlotLabel -> "Free Ca reported by dye (μM)"]
CaListDyePeak =
  Table[NMaximize[{CaListDye[[nn]][[1]][[1]], 0 ≤ tt ≤ TimeWindow}, tt][[1]],
    {nn, Length[CaListDye]}]
  (* "[1][1]" is needed to get rid of these brackets { } *)

```





```
Out[*]:= {7.03073 × 10-7, 4.79194 × 10-6, 5.53376 × 10-6,  
          0.0000257412, 0.0000299583, 0.0000740312}
```

```
In[*]:= runs = Length[CaListDyePeak];
```

Release scheme and parameters

Define release scheme

```
In[*]:= nStates = 7;  
mat = Table[0, {nStates}, {nStates}];
```

forward rates

```

ln[#:]= from = 1; (*0 ca bound*)
      kk = 5 kon;
      mat[[from+1, from]] += kk; mat[[from, from]] += -kk;

      from = 2;
      kk = 4 kon;
      mat[[from+1, from]] += kk; mat[[from, from]] += -kk;

      from = 3;
      kk = 3 kon;
      mat[[from+1, from]] += kk; mat[[from, from]] += -kk;

      from = 4;
      kk = 2 kon;
      mat[[from+1, from]] += kk; mat[[from, from]] += -kk;

      from = 5; (*4 ca bound*)
      kk = kon;
      mat[[from+1, from]] += kk; mat[[from, from]] += -kk;

      from = 6; (*5 ca bound*)
      kk = gamma;
      mat[[from+1, from]] += kk; mat[[from, from]] += -kk;

```

backwards rates

```
In[ ]:= from = 2; (*1 ca bound*)
      kk = koff b^0;
      mat[[from-1, from]] += kk; mat[[from, from]] += -kk;

      from = 3;
      kk = 2 koff b^1;
      mat[[from-1, from]] += kk; mat[[from, from]] += -kk;

      from = 4;
      kk = 3 koff b^2;
      mat[[from-1, from]] += kk; mat[[from, from]] += -kk;

      from = 5;
      kk = 4 koff b^3;
      mat[[from-1, from]] += kk; mat[[from, from]] += -kk;

      from = 6; (*5 ca bound*)
      kk = 5 koff b^4;
      mat[[from-1, from]] += kk; mat[[from, from]] += -kk;
```

outflux from matrix

```
In[ ]:= mat[[1, 1]] += -kunfill; (* is multiplied by ss1[t] *)
```

influx in matrix

```
In[ ]:= mat[[1, 1]] += (1/ss1[t]) kfill fillStateSS[t];
      (* (1/ss1[t]) is needed to merge the fillState
      Diff Eq. in the matrix format. Note ss1[t] is never 0 *)
```

Matrix

```
In[ ]:= mat // TableForm
```

```
Out[ ]//TableForm=
```

| | | | |
|---|--------------------------------|-------------------------------------|---|
| $-5 \text{ kon} - \text{kunfill} + \frac{\text{kfill fillStateSS[t]}}{\text{ss1[t]}}$ | koff | 0 | 0 |
| 5 kon | $-\text{koff} - 4 \text{ kon}$ | 2 b koff | 0 |
| 0 | 4 kon | $-2 \text{ b koff} - 3 \text{ kon}$ | $3 \text{ b}^2 \text{ koff}$ |
| 0 | 0 | 3 kon | $-3 \text{ b}^2 \text{ koff} - 2 \text{ kon}$ |
| 0 | 0 | 0 | 2 kon |
| 0 | 0 | 0 | 0 |
| 0 | 0 | 0 | 0 |

Parameters of release scheme

```
In[ ]:= linInterpol[x_, a_, b_] := a + x * (b - a);
```

```
In[ ]:= q10 = 2.3;  
tempFact = q10 ^ ((37 - 24) / 10);
```

```

In[ ]:= Clear[caFunc, kprimScheme];
(*Clear is needed if the cell is executed for a 2nd time when
caFunc is already set to a value or an Interpolationfunction*)

caRest = CaRest; (*227nM see above*)

affinityFactor = 3.0;
konScheme = linInterpol[sitePlugging[t],
  caFunc[t] Sqrt[affinityFactor] tempFact 1.*^8,
  0.1 caFunc[t] Sqrt[affinityFactor] tempFact 1.*^8
]; (*M^-1 s^-1*)

koffScheme = linInterpol[sitePlugging[t],
  (1/Sqrt[affinityFactor]) tempFact 15 000,
  0.4 (1/Sqrt[affinityFactor]) tempFact 15 000
]; (*s^-1*)
gammaScheme = tempFact 6000; (*s^-1*)
bScheme = 0.25;

KdPrim = 2.*^-6;
kprimScheme = 2.5 + 60. (caFunc[t] / (KdPrim + caFunc[t]));
kunprimScheme = 2.5 + 60. (caRest / (KdPrim + caRest));

KdFill = 2.*^-6;
kfillScheme = 100 + 800. (caFunc[t] / (KdFill + caFunc[t]));
kunfillScheme = 100 + 800. (caRest / (KdFill + caRest));

repl = {
  kon → konScheme,
  koff → koffScheme ,
  gamma → gammaScheme ,
  b → bScheme,

  kprim → kprimScheme ,
  kunprim → kunprimScheme ,

  kfill → kfillScheme ,
  kunfill → kunfillScheme

  (*
  kbasal → kbasalScheme ,
  kunfill → kunfillScheme
  *)
};

In[ ]:= tauOfDecayOfUncagedCa = 0.4;

```

```
In[ ]:= siteClearanceTau = 0.04;
```

Initial occupancy


```
In[ ]:= (*test initial equilibrium occupancy*)
caFunc[t_] := caTmp;
fillStateSSInitial = kprimScheme / kunprimScheme;
ss0Initial = fillStateSSInitial * kfillScheme / kunfillScheme;
(ss0Initial /. caTmp → 180*^-9)
(ss0Initial /. caTmp → 50*^-9)
(ss0Initial /. caTmp → 30*^-9)
(ss0Initial /. caTmp → 180*^-9) / (ss0Initial /. caTmp → 30*^-9)
(*test initial *)
Plot[kprimScheme / kunprimScheme, {caTmp, 0, 300*^-9}]
Plot[kfillScheme / kunfillScheme, {caTmp, 0, 300*^-9}]
LogLinearPlot[{kprimScheme / kunprimScheme, kfillScheme / kunfillScheme},
  {caTmp, .1*^-9, 30*^-6}, PlotRange → All]
Plot[{kprimScheme / kunprimScheme, kfillScheme / kunfillScheme},
  {caTmp, .1*^-9, 1*^-6}, PlotRange → All]
```




```
Out[ ]:= 0.791348
```

```
Out[ ]:= 0.302831
```

```
Out[ ]:= 0.242117
```

```
Out[ ]:= 3.26845
```





```

In[ ]:= (*calculate initial equilibrium occupancy*)
caFunc[t_] := caRest;
kprimScheme
kunprimScheme
fillStateSSInitial = kprimScheme / kunprimScheme
kfillScheme
kunfillScheme
ss0Initial = fillStateSSInitial * kfillScheme / kunfillScheme

Out[ ]:= 8.61585

Out[ ]:= 8.61585

Out[ ]:= 1.

Out[ ]:= 181.545

Out[ ]:= 181.545

Out[ ]:= 1.

In[ ]:= caRest
Out[ ]:=  $2.27 \times 10^{-7}$ 

```

Diff eq.

```

In[ ]:= Clear[caFunc, eq]; (*Clear is needed if the cell is executed for a 2nd time
when caFunc is already set to a value or an Interpolationfunction*)
ss[t_] = {ss1[t], ss2[t], ss3[t], ss4[t], ss5[t], ss6[t], ss7[t]};
eq = {ss'[t] == (mat /. repl).ss[t],
      ss[0] == {ss0Initial, 0., 0., 0., 0., 0., 0.},
      (fillStateSS'[t] == kprim - kunprim fillStateSS[t] -
        kfill fillStateSS[t] + kunfill ss1[t]) /. repl,
      fillStateSS[0] == fillStateSSInitial,
      sitePlugging'[t] ==
        (1 - sitePlugging[t]) ss7'[t] - siteClearanceTau sitePlugging[t],
      sitePlugging[0] == 0
    };

```

Print diff eq.

In[]:= **mat**

```
Out[ ]:= { {-5 kon - kunfill +  $\frac{kfill \text{ fillStateSS}[t]}{ss1[t]}$ , koff, 0, 0, 0, 0, 0},
  {5 kon, -koff - 4 kon, 2 b koff, 0, 0, 0, 0},
  {0, 4 kon, -2 b koff - 3 kon, 3 b2 koff, 0, 0, 0},
  {0, 0, 3 kon, -3 b2 koff - 2 kon, 4 b3 koff, 0, 0},
  {0, 0, 0, 2 kon, -4 b3 koff - kon, 5 b4 koff, 0},
  {0, 0, 0, 0, kon, -gamma - 5 b4 koff, 0}, {0, 0, 0, 0, 0, gamma, 0}}
```

In[]:= **repl**

```
Out[ ]:= { kon →  $5.11454 \times 10^8 \text{ caFunc}[t] - 4.60309 \times 10^8 \text{ caFunc}[t] \times \text{sitePlugging}[t]$ ,
  koff →  $25572.7 - 15343.6 \text{ sitePlugging}[t]$ , gamma →  $17717.3$ ,
  b →  $0.25$ , kprim →  $2.5 + \frac{60. \text{ caFunc}[t]}{2. \times 10^{-6} + \text{ caFunc}[t]}$ , kunprim →  $8.61585$ ,
  kfill →  $100 + \frac{800. \text{ caFunc}[t]}{2. \times 10^{-6} + \text{ caFunc}[t]}$ , kunfill →  $181.545$ }
```

In[]:= **mat /. repl**

```
Out[ ]:= { {-181.545 - 5 ( $5.11454 \times 10^8 \text{ caFunc}[t] - 4.60309 \times 10^8 \text{ caFunc}[t] \times \text{sitePlugging}[t]$ ) +
  ( $100 + \frac{800. \text{ caFunc}[t]}{2. \times 10^{-6} + \text{ caFunc}[t]}$ )  $\text{ fillStateSS}[t]$ 
   $\frac{\text{ fillStateSS}[t]}{ss1[t]}$ ,
  25572.7 - 15343.6  $\text{ sitePlugging}[t]$ , 0, 0, 0, 0, 0},
  {5 ( $5.11454 \times 10^8 \text{ caFunc}[t] - 4.60309 \times 10^8 \text{ caFunc}[t] \times \text{sitePlugging}[t]$ ),
  -25572.7 + 15343.6  $\text{ sitePlugging}[t]$  -
  4 ( $5.11454 \times 10^8 \text{ caFunc}[t] - 4.60309 \times 10^8 \text{ caFunc}[t] \times \text{sitePlugging}[t]$ ),
  0.5 ( $25572.7 - 15343.6 \text{ sitePlugging}[t]$ ), 0, 0, 0, 0},
  {0, 4 ( $5.11454 \times 10^8 \text{ caFunc}[t] - 4.60309 \times 10^8 \text{ caFunc}[t] \times \text{sitePlugging}[t]$ ),
  -0.5 ( $25572.7 - 15343.6 \text{ sitePlugging}[t]$ ) -
  3 ( $5.11454 \times 10^8 \text{ caFunc}[t] - 4.60309 \times 10^8 \text{ caFunc}[t] \times \text{sitePlugging}[t]$ ),
  0.1875 ( $25572.7 - 15343.6 \text{ sitePlugging}[t]$ ), 0, 0, 0},
  {0, 0, 3 ( $5.11454 \times 10^8 \text{ caFunc}[t] - 4.60309 \times 10^8 \text{ caFunc}[t] \times \text{sitePlugging}[t]$ ),
  -0.1875 ( $25572.7 - 15343.6 \text{ sitePlugging}[t]$ ) -
  2 ( $5.11454 \times 10^8 \text{ caFunc}[t] - 4.60309 \times 10^8 \text{ caFunc}[t] \times \text{sitePlugging}[t]$ ),
  0.0625 ( $25572.7 - 15343.6 \text{ sitePlugging}[t]$ ), 0, 0},
  {0, 0, 0, 2 ( $5.11454 \times 10^8 \text{ caFunc}[t] - 4.60309 \times 10^8 \text{ caFunc}[t] \times \text{sitePlugging}[t]$ ),
  -5.11454  $\times 10^8 \text{ caFunc}[t] - 0.0625$  ( $25572.7 - 15343.6 \text{ sitePlugging}[t]$ ) +
  4.60309  $\times 10^8 \text{ caFunc}[t] \times \text{sitePlugging}[t]$ ,
  0.0195313 ( $25572.7 - 15343.6 \text{ sitePlugging}[t]$ ), 0},
  {0, 0, 0, 0,  $5.11454 \times 10^8 \text{ caFunc}[t] - 4.60309 \times 10^8 \text{ caFunc}[t] \times \text{sitePlugging}[t]$ ,
  -17717.3 - 0.0195313 ( $25572.7 - 15343.6 \text{ sitePlugging}[t]$ ), 0},
  {0, 0, 0, 0, 0, 17717.3, 0}}
```


In[*]:= eq

Out[*]= { {ss1'[t], ss2'[t], ss3'[t], ss4'[t], ss5'[t], ss6'[t], ss7'[t]} ==


$$\left\{ \begin{aligned} & -181.545 - 5 \left(5.11454 \times 10^8 \text{caFunc}[t] - 4.60309 \times 10^8 \text{caFunc}[t] \times \text{sitePlugging}[t] \right) + \\ & \frac{\left(100 + \frac{800. \text{caFunc}[t]}{2. \times 10^{-6} + \text{caFunc}[t]} \right) \text{fillStateSS}[t]}{\text{ss1}[t]} \right\} \text{ss1}[t] + \\ & (25572.7 - 15343.6 \text{sitePlugging}[t]) \text{ss2}[t], \\ & 5 \left(5.11454 \times 10^8 \text{caFunc}[t] - 4.60309 \times 10^8 \text{caFunc}[t] \times \text{sitePlugging}[t] \right) \text{ss1}[t] + \\ & (-25572.7 + 15343.6 \text{sitePlugging}[t] - \\ & 4 \left(5.11454 \times 10^8 \text{caFunc}[t] - 4.60309 \times 10^8 \text{caFunc}[t] \times \text{sitePlugging}[t] \right)) \\ & \text{ss2}[t] + 0.5 \left(25572.7 - 15343.6 \text{sitePlugging}[t] \right) \text{ss3}[t], \\ & 4 \left(5.11454 \times 10^8 \text{caFunc}[t] - 4.60309 \times 10^8 \text{caFunc}[t] \times \text{sitePlugging}[t] \right) \text{ss2}[t] + \\ & (-0.5 \left(25572.7 - 15343.6 \text{sitePlugging}[t] \right) - \\ & 3 \left(5.11454 \times 10^8 \text{caFunc}[t] - 4.60309 \times 10^8 \text{caFunc}[t] \times \text{sitePlugging}[t] \right)) \\ & \text{ss3}[t] + 0.1875 \left(25572.7 - 15343.6 \text{sitePlugging}[t] \right) \text{ss4}[t], \\ & 3 \left(5.11454 \times 10^8 \text{caFunc}[t] - 4.60309 \times 10^8 \text{caFunc}[t] \times \text{sitePlugging}[t] \right) \text{ss3}[t] + \\ & (-0.1875 \left(25572.7 - 15343.6 \text{sitePlugging}[t] \right) - \\ & 2 \left(5.11454 \times 10^8 \text{caFunc}[t] - 4.60309 \times 10^8 \text{caFunc}[t] \times \text{sitePlugging}[t] \right)) \\ & \text{ss4}[t] + 0.0625 \left(25572.7 - 15343.6 \text{sitePlugging}[t] \right) \text{ss5}[t], \\ & 2 \left(5.11454 \times 10^8 \text{caFunc}[t] - 4.60309 \times 10^8 \text{caFunc}[t] \times \text{sitePlugging}[t] \right) \text{ss4}[t] + \\ & (-5.11454 \times 10^8 \text{caFunc}[t] - 0.0625 \left(25572.7 - 15343.6 \text{sitePlugging}[t] \right) + \\ & 4.60309 \times 10^8 \text{caFunc}[t] \times \text{sitePlugging}[t]) \text{ss5}[t] + \\ & 0.0195313 \left(25572.7 - 15343.6 \text{sitePlugging}[t] \right) \text{ss6}[t], \\ & \left(5.11454 \times 10^8 \text{caFunc}[t] - 4.60309 \times 10^8 \text{caFunc}[t] \times \text{sitePlugging}[t] \right) \text{ss5}[t] + \\ & (-17717.3 - 0.0195313 \left(25572.7 - 15343.6 \text{sitePlugging}[t] \right)) \text{ss6}[t], \\ & 17717.3 \text{ss6}[t] \}, \{ \text{ss1}[0], \text{ss2}[0], \text{ss3}[0], \text{ss4}[0], \text{ss5}[0], \\ & \text{ss6}[0], \text{ss7}[0] \} = \{ 1., 0., 0., 0., 0., 0., 0. \}, \\ & \text{fillStateSS}'[t] = 2.5 + \frac{60. \text{caFunc}[t]}{2. \times 10^{-6} + \text{caFunc}[t]} - 8.61585 \text{fillStateSS}[t] - \\ & \left(100 + \frac{800. \text{caFunc}[t]}{2. \times 10^{-6} + \text{caFunc}[t]} \right) \text{fillStateSS}[t] + 181.545 \text{ss1}[t], \\ & \text{fillStateSS}[0] = 1., \text{sitePlugging}'[t] = \\ & -0.04 \text{sitePlugging}[t] + (1 - \text{sitePlugging}[t]) \text{ss7}'[t], \\ & \text{sitePlugging}[0] = 0 \} \end{aligned}$$





Solve all states





```
In[ ]:= caFunc[t_] := 3*^-6 * Exp[-t / tauOfDecayOfUncagedCa];;
Plot[caFunc[t], {t, 0, 0.4}, PlotRange -> All]
```



```
In[ ]:= myNDSolveResults = NDSolve[eq,
  {fillStateSS, ss1, ss2, ss3, ss4, ss5, ss6, ss7, sitePlugging}, {t, 0, 10.}];
tEndForPlot = 1.;
Plot[(fillStateSS[t] /. myNDSolveResults), {t, 0, tEndForPlot}, PlotRange -> All]
Plot[(ss1[t] /. myNDSolveResults), {t, 0, tEndForPlot}, PlotRange -> All]
Plot[(ss2[t] /. myNDSolveResults), {t, 0, tEndForPlot}, PlotRange -> All]
Plot[(ss3[t] /. myNDSolveResults), {t, 0, tEndForPlot}, PlotRange -> All]
Plot[(ss4[t] /. myNDSolveResults), {t, 0, tEndForPlot}, PlotRange -> All]
Plot[(ss5[t] /. myNDSolveResults), {t, 0, tEndForPlot}, PlotRange -> All]
Plot[(ss6[t] /. myNDSolveResults), {t, 0, tEndForPlot}, PlotRange -> All]
Plot[(ss7[t] /. myNDSolveResults), {t, 0, tEndForPlot}, PlotRange -> All]
Plot[(sitePlugging[t] /. myNDSolveResults), {t, 0, tEndForPlot}, PlotRange -> All]
```







Loop

make lists for later

```
In[ ]:= simCaList = Table[0, {runs}];
        simParamNv = Table[0, {7}, {runs}];
```

C5

```
In[ ]:= baselineC5 = Table[{ttt, 0}, {ttt, cursorStart, -1*^-6, dtOfDataC5}];
        (*Lists for saving data within loop*)
        simParamNoiseC5 = Table[0, {numberOfFitParamToBeSaved}, {noiseRepeats}];
        simParamMedianC5 = Table[0, {numberOfFitParamToBeSaved}, {runs}];
        simParamQuantile1C5 = Table[0, {numberOfFitParamToBeSaved}, {runs}];
        simParamQuantile2C5 = Table[0, {numberOfFitParamToBeSaved}, {runs}];
```

C10

```
In[ ]:= baselineC10 = Table[{ttt, 0}, {ttt, cursorStart, -1*^-6, dtOfDataC10}];
        (*Lists for saving data within loop*)
        simParamNoiseC10 = Table[0, {numberOfFitParamToBeSaved}, {noiseRepeats}];
        simParamMedianC10 = Table[0, {numberOfFitParamToBeSaved}, {runs}];
        simParamQuantile1C10 = Table[0, {numberOfFitParamToBeSaved}, {runs}];
        simParamQuantile2C10 = Table[0, {numberOfFitParamToBeSaved}, {runs}];
```

D

```
In[ ]:= baselineD = Table[{ttt, 0}, {ttt, cursorStart, -1*^-6, dtOfDataD}];
        (*Lists for saving data within loop*)
        simParamNoiseD = Table[0, {numberOfFitParamToBeSaved}, {noiseRepeats}];
        simParamMedianD = Table[0, {numberOfFitParamToBeSaved}, {runs}];
        simParamQuantile1D = Table[0, {numberOfFitParamToBeSaved}, {runs}];
        simParamQuantile2D = Table[0, {numberOfFitParamToBeSaved}, {runs}];
```

Long

```
In[ ]:= baselineLong = Table[{ttt, 0}, {ttt, -0.05, -1*^-6, dtOfDataLong}];
```

Loop

```
In[ ]:= For[r = 1, r ≤ runs, r += 1,
        myCaNow = CaListDyePeak[[r]];
        lastSimulatedCaListReal = CaListReal[[r]][[1]][[1]] /. tt → TimeWindow;
```

```

(*"[1][]" is needed to get rid of these brackets {}*)
Print[
  "-----"
  "-----"];
Print["----- Ca = ", 1*^6 myCaNow,
  " uM -----"];
Print[
  "-----"
  "-----"];
simCaList[[r]] = myCaNow;
caFunc[t_]:= If[t < TimeWindow,
  CaListReal[[r]][[1]][[1]] /. tt -> t,
  (*tt because this is the symbol used in "Calculate Ca transients"*)
  lastSimulatedCaListReal * Exp[-t/tauOfDecayOfUncagedCa]
];
(* solve Diff Eq.: *)
myNDSolveResults = NDSolve[eq, ss7, {t, 0, 0.4}];
(* plot results: *)
fused[t_] := ss7[t];
Plot[(fused[t] /. myNDSolveResults),
  {t, 0, cursorEnd}, PlotRange -> All] // Print;
Plot[(fused[t] /. myNDSolveResults), {t, 0, cursorEndLong},
  PlotRange -> All] // Print;
If[exportYes == 1,
  toExport = Table[{t, (fused[t] /. myNDSolveResults)[[1]]},
    {t, 0., cursorEndLong, dtOfPlotsForExport}];
  Export["withinLoop r" <> ToString[r] <> " Ca" <> ToString[1*^6 myCaNow] <>
    " withoutNoise.txt", toExport, "Table"];
];
(* sample data and add baseline: -----*)
tmpCumRelC5 = Table[{t, (fused[t] /. myNDSolveResults)[[1]]},
  {t, 0., cursorEnd, dtOfDataC5}];
tmpToFitC5 = Catenate[{baselineC5, tmpCumRelC5}];
tmpCumRelC10 = Table[{t, (fused[t] /. myNDSolveResults)[[1]]},
  {t, 0., cursorEnd, dtOfDataC10}];
tmpToFitC10 = Catenate[{baselineC10, tmpCumRelC10}];
tmpCumRelD = Table[{t, (fused[t] /. myNDSolveResults)[[1]]},
  {t, 0., cursorEnd, dtOfDataD}];
tmpToFitD = Catenate[{baselineD, tmpCumRelD}];
tmpCumRelLong = Table[{t, (fused[t] /. myNDSolveResults)[[1]]},
  {t, 0., cursorEndLong, dtOfDataLong}];
tmpToFitLong = Catenate[{baselineLong, tmpCumRelLong}];

(*----- get amplitude
  without noise and without fitting -----*)
For[NvCount = 1, NvCount <= 7, NvCount += 1,

```

```

simParamNv[[NvCount, r]] =
  (fused[timeOfNv[[NvCount]]] /. myNDSolveResults)[[1]];
(* the [[1]] is somehow needed to get rid of a list
   structure probably related to the interpolate function*)
];

(*----- Startvalues for
   fit the same for all C5 C10 and D -----*)
caAdjustedTau1Guess = tau1Guess / ((myCaNow / 10.*^-6) ^ 4);
caAdjustedTau1Guess = tau1Guess / ((myCaNow / 10.*^-6) ^ 1);
caAdjustedTau2Guess = 10 caAdjustedTau1Guess;
caAdjustedDelayGuess = delayGuess / ((myCaNow / 10.*^-6) ^ 1);

(*----- Fitting of data,
   saving of results, and plotting-----*)
(*-----*)
(*----- C5 -----*)
(*-----*)
(*-----*)
Print[
  "-----
   C5"];
(*check that signal is large enough relative to noise to obtain
   useful fit results. If not, do not do fitting and set everything to {}*)
If[simParamNv[[5, r]] > signalToNoiseRatioC5 myNoiseC5, (*add noise
   several times and do the fitting and then average the results*)
  For[noiseN = 1, noiseN ≤ noiseRepeats, noiseN += 1,
    (*Print[noiseN];*)
    tmpToFitNoise = Transpose[{tmpToFitC5[[All, 1]],
      # + RandomVariate[NormalDistribution[0, myNoiseC5]] & /@
      tmpToFitC5[[All, 2]]}];
    (*fit mono-exp*)
    fitResultsTMP = NonlinearModelFit[tmpToFitNoise, myFitMono[x1],
      {{delayMono, delayGuess}, {ampMono, ampGuess}, {tau1Mono,
        caAdjustedTau1Guess}}, x1, MaxIterations → myMaxIterations];
    fitResultMono = fitResultsTMP[{"BestFitParameters"}];
    simParamNoiseC5[[1, noiseN]] = 0; (*not used anymore*)
    simParamNoiseC5[[2, noiseN]] =
      fitResultsTMP["ANOVATableSumsOfSquares"][[2]];
    (*Print[fitResultsTMP["ANOVATableSumsOfSquares"]];*)
    simParamNoiseC5[[3, noiseN]] = (delayMono /. fitResultMono)[[1]];
    simParamNoiseC5[[4, noiseN]] = ((ampMono /. fitResultMono)[[1]]);
    simParamNoiseC5[[5, noiseN]] = (1 / (tau1Mono /. fitResultMono)[[1]]);
    (*fit bi-exp*)
    fitResultsTMP =

```

```

NonlinearModelFit[tmpToFitNoise, myFitBi[x1], {{delay, delayGuess},
  {amp, ampGuess}, {amp1, amp1Guess}, {tau1, caAdjustedTau1Guess},
  {tau2, caAdjustedTau2Guess}}, x1, MaxIterations → myMaxIterations];
fitResultBi = fitResultsTMP["BestFitParameters"];
simParamNoiseC5[[6, noiseN]] = simParamNoiseC5[[2, noiseN]] /
  fitResultsTMP["ANOVATableSumsOfSquares"][[2]];
simParamNoiseC5[[7, noiseN]] = (delay /. fitResultBi)[[1]];
simParamNoiseC5[[8, noiseN]] = ((amp /. fitResultBi)[[1]]);
simParamNoiseC5[[9, noiseN]] = ((amp amp1 /. fitResultBi)[[1]]);
(*relative amp1*)
simParamNoiseC5[[10, noiseN]] = (1 / (tau1 /. fitResultBi)[[1]]);
simParamNoiseC5[[11, noiseN]] = (1 / (tau2 /. fitResultBi)[[1]]);
(*merge*)
If[
  (*to use the bi-exp fit, the following criteria should be fulfilled:*)
  (*chi2 should improve(=decrease) by >10%*)
  (simParamNoiseC5[[6, noiseN]] > 1.04)
  &&
  (*tau1 and tau2 of bi fit should be factor of >3 different*)
  ((simParamNoiseC5[[11, noiseN]] / simParamNoiseC5[[10, noiseN]]) < 3.)
  &&
  (*relative amplitude of 1st component should be > 5% *)
  (((amp1 /. fitResultBi)[[1]] > 0.05)
  &&
  (*relative amplitude of 1st component should be < 95% *)
  (((amp1 /. fitResultBi)[[1]] < 0.95)
  ,
  (*take bi*)
  Print["take bi"];
  simParamNoiseC5[[12, noiseN]] = simParamNoiseC5[[7, noiseN]];
  (*delay*)
  simParamNoiseC5[[13, noiseN]] = simParamNoiseC5[[8, noiseN]];
  (*amp*)
  simParamNoiseC5[[14, noiseN]] = simParamNoiseC5[[9, noiseN]];
  (*amp1*)
  simParamNoiseC5[[15, noiseN]] = simParamNoiseC5[[10, noiseN]];
  (*tau1*)
  simParamNoiseC5[[16, noiseN]] = simParamNoiseC5[[11, noiseN]]; (*tau2*)
  ,
  (*take mono*)
  Print["take mono"];
  simParamNoiseC5[[12, noiseN]] = simParamNoiseC5[[3, noiseN]];
  (*delay*)
  simParamNoiseC5[[13, noiseN]] = simParamNoiseC5[[4, noiseN]];
  (*amp*)
  simParamNoiseC5[[14, noiseN]] = NaN; (*amp1*)
  simParamNoiseC5[[15, noiseN]] = simParamNoiseC5[[5, noiseN]];

```

```

(*tau1*)
simParamNoiseC5[[16, noiseN]] = NaN; (*tau2*)
];
];
(*plot last example of the noise loop*)
gr1 = ListPlot[tmpToFitNoise, PlotRange → All, PlotStyle → Black];
gr2 = Plot[myFitMono[x1] /. fitResultMono,
  {x1, cursorStart, cursorEnd}, PlotRange → All, PlotStyle → {Blue, Dashed}];
gr3 = Plot[myFitBi[x1] /. fitResultBi, {x1, cursorStart, cursorEnd},
  PlotRange → All, PlotStyle → {Green, Dashed}];
Show[gr1, gr2, gr3, PlotRange → All] // Print;
If[exportYes == 1,
  Export["withinLoop r" <> ToString[r] <> " Ca" <>
    ToString[1*^6 myCaNow] <> " C5 data.txt", tmpToFitNoise, "Table"];
  toExport = Table[{t, (myFitMono[t] /. fitResultMono)[[1]]},
    {t, cursorStart, cursorEnd, dtOfPlotsForExport}];
  Export["withinLoop r" <> ToString[r] <> " Ca" <> ToString[1*^6 myCaNow] <>
    " C5 fitMono.txt", toExport, "Table"];
  toExport = Table[{t, (myFitBi[t] /. fitResultBi)[[1]]},
    {t, cursorStart, cursorEnd, dtOfPlotsForExport}];
  Export["withinLoop r" <> ToString[r] <> " Ca" <>
    ToString[1*^6 myCaNow] <> " C5 fitBi.txt", toExport, "Table"];
];
noiseN = noiseRepeats; (*fit parameter of last noisetrace*)
Print["Mono: chi2 = ", simParamNoiseC5[[2, noiseN]], " d = ",
  simParamNoiseC5[[2, noiseN]], " a = ", simParamNoiseC5[[4, noiseN]],
  " t = ", 1/simParamNoiseC5[[5, noiseN]]];
Print["Bi: ratio chi2Mono/chi2Bi = ", simParamNoiseC5[[6, noiseN]],
  " d = ", simParamNoiseC5[[7, noiseN]], " a = ",
  simParamNoiseC5[[8, noiseN]], " a1 = ", simParamNoiseC5[[9, noiseN]],
  " t1 = ", 1/simParamNoiseC5[[10, noiseN]],
  " t2 = ", 1/simParamNoiseC5[[11, noiseN]]];
(*average fit results*)
For[p = 1, p ≤ numberOfFitParamToBeSaved, p += 1,
  simParamMedianC5[[p, r]] =
    Median[simParamNoiseC5[[p, All]] /. NaN → Sequence[]];
  simParamQuantile1C5[[p, r]] = Quantile[
    simParamNoiseC5[[p, All]] /. NaN → Sequence[], myQuantile1];
  simParamQuantile2C5[[p, r]] = Quantile[
    simParamNoiseC5[[p, All]] /. NaN → Sequence[], myQuantile2];
];

(*if tau1 merge > 10 ms, use long trace for fitting*)
If[(1/simParamMedianC5[[15, r]]) > 0.01,
  Print["Long trace was used for fitting."];
  For[noiseN = 1, noiseN ≤ noiseRepeats, noiseN += 1,

```

```

tmpToFitNoiseLong = Transpose[{tmpToFitLong[[All, 1]],
  # + RandomVariate[NormalDistribution[0, myNoiseLong]] & /@
  tmpToFitLong[[All, 2]]}];
(*fit mono-exp to Long trace*)
fitResultsTMP = NonlinearModelFit[tmpToFitNoiseLong, myFitMono[x1],
  {{delayMono, delayGuess}, {ampMono, ampGuess}, {tau1Mono,
    caAdjustedTau1Guess}}, x1, MaxIterations → myMaxIterations];
fitResultLongMono = fitResultsTMP[{"BestFitParameters"}];
simParamNoiseC5[[2, noiseN]] =
  fitResultsTMP["ANOVATableSumsOfSquares"][[2]];
(*Print[fitResultsTMP["ANOVATableSumsOfSquares"]];*)
simParamNoiseC5[[3, noiseN]] = (delayMono /. fitResultLongMono)[[1]];
simParamNoiseC5[[4, noiseN]] = ((ampMono /. fitResultLongMono)[[1]]);
simParamNoiseC5[[5, noiseN]] = (1 / (tau1Mono /. fitResultLongMono)[[1]]);
(*fit bi-exp*)
fitResultsTMP =
  NonlinearModelFit[tmpToFitNoiseLong, myFitBi[x1], {{delay, delayGuess},
    {amp, ampGuess}, {amp1, amp1Guess}, {tau1, caAdjustedTau1Guess},
    {tau2, caAdjustedTau2Guess}}, x1, MaxIterations → myMaxIterations];
fitResultLongBi = fitResultsTMP[{"BestFitParameters"}];
simParamNoiseC5[[6, noiseN]] = simParamNoiseC5[[2, noiseN]] /
  fitResultsTMP["ANOVATableSumsOfSquares"][[2]];
simParamNoiseC5[[7, noiseN]] = (delay /. fitResultLongBi)[[1]];
simParamNoiseC5[[8, noiseN]] = ((amp /. fitResultLongBi)[[1]]);
simParamNoiseC5[[9, noiseN]] = ((amp amp1 /. fitResultLongBi)[[1]]);
(*relative amp1*)
simParamNoiseC5[[10, noiseN]] = (1 / (tau1 /. fitResultLongBi)[[1]]);
simParamNoiseC5[[11, noiseN]] = (1 / (tau2 /. fitResultLongBi)[[1]]);
(*merge*)
If[
  (*to use the bi-exp fit,
  the following criteria should be fulfilled:*)
  (*chi2 should improve(=decrease) by >10%*)
  (simParamNoiseC5[[6, noiseN]] > 1.04)
  &&
  (*tau1 and tau2 of bi fit should be factor of >3 different*)
  ((simParamNoiseC5[[11, noiseN]] / simParamNoiseC5[[10, noiseN]]) < 3.)
  &&
  (*relative amplitude of 1st component should be > 5% *)
  (((amp1 /. fitResultLongBi)[[1]] > 0.05)
  &&
  (*relative amplitude of 1st component should be < 95% *)
  (((amp1 /. fitResultLongBi)[[1]] < 0.95)
  ,
  (*take bi*)
  Print["take bi"];

```



```

simParamNoiseC5[[12, noiseN]] = simParamNoiseC5[[7, noiseN]];
(*delay*)
simParamNoiseC5[[13, noiseN]] = simParamNoiseC5[[8, noiseN]];
(*amp*)
simParamNoiseC5[[14, noiseN]] = simParamNoiseC5[[9, noiseN]];
(*amp1*)
simParamNoiseC5[[15, noiseN]] = simParamNoiseC5[[10, noiseN]];
(*tau1*)
simParamNoiseC5[[16, noiseN]] = simParamNoiseC5[[11, noiseN]]; (*tau2*)
,
(*take mono*)
Print["take mono"];
simParamNoiseC5[[12, noiseN]] = simParamNoiseC5[[3, noiseN]];
(*delay*)
simParamNoiseC5[[13, noiseN]] = simParamNoiseC5[[4, noiseN]];
(*amp*)
simParamNoiseC5[[14, noiseN]] = NaN; (*amp1*)
simParamNoiseC5[[15, noiseN]] = simParamNoiseC5[[5, noiseN]];
(*tau1*)
simParamNoiseC5[[16, noiseN]] = NaN; (*tau2*)
];
];
(*plot last example of the noise loop*)
gr1 = ListPlot[tmpToFitNoiseLong, PlotRange → All, PlotStyle → Black];
gr2 = Plot[myFitMono[x1] /. fitResultLongMono, {x1, cursorStart,
  cursorEndLong}, PlotRange → All, PlotStyle → {Blue, Dashed}];
gr3 = Plot[myFitBi[x1] /. fitResultLongBi, {x1, cursorStart, cursorEndLong},
  PlotRange → All, PlotStyle → {Green, Dashed}];
Show[gr1, gr2, gr3, PlotRange → All] // Print;
If[exportYes == 1,
  Export["withinLoop r" <> ToString[r] <> " Ca" <> ToString[1*^6 myCaNow] <>
    " C5 dataLong.txt", tmpToFitNoiseLong, "Table"];
  toExport = Table[{t, (myFitMono[t] /. fitResultLongMono)[[1]]},
    {t, cursorStart, cursorEndLong, dtOfPlotsForExport}];
  Export["withinLoop r" <> ToString[r] <> " Ca" <> ToString[1*^6 myCaNow] <>
    " C5 fitLongMono.txt", toExport, "Table"];
  toExport = Table[{t, (myFitBi[t] /. fitResultLongBi)[[1]]},
    {t, cursorStart, cursorEndLong, dtOfPlotsForExport}];
  Export["withinLoop r" <> ToString[r] <> " Ca" <> ToString[1*^6 myCaNow] <>
    " C5 fitLongBi.txt", toExport, "Table"];
];
noiseN = noiseRepeats; (*fit parameter of last noisetrace*)
Print["Mono: chi2 = ", simParamNoiseC5[[2, noiseN]], "      d = ",
  simParamNoiseC5[[3, noiseN]], "      a = ", simParamNoiseC5[[4, noiseN]],
  "      t = ", 1/simParamNoiseC5[[5, noiseN]]];
Print["Bi: ratio chi2Mono/chi2Bi = ", simParamNoiseC5[[6, noiseN]],

```

```

"      d = ", simParamNoiseC5[[7, noiseN]], "      a = ",
simParamNoiseC5[[8, noiseN]], "      a1 = ", simParamNoiseC5[[9, noiseN]],
"      t1 = ", 1/simParamNoiseC5[[10, noiseN]],
"      t2 = ", 1/simParamNoiseC5[[11, noiseN]]];
(*average fit results*)
For[p = 1, p ≤ numberOfFitParamToBeSaved, p += 1,
  simParamMedianC5[[p, r]] =
    Median[simParamNoiseC5[[p, All]] /. NaN → Sequence[]];
  simParamQuantile1C5[[p, r]] = Quantile[
    simParamNoiseC5[[p, All]] /. NaN → Sequence[], myQuantile1];
  simParamQuantile2C5[[p, r]] = Quantile[
    simParamNoiseC5[[p, All]] /. NaN → Sequence[], myQuantile2];
];
];

, (*else: signal is not large enough*)
For[p = 1, p ≤ numberOfFitParamToBeSaved, p += 1,
  simParamMedianC5[[p, r]] = {};
  simParamQuantile1C5[[p, r]] = {};
  simParamQuantile2C5[[p, r]] = {};
];
];

(*----- Fitting of data,
saving of results, and plotting-----*)
(*-----*)
(*-----*)
(*-----*)
(*-----*)
(*-----*)
(*-----*)
Print[
  "-----
  C10"];
(*check that signal is large enough relative to noise to obtain
useful fit results. If not, do not do fitting and set everything to {}*)
If[simParamNv[[5, r]] > signalToNoiseRatioC10 myNoiseC10, (*add noise
and do the fitting several times and then average the results*)
For[noiseN = 1, noiseN ≤ noiseRepeats, noiseN += 1,
  (*Print[noiseN];*)
  tmpToFitNoise = Transpose[{tmpToFitC10[[All, 1]],
    # + RandomVariate[NormalDistribution[0, myNoiseC10]] & /@
    tmpToFitC10[[All, 2]]}];
  (*fit mono-exp*)
  fitResultsTMP = NonlinearModelFit[tmpToFitNoise, myFitMono[x1],
    {{delayMono, delayGuess}, {ampMono, ampGuess}, {tau1Mono,

```

```

    caAdjustedTau1Guess}}, x1, MaxIterations → myMaxIterations];
fitResultMono = fitResultsTMP[{"BestFitParameters"}];
simParamNoiseC10[[1, noiseN]] = 0; (*not used anymore*)
simParamNoiseC10[[2, noiseN]] =
    fitResultsTMP["ANOVATableSumsOfSquares"][[2]];
(*Print[fitResultsTMP["ANOVATableSumsOfSquares"]];*)
simParamNoiseC10[[3, noiseN]] = (delayMono /. fitResultMono)[[1]];
simParamNoiseC10[[4, noiseN]] = ((ampMono /. fitResultMono)[[1]]);
simParamNoiseC10[[5, noiseN]] = (1 / (tau1Mono /. fitResultMono)[[1]]);
(*fit bi-exp*)
fitResultsTMP =
    NonlinearModelFit[tmpToFitNoise, myFitBi[x1], {{delay, delayGuess},
        {amp, ampGuess}, {amp1, amp1Guess}, {tau1, caAdjustedTau1Guess},
        {tau2, caAdjustedTau2Guess}}, x1, MaxIterations → myMaxIterations];
fitResultBi = fitResultsTMP[{"BestFitParameters"}];
simParamNoiseC10[[6, noiseN]] = simParamNoiseC10[[2, noiseN]] /
    fitResultsTMP["ANOVATableSumsOfSquares"][[2]];
simParamNoiseC10[[7, noiseN]] = (delay /. fitResultBi)[[1]];
simParamNoiseC10[[8, noiseN]] = ((amp /. fitResultBi)[[1]]);
simParamNoiseC10[[9, noiseN]] = ((amp amp1 /. fitResultBi)[[1]]);
(*relative amp1*)
simParamNoiseC10[[10, noiseN]] = (1 / (tau1 /. fitResultBi)[[1]]);
simParamNoiseC10[[11, noiseN]] = (1 / (tau2 /. fitResultBi)[[1]]);
(*merge*)
If[
    (*to use the bi-exp fit, the following criteria should be fulfilled:*)
    (*chi2 should improve(=decrease) by >4%*)
    (simParamNoiseC10[[6, noiseN]] > 1.04)
    &&
    (*tau1 and tau2 of bi fit should be factor of >3 different*)
    ((simParamNoiseC10[[11, noiseN]] / simParamNoiseC10[[10, noiseN]]) < 3.)
    &&
    (*relative amplitude of 1st component should be > 5% *)
    (((amp1 /. fitResultBi)[[1]] > 0.05)
    &&
    (*relative amplitude of 1st component should be < 95% *)
    (((amp1 /. fitResultBi)[[1]] < 0.95)
    ,
    (*take bi*)
    Print["take bi"];
    simParamNoiseC10[[12, noiseN]] = simParamNoiseC10[[7, noiseN]];
    (*delay*)
    simParamNoiseC10[[13, noiseN]] = simParamNoiseC10[[8, noiseN]];
    (*amp*)
    simParamNoiseC10[[14, noiseN]] = simParamNoiseC10[[9, noiseN]];
    (*amp1*)

```

```

simParamNoiseC10[[15, noiseN]] = simParamNoiseC10[[10, noiseN]];
(*tau1*)
simParamNoiseC10[[16, noiseN]] = simParamNoiseC10[[11, noiseN]];(*tau2*)
,
(*take mono*)
Print["take mono"];
simParamNoiseC10[[12, noiseN]] = simParamNoiseC10[[3, noiseN]];
(*delay*)
simParamNoiseC10[[13, noiseN]] = simParamNoiseC10[[4, noiseN]];
(*amp*)
simParamNoiseC10[[14, noiseN]] = NaN; (*amp1*)
simParamNoiseC10[[15, noiseN]] = simParamNoiseC10[[5, noiseN]];
(*tau1*)
simParamNoiseC10[[16, noiseN]] = NaN;(*tau2*)
];
];
(*plot last example of the noise loop*)
gr1 = ListPlot[tmpToFitNoise, PlotRange → All, PlotStyle → Black];
gr2 = Plot[myFitMono[x1] /. fitResultMono,
  {x1, cursorStart, cursorEnd}, PlotRange → All, PlotStyle → {Blue, Dashed}];
gr3 = Plot[myFitBi[x1] /. fitResultBi, {x1, cursorStart, cursorEnd},
  PlotRange → All, PlotStyle → {Green, Dashed}];
Show[gr1, gr2, gr3, PlotRange → All] // Print;
If[exportYes == 1,
  Export["withinLoop r" <> ToString[r] <> " Ca" <>
    ToString[1*^6 myCaNow] <> " C10 data.txt", tmpToFitNoise, "Table"];
  toExport = Table[{t, (myFitMono[t] /. fitResultMono)[[1]]},
    {t, cursorStart, cursorEnd, dtOfPlotsForExport}];
  Export["withinLoop r" <> ToString[r] <> " Ca" <> ToString[1*^6 myCaNow] <>
    " C10 fitMono.txt", toExport, "Table"];
  toExport = Table[{t, (myFitBi[t] /. fitResultBi)[[1]]},
    {t, cursorStart, cursorEnd, dtOfPlotsForExport}];
  Export["withinLoop r" <> ToString[r] <> " Ca" <> ToString[1*^6 myCaNow] <>
    " C10 fitBi.txt", toExport, "Table"];
];
noiseN = noiseRepeats; (*fit parameter of last noisetrace*)
Print["Mono: chi2 = ", simParamNoiseC10[[2, noiseN]], " d = ",
  simParamNoiseC10[[2, noiseN]], " a = ", simParamNoiseC10[[4, noiseN]],
  " t = ", 1/simParamNoiseC10[[5, noiseN]]];
Print["Bi: ratio chi2Mono/chi2Bi = ", simParamNoiseC10[[6, noiseN]],
  " d = ", simParamNoiseC10[[7, noiseN]], " a = ",
  simParamNoiseC10[[8, noiseN]], " a1 = ", simParamNoiseC10[[9, noiseN]],
  " t1 = ", 1/simParamNoiseC10[[10, noiseN]],
  " t2 = ", 1/simParamNoiseC10[[11, noiseN]]];
(*average fit results*)
For[p = 1, p ≤ numberOfFitParamToBeSaved, p += 1,

```

```

simParamMedianC10[[p, r]] =
  Median[simParamNoiseC10[[p, All]] /. NaN → Sequence[]];
simParamQuantile1C10[[p, r]] = Quantile[
  simParamNoiseC10[[p, All]] /. NaN → Sequence[], myQuantile1];
simParamQuantile2C10[[p, r]] = Quantile[
  simParamNoiseC10[[p, All]] /. NaN → Sequence[], myQuantile2];
];

(*if tau1 merge > 10 ms, use long trace for fitting*)
If[(1/simParamMedianC10[[15, r]]) > 0.01,
  Print["Long trace was used for fitting."];
  For[noiseN = 1, noiseN ≤ noiseRepeats, noiseN += 1,
    tmpToFitNoiseLong = Transpose[{tmpToFitLong[[All, 1]],
      # + RandomVariate[NormalDistribution[0, myNoiseLong]] & /@
        tmpToFitLong[[All, 2]]}];
    (*fit mono-exp to Long trace*)
    fitResultsTMP = NonlinearModelFit[tmpToFitNoiseLong, myFitMono[x1],
      {{delayMono, delayGuess}, {ampMono, ampGuess}, {tau1Mono,
        caAdjustedTau1Guess}}, x1, MaxIterations → myMaxIterations];
    fitResultLongMono = fitResultsTMP[{"BestFitParameters"}];
    simParamNoiseC10[[2, noiseN]] =
      fitResultsTMP["ANOVATableSumsOfSquares"][[2]];
    (*Print[fitResultsTMP["ANOVATableSumsOfSquares"]];*)
    simParamNoiseC10[[3, noiseN]] = (delayMono /. fitResultLongMono)[[1]];
    simParamNoiseC10[[4, noiseN]] = ((ampMono /. fitResultLongMono)[[1]]);
    simParamNoiseC10[[5, noiseN]] = (1/(tau1Mono /. fitResultLongMono)[[1]]);
    (*fit bi-exp*)
    fitResultsTMP =
      NonlinearModelFit[tmpToFitNoiseLong, myFitBi[x1], {{delay, delayGuess},
        {amp, ampGuess}, {amp1, amp1Guess}, {tau1, caAdjustedTau1Guess},
        {tau2, caAdjustedTau2Guess}}, x1, MaxIterations → myMaxIterations];
    fitResultLongBi = fitResultsTMP[{"BestFitParameters"}];
    simParamNoiseC10[[6, noiseN]] = simParamNoiseC10[[2, noiseN]] /
      fitResultsTMP["ANOVATableSumsOfSquares"][[2]];
    simParamNoiseC10[[7, noiseN]] = (delay /. fitResultLongBi)[[1]];
    simParamNoiseC10[[8, noiseN]] = ((amp /. fitResultLongBi)[[1]]);
    simParamNoiseC10[[9, noiseN]] = ((amp amp1 /. fitResultLongBi)[[1]]);
    (*relative amp1*)
    simParamNoiseC10[[10, noiseN]] = (1/(tau1 /. fitResultLongBi)[[1]]);
    simParamNoiseC10[[11, noiseN]] = (1/(tau2 /. fitResultLongBi)[[1]]);
    (*merge*)
    If[
      (*to use the bi-exp fit,
        the following criteria should be fullfilled:*)
      (*chi2 should improve(=decrease) by >4%*)
      (simParamNoiseC10[[6, noiseN]] > 1.04)
    ]
  ]

```

```

    &&
    (*tau1 and tau2 of bi fit should be factor of >3 different*)
    ((simParamNoiseC10[[11, noiseN]]/simParamNoiseC10[[10, noiseN]]) < 3.)
    &&
    (*relative amplitude of 1st component should be > 5% *)
    (((amp1 /. fitResultLongBi))[[1]] > 0.05)
    &&
    (*relative amplitude of 1st component should be < 95% *)
    (((amp1 /. fitResultLongBi))[[1]] < 0.95)
  ,
  (*take bi*)
  Print["take bi"];
  simParamNoiseC10[[12, noiseN]] = simParamNoiseC10[[7, noiseN]];
  (*delay*)
  simParamNoiseC10[[13, noiseN]] = simParamNoiseC10[[8, noiseN]];
  (*amp*)
  simParamNoiseC10[[14, noiseN]] = simParamNoiseC10[[9, noiseN]];
  (*amp1*)
  simParamNoiseC10[[15, noiseN]] = simParamNoiseC10[[10, noiseN]];
  (*tau1*)
  simParamNoiseC10[[16, noiseN]] = simParamNoiseC10[[11, noiseN]];(*tau2*)
  ,
  (*take mono*)
  Print["take mono"];
  simParamNoiseC10[[12, noiseN]] = simParamNoiseC10[[3, noiseN]];
  (*delay*)
  simParamNoiseC10[[13, noiseN]] = simParamNoiseC10[[4, noiseN]];
  (*amp*)
  simParamNoiseC10[[14, noiseN]] = NaN; (*amp1*)
  simParamNoiseC10[[15, noiseN]] = simParamNoiseC10[[5, noiseN]];
  (*tau1*)
  simParamNoiseC10[[16, noiseN]] = NaN;(*tau2*)
];
];
(*plot last example of the noise loop*)
gr1 = ListPlot[tmpToFitNoiseLong, PlotRange -> All, PlotStyle -> Black];
gr2 = Plot[myFitMono[x1] /. fitResultLongMono, {x1, cursorStart,
  cursorEndLong}, PlotRange -> All, PlotStyle -> {Blue, Dashed}];
gr3 = Plot[myFitBi[x1] /. fitResultLongBi, {x1, cursorStart, cursorEndLong},
  PlotRange -> All, PlotStyle -> {Green, Dashed}];
Show[gr1, gr2, gr3, PlotRange -> All] // Print;
If[exportYes == 1,
  Export["withinLoop r" <> ToString[r] <> " Ca" <> ToString[1*^6 myCaNow] <>
    " C10 dataLong.txt", tmpToFitNoiseLong, "Table"];
  toExport = Table[{t, (myFitMono[t] /. fitResultLongMono)[[1]]},
    {t, cursorStart, cursorEndLong, dtOfPlotsForExport}];
  Export["withinLoop r" <> ToString[r] <> " Ca" <> ToString[1*^6 myCaNow] <>

```

```

    " C10 fitLongMono.txt", toExport, "Table"];
toExport = Table[{t, (myFitBi[t] /. fitResultLongBi)[[1]]},
  {t, cursorStart, cursorEndLong, dtOfPlotsForExport}];
Export["withinLoop r" <> ToString[r] <> " Ca" <> ToString[1*^6 myCaNow] <>
  " C10 fitLongBi.txt", toExport, "Table"];

];
noiseN = noiseRepeats; (*fit parameter of last noisetrace*)
Print["Mono: chi2 = ", simParamNoiseC10[[2, noiseN]], "      d = ",
  simParamNoiseC10[[3, noiseN]], "      a = ", simParamNoiseC10[[4, noiseN]],
  "      t = ", 1/simParamNoiseC10[[5, noiseN]]];
Print["Bi: ratio chi2Mono/chi2Bi = ", simParamNoiseC10[[6, noiseN]],
  "      d = ", simParamNoiseC10[[7, noiseN]], "      a = ",
  simParamNoiseC10[[8, noiseN]], "      a1 = ", simParamNoiseC10[[9, noiseN]],
  "      t1 = ", 1/simParamNoiseC10[[10, noiseN]],
  "      t2 = ", 1/simParamNoiseC10[[11, noiseN]]];
(*average fit results*)
For[p = 1, p ≤ numberOfFitParamToBeSaved, p += 1,
  simParamMedianC10[[p, r]] =
    Median[simParamNoiseC10[[p, All]] /. NaN → Sequence[]];
  simParamQuantile1C10[[p, r]] = Quantile[
    simParamNoiseC10[[p, All]] /. NaN → Sequence[], myQuantile1];
  simParamQuantile2C10[[p, r]] = Quantile[
    simParamNoiseC10[[p, All]] /. NaN → Sequence[], myQuantile2];
];
];

, (*else: signal is not large enough*)
For[p = 1, p ≤ numberOfFitParamToBeSaved, p += 1,
  simParamMedianC10[[p, r]] = {};
  simParamQuantile1C10[[p, r]] = {};
  simParamQuantile2C10[[p, r]] = {};
];
];

(*----- Fitting of data,
saving of results, and plotting-----*)
(*-----*)
(*-----*)
(*-----*)
(*-----*)
Print[
  "-----
  D"];

```

```

(*check that signal is large enough relative to noise to obtain
useful fit results. If not, do not do fitting and set everything to {}*)
If[simParamNv[[5, r]] > signalToNoiseRatioD myNoiseD, (*add noise
several times and do the fitting and then average the results*)
For[noiseN = 1, noiseN ≤ noiseRepeats, noiseN += 1,
(*Print[noiseN];*)
tmpToFitNoise = Transpose[{tmpToFitD[[All, 1]],
#+ RandomVariate[NormalDistribution[0, myNoiseD]] & /@
tmpToFitD[[All, 2]]}];
(*fit mono-exp*)
fitResultsTMP = NonlinearModelFit[tmpToFitNoise, myFitMono[x1],
{{delayMono, delayGuess}, {ampMono, ampGuess}, {tau1Mono,
caAdjustedTau1Guess}}, x1, MaxIterations → myMaxIterations];
fitResultMono = fitResultsTMP[{"BestFitParameters"}];
simParamNoiseD[[1, noiseN]] = 0; (*not used anymore*)
simParamNoiseD[[2, noiseN]] =
fitResultsTMP["ANOVATableSumsOfSquares"][[2]];
(*Print[fitResultsTMP["ANOVATableSumsOfSquares"]];*)
simParamNoiseD[[3, noiseN]] = (delayMono /. fitResultMono)[[1]];
simParamNoiseD[[4, noiseN]] = ((ampMono /. fitResultMono)[[1]]);
simParamNoiseD[[5, noiseN]] = (1 / (tau1Mono /. fitResultMono)[[1]]);
(*fit bi-exp*)
fitResultsTMP =
NonlinearModelFit[tmpToFitNoise, myFitBi[x1], {{delay, delayGuess},
{amp, ampGuess}, {amp1, amp1Guess}, {tau1, caAdjustedTau1Guess},
{tau2, caAdjustedTau2Guess}}, x1, MaxIterations → myMaxIterations];
fitResultBi = fitResultsTMP[{"BestFitParameters"}];
simParamNoiseD[[6, noiseN]] = simParamNoiseD[[2, noiseN]] /
fitResultsTMP["ANOVATableSumsOfSquares"][[2]];
simParamNoiseD[[7, noiseN]] = (delay /. fitResultBi)[[1]];
simParamNoiseD[[8, noiseN]] = ((amp /. fitResultBi)[[1]]);
simParamNoiseD[[9, noiseN]] = ((amp amp1 /. fitResultBi)[[1]]);
(*relative amp1*)
simParamNoiseD[[10, noiseN]] = (1 / (tau1 /. fitResultBi)[[1]]);
simParamNoiseD[[11, noiseN]] = (1 / (tau2 /. fitResultBi)[[1]]);
(*merge*)
If[
(*to use the bi-exp fit, the following criteria should be fulfilled:*)
(*chi2 should improve(=decrease) by >4%*)
(simParamNoiseD[[6, noiseN]] > 1.04)
&&
(*tau1 and tau2 of bi fit should be factor of >3 different*)
((simParamNoiseD[[11, noiseN]] / simParamNoiseD[[10, noiseN]]) < 3.)
&&
(*relative amplitude of 1st component should be > 5% *)
(((amp1 /. fitResultBi)[[1]] > 0.05)

```



```

    &&
    (*relative amplitude of 1st component should be < 95% *)
    ((( amp1 /. fitResultBi)) [[1]] < 0.95)
  ,
  (*take bi*)
  Print["take bi"];
  simParamNoiseD[[12, noiseN]] = simParamNoiseD[[7, noiseN]];
  (*delay*)
  simParamNoiseD[[13, noiseN]] = simParamNoiseD[[8, noiseN]];
  (*amp*)
  simParamNoiseD[[14, noiseN]] = simParamNoiseD[[9, noiseN]];
  (*amp1*)
  simParamNoiseD[[15, noiseN]] = simParamNoiseD[[10, noiseN]];
  (*tau1*)
  simParamNoiseD[[16, noiseN]] = simParamNoiseD[[11, noiseN]]; (*tau2*)
  ,
  (*take mono*)
  Print["take mono"];
  simParamNoiseD[[12, noiseN]] = simParamNoiseD[[3, noiseN]];
  (*delay*)
  simParamNoiseD[[13, noiseN]] = simParamNoiseD[[4, noiseN]];
  (*amp*)
  simParamNoiseD[[14, noiseN]] = NaN; (*amp1*)
  simParamNoiseD[[15, noiseN]] = simParamNoiseD[[5, noiseN]];
  (*tau1*)
  simParamNoiseD[[16, noiseN]] = NaN; (*tau2*)
];
];
(*plot last example of the noise loop*)
gr1 = ListPlot[tmpToFitNoise, PlotRange → All, PlotStyle → Black];
gr2 = Plot[myFitMono[x1] /. fitResultMono,
  {x1, cursorStart, cursorEnd}, PlotRange → All, PlotStyle → {Blue, Dashed}];
gr3 = Plot[myFitBi[x1] /. fitResultBi, {x1, cursorStart, cursorEnd},
  PlotRange → All, PlotStyle → {Green, Dashed}];
Show[gr1, gr2, gr3, PlotRange → All] // Print;
If[exportYes == 1,
  Export["withinLoop r" <> ToString[r] <> " Ca" <>
    ToString[1*^6 myCaNow] <> " D data.txt", tmpToFitNoise, "Table"];
  toExport = Table[{t, (myFitMono[t] /. fitResultMono) [[1]]},
    {t, cursorStart, cursorEnd, dtOfPlotsForExport}];
  Export["withinLoop r" <> ToString[r] <> " Ca" <> ToString[1*^6 myCaNow] <>
    " D fitMono.txt", toExport, "Table"];
  toExport = Table[{t, (myFitBi[t] /. fitResultBi) [[1]]},
    {t, cursorStart, cursorEnd, dtOfPlotsForExport}];
  Export["withinLoop r" <> ToString[r] <> " Ca" <>
    ToString[1*^6 myCaNow] <> " D fitBi.txt", toExport, "Table"];
];

```

```

noiseN = noiseRepeats; (*fit parameter of last noisetrace*)
Print["Mono: chi2 = ", simParamNoiseD[[2, noiseN]],
      "      d = ", simParamNoiseD[[2, noiseN]], "      a = ",
      simParamNoiseD[[4, noiseN]], "      t = ", 1/simParamNoiseD[[5, noiseN]]];
Print["Bi: ratio chi2Mono/chi2Bi = ", simParamNoiseD[[6, noiseN]],
      "      d = ", simParamNoiseD[[7, noiseN]], "      a = ",
      simParamNoiseD[[8, noiseN]], "      a1 = ", simParamNoiseD[[9, noiseN]],
      "      t1 = ", 1/simParamNoiseD[[10, noiseN]],
      "      t2 = ", 1/simParamNoiseD[[11, noiseN]]];
(*average fit results*)
For[p = 1, p ≤ numberOfFitParamToBeSaved, p += 1,
  simParamMedianD[[p, r]] =
    Median[simParamNoiseD[[p, All]] /. NaN → Sequence[]];
  simParamQuantile1D[[p, r]] = Quantile[
    simParamNoiseD[[p, All]] /. NaN → Sequence[], myQuantile1];
  simParamQuantile2D[[p, r]] = Quantile[
    simParamNoiseD[[p, All]] /. NaN → Sequence[], myQuantile2];
];

(*if tau1 merge > 10 ms, use long trace for fitting*)
If[(1/simParamMedianD[[15, r]]) > 0.01,
  Print["Long trace was used for fitting."];
  For[noiseN = 1, noiseN ≤ noiseRepeats, noiseN += 1,
    tmpToFitNoiseLong = Transpose[{tmpToFitLong[[All, 1]],
      # + RandomVariate[NormalDistribution[0, myNoiseLong]] & /@
      tmpToFitLong[[All, 2]]}];
    (*fit mono-exp to Long trace*)
    fitResultsTMP = NonlinearModelFit[tmpToFitNoiseLong, myFitMono[x1],
      {{delayMono, delayGuess}, {ampMono, ampGuess}, {tau1Mono,
        caAdjustedTau1Guess}}, x1, MaxIterations → myMaxIterations];
    fitResultLongMono = fitResultsTMP[{"BestFitParameters"}];
    simParamNoiseD[[2, noiseN]] =
      fitResultsTMP["ANOVATableSumsOfSquares"][[2]];
    (*Print[fitResultsTMP["ANOVATableSumsOfSquares"]];*)
    simParamNoiseD[[3, noiseN]] = (delayMono /. fitResultLongMono)[[1]];
    simParamNoiseD[[4, noiseN]] = (ampMono /. fitResultLongMono)[[1]];
    simParamNoiseD[[5, noiseN]] = (1/(tau1Mono /. fitResultLongMono))[1];
    (*fit bi-exp*)
    fitResultsTMP =
      NonlinearModelFit[tmpToFitNoiseLong, myFitBi[x1], {{delay, delayGuess},
        {amp, ampGuess}, {amp1, amp1Guess}, {tau1, caAdjustedTau1Guess},
        {tau2, caAdjustedTau2Guess}}, x1, MaxIterations → myMaxIterations];
    fitResultLongBi = fitResultsTMP[{"BestFitParameters"}];
    simParamNoiseD[[6, noiseN]] = simParamNoiseD[[2, noiseN]] /
      fitResultsTMP["ANOVATableSumsOfSquares"][[2]];
    simParamNoiseD[[7, noiseN]] = (delay /. fitResultLongBi)[[1]];

```

```

simParamNoiseD[[8, noiseN]] = ((amp /. fitResultLongBi))[[1]];
simParamNoiseD[[9, noiseN]] = ((amp amp1 /. fitResultLongBi))[[1]];
(*relative amp1*)
simParamNoiseD[[10, noiseN]] = (1/(tau1 /. fitResultLongBi))[[1]];
simParamNoiseD[[11, noiseN]] = (1/(tau2 /. fitResultLongBi))[[1]];
(*merge*)
If[
  (*to use the bi-exp fit,
  the following criteria should be fulfilled:*)
  (*chi2 should improve(=decrease) by >4%*)
  (simParamNoiseD[[6, noiseN]] > 1.04)
  &&
  (*tau1 and tau2 of bi fit should be factor of >3 different*)
  ((simParamNoiseD[[11, noiseN]]/simParamNoiseD[[10, noiseN]]) < 3.)
  &&
  (*relative amplitude of 1st component should be > 5% *)
  (((amp1 /. fitResultLongBi))[[1]] > 0.05)
  &&
  (*relative amplitude of 1st component should be < 95% *)
  (((amp1 /. fitResultLongBi))[[1]] < 0.95)
  ,
  (*take bi*)
  Print["take bi"];
  simParamNoiseD[[12, noiseN]] = simParamNoiseD[[7, noiseN]];
  (*delay*)
  simParamNoiseD[[13, noiseN]] = simParamNoiseD[[8, noiseN]];
  (*amp*)
  simParamNoiseD[[14, noiseN]] = simParamNoiseD[[9, noiseN]];
  (*amp1*)
  simParamNoiseD[[15, noiseN]] = simParamNoiseD[[10, noiseN]];
  (*tau1*)
  simParamNoiseD[[16, noiseN]] = simParamNoiseD[[11, noiseN]]; (*tau2*)
  ,
  (*take mono*)
  Print["take mono"];
  simParamNoiseD[[12, noiseN]] = simParamNoiseD[[3, noiseN]];
  (*delay*)
  simParamNoiseD[[13, noiseN]] = simParamNoiseD[[4, noiseN]];
  (*amp*)
  simParamNoiseD[[14, noiseN]] = NaN; (*amp1*)
  simParamNoiseD[[15, noiseN]] = simParamNoiseD[[5, noiseN]];
  (*tau1*)
  simParamNoiseD[[16, noiseN]] = NaN; (*tau2*)
];
];
(*plot last example of the noise loop*)
gr1 = ListPlot[tmpToFitNoiseLong, PlotRange -> All, PlotStyle -> Black];

```

```



gr2 = Plot[myFitMono[x1] /. fitResultLongMono, {x1, cursorStart,
  cursorEndLong}, PlotRange → All, PlotStyle → {Blue, Dashed}];
gr3 = Plot[myFitBi[x1] /. fitResultLongBi, {x1, cursorStart, cursorEndLong},
  PlotRange → All, PlotStyle → {Green, Dashed}];
Show[gr1, gr2, gr3, PlotRange → All] // Print;
If[exportYes == 1,
  Export["withinLoop r" <> ToString[r] <> " Ca" <> ToString[1*^6 myCaNow] <>
    " D dataLong.txt", tmpToFitNoiseLong, "Table"];
  toExport = Table[{t, (myFitMono[t] /. fitResultLongMono)[[1]]},
    {t, cursorStart, cursorEndLong, dtOfPlotsForExport}];
  Export["withinLoop r" <> ToString[r] <> " Ca" <> ToString[1*^6 myCaNow] <>
    " D fitLongMono.txt", toExport, "Table"];
  toExport = Table[{t, (myFitBi[t] /. fitResultLongBi)[[1]]},
    {t, cursorStart, cursorEndLong, dtOfPlotsForExport}];
  Export["withinLoop r" <> ToString[r] <> " Ca" <> ToString[1*^6 myCaNow] <>
    " D fitLongBi.txt", toExport, "Table"];

];
noiseN = noiseRepeats; (*fit parameter of last noisetrace*)
Print["Mono: chi2 = ", simParamNoiseD[[2, noiseN]],
  "      d = ", simParamNoiseD[[3, noiseN]], "      a = ",
  simParamNoiseD[[4, noiseN]], "      t = ", 1/simParamNoiseD[[5, noiseN]]];
Print["Bi: ratio chi2Mono/chi2Bi = ", simParamNoiseD[[6, noiseN]],
  "      d = ", simParamNoiseD[[7, noiseN]], "      a = ",
  simParamNoiseD[[8, noiseN]], "      a1 = ", simParamNoiseD[[9, noiseN]],
  "      t1 = ", 1/simParamNoiseD[[10, noiseN]],
  "      t2 = ", 1/simParamNoiseD[[11, noiseN]]];
(*average fit results*)
For[p = 1, p ≤ numberOfFitParamToBeSaved, p += 1,
  simParamMedianD[[p, r]] =
    Median[simParamNoiseD[[p, All]] /. NaN → Sequence[]];
  simParamQuantile1D[[p, r]] = Quantile[
    simParamNoiseD[[p, All]] /. NaN → Sequence[], myQuantile1];
  simParamQuantile2D[[p, r]] = Quantile[
    simParamNoiseD[[p, All]] /. NaN → Sequence[], myQuantile2];
];
];
, (*else: signal is not large enough*)
For[p = 1, p ≤ numberOfFitParamToBeSaved, p += 1,
  simParamMedianD[[p, r]] = {};
  simParamQuantile1D[[p, r]] = {};
  simParamQuantile2D[[p, r]] = {};
];
];
];
];

```

Ca = 0.703073

uM





C5

C10

D

Ca = 4.79194

uM



C5

NonlinearModelFit: Failed to converge to the requested accuracy or precision within 100 iterations.

take mono


NonlinearModelFit: Failed to converge to the requested accuracy or precision within 100 iterations.

take mono

NonlinearModelFit: Failed to converge to the requested accuracy or precision within 100 iterations.

General: Further output of NonlinearModelFit::cvmit will be suppressed during this calculation.

take mono



Mono: $\chi^2 = 2.96481$ $d = 2.96481$ $a = 1.26086$ $t = 0.0038824$

Bi: ratio $\chi^2_{\text{Mono}}/\chi^2_{\text{Bi}} = 1.00554$ $d = 0.000716352$ $a =$
 21.5738 $a1 = 0.736358$ $t1 = 0.00217229$ $t2 = 0.421949$


... **Quantile:** Argument {} should be a non-empty list.
 ... **Quantile:** Argument {} should be a non-empty list.
 ... **Quantile:** Argument {} should be a non-empty list.
 ... **General:** Further output of Quantile::empt will be suppressed during this calculation.

----- C10

take mono

take mono

take mono



Mono: chi2 = 7.08688 d = 7.08688 a = 1.17872 t = 0.00403296


Bi: ratio chi2Mono/chi2Bi = 0.999794 d = 0.0007 a =
1.44509 a1 = 1.12956 t1 = 0.00391193 t2 = 0.070724

----- D

take mono

take mono


take mono



Mono: chi2 = 0.158654 d = 0.158654 a = 1.49144 t = 0.00550646

Bi: ratio chi2Mono/chi2Bi = 1.01159 d = 0.000623127 a =
0.86273 a1 = 2.87366 t1 = 0.00768285 t2 = 0.0181125-----
----- Ca = 5.53376

uM -----




C5

take mono

take mono

take mono



Mono: $\chi^2 = 2.46192$ $d = 2.46192$ $a = 1.5634$ $t = 0.00420158$

Bi: ratio $\chi^2_{\text{Mono}}/\chi^2_{\text{Bi}} = 1.00006$ $d = 0.000641544$


$a = 4.70221$ $a1 = 1.44954$ $t1 = 0.0039355$ $t2 = 0.360279$

C10

take mono

take mono

take mono



Mono: $\chi^2 = 8.52092$ $d = 8.52092$ $a = 1.79507$ $t = 0.0052043$


Bi: ratio $\chi^2_{\text{Mono}}/\chi^2_{\text{Bi}} = 0.99677$ $d = 0.000541875$ $a =$
 1.82858 $a1 = 1.33796$ $t1 = 0.00416516$ $t2 = 0.00971541$

----- D

take mono

take mono

take mono





Mono: $\chi^2 = 0.150791$ $d = 0.150791$ $a = 1.52878$ $t = 0.00397755$

Bi: ratio $\chi^2_{\text{Mono}}/\chi^2_{\text{Bi}} = 1.00064$ $d = 0.000535539$ $a =$
 1.481 $a1 = 1.94351$ $t1 = 0.00439514$ $t2 = 0.00743034$

----- Ca = 25.7412

uM -----




C5

```
take bi
```

```
take bi
```

```
take bi
```



```
Mono: chi2 = 2.32801      d = 2.32801      a = 2.47382      t = 0.00258321
```


```
Bi: ratio chi2Mono/chi2Bi = 1.35302      d = 0.000108022      a =  
23.5084      a1 = 1.45666      t1 = 0.000763861      t2 = 0.183317
```

C10

```
take bi
```

```
take bi
```

```
take bi
```



Mono: $\chi^2 = 6.84202$ $d = 6.84202$ $a = 2.32614$ $t = 0.00202853$


Bi: ratio $\chi^2_{\text{Mono}}/\chi^2_{\text{Bi}} = 1.0904$ $d = 0.00016458$ $a =$
 3.45458 $a1 = 1.50402$ $t1 = 0.000799165$ $t2 = 0.0147441$

----- D

take bi

take bi

take bi





Mono: $\chi^2 = 0.623135$ $d = 0.623135$ $a = 2.3009$ $t = 0.00192783$

Bi: ratio $\chi^2_{\text{Mono}}/\chi^2_{\text{Bi}} = 3.66281$ $d = 0.0000793084$ $a =$
 2.50245 $a1 = 1.10304$ $t1 = 0.000577102$ $t2 = 0.00413312$

----- Ca = 29.9583

uM -----




C5

```
take bi
```

```
take bi
```

```
take bi
```



```
Mono: chi2 = 2.81045      d = 2.81045      a = 2.29184      t = 0.00147492
```


```
Bi: ratio chi2Mono/chi2Bi = 1.25971      d = 0.000136624      a =  
20.7439      a1 = 1.69265      t1 = 0.000671877      t2 = 0.228367
```

C10

```
take mono
```

```
take bi
```

```
take bi
```



Mono: $\chi^2 = 10.4883$ $d = 10.4883$ $a = 2.2743$ $t = 0.00160435$


Bi: ratio $\chi^2_{\text{Mono}}/\chi^2_{\text{Bi}} = 1.09923$ $d = 0.0000747615$ $a =$
 3.29227 $a1 = 1.57775$ $t1 = 0.000681779$ $t2 = 0.0142666$

----- D

take bi

take bi

take bi





Mono: $\chi^2 = 0.91061$ $d = 0.91061$ $a = 2.30711$ $t = 0.00181864$

Bi: ratio $\chi^2_{\text{Mono}}/\chi^2_{\text{Bi}} = 4.79737$ $d = 0.0000900976$ $a =$
 2.46542 $a1 = 1.0158$ $t1 = 0.000302678$ $t2 = 0.00344934$

----- Ca = 74.0312

uM -----



C5

NonlinearModelFit: The step size in the search has become less than the tolerance prescribed by the PrecisionGoal option, but the gradient is larger than the tolerance specified by the AccuracyGoal option. There is a possibility that the method has stalled at a point that is not a local minimum.

General: Exp[-736.49] is too small to represent as a normalized machine number; precision may be lost.

General: Exp[-793.04] is too small to represent as a normalized machine number; precision may be lost.


General: Exp[-849.59] is too small to represent as a normalized machine number; precision may be lost.

General: Further output of General::munfl will be suppressed during this calculation.

take mono

take bi

take bi



Mono: chi2 = 4.01756 d = 4.01756 a = 2.37426 t = 0.00199883


```
Bi: ratio chi2Mono/chi2Bi = 1.58562      d = -8.24866 × 10-17      a =
2.75155      a1 = 1.11654      t1 = 0.000069318      t2 = 0.00526753
```

----- C10

take bi

take mono

take bi



```
Mono: chi2 = 8.52843      d = 8.52843      a = 2.29944      t = 0.00158323
```


```
Bi: ratio chi2Mono/chi2Bi = 1.07682      d = 0.000145139      a =
2.39724      a1 = 0.936027      t1 = 0.0000897784      t2 = 0.00259214
```

----- D

take bi

take bi

take bi



```
Mono: chi2 = 1.41395      d = 1.41395      a = 2.33924      t = 0.00155065
```

```
Bi: ratio chi2Mono/chi2Bi = 5.74032      d = 0.0000457876      a =
2.54393      a1 = 1.22128      t1 = 0.000236239      t2 = 0.00374787
```

Plots

```
In[ ]:= caFact = 1*^6;
```


```
In[ ]:= colorA = Green;
        colorB = Red;
        colorC = Blue;
```

release rate $1/\tau_1$ (merge of mono $1/\tau$ and bi $1/\tau_1$)

```
In[ ]:= simParam = 15;
```

C5

```
In[ ]:= gr1a = ListLogLogPlot[
  Transpose[{dataT1C5Ca, dataT1C5RelRate}], PlotStyle → {colorA}];
gr2a = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamMedianC5[[simParam, All]]}],
  PlotStyle → {colorA}, Joined → True, PlotRange → All];
gr3a = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamQuantile1C5[[simParam, All]]}],
  PlotStyle → {colorA}, Joined → True, PlotRange → All];
gr4a = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamQuantile2C5[[simParam, All]]}],
  PlotStyle → {colorA}, Joined → True, PlotRange → All];
Show[gr1a, gr2a, gr3a, gr4a, PlotRange → All]
If[exportYes == 1,
  Export["plot InvTau1 C5 data.txt",
    Transpose[{dataT1C5Ca, dataT1C5RelRate}], "Table"];
toExport = Transpose[{caFact simCaList, simParamQuantile1C5[[simParam, All]],
  simParamMedianC5[[simParam, All]], simParamQuantile2C5[[simParam, All]]}];
Export["plot InvTau1 C5 fit - quantiles and median.txt", toExport, "Table"];
];
```




C10

```

In[ ]:= gr1b = ListLogLogPlot[
  Transpose[{dataT1C10Ca, dataT1C10RelRate}], PlotStyle -> {colorB}];
gr2b = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamMedianC10[[simParam, All]]}],
  PlotStyle -> {colorB}, Joined -> True, PlotRange -> All];
gr3b = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamQuantile1C10[[simParam, All]]}],
  PlotStyle -> {colorB}, Joined -> True, PlotRange -> All];
gr4b = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamQuantile2C10[[simParam, All]]}],
  PlotStyle -> {colorB}, Joined -> True, PlotRange -> All];
Show[gr1b, gr2b, gr3b, gr4b, PlotRange -> All]
If[exportYes == 1,
  Export["plot InvTau1 C10 data.txt",
    Transpose[{dataT1C10Ca, dataT1C10RelRate}], "Table"];
toExport = Transpose[{caFact simCaList, simParamQuantile1C10[[simParam, All]],
  simParamMedianC10[[simParam, All]],
  simParamQuantile2C10[[simParam, All]]}];
Export["plot InvTau1 C10 fit - quantiles and median.txt", toExport, "Table"];
];

```




D

```


In[ ]:= gr1c =
  ListLogLogPlot[Transpose[{dataT1DCa, dataT1DRelRate}], PlotStyle → {colorC}];
gr2c = ListLogLogPlot[Transpose[
  {caFact simCaList, simParamMedianD[[simParam, All]]}],
  PlotStyle → {colorC}, Joined → True, PlotRange → All];
gr3c = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamQuantile1D[[simParam, All]]}],
  PlotStyle → {colorC}, Joined → True, PlotRange → All];
gr4c = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamQuantile2D[[simParam, All]]}],
  PlotStyle → {colorC}, Joined → True, PlotRange → All];
Show[gr1c, gr2c, gr3c, gr4c, PlotRange → All]
If[exportYes == 1,
  Export["plot InvTau1 D data.txt",
    Transpose[{dataT1DCa, dataT1DRelRate}], "Table"];
toExport = Transpose[{caFact simCaList, simParamQuantile1D[[simParam, All]],
  simParamMedianD[[simParam, All]], simParamQuantile2D[[simParam, All]]}];
Export["plot InvTau1 D fit - quantiles and median.txt", toExport, "Table"];
];

```



C5 and C10 and D

```
In[ ]:= Show[gr1a, gr2a, gr3a, gr4a, gr1b, gr2b, gr3b,
             gr4b, gr1c, gr2c, gr3c, gr4c, PlotRange -> {All, {0, 10}}]
```



```
In[ ]:= Show[gr1a, gr1b, gr1c, PlotRange -> {All, {2, 10}}];
```

delay (mono and bi merged)

```
In[ ]:= simParam = 12;
```

```
In[ ]:= Transpose[{caFact simCaList, simParamMedianC5[[simParam, All]]}] // TableForm
```

Out[]//TableForm=


| | |
|----------|--------------|
| 0.703073 | |
| 4.79194 | 0.00134142 |
| 5.53376 | 0.00049394 |
| 25.7412 | 0.000135972 |
| 29.9583 | 0.000177138 |
| 74.0312 | -0.000147837 |

C5

```

In[ ]:= gr1a =
  ListLogLogPlot[Transpose[{dataT1C5Ca, dataT1C5Delay}], PlotStyle → {colorA}];
gr2a = ListLogLogPlot[Transpose[
  {caFact simCaList, simParamMedianC5[[simParam, All]]}],
  PlotStyle → {colorA}, Joined → True, PlotRange → All];
gr3a = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamQuantile1C5[[simParam, All]]}],
  PlotStyle → {colorA}, Joined → True, PlotRange → All];
gr4a = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamQuantile2C5[[simParam, All]]}],
  PlotStyle → {colorA}, Joined → True, PlotRange → All];
Show[gr1a, gr2a, gr3a, gr4a, PlotRange → All]
If[exportYes == 1,
  Export["plot delay C5 data.txt",
    Transpose[{dataT1C5Ca, dataT1C5Delay}], "Table"];
toExport = Transpose[{caFact simCaList, simParamQuantile1C5[[simParam, All]],
  simParamMedianC5[[simParam, All]], simParamQuantile2C5[[simParam, All]]}];
Export["plot delay C5 fit - quantiles and median.txt", toExport, "Table"];
];

```




C10

```

In[ ]:= gr1b = ListLogLogPlot[
  Transpose[{dataT1C10Ca, dataT1C10Delay}], PlotStyle -> {colorB}];
gr2b = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamMedianC10[[simParam, All]]}],
  PlotStyle -> {colorB}, Joined -> True, PlotRange -> All];
gr3b = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamQuantile1C10[[simParam, All]]}],
  PlotStyle -> {colorB}, Joined -> True, PlotRange -> All];
gr4b = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamQuantile2C10[[simParam, All]]}],
  PlotStyle -> {colorB}, Joined -> True, PlotRange -> All];
Show[gr1b, gr2b, gr3b, gr4b, PlotRange -> All]
If[exportYes == 1,
  Export["plot delay C10 data.txt",
    Transpose[{dataT1C10Ca, dataT1C10Delay}], "Table"];
toExport = Transpose[{caFact simCaList, simParamQuantile1C10[[simParam, All]],
  simParamMedianC10[[simParam, All]],
  simParamQuantile2C10[[simParam, All]]}];
Export["plot delay C10 fit - quantiles and median.txt", toExport, "Table"];
];

```

Out[]:=




D

```


In[ ]:= gr1c =
  ListLogLogPlot[Transpose[{dataT1DCa, dataT1DDelay}], PlotStyle -> {colorC}];
gr2c = ListLogLogPlot[Transpose[
  {caFact simCaList, simParamMedianD[[simParam, All]]}],
  PlotStyle -> {colorC}, Joined -> True, PlotRange -> All];
gr3c = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamQuantile1D[[simParam, All]]}],
  PlotStyle -> {colorC}, Joined -> True, PlotRange -> All];
gr4c = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamQuantile2D[[simParam, All]]}],
  PlotStyle -> {colorC}, Joined -> True, PlotRange -> All];
Show[gr1c, gr2c, gr3c, gr4c, PlotRange -> All]
If[exportYes == 1,
  Export["plot delay D data.txt",
    Transpose[{dataT1DCa, dataT1DDelay}], "Table"];
toExport = Transpose[{caFact simCaList, simParamQuantile1D[[simParam, All]],
  simParamMedianD[[simParam, All]], simParamQuantile2D[[simParam, All]]}];
Export["plot delay D fit - quantiles and median.txt", toExport, "Table"];
];

```



C5 and C10 and D

```
In[ ]:= Show[gr1a, gr2a, gr3a, gr4a, gr1b, gr2b, gr3b,  
             gr4b, gr1c, gr2c, gr3c, gr4c, PlotRange -> {-10, -5}]
```



```
In[ ]:= Show[gr1a, gr1b, gr1c, PlotRange -> All];
```

amp (merge of mono amp and bi amp)


```
In[ ]:= simParam = 13;
```

C5

```

In[ ]:= gr1a = ListLogLogPlot[
  Transpose[{dataT1C5Ca, dataT1C5Amplitude}], PlotStyle → {colorA}];
gr2a = ListLogLogPlot[Transpose[{caFact simCaList,
  rrp simParamMedianC5[[simParam, All]]}],
  PlotStyle → {colorA}, Joined → True, PlotRange → All];
gr3a = ListLogLogPlot[Transpose[{caFact simCaList,
  rrp simParamQuantile1C5[[simParam, All]]}],
  PlotStyle → {colorA}, Joined → True, PlotRange → All];
gr4a = ListLogLogPlot[Transpose[{caFact simCaList,
  rrp simParamQuantile2C5[[simParam, All]]}],
  PlotStyle → {colorA}, Joined → True, PlotRange → All];
Show[gr1a, gr2a, gr3a, gr4a, PlotRange → All ]

```




C10

```

In[ ]:= gr1b = ListLogLogPlot[
  Transpose[{dataT1C10Ca, dataT1C10Amplitude}], PlotStyle -> {colorB}];
gr2b = ListLogLogPlot[Transpose[{caFact simCaList,
  rrp simParamMedianC10[[simParam, All]]}],
  PlotStyle -> {colorB}, Joined -> True, PlotRange -> All];
gr3b = ListLogLogPlot[Transpose[{caFact simCaList,
  rrp simParamQuantile1C10[[simParam, All]]}],
  PlotStyle -> {colorB}, Joined -> True, PlotRange -> All];
gr4b = ListLogLogPlot[Transpose[{caFact simCaList,
  rrp simParamQuantile2C10[[simParam, All]]}],
  PlotStyle -> {colorB}, Joined -> True, PlotRange -> All];
Show[gr1b, gr2b, gr3b, gr4b, PlotRange -> All ]

```




D

```

In[ ]:= gr1c = ListLogLogPlot[
  Transpose[{dataT1DCa, dataT1DAmplitude}], PlotStyle -> {colorC}];
gr2c = ListLogLogPlot[Transpose[{caFact simCaList,
  rrp simParamMedianD[[simParam, All]]}],
  PlotStyle -> {colorC}, Joined -> True, PlotRange -> All];
gr3c = ListLogLogPlot[Transpose[{caFact simCaList,
  rrp simParamQuantile1D[[simParam, All]]}],
  PlotStyle -> {colorC}, Joined -> True, PlotRange -> All];
gr4c = ListLogLogPlot[Transpose[{caFact simCaList,
  rrp simParamQuantile2D[[simParam, All]]}],
  PlotStyle -> {colorC}, Joined -> True, PlotRange -> All];
Show[gr1c, gr2c, gr3c, gr4c, PlotRange -> All ]

```




C5 and C10 and D

```

In[ ]:= Show[gr1a, gr2a, gr3a, gr4a, gr1b, gr2b, gr3b,
  gr4b, gr1c, gr2c, gr3c, gr4c, PlotRange -> {-1, 6} ]

```



release rate $1/\tau^2$ of bi fits (if bi is justified)

```

In[ ]:= simParam = 16;


```

C5

```

In[ ]:= gr1a = ListLogLogPlot[
  Transpose[{dataT2C5Ca, dataT2C5RelRate}], PlotStyle -> {colorA}];
gr2a = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamMedianC5[[simParam, All]]}],
  PlotStyle -> {colorA}, Joined -> True, PlotRange -> All];
gr3a = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamQuantile1C5[[simParam, All]]}],
  PlotStyle -> {colorA}, Joined -> True, PlotRange -> All];
gr4a = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamQuantile2C5[[simParam, All]]}],
  PlotStyle -> {colorA}, Joined -> True, PlotRange -> All];
Show[gr1a, gr2a, gr3a, gr4a, PlotRange -> All]
If[exportYes == 1,
  Export["plot InvTau2 C5 data.txt",
    Transpose[{dataT2C5Ca, dataT2C5RelRate}], "Table"];
toExport = Transpose[{caFact simCaList, simParamQuantile1C5[[simParam, All]],
  simParamMedianC5[[simParam, All]], simParamQuantile2C5[[simParam, All]]}];
Export["plot InvTau2 C5 fit - quantiles and median.txt", toExport, "Table"];
];

```




C10

```

In[ ]:= gr1b = ListLogLogPlot[
  Transpose[{dataT2C10Ca, dataT2C10RelRate}], PlotStyle -> {colorB}];
gr2b = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamMedianC10[[simParam, All]]}],
  PlotStyle -> {colorB}, Joined -> True, PlotRange -> All];
gr3b = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamQuantile1C10[[simParam, All]]}],
  PlotStyle -> {colorB}, Joined -> True, PlotRange -> All];
gr4b = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamQuantile2C10[[simParam, All]]}],
  PlotStyle -> {colorB}, Joined -> True, PlotRange -> All];
Show[gr1b, gr2b, gr3b, gr4b, PlotRange -> All]
If[exportYes == 1,
  Export["plot InvTau2 C10 data.txt",
    Transpose[{dataT2C10Ca, dataT2C10RelRate}], "Table"];
toExport = Transpose[{caFact simCaList, simParamQuantile1C10[[simParam, All]],
  simParamMedianC10[[simParam, All]],
  simParamQuantile2C10[[simParam, All]]}];
Export["plot InvTau2 C10 fit - quantiles and median.txt", toExport, "Table"];
];

```




D

```


In[ ]:= gr1c =
  ListLogLogPlot[Transpose[{dataT2DCa, dataT2DRelRate}], PlotStyle → {colorC}];
gr2c = ListLogLogPlot[Transpose[
  {caFact simCaList, simParamMedianD[[simParam, All]]}],
  PlotStyle → {colorC}, Joined → True, PlotRange → All];
gr3c = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamQuantile1D[[simParam, All]]}],
  PlotStyle → {colorC}, Joined → True, PlotRange → All];
gr4c = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamQuantile2D[[simParam, All]]}],
  PlotStyle → {colorC}, Joined → True, PlotRange → All];
Show[gr1c, gr2c, gr3c, gr4c, PlotRange → All]
If[exportYes == 1,
  Export["plot InvTau2 D data.txt",
    Transpose[{dataT2DCa, dataT2DRelRate}], "Table"];
toExport = Transpose[{caFact simCaList, simParamQuantile1D[[simParam, All]],
  simParamMedianD[[simParam, All]], simParamQuantile2D[[simParam, All]]}];
Export["plot InvTau2 D fit - quantiles and median.txt", toExport, "Table"];
];

```



C5 and C10 and D

```
In[ ]:= Show[gr1a, gr2a, gr3a, gr4a, gr1b, gr2b, gr3b,
             gr4b, gr1c, gr2c, gr3c, gr4c, PlotRange -> {All, {2, 10}}]
```



```
In[ ]:= Show[gr1a, gr1b, gr1c, PlotRange -> All];
```

amp1 of bi fits (if bi is justified)


```
In[ ]:= simParam = 14;
```

C5

```

In[ ]:= gr1a = ListLogLogPlot[
  Transpose[{dataT2C5Ca, dataT2C5Amplitude1}], PlotStyle -> {colorA}];
gr2a = ListLogLogPlot[Transpose[{caFact simCaList,
  rrp simParamMedianC5[[simParam, All]]}],
  PlotStyle -> {colorA}, Joined -> True, PlotRange -> All];
gr3a = ListLogLogPlot[Transpose[{caFact simCaList,
  rrp simParamQuantile1C5[[simParam, All]]}],
  PlotStyle -> {colorA}, Joined -> True, PlotRange -> All];
gr4a = ListLogLogPlot[Transpose[{caFact simCaList,
  rrp simParamQuantile2C5[[simParam, All]]}],
  PlotStyle -> {colorA}, Joined -> True, PlotRange -> All];
Show[gr1a, gr2a, gr3a, gr4a, PlotRange -> All ]

```




C10

```

In[ ]:= gr1b = ListLogLogPlot[
  Transpose[{dataT2C10Ca, dataT2C10Amplitude1}], PlotStyle -> {colorB}];
gr2b = ListLogLogPlot[Transpose[{caFact simCaList,
  rrp simParamMedianC10[[simParam, All]]}],
  PlotStyle -> {colorB}, Joined -> True, PlotRange -> All];
gr3b = ListLogLogPlot[Transpose[{caFact simCaList,
  rrp simParamQuantile1C10[[simParam, All]]}],
  PlotStyle -> {colorB}, Joined -> True, PlotRange -> All];
gr4b = ListLogLogPlot[Transpose[{caFact simCaList,
  rrp simParamQuantile2C10[[simParam, All]]}],
  PlotStyle -> {colorB}, Joined -> True, PlotRange -> All];
Show[gr1b, gr2b, gr3b, gr4b, PlotRange -> All ]

```




D

```

In[ ]:= gr1c = ListLogLogPlot[
  Transpose[{dataT2DCa, dataT2DAmplitude1}], PlotStyle -> {colorC}];
gr2c = ListLogLogPlot[Transpose[{caFact simCaList,
  rrp simParamMedianD[[simParam, All]]}],
  PlotStyle -> {colorC}, Joined -> True, PlotRange -> All];
gr3c = ListLogLogPlot[Transpose[{caFact simCaList,
  rrp simParamQuantile1D[[simParam, All]]}],
  PlotStyle -> {colorC}, Joined -> True, PlotRange -> All];
gr4c = ListLogLogPlot[Transpose[{caFact simCaList,
  rrp simParamQuantile2D[[simParam, All]]}],
  PlotStyle -> {colorC}, Joined -> True, PlotRange -> All];
Show[gr1c, gr2c, gr3c, gr4c, PlotRange -> All]

```




C5 and C10 and D

```

In[ ]:= Show[gr1a, gr2a, gr3a, gr4a, gr1b, gr2b,
  gr3b, gr4b, gr1c, gr2c, gr3c, gr4c, PlotRange -> All]
Show[gr1a, gr1b, gr1c, PlotRange -> All];

```




chi2 mono/bi ratio

```
In[ ]:= simParam = 6;
```

C5

```
In[ ]:= gr1a = ListLogLogPlot[
  Transpose[{dataT1C5Ca, dataT1C5ChiRatio}], PlotStyle → {colorA}];
gr2a = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamMedianC5[[simParam, All]]}],
  PlotStyle → {colorA}, Joined → True, PlotRange → All];
gr3a = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamQuantile1C5[[simParam, All]]}],
  PlotStyle → {colorA}, Joined → True, PlotRange → All];
gr4a = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamQuantile2C5[[simParam, All]]}],
  PlotStyle → {colorA}, Joined → True, PlotRange → All];
Show[gr1a, gr2a, gr3a, gr4a, PlotRange → {All, {-0.8, 5}} ]
If[exportYes == 1,
  Export["plot chi2Ratio C5 data.txt",
    Transpose[{dataT1C5Ca, dataT1C5ChiRatio}], "Table"];
toExport = Transpose[{caFact simCaList, simParamQuantile1C5[[simParam, All]],
  simParamMedianC5[[simParam, All]], simParamQuantile2C5[[simParam, All]]}];
Export["plot chi2Ratio C5 fit - quantiles and median.txt",
  toExport, "Table"];
];
```




C10

```

In[ ]:= gr1b = ListLogLogPlot[
  Transpose[{dataT1C10Ca, dataT1C10ChiRatio}], PlotStyle → {colorB}];
gr2b = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamMedianC10[[simParam, All]]}],
  PlotStyle → {colorB}, Joined → True, PlotRange → All];
gr3b = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamQuantile1C10[[simParam, All]]}],
  PlotStyle → {colorB}, Joined → True, PlotRange → All];
gr4b = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamQuantile2C10[[simParam, All]]}],
  PlotStyle → {colorB}, Joined → True, PlotRange → All];
Show[gr1b, gr2b, gr3b, gr4b, PlotRange → All]
If[exportYes == 1,
  Export["plot chi2Ratio C10 data.txt",
    Transpose[{dataT1C10Ca, dataT1C10ChiRatio}], "Table"];
toExport = Transpose[{caFact simCaList, simParamQuantile1C10[[simParam, All]],
  simParamMedianC10[[simParam, All]],
  simParamQuantile2C10[[simParam, All]]}];
Export["plot chi2Ratio C10 fit - quantiles and median.txt",
  toExport, "Table"];
];

```

Out[]:=




D

```


In[ ]:= gr1c =
  ListLogLogPlot[Transpose[{dataT1DCa, dataT1DChiRatio}], PlotStyle -> {colorC}];
gr2c = ListLogLogPlot[Transpose[
  {caFact simCaList, simParamMedianD[[simParam, All]]}],
  PlotStyle -> {colorC}, Joined -> True, PlotRange -> All];
gr3c = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamQuantile1D[[simParam, All]]}],
  PlotStyle -> {colorC}, Joined -> True, PlotRange -> All];
gr4c = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamQuantile2D[[simParam, All]]}],
  PlotStyle -> {colorC}, Joined -> True, PlotRange -> All];
Show[gr1c, gr2c, gr3c, gr4c, PlotRange -> All]
If[exportYes == 1,
  Export["plot chi2Ratio D data.txt",
    Transpose[{dataT1DCa, dataT1DChiRatio}], "Table"];
toExport = Transpose[{caFact simCaList, simParamQuantile1D[[simParam, All]],
  simParamMedianD[[simParam, All]], simParamQuantile2D[[simParam, All]]}];
Export["plot chi2Ratio D fit - quantiles and median.txt", toExport, "Table"];
];

```




C5 and C10 and D

```
In[ ]:= Show[gr1a, gr2a, gr3a, gr4a, gr1b, gr2b, gr3b,
  gr4b, gr1c, gr2c, gr3c, gr4c, PlotRange → {All, {-0.8, 5}}]
Show[gr1a, gr1b, gr1c, PlotRange → All];
```




Nv


```
In[ ]:= For[NvCount = 1, NvCount ≤ 7, NvCount += 1,
  Print[" time for Nv (ms) = ", 1000 * timeOfNv[NvCount]];
  gr1a = ListLogLogPlot[
    Transpose[{dataT1C5Ca, dataT1C5Nv[NvCount]}], PlotStyle → {colorA}];
  gr1b = ListLogLogPlot[Transpose[{dataT1C10Ca, dataT1C10Nv[NvCount]}],
    PlotStyle → {colorB}];
  gr1c = ListLogLogPlot[Transpose[{dataT1DCa, dataT1DNv[NvCount]}],
    PlotStyle → {colorC}];
  gr2 = ListLogLogPlot[Transpose[{caFact simCaList, rrp simParamNv[NvCount,
    All]}], PlotStyle → {Black}, Joined → True, PlotRange → All];
  Show[gr1a, gr1b, gr1c, gr2, PlotRange → {All, {-4, 5}}] // Print;
];
time for Nv (ms) = 0.1
```




```
time for Nv (ms) = 0.2
```




time for Nv (ms) = 1.




time for Nv (ms) = 5.




time for Nv (ms) = 10.



time for Nv (ms) = 100.



time for Nv (ms) = 400.



sustained release 10 to 100 ms


```

In[ ]:= ttt1 = Transpose[{dataT1C5Ca, (dataT1C5Nv[[6]] - dataT1C5Nv[[5]]) / 0.09}];
ttt2 = Transpose[{dataT1C10Ca, (dataT1C10Nv[[6]] - dataT1C10Nv[[5]]) / 0.09}];
ttt3 = Transpose[{dataT1DCa, (dataT1DNv[[6]] - dataT1DNv[[5]]) / 0.09}];
ttt4 = Transpose[
  {caFact simCaList, rrp (simParamNv[[6, All]] - simParamNv[[5, All]]) / 0.09}];

gr1a = ListLogLogPlot[ttt1, PlotStyle -> {colorA}];
gr1b = ListLogLogPlot[ttt2, PlotStyle -> {colorB}];
gr1c = ListLogLogPlot[ttt3, PlotStyle -> {colorC}];
gr2 = ListLogLogPlot[ttt4, PlotStyle -> {Black}, Joined -> True, PlotRange -> All];
Show[gr1a, gr1b, gr1c, gr2, PlotRange -> {All, {0, 7}}] // Print;

gr1a = ListLogLinearPlot[ttt1, PlotStyle -> {colorA}];
gr1b = ListLogLinearPlot[ttt2, PlotStyle -> {colorB}];
gr1c = ListLogLinearPlot[ttt3, PlotStyle -> {colorC}];
gr2 = ListLogLinearPlot[ttt4,
  PlotStyle -> {Black}, Joined -> True, PlotRange -> All];
Show[gr1a, gr1b, gr1c, gr2, PlotRange -> {All, All}] // Print;

```




```

In[ ]:= If[exportYes == 1,
  Export["plot sustained release Cm5 data.txt", ttt1, "Table"];
  Export["plot sustained release Cm10 data.txt", ttt2, "Table"];
  Export["plot sustained release D data.txt", ttt3, "Table"];
  Export["plot sustained release sim.txt", ttt4, "Table"]
];

```

Nv normalize to the value at 5 ms

```

In[ ]:= timeOfNv
  nromPos = 5;
  1000 * timeOfNv[[nromPos]]

```

```
Out[ ]:= {0.0001, 0.0002, 0.001, 0.005, 0.01, 0.1, 0.4}
```

```
Out[ ]:= 10.
```

```

In[ ]:= dataT1DNvNorm = Transpose[Transpose[dataT1DNv] / dataT1DNv[[nromPos]]];
  dataT1C10NvNorm = Transpose[Transpose[dataT1C10Nv] / dataT1C10Nv[[nromPos]]];
  dataT1C5NvNorm = Transpose[Transpose[dataT1C5Nv] / dataT1C5Nv[[nromPos]]];

```

```
In[ ]:= dataT1C5NvNorm // TableForm
```

```
Out[ ]//TableForm=
```

| | | | | | | |
|----------|----------|----------|----------|----------|----------|----------|
| 0. | 0. | 0. | 0. | 0. | 0. | 0. |
| 0. | 0. | 0. | 0. | 0. | 0. | 0. |
| 0.20362 | 0.265687 | 0.42823 | 0.550679 | 0.804146 | 0.862111 | 0.657036 |
| 0.719618 | 0.914034 | 0.947765 | 0.995367 | 0.999983 | 0.961307 | 0.985586 |
| 1. | 1. | 1. | 1. | 1. | 1. | 1. |
| 1.97523 | 1.00693 | 1.44309 | 1.00001 | 1. | 1.38099 | 1.17479 |
| 1.98885 | 1.00693 | 1.64647 | 1.00001 | 1. | 1.52805 | 1.34343 |

```
In[ ]:= simParamNv // TableForm
```

```

simParamNvNorm = Transpose[Transpose[simParamNv] / simParamNv[[nromPos]]];
simParamNvNorm // TableForm

```

```
Out[ ]//TableForm=
```

| | | | | | |
|--------------------------|--------------|--------------|-----------|-----------|----------|
| 1.15831×10^{-8} | 0.0000225289 | 0.0000470166 | 0.0120637 | 0.0330104 | 0.182311 |
| 4.04537×10^{-7} | 0.000699228 | 0.00131308 | 0.158638 | 0.305208 | 0.713778 |
| 0.000100151 | 0.0977688 | 0.154622 | 1.16532 | 1.26874 | 1.44248 |
| 0.00143825 | 0.822265 | 1.03048 | 2.08205 | 2.11032 | 2.18122 |
| 0.00304654 | 1.21973 | 1.41133 | 2.40188 | 2.42511 | 2.49533 |
| 0.022522 | 2.54577 | 2.84791 | 7.2319 | 7.40418 | 7.86544 |
| 0.0339701 | 3.16342 | 3.61667 | 21.0621 | 22.3219 | 25.4018 |


```
Out[ ]//TableForm=
```

| | | | | | |
|--------------------------|--------------|--------------|-----------|-----------|----------|
| 3.80206×10^{-6} | 0.0000184704 | 0.0000333137 | 0.0050226 | 0.0136119 | 0.073061 |
| 0.000132786 | 0.000573263 | 0.000930384 | 0.0660475 | 0.125853 | 0.286046 |
| 0.0328736 | 0.0801559 | 0.109558 | 0.48517 | 0.523167 | 0.578071 |
| 0.472094 | 0.674135 | 0.730146 | 0.866841 | 0.870194 | 0.87412 |
| 1. | 1. | 1. | 1. | 1. | 1. |
| 7.39265 | 2.08715 | 2.0179 | 3.01093 | 3.05313 | 3.15207 |
| 11.1504 | 2.59354 | 2.5626 | 8.769 | 9.20447 | 10.1797 |


```

In[ ]:= For[NvCount = 1, NvCount ≤ 7, NvCount += 1,
  Print[" time for Nv (ms) = ", 1000 * timeOfNv[[NvCount]]];
  gr1a = ListLogLogPlot[
    Transpose[{dataT1C5Ca, dataT1C5NvNorm[[NvCount]]}], PlotStyle → {colorA}];
  gr1b = ListLogLogPlot[Transpose[{dataT1C10Ca, dataT1C10NvNorm[[NvCount]]}],
    PlotStyle → {colorB}];
  gr1c = ListLogLogPlot[Transpose[{dataT1DCa, dataT1DNvNorm[[NvCount]]}],
    PlotStyle → {colorC}];
  gr2 = ListLogLogPlot[Transpose[{caFact simCaList, simParamNvNorm[[NvCount,
    All]]}], PlotStyle → {Black}, Joined → True, PlotRange → All];
  Show[gr1a, gr1b, gr1c, gr2, PlotRange → {All, {-5, 1}}] // Print;
];
time for Nv (ms) = 0.1


```




```
time for Nv (ms) = 0.2
```




```
time for Nv (ms) = 1.
```




time for Nv (ms) = 5.



time for Nv (ms) = 10.



time for Nv (ms) = 100.



Export Nv

```

In[*]:= If[exportYes == 1,
  Export["Nv export Ca,0.0001,0.0002,0.001,0.005,0.01,0.1,0.4.txt",
    Transpose[Prepend[simParamNv, caFact simCaList]], "Table"];
];

```

Print some values

C5

```
In[ ]:= Transpose[simParamMedianC5] // TableForm
        Transpose[simParamQuantile1C5] // TableForm
        Transpose[simParamQuantile2C5] // TableForm
```

Out[]//TableForm=

| | | | | | | |
|---|---------|---------------|---------|---------|---------|----------------------------|
| 0 | 2.56849 | 0.00134142 | 1.26086 | 257.573 | 1.0015 | 0.00133815 |
| 0 | 2.50124 | 0.00049394 | 1.62794 | 197.853 | 1.00035 | 0.000530593 |
| 0 | 2.68527 | -0.0002 | 2.33647 | 533.976 | 1.3235 | 0.000135972 |
| 0 | 3.61673 | -0.0000938486 | 2.26669 | 678.002 | 1.30857 | 0.000177138 |
| 0 | 3.4176 | -0.000336771 | 2.37426 | 649.489 | 1.18241 | -8.24866×10^{-17} |

Out[]//TableForm=

| | | | | | | | |
|---|---------|--------------|---------|---------|----------|--------------|---|
| 0 | 2.51745 | 0.000612205 | 1.08074 | 162.488 | 1.0013 | 0.000716352 | 6 |
| 0 | 2.46192 | 0.000023287 | 1.5634 | 181.755 | 1.00006 | 0.00032736 | 1 |
| 0 | 2.32801 | -0.000258229 | 2.25444 | 387.116 | 1.25661 | 0.000108022 | 3 |
| 0 | 2.81045 | -0.0002 | 2.21093 | 636.485 | 1.25971 | 0.000136624 | 2 |
| 0 | 3.22059 | -0.000412487 | 2.31679 | 500.293 | 0.708503 | -0.000147837 | 2 |

Out[]//TableForm=

| | | | | | | | |
|---|---------|---------------------------|---------|---------|---------|-------------|----|
| 0 | 2.96481 | 0.00145823 | 1.74265 | 538.158 | 1.00554 | 0.00150193 | 21 |
| 0 | 2.74063 | 0.000632746 | 1.7046 | 238.006 | 1.00713 | 0.000641544 | 28 |
| 0 | 2.86931 | -0.000103434 | 2.47382 | 543.718 | 1.35302 | 0.000177605 | 23 |
| 0 | 3.61708 | 2.06141×10^{-17} | 2.29184 | 685.279 | 1.39066 | 0.000194935 | 20 |
| 0 | 4.01756 | -0.000301624 | 2.38101 | 656.787 | 1.58562 | 0.000595264 | 23 |

C10

```
In[ ]:= Transpose[simParamMedianC10] // TableForm
Transpose[simParamQuantile1C10] // TableForm
Transpose[simParamQuantile2C10] // TableForm
```

Out[]//TableForm=

| | | | | | | | |
|---|---------|--------------|---------|---------|----------|--------------|---|
| 0 | 7.71188 | 0.0002 | 1.47987 | 160.138 | 0.999958 | 0.0002 | 2 |
| 0 | 7.8405 | 0.000429173 | 1.62998 | 227.791 | 1.0016 | 0.000541875 | 1 |
| 0 | 8.82845 | -0.0001 | 2.32614 | 492.968 | 1.0904 | 0.000166732 | 2 |
| 0 | 7.98178 | -0.000113113 | 2.2743 | 611.729 | 1.10079 | 0.0000747615 | 3 |
| 0 | 8.52843 | -0.000353607 | 2.33671 | 581.76 | 1.06048 | 0.000145139 | 2 |

Out[]//TableForm=

| | | | | | | | |
|---|---------|--------------|---------|---------|----------|---------------------------|--|
| 0 | 7.08688 | 0.000126294 | 1.17872 | 71.2006 | 0.999794 | 0.0002 | |
| 0 | 7.64974 | 0.0004 | 1.41652 | 192.149 | 0.99677 | 0.000360713 | |
| 0 | 6.84202 | -0.000209557 | 2.31236 | 489.208 | 1.07923 | 0.00016458 | |
| 0 | 7.73302 | -0.000542769 | 2.23329 | 484.653 | 1.09923 | -0.0000275514 | |
| 0 | 7.1172 | -0.00040585 | 2.29944 | 571.306 | 0.861835 | 2.18527×10^{-17} | |

Out[]//TableForm=

| | | | | | | | |
|---|---------|---------------|---------|---------|---------|-------------|----|
| 0 | 9.16516 | 0.0007 | 2.51777 | 247.957 | 1.00488 | 0.0007 | 2. |
| 0 | 8.52092 | 0.000947926 | 1.79507 | 281.491 | 1.01257 | 0.00106018 | 36 |
| 0 | 9.75145 | -0.0000231327 | 2.34355 | 549.149 | 1.09068 | 0.0002 | 3. |
| 0 | 10.4883 | -0.0001 | 2.3394 | 623.304 | 1.21877 | 0.000121074 | 35 |
| 0 | 10.3438 | -0.000214012 | 2.34291 | 631.621 | 1.07682 | 0.000530734 | 2. |

D

```
In[ ]:= Transpose[simParamMedianD] // TableForm
Transpose[simParamQuantile1D] // TableForm
Transpose[simParamQuantile2D] // TableForm
```

Out[]//TableForm=

| | | | | | | | |
|---|----------|--------------|---------|---------|---------|--------------|---|
| 0 | 0.158654 | 0.000641456 | 1.49144 | 181.605 | 1.01159 | 0.000623127 | 0 |
| 0 | 0.150791 | 0.000542492 | 1.52878 | 251.411 | 1.00113 | 0.000535539 | 1 |
| 0 | 0.657417 | -0.000147871 | 2.3009 | 523.787 | 4.20555 | 0.000105559 | 2 |
| 0 | 0.887898 | -0.000208162 | 2.29844 | 561.668 | 4.79737 | 0.0000896594 | 2 |
| 0 | 1.36275 | -0.000259953 | 2.33484 | 665.864 | 5.74032 | 0.0000457876 | 2 |

Out[]//TableForm=

| | | | | | | | |
|---|----------|--------------|---------|---------|---------|--------------|---|
| 0 | 0.157877 | 0.000618486 | 1.47258 | 178.885 | 1. | 0.000589261 | 0 |
| 0 | 0.132567 | 0.000430563 | 1.50741 | 223.687 | 1.00064 | 0.000422803 | 1 |
| 0 | 0.623135 | -0.000150779 | 2.30057 | 518.718 | 3.66281 | 0.0000793084 | 2 |
| 0 | 0.839884 | -0.000228528 | 2.29565 | 549.863 | 4.7089 | 0.000073433 | 2 |
| 0 | 1.35841 | -0.00028396 | 2.32779 | 644.892 | 5.40133 | 0.0000408617 | 2 |

Out[]//TableForm=

| | | | | | | | |
|---|----------|--------------|---------|---------|---------|--------------|---|
| 0 | 0.171913 | 0.000743647 | 1.50705 | 191.866 | 1.02839 | 0.000743647 | 1 |
| 0 | 0.163033 | 0.000653992 | 1.60985 | 271.131 | 1.00906 | 0.000681785 | 1 |
| 0 | 0.715741 | -0.00011199 | 2.3021 | 533.414 | 4.71027 | 0.000124935 | 2 |
| 0 | 0.91061 | -0.0002 | 2.30711 | 564.712 | 5.79008 | 0.0000900976 | 2 |
| 0 | 1.41395 | -0.000257475 | 2.33924 | 666.878 | 7.28554 | 0.0000856202 | 2 |

Nv

```
In[ ]:= Transpose[simParamNv] // TableForm
```


```
Out[ ]:= TableForm=
```

| | | | | | |
|--------------------------|--------------------------|-------------|------------|------------|---------|
| 1.15831×10^{-8} | 4.04537×10^{-7} | 0.000100151 | 0.00143825 | 0.00304654 | 0.02252 |
| 0.0000225289 | 0.000699228 | 0.0977688 | 0.822265 | 1.21973 | 2.54577 |
| 0.0000470166 | 0.00131308 | 0.154622 | 1.03048 | 1.41133 | 2.84791 |
| 0.0120637 | 0.158638 | 1.16532 | 2.08205 | 2.40188 | 7.2319 |
| 0.0330104 | 0.305208 | 1.26874 | 2.11032 | 2.42511 | 7.40418 |
| 0.182311 | 0.713778 | 1.44248 | 2.18122 | 2.49533 | 7.86544 |

EPSC with different caRest

Interpolate

```
In[ ]:= locaCa = Transpose[{dataLocalCaTime, dataLocalCa}];
locaCaWithoutdublicties = Mean /@ GatherBy[locaCa, First];
interpolFunc = Interpolation[locaCaWithoutdublicties, InterpolationOrder -> 1];
caFunc[t_] := interpolFunc[t];
Plot[caFunc[t], {t, 0.00, 0.003}, PlotRange -> All]
```








NDSolve





```

In[ ]:= timeStartForPlot = 0.0;
timeEndForPlot = 0.003;
myNDSolveResults = NDSolve[eq,
  {fillStateSS, ss1, ss2, ss3, ss4, ss5, ss6, ss7, sitePlugging}, {t, 0, 0.003}];
Plot[(fillStateSS[t] /. myNDSolveResults),
  {t, timeStartForPlot, timeEndForPlot}, PlotRange -> All]
Plot[(ss1[t] /. myNDSolveResults),
  {t, timeStartForPlot, timeEndForPlot}, PlotRange -> All]
Plot[(ss2[t] /. myNDSolveResults),
  {t, timeStartForPlot, timeEndForPlot}, PlotRange -> All]
Plot[(ss3[t] /. myNDSolveResults),
  {t, timeStartForPlot, timeEndForPlot}, PlotRange -> All]
Plot[(ss4[t] /. myNDSolveResults),
  {t, timeStartForPlot, timeEndForPlot}, PlotRange -> All]
Plot[(ss5[t] /. myNDSolveResults),
  {t, timeStartForPlot, timeEndForPlot}, PlotRange -> All]
Plot[(ss6[t] /. myNDSolveResults),
  {t, timeStartForPlot, timeEndForPlot}, PlotRange -> All]
Plot[(ss7[t] /. myNDSolveResults),
  {t, timeStartForPlot, timeEndForPlot}, PlotRange -> All]
Plot[(sitePlugging[t] /. myNDSolveResults),
  {t, timeStartForPlot, timeEndForPlot}, PlotRange -> All]

```







different caRest

```
In[ ]:= caRestLow = 30*^-9;
        caRestHigh = 180*^-9;
```

Low Ca

Initial occupancy

```
In[ ]:= (*calualte initial equilibrium occupancy*)
        caFunc[t_] := caRestLow;
        kprimScheme
        kunprimScheme
        fillStateSSInitial = kprimScheme / kunprimScheme
        kfillScheme
        kunfillScheme
        ss0Initial = fillStateSSInitial * kfillScheme / kunfillScheme

Out[ ]:= 3.3867

Out[ ]:= 8.61585

Out[ ]:= 0.393078

Out[ ]:= 111.823

Out[ ]:= 181.545

Out[ ]:= 0.242117
```

Diff eq.


```
In[ ]:= Clear[caFunc, eq]; (*Clear is needed if the cell is exected for a 2nd time
    when caFunc is already set to a value or an Interpolationfunction*)
        caFunc[t_] := interpolFunc[t];
        ss[t_] = {ss1[t], ss2[t], ss3[t], ss4[t], ss5[t], ss6[t], ss7[t]};
        eq = {ss'[t] == (mat /. repl).ss[t],
              ss[0] == {ss0Initial, 0., 0., 0., 0., 0., 0.},
              (fillStateSS'[t] == kprim - kunprim fillStateSS[t] -
                kfill fillStateSS[t] + kunfill ss1[t]) /. repl,
              fillStateSS[0] == fillStateSSInitial,
              sitePlugging'[t] ==
                (1 - sitePlugging[t]) ss7'[t] - siteClearanceTau sitePlugging[t],
              sitePlugging[0] == 0
              };
```





NDSolve





```

In[ ]:= myNDSolveResults = NDSolve[eq,
  {fillStateSS, ss1, ss2, ss3, ss4, ss5, ss6, ss7, sitePlugging}, {t, 0, 0.003}];
Plot[(fillStateSS[t] /. myNDSolveResults),
  {t, timeStartForPlot, timeEndForPlot}, PlotRange → All]
Plot[(ss1[t] /. myNDSolveResults),
  {t, timeStartForPlot, timeEndForPlot}, PlotRange → All]
Plot[(ss2[t] /. myNDSolveResults),
  {t, timeStartForPlot, timeEndForPlot}, PlotRange → All]
Plot[(ss3[t] /. myNDSolveResults),
  {t, timeStartForPlot, timeEndForPlot}, PlotRange → All]
Plot[(ss4[t] /. myNDSolveResults),
  {t, timeStartForPlot, timeEndForPlot}, PlotRange → All]
Plot[(ss5[t] /. myNDSolveResults),
  {t, timeStartForPlot, timeEndForPlot}, PlotRange → All]
Plot[(ss6[t] /. myNDSolveResults),
  {t, timeStartForPlot, timeEndForPlot}, PlotRange → All]
Plot[(ss7[t] /. myNDSolveResults),
  {t, timeStartForPlot, timeEndForPlot}, PlotRange → All]
Plot[(sitePlugging[t] /. myNDSolveResults),
  {t, timeStartForPlot, timeEndForPlot}, PlotRange → All]

```








Plot EPSC

```
In[ ]:= epscLowCa = D[(ss7[t] /. myNDSolveResults), t];
Plot[(ss7[t] /. myNDSolveResults), {t, 0, 2*^-3}, PlotRange -> All];
Plot[epscLowCa, {t, 0, 0.5*^-3}, PlotRange -> All]
```



High Ca

Initial occupancy

```
In[ ]:= (*calculate initial equilibrium occupancy*)
caFunc[t_] := caRestHigh;
kprimScheme
kunprimScheme
fillStateSSInitial = kprimScheme / kunprimScheme
kfillScheme
kunfillScheme
ss0Initial = fillStateSSInitial * kfillScheme / kunfillScheme
```

Out[]:= 7.45413

Out[]:= 8.61585

Out[]:= 0.865165

Out[]:= 166.055

Out[]:= 181.545

Out[]:= 0.791348

Diff eq.

```

In[ ]:= Clear[caFunc, eq]; (*Clear is needed if the cell is executed for a 2nd time
when caFunc is already set to a value or an Interpolationfunction*)
caFunc[t_] := interpolFunc[t];
ss[t_] = {ss1[t], ss2[t], ss3[t], ss4[t], ss5[t], ss6[t], ss7[t]};
eq = {ss'[t] == (mat /. repl).ss[t],
      ss[0] == {ss0Initial, 0., 0., 0., 0., 0., 0.},
      (fillStateSS'[t] == kprim - kunprim fillStateSS[t] -
        kfill fillStateSS[t] + kunfill ss1[t]) /. repl,
      fillStateSS[0] == fillStateSSInitial,
      sitePlugging'[t] ==
        (1 - sitePlugging[t]) ss7'[t] - siteClearanceTau sitePlugging[t],
      sitePlugging[0] == 0
    };





```





NDSolve


```

In[ ]:= myNDSolveResults = NDSolve[eq,
  {fillStateSS, ss1, ss2, ss3, ss4, ss5, ss6, ss7, sitePlugging}, {t, 0, 0.003}];
Plot[(fillStateSS[t] /. myNDSolveResults),
  {t, timeStartForPlot, timeEndForPlot}, PlotRange -> All]
Plot[(ss1[t] /. myNDSolveResults),
  {t, timeStartForPlot, timeEndForPlot}, PlotRange -> All]
Plot[(ss2[t] /. myNDSolveResults),
  {t, timeStartForPlot, timeEndForPlot}, PlotRange -> All]
Plot[(ss3[t] /. myNDSolveResults),
  {t, timeStartForPlot, timeEndForPlot}, PlotRange -> All]
Plot[(ss4[t] /. myNDSolveResults),
  {t, timeStartForPlot, timeEndForPlot}, PlotRange -> All]
Plot[(ss5[t] /. myNDSolveResults),
  {t, timeStartForPlot, timeEndForPlot}, PlotRange -> All]
Plot[(ss6[t] /. myNDSolveResults),
  {t, timeStartForPlot, timeEndForPlot}, PlotRange -> All]
Plot[(ss7[t] /. myNDSolveResults),
  {t, timeStartForPlot, timeEndForPlot}, PlotRange -> All]
Plot[(sitePlugging[t] /. myNDSolveResults),
  {t, timeStartForPlot, timeEndForPlot}, PlotRange -> All]

```






Plot EPSC

```

In[ ]:= epscHighCa = D[(ss7[t] /. myNDSolveResults), t];
Plot[(ss7[t] /. myNDSolveResults), {t, 0, 2*^-3}, PlotRange -> All];
Plot[epscLowCa, {t, 0, 0.5*^-3}, PlotRange -> All]


```



Compare


Plot both release rates


```
In[ ]:= Plot[{epscLowCa, epscHighCa}, {t, 0, 0.5*^-3}, PlotRange -> All]
```



Convolution RelRate => EPSC

```
In[ ]:= miniKernel[t_] := If[t <= 0, 0, (1 - Exp[-t/0.0001]) * Exp[-t/0.002]];
Plot[miniKernel[t], {t, -.001, .01}]
dtForConvolve = 0.00005;
tEndConv = 0.01;
miniKernelList = Table[miniKernel[t], {t, 0.0, tEndConv, dtForConvolve}];
epscHighCaList = {Table[0, {t, 0, tEndConv, dtForConvolve}],
  Table[epscHighCa, {t, 0.0, 0.0025, dtForConvolve}],
  Table[0, {t, 0, tEndConv, dtForConvolve}]} // Flatten;
epscLowCaList = {Table[0, {t, 0, tEndConv, dtForConvolve}],
  Table[epscLowCa, {t, 0.0, 0.0025, dtForConvolve}],
  Table[0, {t, 0, tEndConv, dtForConvolve}]} // Flatten;
ListPlot[miniKernelList]
ListPlot[epscLowCaList, PlotRange -> All]
```







```

In[ ]:= epscLowCaCurrentList = ListConvolve[miniKernelList, epscLowCaList];
epscHighCaCurrentList = ListConvolve[miniKernelList, epscHighCaList];
timeConv = Table[t * dtForConvolve, {t, Length[epscLowCaCurrentList]};
ListPlot[{Transpose[{timeConv, epscLowCaCurrentList}],
  Transpose[{timeConv, epscHighCaCurrentList}]}], Joined → True, PlotRange → All]
ListPlot[{Transpose[{timeConv, epscLowCaCurrentList}],
  Transpose[{timeConv, epscHighCaCurrentList}]}],
  Joined → True, PlotRange → {{0, 0.002}, All}]
maxLow = Max[epscLowCaCurrentList]
maxHigh = Max[epscHighCaCurrentList]
Print["maxHigh/maxLow = ", maxHigh/maxLow];
ListPlot[{Transpose[{timeConv, (1/maxLow) * epscLowCaCurrentList}],
  Transpose[{timeConv, (1/maxHigh) * epscHighCaCurrentList}]}],
  Joined → True, PlotRange → All]
ListPlot[{Transpose[{timeConv, (1/maxLow) * epscLowCaCurrentList}],
  Transpose[{timeConv, (1/maxHigh) * epscHighCaCurrentList}]}],
  Joined → True, PlotRange → {{0, 0.002}, All}]
If[exportYes == 1,
  toExport = Transpose[{timeConv, epscLowCaCurrentList, epscHighCaCurrentList,
    (1/maxLow) * epscLowCaCurrentList, (1/maxHigh) * epscHighCaCurrentList}];
  Export["plot EPSC - low and high - abs and norm.txt", toExport, "Table"];
];


```




$Out[*]=$ 3027.59

$Out[*]=$ 8899.31

$\text{maxHigh}/\text{maxLow} = 2.9394$





Timing

```
In[ ]:= timeEnd = AbsoluteTime[];  
        (timeEnd - timeStart) / 60. (*time of calculation in min*)
```

Out[]:= 0.252691