

```
In[613]:= (* Mathematica code for Modell of Eshra et al. eLife 2021 *)  
          (* Stefan Hallermann and Hartmut Schmidt Aug 2021 *)
```

# Import

---

## general

```
In[614]:= (* imported data all Ca in uM, all times in ms,  
          all amplitudes and Nv in vesicles *)  
  
In[615]:= CmToVesConversionFactor = (1/90.12) * (1/70*^-18); (* explained in methods *)  
  
In[616]:= rrp = 10; (* pool of release-ready vesicles per connection *)  
  
In[617]:= dir = NotebookDirectory[];  
          SetDirectory[dir];  
          dataFolder = "../data to fit/";
```

---

## tau1 Cm 5kHz

```
In[620]:= data = Import[dataFolder <> "all_t1_v02_C5.txt", "Table"];
```

```

In[621]:= dataT1C5Ca = 0.001 * data[[All, 1]];
dataT1C5RelRate = 1000. * data[[All, 2]];
dataT1C5Delay = data[[All, 3]];
dataT1C5ChiRatio = data[[All, 4]];
dataT1C5Amplitude = CmToVesConversionFactor data[[All, 5]];

dataT1C5Nv = Table[0, {7}];
tmp1 = 1;
tmp2 = 6;
dataT1C5Nv[[tmp1]] = CmToVesConversionFactor data[[All, tmp2]];
tmp1 += 1;
tmp2 += 1;
dataT1C5Nv[[tmp1]] = CmToVesConversionFactor data[[All, tmp2]];
tmp1 += 1;
tmp2 += 1;
dataT1C5Nv[[tmp1]] = CmToVesConversionFactor data[[All, tmp2]];
tmp1 += 1;
tmp2 += 1;
dataT1C5Nv[[tmp1]] = CmToVesConversionFactor data[[All, tmp2]];
tmp1 += 1;
tmp2 += 1;
dataT1C5Nv[[tmp1]] = CmToVesConversionFactor data[[All, tmp2]];
tmp1 += 1;
tmp2 += 1;
dataT1C5Nv[[tmp1]] = CmToVesConversionFactor data[[All, tmp2]];
tmp1 += 1;
tmp2 += 1;
dataT1C5Nv[[tmp1]] = CmToVesConversionFactor data[[All, tmp2]];

```

---

## tau1 Cm 10kHz

```

In[634]:= data = Import[dataFolder <> "all_t1_v02_C10.txt", "Table"];

```

```

In[635]:= dataT1C10Ca = 0.001 * data[[All, 1]];
dataT1C10RelRate = 1000. * data[[All, 2]];
dataT1C10Delay = data[[All, 3]];
dataT1C10ChiRatio = data[[All, 4]];
dataT1C10Amplitude = CmToVesConversionFactor data[[All, 5]];

dataT1C10Nv = Table[0, {7}];
tmp1 = 1;
tmp2 = 6;
dataT1C10Nv[[tmp1]] = CmToVesConversionFactor data[[All, tmp2]];
tmp1 += 1;
tmp2 += 1;
dataT1C10Nv[[tmp1]] = CmToVesConversionFactor data[[All, tmp2]];
tmp1 += 1;
tmp2 += 1;
dataT1C10Nv[[tmp1]] = CmToVesConversionFactor data[[All, tmp2]];
tmp1 += 1;
tmp2 += 1;
dataT1C10Nv[[tmp1]] = CmToVesConversionFactor data[[All, tmp2]];
tmp1 += 1;
tmp2 += 1;
dataT1C10Nv[[tmp1]] = CmToVesConversionFactor data[[All, tmp2]];
tmp1 += 1;
tmp2 += 1;
dataT1C10Nv[[tmp1]] = CmToVesConversionFactor data[[All, tmp2]];
tmp1 += 1;
tmp2 += 1;
dataT1C10Nv[[tmp1]] = CmToVesConversionFactor data[[All, tmp2]];

```

---

## tau1 Deconv

```

In[648]:= data = Import[dataFolder <> "all_t1_v02_D.txt", "Table"];

```

```

In[649]:= dataT1DCa = 0.001 * data[[All, 1]];
dataT1DRelRate = 1000. * data[[All, 2]];
dataT1DDelay = data[[All, 3]];
dataT1DChiRatio = data[[All, 4]];
dataT1DAmplitude = data[[All, 5]];

dataT1DNv = Table[0, {7}];
tmp1 = 1; tmp2 = 6; dataT1DNv[[tmp1]] = data[[All, tmp2]];
tmp1 += 1; tmp2 += 1; dataT1DNv[[tmp1]] = data[[All, tmp2]];
tmp1 += 1; tmp2 += 1; dataT1DNv[[tmp1]] = data[[All, tmp2]];
tmp1 += 1; tmp2 += 1; dataT1DNv[[tmp1]] = data[[All, tmp2]];
tmp1 += 1; tmp2 += 1; dataT1DNv[[tmp1]] = data[[All, tmp2]];
tmp1 += 1; tmp2 += 1; dataT1DNv[[tmp1]] = data[[All, tmp2]];
tmp1 += 1; tmp2 += 1; dataT1DNv[[tmp1]] = data[[All, tmp2]];

```

---

## tau2 Cm 5kHz

```

In[662]:= data = Import[dataFolder <> "all_t2_v02_C5.txt", "Table"];

In[663]:= dataT2C5Ca = 0.001 * data[[All, 1]];
dataT2C5RelRate = 1000. * data[[All, 2]];
dataT2C5Amplitude2 = CmToVesConversionFactor data[[All, 3]];
dataT2C5Amplitude1 = CmToVesConversionFactor data[[All, 4]];

```

---

## tau2 Cm 10kHz

```

In[667]:= data = Import[dataFolder <> "all_t2_v02_C10.txt", "Table"];

In[668]:= dataT2C10Ca = 0.001 * data[[All, 1]];
dataT2C10RelRate = 1000. * data[[All, 2]];
dataT2C10Amplitude2 = CmToVesConversionFactor data[[All, 3]];
dataT2C10Amplitude1 = CmToVesConversionFactor data[[All, 4]];

```

---

## tau2 Deconv

```


In[671]:= data = Import[dataFolder <> "all_t2_v02_D.txt", "Table"];

In[672]:= dataT2DCa = 0.001 * data[[All, 1]];
dataT2DRelRate = 1000. * data[[All, 2]];
dataT2DAmplitude2 = data[[All, 3]];
dataT2DAmplitude1 = data[[All, 4]];

```

## local Ca

```
In[676]:= data = Import[dataFolder <> "local Ca at 20 nm in uM and ms.txt", "Table"];  
dataLocalCa = 1*^-6 data[[All, 1]];  
dataLocalCaTime = 1*^-3 data[[All, 2]];  
ListPlot[Transpose[{dataLocalCaTime, dataLocalCa}], PlotRange -> All]
```



# General parameters and definitions

---

## general stuff

```
In[680]:= (* for calculations: time in s, Ca in M *)
numberOfFitParamToBeSaved = 16;
(*
1 max release

Mono
2 chi2Mono
3 delayMono
4 ampMono
5 1/tau1Mono

Bi
6 chi2Mono/chi2Bi
7 delay
8 amp
9 amp1 (=amp*relative amp1)
10 1/tau1
11 1/tau2

merge
12 delay
13 amp
14 amp1
15 1/tau1
16 1/tau2
*)
cursorStart = -0.002; (*s*)
cursorEnd = 0.01; (*s*)
cursorEndLong = 0.061; (*s*)
timeOfNv = {0.0001, 0.0002, 0.001, 0.005, 0.01, 0.1, 0.4};
SeedRandom[1];
myMaxIterations = 100;
```

```
In[687]:= timeStart = AbsoluteTime[]
```

```
Out[687]:= 3.839163897148013 × 109
```

## noiseRepeats

```
In[688]:= noiseRepeats = 3;
          (* should be increased to 50 for a full dataset *)
          myQuantile1 = 0.25;
          myQuantile2 = 0.75;
```

## export parameters

```
In[691]:= dtOfPlotsForExport = 20*^-5;
          exportYes = 1;
```

## sampling and myNoise

```
In[693]:= samplingOfDataInKHzC5 = 5;
          myNoiseC5 = CmToVesConversionFactor * 1.36937*^-14 / rrp(*cannot be 0*)
          signalToNoiseRatioC5 = 1.;(*minimum s-to-n-ratio to attempt fitting*)
          dtOfDataC5 = (1 / (1000 * samplingOfDataInKHzC5));

          samplingOfDataInKHzC10 = 10;
          myNoiseC10 = CmToVesConversionFactor * 1.67583*^-14 / rrp(*cannot be 0*)
          signalToNoiseRatioC10 = 1.;(*minimum s-to-n-ratio to attempt fitting*)
          dtOfDataC10 = (1 / (1000 * samplingOfDataInKHzC10));

          samplingOfDataInKHzD = 10;
          myNoiseD = 0.367584 / rrp(*cannot be 0*)
          signalToNoiseRatioD = 1.;(*minimum s-to-n-ratio to attempt fitting*)
          dtOfDataD = (1 / (1000 * samplingOfDataInKHzD));

          samplingOfDataInKHzLong = 1;
          myNoiseLong = myNoiseC5;(*cannot be 0*)
          dtOfDataLong = (1 / (1000 * samplingOfDataInKHzLong));
```

```
Out[694]= 0.217071
```

```
Out[698]= 0.265651
```

```
Out[702]= 0.0367584
```

## number of simulations per DMN

```
In[708]:= aNumberDMN05 = 2;
          aNumberDMN2 = 2;
          aNumberDMN10 = 2;

          (* for full dataset: *)
          (*
          aNumberDMN05=2*20;
          aNumberDMN2=2*17;
          aNumberDMN10=2*10;
          *)
```

## Exp fit function

```
In[711]:= myFitMono[t_] :=
          If[t <= delayMono, 0, ampMono (1 - Exp[-(t - delayMono) / tau1Mono])];

          myFitBi[t_] := If[t <= delay, 0,
          amp (1 - amp1 Exp[-(t - delay) / tau1] - (1 - amp1) Exp[-(t - delay) / tau2])];

          (*guess for 10 uM; will be changed according to a power of 1 law*)(*in s*)
          ampGuess = 2.;(*each pool has size 1.0*)
          tau1Guess = 0.001;(*in s*)
          delayGuess = 0.0005;(*in s*)
          amp1Guess = 0.5;
```

## Calculate Ca transients

First, the resting conditions are numerically calculated. Subsequently, the resulting values are used as initial conditions for the main simulations of the flash-evoked  $\text{Ca}^{2+}$  transitions. All calculations are repeated in a loop with increasing uncaging efficacy for three different DMN concentrations. The resulting free  $\text{Ca}^{2+}$  concentration is later used to drive the release schemes.

## General definitions for all DMN conc.

```
In[717]:= CaListReal = CaListDye = {};
```

## 0.5 mM DMN



## general parameters

```
In[718]:= TimeWindow = 0.006; (*End of simulation*)
          tflash = 0.0; (*Time of flash*)
          PlStart = 0.; (*Plot start*)

          af = 0.67; (*fast uncaging fraction; Faas et al*)

          (*Select dye*)
          OGB1 = 0;
          OGB5N = 0;
          OGB6F = 0;
          Fluo5F = 1;

          CaRest = 227. * 10^-9; (*Free pre-flash resting Ca;
          equilibrates with all buffers and DM*)
          MgT = 0.5 * 10^-3; (*total Mg in pipette*)
          γ = 0.; (*Pump rate*)

          (*Concentrations of dye, buffers, DM*)
          OGtotal = 50. * 10^-6;
          ATPtotal = 5. * 10^-3;
          MBtotal = 480. * 10^-6; (*(*Delvendahl, PNAS, 2015*)*)

          DMT = 0.5 * 10^-3; (*total concentration of DMn *)
          (*uncaging efficiency*)
          aStartDMN05 = 0.08;
          aEndDMN05 = 0.5;
```

## definitions and loop

```
In[735]:= (*Dye*)
          If[OGB1 == 1,
            kOnOG = 4.3 * 10^8;
            kOffOG = 103.;]

          If[OGB5N == 1,
            kOnOG = 2.5 * 10^8;
            kOffOG = 6000.;]

          If[OGB6F == 1,
            kOnOG = 3. * 10^8;
            kOffOG = 900.;]

          If[Fluo5F == 1,
```

```

kOnOG = 3. * 108;
kOffOG = 249.;] (*Delvendahl PNAS; before: 432*)

KdOG = kOffOG / kOnOG;
kappaOG = OGtotal / KdOG;

(*ATP*)
kOnATP = 5. * 108;
kOffATP = 100000.;
kOnMgATP = 1. * 107; (*Bollmann Dissertation S. 59; *)
kOffMgATP = 1000.;

KdATP = kOffATP / kOnATP;
kappaATP = ATPtotal / KdATP;
KdMgATP = kOffMgATP / kOnMgATP;

(*DM*)
If[MgT == 0.,
  kOnDM = 1.98 * 107; (*Faas Plos Biol, 2007*)
  kOffDM = 0.14;
,
  kOnDM = 2.9 * 107; (*Faas Biophys J, 2005*)
  kOffDM = 0.19;
]

(*Mg binding constants for DMn, DMf, DMs*)
kOnMg = 1.3 * 105; (*all values for Mg are from Faas et al., 2005*)
kOffMg = 0.2;

(*Ca binding constants for PP*)
kOnPP2 = kOnPP1 = kOnDM;
kOffPP2 = 3.6 * 103;
If[MgT == 0.,
  kOffPP1 = 7. * 104;;
  kOffPP1 = 6.9 * 104; ]

(*Mg binding constants for PP1,PP2*)
kOffMgPP = 3. * 102; (*for PP1,PP2*)
konMgPP = kOnMg; (*koMgPP not used in below diff. eq., only kOnMg*)

(*Equilibrium constants (not complete)*)
KdDM = kOffDM / kOnDM;
KdPP1 = kOffPP1 / kOnPP1;
KdMg = kOffMg / kOnMg;
kappaDM = DMT / KdDM;

```

```

(*Endogenous buffer*)
kOnMB = 5 * 108; (*DeIvendahl, PNAS, 2015*)
kOffMB = 16 000;
KdMB = kOffMB / kOnMB;

TRest = 1000.;

(*----- Loop -----
-----*)
(*----- Loop -----
-----*)
(*----- Loop -----
-----*)

For[aCount = 1, aCount ≤ aNumberDMN05, aCount += 1,
  a = 10^(Log10[aStartDMN05] +
    (aCount - 1) * (Log10[aEndDMN05] - Log10[aStartDMN05]) / (aNumberDMN05 - 1));

  (*----- Resting
  Equations -----*)

  (*Dye*)
  OGRest := {

    OG[0] == OGtotal,
    CaOG[0] == 0,

    OG'[tt] == -kOnOG * CaRest * OG[tt] + kOffOG * CaOG[tt],
    CaOG'[tt] == kOnOG * CaRest * OG[tt] - kOffOG * CaOG[tt]
  }
;

  (*ATP*)
  ATPRest := {

    ATP[0] == ATPtotal,
    CaATP[0] == 0,
    MgATP[0] == 0,

    ATP'[tt] == -kOnATP * CaRest * ATP[tt] + kOffATP * CaATP[tt] -
      kOnMgATP * Mg[tt] * ATP[tt] + kOffMgATP * MgATP[tt],
    CaATP'[tt] == kOnATP * CaRest * ATP[tt] - kOffATP * CaATP[tt],
    MgATP'[tt] == kOnMgATP * Mg[tt] * ATP[tt] - kOffMgATP * MgATP[tt]
  }

```

```

;

(*DM nitrophenene*)
DMnRest := {

  DMn[0] == (1 - a) * DMT,
  CaDMn[0] == 0.,
  MgDMn[0] == 0.,

  DMn'[tt] == -kOnDM * CaRest * DMn[tt] +
    kOffDM * CaDMn[tt] - kOnMg * Mg[tt] * DMn[tt] + kOffMg * MgDMn[tt],
  CaDMn'[tt] == kOnDM * CaRest * DMn[tt] - kOffDM * CaDMn[tt],
  MgDMn'[tt] == kOnMg * Mg[tt] * DMn[tt] - kOffMg * MgDMn[tt]
}

;
DMfRest := {

  DMf[0] == a * af * DMT,
  CaDMf[0] == 0.,
  MgDMf[0] == 0.,

  DMf'[tt] == -kOnDM * CaRest * DMf[tt] +
    kOffDM * CaDMf[tt] - kOnMg * Mg[tt] * DMf[tt] + kOffMg * MgDMf[tt],
  CaDMf'[tt] == kOnDM * CaRest * DMf[tt] - kOffDM * CaDMf[tt],
  MgDMf'[tt] == kOnMg * Mg[tt] * DMf[tt] - kOffMg * MgDMf[tt]
}

;
DMsRest := {

  DMs[0] == a * (1 - af) * DMT,
  CaDMs[0] == 0.,
  MgDMs[0] == 0.,

  DMs'[tt] == -kOnDM * CaRest * DMs[tt] +
    kOffDM * CaDMs[tt] - kOnMg * Mg[tt] * DMs[tt] + kOffMg * MgDMs[tt],
  CaDMs'[tt] == kOnDM * CaRest * DMs[tt] - kOffDM * CaDMs[tt],
  MgDMs'[tt] == kOnMg * Mg[tt] * DMs[tt] - kOffMg * MgDMs[tt]
}

;

(*Endogeneous buffer*)
MBRest := {

  MB[0] == MBtotal,

```

```

CaMB[0] == 0,

MB'[tt] == -kOnMB * CaRest * MB[tt] + kOffMB * CaMB[tt],
CaMB'[tt] == kOnMB * CaRest * MB[tt] - kOffMB * CaMB[tt]
}

;

(*Free Mg*)
MgfRest := {
  Mg[0] == MgT,

  Mg'[tt] ==
    -kOnMgATP * Mg[tt] * ATP[tt] + kOffMgATP * MgATP[tt]
    - kOnMg * Mg[tt] * DMn[tt] + kOffMg * MgDMn[tt]
    - kOnMg * Mg[tt] * DMf[tt] + kOffMg * MgDMf[tt]
    - kOnMg * Mg[tt] * DMs[tt] + kOffMg * MgDMs[tt]
}

;

EqRest := {ATPRest, MgfRest, OGRest, DMnRest, DMfRest, DMsRest, MBRest};
VarsRest := {ATP, Mg, CaATP, MgATP, CaOG, OG, DMn,
  CaDMn, MgDMn, DMf, CaDMf, MgDMf, DMs, CaDMs, MgDMs, MB, CaMB}
;
solr := NDSolve[EqRest, VarsRest, {tt, 0, TRest}]
;

Ca0 = CaRest;
Mg0 = Extract[Mg[TRest] /. solr, 1];
ATP0 = Extract[ATP[TRest] /. solr, 1];
CaATP0 = Extract[CaATP[TRest] /. solr, 1];
MgATP0 = Extract[MgATP[TRest] /. solr, 1];
OG0 = Extract[OG[TRest] /. solr, 1];
CaOG0 = Extract[CaOG[TRest] /. solr, 1];
DMn0 = Extract[DMn[TRest] /. solr, 1];
CaDMn0 = Extract[CaDMn[TRest] /. solr, 1];
MgDMn0 = Extract[MgDMn[TRest] /. solr, 1];
DMf0 = Extract[DMf[TRest] /. solr, 1];
CaDMf0 = Extract[CaDMf[TRest] /. solr, 1];
MgDMf0 = Extract[MgDMf[TRest] /. solr, 1];
DMs0 = Extract[DMs[TRest] /. solr, 1];
CaDMs0 = Extract[CaDMs[TRest] /. solr, 1];
MgDMs0 = Extract[MgDMs[TRest] /. solr, 1];
MB0 = Extract[MB[TRest] /. solr, 1];
CaMB0 = Extract[CaMB[TRest] /. solr, 1];

```

```

ClearAll[EqRest, VarsRest];

(*----- Flash
Equations -----*)

(*Dye*)
BufferOG := {

  OG[0] == OG0,
  CaOG[0] == CaOG0,

  OG'[tt] == -kOnOG * Ca[tt] * OG[tt] + kOffOG * CaOG[tt],
  CaOG'[tt] == kOnOG * Ca[tt] * OG[tt] - kOffOG * CaOG[tt]}
;

(*ATP*)
BufferATP := {

  ATP[0] == ATP0,
  CaATP[0] == CaATP0,
  MgATP[0] == MgATP0,

  ATP'[tt] == -kOnATP * Ca[tt] * ATP[tt] + kOffATP * CaATP[tt] -
    kOnMgATP * Mg[tt] * ATP[tt] + kOffMgATP * MgATP[tt],
  CaATP'[tt] == kOnATP * Ca[tt] * ATP[tt] - kOffATP * CaATP[tt],
  MgATP'[tt] == kOnMgATP * Mg[tt] * ATP[tt] - kOffMgATP * MgATP[tt]
}
;

(*fast (tauf) and slow (taus) time constants for uncageing;
Faas et al., 2005,2007*)
If[MgT == 0.,
  tauf = 15.2 * 10^-6; (*Faas, 2007*)
  taus = 1.9 * 10^-3;
,
  tauf = 15. * 10^-6; (*Faas,2005*)
  taus = 2. * 10^-3; ]

;

(*The differential equations*)
(*non uncaging fraction of DMn*)
BufferDMn := {

  DMn[0] == DMn0,
  CaDMn[0] == CaDMn0,

```

```

MgDMn[0] == MgDMn0,

DMn'[tt] == -kOnDM * Ca[tt] * DMn[tt] +
  kOffDM * CaDMn[tt] - kOnMg * Mg[tt] * DMn[tt] + kOffMg * MgDMn[tt],
CaDMn'[tt] == kOnDM * Ca[tt] * DMn[tt] - kOffDM * CaDMn[tt],
MgDMn'[tt] == kOnMg * Mg[tt] * DMn[tt] - kOffMg * MgDMn[tt]
}
;

(*fast uncaging fraction of DMn*)
BufferDMf := {

  DMf[0] == DMf0,
  CaDMf[0] == CaDMf0,
  MgDMf[0] == MgDMf0,

  DMf'[tt] == -kOnDM * Ca[tt] * DMf[tt] + kOffDM * CaDMf[tt] - kOnMg * Mg[tt] *
    DMf[tt] + kOffMg * MgDMf[tt] - 1/tauf * DMf[tt] * UnitStep[tt - tflash],
  CaDMf'[tt] == kOnDM * Ca[tt] * DMf[tt] - kOffDM * CaDMf[tt] -
    1/tauf * CaDMf[tt] * UnitStep[tt - tflash],
  MgDMf'[tt] == kOnMg * Mg[tt] * DMf[tt] - kOffMg * MgDMf[tt] -
    1/tauf * MgDMf[tt] * UnitStep[tt - tflash]
}

;

(*slow uncaging fraction of DMn*)
BufferDMS := {

  DMS[0] == DMS0,
  CaDMS[0] == CaDMS0,
  MgDMS[0] == MgDMS0,

  DMS'[tt] == -kOnDM * Ca[tt] * DMS[tt] + kOffDM * CaDMS[tt] - kOnMg * Mg[tt] *
    DMS[tt] + kOffMg * MgDMS[tt] - 1/taus * DMS[tt] * UnitStep[tt - tflash],
  CaDMS'[tt] == kOnDM * Ca[tt] * DMS[tt] - kOffDM * CaDMS[tt] -
    1/taus * CaDMS[tt] * UnitStep[tt - tflash],
  MgDMS'[tt] == kOnMg * Mg[tt] * DMS[tt] - kOffMg * MgDMS[tt] -
    1/taus * MgDMS[tt] * UnitStep[tt - tflash]
}

;

(*Photoproducts*)
(*PP2: comes from DMf,DMS and MgDMf,MgDMS; but also binds Ca*)
BufferPP2 := {

  PP2[0] == 0,
  CaPP2[0] == 0,

```

```

MgPP2[0] == 0,

PP2'[tt] == -kOnPP2 * Ca[tt] * PP2[tt] + kOffPP2 * CaPP2[tt] -
  kOnMg * Mg[tt] * PP2[tt] + kOffMgPP * MgPP2[tt] + 2 * (1 / tauf * DMf[tt] *
    UnitStep[tt - tflash] + 1 / taus * DMs[tt] * UnitStep[tt - tflash])
  + 1 / tauf * MgDMf[tt] * UnitStep[tt - tflash] +
  1 / taus * MgDMs[tt] * UnitStep[tt - tflash],

CaPP2'[tt] == kOnPP2 * Ca[tt] * PP2[tt] - kOffPP2 * CaPP2[tt],

MgPP2'[tt] == kOnMg * Mg[tt] * PP2[tt] - kOffMgPP * MgPP2[tt] + 1 / tauf *
  MgDMf[tt] * UnitStep[tt - tflash] + 1 / taus * MgDMs[tt] * UnitStep[tt - tflash]
}
;

(*PP1: Comes from CaDMf,CaDMs and binds Ca and Mg*)
BufferPP1 := {

  PP1[0] == 0,
  CaPP1[0] == 0,
  MgPP1[0] == 0,

  PP1'[tt] == -kOnPP1 * Ca[tt] * PP1[tt] +
    kOffPP1 * CaPP1[tt] - kOnMg * Mg[tt] * PP1[tt] + kOffMgPP * MgPP1[tt]
    + 1 / tauf * CaDMf[tt] * UnitStep[tt - tflash] +
    1 / taus * CaDMs[tt] * UnitStep[tt - tflash],

  CaPP1'[tt] == kOnPP1 * Ca[tt] * PP1[tt] -
    kOffPP1 * CaPP1[tt] + 1 / tauf * CaDMf[tt] * UnitStep[tt - tflash] +
    1 / taus * CaDMs[tt] * UnitStep[tt - tflash],

  MgPP1'[tt] == kOnMg * Mg[tt] * PP1[tt] - kOffMgPP * MgPP1[tt]

}
;

(*Endogeneous Buffer*)
BufferMB := {

  MB[0] == MB0,
  CaMB[0] == CaMB0,

  MB'[tt] == -kOnMB * Ca[tt] * MB[tt] + kOffMB * CaMB[tt],
  CaMB'[tt] == kOnMB * Ca[tt] * MB[tt] - kOffMB * CaMB[tt]}

;

```



```

(*Clear[Eqns,Vars,sol]*)

(*Free Ca*)
FreeCa := {
  Ca[0] == Ca0,

  Ca'[tt] == -γ * (Ca[tt] - CaRest)
  (*DMn*)
  - kOnPP1 * Ca[tt] * PP1[tt] + kOffPP1 * CaPP1[tt]
  - kOnPP2 * Ca[tt] * PP2[tt] + kOffPP2 * CaPP2[tt]
  - kOnDM * Ca[tt] * DMn[tt] + kOffDM * CaDMn[tt]
  - kOnDM * Ca[tt] * DMf[tt] + kOffDM * CaDMf[tt]
  - kOnDM * Ca[tt] * DMS[tt] + kOffDM * CaDMS[tt]
  (*buffers*)
  - kOnATP * Ca[tt] * ATP[tt] + kOffATP * CaATP[tt]
  - kOnMB * Ca[tt] * MB[tt] + kOffMB * CaMB[tt]
  (*dye*)
  - kOnOG * Ca[tt] * OG[tt] + kOffOG * CaOG[tt]
}
;

(*Free Mg*)
FreeMg := {
  Mg[0] == Mg0,

  Mg'[tt] ==
  - kOnMgATP * Mg[tt] * ATP[tt] + kOffMgATP * MgATP[tt]
  - kOnMg * Mg[tt] * DMn[tt] + kOffMg * MgDMn[tt]
  - kOnMg * Mg[tt] * DMf[tt] + kOffMg * MgDMf[tt]
  - kOnMg * Mg[tt] * DMS[tt] + kOffMg * MgDMS[tt]
  - kOnMg * Mg[tt] * PP2[tt] + kOffMgPP * MgPP2[tt]
  - kOnMg * Mg[tt] * PP1[tt] + kOffMgPP * MgPP1[tt]
}
;

Eqns := {BufferDMn, BufferDMf, BufferDMS, BufferATP,
  BufferPP1, BufferPP2, FreeCa, FreeMg, BufferMB, BufferOG}
;
Vars := {ATP, CaATP, MgATP, Ca, Mg, CaDMn, DMn, CaDMf, DMf, CaDMS,
  DMS, CaPP1, PP1, CaPP2, PP2, MgPP2, MgPP1, MB, CaMB, OG, CaOG}
;
sol := NDSolve[Eqns, Vars, {tt, 0., TimeWindow}
  (*,Method->{"EquationSimplification"->"Solve"}*)]
;
CafP = Extract[Ca[TimeWindow] /. sol, 1];
CafOG = KdOG * CaOG[tt] / OG[tt];

```

```

AppendTo[CaListReal, Evaluate[{Ca[tt]} /. sol]];
AppendTo[CaListDye, Evaluate[{Caf0G} /. sol]];

];

```

## 2 mM DMN

### general parameters

```

In[765]:= TimeWindow = 0.006; (*End of simulation*)
tflash = 0.0; (*Time of flash*)
PlStart = 0.; (*Plot start*)

af = 0.67; (*fast uncaging fraction; Faas et al*)

(*Select dye*)
OGB1 = 0;
OGB5N = 1;
OGB6F = 0;
Fluo5F = 0;

CaRest = 227. * 10^-9; (*Free pre-flash resting Ca;
equilibrates with all buffers and DM*)
MgT = 0.5 * 10^-3; (*total Mg in pipette*)
γ = 0.; (*Pump rate*)

(*Concentrations of dye, buffers, DM*)
OGtotal = 200. * 10^-6;
ATPtotal = 5. * 10^-3;
MBtotal = 480. * 10^-6; (*(*Delvendahl, PNAS, 2015*)*)

DMT = 2. * 10^-3; (*total concentration of DMn *)
(*uncaging efficiency*)
aStartDMN2 = 0.15;
aEndDMN2 = 0.55;

```

### definitions and loop

```

In[782]:= (*Dye*)
If[OGB1 == 1,
  kOnOG = 4.3 * 10^8;
  kOffOG = 103.;]

```

```

If[OGB5N == 1,
  kOnOG = 2.5 * 108;
  kOffOG = 6000.;]

If[OGB6F == 1,
  kOnOG = 3. * 108;
  kOffOG = 900.;]

If[Fluo5F == 1,
  kOnOG = 3. * 108;
  kOffOG = 249.;] (*Delvendahl PNAS; before: 432*)

KdOG = kOffOG / kOnOG;
kappaOG = OGtotal / KdOG;

(*ATP*)
kOnATP = 5. * 108;
kOffATP = 100 000.;
kOnMgATP = 1. * 107; (*Bollmann Dissertation S. 59; *)
kOffMgATP = 1000.;

KdATP = kOffATP / kOnATP;
kappaATP = ATPtotal / KdATP;
KdMgATP = kOffMgATP / kOnMgATP;

(*DM*)
If[MgT == 0.,
  kOnDM = 1.98 * 107; (*Faas Plos Biol, 2007*)
  kOffDM = 0.14;
  ,
  kOnDM = 2.9 * 107; (*Faas Biophys J, 2005*)
  kOffDM = 0.19;
]

(*Mg binding constants for DMn, DMf, DMs*)
kOnMg = 1.3 * 105; (*all values for Mg are from Faas et al., 2005*)
kOffMg = 0.2;

(*Ca binding constants for PP*)
kOnPP2 = kOnPP1 = kOnDM;
kOffPP2 = 3.6 * 103;
If[MgT == 0.,
  kOffPP1 = 7. * 104;;
  kOffPP1 = 6.9 * 104; ]

(*Mg binding constants for PP1,PP2*)

```

```

kOffMgPP = 3. * 10^2; (*for PP1,PP2*)
konMgPP = kOnMg; (*koMgPP not used in below diff. eq., only kOnMg*)

(*Equilibrium constants (not complete)*)
KdDM = kOffDM / kOnDM;
KdPP1 = kOffPP1 / kOnPP1;
KdMg = kOffMg / kOnMg;
kappaDM = DMT / KdDM;

(*Endogenous buffer*)
kOnMB = 5 * 10^8; (*Delvendahl, PNAS, 2015*)
kOffMB = 16000;
KdMB = kOffMB / kOnMB;

TRest = 1000.;

(*----- Loop -----
-----*)
(*----- Loop -----
-----*)
(*----- Loop -----
-----*)

For[aCount = 1, aCount ≤ aNumberDMN2, aCount += 1,
  a = 10^ (Log10[aStartDMN2] +
    (aCount - 1) * (Log10[aEndDMN2] - Log10[aStartDMN2]) / (aNumberDMN2 - 1));

  (*----- Resting
  Equations -----*)

  (*Dye*)
  OGRest := {

    OG[0] == OGtotal,
    CaOG[0] == 0,

    OG'[tt] == -kOnOG * CaRest * OG[tt] + kOffOG * CaOG[tt],
    CaOG'[tt] == kOnOG * CaRest * OG[tt] - kOffOG * CaOG[tt]
  }
;

  (*ATP*)
  ATPRest := {

    ATP[0] == ATPtotal,
    CaATP[0] == 0,

```

```

MgATP[0] == 0,

ATP'[tt] == -kOnATP * CaRest * ATP[tt] + kOffATP * CaATP[tt] -
  kOnMgATP * Mg[tt] * ATP[tt] + kOffMgATP * MgATP[tt],
CaATP'[tt] == kOnATP * CaRest * ATP[tt] - kOffATP * CaATP[tt],
MgATP'[tt] == kOnMgATP * Mg[tt] * ATP[tt] - kOffMgATP * MgATP[tt]

}

;

(*DM nitrophenene*)
DMnRest := {

  DMn[0] == (1 - a) * DMT,
  CaDMn[0] == 0.,
  MgDMn[0] == 0.,

  DMn'[tt] == -kOnDM * CaRest * DMn[tt] +
    kOffDM * CaDMn[tt] - kOnMg * Mg[tt] * DMn[tt] + kOffMg * MgDMn[tt],
  CaDMn'[tt] == kOnDM * CaRest * DMn[tt] - kOffDM * CaDMn[tt],
  MgDMn'[tt] == kOnMg * Mg[tt] * DMn[tt] - kOffMg * MgDMn[tt]

}

;

DMfRest := {

  DMf[0] == a * af * DMT,
  CaDMf[0] == 0.,
  MgDMf[0] == 0.,

  DMf'[tt] == -kOnDM * CaRest * DMf[tt] +
    kOffDM * CaDMf[tt] - kOnMg * Mg[tt] * DMf[tt] + kOffMg * MgDMf[tt],
  CaDMf'[tt] == kOnDM * CaRest * DMf[tt] - kOffDM * CaDMf[tt],
  MgDMf'[tt] == kOnMg * Mg[tt] * DMf[tt] - kOffMg * MgDMf[tt]

}

;

DMsRest := {

  DMs[0] == a * (1 - af) * DMT,
  CaDMs[0] == 0.,
  MgDMs[0] == 0.,

  DMs'[tt] == -kOnDM * CaRest * DMs[tt] +
    kOffDM * CaDMs[tt] - kOnMg * Mg[tt] * DMs[tt] + kOffMg * MgDMs[tt],
  CaDMs'[tt] == kOnDM * CaRest * DMs[tt] - kOffDM * CaDMs[tt],

```

```

    MgDMs'[tt] == kOnMg * Mg[tt] * DMs[tt] - kOffMg * MgDMs[tt]
  }
;

(*Endogeneous buffer*)
MBRest := {

  MB[0] == MBtotal,
  CaMB[0] == 0,

  MB'[tt] == -kOnMB * CaRest * MB[tt] + kOffMB * CaMB[tt],
  CaMB'[tt] == kOnMB * CaRest * MB[tt] - kOffMB * CaMB[tt]
}

;

(*Free Mg*)
MgfRest := {
  Mg[0] == MgT,

  Mg'[tt] ==
    -kOnMgATP * Mg[tt] * ATP[tt] + kOffMgATP * MgATP[tt]
    - kOnMg * Mg[tt] * DMn[tt] + kOffMg * MgDMn[tt]
    - kOnMg * Mg[tt] * DMf[tt] + kOffMg * MgDMf[tt]
    - kOnMg * Mg[tt] * DMs[tt] + kOffMg * MgDMs[tt]
}

;
EqRest := {ATPrest, MgfRest, OGRest, DMnRest, DMfRest, DMsRest, MBRest};
VarsRest := {ATP, Mg, CaATP, MgATP, CaOG, OG, DMn,
  CaDMn, MgDMn, DMf, CaDMf, MgDMf, DMs, CaDMs, MgDMs, MB, CaMB}
;
solr := NDSolve[EqRest, VarsRest, {tt, 0, TRest}]
;

Ca0 = CaRest;
Mg0 = Extract[Mg[TRest] /. solr, 1];
ATP0 = Extract[ATP[TRest] /. solr, 1];
CaATP0 = Extract[CaATP[TRest] /. solr, 1];
MgATP0 = Extract[MgATP[TRest] /. solr, 1];
OG0 = Extract[OG[TRest] /. solr, 1];
CaOG0 = Extract[CaOG[TRest] /. solr, 1];
DMn0 = Extract[DMn[TRest] /. solr, 1];
CaDMn0 = Extract[CaDMn[TRest] /. solr, 1];
MgDMn0 = Extract[MgDMn[TRest] /. solr, 1];
DMf0 = Extract[DMf[TRest] /. solr, 1];
CaDMf0 = Extract[CaDMf[TRest] /. solr, 1];

```

```

MgDMf0 = Extract[MgDMf[TRest] /. solr, 1];
DMs0 = Extract[DMs[TRest] /. solr, 1];
CaDMs0 = Extract[CaDMs[TRest] /. solr, 1];
MgDMs0 = Extract[MgDMs[TRest] /. solr, 1];
MB0 = Extract[MB[TRest] /. solr, 1];
CaMB0 = Extract[CaMB[TRest] /. solr, 1];

ClearAll[EqRest, VarsRest];

(*----- Flash
Equations -----*)

(*Dye*)
BufferOG := {

  OG[0] == OG0,
  CaOG[0] == CaOG0,

  OG'[tt] == -kOnOG * Ca[tt] * OG[tt] + kOffOG * CaOG[tt],
  CaOG'[tt] == kOnOG * Ca[tt] * OG[tt] - kOffOG * CaOG[tt]
};

(*ATP*)
BufferATP := {

  ATP[0] == ATP0,
  CaATP[0] == CaATP0,
  MgATP[0] == MgATP0,

  ATP'[tt] == -kOnATP * Ca[tt] * ATP[tt] + kOffATP * CaATP[tt] -
    kOnMgATP * Mg[tt] * ATP[tt] + kOffMgATP * MgATP[tt],
  CaATP'[tt] == kOnATP * Ca[tt] * ATP[tt] - kOffATP * CaATP[tt],
  MgATP'[tt] == kOnMgATP * Mg[tt] * ATP[tt] - kOffMgATP * MgATP[tt]
};

(*fast (tauf) and slow (taus) time constants for uncageing;
Faas et al., 2005,2007*)
If[MgT == 0.,
  tauf = 15.2 * 10^-6; (*Faas, 2007*)
  taus = 1.9 * 10^-3;
,
  tauf = 15. * 10^-6; (*Faas,2005*)
  taus = 2. * 10^-3; ]

```

```

;

(*The differential equations*)
(*non uncaging fraction of DMn*)
BufferDMn := {

  DMn[0] == DMn0,
  CaDMn[0] == CaDMn0,
  MgDMn[0] == MgDMn0,

  DMn'[tt] == -kOnDM * Ca[tt] * DMn[tt] +
    kOffDM * CaDMn[tt] - kOnMg * Mg[tt] * DMn[tt] + kOffMg * MgDMn[tt],
  CaDMn'[tt] == kOnDM * Ca[tt] * DMn[tt] - kOffDM * CaDMn[tt],
  MgDMn'[tt] == kOnMg * Mg[tt] * DMn[tt] - kOffMg * MgDMn[tt]
}

;

(*fast uncaging fraction of DMn*)
BufferDMf := {

  DMf[0] == DMf0,
  CaDMf[0] == CaDMf0,
  MgDMf[0] == MgDMf0,

  DMf'[tt] == -kOnDM * Ca[tt] * DMf[tt] + kOffDM * CaDMf[tt] - kOnMg * Mg[tt] *
    DMf[tt] + kOffMg * MgDMf[tt] - 1/tauf * DMf[tt] * UnitStep[tt - tflash],
  CaDMf'[tt] == kOnDM * Ca[tt] * DMf[tt] - kOffDM * CaDMf[tt] -
    1/tauf * CaDMf[tt] * UnitStep[tt - tflash],
  MgDMf'[tt] == kOnMg * Mg[tt] * DMf[tt] - kOffMg * MgDMf[tt] -
    1/tauf * MgDMf[tt] * UnitStep[tt - tflash]
}

;

(*slow uncaging fraction of DMn*)
BufferDMs := {

  DMs[0] == DMs0,
  CaDMs[0] == CaDMs0,
  MgDMs[0] == MgDMs0,

  DMs'[tt] == -kOnDM * Ca[tt] * DMs[tt] + kOffDM * CaDMs[tt] - kOnMg * Mg[tt] *
    DMs[tt] + kOffMg * MgDMs[tt] - 1/taus * DMs[tt] * UnitStep[tt - tflash],
  CaDMs'[tt] == kOnDM * Ca[tt] * DMs[tt] - kOffDM * CaDMs[tt] -
    1/taus * CaDMs[tt] * UnitStep[tt - tflash],
  MgDMs'[tt] == kOnMg * Mg[tt] * DMs[tt] - kOffMg * MgDMs[tt] -
    1/taus * MgDMs[tt] * UnitStep[tt - tflash]
}

```



;

(\*Photoproducts\*)

(\*PP2: comes from DMf,DMS and MgDMf,MgDMS; but also binds Ca\*)

BufferPP2 := {

PP2[0] == 0,

CaPP2[0] == 0,

MgPP2[0] == 0,

$$\begin{aligned} \text{PP2}'[tt] = & -k_{\text{OnPP2}} * \text{Ca}[tt] * \text{PP2}[tt] + k_{\text{OffPP2}} * \text{CaPP2}[tt] - \\ & k_{\text{OnMg}} * \text{Mg}[tt] * \text{PP2}[tt] + k_{\text{OffMgPP}} * \text{MgPP2}[tt] + 2 * (1 / \text{tauf} * \text{DMf}[tt] * \\ & \text{UnitStep}[tt - tflash] + 1 / \text{taus} * \text{DMS}[tt] * \text{UnitStep}[tt - tflash]) \\ & + 1 / \text{tauf} * \text{MgDMf}[tt] * \text{UnitStep}[tt - tflash] + \\ & 1 / \text{taus} * \text{MgDMS}[tt] * \text{UnitStep}[tt - tflash], \end{aligned}$$

$$\text{CaPP2}'[tt] = k_{\text{OnPP2}} * \text{Ca}[tt] * \text{PP2}[tt] - k_{\text{OffPP2}} * \text{CaPP2}[tt],$$

$$\begin{aligned} \text{MgPP2}'[tt] = & k_{\text{OnMg}} * \text{Mg}[tt] * \text{PP2}[tt] - k_{\text{OffMgPP}} * \text{MgPP2}[tt] + 1 / \text{tauf} * \\ & \text{MgDMf}[tt] * \text{UnitStep}[tt - tflash] + 1 / \text{taus} * \text{MgDMS}[tt] * \text{UnitStep}[tt - tflash] \end{aligned}$$

}

;

(\*PP1: Comes from CaDMf,CaDMS and binds Ca and Mg\*)

BufferPP1 := {

PP1[0] == 0,

CaPP1[0] == 0,

MgPP1[0] == 0,

$$\begin{aligned} \text{PP1}'[tt] = & -k_{\text{OnPP1}} * \text{Ca}[tt] * \text{PP1}[tt] + \\ & k_{\text{OffPP1}} * \text{CaPP1}[tt] - k_{\text{OnMg}} * \text{Mg}[tt] * \text{PP1}[tt] + k_{\text{OffMgPP}} * \text{MgPP1}[tt] \\ & + 1 / \text{tauf} * \text{CaDMf}[tt] * \text{UnitStep}[tt - tflash] + \\ & 1 / \text{taus} * \text{CaDMS}[tt] * \text{UnitStep}[tt - tflash], \end{aligned}$$

$$\begin{aligned} \text{CaPP1}'[tt] = & k_{\text{OnPP1}} * \text{Ca}[tt] * \text{PP1}[tt] - \\ & k_{\text{OffPP1}} * \text{CaPP1}[tt] + 1 / \text{tauf} * \text{CaDMf}[tt] * \text{UnitStep}[tt - tflash] + \\ & 1 / \text{taus} * \text{CaDMS}[tt] * \text{UnitStep}[tt - tflash], \end{aligned}$$

$$\text{MgPP1}'[tt] = k_{\text{OnMg}} * \text{Mg}[tt] * \text{PP1}[tt] - k_{\text{OffMgPP}} * \text{MgPP1}[tt]$$

}

;

(\*Endogeneous Buffer\*)

BufferMB := {

```

MB[0] == MB0,
CaMB[0] == CaMB0,

MB'[tt] == -kOnMB * Ca[tt] * MB[tt] + kOffMB * CaMB[tt],
CaMB'[tt] == kOnMB * Ca[tt] * MB[tt] - kOffMB * CaMB[tt]

```

```
;
```

```
(*Clear[Eqns,Vars,sol]*)
```

```
(*Free Ca*)
```

```
FreeCa := {
```

```
Ca[0] == Ca0,
```

```
Ca'[tt] == -γ * (Ca[tt] - CaRest)
```

```
(*DMn*)
```

```
- kOnPP1 * Ca[tt] * PP1[tt] + kOffPP1 * CaPP1[tt]
```

```
- kOnPP2 * Ca[tt] * PP2[tt] + kOffPP2 * CaPP2[tt]
```

```
- kOnDM * Ca[tt] * DMn[tt] + kOffDM * CaDMn[tt]
```

```
- kOnDM * Ca[tt] * DMf[tt] + kOffDM * CaDMf[tt]
```

```
- kOnDM * Ca[tt] * DMs[tt] + kOffDM * CaDMs[tt]
```

```
(*buffers*)
```

```
- kOnATP * Ca[tt] * ATP[tt] + kOffATP * CaATP[tt]
```

```
- kOnMB * Ca[tt] * MB[tt] + kOffMB * CaMB[tt]
```

```
(*dye*)
```

```
- kOnOG * Ca[tt] * OG[tt] + kOffOG * CaOG[tt]
```

```
}
```

```
;
```

```
(*Free Mg*)
```

```
FreeMg := {
```

```
Mg[0] == Mg0,
```

```
Mg'[tt] ==
```

```
- kOnMgATP * Mg[tt] * ATP[tt] + kOffMgATP * MgATP[tt]
```

```
- kOnMg * Mg[tt] * DMn[tt] + kOffMg * MgDMn[tt]
```

```
- kOnMg * Mg[tt] * DMf[tt] + kOffMg * MgDMf[tt]
```

```
- kOnMg * Mg[tt] * DMs[tt] + kOffMg * MgDMs[tt]
```

```
- kOnMg * Mg[tt] * PP2[tt] + kOffMgPP * MgPP2[tt]
```

```
- kOnMg * Mg[tt] * PP1[tt] + kOffMgPP * MgPP1[tt]
```

```
}
```

```
;
```

```
Eqns := {BufferDMn, BufferDMf, BufferDMs, BufferATP,
BufferPP1, BufferPP2, FreeCa, FreeMg, BufferMB, BufferOG}
```

```
;
```

```

Vars := {ATP, CaATP, MgATP, Ca, Mg, CaDMn, DMn, CaDMf, DMf, CaDMs,
  DMs, CaPP1, PP1, CaPP2, PP2, MgPP2, MgPP1, MB, CaMB, OG, CaOG}
;
sol := NDSolve[Eqns, Vars, {tt, 0., TimeWindow}
  (*,Method->{"EquationSimplification"->"Solve"}*)]
;
CafP = Extract[Ca[TimeWindow] /. sol, 1];
CafOG = KdOG * CaOG[tt] / OG[tt];

AppendTo[CaListReal, Evaluate[{Ca[tt]} /. sol]];
AppendTo[CaListDye, Evaluate[{CafOG} /. sol]];

];

```

## 10 mM DMN

### general parameters

```

In[812]:= TimeWindow = 0.006; (*End of simulation*)
tflash = 0.0; (*Time of flash*)
PlStart = 0.; (*Plot start*)

af = 0.67; (*fast uncaging fraction; Faas et al*)

(*Select dye*)
OGB1 = 0;
OGB5N = 1;
OGB6F = 0;
Fluo5F = 0;

CaRest = 227. * 10^-9; (*Free pre-flash resting Ca;
  equilibrates with all buffers and DM*)
MgT = 0.5 * 10^-3; (*total Mg in pipette*)
γ = 0.; (*Pump rate*)

(*Concentrations of dye, buffers, DM*)
OGtotal = 200. * 10^-6;
ATPtotal = 5. * 10^-3;
MBtotal = 480. * 10^-6; (*(*Delvendahl, PNAS, 2015*)*)

DMT = 10. * 10^-3; (*total concentration of DMn *)
(*uncaging efficiency*)
aStartDMN10 = 0.14;
aEndDMN10 = 0.25;

```

## definitions and loop

```

ln[829]:= (*Dye*)
  If[OGB1 == 1,
    kOnOG =  $4.3 \cdot 10^8$ ;
    kOffOG = 103.;]

  If[OGB5N == 1,
    kOnOG =  $2.5 \cdot 10^8$ ;
    kOffOG = 6000.;]

  If[OGB6F == 1,
    kOnOG =  $3. \cdot 10^8$ ;
    kOffOG = 900.;]

  If[Fluo5F == 1,
    kOnOG =  $3. \cdot 10^8$ ;
    kOffOG = 249.;] (*Delvendahl PNAS; before: 432*)

  KdOG = kOffOG/kOnOG;
  kappaOG = OGtotal/KdOG;

  (*ATP*)
  kOnATP =  $5. \cdot 10^8$ ;
  kOffATP = 100000.;
  kOnMgATP =  $1. \cdot 10^7$ ; (*Bollmann Dissertation S. 59; *)
  kOffMgATP = 1000.;

  KdATP = kOffATP/kOnATP;
  kappaATP = ATPtotal/KdATP;
  KdMgATP = kOffMgATP/kOnMgATP;

  (*DM*)
  If[MgT == 0.,
    kOnDM =  $1.98 \cdot 10^7$ ; (*Faas Plos Biol, 2007*)
    kOffDM = 0.14;
    ,
    kOnDM =  $2.9 \cdot 10^7$ ; (*Faas Biophys J, 2005*)
    kOffDM = 0.19;
  ]

  (*Mg binding constants for DMn, DMf, DMs*)
  kOnMg =  $1.3 \cdot 10^5$ ; (*all values for Mg are from Faas et al., 2005*)
  kOffMg = 0.2;

```

```

(*Ca binding constants for PP*)
kOnPP2 = kOnPP1 = kOnDM;
kOffPP2 = 3.6 * 10^3;
If[MgT == 0.,
  kOffPP1 = 7. * 10^4;,
  kOffPP1 = 6.9 * 10^4; ]

(*Mg binding constants for PP1,PP2*)
kOffMgPP = 3. * 10^2; (*for PP1,PP2*)
konMgPP = kOnMg; (*koMgPP not used in below diff. eq., only kOnMg*)

(*Equilibrium constants (not complete)*)
KdDM = kOffDM / kOnDM;
KdPP1 = kOffPP1 / kOnPP1;
KdMg = kOffMg / kOnMg;
kappaDM = DMT / KdDM;

(*Endogenous buffer*)
kOnMB = 5 * 10^8; (*Delvendahl, PNAS, 2015*)
kOffMB = 16 000;
KdMB = kOffMB / kOnMB;

TRest = 1000.;

(*----- Loop -----
-----*)
(*----- Loop -----
-----*)
(*----- Loop -----
-----*)

For[aCount = 1, aCount ≤ aNumberDMN10, aCount += 1,
  a = 10^ (Log10[aStartDMN10] +
    (aCount - 1) * (Log10[aEndDMN10] - Log10[aStartDMN10]) / (aNumberDMN10 - 1));

  (*----- Resting
  Equations -----*)

  (*Dye*)
  OGRest := {

    OG[0] == OGtotal,
    CaOG[0] == 0,

    OG'[tt] == -kOnOG * CaRest * OG[tt] + kOffOG * CaOG[tt],
    CaOG'[tt] == kOnOG * CaRest * OG[tt] - kOffOG * CaOG[tt]
  }

```

```

    }
;

(*ATP*)
ATPrest := {

    ATP[0] == ATPtotal,
    CaATP[0] == 0,
    MgATP[0] == 0,

    ATP'[tt] == -kOnATP * CaRest * ATP[tt] + kOffATP * CaATP[tt] -
        kOnMgATP * Mg[tt] * ATP[tt] + kOffMgATP * MgATP[tt],
    CaATP'[tt] == kOnATP * CaRest * ATP[tt] - kOffATP * CaATP[tt],
    MgATP'[tt] == kOnMgATP * Mg[tt] * ATP[tt] - kOffMgATP * MgATP[tt]

}

;

(*DM nitrophenene*)
DMnRest := {

    DMn[0] == (1 - a) * DMT,
    CaDMn[0] == 0.,
    MgDMn[0] == 0.,

    DMn'[tt] == -kOnDM * CaRest * DMn[tt] +
        kOffDM * CaDMn[tt] - kOnMg * Mg[tt] * DMn[tt] + kOffMg * MgDMn[tt],
    CaDMn'[tt] == kOnDM * CaRest * DMn[tt] - kOffDM * CaDMn[tt],
    MgDMn'[tt] == kOnMg * Mg[tt] * DMn[tt] - kOffMg * MgDMn[tt]

}

;

DMfRest := {

    DMf[0] == a * af * DMT,
    CaDMf[0] == 0.,
    MgDMf[0] == 0.,

    DMf'[tt] == -kOnDM * CaRest * DMf[tt] +
        kOffDM * CaDMf[tt] - kOnMg * Mg[tt] * DMf[tt] + kOffMg * MgDMf[tt],
    CaDMf'[tt] == kOnDM * CaRest * DMf[tt] - kOffDM * CaDMf[tt],
    MgDMf'[tt] == kOnMg * Mg[tt] * DMf[tt] - kOffMg * MgDMf[tt]

}

;

DMsRest := {

```

```

DMS[0] == a * (1 - af) * DMT,
CaDMs[0] == 0.,
MgDMs[0] == 0.,

DMS'[tt] == -kOnDM * CaRest * DMS[tt] +
  kOffDM * CaDMs[tt] - kOnMg * Mg[tt] * DMS[tt] + kOffMg * MgDMs[tt],
CaDMs'[tt] == kOnDM * CaRest * DMS[tt] - kOffDM * CaDMs[tt],
MgDMs'[tt] == kOnMg * Mg[tt] * DMS[tt] - kOffMg * MgDMs[tt]
}
;

(*Endogeneous buffer*)
MBRest := {

  MB[0] == MBtotal,
  CaMB[0] == 0,

  MB'[tt] == -kOnMB * CaRest * MB[tt] + kOffMB * CaMB[tt],
  CaMB'[tt] == kOnMB * CaRest * MB[tt] - kOffMB * CaMB[tt]
}

;

(*Free Mg*)
MgfRest := {
  Mg[0] == MgT,

  Mg'[tt] ==
    -kOnMgATP * Mg[tt] * ATP[tt] + kOffMgATP * MgATP[tt]
    - kOnMg * Mg[tt] * DMn[tt] + kOffMg * MgDMn[tt]
    - kOnMg * Mg[tt] * DMf[tt] + kOffMg * MgDMf[tt]
    - kOnMg * Mg[tt] * DMS[tt] + kOffMg * MgDMs[tt]
}

;
EqRest := {ATPrest, MgfRest, OGRest, DMnRest, DMfRest, DMSrest, MBRest};
VarsRest := {ATP, Mg, CaATP, MgATP, CaOG, OG, DMn,
  CaDMn, MgDMn, DMf, CaDMf, MgDMf, DMS, CaDMs, MgDMs, MB, CaMB}
;
solr := NDSolve[EqRest, VarsRest, {tt, 0, TRest}]
;

Ca0 = CaRest;
Mg0 = Extract[Mg[TRest] /. solr, 1];
ATP0 = Extract[ATP[TRest] /. solr, 1];
CaATP0 = Extract[CaATP[TRest] /. solr, 1];

```

```

MgATP0 = Extract[MgATP[TRest] /. solr, 1];
OG0 = Extract[OG[TRest] /. solr, 1];
CaOG0 = Extract[CaOG[TRest] /. solr, 1];
DMn0 = Extract[DMn[TRest] /. solr, 1];
CaDMn0 = Extract[CaDMn[TRest] /. solr, 1];
MgDMn0 = Extract[MgDMn[TRest] /. solr, 1];
DMf0 = Extract[DMf[TRest] /. solr, 1];
CaDMf0 = Extract[CaDMf[TRest] /. solr, 1];
MgDMf0 = Extract[MgDMf[TRest] /. solr, 1];
DMs0 = Extract[DMs[TRest] /. solr, 1];
CaDMs0 = Extract[CaDMs[TRest] /. solr, 1];
MgDMs0 = Extract[MgDMs[TRest] /. solr, 1];
MB0 = Extract[MB[TRest] /. solr, 1];
CaMB0 = Extract[CaMB[TRest] /. solr, 1];

ClearAll[EqRest, VarsRest];

(*----- Flash
Equations -----*)

(*Dye*)
BufferOG := {

  OG[0] == OG0,
  CaOG[0] == CaOG0,

  OG'[tt] == -kOnOG * Ca[tt] * OG[tt] + kOffOG * CaOG[tt],
  CaOG'[tt] == kOnOG * Ca[tt] * OG[tt] - kOffOG * CaOG[tt]}
;

(*ATP*)
BufferATP := {

  ATP[0] == ATP0,
  CaATP[0] == CaATP0,
  MgATP[0] == MgATP0,

  ATP'[tt] == -kOnATP * Ca[tt] * ATP[tt] + kOffATP * CaATP[tt] -
    kOnMgATP * Mg[tt] * ATP[tt] + kOffMgATP * MgATP[tt],
  CaATP'[tt] == kOnATP * Ca[tt] * ATP[tt] - kOffATP * CaATP[tt],
  MgATP'[tt] == kOnMgATP * Mg[tt] * ATP[tt] - kOffMgATP * MgATP[tt]
}
;

(*fast (tauf) and slow (taus) time constants for uncageing;

```



```

Faas et al., 2005,2007*)
If[MgT == 0.,
  tauf = 15.2 * 10^-6; (*Faas, 2007*)
  taus = 1.9 * 10^-3;
,
  tauf = 15. * 10^-6; (*Faas,2005*)
  taus = 2. * 10^-3; ]

;

(*The differential equations*)
(*non uncaging fraction of DMn*)
BufferDMn := {

  DMn[0] == DMn0,
  CaDMn[0] == CaDMn0,
  MgDMn[0] == MgDMn0,

  DMn'[tt] == -kOnDM * Ca[tt] * DMn[tt] +
    kOffDM * CaDMn[tt] - kOnMg * Mg[tt] * DMn[tt] + kOffMg * MgDMn[tt],
  CaDMn'[tt] == kOnDM * Ca[tt] * DMn[tt] - kOffDM * CaDMn[tt],
  MgDMn'[tt] == kOnMg * Mg[tt] * DMn[tt] - kOffMg * MgDMn[tt]
}

;

(*fast uncaging fraction of DMn*)
BufferDMf := {

  DMf[0] == DMf0,
  CaDMf[0] == CaDMf0,
  MgDMf[0] == MgDMf0,

  DMf'[tt] == -kOnDM * Ca[tt] * DMf[tt] + kOffDM * CaDMf[tt] - kOnMg * Mg[tt] *
    DMf[tt] + kOffMg * MgDMf[tt] - 1/tauf * DMf[tt] * UnitStep[tt - tflash],
  CaDMf'[tt] == kOnDM * Ca[tt] * DMf[tt] - kOffDM * CaDMf[tt] -
    1/tauf * CaDMf[tt] * UnitStep[tt - tflash],
  MgDMf'[tt] == kOnMg * Mg[tt] * DMf[tt] - kOffMg * MgDMf[tt] -
    1/tauf * MgDMf[tt] * UnitStep[tt - tflash]
}

;

(*slow uncaging fraction of DMn*)
BufferDMS := {

  DMS[0] == DMS0,
  CaDMS[0] == CaDMS0,
  MgDMS[0] == MgDMS0,

```

```

DMS'[tt] == -kOnDM * Ca[tt] * DMS[tt] + kOffDM * CaDMS[tt] - kOnMg * Mg[tt] *
  DMS[tt] + kOffMg * MgDMS[tt] - 1 / taus * DMS[tt] * UnitStep[tt - tflash],
CaDMS'[tt] == kOnDM * Ca[tt] * DMS[tt] - kOffDM * CaDMS[tt] -
  1 / taus * CaDMS[tt] * UnitStep[tt - tflash],
MgDMS'[tt] == kOnMg * Mg[tt] * DMS[tt] - kOffMg * MgDMS[tt] -
  1 / taus * MgDMS[tt] * UnitStep[tt - tflash]
}
;

(*Photoproducts*)
(*PP2: comes from DMf,DMS and MgDMf,MgDMS; but also binds Ca*)
BufferPP2 := {

  PP2[0] == 0,
  CaPP2[0] == 0,
  MgPP2[0] == 0,

  PP2'[tt] == -kOnPP2 * Ca[tt] * PP2[tt] + kOffPP2 * CaPP2[tt] -
    kOnMg * Mg[tt] * PP2[tt] + kOffMgPP * MgPP2[tt] + 2 * (1 / tauF * DMf[tt] *
      UnitStep[tt - tflash] + 1 / taus * DMS[tt] * UnitStep[tt - tflash])
    + 1 / tauF * MgDMf[tt] * UnitStep[tt - tflash] +
    1 / taus * MgDMS[tt] * UnitStep[tt - tflash],

  CaPP2'[tt] == kOnPP2 * Ca[tt] * PP2[tt] - kOffPP2 * CaPP2[tt],

  MgPP2'[tt] == kOnMg * Mg[tt] * PP2[tt] - kOffMgPP * MgPP2[tt] + 1 / tauF *
    MgDMf[tt] * UnitStep[tt - tflash] + 1 / taus * MgDMS[tt] * UnitStep[tt - tflash]
}
;

(*PP1: Comes from CaDMf,CaDMS and binds Ca and Mg*)
BufferPP1 := {

  PP1[0] == 0,
  CaPP1[0] == 0,
  MgPP1[0] == 0,

  PP1'[tt] == -kOnPP1 * Ca[tt] * PP1[tt] +
    kOffPP1 * CaPP1[tt] - kOnMg * Mg[tt] * PP1[tt] + kOffMgPP * MgPP1[tt]
    + 1 / tauF * CaDMf[tt] * UnitStep[tt - tflash] +
    1 / taus * CaDMS[tt] * UnitStep[tt - tflash],

  CaPP1'[tt] == kOnPP1 * Ca[tt] * PP1[tt] -
    kOffPP1 * CaPP1[tt] + 1 / tauF * CaDMf[tt] * UnitStep[tt - tflash] +
    1 / taus * CaDMS[tt] * UnitStep[tt - tflash],

```

```

MgPP1'[tt] == kOnMg * Mg[tt] * PP1[tt] - kOffMgPP * MgPP1[tt]

}
;

(*Endogeneous Buffer*)
BufferMB := {

  MB[0] == MB0,
  CaMB[0] == CaMB0,

  MB'[tt] == -kOnMB * Ca[tt] * MB[tt] + kOffMB * CaMB[tt],
  CaMB'[tt] == kOnMB * Ca[tt] * MB[tt] - kOffMB * CaMB[tt]

}

;

(*Clear[Eqns,Vars,sol]*)

(*Free Ca*)
FreeCa := {
  Ca[0] == Ca0,

  Ca'[tt] == -γ * (Ca[tt] - CaRest)
  (*DMn*)
  - kOnPP1 * Ca[tt] * PP1[tt] + kOffPP1 * CaPP1[tt]
  - kOnPP2 * Ca[tt] * PP2[tt] + kOffPP2 * CaPP2[tt]
  - kOnDM * Ca[tt] * DMn[tt] + kOffDM * CaDMn[tt]
  - kOnDM * Ca[tt] * DMf[tt] + kOffDM * CaDMf[tt]
  - kOnDM * Ca[tt] * DMs[tt] + kOffDM * CaDMs[tt]
  (*buffers*)
  - kOnATP * Ca[tt] * ATP[tt] + kOffATP * CaATP[tt]
  - kOnMB * Ca[tt] * MB[tt] + kOffMB * CaMB[tt]
  (*dye*)
  - kOnOG * Ca[tt] * OG[tt] + kOffOG * CaOG[tt]
}
;

(*Free Mg*)
FreeMg := {
  Mg[0] == Mg0,

  Mg'[tt] ==
  - kOnMgATP * Mg[tt] * ATP[tt] + kOffMgATP * MgATP[tt]
  - kOnMg * Mg[tt] * DMn[tt] + kOffMg * MgDMn[tt]
  - kOnMg * Mg[tt] * DMf[tt] + kOffMg * MgDMf[tt]
  - kOnMg * Mg[tt] * DMs[tt] + kOffMg * MgDMs[tt]
  - kOnMg * Mg[tt] * PP2[tt] + kOffMgPP * MgPP2[tt]
}

```

```

      - kOnMg * Mg[tt] * PP1[tt] + kOffMgPP * MgPP1[tt]
    }

;

Eqns := {BufferDMn, BufferDMf, BufferDMs, BufferATP,
        BufferPP1, BufferPP2, FreeCa, FreeMg, BufferMB, BufferOG}
;
Vars := {ATP, CaATP, MgATP, Ca, Mg, CaDMn, DMn, CaDMf, DMf, CaDMs,
        DMs, CaPP1, PP1, CaPP2, PP2, MgPP2, MgPP1, MB, CaMB, OG, CaOG}
;
sol := NDSolve[Eqns, Vars, {tt, 0., TimeWindow}
  (*,Method->{"EquationSimplification"->"Solve"}*)]
;
CafP = Extract[Ca[TimeWindow] /. sol, 1];
CafOG = KdOG * CaOG[tt] / OG[tt];

AppendTo[CaListReal, Evaluate[{Ca[tt]} /. sol]];
AppendTo[CaListDye, Evaluate[{CafOG} /. sol]];
];




```


## Plot and further processing

```

In[859]:= Plot[10^6 * CaListReal, {tt, 0, TimeWindow}, PlotLabel -> "Real free Ca (μM)"]
Plot[10^6 * CaListDye, {tt, 0, TimeWindow},
  PlotLabel -> "Free Ca reported by dye (μM)"]
LogPlot[10^6 * CaListReal, {tt, 0, TimeWindow}, PlotLabel -> "Real free Ca (μM)"]
LogPlot[10^6 * CaListDye, {tt, 0, TimeWindow},
  PlotLabel -> "Free Ca reported by dye (μM)"]
CaListDyePeak =
  Table[NMaximize[{CaListDye[[nn]][[1]][[1]], 0 ≤ tt ≤ TimeWindow}, tt][[1]],
    {nn, Length[CaListDye]}]
  (*"[1][1]" is needed to get rid of these brackets {}*)

```





Out[863]=  $\{7.03073 \times 10^{-7}, 4.79194 \times 10^{-6}, 5.53376 \times 10^{-6}, 0.0000257412, 0.0000299583, 0.0000740312\}$

In[864]:= runs = Length[CaListDyePeak];

## Release scheme and start values

### Define release scheme

In[865]:= nStates = 7;  
mat = Table[0, {nStates}, {nStates}];

## forward rates

```

ln[867]:= from = 1; (*0 ca bound*)
kk = 5 kon;
mat[[from + 1, from]] += kk; mat[[from, from]] += -kk;

from = 2;
kk = 4 kon;
mat[[from + 1, from]] += kk; mat[[from, from]] += -kk;

from = 3;
kk = 3 kon;
mat[[from + 1, from]] += kk; mat[[from, from]] += -kk;

from = 4;
kk = 2 kon;
mat[[from + 1, from]] += kk; mat[[from, from]] += -kk;

from = 5; (*4 ca bound*)
kk = kon;
mat[[from + 1, from]] += kk; mat[[from, from]] += -kk;

from = 6; (*5 ca bound*)
kk = gamma;
mat[[from + 1, from]] += kk; mat[[from, from]] += -kk;

```

## backwards rates

```
In[885]:= from = 2; (*1 ca bound*)
kk = koff b^0;
mat[[from - 1, from]] += kk; mat[[from, from]] += -kk;

from = 3;
kk = 2 koff b^1;
mat[[from - 1, from]] += kk; mat[[from, from]] += -kk;

from = 4;
kk = 3 koff b^2;
mat[[from - 1, from]] += kk; mat[[from, from]] += -kk;

from = 5;
kk = 4 koff b^3;
mat[[from - 1, from]] += kk; mat[[from, from]] += -kk;

from = 6; (*5 ca bound*)
kk = 5 koff b^4;
mat[[from - 1, from]] += kk; mat[[from, from]] += -kk;
```

## outflux from matrix

```
In[900]:= mat[[1, 1]] += -kunfill; (* is multiplied by ss1[t] *)
```

## influx in matrix

```
In[901]:= mat[[1, 1]] += (1 / ss1[t]) kfill fillStateSS[t];
(* (1/ss1[t]) is needed to merge the fillState
Diff Eq. in the matrix format. Note ss1[t] is never 0 *)
```

## Matrix

```
In[902]:= mat // TableForm
Out[902]//TableForm=
```

$-5 \text{ kon} - \text{kunfill} + \frac{\text{kfill fillStateSS[t]}}{\text{ss1[t]}}$	koff	0	0
5 kon	$-\text{koff} - 4 \text{ kon}$	2 b koff	0
0	4 kon	$-2 \text{ b koff} - 3 \text{ kon}$	$3 \text{ b}^2 \text{ koff}$
0	0	3 kon	$-3 \text{ b}^2 \text{ koff} - 2 \text{ kon}$
0	0	0	2 kon
0	0	0	0
0	0	0	0



---

## Startvalues

```
In[903]:= linInterpol[x_, a_, b_] := a + x * (b - a);
```

```
In[904]:= q10 = 2.3;  
tempFact = q10 ^ ((37 - 24) / 10);
```

```

In[906]:= Clear[caFunc, kprimScheme];
(*Clear is needed if the cell is executed for a 2nd time when
caFunc is already set to a value or an Interpolationfunction*)

caRest = CaRest; (*227nM see above*)

affinityFactor = 3.0;
konScheme = linInterpol[sitePlugging[t],
  caFunc[t] Sqrt[affinityFactor] tempFact 1.*^8,
  0.1 caFunc[t] Sqrt[affinityFactor] tempFact 1.*^8
]; (*M^-1 s^-1*)

koffScheme = linInterpol[sitePlugging[t],
  (1/Sqrt[affinityFactor]) tempFact 15 000,
  0.4 (1/Sqrt[affinityFactor]) tempFact 15 000
]; (*s^-1*)
gammaScheme = tempFact 6000; (*s^-1*)
bScheme = 0.25;

KdPrim = 2.*^-6;
kprimScheme = 2.5 + 60. (caFunc[t] / (KdPrim + caFunc[t]));
kunprimScheme = 2.5 + 60. (caRest / (KdPrim + caRest));

KdFill = 2.*^-6;
kfillScheme = 100 + 800. (caFunc[t] / (KdFill + caFunc[t]));
kunfillScheme = 100 + 800. (caRest / (KdFill + caRest));

repl = {
  kon → konScheme,
  koff → koffScheme ,
  gamma → gammaScheme ,
  b → bScheme,

  kprim → kprimScheme ,
  kunprim → kunprimScheme ,

  kfill → kfillScheme ,
  kunfill → kunfillScheme

  (*
  kbasal → kbasalScheme ,
  kunfill → kunfillScheme
  *)
};

In[920]:= tauOfDecayOfUncagedCa = 0.4;

```

```
In[921]:= siteClearanceTau = 0.04;
```

## Initial occupancy


```
In[922]:= (*test initial equilibrium occupancy*)
caFunc[t_] := caTmp;
fillStateSSInitial = kprimScheme / kunprimScheme;
ss0Initial = fillStateSSInitial * kfillScheme / kunfillScheme;
(ss0Initial /. caTmp → 180*^-9)
(ss0Initial /. caTmp → 50*^-9)
(ss0Initial /. caTmp → 30*^-9)
(ss0Initial /. caTmp → 180*^-9) / (ss0Initial /. caTmp → 30*^-9)
(*test initial *)
Plot[kprimScheme / kunprimScheme, {caTmp, 0, 300*^-9}]
Plot[kfillScheme / kunfillScheme, {caTmp, 0, 300*^-9}]
LogLinearPlot[{kprimScheme / kunprimScheme, kfillScheme / kunfillScheme},
  {caTmp, .1*^-9, 30*^-6}, PlotRange → All]
Plot[{kprimScheme / kunprimScheme, kfillScheme / kunfillScheme},
  {caTmp, .1*^-9, 1*^-6}, PlotRange → All]
```




```
Out[925]= 0.791348
```

```
Out[926]= 0.302831
```

```
Out[927]= 0.242117
```

```
Out[928]= 3.26845
```





```

In[933]:= (*calualte initial equilibrium occupancy*)
caFunc[t_] := caRest;
kprimScheme
kunprimScheme
fillStateSSInitial = kprimScheme / kunprimScheme
kfillScheme
kunfillScheme
ss0Initial = fillStateSSInitial * kfillScheme / kunfillScheme

Out[934]= 8.61585

Out[935]= 8.61585

Out[936]= 1.

Out[937]= 181.545

Out[938]= 181.545

Out[939]= 1.

In[940]:= caRest
Out[940]=  $2.27 \times 10^{-7}$ 

```

---

## Diff eq.

```

In[941]:= Clear[caFunc, eq]; (*Clear is needed if the cell is exected for a 2nd time
when caFunc is already set to a value or an Interpolationfunction*)
ss[t_] = {ss1[t], ss2[t], ss3[t], ss4[t], ss5[t], ss6[t], ss7[t]};
eq = {ss'[t] == (mat /. repl).ss[t],
      ss[0] == {ss0Initial, 0., 0., 0., 0., 0., 0.},
      (fillStateSS'[t] == kprim - kunprim fillStateSS[t] -
        kfill fillStateSS[t] + kunfill ss1[t]) /. repl,
      fillStateSS[0] == fillStateSSInitial,
      sitePlugging'[t] ==
        (1 - sitePlugging[t]) ss7'[t] - siteClearanceTau sitePlugging[t],
      sitePlugging[0] == 0
    };

```

## Print diff eq.

In[944]:= **mat**

Out[944]=  $\left\{ \left\{ -5 \text{kon} - \text{kunfill} + \frac{\text{kfill fillStateSS}[t]}{\text{ss1}[t]}, \text{koff}, 0, 0, 0, 0, 0 \right\}, \right.$   
 $\left. \left\{ 5 \text{kon}, -\text{koff} - 4 \text{kon}, 2 \text{b koff}, 0, 0, 0, 0 \right\}, \right.$   
 $\left. \left\{ 0, 4 \text{kon}, -2 \text{b koff} - 3 \text{kon}, 3 \text{b}^2 \text{koff}, 0, 0, 0 \right\}, \right.$   
 $\left. \left\{ 0, 0, 3 \text{kon}, -3 \text{b}^2 \text{koff} - 2 \text{kon}, 4 \text{b}^3 \text{koff}, 0, 0 \right\}, \right.$   
 $\left. \left\{ 0, 0, 0, 2 \text{kon}, -4 \text{b}^3 \text{koff} - \text{kon}, 5 \text{b}^4 \text{koff}, 0 \right\}, \right.$   
 $\left. \left\{ 0, 0, 0, 0, \text{kon}, -\text{gamma} - 5 \text{b}^4 \text{koff}, 0 \right\}, \left\{ 0, 0, 0, 0, 0, \text{gamma}, 0 \right\} \right\}$

In[945]:= **repl**

Out[945]=  $\left\{ \text{kon} \rightarrow 5.11454 \times 10^8 \text{caFunc}[t] - 4.60309 \times 10^8 \text{caFunc}[t] \times \text{sitePlugging}[t], \right.$   
 $\text{koff} \rightarrow 25572.7 - 15343.6 \text{sitePlugging}[t], \text{gamma} \rightarrow 17717.3,$   
 $\text{b} \rightarrow 0.25, \text{kprim} \rightarrow 2.5 + \frac{60. \text{caFunc}[t]}{2. \times 10^{-6} + \text{caFunc}[t]}, \text{kunprim} \rightarrow 8.61585,$   
 $\text{kfill} \rightarrow 100 + \frac{800. \text{caFunc}[t]}{2. \times 10^{-6} + \text{caFunc}[t]}, \text{kunfill} \rightarrow 181.545 \}$

In[946]:= **mat /. repl**

Out[946]=  $\left\{ \left\{ -181.545 - 5 \left( 5.11454 \times 10^8 \text{caFunc}[t] - 4.60309 \times 10^8 \text{caFunc}[t] \times \text{sitePlugging}[t] \right) + \right.$   
 $\left. \frac{\left( 100 + \frac{800. \text{caFunc}[t]}{2. \times 10^{-6} + \text{caFunc}[t]} \right) \text{fillStateSS}[t]}{\text{ss1}[t]}, \right.$   
 $25572.7 - 15343.6 \text{sitePlugging}[t], 0, 0, 0, 0, 0 \},$   
 $\left\{ 5 \left( 5.11454 \times 10^8 \text{caFunc}[t] - 4.60309 \times 10^8 \text{caFunc}[t] \times \text{sitePlugging}[t] \right), \right.$   
 $-25572.7 + 15343.6 \text{sitePlugging}[t] -$   
 $4 \left( 5.11454 \times 10^8 \text{caFunc}[t] - 4.60309 \times 10^8 \text{caFunc}[t] \times \text{sitePlugging}[t] \right),$   
 $0.5 \left( 25572.7 - 15343.6 \text{sitePlugging}[t] \right), 0, 0, 0, 0 \},$   
 $\left\{ 0, 4 \left( 5.11454 \times 10^8 \text{caFunc}[t] - 4.60309 \times 10^8 \text{caFunc}[t] \times \text{sitePlugging}[t] \right), \right.$   
 $-0.5 \left( 25572.7 - 15343.6 \text{sitePlugging}[t] \right) -$   
 $3 \left( 5.11454 \times 10^8 \text{caFunc}[t] - 4.60309 \times 10^8 \text{caFunc}[t] \times \text{sitePlugging}[t] \right),$   
 $0.1875 \left( 25572.7 - 15343.6 \text{sitePlugging}[t] \right), 0, 0, 0 \},$   
 $\left\{ 0, 0, 3 \left( 5.11454 \times 10^8 \text{caFunc}[t] - 4.60309 \times 10^8 \text{caFunc}[t] \times \text{sitePlugging}[t] \right), \right.$   
 $-0.1875 \left( 25572.7 - 15343.6 \text{sitePlugging}[t] \right) -$   
 $2 \left( 5.11454 \times 10^8 \text{caFunc}[t] - 4.60309 \times 10^8 \text{caFunc}[t] \times \text{sitePlugging}[t] \right),$   
 $0.0625 \left( 25572.7 - 15343.6 \text{sitePlugging}[t] \right), 0, 0 \},$   
 $\left\{ 0, 0, 0, 2 \left( 5.11454 \times 10^8 \text{caFunc}[t] - 4.60309 \times 10^8 \text{caFunc}[t] \times \text{sitePlugging}[t] \right), \right.$   
 $-5.11454 \times 10^8 \text{caFunc}[t] - 0.0625 \left( 25572.7 - 15343.6 \text{sitePlugging}[t] \right) +$   
 $4.60309 \times 10^8 \text{caFunc}[t] \times \text{sitePlugging}[t],$   
 $0.0195313 \left( 25572.7 - 15343.6 \text{sitePlugging}[t] \right), 0 \},$   
 $\left\{ 0, 0, 0, 0, 5.11454 \times 10^8 \text{caFunc}[t] - 4.60309 \times 10^8 \text{caFunc}[t] \times \text{sitePlugging}[t], \right.$   
 $-17717.3 - 0.0195313 \left( 25572.7 - 15343.6 \text{sitePlugging}[t] \right), 0 \},$   
 $\left. \left\{ 0, 0, 0, 0, 0, 17717.3, 0 \right\} \right\}$

In[947]:= eq

```

Out[947]= { {ss1'[t], ss2'[t], ss3'[t], ss4'[t], ss5'[t], ss6'[t], ss7'[t]} ==
  {
    -181.545 - 5 (5.11454 × 108 caFunc[t] - 4.60309 × 108 caFunc[t] × sitePlugging[t]) +
    
$$\left( \frac{100 + \frac{800 \cdot \text{caFunc}[t]}{2 \times 10^{-6} + \text{caFunc}[t]}}{\text{ss1}[t]} \right) \text{fillStateSS}[t] \Bigg) \text{ss1}[t] +$$


    (25572.7 - 15343.6 sitePlugging[t]) ss2[t],
    5 (5.11454 × 108 caFunc[t] - 4.60309 × 108 caFunc[t] × sitePlugging[t]) ss1[t] +
    (-25572.7 + 15343.6 sitePlugging[t] -
      4 (5.11454 × 108 caFunc[t] - 4.60309 × 108 caFunc[t] × sitePlugging[t]))
    ss2[t] + 0.5 (25572.7 - 15343.6 sitePlugging[t]) ss3[t],
    4 (5.11454 × 108 caFunc[t] - 4.60309 × 108 caFunc[t] × sitePlugging[t]) ss2[t] +
    (-0.5 (25572.7 - 15343.6 sitePlugging[t]) -
      3 (5.11454 × 108 caFunc[t] - 4.60309 × 108 caFunc[t] × sitePlugging[t]))
    ss3[t] + 0.1875 (25572.7 - 15343.6 sitePlugging[t]) ss4[t],
    3 (5.11454 × 108 caFunc[t] - 4.60309 × 108 caFunc[t] × sitePlugging[t]) ss3[t] +
    (-0.1875 (25572.7 - 15343.6 sitePlugging[t]) -
      2 (5.11454 × 108 caFunc[t] - 4.60309 × 108 caFunc[t] × sitePlugging[t]))
    ss4[t] + 0.0625 (25572.7 - 15343.6 sitePlugging[t]) ss5[t],
    2 (5.11454 × 108 caFunc[t] - 4.60309 × 108 caFunc[t] × sitePlugging[t]) ss4[t] +
    (-5.11454 × 108 caFunc[t] - 0.0625 (25572.7 - 15343.6 sitePlugging[t]) +
      4.60309 × 108 caFunc[t] × sitePlugging[t]) ss5[t] +
    0.0195313 (25572.7 - 15343.6 sitePlugging[t]) ss6[t],
    (5.11454 × 108 caFunc[t] - 4.60309 × 108 caFunc[t] × sitePlugging[t]) ss5[t] +
    (-17717.3 - 0.0195313 (25572.7 - 15343.6 sitePlugging[t])) ss6[t],
    17717.3 ss6[t] }, {ss1[0], ss2[0], ss3[0], ss4[0], ss5[0],
    ss6[0], ss7[0]} == {1., 0., 0., 0., 0., 0., 0.},
    fillStateSS'[t] == 2.5 +  $\frac{60 \cdot \text{caFunc}[t]}{2 \times 10^{-6} + \text{caFunc}[t]}$  - 8.61585 fillStateSS[t] -
    
$$\left( 100 + \frac{800 \cdot \text{caFunc}[t]}{2 \times 10^{-6} + \text{caFunc}[t]} \right) \text{fillStateSS}[t] + 181.545 \text{ss1}[t],$$

    fillStateSS[0] == 1., sitePlugging'[t] ==
    -0.04 sitePlugging[t] + (1 - sitePlugging[t]) ss7'[t],
    sitePlugging[0] == 0}


```

## Solve all states





```
In[948]:= caFunc[t_] := 3*^-6 * Exp[-t / tauOfDecayOfUncagedCa];;
Plot[caFunc[t], {t, 0, 0.4}, PlotRange -> All]
```







```
In[950]:= merkSS = NDSolve[eq,
  {fillStateSS, ss1, ss2, ss3, ss4, ss5, ss6, ss7, sitePlugging}, {t, 0, 10.}];
tEndForPlot = 1.;
Plot[(fillStateSS[t] /. merkSS), {t, 0, tEndForPlot}, PlotRange -> All]
Plot[(ss1[t] /. merkSS), {t, 0, tEndForPlot}, PlotRange -> All]
Plot[(ss2[t] /. merkSS), {t, 0, tEndForPlot}, PlotRange -> All]
Plot[(ss3[t] /. merkSS), {t, 0, tEndForPlot}, PlotRange -> All]
Plot[(ss4[t] /. merkSS), {t, 0, tEndForPlot}, PlotRange -> All]
Plot[(ss5[t] /. merkSS), {t, 0, tEndForPlot}, PlotRange -> All]
Plot[(ss6[t] /. merkSS), {t, 0, tEndForPlot}, PlotRange -> All]
Plot[(ss7[t] /. merkSS), {t, 0, tEndForPlot}, PlotRange -> All]
Plot[(sitePlugging[t] /. merkSS), {t, 0, tEndForPlot}, PlotRange -> All]
```









# Loop

## make lists for later

```
In[961]:= simCaList = Table[0, {runs}];
          simParamNv = Table[0, {7}, {runs}];
```

### C5

```
In[963]:= baselineC5 = Table[{ttt, 0}, {ttt, cursorStart, -1*^-6, dtOfDataC5}];
          (*Lists for saving data within loop*)
          simParamNoiseC5 = Table[0, {numberOfFitParamToBeSaved}, {noiseRepeats}];
          simParamMedianC5 = Table[0, {numberOfFitParamToBeSaved}, {runs}];
          simParamQuantile1C5 = Table[0, {numberOfFitParamToBeSaved}, {runs}];
          simParamQuantile2C5 = Table[0, {numberOfFitParamToBeSaved}, {runs}];
```

### C10

```
In[968]:= baselineC10 = Table[{ttt, 0}, {ttt, cursorStart, -1*^-6, dtOfDataC10}];
          (*Lists for saving data within loop*)
          simParamNoiseC10 = Table[0, {numberOfFitParamToBeSaved}, {noiseRepeats}];
          simParamMedianC10 = Table[0, {numberOfFitParamToBeSaved}, {runs}];
          simParamQuantile1C10 = Table[0, {numberOfFitParamToBeSaved}, {runs}];
          simParamQuantile2C10 = Table[0, {numberOfFitParamToBeSaved}, {runs}];
```

### D

```
In[973]:= baselineD = Table[{ttt, 0}, {ttt, cursorStart, -1*^-6, dtOfDataD}];
          (*Lists for saving data within loop*)
          simParamNoiseD = Table[0, {numberOfFitParamToBeSaved}, {noiseRepeats}];
          simParamMedianD = Table[0, {numberOfFitParamToBeSaved}, {runs}];
          simParamQuantile1D = Table[0, {numberOfFitParamToBeSaved}, {runs}];
          simParamQuantile2D = Table[0, {numberOfFitParamToBeSaved}, {runs}];
```

### Long

```
In[978]:= baselineLong = Table[{ttt, 0}, {ttt, -0.05, -1*^-6, dtOfDataLong}];
```

## Loop

```
In[979]:= For[r = 1, r ≤ runs, r += 1,
              myCaNow = CaListDyePeak[[r]];
              lastSimulatedCaListReal = CaListReal[[r]][[1]][[1]] /. tt → TimeWindow;
```

```

(* "[1][1]" is needed to get rid of these brackets {{}}*)
Print[
  "-----
  -----"];
Print["----- Ca = ", 1*^6 myCaNow,
  " uM -----"];
Print[
  "-----
  -----"];
simCaList[[r]] = myCaNow;
caFunc[t_]:= If[t < TimeWindow,
  CaListReal[[r]][[1]][[1]] /. tt -> t,
  (* tt because this is the symbol used in "Calculate Ca transients"*)
  lastSimulatedCaListReal * Exp[-t/tauOfDecayOfUncagedCa]
];
(* solve Diff Eq.: *)
merkSS = NDSolve[eq, ss7, {t, 0, cursorEndLong}];
(* plot results: *)
fused[t_] := ss7[t];
Plot[(fused[t] /. merkSS), {t, 0, cursorEnd}, PlotRange -> All] // Print;
Plot[(fused[t] /. merkSS), {t, 0, cursorEndLong}, PlotRange -> All] // Print;
If[exportYes == 1,
  toExport = Table[{t, (fused[t] /. merkSS)[[1]]},
    {t, 0., cursorEndLong, dtOfPlotsForExport}];
  Export["withinLoop r" <> ToString[r] <> " Ca" <> ToString[1*^6 myCaNow] <>
    " withoutNoise.txt", toExport, "Table"];
];
(* sample data and add baseline: -----*)
tmpCumRelC5 =
  Table[{t, (fused[t] /. merkSS)[[1]]}, {t, 0., cursorEnd, dtOfDataC5}];
tmpToFitC5 = Catenate[{baselineC5, tmpCumRelC5}];
tmpCumRelC10 =
  Table[{t, (fused[t] /. merkSS)[[1]]}, {t, 0., cursorEnd, dtOfDataC10}];
tmpToFitC10 = Catenate[{baselineC10, tmpCumRelC10}];
tmpCumRelD =
  Table[{t, (fused[t] /. merkSS)[[1]]}, {t, 0., cursorEnd, dtOfDataD}];
tmpToFitD = Catenate[{baselineD, tmpCumRelD}];
tmpCumRelLong = Table[{t, (fused[t] /. merkSS)[[1]]},
  {t, 0., cursorEndLong, dtOfDataLong}];
tmpToFitLong = Catenate[{baselineLong, tmpCumRelLong}];

(*----- get amplitude
without noise and without fitting -----*)
For[NvCount = 1, NvCount <= 7, NvCount += 1,
  simParamNv[[NvCount, r]] = (fused[timeOfNv[[NvCount]]] /. merkSS)[[1]];
  (* the [[1]] is somehow needed to get rid of a list

```

```

    structure probably related to the interpolate function*)
];

(*----- Startvalues for
fit the same for all C5 C10 and D -----*)
caAdjustedTau1Guess = tau1Guess / ((myCaNow / 10.*^-6) ^ 4);
caAdjustedTau1Guess = tau1Guess / ((myCaNow / 10.*^-6) ^ 1);
caAdjustedTau2Guess = 10 caAdjustedTau1Guess;
caAdjustedDelayGuess = delayGuess / ((myCaNow / 10.*^-6) ^ 1);

(*----- Fitting of data,
saving of results, and plotting-----*)
(*-----*)
(*----- C5 -----*)
(*-----*)
(*-----*)
Print[
"-----
C5"];
(*check that signal is large enough relative to noise to obtain
useful fit results. If not, do not do fitting and set everything to {}*)
If[simParamNv[[5, r]] > signalToNoiseRatioC5 myNoiseC5, (*add noise
several times and do the fitting and then average the results*)
For[noiseN = 1, noiseN ≤ noiseRepeats, noiseN += 1,
(*Print[noiseN];*)
tmpToFitNoise = Transpose[{tmpToFitC5[[All, 1]],
#+ RandomVariate[NormalDistribution[0, myNoiseC5]] & /@
tmpToFitC5[[All, 2]]}];
(*fit mono-exp*)
merk = NonlinearModelFit[tmpToFitNoise, myFitMono[x1],
{{delayMono, delayGuess}, {ampMono, ampGuess}, {tau1Mono,
caAdjustedTau1Guess}}, x1, MaxIterations → myMaxIterations];
fitResultMono = merk[{"BestFitParameters"}];
simParamNoiseC5[[1, noiseN]] = 0; (*not used anymore*)
simParamNoiseC5[[2, noiseN]] = merk["ANOVATableSumsOfSquares"][[2]];
(*Print[merk["ANOVATableSumsOfSquares"]];*)
simParamNoiseC5[[3, noiseN]] = (delayMono /. fitResultMono)[[1]];
simParamNoiseC5[[4, noiseN]] = (ampMono /. fitResultMono)[[1]];
simParamNoiseC5[[5, noiseN]] = (1 / (tau1Mono /. fitResultMono))[1];
(*fit bi-exp*)
merk = NonlinearModelFit[tmpToFitNoise, myFitBi[x1], {{delay, delayGuess},
{amp, ampGuess}, {amp1, amp1Guess}, {tau1, caAdjustedTau1Guess},
{tau2, caAdjustedTau2Guess}}, x1, MaxIterations → myMaxIterations];
fitResultBi = merk[{"BestFitParameters"}];
simParamNoiseC5[[6, noiseN]] =

```

```

simParamNoiseC5[[2, noiseN]] / merk["ANOVATableSumsOfSquares"][[2]];
simParamNoiseC5[[7, noiseN]] = (delay /. fitResultBi)[[1]];
simParamNoiseC5[[8, noiseN]] = ((amp /. fitResultBi)[[1]]);
simParamNoiseC5[[9, noiseN]] = ((amp amp1 /. fitResultBi)[[1]]);
(*relative amp1*)
simParamNoiseC5[[10, noiseN]] = (1 / (tau1 /. fitResultBi)[[1]]);
simParamNoiseC5[[11, noiseN]] = (1 / (tau2 /. fitResultBi)[[1]]);
(*merge*)
If[
  (*to use the bi-exp fit, the following criteria should be fulfilled:*)
  (*chi2 should improve(=decrease) by >10%*)
  (simParamNoiseC5[[6, noiseN]] > 1.04)
  &&
  (*tau1 and tau2 of bi fit should be factor of >3 different*)
  ((simParamNoiseC5[[11, noiseN]] / simParamNoiseC5[[10, noiseN]]) < 3.)
  &&
  (*relative amplitude of 1st component should be > 5% *)
  (((amp1 /. fitResultBi)[[1]] > 0.05)
  &&
  (*relative amplitude of 1st component should be < 95% *)
  (((amp1 /. fitResultBi)[[1]] < 0.95)
  ,
  (*take bi*)
  Print["take bi"];
  simParamNoiseC5[[12, noiseN]] = simParamNoiseC5[[7, noiseN]];
  (*delay*)
  simParamNoiseC5[[13, noiseN]] = simParamNoiseC5[[8, noiseN]];
  (*amp*)
  simParamNoiseC5[[14, noiseN]] = simParamNoiseC5[[9, noiseN]];
  (*amp1*)
  simParamNoiseC5[[15, noiseN]] = simParamNoiseC5[[10, noiseN]];
  (*tau1*)
  simParamNoiseC5[[16, noiseN]] = simParamNoiseC5[[11, noiseN]]; (*tau2*)
  ,
  (*take mono*)
  Print["take mono"];
  simParamNoiseC5[[12, noiseN]] = simParamNoiseC5[[3, noiseN]];
  (*delay*)
  simParamNoiseC5[[13, noiseN]] = simParamNoiseC5[[4, noiseN]];
  (*amp*)
  simParamNoiseC5[[14, noiseN]] = NaN; (*amp1*)
  simParamNoiseC5[[15, noiseN]] = simParamNoiseC5[[5, noiseN]];
  (*tau1*)
  simParamNoiseC5[[16, noiseN]] = NaN; (*tau2*)
];
];

```

```

(*plot last example of the noise loop*)
gr1 = ListPlot[tmpToFitNoise, PlotRange → All, PlotStyle → Black];
gr2 = Plot[myFitMono[x1] /. fitResultMono,
  {x1, cursorStart, cursorEnd}, PlotRange → All, PlotStyle → {Blue, Dashed}];
gr3 = Plot[myFitBi[x1] /. fitResultBi, {x1, cursorStart, cursorEnd},
  PlotRange → All, PlotStyle → {Green, Dashed}];
Show[gr1, gr2, gr3, PlotRange → All] // Print;
If[exportYes == 1,
  Export["withinLoop r" <> ToString[r] <> " Ca" <>
    ToString[1*^6 myCaNow] <> " C5 data.txt", tmpToFitNoise, "Table"];
  toExport = Table[{t, (myFitMono[t] /. fitResultMono)[[1]]},
    {t, cursorStart, cursorEnd, dtOfPlotsForExport}];
  Export["withinLoop r" <> ToString[r] <> " Ca" <> ToString[1*^6 myCaNow] <>
    " C5 fitMono.txt", toExport, "Table"];
  toExport = Table[{t, (myFitBi[t] /. fitResultBi)[[1]]},
    {t, cursorStart, cursorEnd, dtOfPlotsForExport}];
  Export["withinLoop r" <> ToString[r] <> " Ca" <>
    ToString[1*^6 myCaNow] <> " C5 fitBi.txt", toExport, "Table"];
];
noiseN = noiseRepeats; (*fit parameter of last noisetrace*)
Print["Mono: chi2 = ", simParamNoiseC5[[2, noiseN]], "      d = ",
  simParamNoiseC5[[2, noiseN]], "      a = ", simParamNoiseC5[[4, noiseN]],
  "      t = ", 1/simParamNoiseC5[[5, noiseN]]];
Print["Bi: ratio chi2Mono/chi2Bi = ", simParamNoiseC5[[6, noiseN]],
  "      d = ", simParamNoiseC5[[7, noiseN]], "      a = ",
  simParamNoiseC5[[8, noiseN]], "      a1 = ", simParamNoiseC5[[9, noiseN]],
  "      t1 = ", 1/simParamNoiseC5[[10, noiseN]],
  "      t2 = ", 1/simParamNoiseC5[[11, noiseN]]];
(*average fit results*)
For[p = 1, p ≤ numberOfFitParamToBeSaved, p += 1,
  simParamMedianC5[[p, r]] =
    Median[simParamNoiseC5[[p, All]] /. NaN → Sequence[]];
  simParamQuantile1C5[[p, r]] = Quantile[
    simParamNoiseC5[[p, All]] /. NaN → Sequence[], myQuantile1];
  simParamQuantile2C5[[p, r]] = Quantile[
    simParamNoiseC5[[p, All]] /. NaN → Sequence[], myQuantile2];
];

(*if tau1 merge > 10 ms, use long trace for fitting*)
If[(1/simParamMedianC5[[15, r]]) > 0.01,
  Print["Long trace was used for fitting."];
  For[noiseN = 1, noiseN ≤ noiseRepeats, noiseN += 1,
    tmpToFitNoiseLong = Transpose[{tmpToFitLong[[All, 1]],
      # + RandomVariate[NormalDistribution[0, myNoiseLong]] & /@
        tmpToFitLong[[All, 2]]}];
    (*fit mono-exp to Long trace*)

```

```

merk = NonlinearModelFit[tmpToFitNoiseLong, myFitMono[x1],
  {{delayMono, delayGuess}, {ampMono, ampGuess}, {tau1Mono,
    caAdjustedTau1Guess}}, x1, MaxIterations → myMaxIterations];
fitResultLongMono = merk[{"BestFitParameters"}];
simParamNoiseC5[[2, noiseN]] = merk["ANOVATableSumsOfSquares"][[2]];
(*Print[merk["ANOVATableSumsOfSquares"]];*)
simParamNoiseC5[[3, noiseN]] = (delayMono /. fitResultLongMono)[[1]];
simParamNoiseC5[[4, noiseN]] = ((ampMono /. fitResultLongMono)[[1]]);
simParamNoiseC5[[5, noiseN]] = (1 / (tau1Mono /. fitResultLongMono))[1];
(*fit bi-exp*)
merk = NonlinearModelFit[tmpToFitNoiseLong, myFitBi[x1],
  {{delay, delayGuess}, {amp, ampGuess}, {amp1, amp1Guess},
    {tau1, caAdjustedTau1Guess}, {tau2, caAdjustedTau2Guess}},
  x1, MaxIterations → myMaxIterations];
fitResultLongBi = merk[{"BestFitParameters"}];
simParamNoiseC5[[6, noiseN]] =
  simParamNoiseC5[[2, noiseN]] / merk["ANOVATableSumsOfSquares"][[2]];
simParamNoiseC5[[7, noiseN]] = (delay /. fitResultLongBi)[[1]];
simParamNoiseC5[[8, noiseN]] = ((amp /. fitResultLongBi)[[1]]);
simParamNoiseC5[[9, noiseN]] = ((amp amp1 /. fitResultLongBi)[[1]]);
(*relative amp1*)
simParamNoiseC5[[10, noiseN]] = (1 / (tau1 /. fitResultLongBi))[1];
simParamNoiseC5[[11, noiseN]] = (1 / (tau2 /. fitResultLongBi))[1];
(*merge*)
If[
  (*to use the bi-exp fit,
  the following criteria should be fulfilled:*)
  (*chi2 should improve(=decrease) by >10%*)
  (simParamNoiseC5[[6, noiseN]] > 1.04)
  &&
  (*tau1 and tau2 of bi fit should be factor of >3 different*)
  ((simParamNoiseC5[[11, noiseN]] / simParamNoiseC5[[10, noiseN]]) < 3.)
  &&
  (*relative amplitude of 1st component should be > 5% *)
  (((amp1 /. fitResultLongBi)[[1]] > 0.05)
  &&
  (*relative amplitude of 1st component should be < 95% *)
  (((amp1 /. fitResultLongBi)[[1]] < 0.95)
  ,
  (*take bi*)
  Print["take bi"];
  simParamNoiseC5[[12, noiseN]] = simParamNoiseC5[[7, noiseN]];
  (*delay*)
  simParamNoiseC5[[13, noiseN]] = simParamNoiseC5[[8, noiseN]];
  (*amp*)
  simParamNoiseC5[[14, noiseN]] = simParamNoiseC5[[9, noiseN]];

```



```

(*amp1*)
simParamNoiseC5[[15, noiseN]] = simParamNoiseC5[[10, noiseN]];
(*tau1*)
simParamNoiseC5[[16, noiseN]] = simParamNoiseC5[[11, noiseN]]; (*tau2*)
,
(*take mono*)
Print["take mono"];
simParamNoiseC5[[12, noiseN]] = simParamNoiseC5[[3, noiseN]];
(*delay*)
simParamNoiseC5[[13, noiseN]] = simParamNoiseC5[[4, noiseN]];
(*amp*)
simParamNoiseC5[[14, noiseN]] = NaN; (*amp1*)
simParamNoiseC5[[15, noiseN]] = simParamNoiseC5[[5, noiseN]];
(*tau1*)
simParamNoiseC5[[16, noiseN]] = NaN; (*tau2*)
];
];
(*plot last example of the noise loop*)
gr1 = ListPlot[tmpToFitNoiseLong, PlotRange → All, PlotStyle → Black];
gr2 = Plot[myFitMono[x1] /. fitResultLongMono, {x1, cursorStart,
  cursorEndLong}, PlotRange → All, PlotStyle → {Blue, Dashed}];
gr3 = Plot[myFitBi[x1] /. fitResultLongBi, {x1, cursorStart, cursorEndLong},
  PlotRange → All, PlotStyle → {Green, Dashed}];
Show[gr1, gr2, gr3, PlotRange → All] // Print;
If[exportYes == 1,
  Export["withinLoop r" <> ToString[r] <> " Ca" <> ToString[1*^6 myCaNow] <>
    " C5 dataLong.txt", tmpToFitNoiseLong, "Table"];
  toExport = Table[{t, (myFitMono[t] /. fitResultLongMono)[[1]]},
    {t, cursorStart, cursorEndLong, dtOfPlotsForExport}];
  Export["withinLoop r" <> ToString[r] <> " Ca" <> ToString[1*^6 myCaNow] <>
    " C5 fitLongMono.txt", toExport, "Table"];
  toExport = Table[{t, (myFitBi[t] /. fitResultLongBi)[[1]]},
    {t, cursorStart, cursorEndLong, dtOfPlotsForExport}];
  Export["withinLoop r" <> ToString[r] <> " Ca" <> ToString[1*^6 myCaNow] <>
    " C5 fitLongBi.txt", toExport, "Table"];
];
noiseN = noiseRepeats; (*fit parameter of last noisetrace*)
Print["Mono: chi2 = ", simParamNoiseC5[[2, noiseN]], " d = ",
  simParamNoiseC5[[3, noiseN]], " a = ", simParamNoiseC5[[4, noiseN]],
  " t = ", 1/simParamNoiseC5[[5, noiseN]]];
Print["Bi: ratio chi2Mono/chi2Bi = ", simParamNoiseC5[[6, noiseN]],
  " d = ", simParamNoiseC5[[7, noiseN]], " a = ",
  simParamNoiseC5[[8, noiseN]], " a1 = ", simParamNoiseC5[[9, noiseN]],
  " t1 = ", 1/simParamNoiseC5[[10, noiseN]],
  " t2 = ", 1/simParamNoiseC5[[11, noiseN]]];

```

```

(*average fit results*)
For[p = 1, p ≤ numberOfFitParamToBeSaved, p += 1,
  simParamMedianC5[[p, r]] =
    Median[simParamNoiseC5[[p, All]] /. NaN → Sequence[]];
  simParamQuantile1C5[[p, r]] = Quantile[
    simParamNoiseC5[[p, All]] /. NaN → Sequence[], myQuantile1];
  simParamQuantile2C5[[p, r]] = Quantile[
    simParamNoiseC5[[p, All]] /. NaN → Sequence[], myQuantile2];
];
];

, (*else: signal is not large enough*)
For[p = 1, p ≤ numberOfFitParamToBeSaved, p += 1,
  simParamMedianC5[[p, r]] = {};
  simParamQuantile1C5[[p, r]] = {};
  simParamQuantile2C5[[p, r]] = {};
];
];

(*----- Fitting of data,
saving of results, and plotting-----*)
(*-----*)
(*----- C10 -----*)
(*-----*)
(*-----*)

Print[
  "-----
  C10"];
(*check that signal is large enough relative to noise to obtain
useful fit results. If not, do not do fitting and set everything to {}*)
If[simParamNv[[5, r]] > signalToNoiseRatioC10 myNoiseC10, (*add noise
and do the fitting several times and then average the results*)
For[noiseN = 1, noiseN ≤ noiseRepeats, noiseN += 1,
  (*Print[noiseN];*)
  tmpToFitNoise = Transpose[{tmpToFitC10[[All, 1]],
    # + RandomVariate[NormalDistribution[0, myNoiseC10]] & /@
    tmpToFitC10[[All, 2]]}];
  (*fit mono-exp*)
  merk = NonlinearModelFit[tmpToFitNoise, myFitMono[x1],
    {{delayMono, delayGuess}, {ampMono, ampGuess}, {tau1Mono,
    caAdjustedTau1Guess}}, x1, MaxIterations → myMaxIterations];
  fitResultMono = merk[{"BestFitParameters"}];
  simParamNoiseC10[[1, noiseN]] = 0; (*not used anymore*)
  simParamNoiseC10[[2, noiseN]] = merk["ANOVATableSumsOfSquares"][[2]];

```

```

(*Print[merk["ANOVATableSumsOfSquares"]];*)
simParamNoiseC10[[3, noiseN]] = (delayMono /. fitResultMono)[[1]];
simParamNoiseC10[[4, noiseN]] = ((ampMono /. fitResultMono)[[1]]);
simParamNoiseC10[[5, noiseN]] = (1 / (tau1Mono /. fitResultMono)[[1]]);
(*fit bi-exp*)
merk = NonlinearModelFit[tmpToFitNoise, myFitBi[x1], {{delay, delayGuess},
  {amp, ampGuess}, {amp1, amp1Guess}, {tau1, caAdjustedTau1Guess},
  {tau2, caAdjustedTau2Guess}}, x1, MaxIterations -> myMaxIterations];
fitResultBi = merk[{"BestFitParameters"}];
simParamNoiseC10[[6, noiseN]] =
  simParamNoiseC10[[2, noiseN]] / merk["ANOVATableSumsOfSquares"][[2]];
simParamNoiseC10[[7, noiseN]] = (delay /. fitResultBi)[[1]];
simParamNoiseC10[[8, noiseN]] = ((amp /. fitResultBi)[[1]]);
simParamNoiseC10[[9, noiseN]] = ((amp amp1 /. fitResultBi)[[1]]);
(*relative amp1*)
simParamNoiseC10[[10, noiseN]] = (1 / (tau1 /. fitResultBi)[[1]]);
simParamNoiseC10[[11, noiseN]] = (1 / (tau2 /. fitResultBi)[[1]]);
(*merge*)
If[
  (*to use the bi-exp fit, the following criteria should be fulfilled:*)
  (*chi2 should improve(=decrease) by >4%*)
  (simParamNoiseC10[[6, noiseN]] > 1.04)
  &&
  (*tau1 and tau2 of bi fit should be factor of >3 different*)
  (((simParamNoiseC10[[11, noiseN]] / simParamNoiseC10[[10, noiseN]]) < 3.)
  &&
  (*relative amplitude of 1st component should be > 5% *)
  (((amp1 /. fitResultBi)[[1]] > 0.05)
  &&
  (*relative amplitude of 1st component should be < 95% *)
  (((amp1 /. fitResultBi)[[1]] < 0.95)
  ,
  (*take bi*)
  Print["take bi"];
  simParamNoiseC10[[12, noiseN]] = simParamNoiseC10[[7, noiseN]];
  (*delay*)
  simParamNoiseC10[[13, noiseN]] = simParamNoiseC10[[8, noiseN]];
  (*amp*)
  simParamNoiseC10[[14, noiseN]] = simParamNoiseC10[[9, noiseN]];
  (*amp1*)
  simParamNoiseC10[[15, noiseN]] = simParamNoiseC10[[10, noiseN]];
  (*tau1*)
  simParamNoiseC10[[16, noiseN]] = simParamNoiseC10[[11, noiseN]]; (*tau2*)
  ,
  (*take mono*)
  Print["take mono"];

```

```

simParamNoiseC10[[12, noiseN]] = simParamNoiseC10[[3, noiseN]];
(*delay*)
simParamNoiseC10[[13, noiseN]] = simParamNoiseC10[[4, noiseN]];
(*amp*)
simParamNoiseC10[[14, noiseN]] = NaN; (*amp1*)
simParamNoiseC10[[15, noiseN]] = simParamNoiseC10[[5, noiseN]];
(*taul*)
simParamNoiseC10[[16, noiseN]] = NaN; (*tau2*)
];
];
(*plot last example of the noise loop*)
gr1 = ListPlot[tmpToFitNoise, PlotRange → All, PlotStyle → Black];
gr2 = Plot[myFitMono[x1] /. fitResultMono,
  {x1, cursorStart, cursorEnd}, PlotRange → All, PlotStyle → {Blue, Dashed}];
gr3 = Plot[myFitBi[x1] /. fitResultBi, {x1, cursorStart, cursorEnd},
  PlotRange → All, PlotStyle → {Green, Dashed}];
Show[gr1, gr2, gr3, PlotRange → All] // Print;
If[exportYes == 1,
  Export["withinLoop r" <> ToString[r] <> " Ca" <>
    ToString[1*^6 myCaNow] <> " C10 data.txt", tmpToFitNoise, "Table"];
  toExport = Table[{t, (myFitMono[t] /. fitResultMono)[[1]]},
    {t, cursorStart, cursorEnd, dtOfPlotsForExport}];
  Export["withinLoop r" <> ToString[r] <> " Ca" <> ToString[1*^6 myCaNow] <>
    " C10 fitMono.txt", toExport, "Table"];
  toExport = Table[{t, (myFitBi[t] /. fitResultBi)[[1]]},
    {t, cursorStart, cursorEnd, dtOfPlotsForExport}];
  Export["withinLoop r" <> ToString[r] <> " Ca" <> ToString[1*^6 myCaNow] <>
    " C10 fitBi.txt", toExport, "Table"];
];
noiseN = noiseRepeats; (*fit parameter of last noisetrajectory*)
Print["Mono: chi2 = ", simParamNoiseC10[[2, noiseN]], " d = ",
  simParamNoiseC10[[2, noiseN]], " a = ", simParamNoiseC10[[4, noiseN]],
  " t = ", 1/simParamNoiseC10[[5, noiseN]]];
Print["Bi: ratio chi2Mono/chi2Bi = ", simParamNoiseC10[[6, noiseN]],
  " d = ", simParamNoiseC10[[7, noiseN]], " a = ",
  simParamNoiseC10[[8, noiseN]], " a1 = ", simParamNoiseC10[[9, noiseN]],
  " t1 = ", 1/simParamNoiseC10[[10, noiseN]],
  " t2 = ", 1/simParamNoiseC10[[11, noiseN]]];
(*average fit results*)
For[p = 1, p ≤ numberOfFitParamToBeSaved, p += 1,
  simParamMedianC10[[p, r]] =
    Median[simParamNoiseC10[[p, All]] /. NaN → Sequence[]];
  simParamQuantile1C10[[p, r]] = Quantile[
    simParamNoiseC10[[p, All]] /. NaN → Sequence[], myQuantile1];
  simParamQuantile2C10[[p, r]] = Quantile[
    simParamNoiseC10[[p, All]] /. NaN → Sequence[], myQuantile2];

```

```

];

(*if tau1 merge > 10 ms, use long trace for fitting*)
If[(1/simParamMedianC10[[15, r]]) > 0.01,
  Print["Long trace was used for fitting."];
  For[noiseN = 1, noiseN ≤ noiseRepeats, noiseN += 1,
    tmpToFitNoiseLong = Transpose[{tmpToFitLong[[All, 1]],
      # + RandomVariate[NormalDistribution[0, myNoiseLong]] & /@
      tmpToFitLong[[All, 2]]}];
    (*fit mono-exp to Long trace*)
    merk = NonlinearModelFit[tmpToFitNoiseLong, myFitMono[x1],
      {{delayMono, delayGuess}, {ampMono, ampGuess}, {tau1Mono,
        caAdjustedTau1Guess}}, x1, MaxIterations → myMaxIterations];
    fitResultLongMono = merk[{"BestFitParameters"}];
    simParamNoiseC10[[2, noiseN]] = merk["ANOVATableSumsOfSquares"][[2]];
    (*Print[merk["ANOVATableSumsOfSquares"]];*)
    simParamNoiseC10[[3, noiseN]] = (delayMono /. fitResultLongMono)[[1]];
    simParamNoiseC10[[4, noiseN]] = ((ampMono /. fitResultLongMono)[[1]]);
    simParamNoiseC10[[5, noiseN]] = (1/(tau1Mono /. fitResultLongMono)[[1]]);
    (*fit bi-exp*)
    merk = NonlinearModelFit[tmpToFitNoiseLong, myFitBi[x1],
      {{delay, delayGuess}, {amp, ampGuess}, {amp1, amp1Guess},
        {tau1, caAdjustedTau1Guess}, {tau2, caAdjustedTau2Guess}},
      x1, MaxIterations → myMaxIterations];
    fitResultLongBi = merk[{"BestFitParameters"}];
    simParamNoiseC10[[6, noiseN]] =
      simParamNoiseC10[[2, noiseN]]/merk["ANOVATableSumsOfSquares"][[2]];
    simParamNoiseC10[[7, noiseN]] = (delay /. fitResultLongBi)[[1]];
    simParamNoiseC10[[8, noiseN]] = ((amp /. fitResultLongBi)[[1]]);
    simParamNoiseC10[[9, noiseN]] = ((amp amp1 /. fitResultLongBi)[[1]]);
    (*relative amp1*)
    simParamNoiseC10[[10, noiseN]] = (1/(tau1 /. fitResultLongBi)[[1]]);
    simParamNoiseC10[[11, noiseN]] = (1/(tau2 /. fitResultLongBi)[[1]]);
    (*merge*)
    If[
      (*to use the bi-exp fit,
        the following criteria should be fulfilled:*)
      (*chi2 should improve(=decrease) by >4%*)
      (simParamNoiseC10[[6, noiseN]] > 1.04)
      &&
      (*tau1 and tau2 of bi fit should be factor of >3 different*)
      ((simParamNoiseC10[[11, noiseN]]/simParamNoiseC10[[10, noiseN]]) < 3.)
      &&
      (*relative amplitude of 1st component should be > 5% *)
      (((amp1 /. fitResultLongBi)[[1]] > 0.05)
      &&

```

```

    (*relative amplitude of 1st component should be < 95% *)
    ((( amp1 /. fitResultLongBi)) [[1]] < 0.95)
  ,
  (*take bi*)
  Print["take bi"];
  simParamNoiseC10[[12, noiseN]] = simParamNoiseC10[[7, noiseN]];
  (*delay*)
  simParamNoiseC10[[13, noiseN]] = simParamNoiseC10[[8, noiseN]];
  (*amp*)
  simParamNoiseC10[[14, noiseN]] = simParamNoiseC10[[9, noiseN]];
  (*amp1*)
  simParamNoiseC10[[15, noiseN]] = simParamNoiseC10[[10, noiseN]];
  (*tau1*)
  simParamNoiseC10[[16, noiseN]] = simParamNoiseC10[[11, noiseN]]; (*tau2*)
  ,
  (*take mono*)
  Print["take mono"];
  simParamNoiseC10[[12, noiseN]] = simParamNoiseC10[[3, noiseN]];
  (*delay*)
  simParamNoiseC10[[13, noiseN]] = simParamNoiseC10[[4, noiseN]];
  (*amp*)
  simParamNoiseC10[[14, noiseN]] = NaN; (*amp1*)
  simParamNoiseC10[[15, noiseN]] = simParamNoiseC10[[5, noiseN]];
  (*tau1*)
  simParamNoiseC10[[16, noiseN]] = NaN; (*tau2*)
];
];
(*plot last example of the noise loop*)
gr1 = ListPlot[tmpToFitNoiseLong, PlotRange → All, PlotStyle → Black];
gr2 = Plot[myFitMono[x1] /. fitResultLongMono, {x1, cursorStart,
  cursorEndLong}, PlotRange → All, PlotStyle → {Blue, Dashed}];
gr3 = Plot[myFitBi[x1] /. fitResultLongBi, {x1, cursorStart, cursorEndLong},
  PlotRange → All, PlotStyle → {Green, Dashed}];
Show[gr1, gr2, gr3, PlotRange → All] // Print;
If[exportYes == 1,
  Export["withinLoop r" <> ToString[r] <> " Ca" <> ToString[1*^6 myCaNow] <>
    " C10 dataLong.txt", tmpToFitNoiseLong, "Table"];
  toExport = Table[{t, (myFitMono[t] /. fitResultLongMono) [[1]]},
    {t, cursorStart, cursorEndLong, dtOfPlotsForExport}];
  Export["withinLoop r" <> ToString[r] <> " Ca" <> ToString[1*^6 myCaNow] <>
    " C10 fitLongMono.txt", toExport, "Table"];
  toExport = Table[{t, (myFitBi[t] /. fitResultLongBi) [[1]]},
    {t, cursorStart, cursorEndLong, dtOfPlotsForExport}];
  Export["withinLoop r" <> ToString[r] <> " Ca" <> ToString[1*^6 myCaNow] <>
    " C10 fitLongBi.txt", toExport, "Table"];
];

```

```

noiseN = noiseRepeats; (*fit parameter of last noisetrace*)
Print["Mono: chi2 = ", simParamNoiseC10[[2, noiseN]], "      d = ",
      simParamNoiseC10[[3, noiseN]], "      a = ", simParamNoiseC10[[4, noiseN]],
      "      t = ", 1/simParamNoiseC10[[5, noiseN]]];
Print["Bi: ratio chi2Mono/chi2Bi = ", simParamNoiseC10[[6, noiseN]],
      "      d = ", simParamNoiseC10[[7, noiseN]], "      a = ",
      simParamNoiseC10[[8, noiseN]], "      a1 = ", simParamNoiseC10[[9, noiseN]],
      "      t1 = ", 1/simParamNoiseC10[[10, noiseN]],
      "      t2 = ", 1/simParamNoiseC10[[11, noiseN]]];
(*average fit results*)
For[p = 1, p ≤ numberOfFitParamToBeSaved, p += 1,
  simParamMedianC10[[p, r]] =
    Median[simParamNoiseC10[[p, All]] /. NaN → Sequence[]];
  simParamQuantile1C10[[p, r]] = Quantile[
    simParamNoiseC10[[p, All]] /. NaN → Sequence[], myQuantile1];
  simParamQuantile2C10[[p, r]] = Quantile[
    simParamNoiseC10[[p, All]] /. NaN → Sequence[], myQuantile2];
];
];

, (*else: signal is not large enough*)
For[p = 1, p ≤ numberOfFitParamToBeSaved, p += 1,
  simParamMedianC10[[p, r]] = {};
  simParamQuantile1C10[[p, r]] = {};
  simParamQuantile2C10[[p, r]] = {};
];
];

(*----- Fitting of data,
saving of results, and plotting-----*)
(*-----
                                ----*)
(*----- D -----
                                --*)
(*-----
                                ----*)

Print[
  "-----
  D"];

(*check that signal is large enough relative to noise to obtain
useful fit results. If not, do not do fitting and set everything to {}*)
If[simParamNv[[5, r]] > signalToNoiseRatioDmyNoiseD, (*add noise
several times and do the fitting and than average the results*)
For[noiseN = 1, noiseN ≤ noiseRepeats, noiseN += 1,
  (*Print[noiseN];*)
  tmpToFitNoise = Transpose[{tmpToFitD[[All, 1]],

```

```

    # + RandomVariate[NormalDistribution[0, myNoiseD]] & /@
    tmpToFitD[All, 2]]];
(*fit mono-exp*)
merk = NonlinearModelFit[tmpToFitNoise, myFitMono[x1],
  {{delayMono, delayGuess}, {ampMono, ampGuess}, {tau1Mono,
    caAdjustedTau1Guess}}, x1, MaxIterations → myMaxIterations];
fitResultMono = merk[{"BestFitParameters"}];
simParamNoiseD[[1, noiseN]] = 0; (*not used anymore*)
simParamNoiseD[[2, noiseN]] = merk["ANOVATableSumsOfSquares"][[2]];
(*Print[merk["ANOVATableSumsOfSquares"]];*)
simParamNoiseD[[3, noiseN]] = (delayMono /. fitResultMono)[[1]];
simParamNoiseD[[4, noiseN]] = ((ampMono /. fitResultMono)[[1]]);
simParamNoiseD[[5, noiseN]] = (1 / (tau1Mono /. fitResultMono)[[1]]);
(*fit bi-exp*)
merk = NonlinearModelFit[tmpToFitNoise, myFitBi[x1], {{delay, delayGuess},
  {amp, ampGuess}, {amp1, amp1Guess}, {tau1, caAdjustedTau1Guess},
  {tau2, caAdjustedTau2Guess}}, x1, MaxIterations → myMaxIterations];
fitResultBi = merk[{"BestFitParameters"}];
simParamNoiseD[[6, noiseN]] =
  simParamNoiseD[[2, noiseN]] / merk["ANOVATableSumsOfSquares"][[2]];
simParamNoiseD[[7, noiseN]] = (delay /. fitResultBi)[[1]];
simParamNoiseD[[8, noiseN]] = ((amp /. fitResultBi)[[1]]);
simParamNoiseD[[9, noiseN]] = ((amp amp1 /. fitResultBi)[[1]]);
(*relative amp1*)
simParamNoiseD[[10, noiseN]] = (1 / (tau1 /. fitResultBi)[[1]]);
simParamNoiseD[[11, noiseN]] = (1 / (tau2 /. fitResultBi)[[1]]);
(*merge*)
If[
  (*to use the bi-exp fit, the following criteria should be fulfilled:*)
  (*chi2 should improve(=decrease) by >4%*)
  (simParamNoiseD[[6, noiseN]] > 1.04)
  &&
  (*tau1 and tau2 of bi fit should be factor of >3 different*)
  ((simParamNoiseD[[11, noiseN]] / simParamNoiseD[[10, noiseN]]) < 3.)
  &&
  (*relative amplitude of 1st component should be > 5% *)
  (((amp1 /. fitResultBi)[[1]] > 0.05)
  &&
  (*relative amplitude of 1st component should be < 95% *)
  (((amp1 /. fitResultBi)[[1]] < 0.95)
  ,
  (*take bi*)
  Print["take bi"];
  simParamNoiseD[[12, noiseN]] = simParamNoiseD[[7, noiseN]];
  (*delay*)
  simParamNoiseD[[13, noiseN]] = simParamNoiseD[[8, noiseN]];

```



```

(*amp*)
simParamNoiseD[[14, noiseN]] = simParamNoiseD[[9, noiseN]];
(*amp1*)
simParamNoiseD[[15, noiseN]] = simParamNoiseD[[10, noiseN]];
(*tau1*)
simParamNoiseD[[16, noiseN]] = simParamNoiseD[[11, noiseN]];(*tau2*)
,
(*take mono*)
Print["take mono"];
simParamNoiseD[[12, noiseN]] = simParamNoiseD[[3, noiseN]];
(*delay*)
simParamNoiseD[[13, noiseN]] = simParamNoiseD[[4, noiseN]];
(*amp*)
simParamNoiseD[[14, noiseN]] = NaN; (*amp1*)
simParamNoiseD[[15, noiseN]] = simParamNoiseD[[5, noiseN]];
(*tau1*)
simParamNoiseD[[16, noiseN]] = NaN;(*tau2*)
];
];
(*plot last example of the noise loop*)
gr1 = ListPlot[tmpToFitNoise, PlotRange → All, PlotStyle → Black];
gr2 = Plot[myFitMono[x1] /. fitResultMono,
  {x1, cursorStart, cursorEnd}, PlotRange → All, PlotStyle → {Blue, Dashed}];
gr3 = Plot[myFitBi[x1] /. fitResultBi, {x1, cursorStart, cursorEnd},
  PlotRange → All, PlotStyle → {Green, Dashed}];
Show[gr1, gr2, gr3, PlotRange → All] // Print;
If[exportYes == 1,
  Export["withinLoop r" <> ToString[r] <> " Ca" <>
    ToString[1*^6 myCaNow] <> " D data.txt", tmpToFitNoise, "Table"];
  toExport = Table[{t, (myFitMono[t] /. fitResultMono)[[1]]},
    {t, cursorStart, cursorEnd, dtOfPlotsForExport}];
  Export["withinLoop r" <> ToString[r] <> " Ca" <> ToString[1*^6 myCaNow] <>
    " D fitMono.txt", toExport, "Table"];
  toExport = Table[{t, (myFitBi[t] /. fitResultBi)[[1]]},
    {t, cursorStart, cursorEnd, dtOfPlotsForExport}];
  Export["withinLoop r" <> ToString[r] <> " Ca" <>
    ToString[1*^6 myCaNow] <> " D fitBi.txt", toExport, "Table"];
];
noiseN = noiseRepeats; (*fit parameter of last noisetrace*)
Print["Mono: chi2 = ", simParamNoiseD[[2, noiseN]],
  "      d = ", simParamNoiseD[[2, noiseN]], "      a = ",
  simParamNoiseD[[4, noiseN]], "      t = ", 1/simParamNoiseD[[5, noiseN]]];
Print["Bi: ratio chi2Mono/chi2Bi = ", simParamNoiseD[[6, noiseN]],
  "      d = ", simParamNoiseD[[7, noiseN]], "      a = ",
  simParamNoiseD[[8, noiseN]], "      a1 = ", simParamNoiseD[[9, noiseN]],
  "      t1 = ", 1/simParamNoiseD[[10, noiseN]],

```

```

"      t2 = ", 1/simParamNoiseD[[11, noiseN]]];
(*average fit results*)
For[p = 1, p ≤ numberOfFitParamToBeSaved, p += 1,
  simParamMedianD[[p, r]] =
    Median[simParamNoiseD[[p, All]] /. NaN → Sequence[]];
  simParamQuantile1D[[p, r]] = Quantile[
    simParamNoiseD[[p, All]] /. NaN → Sequence[], myQuantile1];
  simParamQuantile2D[[p, r]] = Quantile[
    simParamNoiseD[[p, All]] /. NaN → Sequence[], myQuantile2];
];

(*if tau1 merge > 10 ms, use long trace for fitting*)
If[(1/simParamMedianD[[15, r]]) > 0.01,
  Print["Long trace was used for fitting."];
  For[noiseN = 1, noiseN ≤ noiseRepeats, noiseN += 1,
    tmpToFitNoiseLong = Transpose[{tmpToFitLong[[All, 1]],
      # + RandomVariate[NormalDistribution[0, myNoiseLong]] & /@
        tmpToFitLong[[All, 2]]}];
    (*fit mono-exp to Long trace*)
    merk = NonlinearModelFit[tmpToFitNoiseLong, myFitMono[x1],
      {{delayMono, delayGuess}, {ampMono, ampGuess}, {tau1Mono,
        caAdjustedTau1Guess}}, x1, MaxIterations → myMaxIterations];
    fitResultLongMono = merk[{"BestFitParameters"}];
    simParamNoiseD[[2, noiseN]] = merk["ANOVATableSumsOfSquares"][[2]];
    (*Print[merk["ANOVATableSumsOfSquares"]];*)
    simParamNoiseD[[3, noiseN]] = (delayMono /. fitResultLongMono)[[1]];
    simParamNoiseD[[4, noiseN]] = ((ampMono /. fitResultLongMono)[[1]]);
    simParamNoiseD[[5, noiseN]] = (1 / (tau1Mono /. fitResultLongMono)[[1]]);
    (*fit bi-exp*)
    merk = NonlinearModelFit[tmpToFitNoiseLong, myFitBi[x1],
      {{delay, delayGuess}, {amp, ampGuess}, {amp1, amp1Guess},
        {tau1, caAdjustedTau1Guess}, {tau2, caAdjustedTau2Guess}},
      x1, MaxIterations → myMaxIterations];
    fitResultLongBi = merk[{"BestFitParameters"}];
    simParamNoiseD[[6, noiseN]] =
      simParamNoiseD[[2, noiseN]] / merk["ANOVATableSumsOfSquares"][[2]];
    simParamNoiseD[[7, noiseN]] = (delay /. fitResultLongBi)[[1]];
    simParamNoiseD[[8, noiseN]] = ((amp /. fitResultLongBi)[[1]]);
    simParamNoiseD[[9, noiseN]] = ((amp amp1 /. fitResultLongBi)[[1]]);
    (*relative amp1*)
    simParamNoiseD[[10, noiseN]] = (1 / (tau1 /. fitResultLongBi)[[1]]);
    simParamNoiseD[[11, noiseN]] = (1 / (tau2 /. fitResultLongBi)[[1]]);
    (*merge*)
    If[
      (*to use the bi-exp fit,
        the following criteria should be fullfilled:*)

```

```

(*chi2 should improve(=decrease) by >4%*)
(simParamNoiseD[[6, noiseN]] > 1.04)
&&
(*tau1 and tau2 of bi fit should be factor of >3 different*)
((simParamNoiseD[[11, noiseN]]/simParamNoiseD[[10, noiseN]]) < 3.)
&&
(*relative amplitude of 1st component should be > 5% *)
(((amp1 /. fitResultLongBi))[[1]] > 0.05)
&&
(*relative amplitude of 1st component should be < 95% *)
(((amp1 /. fitResultLongBi))[[1]] < 0.95)
,
(*take bi*)
Print["take bi"];
simParamNoiseD[[12, noiseN]] = simParamNoiseD[[7, noiseN]];
(*delay*)
simParamNoiseD[[13, noiseN]] = simParamNoiseD[[8, noiseN]];
(*amp*)
simParamNoiseD[[14, noiseN]] = simParamNoiseD[[9, noiseN]];
(*amp1*)
simParamNoiseD[[15, noiseN]] = simParamNoiseD[[10, noiseN]];
(*tau1*)
simParamNoiseD[[16, noiseN]] = simParamNoiseD[[11, noiseN]]; (*tau2*)
,
(*take mono*)
Print["take mono"];
simParamNoiseD[[12, noiseN]] = simParamNoiseD[[3, noiseN]];
(*delay*)
simParamNoiseD[[13, noiseN]] = simParamNoiseD[[4, noiseN]];
(*amp*)
simParamNoiseD[[14, noiseN]] = NaN; (*amp1*)
simParamNoiseD[[15, noiseN]] = simParamNoiseD[[5, noiseN]];
(*tau1*)
simParamNoiseD[[16, noiseN]] = NaN; (*tau2*)
];
];
(*plot last example of the noise loop*)
gr1 = ListPlot[tmpToFitNoiseLong, PlotRange → All, PlotStyle → Black];
gr2 = Plot[myFitMono[x1] /. fitResultLongMono, {x1, cursorStart,
  cursorEndLong}, PlotRange → All, PlotStyle → {Blue, Dashed}];
gr3 = Plot[myFitBi[x1] /. fitResultLongBi, {x1, cursorStart, cursorEndLong},
  PlotRange → All, PlotStyle → {Green, Dashed}];
Show[gr1, gr2, gr3, PlotRange → All] // Print;
If[exportYes == 1,
  Export["withinLoop r" <> ToString[r] <> " Ca" <> ToString[1*^6 myCaNow] <>
    " D dataLong.txt", tmpToFitNoiseLong, "Table"];
  toExport = Table[{t, (myFitMono[t] /. fitResultLongMono)[[1]]},

```

```



    {t, cursorStart, cursorEndLong, dtOfPlotsForExport}];
Export["withinLoop r" <> ToString[r] <> " Ca" <> ToString[1*^6 myCaNow] <>
  " D fitLongMono.txt", toExport, "Table"];
toExport = Table[{t, (myFitBi[t] /. fitResultLongBi)[[1]]},
  {t, cursorStart, cursorEndLong, dtOfPlotsForExport}];
Export["withinLoop r" <> ToString[r] <> " Ca" <> ToString[1*^6 myCaNow] <>
  " D fitLongBi.txt", toExport, "Table"];

];
noiseN = noiseRepeats; (*fit parameter of last noisetrace*)
Print["Mono: chi2 = ", simParamNoised[[2, noiseN]],
  "      d = ", simParamNoised[[3, noiseN]], "      a = ",
  simParamNoised[[4, noiseN]], "      t = ", 1/simParamNoised[[5, noiseN]]];
Print["Bi: ratio chi2Mono/chi2Bi = ", simParamNoised[[6, noiseN]],
  "      d = ", simParamNoised[[7, noiseN]], "      a = ",
  simParamNoised[[8, noiseN]], "      a1 = ", simParamNoised[[9, noiseN]],
  "      t1 = ", 1/simParamNoised[[10, noiseN]],
  "      t2 = ", 1/simParamNoised[[11, noiseN]]];
(*average fit results*)
For[p = 1, p ≤ numberOfFitParamToBeSaved, p += 1,
  simParamMedianD[[p, r]] =
    Median[simParamNoised[[p, All]] /. NaN → Sequence[]];
  simParamQuantile1D[[p, r]] = Quantile[
    simParamNoised[[p, All]] /. NaN → Sequence[], myQuantile1];
  simParamQuantile2D[[p, r]] = Quantile[
    simParamNoised[[p, All]] /. NaN → Sequence[], myQuantile2];
];
];

, (*else: signal is not large enough*)
For[p = 1, p ≤ numberOfFitParamToBeSaved, p += 1,
  simParamMedianD[[p, r]] = {};
  simParamQuantile1D[[p, r]] = {};
  simParamQuantile2D[[p, r]] = {};
];
];
];

-----
-----
-----      Ca = 0.703073
uM      -----
-----
-----

```





... **InterpolatingFunction**: Input value {0.1} lies outside the range of data in the interpolating function. Extrapolation will be used.

... **InterpolatingFunction**: Input value {0.4} lies outside the range of data in the interpolating function. Extrapolation will be used.

```

----- C5
----- C10
----- D
-----
-----
----- Ca = 4.79194
----- uM
-----
-----
-----

```



... **InterpolatingFunction**: Input value {0.1} lies outside the range of data in the interpolating function. Extrapolation will be used.

... **General**: Further output of InterpolatingFunction::dmval will be suppressed during this calculation.

```

----- C5

```

... **Set**: Symbol simParamNoiseC5 in part assignment does not have an immediate value.

... **Set**: Symbol simParamNoiseC5 in part assignment does not have an immediate value.

... **Set**: Symbol simParamNoiseC5 in part assignment does not have an immediate value.

... **General**: Further output of Set::noval will be suppressed during this calculation.

... **NonlinearModelFit**: Failed to converge to the requested accuracy or precision within 100 iterations.

... **Part**: Part specification simParamNoiseC5[[2, 1]] is longer than depth of object.

... **Part**: Part specification simParamNoiseC5[[6, 1]] is longer than depth of object.

... **Part**: Part specification simParamNoiseC5[[11, 1]] is longer than depth of object.

... **General**: Further output of Part::partd will be suppressed during this calculation.


take mono

NonlinearModelFit: Failed to converge to the requested accuracy or precision within 100 iterations.

NonlinearModelFit: Failed to converge to the requested accuracy or precision within 100 iterations.

General: Further output of NonlinearModelFit::cvmit will be suppressed during this calculation.

take mono



Mono:  $\chi^2 = \text{simParamNoiseC5}[[2, 3]]$        $d = \text{simParamNoiseC5}[[2, 3]]$   
 $a = \text{simParamNoiseC5}[[4, 3]]$        $t = \frac{1}{\text{simParamNoiseC5}[[5, 3]]}$


Bi:  $\text{ratio } \chi^2_{\text{Mono}}/\chi^2_{\text{Bi}} = \text{simParamNoiseC5}[[6, 3]]$        $d = \text{simParamNoiseC5}[[7, 3]]$   
 $a = \text{simParamNoiseC5}[[8, 3]]$        $a1 = \text{simParamNoiseC5}[[9, 3]]$   
 $t1 = \frac{1}{\text{simParamNoiseC5}[[10, 3]]}$        $t2 = \frac{1}{\text{simParamNoiseC5}[[11, 3]]}$

C10

take mono

take mono

take mono



Mono:  $\chi^2 = 7.08688$        $d = 7.08688$        $a = 1.17872$        $t = 0.00403296$

Bi:  $\text{ratio } \chi^2_{\text{Mono}}/\chi^2_{\text{Bi}} = 0.999794$        $d = 0.0007$        $a =$   
 $1.44509$        $a1 = 1.12956$        $t1 = 0.00391193$        $t2 = 0.070724$

Quantile: Argument {} should be a non-empty list.

Quantile: Argument {} should be a non-empty list.

Quantile: Argument {} should be a non-empty list.


... **General:** Further output of Quantile::empt will be suppressed during this calculation.

D

take mono

take mono

take mono




Mono:  $\chi^2 = 0.158654$        $d = 0.158654$        $a = 1.49144$        $t = 0.00550646$


Bi: ratio  $\chi^2_{\text{Mono}}/\chi^2_{\text{Bi}} = 1.01159$        $d = 0.000623127$        $a =$   
 $0.86273$        $a1 = 2.87366$        $t1 = 0.00768285$        $t2 = 0.0181125$

Ca = 5.53376

uM








C5

take mono



```

Mono: chi2 = simParamNoiseC5[[2, 3]]      d = simParamNoiseC5[[2, 3]]
      a = simParamNoiseC5[[4, 3]]      t =  $\frac{1}{\text{simParamNoiseC5}[[5, 3]]}$ 

Bi: ratio chi2Mono/chi2Bi = simParamNoiseC5[[6, 3]]      d = simParamNoiseC5[[7, 3]]
    a = simParamNoiseC5[[8, 3]]      a1 = simParamNoiseC5[[9, 3]]
    t1 =  $\frac{1}{\text{simParamNoiseC5}[[10, 3]]}$       t2 =  $\frac{1}{\text{simParamNoiseC5}[[11, 3]]}$ 


```

C10

take mono

take mono

take mono



Mono:  $\chi^2 = 8.52092$        $d = 8.52092$        $a = 1.79507$        $t = 0.0052043$


Bi: ratio  $\chi^2_{\text{Mono}}/\chi^2_{\text{Bi}} = 0.99677$        $d = 0.000541875$        $a =$   
 $1.82858$        $a1 = 1.33796$        $t1 = 0.00416516$        $t2 = 0.00971541$

----- D

take mono

take mono

take mono



Mono:  $\chi^2 = 0.150791$        $d = 0.150791$        $a = 1.52878$        $t = 0.00397755$


Bi: ratio  $\chi^2_{\text{Mono}}/\chi^2_{\text{Bi}} = 1.00064$        $d = 0.000535539$        $a =$   
 $1.481$        $a1 = 1.94351$        $t1 = 0.00439514$        $t2 = 0.00743034$


-----

----- Ca = 25.7412


uM

-----





C5



```

Mono: chi2 = simParamNoiseC5[[2, 3]]      d = simParamNoiseC5[[2, 3]]
      a = simParamNoiseC5[[4, 3]]      t =  $\frac{1}{\text{simParamNoiseC5}[[5, 3]]}$ 

Bi: ratio chi2Mono/chi2Bi = simParamNoiseC5[[6, 3]]      d = simParamNoiseC5[[7, 3]]
    a = simParamNoiseC5[[8, 3]]      a1 = simParamNoiseC5[[9, 3]]
    t1 =  $\frac{1}{\text{simParamNoiseC5}[[10, 3]]}$       t2 =  $\frac{1}{\text{simParamNoiseC5}[[11, 3]]}$ 


```

C10

```

take bi
take bi
take bi

```



```

Mono: chi2 = 6.84202      d = 6.84202      a = 2.32614      t = 0.00202853

```


Bi: ratio  $\chi^2_{\text{Mono}}/\chi^2_{\text{Bi}} = 1.0904$        $d = 0.00016458$        $a =$   
 3.45458       $a1 = 1.50402$        $t1 = 0.000799165$        $t2 = 0.0147441$

----- D

take bi

take bi

take bi



Mono:  $\chi^2 = 0.623135$        $d = 0.623135$        $a = 2.3009$        $t = 0.00192783$


Bi: ratio  $\chi^2_{\text{Mono}}/\chi^2_{\text{Bi}} = 3.66281$        $d = 0.0000793084$        $a =$   
 2.50245       $a1 = 1.10304$        $t1 = 0.000577102$        $t2 = 0.00413312$


-----

----- Ca = 29.9583


uM

-----





C5



```

Mono: chi2 = simParamNoiseC5[[2, 3]]      d = simParamNoiseC5[[2, 3]]
      a = simParamNoiseC5[[4, 3]]      t = 1 / simParamNoiseC5[[5, 3]]

Bi: ratio chi2Mono/chi2Bi = simParamNoiseC5[[6, 3]]      d = simParamNoiseC5[[7, 3]]
    a = simParamNoiseC5[[8, 3]]      a1 = simParamNoiseC5[[9, 3]]
    t1 = 1 / simParamNoiseC5[[10, 3]]      t2 = 1 / simParamNoiseC5[[11, 3]]


```

C10

```
take mono
```

```
take bi
```

```
take bi
```



```

Mono: chi2 = 10.4883      d = 10.4883      a = 2.2743      t = 0.00160435

```


Bi: ratio  $\chi^2_{\text{Mono}}/\chi^2_{\text{Bi}} = 1.09923$        $d = 0.0000747615$        $a =$   
 3.29227       $a_1 = 1.57775$        $t_1 = 0.000681779$        $t_2 = 0.0142666$

----- D

take bi

take bi

take bi



Mono:  $\chi^2 = 0.91061$        $d = 0.91061$        $a = 2.30711$        $t = 0.00181864$


Bi: ratio  $\chi^2_{\text{Mono}}/\chi^2_{\text{Bi}} = 4.79737$        $d = 0.0000900976$        $a =$   
 2.46542       $a_1 = 1.0158$        $t_1 = 0.000302678$        $t_2 = 0.00344934$


-----

----- Ca = 74.0312

uM


-----





C5

- NonlinearModelFit: The step size in the search has become less than the tolerance prescribed by the PrecisionGoal option, but the gradient is larger than the tolerance specified by the AccuracyGoal option. There is a possibility that the method has stalled at a point that is not a local minimum.
- General: Exp[−736.49] is too small to represent as a normalized machine number; precision may be lost.
- General: Exp[−793.04] is too small to represent as a normalized machine number; precision may be lost.
- General: Exp[−849.59] is too small to represent as a normalized machine number; precision may be lost.
- General: Further output of General::munfl will be suppressed during this calculation.



```

Mono: chi2 = simParamNoiseC5[[2, 3]]      d = simParamNoiseC5[[2, 3]]
      a = simParamNoiseC5[[4, 3]]      t = 1 / simParamNoiseC5[[5, 3]]

Bi: ratio chi2Mono/chi2Bi = simParamNoiseC5[[6, 3]]      d = simParamNoiseC5[[7, 3]]
    a = simParamNoiseC5[[8, 3]]      a1 = simParamNoiseC5[[9, 3]]
    t1 = 1 / simParamNoiseC5[[10, 3]]      t2 = 1 / simParamNoiseC5[[11, 3]]


```

C10

```

take bi
take mono
take bi

```



Mono: chi2 = 8.52843      d = 8.52843      a = 2.29944      t = 0.00158323


Bi: ratio chi2Mono/chi2Bi = 1.07682      d = 0.000145139      a =  
2.39724      a1 = 0.936027      t1 = 0.0000897784      t2 = 0.00259214

----- D

take bi

take bi

take bi



Mono: chi2 = 1.41395      d = 1.41395      a = 2.33924      t = 0.00155065

Bi: ratio chi2Mono/chi2Bi = 5.74032      d = 0.0000457876      a =  
2.54393      a1 = 1.22128      t1 = 0.000236239      t2 = 0.00374787

## Plots

In[980]:= caFact = 1\*^6;

In[981]:= colorA = Green;  
colorB = Red;  
colorC = Blue;




## release rate $1/\tau_1$ (merge of mono $1/\tau_1$ and bi $1/\tau_1$ )

In[984]:= `simParam = 15;`

### C5

```
In[985]:= gr1a = ListLogLogPlot[
  Transpose[{dataT1C5Ca, dataT1C5RelRate}], PlotStyle → {colorA}];
gr2a = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamMedianC5[[simParam, All]]}],
  PlotStyle → {colorA}, Joined → True, PlotRange → All];
gr3a = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamQuantile1C5[[simParam, All]]}],
  PlotStyle → {colorA}, Joined → True, PlotRange → All];
gr4a = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamQuantile2C5[[simParam, All]]}],
  PlotStyle → {colorA}, Joined → True, PlotRange → All];
Show[gr1a, gr2a, gr3a, gr4a, PlotRange → All]
If[exportYes == 1,
  Export["plot InvTau1 C5 data.txt",
    Transpose[{dataT1C5Ca, dataT1C5RelRate}], "Table"];
toExport = Transpose[{caFact simCaList, simParamQuantile1C5[[simParam, All]],
  simParamMedianC5[[simParam, All]], simParamQuantile2C5[[simParam, All]]}];
Export["plot InvTau1 C5 fit - quantiles and median.txt", toExport, "Table"];
];
```




## C10

```

In[991]:= gr1b = ListLogLogPlot[
  Transpose[{dataT1C10Ca, dataT1C10RelRate}], PlotStyle → {colorB}];
gr2b = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamMedianC10[[simParam, All]]}],
  PlotStyle → {colorB}, Joined → True, PlotRange → All];
gr3b = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamQuantile1C10[[simParam, All]]}],
  PlotStyle → {colorB}, Joined → True, PlotRange → All];
gr4b = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamQuantile2C10[[simParam, All]]}],
  PlotStyle → {colorB}, Joined → True, PlotRange → All];
Show[gr1b, gr2b, gr3b, gr4b, PlotRange → All]
If[exportYes == 1,
  Export["plot InvTau1 C10 data.txt",
    Transpose[{dataT1C10Ca, dataT1C10RelRate}], "Table"];
toExport = Transpose[{caFact simCaList, simParamQuantile1C10[[simParam, All]],
  simParamMedianC10[[simParam, All]],
  simParamQuantile2C10[[simParam, All]]}];
Export["plot InvTau1 C10 fit - quantiles and median.txt", toExport, "Table"];
];

```




D

```


In[997]:= gr1c =
  ListLogLogPlot[Transpose[{dataT1DCa, dataT1DRelRate}], PlotStyle → {colorC}];
gr2c = ListLogLogPlot[Transpose[
  {caFact simCaList, simParamMedianD[[simParam, All]]}],
  PlotStyle → {colorC}, Joined → True, PlotRange → All];
gr3c = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamQuantile1D[[simParam, All]]}],
  PlotStyle → {colorC}, Joined → True, PlotRange → All];
gr4c = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamQuantile2D[[simParam, All]]}],
  PlotStyle → {colorC}, Joined → True, PlotRange → All];
Show[gr1c, gr2c, gr3c, gr4c, PlotRange → All]
If[exportYes == 1,
  Export["plot InvTau1 D data.txt",
    Transpose[{dataT1DCa, dataT1DRelRate}], "Table"];
  toExport = Transpose[{caFact simCaList, simParamQuantile1D[[simParam, All]],
    simParamMedianD[[simParam, All]], simParamQuantile2D[[simParam, All]]}];
  Export["plot InvTau1 D fit - quantiles and median.txt", toExport, "Table"];
];

```



## C5 and C10 and D

```
In[1003]:= Show[gr1a, gr2a, gr3a, gr4a, gr1b, gr2b, gr3b,
  gr4b, gr1c, gr2c, gr3c, gr4c, PlotRange -> {All, {0, 10}}]
```



```
In[1004]:= Show[gr1a, gr1b, gr1c, PlotRange -> {All, {2, 10}}];
```

---

## delay (mono and bi merged)

```
In[1005]:= simParam = 12;
```

```
In[1006]:= Transpose[{caFact simCaList, simParamMedianC5[[simParam, All]]}] // TableForm
```

Out[1006]//TableForm=


0.703073	
4.79194	Median[simParamNoiseC5[[12, All]]]
5.53376	Median[simParamNoiseC5[[12, All]]]
25.7412	Median[simParamNoiseC5[[12, All]]]
29.9583	Median[simParamNoiseC5[[12, All]]]
74.0312	Median[simParamNoiseC5[[12, All]]]

## C5

```

In[1007]:= gr1a =
  ListLogLogPlot[Transpose[{dataT1C5Ca, dataT1C5Delay}], PlotStyle → {colorA}];
gr2a = ListLogLogPlot[Transpose[
  {caFact simCaList, simParamMedianC5[[simParam, All]]}],
  PlotStyle → {colorA}, Joined → True, PlotRange → All];
gr3a = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamQuantile1C5[[simParam, All]]}],
  PlotStyle → {colorA}, Joined → True, PlotRange → All];
gr4a = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamQuantile2C5[[simParam, All]]}],
  PlotStyle → {colorA}, Joined → True, PlotRange → All];
Show[gr1a, gr2a, gr3a, gr4a, PlotRange → All]
If[exportYes == 1,
  Export["plot delay C5 data.txt",
    Transpose[{dataT1C5Ca, dataT1C5Delay}], "Table"];
toExport = Transpose[{caFact simCaList, simParamQuantile1C5[[simParam, All]],
  simParamMedianC5[[simParam, All]], simParamQuantile2C5[[simParam, All]]}];
Export["plot delay C5 fit - quantiles and median.txt", toExport, "Table"];
];

```




## C10

```

In[1013]:= gr1b = ListLogLogPlot[
  Transpose[{dataT1C10Ca, dataT1C10Delay}], PlotStyle → {colorB}];
gr2b = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamMedianC10[[simParam, All]]}],
  PlotStyle → {colorB}, Joined → True, PlotRange → All];
gr3b = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamQuantile1C10[[simParam, All]]}],
  PlotStyle → {colorB}, Joined → True, PlotRange → All];
gr4b = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamQuantile2C10[[simParam, All]]}],
  PlotStyle → {colorB}, Joined → True, PlotRange → All];
Show[gr1b, gr2b, gr3b, gr4b, PlotRange → All]
If[exportYes == 1,
  Export["plot delay C10 data.txt",
    Transpose[{dataT1C10Ca, dataT1C10Delay}], "Table"];
toExport = Transpose[{caFact simCaList, simParamQuantile1C10[[simParam, All]],
  simParamMedianC10[[simParam, All]],
  simParamQuantile2C10[[simParam, All]]}];
Export["plot delay C10 fit - quantiles and median.txt", toExport, "Table"];
];

```

Out[1017]=




D

```


In[1019]:= gr1c =
  ListLogLogPlot[Transpose[{dataT1DCa, dataT1DDelay}], PlotStyle → {colorC}];
gr2c = ListLogLogPlot[Transpose[
  {caFact simCaList, simParamMedianD[[simParam, All]]}],
  PlotStyle → {colorC}, Joined → True, PlotRange → All];
gr3c = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamQuantile1D[[simParam, All]]}],
  PlotStyle → {colorC}, Joined → True, PlotRange → All];
gr4c = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamQuantile2D[[simParam, All]]}],
  PlotStyle → {colorC}, Joined → True, PlotRange → All];
Show[gr1c, gr2c, gr3c, gr4c, PlotRange → All]
If[exportYes == 1,
  Export["plot delay D data.txt",
    Transpose[{dataT1DCa, dataT1DDelay}], "Table"];
toExport = Transpose[{caFact simCaList, simParamQuantile1D[[simParam, All]],
  simParamMedianD[[simParam, All]], simParamQuantile2D[[simParam, All]]}];
Export["plot delay D fit - quantiles and median.txt", toExport, "Table"];
];

```



## C5 and C10 and D

```
In[1025]:= Show[gr1a, gr2a, gr3a, gr4a, gr1b, gr2b, gr3b,
  gr4b, gr1c, gr2c, gr3c, gr4c, PlotRange → {-10, -5}]
```



```
In[1026]:= Show[gr1a, gr1b, gr1c, PlotRange → All];
```

---

## amp (merge of mono amp and bi amp)

```
In[1027]:= simParam = 13;
```




## C5

```

In[1028]:= gr1a = ListLogLogPlot[
  Transpose[{dataT1C5Ca, dataT1C5Amplitude}], PlotStyle → {colorA}];
gr2a = ListLogLogPlot[Transpose[{caFact simCaList,
  rrp simParamMedianC5[[simParam, All]]}],
  PlotStyle → {colorA}, Joined → True, PlotRange → All];
gr3a = ListLogLogPlot[Transpose[{caFact simCaList,
  rrp simParamQuantile1C5[[simParam, All]]}],
  PlotStyle → {colorA}, Joined → True, PlotRange → All];
gr4a = ListLogLogPlot[Transpose[{caFact simCaList,
  rrp simParamQuantile2C5[[simParam, All]]}],
  PlotStyle → {colorA}, Joined → True, PlotRange → All];
Show[gr1a, gr2a, gr3a, gr4a, PlotRange → All ]

```




## C10

```

In[1033]:= gr1b = ListLogLogPlot[
  Transpose[{dataT1C10Ca, dataT1C10Amplitude}], PlotStyle → {colorB}];
gr2b = ListLogLogPlot[Transpose[{caFact simCaList,
  rrp simParamMedianC10[[simParam, All]]}],
  PlotStyle → {colorB}, Joined → True, PlotRange → All];
gr3b = ListLogLogPlot[Transpose[{caFact simCaList,
  rrp simParamQuantile1C10[[simParam, All]]}],
  PlotStyle → {colorB}, Joined → True, PlotRange → All];
gr4b = ListLogLogPlot[Transpose[{caFact simCaList,
  rrp simParamQuantile2C10[[simParam, All]]}],
  PlotStyle → {colorB}, Joined → True, PlotRange → All];
Show[gr1b, gr2b, gr3b, gr4b, PlotRange → All ]

```

Out[1037]=




D

```

In[1038]:= gr1c = ListLogLogPlot[
  Transpose[{dataT1DCa, dataT1DAmplitude}], PlotStyle → {colorC}];
gr2c = ListLogLogPlot[Transpose[{caFact simCaList,
  rrp simParamMedianD[[simParam, All]]}],
  PlotStyle → {colorC}, Joined → True, PlotRange → All];
gr3c = ListLogLogPlot[Transpose[{caFact simCaList,
  rrp simParamQuantile1D[[simParam, All]]}],
  PlotStyle → {colorC}, Joined → True, PlotRange → All];
gr4c = ListLogLogPlot[Transpose[{caFact simCaList,
  rrp simParamQuantile2D[[simParam, All]]}],
  PlotStyle → {colorC}, Joined → True, PlotRange → All];
Show[gr1c, gr2c, gr3c, gr4c, PlotRange → All ]

```




C5 and C10 and D

```

In[1043]:= Show[gr1a, gr2a, gr3a, gr4a, gr1b, gr2b, gr3b,
  gr4b, gr1c, gr2c, gr3c, gr4c, PlotRange → {-1, 6} ]

```



release rate  $1/\tau^2$  of bi fits (if bi is justified)

```

In[1044]:= simParam = 16;


```

## C5

```

In[1045]:= gr1a = ListLogLogPlot[
  Transpose[{dataT2C5Ca, dataT2C5RelRate}], PlotStyle → {colorA}];
gr2a = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamMedianC5[[simParam, All]]}],
  PlotStyle → {colorA}, Joined → True, PlotRange → All];
gr3a = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamQuantile1C5[[simParam, All]]}],
  PlotStyle → {colorA}, Joined → True, PlotRange → All];
gr4a = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamQuantile2C5[[simParam, All]]}],
  PlotStyle → {colorA}, Joined → True, PlotRange → All];
Show[gr1a, gr2a, gr3a, gr4a, PlotRange → All]
If[exportYes == 1,
  Export["plot InvTau2 C5 data.txt",
    Transpose[{dataT2C5Ca, dataT2C5RelRate}], "Table"];
toExport = Transpose[{caFact simCaList, simParamQuantile1C5[[simParam, All]],
  simParamMedianC5[[simParam, All]], simParamQuantile2C5[[simParam, All]]}];
Export["plot InvTau2 C5 fit - quantiles and median.txt", toExport, "Table"];
];

```




## C10

```

In[1051]:= gr1b = ListLogLogPlot[
  Transpose[{dataT2C10Ca, dataT2C10RelRate}], PlotStyle → {colorB}];
gr2b = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamMedianC10[[simParam, All]]}],
  PlotStyle → {colorB}, Joined → True, PlotRange → All];
gr3b = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamQuantile1C10[[simParam, All]]}],
  PlotStyle → {colorB}, Joined → True, PlotRange → All];
gr4b = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamQuantile2C10[[simParam, All]]}],
  PlotStyle → {colorB}, Joined → True, PlotRange → All];
Show[gr1b, gr2b, gr3b, gr4b, PlotRange → All]
If[exportYes == 1,
  Export["plot InvTau2 C10 data.txt",
    Transpose[{dataT2C10Ca, dataT2C10RelRate}], "Table"];
toExport = Transpose[{caFact simCaList, simParamQuantile1C10[[simParam, All]],
  simParamMedianC10[[simParam, All]],
  simParamQuantile2C10[[simParam, All]]}];
Export["plot InvTau2 C10 fit - quantiles and median.txt", toExport, "Table"];
];

```




D

```

In[1057]:= gr1c =
  ListLogLogPlot[Transpose[{dataT2DCa, dataT2DRelRate}], PlotStyle → {colorC}];
gr2c = ListLogLogPlot[Transpose[
  {caFact simCaList, simParamMedianD[[simParam, All]]}],
  PlotStyle → {colorC}, Joined → True, PlotRange → All];
gr3c = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamQuantile1D[[simParam, All]]}],
  PlotStyle → {colorC}, Joined → True, PlotRange → All];
gr4c = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamQuantile2D[[simParam, All]]}],
  PlotStyle → {colorC}, Joined → True, PlotRange → All];
Show[gr1c, gr2c, gr3c, gr4c, PlotRange → All]
If[exportYes == 1,
  Export["plot InvTau2 D data.txt",
    Transpose[{dataT2DCa, dataT2DRelRate}], "Table"];
toExport = Transpose[{caFact simCaList, simParamQuantile1D[[simParam, All]],
  simParamMedianD[[simParam, All]], simParamQuantile2D[[simParam, All]]}];
Export["plot InvTau2 D fit - quantiles and median.txt", toExport, "Table"];
];


```

Out[1061]=



## C5 and C10 and D

```
In[1063]:= Show[gr1a, gr2a, gr3a, gr4a, gr1b, gr2b, gr3b,  
gr4b, gr1c, gr2c, gr3c, gr4c, PlotRange -> {All, {2, 10}}]
```



```
In[1064]:= Show[gr1a, gr1b, gr1c, PlotRange -> All];
```

---

amp1 of bi fits (if bi is justified)


```
In[1065]:= simParam = 14;
```

## C5

```

In[1066]:= gr1a = ListLogLogPlot[
  Transpose[{dataT2C5Ca, dataT2C5Amplitude1}], PlotStyle → {colorA}];
gr2a = ListLogLogPlot[Transpose[{caFact simCaList,
  rrp simParamMedianC5[[simParam, All]]}],
  PlotStyle → {colorA}, Joined → True, PlotRange → All];
gr3a = ListLogLogPlot[Transpose[{caFact simCaList,
  rrp simParamQuantile1C5[[simParam, All]]}],
  PlotStyle → {colorA}, Joined → True, PlotRange → All];
gr4a = ListLogLogPlot[Transpose[{caFact simCaList,
  rrp simParamQuantile2C5[[simParam, All]]}],
  PlotStyle → {colorA}, Joined → True, PlotRange → All];
Show[gr1a, gr2a, gr3a, gr4a, PlotRange → All ]

```






## C10

```

In[1071]:= gr1b = ListLogLogPlot[
  Transpose[{dataT2C10Ca, dataT2C10Amplitude1}], PlotStyle -> {colorB}];
gr2b = ListLogLogPlot[Transpose[{caFact simCaList,
  rrp simParamMedianC10[[simParam, All]]}],
  PlotStyle -> {colorB}, Joined -> True, PlotRange -> All];
gr3b = ListLogLogPlot[Transpose[{caFact simCaList,
  rrp simParamQuantile1C10[[simParam, All]]}],
  PlotStyle -> {colorB}, Joined -> True, PlotRange -> All];
gr4b = ListLogLogPlot[Transpose[{caFact simCaList,
  rrp simParamQuantile2C10[[simParam, All]]}],
  PlotStyle -> {colorB}, Joined -> True, PlotRange -> All];
Show[gr1b, gr2b, gr3b, gr4b, PlotRange -> All ]

```




D

```

In[1076]:= gr1c = ListLogLogPlot[
  Transpose[{dataT2DCa, dataT2DAmplitude1}], PlotStyle → {colorC}];
gr2c = ListLogLogPlot[Transpose[{caFact simCaList,
  rrp simParamMedianD[[simParam, All]]}],
  PlotStyle → {colorC}, Joined → True, PlotRange → All];
gr3c = ListLogLogPlot[Transpose[{caFact simCaList,
  rrp simParamQuantile1D[[simParam, All]]}],
  PlotStyle → {colorC}, Joined → True, PlotRange → All];
gr4c = ListLogLogPlot[Transpose[{caFact simCaList,
  rrp simParamQuantile2D[[simParam, All]]}],
  PlotStyle → {colorC}, Joined → True, PlotRange → All];
Show[gr1c, gr2c, gr3c, gr4c, PlotRange → All]

```




C5 and C10 and D

```

In[1081]:= Show[gr1a, gr2a, gr3a, gr4a, gr1b, gr2b,
  gr3b, gr4b, gr1c, gr2c, gr3c, gr4c, PlotRange → All]
Show[gr1a, gr1b, gr1c, PlotRange → All];

```




## chi2 mono/bi ratio

In[1083]:= `simParam = 6;`

### C5

In[1084]:= `gr1a = ListLogLogPlot[  
 Transpose[{dataT1C5Ca, dataT1C5ChiRatio}], PlotStyle → {colorA}];  
gr2a = ListLogLogPlot[Transpose[{caFact simCaList,  
 simParamMedianC5[[simParam, All]]}],  
 PlotStyle → {colorA}, Joined → True, PlotRange → All];  
gr3a = ListLogLogPlot[Transpose[{caFact simCaList,  
 simParamQuantile1C5[[simParam, All]]}],  
 PlotStyle → {colorA}, Joined → True, PlotRange → All];  
gr4a = ListLogLogPlot[Transpose[{caFact simCaList,  
 simParamQuantile2C5[[simParam, All]]}],  
 PlotStyle → {colorA}, Joined → True, PlotRange → All];  
Show[gr1a, gr2a, gr3a, gr4a, PlotRange → {All, {-0.8, 5}} ]  
If[exportYes == 1,  
 Export["plot chi2Ratio C5 data.txt",  
 Transpose[{dataT1C5Ca, dataT1C5ChiRatio}], "Table";  
 toExport = Transpose[{caFact simCaList, simParamQuantile1C5[[simParam, All]],  
 simParamMedianC5[[simParam, All]], simParamQuantile2C5[[simParam, All]]}];  
 Export["plot chi2Ratio C5 fit - quantiles and median.txt",  
 toExport, "Table";  
];`

Out[1088]=




## C10

```

In[1090]:= gr1b = ListLogLogPlot[
  Transpose[{dataT1C10Ca, dataT1C10ChiRatio}], PlotStyle → {colorB}];
gr2b = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamMedianC10[[simParam, All]]}],
  PlotStyle → {colorB}, Joined → True, PlotRange → All];
gr3b = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamQuantile1C10[[simParam, All]]}],
  PlotStyle → {colorB}, Joined → True, PlotRange → All];
gr4b = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamQuantile2C10[[simParam, All]]}],
  PlotStyle → {colorB}, Joined → True, PlotRange → All];
Show[gr1b, gr2b, gr3b, gr4b, PlotRange → All]
If[exportYes == 1,
  Export["plot chi2Ratio C10 data.txt",
    Transpose[{dataT1C10Ca, dataT1C10ChiRatio}], "Table"];
toExport = Transpose[{caFact simCaList, simParamQuantile1C10[[simParam, All]],
  simParamMedianC10[[simParam, All]],
  simParamQuantile2C10[[simParam, All]]}];
Export["plot chi2Ratio C10 fit - quantiles and median.txt",
  toExport, "Table"];
];

```

Out[1094]=




D

```


In[1096]:= gr1c =
  ListLogLogPlot[Transpose[{dataT1DCa, dataT1DChiRatio}], PlotStyle → {colorC}];
gr2c = ListLogLogPlot[Transpose[
  {caFact simCaList, simParamMedianD[[simParam, All]]}],
  PlotStyle → {colorC}, Joined → True, PlotRange → All];
gr3c = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamQuantile1D[[simParam, All]]}],
  PlotStyle → {colorC}, Joined → True, PlotRange → All];
gr4c = ListLogLogPlot[Transpose[{caFact simCaList,
  simParamQuantile2D[[simParam, All]]}],
  PlotStyle → {colorC}, Joined → True, PlotRange → All];
Show[gr1c, gr2c, gr3c, gr4c, PlotRange → All]
If[exportYes == 1,
  Export["plot chi2Ratio D data.txt",
    Transpose[{dataT1DCa, dataT1DChiRatio}], "Table"];
toExport = Transpose[{caFact simCaList, simParamQuantile1D[[simParam, All]],
  simParamMedianD[[simParam, All]], simParamQuantile2D[[simParam, All]]}];
Export["plot chi2Ratio D fit - quantiles and median.txt", toExport, "Table"];
];

```




## C5 and C10 and D

```
In[1102]:= Show[gr1a, gr2a, gr3a, gr4a, gr1b, gr2b, gr3b,
  gr4b, gr1c, gr2c, gr3c, gr4c, PlotRange → {All, {-0.8, 5}}]
Show[gr1a, gr1b, gr1c, PlotRange → All];
```




## Nv


```
In[1104]:= For[NvCount = 1, NvCount ≤ 7, NvCount += 1,
  Print[" time for Nv (ms) = ", 1000 * timeOfNv[NvCount]];
  gr1a = ListLogLogPlot[
    Transpose[{dataT1C5Ca, dataT1C5Nv[NvCount]}], PlotStyle → {colorA}];
  gr1b = ListLogLogPlot[Transpose[{dataT1C10Ca, dataT1C10Nv[NvCount]}],
    PlotStyle → {colorB}];
  gr1c = ListLogLogPlot[Transpose[{dataT1DCa, dataT1DNv[NvCount]}],
    PlotStyle → {colorC}];
  gr2 = ListLogLogPlot[Transpose[{caFact simCaList, rrp simParamNv[NvCount,
    All]}], PlotStyle → {Black}, Joined → True, PlotRange → All];
  Show[gr1a, gr1b, gr1c, gr2, PlotRange → {All, {-4, 5}}] // Print;
];
time for Nv (ms) = 0.1
```




```
time for Nv (ms) = 0.2
```




time for Nv (ms) = 1.




time for Nv (ms) = 5.




time for Nv (ms) = 10.



time for Nv (ms) = 100.



time for Nv (ms) = 400.





## sustained release 10 to 100 ms


```

In[1105]:= ttt1 = Transpose[{dataT1C5Ca, (dataT1C5Nv[[6]] - dataT1C5Nv[[5]]) / 0.09}];
ttt2 = Transpose[{dataT1C10Ca, (dataT1C10Nv[[6]] - dataT1C10Nv[[5]]) / 0.09}];
ttt3 = Transpose[{dataT1DCa, (dataT1DNv[[6]] - dataT1DNv[[5]]) / 0.09}];
ttt4 = Transpose[
  {caFact simCaList, rrp (simParamNv[[6, All]] - simParamNv[[5, All]]) / 0.09}];

gr1a = ListLogLogPlot[ttt1, PlotStyle -> {colorA}];
gr1b = ListLogLogPlot[ttt2, PlotStyle -> {colorB}];
gr1c = ListLogLogPlot[ttt3, PlotStyle -> {colorC}];
gr2 = ListLogLogPlot[ttt4, PlotStyle -> {Black}, Joined -> True, PlotRange -> All];
Show[gr1a, gr1b, gr1c, gr2, PlotRange -> {All, {0, 7}}] // Print;

gr1a = ListLogLinearPlot[ttt1, PlotStyle -> {colorA}];
gr1b = ListLogLinearPlot[ttt2, PlotStyle -> {colorB}];
gr1c = ListLogLinearPlot[ttt3, PlotStyle -> {colorC}];
gr2 = ListLogLinearPlot[ttt4,
  PlotStyle -> {Black}, Joined -> True, PlotRange -> All];
Show[gr1a, gr1b, gr1c, gr2, PlotRange -> {All, All}] // Print;

```



```
In[1113]:= If[exportYes == 1,
  Export["plot sustained release Cm5 data.txt", ttt1, "Table"];
  Export["plot sustained release Cm10 data.txt", ttt2, "Table"];
  Export["plot sustained release D data.txt", ttt3, "Table"];
  Export["plot sustained release sim.txt", ttt4, "Table"]
];
```

## Nv normalize to the value at 5 ms

```
In[1114]:= timeOfNv
  nromPos = 5;
  1000 * timeOfNv[[nromPos]]
```

```
Out[1114]= {0.0001, 0.0002, 0.001, 0.005, 0.01, 0.1, 0.4}
```

```
Out[1116]= 10.
```

```
In[1117]:= dataT1DNvNorm = Transpose[Transpose[dataT1DNv] / dataT1DNv[[nromPos]]];
  dataT1C10NvNorm = Transpose[Transpose[dataT1C10Nv] / dataT1C10Nv[[nromPos]]];
  dataT1C5NvNorm = Transpose[Transpose[dataT1C5Nv] / dataT1C5Nv[[nromPos]]];
```

```
In[1120]:= dataT1C5NvNorm // TableForm
```

```
Out[1120]//TableForm=
```

0.	0.	0.	0.	0.	0.	0.
0.	0.	0.	0.	0.	0.	0.
0.20362	0.265687	0.42823	0.550679	0.804146	0.862111	0.657036
0.719618	0.914034	0.947765	0.995367	0.999983	0.961307	0.985586
1.	1.	1.	1.	1.	1.	1.
1.97523	1.00693	1.44309	1.00001	1.	1.38099	1.17479
1.98885	1.00693	1.64647	1.00001	1.	1.52805	1.34343

```
In[1121]:= simParamNv // TableForm
```

```
simParamNvNorm = Transpose[Transpose[simParamNv] / simParamNv[[nromPos]]];
simParamNvNorm // TableForm
```

```
Out[1121]//TableForm=
```

$1.15831 \times 10^{-8}$	0.0000225289	0.0000470166	0.0120637	0.0330104	0.182311
$4.04537 \times 10^{-7}$	0.000699228	0.00131308	0.158638	0.305208	0.713778
0.000100151	0.0977688	0.154622	1.16532	1.26874	1.44248
0.00143825	0.822265	1.03048	2.08205	2.11032	2.18122
0.00304654	1.21973	1.41133	2.40188	2.42511	2.49533
0.022516	2.55684	2.85988	7.23487	7.40447	7.86461
0.0489061	21.376	21.9125	20.38	19.6389	23.8767


```
Out[1123]//TableForm=
```

$3.80206 \times 10^{-6}$	0.0000184704	0.0000333137	0.0050226	0.0136119	0.073061
0.000132786	0.000573263	0.000930384	0.0660475	0.125853	0.286046
0.0328736	0.0801559	0.109558	0.48517	0.523167	0.578071
0.472094	0.674135	0.730146	0.866841	0.870194	0.87412
1.	1.	1.	1.	1.	1.
7.39066	2.09623	2.02637	3.01217	3.05325	3.15173
16.053	17.5252	15.5262	8.485	8.09814	9.56857


```

In[1124]:= For[NvCount = 1, NvCount ≤ 7, NvCount += 1,
  Print[" time for Nv (ms) = ", 1000 * timeOfNv[[NvCount]]];
  gr1a = ListLogLogPlot[
    Transpose[{dataT1C5Ca, dataT1C5NvNorm[[NvCount]]}], PlotStyle → {colorA}];
  gr1b = ListLogLogPlot[Transpose[{dataT1C10Ca, dataT1C10NvNorm[[NvCount]]}],
    PlotStyle → {colorB}];
  gr1c = ListLogLogPlot[Transpose[{dataT1DCa, dataT1DNvNorm[[NvCount]]}],
    PlotStyle → {colorC}];
  gr2 = ListLogLogPlot[Transpose[{caFact simCaList, simParamNvNorm[[NvCount,
    All]]}], PlotStyle → {Black}, Joined → True, PlotRange → All];
  Show[gr1a, gr1b, gr1c, gr2, PlotRange → {All, {-5, 1}}] // Print;
];
time for Nv (ms) = 0.1


```




time for Nv (ms) = 0.2




time for Nv (ms) = 1.




time for Nv (ms) = 5.




time for Nv (ms) = 10.



time for Nv (ms) = 100.



time for Nv (ms) = 400.



## Export Nv

```
In[1125]:= If[exportYes == 1,
  Export["Nv export Ca,0.0001,0.0002,0.001,0.005,0.01,0.1,0.4.txt",
    Transpose[Prepend[simParamNv, caFact simCaList]], "Table"];
];
```

# Print some values

## C5

```
In[1126]:= Transpose[simParamMedianC5] // TableForm
Transpose[simParamQuantile1C5] // TableForm
Transpose[simParamQuantile2C5] // TableForm
```

Out[1126]//TableForm=

Median[simParamNoiseC5[1, All]]	Median[simParamNoiseC5[2, All]]	Median[simPa
Median[simParamNoiseC5[1, All]]	Median[simParamNoiseC5[2, All]]	Median[simPa
Median[simParamNoiseC5[1, All]]	Median[simParamNoiseC5[2, All]]	Median[simPa
Median[simParamNoiseC5[1, All]]	Median[simParamNoiseC5[2, All]]	Median[simPa
Median[simParamNoiseC5[1, All]]	Median[simParamNoiseC5[2, All]]	Median[simPa

Out[1127]//TableForm=

Quantile[simParamNoiseC5[1, All], 0.25]	Quantile[simParamNoiseC5[2, All], 0.25]
Quantile[simParamNoiseC5[1, All], 0.25]	Quantile[simParamNoiseC5[2, All], 0.25]
Quantile[simParamNoiseC5[1, All], 0.25]	Quantile[simParamNoiseC5[2, All], 0.25]
Quantile[simParamNoiseC5[1, All], 0.25]	Quantile[simParamNoiseC5[2, All], 0.25]
Quantile[simParamNoiseC5[1, All], 0.25]	Quantile[simParamNoiseC5[2, All], 0.25]

Out[1128]//TableForm=

Quantile[simParamNoiseC5[1, All], 0.75]	Quantile[simParamNoiseC5[2, All], 0.75]
Quantile[simParamNoiseC5[1, All], 0.75]	Quantile[simParamNoiseC5[2, All], 0.75]
Quantile[simParamNoiseC5[1, All], 0.75]	Quantile[simParamNoiseC5[2, All], 0.75]
Quantile[simParamNoiseC5[1, All], 0.75]	Quantile[simParamNoiseC5[2, All], 0.75]
Quantile[simParamNoiseC5[1, All], 0.75]	Quantile[simParamNoiseC5[2, All], 0.75]

## C10

```
In[1129]:= Transpose[simParamMedianC10] // TableForm
Transpose[simParamQuantile1C10] // TableForm
Transpose[simParamQuantile2C10] // TableForm
```

Out[1129]//TableForm=

0	7.71188	0.0002	1.47987	160.138	0.999958	0.0002	2
0	7.8405	0.000429173	1.62998	227.791	1.0016	0.000541875	1
0	8.82845	-0.0001	2.32614	492.968	1.0904	0.000166732	2
0	7.98178	-0.000113113	2.2743	611.729	1.10079	0.0000747615	3
0	8.52843	-0.000353607	2.33671	581.76	1.06048	0.000145139	2

Out[1130]//TableForm=

0	7.08688	0.000126294	1.17872	71.2006	0.999794	0.0002
0	7.64974	0.0004	1.41652	192.149	0.99677	0.000360713
0	6.84202	-0.000209557	2.31236	489.208	1.07923	0.00016458
0	7.73302	-0.000542769	2.23329	484.653	1.09923	-0.0000275514
0	7.1172	-0.00040585	2.29944	571.306	0.861835	$2.18527 \times 10^{-17}$

Out[1131]//TableForm=

0	9.16516	0.0007	2.51777	247.957	1.00488	0.0007	2.
0	8.52092	0.000947926	1.79507	281.491	1.01257	0.00106018	36
0	9.75145	-0.0000231327	2.34355	549.149	1.09068	0.0002	3.
0	10.4883	-0.0001	2.3394	623.304	1.21877	0.000121074	35
0	10.3438	-0.000214012	2.34291	631.621	1.07682	0.000530734	2.

## D

```
In[1132]:= Transpose[simParamMedianD] // TableForm
Transpose[simParamQuantile1D] // TableForm
Transpose[simParamQuantile2D] // TableForm
```

Out[1132]//TableForm=

0	0.158654	0.000641456	1.49144	181.605	1.01159	0.000623127	0
0	0.150791	0.000542492	1.52878	251.411	1.00113	0.000535539	1
0	0.657417	-0.000147871	2.3009	523.787	4.20555	0.000105559	2
0	0.887898	-0.000208162	2.29844	561.668	4.79737	0.0000896594	2
0	1.36275	-0.000259953	2.33484	665.864	5.74032	0.0000457876	2

Out[1133]//TableForm=

0	0.157877	0.000618486	1.47258	178.885	1.	0.000589261	0
0	0.132567	0.000430563	1.50741	223.687	1.00064	0.000422803	1
0	0.623135	-0.000150779	2.30057	518.718	3.66281	0.0000793084	2
0	0.839884	-0.000228528	2.29565	549.863	4.7089	0.000073433	2
0	1.35841	-0.00028396	2.32779	644.892	5.40133	0.0000408617	2

Out[1134]//TableForm=

0	0.171913	0.000743647	1.50705	191.866	1.02839	0.000743647	1
0	0.163033	0.000653992	1.60985	271.131	1.00906	0.000681785	1
0	0.715741	-0.00011199	2.3021	533.414	4.71027	0.000124935	2
0	0.91061	-0.0002	2.30711	564.712	5.79008	0.0000900976	2
0	1.41395	-0.000257475	2.33924	666.878	7.28554	0.0000856202	2

## Nv

```
In[1135]:= Transpose[simParamNv] // TableForm
```


Out[1135]//TableForm=

$1.15831 \times 10^{-8}$	$4.04537 \times 10^{-7}$	0.000100151	0.00143825	0.00304654	0.02251
0.0000225289	0.000699228	0.0977688	0.822265	1.21973	2.55684
0.0000470166	0.00131308	0.154622	1.03048	1.41133	2.85988
0.0120637	0.158638	1.16532	2.08205	2.40188	7.23487
0.0330104	0.305208	1.26874	2.11032	2.42511	7.40447
0.182311	0.713778	1.44248	2.18122	2.49533	7.86461

# EPSC with different caRest

## Interpolate





```
In[1136]:= locaCa = Transpose[{dataLocalCaTime, dataLocalCa}];
locaCaWithoutdublicties = Mean /@ GatherBy[locaCa, First];
interpFunc = Interpolation[locaCaWithoutdublicties, InterpolationOrder → 1];
caFunc[t_] := interpFunc[t];
Plot[caFunc[t], {t, 0.000, 0.003}, PlotRange → All]
```








## NDSolve

```
In[1141]:= timeStartForPlot = 0.0;
timeEndForPlot = 0.003;
merkSS = NDSolve[eq,
  {fillStateSS, ss1, ss2, ss3, ss4, ss5, ss6, ss7, sitePlugging}, {t, 0, 0.003}];
Plot[(fillStateSS[t] /. merkSS), {t, timeStartForPlot, timeEndForPlot},
  PlotRange → All]
Plot[(ss1[t] /. merkSS), {t, timeStartForPlot, timeEndForPlot}, PlotRange → All]
Plot[(ss2[t] /. merkSS), {t, timeStartForPlot, timeEndForPlot}, PlotRange → All]
Plot[(ss3[t] /. merkSS), {t, timeStartForPlot, timeEndForPlot}, PlotRange → All]
Plot[(ss4[t] /. merkSS), {t, timeStartForPlot, timeEndForPlot}, PlotRange → All]
Plot[(ss5[t] /. merkSS), {t, timeStartForPlot, timeEndForPlot}, PlotRange → All]
Plot[(ss6[t] /. merkSS), {t, timeStartForPlot, timeEndForPlot}, PlotRange → All]
Plot[(ss7[t] /. merkSS), {t, timeStartForPlot, timeEndForPlot}, PlotRange → All]
Plot[(sitePlugging[t] /. merkSS),
  {t, timeStartForPlot, timeEndForPlot}, PlotRange → All]
```









## different caRest

```
In[1153]:= caRestLow = 30*^-9;
           caRestHigh = 180*^-9;
```

## Low Ca

### Initial occupancy

```
In[1155]:= (*calculate initial equilibrium occupancy*)
           caFunc[t_] := caRestLow;
           kprimScheme
           kunprimScheme
           fillStateSSInitial = kprimScheme / kunprimScheme
           kfillScheme
           kunfillScheme
           ss0Initial = fillStateSSInitial * kfillScheme / kunfillScheme
```

Out[1156]= 3.3867

Out[1157]= 8.61585

Out[1158]= 0.393078

Out[1159]= 111.823

Out[1160]= 181.545


Out[1161]= 0.242117





## Diff eq.





```
In[1162]:= Clear[caFunc, eq]; (*Clear is needed if the cell is executed for a 2nd time
when caFunc is already set to a value or an Interpolationfunction*)
caFunc[t_] := interpolFunc[t];
ss[t_] = {ss1[t], ss2[t], ss3[t], ss4[t], ss5[t], ss6[t], ss7[t]};
eq = {ss'[t] == (mat /. repl).ss[t],
      ss[0] == {ss0Initial, 0., 0., 0., 0., 0., 0.},
      (fillStateSS'[t] == kprim - kunprim fillStateSS[t] -
        kfill fillStateSS[t] + kunfill ss1[t]) /. repl,
      fillStateSS[0] == fillStateSSInitial,
      sitePlugging'[t] ==
        (1 - sitePlugging[t]) ss7'[t] - siteClearanceTau sitePlugging[t],
      sitePlugging[0] == 0
    };
```

## NDSolve

```
In[1166]:= merkSS = NDSolve[eq,
      {fillStateSS, ss1, ss2, ss3, ss4, ss5, ss6, ss7, sitePlugging}, {t, 0, 0.003}];
Plot[(fillStateSS[t] /. merkSS), {t, timeStartForPlot, timeEndForPlot},
      PlotRange → All]
Plot[(ss1[t] /. merkSS), {t, timeStartForPlot, timeEndForPlot}, PlotRange → All]
Plot[(ss2[t] /. merkSS), {t, timeStartForPlot, timeEndForPlot}, PlotRange → All]
Plot[(ss3[t] /. merkSS), {t, timeStartForPlot, timeEndForPlot}, PlotRange → All]
Plot[(ss4[t] /. merkSS), {t, timeStartForPlot, timeEndForPlot}, PlotRange → All]
Plot[(ss5[t] /. merkSS), {t, timeStartForPlot, timeEndForPlot}, PlotRange → All]
Plot[(ss6[t] /. merkSS), {t, timeStartForPlot, timeEndForPlot}, PlotRange → All]
Plot[(ss7[t] /. merkSS), {t, timeStartForPlot, timeEndForPlot}, PlotRange → All]
Plot[(sitePlugging[t] /. merkSS),
      {t, timeStartForPlot, timeEndForPlot}, PlotRange → All]
```








## Plot EPSC

```
In[1176]:= epscLowCa = D[(ss7[t] /. merkSS), t];
Plot[(ss7[t] /. merkSS), {t, 0, 2*^-3}, PlotRange -> All];
Plot[epscLowCa, {t, 0, 0.5*^-3}, PlotRange -> All]
```



## High Ca

### Initial occupancy

```
In[1179]:= (*calculate initial equilibrium occupancy*)
caFunc[t_] := caRestHigh;
kprimScheme
kunprimScheme
fillStateSSInitial = kprimScheme / kunprimScheme
kfillScheme
kunfillScheme
ss0Initial = fillStateSSInitial * kfillScheme / kunfillScheme
```

Out[1180]= 7.45413

Out[1181]= 8.61585

Out[1182]= 0.865165

Out[1183]= 166.055

Out[1184]= 181.545


Out[1185]= 0.791348

## Diff eq.





```
In[1186]:= Clear[caFunc, eq]; (*Clear is needed if the cell is executed for a 2nd time
when caFunc is already set to a value or an Interpolationfunction*)
caFunc[t_] := interpolFunc[t];
ss[t_] = {ss1[t], ss2[t], ss3[t], ss4[t], ss5[t], ss6[t], ss7[t]};
eq = {ss'[t] == (mat /. repl).ss[t],
      ss[0] == {ss0Initial, 0., 0., 0., 0., 0., 0.},
      (fillStateSS'[t] == kprim - kunprim fillStateSS[t] -
        kfill fillStateSS[t] + kunfill ss1[t]) /. repl,
      fillStateSS[0] == fillStateSSInitial,
      sitePlugging'[t] ==
        (1 - sitePlugging[t]) ss7'[t] - siteClearanceTau sitePlugging[t],
      sitePlugging[0] == 0
    };
```





## NDSolve

```
In[1190]:= merkSS = NDSolve[eq,
      {fillStateSS, ss1, ss2, ss3, ss4, ss5, ss6, ss7, sitePlugging}, {t, 0, 0.003}];
Plot[(fillStateSS[t] /. merkSS), {t, timeStartForPlot, timeEndForPlot},
      PlotRange → All]
Plot[(ss1[t] /. merkSS), {t, timeStartForPlot, timeEndForPlot}, PlotRange → All]
Plot[(ss2[t] /. merkSS), {t, timeStartForPlot, timeEndForPlot}, PlotRange → All]
Plot[(ss3[t] /. merkSS), {t, timeStartForPlot, timeEndForPlot}, PlotRange → All]
Plot[(ss4[t] /. merkSS), {t, timeStartForPlot, timeEndForPlot}, PlotRange → All]
Plot[(ss5[t] /. merkSS), {t, timeStartForPlot, timeEndForPlot}, PlotRange → All]
Plot[(ss6[t] /. merkSS), {t, timeStartForPlot, timeEndForPlot}, PlotRange → All]
Plot[(ss7[t] /. merkSS), {t, timeStartForPlot, timeEndForPlot}, PlotRange → All]
Plot[(sitePlugging[t] /. merkSS),
      {t, timeStartForPlot, timeEndForPlot}, PlotRange → All]
```










---

## Plot EPSC


```
In[1200]:= epscHighCa = D[(ss7[t] /. merkSS), t];
Plot[(ss7[t] /. merkSS), {t, 0, 2*^-3}, PlotRange -> All];
Plot[epscLowCa, {t, 0, 0.5*^-3}, PlotRange -> All]
```



## Compare

### Plot both release rates

```
In[1203]:= Plot[{epscLowCa, epscHighCa}, {t, 0, 0.5*^-3}, PlotRange -> All]
```






## Convolution RelRate => EPSC

```

In[1204]:= miniKernel[t_] := If[t ≤ 0, 0, (1 - Exp[-t/0.0001]) * Exp[-t/0.002]];
Plot[miniKernel[t], {t, -.001, .01}]
dtForConvolve = 0.00005;
tEndConv = 0.01;
miniKernelList = Table[miniKernel[t], {t, 0.0, tEndConv, dtForConvolve}];
epscHighCaList = {Table[0, {t, 0, tEndConv, dtForConvolve}],
  Table[epscHighCa, {t, 0.0, 0.0025, dtForConvolve}],
  Table[0, {t, 0, tEndConv, dtForConvolve}]} // Flatten;
epscLowCaList = {Table[0, {t, 0, tEndConv, dtForConvolve}],
  Table[epscLowCa, {t, 0.0, 0.0025, dtForConvolve}],
  Table[0, {t, 0, tEndConv, dtForConvolve}]} // Flatten;
ListPlot[miniKernelList]
ListPlot[epscLowCaList, PlotRange → All]

```







```

In[1212]:= epscLowCaCurrentList = ListConvolve[miniKernellist, epscLowCaList];
epscHighCaCurrentList = ListConvolve[miniKernellist, epscHighCaList];
timeConv = Table[t * dtForConvolve, {t, Length[epscLowCaCurrentList]};
ListPlot[{Transpose[{timeConv, epscLowCaCurrentList}],
  Transpose[{timeConv, epscHighCaCurrentList}]}], Joined → True, PlotRange → All]
ListPlot[{Transpose[{timeConv, epscLowCaCurrentList}],
  Transpose[{timeConv, epscHighCaCurrentList}]}],
  Joined → True, PlotRange → {{0, 0.002}, All}]
maxLow = Max[epscLowCaCurrentList]
maxHigh = Max[epscHighCaCurrentList]
Print["maxHigh/maxLow = ", maxHigh/maxLow];
ListPlot[{Transpose[{timeConv, (1/maxLow) * epscLowCaCurrentList}],
  Transpose[{timeConv, (1/maxHigh) * epscHighCaCurrentList}]}],
  Joined → True, PlotRange → All]
ListPlot[{Transpose[{timeConv, (1/maxLow) * epscLowCaCurrentList}],
  Transpose[{timeConv, (1/maxHigh) * epscHighCaCurrentList}]}],
  Joined → True, PlotRange → {{0, 0.002}, All}]
If[exportYes == 1,
  toExport = Transpose[{timeConv, epscLowCaCurrentList, epscHighCaCurrentList,
    (1/maxLow) * epscLowCaCurrentList, (1/maxHigh) * epscHighCaCurrentList}];
  Export["plot EPSC - low and high - abs and norm.txt", toExport, "Table"];
];

```







Out[1217]= 3027.59

Out[1218]= 8899.31

maxHigh/maxLow = 2.9394



# Timing

```
In[1223]:= timeEnd = AbsoluteTime[];
            (timeEnd - timeStart) / 60. (*time of calculation in min*)
```

Out[1224]= 0.261271