

APIs Documentation for CRUD system(admin)

[Auth Required]

- **Token Type:** Bearer Token (Sanctum)
 - **Middleware:** auth:sanctum + manager
-

Base URL

http://127.0.0.1:8000/api/admin

(production) غيِّره إلى الدومين الحقيقي في بيئة

Endpoints

1 [GET] /employees

 عرض جميع الموظفين: وصف

URL: http://127.0.0.1:8000/api/admin/employees

- **Method:** GET
- **Headers:**
 - Authorization: Bearer {token}
- **Response Example:**

```
[
{
  "user_id": 1,
  "user_name": "ahmed",
  "first_name": "Ahmed",
  "last_name": "Ali",
  "email": "ahmed@example.com",
  "phone_num": "0999999999",
  "roles": [
    {
      "role_id": 1,
      "role_name": "Manager"
    }
  ]
}
```

```
}  
]  
},  
...  
]
```

2 [POST] /employees

✅ **وصف:** إضافة موظف جديد

URL: http://127.0.0.1:8000/api/admin/employees

- **Method:** POST
- **Headers:**
 - Content-Type: application/json
 - Authorization: Bearer {token}
- **Body (JSON):**

```
{  
  "user_name": "newuser",  
  "national_num": "1234567890",  
  "password": "password123",  
  "first_name": "Ali",  
  "last_name": "Khaled",  
  "phone_num": "0999888777",  
  "email": "ali.khaled@example.com",  
  "age": 25,  
  "gender": "male",  
  "role_id": 2  
}
```

- **Response Example:**

```
{  
  "message": "Employee created successfully",  
}
```

```
"employee": {  
  "user_id": 2,  
  "user_name": "newuser",  
  ...  
}  
}
```

3 [GET] /employees/{user_id}

✓ عرض موظف محدد: وصف

- **URL:** http://127.0.0.1:8000/api/admin/employees/{user_id}
- **Method:** GET
- **Headers:**
 - Authorization: Bearer {token}
- **Response Example:**

```
{  
  "user_id": 2,  
  "user_name": "newuser",  
  ...  
}
```

4 [PUT] /employees/{user_id}

✓ تحديث بيانات موظف: وصف

- **URL:** http://127.0.0.1:8000/api/admin/employees/{user_id}
- **Method:** PUT
- **Headers:**
 - Content-Type: application/json
 - Authorization: Bearer {token}
- **Body (JSON)** – فقط الحقول المراد تحديثها:

```
{
  "user_name": "updateduser",
  "first_name": "Updated",
  "last_name": "User",
  "phone_num": "0999111222",
  "email": "updated@example.com",
  "age": 28,
  "gender": "female",
  "password": "newpass123", // optional
  "role_id": 3 // optional
}
```

- **Response Example:**

```
{
  "message": "Employee updated successfully",
  "employee": {
    "user_id": 2,
    "user_name": "updateduser",
    ...
  }
}
```

5 [DELETE] /employees/{user_id}

✓ حذف موظف: وصف

- **URL:** http://127.0.0.1:8000/api/admin/employees/{user_id}
- **Method:** DELETE
- **Headers:**
 - Authorization: Bearer {token}
- **Response Example:**

```
{
```

"message": "Employee deleted successfully"

}
