
1 The big picture: the parts of an AI agent

Remember: the model only writes text. Your code (the runtime) does every action and holds every key.



LAW 1 **The model proposes. The runtime executes.**
Your code decides if each tool call runs.

LAW 2 **The model never sees a key.**
Keys go in HTTP headers, never in the prompt.

LAW 3 **Control access at the service, not in the prompt.**
A prompt is advice. A token scope is a lock.

Example: the albums agent, from goal to answer

1. **You:** "List the studio albums of Radiohead, oldest first."
2. **Runtime:** sends the goal, the system prompt and 2 tool definitions.
3. **Model:** tool call `search_artist` `{"name": "Radiohead"}`
4. **Runtime:** R read-only token, `GET /search`, returns the artist ID.
5. **Model:** tool call `get_artist_albums` with the ID and `"type": "album"`
6. **Runtime:** reads 2 pages, removes repeat editions, returns 9 albums.
7. **Model:** writes the list. `stop_reason: end_turn`
8. **Runtime:** shows the answer. It logs each step.

Version 2 adds a write ("…and save them to my library"): the executor asks you, then uses *your* OAuth token with scope `user-library-modify` **(sheet 4, 5)**.

An agent = five parts

Model	chooses the next step from the text it reads
Tools	functions that read or change the world
Loop	repeats: ask the model, run the tool, send the result
State	keeps the history, data and memory between calls
Guards	limit turns, cost, access and damage

Who decides the next step?

Chatbot — you → model → answer. No tools. One reply.

Workflow — step 1 → model → step 2. **Your code** sets a fixed path.

Agent — model ⇄ tool. **The model** sets the path, one step at a time.

Use the simplest form that does the task. An agent costs more and is harder to test **(sheet 8)**.

Terms used in this document

Agent	A program in which a model chooses each next step and uses tools until the goal is complete.
Model	The LLM. It reads text and writes text or a tool call. It cannot do anything else.
Runtime	Your code that runs the loop, holds the credentials and runs the tools. Other names: harness, orchestrator.
Tool	A function that the runtime runs for the model. It has a name, a description and an input schema.
Tool call	A request from the model to run one tool with given input (`tool_use`).
Tool result	The output that the runtime sends back to the model (`tool_result`).
Context window	All the text that the model reads in one call. It has a maximum size in tokens.
Credential	A secret that proves who you are to a service: API key, access token, refresh token or password.
API key	A long-lived secret string that identifies an application or an account.
Access token	A short-lived credential (often 1 hour) that a login or a key exchange gives.
Refresh token	A long-lived credential that gets a new access token without a new login.
Scope	The list of actions that a token permits, for example `user-library-read`.
Permission policy	The runtime rule that allows, asks about or denies each tool call.
MCP	Model Context Protocol: a standard way to connect a tool server to an agent **(sheet 3)**.

How to use these sheets

Each later sheet zooms into one part of this map. Badges **1–8** mark the same parts on every sheet. Sheet 10 gives you a blank copy to fill in from memory.

Check yourself


1. Which part holds the credentials: the model or the runtime?
2. Name the five trust zones on the map.
3. What makes a program an agent and not a workflow?

Colour key: user, human approval · runtime (your code) · model · external service · credential · storage · R read · W write · deny, danger


2 The agent loop: one cycle, step by step

Remember: the Model API keeps no memory. Each request carries the full history, and your code runs every tool call.

The loop that your code runs



Example: the albums agent as HTTP calls



The history grows: 1, then 3, then 5 messages. The Model API forgets each request when it replies, so the runtime must send everything again. Gold arrows carry a credential in the HTTP header.

Request 1: what the runtime sends

```
POST https://api.anthropic.com/v1/messages
x-api-key: <your Anthropic API key>   <- header only
anthropic-version: 2026-10-21
content-type: application/json
{
  "model": "claude-opus-5-5",
  "max_tokens": 16000,
  "system": "You find music data. Use the tools.",
  "tools": [
    {"name": "search_artist",
     "description": "Find an artist by name. Returns the ID.",
     "input_schema": {"type": "object",
       "properties": {"name": {"type": "string"}},
       "required": ["name"]}},
    {"name": "get_artist_albums",
     "description": "List all albums of one artist.",
     "input_schema": {"type": "object",
       "properties": {
         "artist_id": {"type": "string"},
         "type": {"enum": ["album", "single", "compilation"]}},
       "required": ["artist_id"]}}
  ],
  "messages": [
    {"role": "user", "content":
      "List the studio albums of Radiohead, oldest first."}
  ]
}
```

Response 1: what comes back (main fields)

```
HTTP/1.1 200 OK
{
  "id": "msg_01...",
  "role": "assistant",
  "content": [
    {"type": "tool_use",
     "id": "toolu_01A",
     "name": "search_artist",
     "input": {"name": "Radiohead"}}
  ],
  "stop_reason": "tool_use",
  "usage": {"input_tokens": ..., "output_tokens": ...}
}
```

Teal = the model wrote it. The model writes only the `id`, the `name` and the `input`. `content` can also hold `text` and `thinking` blocks: send all blocks back unchanged.

Request 2: the result goes back

```
"messages": [
  {"role": "user", "content":
    "List the studio albums of Radiohead, oldest first."},
  {"role": "assistant", "content": [
    {"type": "tool_use", "id": "toolu_01A",
     "name": "search_artist",
     "input": {"name": "Radiohead"}}]},
  {"role": "user", "content": [
    {"type": "tool_result", "tool_use_id": "toolu_01A",
     "content": "Found 1 artist: Radiohead, ID ar_1029."}]}
]
If the tool fails, the runtime still sends a result:
  {"type": "tool_result", "tool_use_id": "toolu_01A",
   "is_error": true,
   "content": "No artist named 'Radiohed'. Check the spelling."}
```

Navy = your code wrote it. The `tool_use_id` links each result to its call.

Other providers use the same loop with other names. OpenAI Chat Completions: `tools[].function.parameters`, the reply has `tool_calls`, and the result is a message with role `tool` and a `tool_call_id`. OpenAI Responses API: `function_call` and `function_call_output` items. Both send the key as `Authorization: Bearer`.

Check yourself

1. What does `stop_reason: "tool_use"` tell the runtime to do?
2. Why does request 3 hold requests 1 and 2? 3. Where does a failed tool call go?

3 Tools and MCP: what the model can ask for

Remember: the model sees the name, description and input schema only. The URL, key and logic stay in your code.

Anatomy of a tool definition (Python SDK form)

What the model reads

```
{
  "name": "get_artist_albums",                          1
  "description": (                                      2
    "List all albums of one artist, oldest first. "
    "Use it after search_artist. Returns title, "
    "year and album_id for each album."
  ),
  "strict": True,                                       3
  "input_schema": {
    "type": "object",
    "properties": {                                     4
      "artist_id": {"type": "string",
        "description": "ID from search_artist"},
      "type": {"type": "string",
        "enum": ["album", "single", "compilation"]},
    },
    "required": ["artist_id", "type"],                  5
    "additionalProperties": False,
  },
}
```

1. **name**: the model calls the tool by this name. Use a verb and a noun.
2. **description**: the model's only manual. Say what the tool does, when to use it, what it returns and its limits.
3. **strict**: the API makes the input match the schema exactly.
4. **properties**: JSON Schema. An `enum` limits the choices. A description for each field helps the model.
5. **required** and `additionalProperties: False`: no missing fields and no extra fields.

Hidden from the model: your code

```
def get_artist_albums(artist_id, type):
    token = secrets.app_token()   # runtime only
    albums = music_api.get_all_pages(
        f"/artists/{artist_id}/albums",
        params={"type": type}, token=token)
    albums = remove_repeat_editions(albums)
    return sorted(albums, key=lambda a: a["year"])
```

Pages, repeats and sorting are in code: cheaper, faster, the same each time.

The side-effect scale: more risk needs more gates

1. Pure compute	2. Read public data	3. Read private data	4. Write, can undo	5. Write, no undo	6. Run any code
sort, convert dates	catalogue search	my library, my email	save an album	delete, send, pay	shell, Python
no credential ✔ allow	app token R ✔ allow	user token R ✔ allow and log	user token W 🔒 ask	user token W 🔒 ask each time	sandbox, no secrets 🔒 ask or sandbox

Put each tool at its level. The level sets the credential and the gate. A tool that can do level 5 is a level-5 tool, even if the model uses it only to read.

Rules for good tools

- **One job for each tool.** Name it with a verb and a noun.
- **Limit the input:** `enum`, `required`, minimum and maximum, `strict`.
- **Return small, structured results:** IDs and key fields, with a size limit.
- **Separate read tools from write tools,** so that each gets its own gate.
- **Write the description for a new colleague:** what, when, output, limits.
- **Do fixed work in code:** pages, repeats, sorting, units.
- **Errors say how to fix them:** "No artist named … Check the spelling."
- **Make writes idempotent:** the same call two times gives the same result.

✘ **Bad:** `api_call(method, url, body)`. One tool can read, delete and pay. You cannot give it a safe gate.

✔ **Good:** `get_artist_albums(artist_id, type)`. One job, read only, level 2, ✔ allow.

Check yourself

1. Which parts of a tool definition does the model read? Which parts does it never see?
2. Where is the key for a client tool, a server tool and a remote MCP tool? 3. Why must an MCP server not pass on the token that it received?

Who runs the tool, and where is the key?

Client tool
You define it and your runtime runs it. Your runtime holds the key. Example: `get_artist_albums`.

Model → Your runtime 🔑 → Service

Server tool
The model provider runs it inside the same API call. You hold no key for it. You limit it with settings such as `allowed_domains` and `max_uses`. Examples: `web_search`, `web_fetch`, `code_execution`.


Model → Provider tool runner → Web or sandbox

MCP tool
A separate program, the MCP server, runs it. The server holds or gets its own credential. Your runtime talks to it through an MCP client.

Model → MCP client in your runtime ↔ MCP server 🔑

The Anthropic API can also connect to a remote MCP server for you (MCP connector, beta: `mcp_servers` plus an `mcp_toolset` entry in `tools`). Then the provider is the MCP client.

MCP: how a tool server connects, and where its keys live



An MCP server offers **tools** (the model calls them), **resources** (data for the app) and **prompts** (templates for the user).

A local server gets its key from the host config

```
{"mcpServers": {
  "music": {
    "command": "music-mcp",
    "env": {"MUSIC_API_KEY": "<from your secret store>"}
}}}
```

Keep the value in a secret store, not as plain text in the file.

Rules in the MCP specification (2025-06-18)

- A stdio server gets credentials from the environment, not from OAuth.
- An HTTP server is an OAuth 2.1 resource server. The client must use PKCE.
- A token is for one server only: the client names the server (`resource`), and the server checks it.
- A server must not pass on the token that it received. It uses its own token upstream.


4 Keys, tokens and identity: who is calling?

Remember: every call has an identity. Give each identity the smallest scope, the shortest life and one safe place to live.

Who does the agent act as, and with what secret?

	LONG-LIVED SECRET	SHORT-LIVED TOKEN
AS THE APP	**API key.** One string in a header. Example: the LLM API key, a catalogue key. It works until you revoke it.	**OAuth client credentials:** ID + secret give a 1-hour token. **Workload identity:** the cloud gives a token, and no stored secret exists. **Best for the app.**
AS ONE USER	**Password or personal token.** It acts as the whole person, with all rights. Never give one to an agent.	**OAuth authorization code + PKCE**, or a browser SSO login. The user agrees to named scopes. **Best for user data.**

The life of a credential



Never put a credential in:
the system prompt or a message
a tool result
model output
git
logs and traces
browser code
a URL
an error message

Leak? Revoke at once. Then rotate, and read the logs.

Inside one HTTP call: who chooses each part

```
GET /v1/artists/ar_1029/albums?type=album&limit=50 HTTP/1.1
Host: api.music.example
Authorization: Bearer eyJhbGciOiJSUzI1NiIs...          app token, read only
Accept: application/json

PUT /v1/me/albums HTTP/1.1
Host: api.music.example
Authorization: Bearer <user access token>              scope user-library-modify
Idempotency-Key: 5f0c2a7e-...                           if the API supports it
Content-Type: application/json

{"ids": ["al_301", "al_302", "al_303"]}
```


Teal: the model chose it (tool input). **Navy**: your code chose it. **Gold**: the credential.

The model fills in values only. Your code chooses the host, the path, the headers and the token, and an allow-list of hosts stops calls to other places. Do not put a token in a URL: URLs go into logs. An `Idempotency-Key` stops a retry from saving two times **(sheet 5)**.

Credential inventory for a typical agent

Credential	Identifies	Stored in	Read by	Sent to	Lifetime	If it leaks
LLM API key	your workspace (billing)	secret store	runtime, at start	`x-api-key` header, Model API only	until revoked	others run requests on your bill and read files in that workspace
Tool API key	your app	secret store	tool executor	one header, one service	until revoked	others use your quota and all data that the key reaches
OAuth client secret	your app, to the login service	secret store	token code	token endpoint only	until rotated	others get app tokens as you
User access token	one user + scopes	memory or token cache	tool executor	`Authorization: Bearer`, one service	about 1 hour	others act as that user, inside the scopes, until it expires
User refresh token	one user, long term	encrypted database, one row per user	token code	token endpoint only	days to months	others get new access tokens: **revoke at once**
Database role	a service account	secret store, or SSO	data tool	database connection	one session	others read (or change) all that the role permits
MCP token	your client, for one server	host token cache	MCP client	that MCP server only	short	limited to that one server
Workload identity	the running service	nothing: the cloud gives it	cloud SDK	cloud APIs, for example the secret manager	minutes	small: no long-lived secret exists
Webhook signing secret	the service that calls you back	secret store	webhook handler	not sent: it checks signatures	until rotated	others send fake callbacks
Logging key	your app, to the log service	secret store	logger	log service only	until revoked	others send fake logs, or read traces if the key permits

Acting for one user: OAuth authorization code with PKCE (version 2: “save to my library”)



The link carries `client_id`, `redirect_uri`, `scope`, `state` and `code_challenge`.

PKCE. The runtime keeps a random `code_verifier` and sends only its SHA-256 hash. A stolen `code` is useless without the verifier.

state stops forged redirects.

The model is not in this diagram. It sees only “Saved 9 albums.”

Check yourself

1. A database of refresh tokens leaks. What do you do first? 2. Why is workload identity safer than an API key in an environment variable? 3. In an HTTP call, which parts does the model choose?

5 Read and write access: what each part may touch

Remember: give each tool the least access that does its job, and control that access at the service, not in the prompt.

Access matrix for the albums agent

Resource	Operation	R/W	Credential	Scope or role	Gate	Undo?	Version
Music catalogue	search artists	R	app token	none: public data	✔ allow	–	v1
Music catalogue	list albums	R	app token	none: public data	✔ allow	–	v1
User library	read saved albums	R	user OAuth token	`user-library-read`	✔ allow	–	v2
User library	save albums	W	user OAuth token	`user-library-modify`	🔒 ask	yes	v2
User library	remove albums	W	none	not requested	🚫 deny: no tool exists	–	never
Conversation store	save each turn	R W	runtime database role	own table only	runtime only, no tool	yes	v1
Long-term memory	save a preference	R W	runtime database role	one area per user	✔ allow reads, 🔒 ask writes	yes	v2
Trace logs	add a record	W	logging key	append only, no delete	runtime only	no	v1
Secret store	read the keys	R	workload identity	this agent's secrets only	at start-up only	–	v1
Model API	send a request	–	LLM API key	one workspace, spend limit	runtime only	–	v1
Local files	read, write	R W	process rights	one work folder only	🔒 ask for writes	sometimes	–


Read the matrix row by row: every row has a credential with its own scope. Version 2 adds two rows with user tokens. The remove row has *no tool*: the safest access is the access that does not exist.

Five layers of control, strongest first

1. **Service scope or role.** The service refuses. A token without `user-library-modify` gets `403`. Nothing in the agent can change this.
2. **Network allow-list.** The runtime can reach only the model API and `api.music.example`. Other hosts fail.
3. **Runtime permission policy.** Code decides ✔ allow, 🔒 ask or 🚫 deny for each tool. The model cannot edit it.
4. **Checks in the tool code.** Schema, ID format, size limits, `SELECT`-only. They block bad input, but a bug can let it through.
5. **System prompt.** "Never delete anything." This is advice only. Injected text can override it.

⚠ **A prompt is not a permission.**

Which gate does a tool need?




Also ask when the input came from untrusted text, such as a web page or an email, even if the action is easy to undo **(sheet 7)**.

Real services work this way (checked October 2026)


Spotify Web API. An app token from client credentials (client ID and secret, token valid for 3600 s) reads the catalogue. It cannot reach user data. To save albums, you need the user's token with scope `user-library-modify`. To read the library, you need `user-library-read`.

MusicBrainz. Reads need no key. Each request must send a `User-Agent` with your app name and a contact, and the limit is about 1 request each second for each IP address. Edits and user data need a login.

The confused deputy: one strong key for many users



✖ **Bad.** User B asks "show user A's albums". The agent can, so it does. The key decides, not the user's rights.



✔ **Good.** Each user's own token. The service checks the rights for each call.

Safe writes: retries, dry runs and limits



Idempotency key: send the same `Idempotency-Key` header with the retry, so that the service does the write only once (if the API supports it). **Check, then write:** read the library first, and save only the albums that are not there. **Dry run:** the tool returns "I will save these 9 albums" and the user approves the list. **Limit:** a maximum number of items or pounds for each run.


Check yourself

1. Which of the five layers can text on a web page get past?
2. Why is a shared admin key dangerous when an agent serves many users?
3. What stops a retry after a timeout from saving the albums two times?

6 Context, memory and state: what the model can see

Remember: the model sees only what is in this request. Keep it small, keep the start of it stable, and keep the rest outside.

Inside one request: the context window




Not to scale. Claude Opus 5.5 reads up to 1,000,000 tokens in one request (October 2026). A token is about three quarters of an English word. The API sorts the request as tools, then system, then messages: put stable content first.

Why the size matters

- **Cost.** You pay for every input token on every call. Turn 30 pays again for turns 1 to 29.
- **Quality.** A long, noisy context hides the important part.
- **Limit.** A request larger than the window fails.
- **Safety.** Every tool result sits next to your instructions, so injected text has a place to act **(sheet 7)**.

Tokens sent in each request, by turn



Illustrative numbers from a stated model, not measured: the stable start is 6k tokens, and each turn adds a 3k-token tool result. With pruning, the last 4 results stay whole and each older result becomes a 0.2k-token summary. Without pruning: $6 + 3n$. With pruning: $6 + 3\min(n, 4) + 0.2\max(n - 4, 0)$.

Four kinds of memory

Kind	What it holds	Lifetime	Read and write	Main risk and control
In the context	the messages in this request	one run	runtime W, model R	overflow; injected text → trim and label results
Session state	full tool results, data tables, cached tokens	one session	runtime only; the model sees a summary or an ID	lost on a crash → save the important parts
Long-term memory	facts for later sessions: “prefers studio albums”	until deleted	model R; W through a gated tool	**memory poisoning**: one bad fact returns in every session → check writes, show them to the user, one area per user
Retrieval index	documents in chunks, with embeddings; a search tool returns the best matches	until rebuilt	agent R; only the load pipeline W	old or poisoned documents → control the sources

Example: where each piece of state lives

In the context	the goal, the 2 tool calls, the trimmed results (9 albums), the answer
Session state	the raw pages from the Music API (all editions), the app token in the token cache
Long-term memory	version 2 only: “prefers studio albums”, saved after you agree
Logs	one trace record for each step, with no secrets **(sheet 7)**

Six ways to keep the context small

1. Trim each result
Set a size limit and return only the fields that matter.

2. Store it, return a handle
“Full result saved as r_12. Call `show_result` for more.”

3. Clear old results first
They are the largest part and the least useful later (context editing).

4. Summarise old turns
Compaction puts a summary in place of the old history.

5. Keep the start stable
No timestamps or random IDs in the system prompt, so the cache works.

6. Use sub-agents
A worker reads a lot in its own context and returns only a summary.


Check yourself

1. Why does turn 30 cost more than turn 3 for the same question? 2. Which kind of memory can one bad tool result poison for every later session? 3. What breaks the prompt cache?

7 Failure and security: who stops what

Remember: your code retries, the model corrects its input, and the run stops for the rest.

A tool call fails: who handles it?



Loop guards

Guard	Example setting	What it stops
turn limit	25 turns for each run	a loop that never ends
token or cost budget	a token or money limit for each run	a large, unexpected bill
time limit	60 s for each tool call, 10 min for each run	calls that hang
repeat-call check	3 identical calls in a row	a model that tries the same thing again and again
error limit	5 errors in a row	a storm of retries
write limit	50 items for each run	one bad decision that changes thousands of records


Observability: one record for each step

```
{"run": "r_81", "step": 4, "time": "2026-10-28T10:15:02Z",
 "tool": "get_artist_albums", "gate": "allow",
 "input": {"artist_id": "ar_1029", "type": "album"},
 "status": 200, "ms": 412, "items": 9,
 "provider_request_id": "req_018...", "tokens_in": 5120,
 "auth": "app token ****"}        <- never the real value
```

An example record. The values are illustrative.


- Write one record for each step: the tool, the input, the gate, the result and the time.
- Replace every secret with `****` before you write.
- Use an append-only store, so that no one can edit the history.
- Keep the provider's request ID for support cases.
- Alert on a burst of `401`, `403` or denied calls.

Prompt injection: text in data that acts like an instruction



Four places to break the chain. **A:** label tool results as untrusted data, and say in the system prompt that text in data is not an instruction (this helps, but it is not a control). **B:** give the agent no tool that can send data to any address; use a fixed list of tools. **C:** ask before any write or send, so that you see the odd call. **D:** the network allows only known hosts, so `evil.example` fails.

Three conditions for data theft: remove one



Private data: your library, your email, company files.

Untrusted content: web pages, emails, reviews, any text that others can write.

A way out: a call to any host, an email, a link in an image.

When one agent has all three, injected text can steal the data. **Albums agent v1** has untrusted content only: safe. Add "read my email" and a free web tool, and it has all three.

The idea is from Simon Willison ("the lethal trifecta", June 2025).

Defence in depth for the albums agent

Credentials	read-only app token for the catalogue; the user's token only for the save tool
Tools	3 fixed tools; no general web tool and no email tool
Gates	✔ allow for reads, 🔒 ask for `save_albums`, a limit of 50 albums for each run
Network	only the model API and `api.music.example`
Results	trimmed, without secrets, labelled as data
Logs	one record for each step, an alert on `403` bursts

Check yourself

1. A `404` and a `403`: which one goes back to the model, and why?
2. Name the four places that break the injection chain.
3. Which of the three conditions does the albums agent `v1` have?

Patterns and deployment: how much agent?

Remember: start with the simplest pattern that does the task. Each step up the ladder costs more and is harder to test.

The pattern ladder, from one call to a full agent


more freedom for the model → more cost, slower, harder to test

1. One model call



Use when: classify, summarise, extract

2. Model + one lookup




Use when: answer from your data with one search

3. Prompt chain




Use when: fixed steps, with a check between steps

4. Routing




Use when: different inputs need different handling

5. Parallel




Use when: independent parts, or several votes

6. Orchestrator and workers




Use when: nobody knows the parts in advance

7. Evaluator and optimiser



Use when: a clear quality test exists


8. Agent



Use when: open task, the path is unknown

M = a model call, T = a tool, W = a worker. Patterns 1 to 7 are workflows: your code sets the path. Only pattern 8 lets the model set the path. Names from Anthropic, “Building effective agents” (December 2024).

Sub-agents: narrow tools and narrow keys for each worker



Each worker has its own context, its own tool list and its own credential. The lead sees only short summaries, so its context stays small. **A worker that reads untrusted pages must not hold a write credential.**

Build an agent in 10 steps


1. Write the task and the test for “done”. If a workflow can do it, do not build an agent.
2. List the tools. Put each one on the side-effect scale **(sheet 3)**.
3. Choose the credential and the scope for each tool **(sheet 4, 5)**.
4. Put the secrets in a secret store. Load them at start-up.
5. Write the tool code: checks, pages, trimming, errors with hints.
6. Write the loop with `stop_reason` handling and guards **(sheet 2)**.
7. Add the permission policy: allow, ask or deny for each tool.
8. Add trace records and alerts **(sheet 7)**.
9. Test with normal, bad and hostile input, including injected text.
10. Start read-only. Add write access only when the logs show safe behaviour.

Example: which pattern does the albums agent need?

Version 1 has a fixed path (search, then list), so a prompt chain (pattern 3) does it. It needs pattern 8 for open questions, such as “find albums like this one that I do not own”.

Three ways to deploy, and where the keys live

A. Local command-line agent



Keys live in: a `.env` file (listed in `.gitignore`) or the OS keychain.

It acts as: you, with your SSO logins, your files and your network.

Main risk: it can do all that you can do.

Controls: read-only roles, one work folder, ask before writes, no admin rights.

Examples: Claude Code; stephen-botson **(sheet 9)**.

B. Web app with a backend

Keys live in: a cloud secret manager, read with workload identity. An encrypted database holds the user tokens, one row per user.


It acts as: the app, and each user through OAuth.

Main risk: a key in browser code; one strong key for all users.

Controls: all calls from the backend; each user’s own token; limits for each user.

Example: a music website with a chat box.

C. Hosted agent



Keys live in: a vault at the provider. The provider adds the credential at the network exit, so the sandbox never sees it.

It acts as: the identities that you put in the vault.

Main risk: broad vault credentials; an open network.

Controls: limited networking with allowed hosts; a permission policy that asks before writes.

Example: Claude Managed Agents, with vault credentials.


Check yourself

1. Patterns 1 to 7 are workflows. What makes pattern 8 different? 2. Why must the browser hold no keys? 3. Which worker may hold a write credential?

9 The same design in stephen-botson

Remember: a real agent mixes strong and weak controls. Find each credential, its scope and the layer that stops misuse.

The map, with the real modules (checked in the code on 28 October 2026)



Every credential that it uses

Service	Credential, in the order that the code tries it	Where it lives	What it permits
Model API	1. `REQUESTY_API_KEY`, as a Bearer token to the Requesty router. 2. `ANTHROPIC_API_KEY`, as `x-api-key`. 3. The Claude Code login token, as a Bearer token; refused 60 s before it expires	`.env`; macOS Keychain	calls to the model, billed to the key or to your subscription
Snowflake	browser SSO (`externalbrowser`); no password; it caches the ID token	OS keychain, if the account allows it	R role `APP-SNOWFLAKE-UK-ROLE-READER-PROD`, warehouse `READER_PROD`
Atlassian	MCP OAuth with PKCE; the callback is on `127.0.0.1:30846`	`~/.config/stephen-botson/atlassian/`	R W the rights that you approve at the consent screen
Google Drive	OAuth for an installed app, from `client_secret.json`	`~/.config/google-mcp/token.json`	R W scope `.../auth/drive`: **all** your Drive files
IRR dashboard	none	–	R a local service only
Local files	your macOS user	–	R any file that you can read; W `output/<session_id>/`

Where each control sits on the five layers (sheet 5)

Action	1 scope	2 network	3 policy	4 code	5 prompt	Result
Snowflake query	●	○	○	●	○	**strong**: the role cannot write, and `validate_query` allows only `SELECT`, `SHOW`, `DESCRIBE`, `EXPLAIN`, `WITH`
Atlassian create or comment	○	○	○	◐	●	**weak**: the prompt says “ONLY when user explicitly asks”; the repeat check stops the run only after a 2nd write has run
Drive delete, move, rename	○	○	○	○	○	**weakest**: full Drive scope, tools always on, not in the write-tool list (delete goes to the trash)
Read local files	◐	○	○	○	○	**broad**: the prompt tells the agent to read any file on the Mac without asking

● present ◐ partial ○ absent

A hidden tool still runs. `tool/registry.py` sends the model only the tools of active groups, but `execute()` runs any registered name. A tool that is not in the list still runs if the model names it.

Check yourself

1. Why is the Snowflake control strong, and the Atlassian control weak?
2. Which single change most reduces the Drive risk? 3. Why does hiding a tool from the list not block it?

Loop and context limits in the code


turns in one run	25	`session/loop.py:76`
continuations after `max_tokens`	3	`session/loop.py:77`
repeat check, after the calls run	3 identical calls; same write tool 2 times	`session/loop.py:66--73, 546`
you press ESC	stops before the next tool call	`session/loop.py:448`
context window and pruning budget	200,000 and 140,000 tokens	`util/env.py:31--32`
recent messages that pruning keeps	8	`util/env.py:33`
tool result sent to the model	12,000 characters at most	`util/env.py:34`; full result in session state

Study notes: changes to think about

- Add an approval step in code for Drive delete, move and rename, and for Atlassian writes.
- Ask Google for a narrower scope, such as `drive.readonly` plus `drive.file`.
- Keep the Snowflake pattern: a read-only role plus a `SELECT`-only check.
- With `REQUESTY_API_KEY` set, a third party sees every prompt and every tool result.

10 Recall test: draw the agent from memory

Remember: you remember what you rebuild. Fill in the blank map before you read the answers.



How to do the test

1. Write the name of each zone and each part 1–8 in the map.
2. On each arrow, write what crosses it.
3. Draw a 🔑 on each arrow that carries a credential.
4. Check your map against sheet 1. Mark what you missed.
5. Answer the questions on sheets 1–9. Then uncover the answers.

Write the three laws

LAW 1 _____

LAW 2 _____

LAW 3 _____

Review plan: space the tests

Do this test today, and again after 1, 3, 7 and 21 days. Each time, start with a blank map. ☐ today ☐ day 1 ☐ day 3 ☐ day 7 ☐ day 21

Model answers (cover this column)

1.1 The runtime. The model only writes text and never holds a key.
1.2 User device, runtime, storage that you control, model provider, tool providers.
1.3 In an agent, the model chooses each next step. In a workflow, your code sets the path.
2.1 Run each requested tool. Send all results in one user message. Then call the model again.
2.2 The Model API keeps no memory, so the runtime sends the full history on every call.
2.3 Back to the model as a `tool_result` with `is_error: true`, so that the model can correct its input. Some errors stop the run **(sheet 7)**.
3.1 It reads the name, the description and the input schema. It never sees the URL, the key or the handler code.
3.2 Client tool: your runtime. Server tool: the provider (you hold no key). Remote MCP tool: the MCP server, with its own token.
3.3 The token is for that server only. A service further on could trust a token that its issuer made for a different server.
4.1 Revoke the refresh tokens at once. Then rotate the client secret if it leaked too, and read the logs.
4.2 No long-lived secret exists to steal. The cloud gives short-lived tokens to the running service only.
4.3 Only the input values, such as the artist ID. Your code chooses the host, the path, the headers and the token.
5.1 Layer 5, the system prompt. The other four layers do not obey text on a web page.
5.2 Any user can make the agent act on the data of another user. Use each user's own token.
5.3 An idempotency key, or a check of the library before the write.
6.1 The request at turn 30 carries turns 1 to 29 again, and you pay for every input token.
6.2 Long-term memory. Check each write, show it to the user, and keep one area for each user.
6.3 Any change in the stable start: a timestamp, a new tool order, an edited system prompt.
7.1 The `404` goes to the model, which can fix the input. A `403` means that the credential lacks the right: stop and tell the user.
7.2 A: label results as data. B: no tool that sends data to any address. C: ask before writes. D: a network allow-list.
7.3 Only untrusted content. It has no private data and no free way to send data out.
8.1 In pattern 8, the model chooses the path. In patterns 1 to 7, your code does.
8.2 Anyone can read browser code, so a key in it is public. Keep all keys in the backend.
8.3 Worker B, the library writer. It reads no untrusted pages, and it asks before each save.
9.1 Snowflake: the service enforces a read-only role. Atlassian: only the prompt stops writes, and the token can write.
9.2 Ask Google for a narrower scope, such as `drive.readonly` plus `drive.file`.
9.3 `execute()` runs any registered name, so the tool runs if the model names it.

Colour key: user, human approval · runtime (your code) · model · external service · credential · storage · R read · W write · deny, danger