

// SPDX-License-Identifier: MIT

//https://betterprogramming.pub/developing-a-smart-contract-by-using-re-mix-ide-81ff6f44ba2f

pragma solidity >=0.7.0 <0.9.0;

contract SimpleBank {

struct client_account{

int client_id; //Keep Client ID

address client_address; //Keep Client Address

uint client_balance_in_ether; ////Keep Client Ether balance

}

client_account[] clients; //Array of all client maintain information

int clientCounter;

address payable manager; // payable function to receives ether address is datatype it is 20
byte hash address public key

modifier onlyManager() { //modifier can check wheather code is executed according to
condition for manager side

require(msg.sender == manager, "Only manager can call this!");

// here sender is manager in this case

// for deposit sender is == manager and for withdrawal sender== client

// when the function should be executed.

_;
 }

modifier onlyClients() { //modifier can check wheather code is executed according to condition
for client side

bool isclient = false; // intially value of isclient false

for(uint i=0;i<clients.length;i++){ //check upto to all client store in array

if(clients[i].client_address == msg.sender){ //now check client address matched with
sender only that client intiate transaction

isclient = true; // client address matched with existing client address in bank database
isclient value updated true.

break;

}
 }

require(isclient, "Only clients can call this!"); // isclient true here so allowed call the
transaction.

_; // when the function should be executed.

}

constructor() {

```

    clientCounter = 0; // those client join contract assign there ID initially it set 0
}
receive() external payable { } // this allows the smart contract to receive ether

function setManager(address managerAddress) public returns(string memory){ //setManager
method will be used to set the manager address to variables
    // string memory store address of manager account instead of store data
    manager = payable(managerAddress); // managerAddress is consumed as a parameter
and cast as payable to provide sending ether.
    return ""; // return payable address of manager
}

function joinAsClient() public payable returns(string memory){
//joinAsClient method will be used to make sure the client joins the contract.

    clients.push(client_account(clientCounter++, msg.sender, address(msg.sender).balance));
// push() array method to add items into a storage array.
    return ""; // return all client details
}

function deposit() public payable onlyClients{ // deposit == client to contract by onlyclient
//deposit method will be used to send ETH from the client account to the contract.
    // We want this method to be callable only by clients who've joined the contract, so the
onlyClient modifier is used for this restriction.
    payable(address(this)).transfer(msg.value); //transfer methods belongs to the contract, and
it's dedicated to sending an indicated amount of ETH between addresses.
    // The payable keyword makes receipt of the ETH transfer possible so the amount of ETH
indicated in the msg.value will be transferred to the contract address.
}

function withdraw(uint amount) public payable onlyClients{ // withdraw == contract to client by
onlyclient
    payable(msg.sender).transfer(amount * 1 ether); // The address of the sender( ie contract )
is held in the msg.sender variable.
    //The withdraw method will be used to send ETH from the contract to the client account. It
sends the unit of ETH indicated in the amount parameter, from the contract to the client who
sent the transaction. We want this method to be callable only by clients who've joined the
contract either,
    // so the onlyClient modifier is used for this restriction.
}

function sendInterest() public payable onlyManager{ //The sendInterest method will be used
to send ETH as interest from the contract to all clients. can called by only manager

```

```

        for(uint i=0;i<clients.length;i++){ // check client in database
            address initialAddress = clients[i].client_address;    //check client address
            payable(initialAddress).transfer(1 ether);

        }
    }

    function getContractBalance() public view returns(uint){
        //getContractBalance method will be used to get the balance of the contract we deployed.
        return address(this).balance;
    }
}

```

//Output steps

//Initially All Account has 100 fake ether

//Step 1: Select first Address (eg.0x5B38Da6a701c568545dCfcB03FcB875f56beddC4)

//Step 2: Click on Deploy button(Contract Created,Can view under Deployed Contract)

//After deploying contract 100 ETH turns to 99.99999. ETH

//Step 3: Set Manager: Follow Following instructions

// i.Select Onother Address(eg.0xAb8483F64d9C6d1EcF9b849Ae677dD3315835cb2)

// ii.Copy this address (eg.0xAb8483F64d9C6d1EcF9b849Ae677dD3315835cb2) and

paste it in contract, infront of set Manager button

// iii. click on set manager button, Now

Manager=0xAb8483F64d9C6d1EcF9b849Ae677dD3315835cb2

//Step 4: join as Client: Follow Following instructions

// i.Select Onother Address(eg.0x4B20993Bc481177ec7E8f571ceCaE8A9e22C02db)

// ii.Copy this address (eg.0x4B20993Bc481177ec7E8f571ceCaE8A9e22C02db) and

paste it in contract, infront of joinAsClient button

// iii.click on joinAsClient button, Now

Client=0x4B20993Bc481177ec7E8f571ceCaE8A9e22C02db

//Initially Balance in contract Will be 0 ETH(can view in Deployed Contract @ Bottom)

//Step 5: Deposit:

// i.Select Client Address(eg.0xAb8483F64d9C6d1EcF9b849Ae677dD3315835cb2)

// ii. Enter 10 ETH ammount in Value Field, Select unit as ETH from dropdown

// iii. Come to the Deployed Contract, Click on deposit button

// iv. 10 ETH transper to Contract , Balance will be updated to 10 ETH in Contract

// V. 10 ETH will be minus from clients Wallet

//Step 6: Withdraw:

// i.Select Client Address(eg.0xAb8483F64d9C6d1EcF9b849Ae677dD3315835cb2)

// ii. Enter 5 ETH ammount in front of withdraw button

// iii. Click on withdraw button

// iv. 5 ETH transper to Wallet

// V. 5 ETH will be Added to clients Wallet

//Step 7: Send Interest:

// i.Select Manager Address(eg.0xAb8483F64d9C6d1EcF9b849Ae677dD3315835cb2)

// ii.Come to contract, Click on sendInterest button

// iii. According to logic written in code, 1 ETH as interest will be send to Client Wallet

//Step 8: getContract Balance:

// i.Click on getcontract balance button to view total balance