FOTOLAB

Canon



Canon EF 35mm F/1.4L II USM Lens

Rs.283,000

Description:

Canon EF 35mm f/1.4L II USM Lens Price & Specs

- EF-Mount Lens/Full -Frame Format
- Aperture Range: f/1.4 to f/22
- Blue Spectrum Refractive Optics Element
- Two Aspherical Elements, One UD Element

Canon EF 35mm f/1.4L II USM Lens Overview

Characterized by its unique and advanced optical composition, the Canon EF 35mm f/1.4L II USM is a wide -angle L -series prime featuring a fast f/1.4 maximum aperture to suit working in difficult lighting conditions. Its optical design incorporates a Blue Spectrum Refractive Optics element; a specially developed element that helps to nearly eliminate chromatic aberrations and color fringin g for notable clarity and color accuracy. In addition to this, an ultra -low dispersion element and two aspherical elements are also featured to further control various aberrations and distortion for great sharpness and resolution. Individual elements also feature a Sub Wavelength Coating to suppress flare and ghosting for high contrast and color fidelity when working in harsh and backlit conditions.

Besides the optical attributes, this lens sports a ring -type USM for quick and quiet autofocus performance an d full -time manual focus override. Its durable physical construction is dust - and moisture -sealed, and a fluorine coating has been added to the exposed elements to guard against fingerprints and smudging.

- Wide -angle 35mm lens is designed for full -frame Ca non EF -mount DSLRs, however can also be used with APS -C models where it provides a 56mm equivalent focal length.
- Fast f/1.4 maximum aperture benefits working in low -light conditions and also affords significant control over depth of field for working with selective focus techniques.
- The Blue Spectrum Refractive Optics element virtually eliminates color fringing and chromatic aberrations by refracting shorter wavelengths of the visible spectrum (blue light).
- A pair of aspherical elements and one UD element a lso help to control aberrations and distortions for sharper, clearer image quality.

- A Sub Wavelength Coating has been applied to individual elements to control lens flare and ghosting for greater contrast and color fidelity when working in strong lighting conditions.
- A ring -type Ultrasonic Motor (USM) is employed to deliver fast, precise, and quiet autofocus performance as well as full -time manual focus override.
- As a member of the esteemed L -series, this lens is sealed against dust and moisture for working in inclement environmental conditions.
- Fluorine -coating on exposed elements affords protection to the optical system, resists smudging and fingerprints, and is easier to clean.
- Rounded nine -blade diaphragm contributes to a pleasing out of focus quality th at benefits the use of shallow depth of field and selective focus techniques.

Pictures



