FOTOLAB



Canon

Canon EOS 5DS R DSLR Camera (Body Only)

Rs.330,900

Description:

Canon EOS 5DS R DSLR Camera (Body Only) Price & Specs

- 50.6MP Full-Frame CMOS Sensor
- Dual DIGIC 6 Image Processors
- Low-Pass Filter Effect Cancellation
- 3.2" 1.04m-Dot ClearView II LCD Monitor
- Full HD 1080p Video Recording at 30 fps
- 61-Point High Density Reticular AF
- ISO 100-6400; 5 fps Continuous Shooting
- 150,000-Pixel RGB+IR Metering Sensor
- User-Selectable Shutter Release Time Lag
- Anti-Flicker Compensation

DESCRIPTIION:

Providing the full resolving power of its new sensor, the EOS 5DS R DSLR Camera from Canon is a variant of the 5DS with the sensor's low-pass filter rendered neutral. By cancelling the effect of the filter, the 50.6MP sensor is enabled to deliver an even higher resolution with more intricate details. The potential downside to this is that the cancellation function brings with it the greater possibility of moiré and other color artifacts. This is a camera for those interested in the utmost resolution from the sensor and the ability to control color artifacts either in-camera or with post-processing software.

This long-awaited follow-up to the vaunted 5D Mark III and brings with it new technology and a number of significant upgrades, placing it in very lofty territory for a DSLR. Featuring a full-frame 50.6MP CMOS sensor, the camera captures ultra-high resolution images suitable for large-scale printing and extensive, creative cropping. The Dual DIGIC 6 Image Processors provide the wherewithal to handle this abundance of information, enabling fast performance speeds and top-of-the-line image quality. The 5DS R also features advanced video capability including HD 1080p capture at 30 fps and a Time Lapse movie function which takes still photos at set intervals and combines them into a full HD movie.

The EOS Scene Detection System with the 150,000-pixel RGB+IR metering sensor provides precise exposure and color metering and the 61-point High Density Reticular AF sensor with 41 cross-type points enables accurate AF placement and Canon's EOS iTR (Intelligent Tracking and Resolution) enhances AF performance by using information from the metering sensor. Crop shooting at 1.3x and 1.6x allows for flexibility in the size of image files created and the selection of lenses. Also, a built-in intervalometer and bulb timer expand your creative options. An advanced mirror control mechanism and new selectable shutter release lag times control camera vibration for reduced blur and quiet operation. Anti-flicker functionality compensates for flickering light sources, providing consistent exposure metering during continuous shooting. Despite its large file sizes, the 5DS R can still offer up to a 5 fps continuous shooting rate.

For stable eye-level composition the 5DS R features the Intelligent Viewfinder II with 100% coverage. In addition to its clear view, a superimposed, transparent LCD is incorporated which displays setting information and offers a customizable view of focus points and grid lines. The 3.2" ClearView II LCD monitor provides playback and live view composition with 1.04m-dot resolution and a 170º viewing angle. High-transparency materials and multi-coating resist reflections for bright viewing, especially important when shooting video.

The 5DS R is a durable and multi-faceted camera for advanced use, yet its dimensions match that of the 5D Mark III. A magnesium-alloy build provides resistance to impact and the elements and inputs include a PC terminal, 3-pin input, an external microphone jack as well as HDMI out and USB 3.0 compatibility. The base plate and tripod socket have also been reinforced to reduce vibrations and ensure a secure attachment to support systems. Dual media slots for Compact Flash and SD format memory cards are supported. A customizable Quick Control System allows you to easily switch between frequently used settings and functions.

New 50.6 Megapixel Full-frame CMOS Sensor

Newly designed 50.6MP full-frame CMOS helps deliver ultra-high resolution images for large-scale printing and extensive, creative cropping, while Dual DIGIC 6 Image Processors enable top-of-the-line image quality and processing speed.

Low-Pass Filter Effect Cancellation

Low-pass filter effect cancellation takes full advantage of the 50.6MP sensor, delivering greater detail and even higher resolution images than those of the 5DS.

Fine Detail Mode in Picture Style

Taking advantage of its sensor's high-resolution capturing power, the EOS 5DS R camera has a new Picture Style called Fine Detail mode. Fine Detail emphasizes fine edges and patterns or textures by setting the camera's Sharpness sub-settings, fineness and threshold to their minimum and by lowering contrast settings as well. Prioritizing minute details in the image allows for better gradations, more detailed textures and fine edges for smoother, more polished photographs.

EOS Scene Detection System with RGB+IR Metering Sensor

The EOS 5DS R camera has the iSA Intelligent Scene Analysis system that employs an independent RGB+IR light sensor with approximately 150,000-pixel resolution. This sensor enables Canon's Intelligent Tracking and Recognition system (iTR AF) that detects and tracks subjects, automatically switching the AF point to optimize tracking. With new tracking algorithms tailored to recognize faces and colors, this system serves as the foundation to the camera's AF system.

61-Point High Density Reticular AF

For fast, precise AF with sophisticated tracking performance, the EOS 5DS R camera has an advanced, 61-point High Density Reticular AF system with up to 41 cross-type AF points. The AF system is sensitive to changes in composition, making adjustments quickly to help ensure consistent, sharp AF. A new RGB+IR AF sensor (with approximately 150,000 pixels) monitors subject motion, and Canon's iTR Intelligent Tracking and Recognition system synchronizes the active AF point with the subject's motion, helping to ensure that AF precision is maintained. With focus modes dedicated to the particulars of the shooting environment, the EOS 5DS R realizes a level of focus accuracy befitting its 50.6MP sensor.

Advanced Mirror Control Mechanism and Shutter Release Time Lag

The camera shake that occurs from the impact of an SLR's mirror can leave blurred details in the recorded image. This effect is magnified when working with a high-resolution sensor like the one found in the EOS 5DS R camera. To counter the effects of conventional, spring-driven SLR mirrors, the EOS 5DS R features a newly developed Mirror Vibration Control system. The camera's mirror is not controlled by springs but instead is driven by a small motor and cams. This system suppresses the impact typical of the camera's mirror, significantly reducing impact and its effects on the image. A new Time Release Lag setting, easily accessed on the menu system, offers added protection against camera shake by setting the shutter release time intentionally longer so the camera does not begin the exposure until after the impact of the camera's mirror has diffused.

Anti-Flicker Feature

With Canon's anti-flicker function, the camera is able to deliver accurate results under cycling lighting situations. Under flickering light, such as fluorescent lighting, a fast shutter speed may result in an irregular exposure. The anti-flicker function detects the frequency and phase of the flicker and captures images near the point of peak brightness when the subject is most likely well illuminated.

1.3x and 1.6x Crop Shooting

For still photography, the EOS 5DS R features the flexibility of a cropping feature that extends the shooting effect 1.3x and 1.6x. With 50.6MP capture, cropped shots are possible with resolution to spare. Images recorded at 1.3x (APS-H) are approximately 30.5MP (6768 x 4512) Large/Fine JPEG, while images recorded at 1.6x (APS-C) are approximately 19.6MP (5424 x 3616) Large/Fine JPEG. Particularly useful in extending the range of telephoto lenses, the crop function also improves the subject tracking capability with almost the entire frame covered with AF points. Image cropping can be displayed in the viewfinder either masked or overlaid with an outline showing the cropped area, and in Live View shooting the image is cropped by the effect chosen. Aspect ratios can also be defined, with the EOS 5DS R shooting in 1:1, 4:3, and 16:9 ratios, in addition to the default 3:2.

Full HD 30p Movie Capability

The Canon 5DS R supports full HD 1080/30p movie capability and Time Lapse Movie function, which takes still photographs at set intervals and combines them into a full HD movie file, is provided. In addition HD and VGA resolution, numerous frame rates and ALL-I and IPB compressions are supported. Still images can be captured during video recording. A jack for an external microphone is provided.

Built-In Intervalometer and Bulb Timer

The EOS 5DS R offers time-lapse fixed-point shooting and long exposures without the need for a remote control. The interval timer takes from 1 to 99 shots at pre-selected intervals (from 1 second to 99 hours 59 minutes 59 seconds, or unlimited), ideal for shooting flowers as they bloom or clouds drifting through the sky. Captured exposures can even be collected and saved as an HD movie. Its built-in bulb timer keeps the shutter open for a designated amount of time, perfect for night photography, to capture the flow of traffic on a street corner, or any other situation where long exposure photography is warranted.

3.2" ClearView II LCD Monitor

The 3.2" ClearView II LCD monitor has 1,040,000 dots, anti-reflective construction and features Canon's ClearView technology for a bright, sharp display in any number of shooting situations. It's ideal for reviewing settings and images, as well as for shooting in Live View mode. In Live View, grid lines can be displayed in 9 sections, 24 sections, or 9 sections with diagonals, as can the electronic level. For image review, the camera has a dedicated Magnify/Reduce button for zooming in or out (up to 16x) simply by pressing the button and turning the Main Dial. Images can be protected or erased quickly, individually or in batches, and slideshows can be created with some or all images and can be sequenced by date, folders, movies, stills or rating. A clear and simple feature guide found in the camera's menu provides detailed reference information whenever needed.

Intelligent Viewfinder II

The Intelligent Viewfinder II makes it easy to both shoot, change and confirm camera settings and shooting modes all without looking away from the viewfinder. Displaying approximately 100% of the composition, the viewfinder can show settings like shooting mode, exposure level, white balance, drive mode, AF operation, metering mode, recording format, an electronic level and more. All of this information can be displayed by or superimposed easily over the image for review while shooting, and multiple views are customizable through the camera's simple user interface.

Customizable Quick Control Screen

In addition to a conventional Quick Control screen, the EOS 5DS R camera features a Quick Control button that enables the photographer to easily access the settings critical for the task at hand. The user can specify features to display, as well as their location and size on the screen.

Continuous Shooting

High-speed continuous shooting up to 5.0 fps allows you to capture fast-moving action at full resolution.

USB 3.0 and Other Connectors

The 5DS R provides support for USB 3.0 connections as well as mini HDMI out, 3-pin input, and a PC terminal. The USB 3.0 digital terminal offers fast transfer to PCs and printers, plus connectivity to Canon's WFT-E7 (Version 2) for wireless transfer and Wi-Fi compatibility.

Pictures:







