FOTOLAB



Nikon

Nikon D-5300 With 18-55mm And 55-200mm VR II Lens

₨.65,000

Description:

Nikon D-5300 with 18-55mm and 55-200mm VR II Lens Price & Specs

- 24.2MP DX-Format CMOS Sensor
- EXPEED 4 Image Processor
- No Optical Low-Pass Filter
- 3.2" 1,037k-Dot Vari-Angle LCD Monitor
- Full HD 1080p Video Recording at 60 fps
- Multi-CAM 4800DX 39-Point AF Sensor
- Native ISO 12800, Extended to ISO 25600
- 5 fps Shooting at Full Resolution
- Built-In Wi-Fi and GPS Connectivity
- AF-P DX 18-55mm f/3.5-5.6G VR Lens
- AF-S DX NIKKOR 55-200mm f/4-5.6G ED VR II Lens
- 65,000 pkr

DESCRIPTION:

The black Nikon D5300 DSLR Camera features a DX-format 24.2 megapixel sensor and EXPEED 4 image processor to produce high-resolution still imagery and Full HD video with notable low-light sensitivity to ISO 12800 and a fast continuous shooting rate of 5 fps. The sensor design omits the traditional optical low-pass filter in order to gain the utmost sharpness and resolution from both photos and videos. Complementing the imaging assets are both a versatile 39-point autofocus system, with nine cross-type sensors, and a 2,016-pixel RGB sensor for precise exposure metering in a wide variety of lighting conditions. Additionally, 1920 x 1080p movie recording is supported, in multiple frame rates up to 60 fps, with full-time continuous auto focusing capabilities.

The compact, yet durably designed, camera body incorporates both an optical pentamirror optical viewfinder along with a large 3.2" 1,037k-dot vari-angle LCD monitor, which features a 180° swivel design to better support working from high and low angles. Also integrated into the D5300 are both Wi-Fi and GPS modules, which enable advanced image sharing capabilities as well as location-based image tagging. When paired with an Android or iOS mobile device, remote viewing and control over the shutter release is possible from a distance and a vast network of pre-populated Points of Interest adds to the overall geotagging functionality.

For creatively enhancing the look and feel of imagery in-camera, a wide range of Picture Control modes, Scene Modes, and Special Effects modes are available as well as a host of in-camera image editing capabilities for adjusting settings prior to sharing. Built-in HDR and Active D-Lighting modes can also be used to optimize exposure results by preserving highlight and shadow details for an extended range of apparent tones.

24.2MP DX-Format Sensor and EXPEED 4 Processor

The 24.2 megapixel DX-format CMOS sensor and EXPEED 4 processor work together to produce overall high image quality with notable detail, dynamic range, color accuracy, and low-light sensitivity to a native ISO 12800, which is further expandable to ISO 25600. Additionally, the sensor's design omits an optical low-pass filter in order to acquire the greatest amount sharpness and detail from subjects. The EXPEED 4 processor also enables a wealth of speed throughout the camera system, including support for Full HD 1080p movie recording and a full-resolution continuous shooting rate of 5 fps.

Multi-CAM 4800DX Autofocus Sensor

Benefitting the high image quality is an apt AF system that employs 39 distinct AF points, including nine cross-type sensors, to quickly acquire focus in a range of lighting conditions, from -1 to +19 EV. A unique 3D-tracking mode utilizes the 2,016-pixel RGB sensor, typically reserved for exposure metering, in order to maintain sharp focus on moving subjects. To better suit specific subject matter when working in AF-A or AF-C focus modes, Dynamic-area AF mode allows you to choose from 9, 21, or 39-point arrays for enhanced subject tracking and recognition, even if the subject briefly leaves the frame. Single-point AF, 3D-tracking, and Auto-area AF modes are also available.

When working in live view, for either still or movie shooting, a contrast-based AF system is employed to acquire focus precisely and can function in continuous, full-time servo mode to better suit working with moving subjects. Additionally, four AF-area modes are available when working in live view: Face-priority AF, Wide-area AF, Normal-area AF, and Subject-tracking AF.

Wi-Fi and GPS Connectivity

Supporting a wealth of sharing and tagging possibilities, the D5300 features built-in Wi-Fi and GPS modules to enable seamless transferring of imagery as well as geotagging functionality. Once the Nikon Wireless Mobile Utility app has been installed on an Android or iOS mobile device, you can use that device to browse the contents of the memory card, select images, and seamlessly transfer files between devices for immediate sharing online. Additionally, the mobile device can remotely trigger the shutter and display a live view image from the camera to enable working from a distance.

The integrated GPS functionality can be used to assign locational data to all image files for geotagging purposes and for plotting imagery to an interactive map. Points of Interest can also be found using this information to further aid in efficient location-based tagging.

Body Design

Even while maintaining an overall compact form-factor, the D5300 integrates a large 3.2" 1,037k-dot vari-angle LCD monitor, which features a 180° swivel design to better suit working from high, low, and front-facing angles. Alternatively, a bright pentamirror optical viewfinder is also integrated into the design for precise eye-level viewing and real-time monitoring of subjects.

A built-in pop-up flash is also available for additional illumination when working in low-light conditions and supports Nikon's i-TTL flash metering system. A hot shoe can be used, too, for connection and optional external flash for even greater lighting control.

Scene Recognition System and Exposure Metering

The intelligent Scene Recognition System with 3D Color Matrix Metering II utilizes a 2016-pixel RGB sensor to evaluate and analyze all aspects within a scene, including brightness, contrast, subject distance, and the scene colors, to quickly determine an accurate exposure and white balance setting to best render the scene at hand. The information gathered is also checked against onboard reference images to ensure consistency from image to image in regard to exposure, white balance, i-TTL flash settings, and subject-tracking AF performance.

Full HD Movie Recording

Full HD 1920 x 1080p movie recording is supported in 60, 30, 25, and 24 fps frame rates, as well as HD 720p and SD 480p in multiple frame rates, in the MPEG-4 AVC/H.264 format. During recording, full-time autofocus can be employed, with face-detection and subject-tracking capabilities, for ensured sharpness with a wide variety of subject types.

A built-in stereo microphone can be used to record high-quality sound or, alternatively, a microphone input is integrated into the body design to support the use of an external microphone for enhanced control over audio recordings.

AF-P DX NIKKOR 18-55mm f/3.5-5.6G VR Lens

Included with the camera body is the standard zoom AF-P DX NIKKOR 18-55mm f/3.5-5.6G VR lens, which provides a 27-82.5mm equivalent focal length range. Featuring an integrated pulse stepping motor, this lens exhibits exceptionally smooth, fast, and quiet autofocus performance to suit both stills and video recording. The optical design incorporates a pair of aspherical elements and a Super Integrated Coating is also featured to suppress lens flare and ghosting. Additionally, this lens also features Vibration Reduction image stabilization to minimize the appearance of camera shake when shooting handheld.

AF-S DX NIKKOR 55-200mm f/4-5.6G ED VR II Lens

The Nikon AF-S DX NIKKOR 55-200mm f/4-5.6G ED VR II Lens is a versatile and compact telephoto zoom lens that is well-suited for portraiture, sports, or wildlife photography. When placed on a Nikon DX camera, it offers an angle of view equivalent to that of a 82-300mm lens on a full-frame 35mm digital camera. When paired with a Nikon DX 18-55mm lens, seamless wide angle to telephoto capability is obtained.

Other Camera Features

Picture Control modes can be directly accessed via a dedicated button and allow you to set predefined looks to imagery in-camera, and include Landscape, Monochrome, Neutral, Portrait, Standard, Vivid, and user-customizable settings.

RAW (NEF) files can be recorded as lossless compressed or compressed at either 12 or 14-bit depth.

Built-in HDR works to extend the tonal and exposure range of a single image by recording two separate exposures and blending them together in order to gain greater highlight and shadow details with an extended range of mid-tones.

Active D-Lighting helps to preserve both highlight and shadow details when working in contrast-rich scenarios, such as backlit lighting. Utilizing the EXPEED 4 processor's power, a more controlled image will be produced with brightness values closer to how they are naturally seen. This mode is suitable for working with moving subjects.

Scene Auto Selector is an automatic mode that intelligently identifies your subject and shooting scenario, selects a proper Scene Mode to apply, and adjusts exposure settings to best render the scene at hand.

Scene Modes: Autumn Colors, Beach / Snow, Blossom, Candlelight, Child, Close-up, Dusk / Dawn, Food, Landscape, Night Landscape, Night Portrait, Party / Indoor, Pet Portrait, Portrait, Sports, and Sunset.

Special Effects Modes: Night vision, Color sketch, Toy camera, Miniature effect, Selective color, Silhouette, High key, Low key, and HDR painting.

In-Camera Image Editing Features: Color Balance, Color Outline, Color Sketch, D-Lighting, Edit Movie, Filter Effects, Fisheye, Image Overlay, Miniature Effect, Monochrome, NEF (RAW) Processing, Perspective Control, Quick retouch, Red-Eye Correction, Resize, Selective Color, Side-by-Side Comparison, Straighten, and Trim.

Language Support: Arabic, Bengali, Brazilian Portuguese, Chinese (Simplified and Traditional), Czech, Danish, Dutch, English, Finnish, French, German, Greek, Hindi, Hungarian, Indonesian, Italian, Japanese, Korean, Norwegian, Persian, Polish, Portuguese, Romanian, Russian, Spanish, Swedish, and Tamil.

Besides the imaging assets, this advanced DSLR also features an impressive handling design that incorporates a 3.2", 2.36m-dot, tilting LCD touchscreen, which affords a comfortable means for working from high and low angles. An updated version of SnapBridge is also featured, which provides Wi-Fi connectivity with NFC, as well as Bluetooth Low Energy technology for linking your mobile device for wireless image sharing. In addition to the convenience features, the D500 is housed within a durable magnesium alloy chassis that is both dust- and weather-sealed for working in inclement conditions and harsh environments.

Included with the camera body is the AF-S DX NIKKOR 16-80mm f/2.8-4E ED VR lens, which provides a 24-120mm equivalent focal length range. In addition to the bright maximum aperture range of f/2.8-4, which avails greater control over selective focus and enhanced low-light shooting capabilities, this DX-dedicated zoom also features 4-stop-effective VR with Sports Mode and a Silent Wave Motor for quick AF speeds. The optical design contains three aspherical elements and four extra-low dispersion glass elements for reduced chromatic and spherical aberrations and controlled distortion throughout the zoom range, as well as both Super Integrated and Nano Crystal Coatings to minimize flare and ghosting. Additionally, this zoom also sports fluorine-coated front and rear elements to guard against smudging, moisture, and dirt.

20.9MP DX-Format CMOS Sensor and EXPEED 5 Image Processor

The DX-format 20.9MP CMOS sensor is paired with the EXPEED 5 image processor to provide an esteemed mixture of high sensitivity, nuanced image quality, and fast overall performance. At native values, a sensitivity range from ISO 100-51200 permits working in a broad array of lighting conditions, an can be further expanded to ISO 50-1640000 (Lo 1 to Hi 5) to handle the most challenging of situations. The mixture of resolution and sensor size also contributes to clean image quality and smooth color transitions with reduced noise throughout the sensitivity range.

In addition to benefitting image quality, the EXPEED 5 processor also affords a wealth of speed throughout the camera system, including a top continuous shooting rate of 10 fps with full-time autofocus and exposure metering. Up to 200 frames can be recorded in a single burst, even when shooting 14-bit lossless compressed NEF files. Additionally, slower continuous shooting rates are available as well as a Quiet Continuous Mode for shooting 3 fps in noise-sensitivity areas.

4K UHD Video Recording

Capable of recording more than just stills, the D500 supports 4K UHD video recording at 30, 25, and 24 fps frame rates and Full HD/HD recording at up to 60 fps, along with the ability to save movie files to the in-camera memory cards or as an uncompressed file to an optional external recorder via HDMI out. For maintained quality and versatility in how your movies look, three image area options are available:

4K UHD movie image format is an area that provides a 1.5x increase in the effective focal length of the lens in use and is reserved for 4K 3840 x 2160 recording.

1.3x-based movie image area provides a 1.3x crop of the DX sensor, and is used for recording FULL HD and HD video.

DX-based movie image format utilizes the full width of the DX-format sensor, and is used to record Full HD 1920 x 1080 and HD 1280 x 720 video. This setting is well-suited for shallow depth of field effects and provides the widest field of view.

As with still shooting, the wide range of sensitivities is available for recording in low- and bright-light conditions, ranging from expanded ISO 100-1640000, and sensitivity values are manually adjustable via the dedicated movie-shooting menu. Also, a video-optimized Flat Picture Control mode can be used during recording to flatten the overall contrast curve for more control during post-production and color grading.

Benefitting handheld shooting, an Electronic Vibration Reduction feature can be used during Full HD and HD recording, which minimizes the appearance of camera shake across three axes to control horizontal, vertical, and rotational movements. Additionally, Active D-Lighting can also be employed during Full HD/HD shooting to preserve highlight and shadow detail when working in high-contrast situations.

In regard to handling, a dedicated power aperture button (Pv) makes it possible to achieve smooth, continuous exposure transitions when switching from light to dark areas and Auto ISO can also be used to maintain consistent brightness when working in changing light situations. Audio recording can be handled using the built-in stereo microphone or an optional external mic can be added via the 3.5mm stereo jack for greater control over quality. Regardless if using the in-camera mic or an external mic, audio levels can be adjusted in 20 increments and live monitoring is possible via the headphone jack, which afford 30 different volume levels for playback.

In addition to straight movie recording, time-lapse recording, for up to 9999 consecutive frames shot over the course of up to one week, is also possible with up to 4K UHD/30p output from the camera.

153-Point Multi-CAM 20K Autofocus System

Matching the speed and imaging capabilities is the apt Multi-CAM 20K AF system, which features 153 total phase-detection points, including 99 cross-type sensors for improved subject recognition, and 55 of the points are selectable for greater compositional freedom. Benefitting the use of super telephoto lenses and teleconverters, 15 of the points, including 9 selectable points, are compatible with an effective aperture of f/8 and all 153 points support working with effective apertures of f/5.6 or brighter.

Complementing the abundance of focusing points is a dedicated AF engine, which offers quick response times to benefit tracking fast and randomly moving subjects, even at the top 10 fps shooting rate. The AF engine also contributes to enhanced focusing sensitivity, with all points capable of focusing -3 EV and the center point capable of reading at -4 EV for working in very dark, low-contrast situations.

Furthering the versatility of the focusing system, seven different AF-area modes can be selected to support varying types of subjects matter:

Single-Point AF: The camera uses a single point to find focus.

Dynamic-Area AF: Available with 25, 72, or 153-point selections, this mode uses a primary single focus point to lock onto focus, and then makes use of the surrounding points for maintaining focus while tracking erratically-moving subjects.

Group-Area AF: This mode treats smaller groups of AF points as a single point for a wider field of recognition, and is well-suited to tracking faces or other detailed subjects.

3D-Tracking: Using a subject's color information, this mode utilizes all 153 points to maintain focus on a moving subject while half-pressing the shutter button.

Auto-Area AF: This mode makes use of all 153 points to quickly identify the main subject, and then prioritizes recognized faces as portrait subjects in any AF servo mode.

In addition to the range of AF-area modes, an AF lock-on function can also be used to improve subject tracking performance, and can be adjusted by two parameters-quick or delayed blacked shot AF response and erratic or steady subject movement. By configuring these settings, the AF performance can be optimized to handle a wide variety of subject movement types.

Lastly, a unique auto AF fine-tune function can be employed to ensure the best possible focus for each mounted lens. Rather than relying on photographing distance charts, this function lets you achieve precise focus manually in live view, and then have the AF system calibrate itself to the fine-tuned focus position in order to alleviate front- and back-focusing issues.

Body Design

A large 3.2" rear LCD monitor features a high 2,359k-dot resolution for clear, vivid playback and live view shooting. The monitor is also a touchscreen for more intuitive menu navigation and settings control, and is usable while shooting, giving you the ability to choose a focus point or an area to set the white balance from. The screen can also be used as a keyboard for quickly entering notes, copyright info, or IPTC information. Additionally, it features a tilting design for easier visibility when shooting from high and low working angles.

A bright pentaprism optical viewfinder offers 100% frame coverage and a 1.0x magnification, and incorporates an organic EL display system to provide shooting information for seamless adjustment over camera settings without removing your eye from the viewfinder. Additionally, the optical glass features enhanced coatings for increased brightness, contrast, and color neutrality for more lifelike viewing.

Extending file saving capabilities by permitting overflow recording, in-camera file duplicating, or the ability to segregate raw and JPEG files between two cards, the D500 is configured with both SD and XQD memory card slots.

A robust magnesium alloy chassis is both dust- and weather-resistant to benefit working in harsh climates and inclement conditions.

The ergonomic grip and overall form factor are shaped to benefit handling for extended periods of time and are further accentuated by anti-slip, textured controls and easy-to-open card slot covers. Additionally, most of the rear buttons on the rear of the camera are illuminated for greater visibility when working in dim lighting conditions. Two configurable Fn buttons, one front-facing and the other rear-facing, may be assigned for checking depth of field or used for other shooting controls.

The included EN-EL15 rechargeable lithium-ion battery is CIPA-rated to last for approximately 1240 shots per charge in single-frame release modes. The optional MB-D17 Multi-Power Battery Pack can also be added to further extend shooting times.

AF-S DX NIKKOR 16-80mm f/2.8-4E ED VR Lens

Included with the camera body is the AF-S DX NIKKOR 16-80mm f/2.8-4E ED VR lens, which provides a 24-120mm equivalent focal length range that covers wide-angle to telephoto perspectives. A bright f/2.8-4 maximum aperture range benefits working in low-light conditions and also affords greater control over focus placement for selective focus shooting. The optical design of this DX-dedicated zoom incorporates three aspherical elements and four extra-low dispersion elements, which combine to reduce both spherical and chromatic aberrations throughout the zoom range. This lens also incorporates a four stop-effective Vibration Reduction system to minimize the appearance of camera shake, and an electromagnetic aperture mechanism offers greater exposure stability at fast continuous shooting rates. Super Integrated and Nano Crystal Coatings have been applied to individual lens elements to control lens flare and ghosting, and both the front and rear elements also receive a fluorine coating to guard against smudging, moisture, and dust.

SnapBridge Wi-Fi Connectivity

Supporting a wealth of sharing and tagging possibilities, the D500 features built-in SnapBridge Wi-Fi connectivity to enable seamless transfer of imagery as well as remote shooting capabilities. BLE – Bluetooth Low Energy technology enables communication between the camera and a smart device. Additionally, the mobile device can remotely trigger the shutter and display a live view image from the camera to enable working from a distance. NFC (Near Field Communication) is also supported to provide a quick and simple tap-to-connect method for linking your mobile devices with the camera.

For faster wireless performance, the D500 is also compatible with the optional WT-7A Wireless Transmitter enabling transmission of image files via FTP server or computer at speeds of up to 866.7 Mbps.

Scene Recognition System and Exposure Metering

The intelligent Scene Recognition System with 3D Color Matrix Metering III utilizes a 180k-pixel RGB sensor to evaluate and analyze all aspects within a scene, including brightness, contrast, subject distance, and the scene colors, to quickly determine an accurate exposure and white balance setting to best render the scene at hand. The information gathered is also checked against onboard reference images to ensure consistency from image to image in regard to exposure, white balance, i-TTL flash settings, and subject-tracking AF performance.

Other Camera Features

Three types of auto white balance are available: Auto 0, which maintains natural white values under any lighting condition; Auto 1, which maintains a balances of color between the subject and ambient light conditions; and Auto 2, which renders colors with a natural warmth and retains the colors of various types of lighting.

In-camera flicker reduction is available for both stills shooting and movie recording.

Three different sizes of raw files can be used depending on your output needs; raw size medium and small are 12-bit lossless compressed NEF files while the large file size is a 14-bit lossless uncompressed or compressed NEF file.

Spot White Balance control for live view shooting makes setting the white balance as easy as pointing to the area in the frame that should be white. Additionally, 1-6 preset white balance settings can be stored for easier switching between different light sources.

The D500 is compatible with the radio-controlled Advanced Wireless Lighting system, which permits working with the optional WR-R10 Controller and WR-A10 Receiver, along with the SB-5000, for intuitive, controllable wireless flash shooting.

Picture Control modes allow you to set predefined looks to imagery in-camera and include Landscape, Monochrome, Neutral, Portrait, Standard, Vivid, Flat, and user-customizable settings.

Language support: Arabic, Bengali, Bulgarian, Chinese (Simplified and Traditional), Czech, Danish, Dutch, English, Finnish, French, German, Greek, Hindi, Hungarian, Indonesian, Italian, Japanese, Korean, Marathi, Norwegian, Persian, Polish, Portuguese (Portugal and Brazil), Romanian, Russian, Serbian, Spanish, Swedish, Tamil, Telugu, Thai, Turkish, Ukrainian, and Vietnamese.

Pictures:







