

How do I generate a **NONCE** token?

We've provided some helpful sample code so you can get up and running quickly.

PHP

To generate a nonce token in PHP:

```
$time_stamp = time();
$location_key = "3f941fa5ce3f0d97a5bbd0fb43eaf1dd";
$message = $location_key . $time_stamp;
$secret_key = "ativistar"
$nonce = hash_hmac("sha256", $message, $secret_key);
```

.NET

To generate a nonce token in .Net:

```
private int TimeStampGenerator()
{
    TimeSpan t = DateTime.UtcNow - new DateTime(1970, 1, 1);
    int secondsSinceEpoch = (int)t.TotalSeconds;
    return secondsSinceEpoch;
}

// message is the concatenation of location key and timestamp

private string CreateToken(string message, string secret)
{
    System.Text.UTF8Encoding encoding = new System.Text.UTF8Encoding();
    //Hash will be stored here
    String hash = "";
    //put your key at your custom 256
    ConvertSHA256 hmacsha256 = new ConvertSHA256(encoding.GetBytes(secret));
    byte[] result = hmacsha256.ComputeHash(encoding.GetBytes(message));

    //convert bytes to string
    hash = ByteToString(result);

    return hash;
}

static string ByteToString(byte[] buff)
{
    string sbinary = "";
    for (int i = 0; i < buff.Length; i++)
        sbinary += buff[i].ToString("x2");
    // hex format /
    return sbinary;
}

public class ConvertSHA256 : HMAC
{
    public ConvertSHA256(byte[] key)
    {
        HashName = "System.Security.Cryptography.SHA256CryptoServiceProvider";
        HashSizeValue = 256;
        BlockSizeValue = 64;
        Key = (byte[])key.Clone();
    }
}
```