
DBMS
data
database
distributed
parallel
shared
system
architecture
processing
network
DBMSs
Distributed
DDBMS
memory
systems
processors
access
centralized
performance
multiple
sites
applications
site
single
computer
nothing
disk
fragments
may
processor
Parallel
provide
local
number
one
stored
technology
physically
require
computers
Shared
logical
sometimes
users
within
Database
typically
major
also
make
large
decentralized
islands
disks
logically
application
bottleneck
interconnection
Figure
development
definition
nodes
transparent
management
organizational
administered
partitioned
global
consists
user
dis
often
Management
replicated
discuss
reliability
eliminates
computing
split
order
scalable
architectures
referred
operational
resources
remote
defined
controlled
based
structure
collection
incompatible
provides
associated
used
least
must
System
capable
mode
directly
com
Date
many
distinction
improve
approach
scalability
control
like
machines
across
fact
communication
distribution
databases
share
way
makes
per
possibly

Database System Concept (CSE 3103)

Lecture 05-Day 01

Nazmus Sakib, Assistant Professor, Dept. of CSE, AUST

Basic Concepts

- Indexing mechanisms used to speed up access to desired data.
  - E.g., author catalog in library
- **Search Key** - attribute to set of attributes used to look up records in a file.
- An **index file** consists of records (called **index entries**) of the form

- Index files are typically much smaller than the original file
- Two basic kinds of indices:
  - **Ordered indices:** search keys are stored in sorted order
  - **Hash indices:** search keys are distributed uniformly across "buckets" using a "hash function".

Index Evaluation Metrics

- Access types supported efficiently. E.g.,
  - records with a specified value in the attribute
  - or records with an attribute value falling in a specified range of values.
- Access time
- Insertion time
- Deletion time
- Space overhead

Ordered Indices

- In an **ordered index,** index entries are stored sorted on the search key value. E.g., author catalog in library.
- **Primary index:** in a sequentially ordered file, the index whose search key specifies the sequential order of the file.
  - Also called **clustering index**
  - The search key of a primary index is usually but not necessarily the primary key.
- **Secondary index**: an index whose search key specifies an order different from the sequential order of the file. Also called non-clustering index**.**
- Index-sequential file**:** ordered sequential file with a primary index.

Dense Index Files

- **Dense index** — Index record appears for every search-key value in the file.
- E.g. index on *ID* attribute of *instructor* relation



10101	10101	Srinivasan	Comp. Sci.	65000
12121	12121	Wu	Finance	90000
15151	15151	Mozart	Music	40000
22222	22222	Einstein	Physics	95000
32343	32343	El Said	History	60000
33456	33456	Gold	Physics	87000
45565	45565	Katz	Comp. Sci.	75000
58583	58583	Califieri	History	62000
76543	76543	Singh	Finance	80000
76766	76766	Crick	Biology	72000
83821	83821	Brandt	Comp. Sci.	92000
98345	98345	Kim	Elec. Eng.	80000

Dense Index Files (Cont.)

- Dense index on *dept_name*, with *instructor* file sorted on *dept_name*



Sparse Index Files

- **Sparse Index**: contains index records for only some search-key values.
  - Applicable when records are sequentially ordered on search-key
- To locate a record with search-key value *K* we:
  - Find index record with largest search-key value < *K*
  - Search file sequentially starting at the record to which the index record points



Sparse Index Files (Cont.)

- Compared to dense indices:
  - Less space and less maintenance overhead for insertions and deletions.
  - Generally slower than dense index for locating records.
- **Good tradeoff**: sparse index with an index entry for every block in file, corresponding to least search-key value in the block.