

Database System Concept (CSE 3103)

Lecture 02-Day 02

Nazmus Sakib, Assistant Professor, Dept. of CSE, AUST

Select Operation – selection of rows (tuples)

- Relation r

A	B	C	D
α	α	1	7
α	β	5	7
β	β	12	3
β	β	23	10

- $\sigma_{A=B \wedge D > 5}(r)$

A	B	C	D
α	α	1	7
β	β	23	10

Project Operation – selection of columns (Attributes)

- Relation r :

A	B	C
α	10	1
α	20	1
β	30	1
β	40	2

- $\Pi_{A,C}(r)$

A	C
α	1
α	1
β	1
β	2

 $=$

A	C
α	1
β	1
β	2

Union of two relations

- Relations r, s :

A	B
α	1
α	2
β	1

r

A	B
α	2
β	3

s

- $r \cup s$:

A	B
α	1
α	2
β	1
β	3

Set difference of two relations

- Relations r, s :

A	B
α	1
α	2
β	1

r

A	B
α	2
β	3

s

- $r - s$:

A	B
α	1
β	1

Set intersection of two relations

- Relation r, s :

A	B
α	1
α	2
β	1

r

A	B
α	2
β	3

s

- $r \cap s$

A	B
α	2

Note: $r \cap s = r - (r - s)$

joining two relations -- Cartesian-product

■ Relations r, s :

A	B
α	1
β	2

r

C	D	E
α	10	a
β	10	a
β	20	b
γ	10	b

s

■ $r \times s$:

A	B	C	D	E
α	1	α	10	a
α	1	β	10	a
α	1	β	20	b
α	1	γ	10	b
β	2	α	10	a
β	2	β	10	a
β	2	β	20	b
β	2	γ	10	b

Cartesian-product – naming issue

■ Relations r, s :

A	B
α	1
β	2

r

B	D	E
α	10	a
β	10	a
β	20	b
γ	10	b

s

■ $r \times s$:

A	$r.B$	$s.B$	D	E
α	1	α	10	a
α	1	β	10	a
α	1	β	20	b
α	1	γ	10	b
β	2	α	10	a
β	2	β	10	a
β	2	β	20	b
β	2	γ	10	b

Renaming a Table

- Allows us to refer to a relation, (say E) by more than one name.

$$\rho_x(E)$$

returns the expression E under the name X

■ Relations r

A	B
α	1
β	2

r

■ $r \bowtie \rho_s(r)$

$r.A$	$r.B$	$s.A$	$s.B$
α	1	α	1
α	1	β	2
β	2	α	1
β	2	β	2

Composition of Operations

- Can build expressions using multiple operations
- Example: $\sigma_{A=C}(r \times s)$

- $r \times s$

A	B	C	D	E
α	1	α	10	a
α	1	β	10	a
α	1	β	20	b
α	1	γ	10	b
β	2	α	10	a
β	2	β	10	a
β	2	β	20	b
β	2	γ	10	b

- $\sigma_{A=C}(r \times s)$

A	B	C	D	E
α	1	α	10	a
β	2	β	10	a
β	2	β	20	b

Joining two relations – Natural Join

- Let r and s be relations on schemas R and S respectively.
Then, the “natural join” of relations R and S is a relation on schema $R \cup S$ obtained as follows:
 - Consider each pair of tuples t_r from r and t_s from s .
 - If t_r and t_s have the same value on each of the attributes in $R \cap S$, add a tuple t to the result, where
 - t has the same value as t_r on r
 - t has the same value as t_s on s

Natural Join Example

- Relations r , s :

A	B	C	D
α	1	α	a
β	2	γ	a
γ	4	β	b
α	1	γ	a
δ	2	β	b

r

B	D	E
1	a	α
3	a	β
1	a	γ
2	b	δ
3	b	ϵ

s

- Natural Join

■ $r \bowtie s$

A	B	C	D	E
α	1	α	a	α
α	1	α	a	γ
α	1	γ	a	α
α	1	γ	a	γ
δ	2	β	b	δ

$$\Pi_{A, r.B, C, r.D, E}(\sigma_{r.B = s.B \wedge r.D = s.D} (r \times s))$$

Notes about Relational Languages

- Each Query input is a table (or set of tables)
- Each query output is a table.
- All data in the output table appears in one of the input tables
- Relational Algebra is not Turing complete
- Can we compute:
 - SUM
 - AVG
 - MAX
 - MIN