Database Systems

Spring 2019 Lab Manual 4

Instructor: Muhammad Junaid Zaffar

Purpose:

- Joins
- Connecting SQL Server database with C# application

Joins:

- Cross Join
- Natural Join
- Equi Join
- Inner Join
- Left Outer Join
- Right Outer Join
- Full Outer Join

C# Connection with database:

There are eight (8) basic steps that must be followed in order to successfully communicate with a database. Let's take a detail overview of all these one by one.

1. Import Required Package

Import the package System.Data.SqlClient that contains useful classes and interfaces to access & work with database. using System.Data.SqlClient;

2. Define Connection URL

To get a connection, we need to specify the URL of a database (Actually we need to specify the address of the database which is in the form of URL)

```
String conURL =
"Data Source=(local);Initial Catalog=MedicalEncyclopedia;Integrated
Security=True;MultipleActiveResultSets=True";

String conURL =
"Data Source=ServerName;Initial Catalog=DbName;User
ID=userId;Password=password;MultipleActiveResultSets=True";
```

3. Establish Connection With DataBase

- Use SqlConnection to get the connection object.
- The URL of the database is passed to the SqlConnection constructor.

```
SqlConnection conn = new SqlConnection(conURL);
```

4. Write statement

```
String cmd = "SELECT * FROM TableName WHERE FirstColumn = @0";
```

5. Create Statement

Create sql command object

```
SqlCommand command = new SqlCommand(command, conn);
// Add the parameters if required
command.Parameters.Add(new SqlParameter("0", 1));
```

6. Execute a Query

The next step is to execute statements. Two methods are generally used for executing SQL queries. These are:

• ExecuteReader(sql) method

Used for SQL SELECT queries.

Returns the ResultSET object that contains the results of the query and can be used to access the query results.

```
SqlDataReader reader = command.ExecuteReader();
```

• command.ExecuteNonQuery() method

This method is used for executing an update statement like INSERT, UPDATE or DELETE. Returns an Integer value representing the number of rows updated. int count = command.ExecuteNonQuery();

7. Process Results of the Query

- The ResultSet provides array index that takes a column index or name and returns the data as object which can then be casted into different types The ResultSet maintains the data in the form tables (rows & columns)
- First row has index 1, not 0.
- The read method of ResultSet returns true or false depending upon whether the next row is available (exist) or not and moves the cursor
- Always remember to call read() method at-least once
- To retrieve the data of the column of the current row you need to use the various getters provided by the ResultSet.
- For example, the following code snippet will iterate over the whole ResultSet

```
while (reader.Read())
{
  Console.WriteLine(reader[0]+" "+ reader[1]);
}
```

8. Close the Connection

An opening connection is expensive, postpone this step if additional database operations are expected

```
con.Close();
```