



# CS 11 C track: lecture 4

---

- Last week: arrays
- This week:
  - Recursion
  - Introduction to pointers



# Lab 4

---

- Harder than previous labs
- One non-obvious trick
  - hints on web page
  - email me if get stuck
- Support code supplied for you
- Read carefully!



# Recursion (1)

---

- Should be familiar from CS 1
- Recursive functions call themselves
- Useful for problems that can be decomposed  
in terms of smaller versions of themselves



# Recursion (2)

---

```
int factorial(int n) {  
    assert(n >= 0);  
    if (n == 0) {  
        return 1; /* Base case. */  
    } else {  
        /* Recursive step: */  
        return n * factorial(n - 1);  
    }  
}
```



# Recursion (3)

---

`factorial(5)`

`--> 5 * factorial(4)`

`--> 5 * 4 * factorial(3)`

`--> 5 * 4 * 3 * factorial(2)`

`--> 5 * 4 * 3 * 2 * factorial(1)`

`--> 5 * 4 * 3 * 2 * 1 * factorial(0)`

`--> 5 * 4 * 3 * 2 * 1 * 1`

`--> 120`



# Pointers (1)

---

- Address:

- A *location* in memory where data can be stored
- *e.g.* a variable or an array
- Address of variable **x** is written **&x**

- Pointer:

- A variable which holds an address



## Pointers (2)

---


name	address	contents
------	---------	----------

i	0x123aa8	
---	----------	--

		10
--	--	----

j	0x123aab	
---	----------	--

		0x123aa8
--	--	----------



```
int i = 10;
```

```
int *j = &i; /* j "points" to i */
```



# Pointers (3)

---

```
int i = 10;
```

```
int *j = &i;
```

```
printf("i = %d\n", i);
```

```
printf("j = %x\n", j);
```

```
printf("j points to: %d\n", *j);
```





## Pointers (4)

---

- `&i` is the **address of** variable `i`
- `*j` is the **contents of** the address stored in pointer variable `j`
  - *i.e.* what `j` points to
- `*` operator **dereferences** the pointer `j`



# Pointers (5)

---

- The many meanings of the `*` operator:

- Multiplication

```
a = b * c;
```

- Declaring a pointer variable

```
int *a;
```

- Dereferencing a pointer

```
printf("%d", *a);
```



# Pointer pitfalls (1)

---

- Declaring multiple pointer variables:

```
int *a, *b;    /* a, b are ptrs to int */
```

- If you do this:

```
int *a, b;     /* b is just an int */
```

- Then only the first variable will be a pointer
- Rule: every pointer variable in declaration must be preceded by a \*



## Pointer pitfalls (2)

---

- Note that

```
int *j = &i;
```

- really means

```
int *j; /* j is a pointer to int */
```

```
j = &i; /* assign i's addr to j */
```

- Don't confuse this `*j` with a dereference!



# Pointers (6)

---

- A harder problem:

```
int    i = 10;
```

```
int    *j = &i;
```

```
int    **k = &j;
```

```
printf("%x\t%d\n", &i, i);
```

```
printf("%x\t%x\t%d\n", &j, j, *j);
```

```
printf("%x\t%x\t%x\t%d\n",
```

```
&k, k, *k, **k);
```



# Pointers (7)

---

**name**

**address**

**contents**

**i**

**0x123aa8**

**10**

**j**



**0x123aab**

**0x123aa8**

**k**

**0x123ab0**

**0x123aab**





# Assigning to pointers (1)

---

```
int i = 10;
int *j = &i;
int *k;

/* Assign to what j points to: */
*j = 20; /* Now i is 20. */

/* Assign j to k: */
k = j; /* Now k points to i too. */

/* Assign to what j points to: */
*j = *k + i; /* Now i is 40. */
```



## Assigning to pointers (2)

---

- When pointer variable is on left-hand side of an assignment statement, what happens depends on whether it's dereferenced or not
  - no dereference: assign the value on RHS (an address) to the pointer variable on the LHS

`j = k;`

- dereference: assign value on RHS into location corresponding to where pointer points to

`*j = *k + 10;`





## Assigning to pointers (3)

---

- When pointer variable is declared and assigned to on the same line:

```
int *j = k;
```

- it means:

```
int *j;    /* declare j    */
```

```
j = k;    /* assign to j */
```

- *i.e.* assign the value on RHS (an address) to the pointer variable on the LHS



# Mnemonics: fetch/store

---

- When you use the `*` (dereference) operator in an expression, you fetch the contents at that address

```
printf("j's contents are: %d\n", *j);
```

- When you use the `*` (dereference) operator on the left-hand side of the `=` sign in an assignment statement, you store into that address

```
*j = 42;    /* store 42 into address */
```



# Pointers – call by reference (1)

---

- Can use pointers for a non-obvious trick
- Recall: in C, variables are copied before being sent to a function
  - referred to as "call-by-value"
- Significance is that passing a variable to a function *cannot* change the variable's value
- But sometimes we *want* to change the variable's value when function returns



## Pointers – call by reference (2)

---

```
void incr(int i) {  
    i++;  
}  
  
/* ... later ... */  
int j = 10;  
incr(j); /* want to increment j */  
/* What is j now? */  
/* Still 10 – incr() does nothing. */
```



# Pointers – call by reference (3)

---

```
void incr(int *i) {  
    (*i)++;  
}
```

```
/* ... later ... */
```

```
int j = 10;
```

```
incr(&j);
```

```
/* What is j now? */
```

```
/* Yep, it's 11. */
```



# Pointers – call by reference (4)

---

```
int j = 10;
```

```
incr(&j);
```

- You should be able to work out why this works
- Where have we seen this before?

```
int i;
```

```
scanf("%d", &i); /* read in i */
```



# Pointers – call by reference (5)

---

- Easy mistake to make:

```
void incr(int *i) {  
    *i++;    /* Won't work! */  
    /* Parsed as: *(i++); */  
}
```

- Need to say `(*i)++` here
- Precedence rules again; use parens `()` if any confusion can exist



# Next week

---

- Pointers and arrays  
(the untold story)
- Dynamic memory allocation