

Package ‘odataR’

May 2, 2016

Type Package
Title Access to OData information
Version 0.1.0
Author Han Oostdijk
Maintainer <han.oostdijk@xs4all.nl>
Description Access to OData information.
License MIT + file LICENSE
LazyData TRUE
RoxygenNote 5.0.1.9000
Imports XML,
curl,
dplyr,
magrittr

R topics documented:

odataR_get_data	1
odataR_get_root	2
odataR_get_subtable	2
odataR_get_subtables	3
odataR_get_table	3
odataR_set_root	4
Index	5

odataR_get_data	<i>Get (part of) an OData data structure</i>
-----------------	--

Description

Determines from which structure the data will be extracted

Usage

```
odataR_get_data(root = odataR_get_root(), table_id = NULL, query = NULL,  
  save_file_name = NULL)
```

Arguments

root	Root of data structure
table_id	Identification of table
query	OData query to restrict data returned from structure
save_file_name	Name of file to save the XML data in or NULL

Examples

```
## Not run:
odataR_get_data(table_id='82935NED')
odataR_get_data(root='http://opendata.cbs.nl/ODataFeed/OData', table_id='82935NED')

## End(Not run)
```

odataR_get_root	<i>Gets the root for OData data structure</i>
-----------------	---

Description

Determines from which structure the data will be extracted

Usage

```
odataR_get_root()
```

Examples

```
odataR_get_root()
```

odataR_get_subtable	<i>Copy table (or properties) to a data.frame</i>
---------------------	---

Description

Copy table to a data.frame

Usage

```
odataR_get_subtable(dsn, mt = "table", query = NULL, save_XML = NULL)
```

Arguments

dsn	Named character vector with full name of subtable
mt	Character 'table' or 'prop' or NULL
query	OData query to restrict data returned from structure
save_XML	Name of file to save the XML data in or NULL or default name

Examples

```
## Not run:
subtabs = odataR_get_subtables(table_id="82935NED")

## End(Not run)
```

odataR_get_subtables *Get information about sub tables in OData data structure*

Description

Get information about sub tables in OData data structure

Usage

```
odataR_get_subtables(root = odataR_get_root(), table_id = NULL)
```

Arguments

root	Root of data structure
table_id	Identification of table

Examples

```
## Not run:
odataR_get_subtables(table_id='82935NED')
odataR_get_subtables(root='http://opendata.cbs.nl/ODataFeed/OData', table_id='82935NED')

## End(Not run)
```

odataR_get_table *Get table in decoded form*

Description

Get table in decoded form

Usage

```
odataR_get_table(root = odataR_get_root(), table_id = NULL, query = NULL,
  typed = T, keepcode = c())
```

Arguments

root	Root of data structure
table_id	Identification of table
query	OData query to restrict data returned from structure
typed	Boolean indicating 'TypedDataSet' when T or 'UntypedDataSet' when F#
keepcode	Character string with dimension(s) for which the coded values are kept

Remark

See <http://docs.oasis-open.org/odata/odata/v4.0/errata02/os/complete/part1-protocol/odata-v4.0-errata02-os-part1-protocol-complete.html> for details about the query possibilities

Examples

```
## Not run:
df      = odataR_get_table(table_id="82935NED")
df      = odataR_get_table(table_id="82935NED",keepcode = "RegioS")
df      = odataR_get_table(table_id="82935NED",keepcode = c("RegioS","Perioden"))
df      = odataR_get_table(table_id="82935NED",keepcode = "RegioS",
  query  = "?$format=atom&$filter=startswith(RegioS,'NL01')" )
df      = odataR_get_table(table_id="82935NED",
  query  = paste0("?$format=atom&$filter=startswith(RegioS,'NL01')",
    "&$select=RegioS,Perioden,TotaleInvesteringen_1") )
df      = odataR_get_table(table_id="82935NED",
  query  = paste0("?$format=atom&$filter=startswith(RegioS,'NL01')",
    "&$select=RegioS,Perioden,TotaleInvesteringen_1",
    "&$skip=2&$top=3") )

## End(Not run)
```

odataR_set_root

Sets the root for OData data structure

Description

Determines from which structure the data will be extracted

Usage

```
odataR_set_root(root = NULL)
```

Arguments

root NULL for the default or the url otherwise

Examples

```
odataR_set_root()
odataR_set_root('http://opendata.cbs.nl/ODataFeed/OData')
```

Index

odataR_get_data, [1](#)
odataR_get_root, [2](#)
odataR_get_subtable, [2](#)
odataR_get_subtables, [3](#)
odataR_get_table, [3](#)
odataR_set_root, [4](#)