

Package ‘odataR’

May 4, 2016

Type Package
Title Access to OData information
Version 0.1.1
Author Han Oostdijk
Maintainer <han.oostdijk@xs4all.nl>
Description Access to OData information.
License MIT + file LICENSE
LazyData TRUE
RoxygenNote 5.0.1.9000
Imports XML,
curl,
dplyr,
magrittr

R topics documented:

odataR	1
odataR_get_data	2
odataR_get_root	3
odataR_get_subtable	3
odataR_get_subtables	4
odataR_get_table	5
odataR_set_root	6
Index	7

odataR	<i>odataR: A package for accessing OData information.</i>
--------	---

Description

The odataR package contains some functions to obtain information from databases with the OData interface.

Details

Located under the root of an OData database are some tables. To obtain the information one should specify the correct root and the name of the table. Because this package was created to access the information of the CBS (Statistics Netherlands) the default root is appropriate for this information. The name of a table (here called `table_id`) can be found in the documentation of the database. For the CBS you can use the catalog <http://opendata.cbs.nl/dataportaal/portal.html> to see the available tables and their metadata.

Setting a different root can be done by using the function `odataR_set_root` and querying the root by executing `odataR_get_root`.

The other functions in the package are related to actually obtain information from the database. In the CBS database a table name (`table_id`) points to a set of sub tables that together provide the information. One 'main' sub table contains the topic data and dimensions in coded form indicating where the topic data relates to. The other sub tables convey the meaning of the coded dimensions. E.g. a topic field could be the number of unemployed workers and the dimensions could be gender, age-class, province and year.

The main function is `odataR_get_table` that extracts the information from the database and decodes the dimensions. The other functions are used by `odataR_get_table` but can also be used independently. E.g. `odataR_get_subtable` can be used to get the information in encoded form (needs less memory) and with `odataR_get_subtable(subtabs['TableInfos'],mt=NULL)` one gets the table information in XML form (however the information in the catalog is better readable for a human.)

For examples see `odataR_get_table`

<code>odataR_get_data</code>	<i>Get (part of) an OData data structure</i>
------------------------------	--

Description

This is the only function in the package that actually acquires data from the database. This function returns a block of at most 10000 rows (restriction of the interface) in XML format. It is therefore also suitable in cases where the result is not a nice table (e.g. in the case of `TypeInfo`). The function `odataR_get_table` will call this function one or more times (depending on the size of the data) and convert the combined data to a table or property structure.

Usage

```
odataR_get_data(root = odataR_get_root(), table_id = NULL, query = NULL,
  save_file_name = NULL)
```

Arguments

<code>root</code>	Root of data structure
<code>table_id</code>	Identification of table
<code>query</code>	OData query to restrict data returned from structure, See <code>odataR_get_table</code> for examples of queries
<code>save_file_name</code>	Name of file to save the XML data in or NULL

Examples

```
## Not run:
odataR_get_data(table_id='82935NED')
odataR_get_data(root='http://opendata.cbs.nl/ODataFeed/OData', table_id='82935NED')

## End(Not run)
```

odataR_get_root	<i>Gets the root for OData data structure</i>
-----------------	---

Description

Determines from which structure the data will be extracted. If the function `odataR_set_root` is not called yet this will be done first with the default `http://opendata.cbs.nl/ODataFeed/OData` (the root for the CBS Statistics Netherlands structures).

Usage

```
odataR_get_root()
```

See Also

[odataR_set_root](#)

Examples

```
odataR_get_root()
```

odataR_get_subtable	<i>Convert a sub table (contents or properties) to a data.frame</i>
---------------------	---

Description

Convert a sub table (contents or properties) to a data.frame. The function calls [odataR_get_data](#) one or more times (the latter if the server returns more than 10000 rows) to actually retrieve the XML data. With parameter `mt` one indicates that the requests relates to a 'normal' sub table or relates to the properties sub table. In these cases the data is converted to a data.frame . By specifying `mt=NULL` the contents is not converted to a data.frame but returned as XML.

Usage

```
odataR_get_subtable(dsn, mt = "table", query = NULL, save_XML = NULL)
```

Arguments

<code>dsn</code>	Named character vector with full name of subtable
<code>mt</code>	Indicates destination of the XML data. Character 'table' (default) or 'prop' or NULL
<code>query</code>	OData query to restrict data returned from structure, See odataR_get_table for examples of queries
<code>save_XML</code>	Name of file to save the XML data in or NULL or default name

Value

A data.frame with the contents of the sub table (mt= ' table ') or the properties of the table (mt= ' prop ') or the XML contents of the sub table (mt=NULL)

Examples

```
## Not run:
subtabs = odataR_get_subtables(table_id="82935NED")

## End(Not run)
```

odataR_get_subtables	<i>Get information about sub tables in OData data structure</i>
----------------------	---

Description

A logical table consists of a some related sub tables. This function returns a named character vector where the names give for each sub table the type and the contents the url of the sub table. This information can be used by the function [odataR_get_subtable](#) to retrieve the contents of a sub table

Usage

```
odataR_get_subtables(root = odataR_get_root(), table_id = NULL)
```

Arguments

root	Root of data structure
table_id	Identification of table

Value

A named character vector where the names give for each sub table the type and the contents the url of the sub table

Examples

```
## Not run:
odataR_get_subtables(table_id='82935NED')
odataR_get_subtables(root='http://opendata.cbs.nl/ODataFeed/OData', table_id='82935NED')

## End(Not run)
```

odataR_get_table	<i>Get table in decoded form</i>
------------------	----------------------------------

Description

The main function is `odataR_get_table` that extracts the information from the database and decodes the dimensions. It uses the other functions in the package behind the screens. E.g. when executing `df = odataR_get_table(table_id="82935NED")` the following is executed:

- get names of sub tables:
`subtabs = odataR_get_subtables(table_id="82935NED")`
- retrieve coded data:
`df = odataR_get_subtable(subtabs['TypedDataSet'])`
- retrieve properties:
`props = odataR_get_subtable(subtabs['DataProperties'],mt='prop')`
- decode dimensions:
`df = couple_data(df, ...)`

Usage

```
odataR_get_table(root = odataR_get_root(), table_id = NULL, query = NULL,
  typed = T, keepcode = c())
```

Arguments

<code>root</code>	Root of data structure
<code>table_id</code>	Identification of table
<code>query</code>	OData query to restrict data returned from structure
<code>typed</code>	Boolean indicating 'TypedDataSet' when T or 'UntypedDataSet' when F
<code>keepcode</code>	Character string with dimension(s) for which the coded values are kept

Remark

See <http://docs.oasis-open.org/odata/odata/v4.0/errata02/os/complete/part1-protocol/odata-v4.0-errata02-os-part1-protocol-complete.html> for details about the query possibilities

Examples

```
## Not run:
df = odataR_get_table(table_id="82935NED")
df = odataR_get_table(table_id="82935NED",keepcode = "RegioS")
df = odataR_get_table(table_id="82935NED",keepcode = c("RegioS","Perioden"))
df = odataR_get_table(table_id="82935NED",keepcode = "RegioS",
  query = "?$format=atom&$filter=startswith(RegioS,'NL01')")
df = odataR_get_table(table_id="82935NED",
  query = paste0("?$format=atom&$filter=startswith(RegioS,'NL01')",
    "&$select=RegioS,Perioden,TotaleInvesteringen_1") )
df = odataR_get_table(table_id="82935NED",
  query = paste0("?$format=atom&$filter=startswith(RegioS,'NL01')",
```

```

    "&$select=RegioS,Perioden,TotaleInvesteringen_1",
    "&$skip=2&$top=3") )

## End(Not run)

```

odataR_set_root	<i>Sets the root for OData data structure</i>
-----------------	---

Description

Determines from which structure the data will be extracted. If this function is not called the default `http://opendata.cbs.nl/ODataFeed/OData` (the root for the CBS Statistics Netherlands structures) will be used

Usage

```
odataR_set_root(root = NULL)
```

Arguments

root	NULL for the default or the url of the root data structure otherwise
------	--

See Also

[odataR_get_root](#)

Examples

```

odataR_set_root()
odataR_set_root('http://opendata.cbs.nl/ODataFeed/OData')

```

Index

odataR, [1](#)
odataR-package (odataR), [1](#)
odataR_get_data, [2](#), [3](#)
odataR_get_root, [2](#), [3](#), [6](#)
odataR_get_subtable, [2](#), [3](#), [4](#)
odataR_get_subtables, [4](#)
odataR_get_table, [2](#), [3](#), [5](#), [5](#)
odataR_set_root, [2](#), [3](#), [6](#)