



2018-09-10

Nankai-Baidu
Joint Laboratory



Parallel and Distributed
Software Technology Lab





➤ ML Confidential: Machine Learning on Encrypted Data

Thore Graepel, Kristin Lauter, and Michael Naehrig

- ❑ ML Confidential Protocol
- ❑ Linear Means (LM) Classifier
- ❑ Fisher's Linear Discriminant (FLD) Classifier
(on a publicly available data set)

Nankai-Baidu
Joint Laboratory



Parallel and Distributed
Software Technology Lab





□ ML Confidential Protocol

- ✓ Key Generation: The Data Owner executes the HE.Keygen algorithm publishes the public key, securely stores the private key locally
- ✓ Encryption and Upload of Training Data: ... encrypt preprocessed version of the training set data, i.e. sufficient statistics

Training:

Classification:

Verification of the Learned Model:

Nankai-Baidu
Joint Laboratory

Parallel and Distributed
Software Technology Lab





□ Linear Means (LM) Classifier

determines w and c such that

$f(x; w, c) = 0$ defines a hyper-plane midway on and orthogonal to the line through the two class conditional means.

It can be derived as the Bayes optimal decision boundary in the case that the two class-conditional distributions have identical isotropic Gaussian distributions.

Nankai-Baidu
Joint Laboratory



Parallel and Distributed
Software Technology Lab





□ Linear Means (LM) Classifier

$$x \in R^n, y = \{+1, -1\}$$

a linear classifier of the form $A(x; w, c) = \text{sign}(f(x; w, c))$

$$f(x; w, c) = w^T x - c$$

Step 1. $I_y = \{i \in \{1, \dots, m\} | y_i = y\}$

the index set of training examples with label y

$$\text{Step 2. } \mathbf{m}_y = m_y^{-1} \mathbf{s}_y \quad m_y = \|I_y\|, \quad \mathbf{s}_y = \sum_{i \in I_y} x_i$$

$$\text{Step 3. } \mathbf{w}^* = \mathbf{m}_{+1} - \mathbf{m}_{-1} \quad \mathbf{w}^{*T} x_0 - c = 0$$

$$x_0 = (\mathbf{m}_{+1} + \mathbf{m}_{-1})/2$$

$$\mathbf{c}^* = \mathbf{w}^{*T} x_0$$

Nankai-Baidu
Joint Laboratory

Parallel and Distributed
Software Technology Lab





□ Linear Means (LM) Classifier

Step 3. $\mathbf{w}^* = \mathbf{m}_{+1} - \mathbf{m}_{-1}$ $\mathbf{c}^* = (\mathbf{m}_{+1} - \mathbf{m}_{-1})^T (\mathbf{m}_{+1} + \mathbf{m}_{-1}) / 2$

$$\mathbf{m}_y = m_y^{-1} \mathbf{s}_y$$

compute $m_{-1} \mathbf{s}_{+1}$ and $m_{+1} \mathbf{s}_{-1}$ instead of \mathbf{m}_{+1} and \mathbf{m}_{-1}

$$\tilde{\mathbf{w}}^* = m_{-1} \mathbf{s}_{+1} - m_{+1} \mathbf{s}_{-1} = m_{+1} m_{-1} (\mathbf{m}_{+1} - \mathbf{m}_{-1}) = m_{+1} m_{-1} \mathbf{w}^*$$

$$\tilde{c}^* = 2m_{+1}^2 m_{-1}^2 \mathbf{c}^*$$

$$\tilde{f}^*(\mathbf{x}; \tilde{\mathbf{w}}^*, \tilde{c}^*) = 2m_{+1} m_{-1} \tilde{\mathbf{w}}^{*T} \mathbf{x} - \tilde{c}^*$$

Nankai-Baidu
Joint Laboratory



Parallel and Distributed
Software Technology Lab

