

Human Pose Estimation

Xiantong Xiang

Shandong University

Wednesday, January 22rd, 2025

Contents

Human Pose
Estimation

Xiantong
Xiang

Background

Methods

Thanks

1 Background

2 Methods

3 Thanks

Background

Human Pose
Estimation

Xiantong
Xiang

Background

Methods

Thanks

- Top-down
 - CPM
 - Hourglass
 - CPN
 - ViTPose/ViTPose++
- Bottom-up
 - OpenPose
- One-Stage
 - RTMO(top-down)
- Multi-Stage
 - CPM
 - Hourglass

CPM


Human Pose Estimation

Xiantong Xiang

Background

Methods

Thanks



- A pose machine consists of a sequence of multi-class predictors $g_t(\cdot)$

$$g_1(x_z) \rightarrow \{b_{p1}(Y_p = z)\}_{p \in \{0, \dots, P\}}$$

where $b_{p1}(Y_p = z)$ is the score predicted by the classifier g_1 for assigning the p th part in the first stage at image location z .

- represent all the beliefs of part p evaluated at every location $z = (u, v)^T$ in the image as $b_{p1} \in \mathbb{R}^{w \times h}$

$$b_{pt}[u, v] = b_{pt}(Y_p = z)$$

-

$$g_t(x'_z, \psi_t(z, b_{t-1})) \rightarrow \{b_{pt}(Y_p = z)\}_{p \in \{0, \dots, P+1\}}$$

where $\psi_{t>1}(\cdot)$ is a mapping from the beliefs b_{t-1} to context features

- The evidence is local because the receptive field of the first stage of the network is constrained to a small patch around the output pixel location.
- composed of five convolutional layers followed by two 1×1 convolutional layers
- **Large receptive fields:**
 - pooling at the expense of precision
 - increasing the kernel size of the convolutional filters at the expense of increasing the number of parameters
 - increasing the number of convolutional layers at the risk of encountering vanishing gradients during training

minimizes the l_2 distance between the predicted and ideal belief maps for each part

$$f_t = \sum_{p=1}^{P+1} \sum_{z \in Z} \|b_p^t(z) - b_p^*(z)\|_2^2$$

$$F = \sum_{t=1}^T f_t$$

Hourglass


Human Pose
Estimation

Xiantong
Xiang


Background

Methods

Thanks



- The Hourglass is a multi-stage architecture, consisting of several stacked Hourglass modules (as the network resembles multiple stacked hourglasses).
- Each Hourglass module includes both a bottom-up process and a top-down process.



- Two stages:
 - GlobalNet learns a good feature representation based on feature pyramid network
 - RefineNet explicitly address the “hard” joints based on an online hard keypoints mining loss

- GlobalNet based on the **ResNet** backbone
- The advantages and disadvantages of feature representation:
 - **the shallow features** have the high spatial resolution for localization but low semantic information for recognition
 - **deep feature** layers have more semantic information but low spatial resolution
- an **U-shape structure** similar to the Feature Pyramid Network (FPN)
- GlobalNet fuses feature maps from different layers through **upsampling and downsampling**

CPN - RefineNet


Human Pose
Estimation

Xiantong
Xiang

Background

Methods

Thanks



- Deep features (low resolution, strong semantics) are upsampled to a higher resolution
- These refined features are then fused with the corresponding shallow features, combining both semantic and detailed information.

ViTPose


Human Pose Estimation

Xiantong Xiang

Background

Methods

Thanks



ViTPose

Human Pose
Estimation

Xiantong
Xiang

Background

Methods

Thanks

- Simplicity
 - Patch Embedding
 - Transformer Encoder
 - Decoder
- Scalability
- Flexibility
 - transferability
 - Pre-training data flexibility
 - Attention type flexibility
 - Finetuning flexibility
 - Task flexibility
- Transferability

OpenPose


Human Pose
Estimation

Xiantong
Xiang

Background

Methods

Thanks



- 2D confidence maps S

$$S_j \in \mathbb{R}^{w \times h}, \quad j \in 1, \dots, J$$

- 2D vector fields L of part affinity fields (PAFs)

$$L_c \in \mathbb{R}^{w \times h \times 2}, \quad c \in 1, \dots, C$$

OpenPose


Human Pose
Estimation

Xiantong
Xiang

Background

Methods

Thanks



- concatenate the predictions from the previous stage and the original image features F

$$L^t = \phi_t(F, L^{t-1}), \forall 2 \leq t \leq T_P,$$

- the process is repeated for the confidence maps detection

$$S^{T_P} = \rho_t(F, L^{T_P}), \forall t = T_P$$

$$S^t = \rho_t(F, L^{T_P}, S^{t-1}), \forall T_P < t \leq T_P + T_C$$

- weight the loss functions spatially

$$f_L^{t_i} = \sum_p \sum_{c=1}^C W(p) \cdot \|L_c^{t_i}(p) - L_c^*(p)\|_2^2$$

$$f_S^{t_k} = \sum_p \sum_{j=1}^J W(p) \cdot \|S_j^{t_k}(p) - S_j^*(p)\|_2^2$$

OpenPose - the groundtruth part confidence map

Human Pose
Estimation

Xiantong
Xiang

Background

Methods

Thanks

- the groundtruth part confidence map

$$S_{j,k}^*(p) = \exp \left(-\frac{|p - x_{j,k}|_2^2}{\sigma^2} \right)$$

- the individual confidence maps via a max operator

$$S_j^*(p) = \max_k S_{j,k}^*(p)$$

OpenPose - the groundtruth PAF

Human Pose
Estimation

Xiantong
Xiang

Background

Methods

Thanks

- the unit vector in the direction of the limb

$$v = \frac{x_{j2,k} - x_{j1,k}}{\|x_{j2,k} - x_{j1,k}\|_2}$$

- p on limb

$$0 \leq v \cdot (p - x_{j1,k}) \leq l_{c,k}$$

$$|v^\perp \cdot (p - x_{j1,k})| \leq \sigma_l$$

- the limb width σ_l
the limb length $l_{c,k} = \|x_{j2,k} - x_{j1,k}\|_2$



OpenPose - the groundtruth PAF

Human Pose
Estimation

Xiantong
Xiang

Background

Methods

Thanks

- the confidence in their association

$$E = \int_{u=0}^{u=1} L_c(p(u)) \cdot \frac{d_{j2} - d_{j1}}{\|d_{j2} - d_{j1}\|_2} du$$

- $p(u)$ interpolates the position of the two body parts

$$p(u) = (1 - u)d_{j1} + ud_{j2}$$

OpenPose

Human Pose
Estimation

Xiantong
Xiang

Background

Methods

Thanks


- a maximum weight bipartite graph matching problem

$$\max_{Z_c} E_c = \max_{Z_c} \sum_{m \in D_{j_1}} \sum_{n \in D_{j_2}} E_{mn} \cdot z_{j_1 j_2}^{mn}$$

$$s.t. \quad \forall m \in D_{j_1}, \quad \sum_{n \in D_{j_2}} z_{j_1 j_2}^{mn} \leq 1$$

$$\forall n \in D_{j_2}, \quad \sum_{m \in D_{j_1}} z_{j_1 j_2}^{mn} \leq 1$$

- the full body pose of multiple people
→ a K -dimensional matching problem (NP-Hard)



OpenPose

Human Pose
Estimation


Xiantong
Xiang

Background

Methods

Thanks

- Two relaxations to the optimization
 - Minimum Spanning Tree Relaxation
 - Local Matching Relaxation



RTMO


Human Pose
Estimation

Xiantong
Xiang

Background

Methods

Thanks



RTMO - Dynamic Coordinate Classifier

Human Pose
Estimation

Xiantong
Xiang

Background

Methods

Thanks

- DCC addresses these limitations by dynamically assigning bins to align with each instance's bounding box, ensuring localized coverage.

$$x_i = x_l + \frac{(x_r - x_l) \cdot (i - 1)}{B_x - 1}$$

- DCC generates tailored representations on-the-fly

$$[\text{PE}(x_i)]_c = \begin{cases} \sin\left(\frac{x_i}{t^{c/C}}\right), & \text{for even } c \\ \cos\left(\frac{x_i}{t^{(c-1)/C}}\right), & \text{for odd } c \end{cases}$$

- The probability heatmap is generated by multiplying the keypoint features with the positional encodings of each bin

$$\hat{p}_k(x_i) = \frac{e^{f_k \cdot \phi(\text{PE}(x_i))}}{\sum_{j=1}^{B_x} e^{f_k \cdot \phi(\text{PE}(x_j))}}$$

RTMO - MLE for Coordinate Classification

Human Pose
Estimation

Xiantong
Xiang

Background

Methods

Thanks

- Gaussian label smoothing

$$p_k(x_i | \mu_x) = \frac{1}{\sqrt{2\pi}\sigma} e^{-\frac{(x_i - \mu_x)^2}{2\sigma^2}} \sim \mathcal{N}(x_i; \mu_x, \sigma^2)$$

- the Gaussian distribution is symmetric with respect to its mean

$$P(\mu_x) = \sum_{i=1}^{B_x} P(\mu_x | x_i) P(x_i) = \sum_{i=1}^{B_x} \frac{1}{\sqrt{2\pi}\sigma} e^{-\frac{(x_i - \mu_x)^2}{2\sigma^2}} \hat{p}_k(x_i)$$

- a negative log-likelihood loss

$$L_{mle}^{(x)} = -\log \left[\sum_{i=1}^{B_x} \frac{1}{\sigma} e^{-\frac{|x_i - \mu_x|}{2\sigma s}} \hat{p}_k(x_i) \right]$$

Thanks

Human Pose
Estimation

Xiantong
Xiang

Background

Methods

Thanks

Happy Xiaonian !