

Opportunities and Challenges of Deep Learning Methods for Electrocardiogram Data: A Systematic Review

Shenda Hong^a, Yuxi Zhou^{b,c}, Junyuan Shang^{b,c}, Cao Xiao^d and Jimeng Sun^e

^aDepartment of Computational Science and Engineering, Georgia Institute of Technology, Atlanta, USA

^bSchool of Electronics Engineering and Computer Science, Peking University, Beijing, China

^cKey Laboratory of Machine Perception (Ministry of Education), Peking University, Beijing, China

^dAnalytics Center of Excellence, IQVIA, Cambridge, USA

^eDepartment of Computer Science, University of Illinois at Urbana-Champaign, Urbana, USA

ARTICLE INFO

Keywords:

Deep Learning
Deep Neural Network(s)
Electrocardiogram (ECG/EKG)
Systematic Review

ABSTRACT

Background: The electrocardiogram (ECG) is one of the most commonly used diagnostic tools in medicine and healthcare. Deep learning methods have achieved promising results on predictive healthcare tasks using ECG signals.

Objective: This paper presents a systematic review of deep learning methods for ECG data from both modeling and application perspectives.

Methods: We extracted papers that applied deep learning (deep neural network) models to ECG data that were published between January 1st of 2010 and February 29th of 2020 from Google Scholar, PubMed, and the Digital Bibliography & Library Project. We then analyzed each article according to three factors: tasks, models, and data. Finally, we discuss open challenges and unsolved problems in this area.

Results: The total number of papers extracted was 191. Among these papers, 108 were published after 2019. Different deep learning architectures have been used in various ECG analytics tasks, such as disease detection/classification, annotation/localization, sleep staging, biometric human identification, and denoising.

Conclusion: The number of works on deep learning for ECG data has grown explosively in recent years. Such works have achieved accuracy comparable to that of traditional feature-based approaches and ensembles of multiple approaches can achieve even better results. Specifically, we found that a hybrid architecture of a convolutional neural network and recurrent neural network ensemble using expert features yields the best results. However, there are some new challenges and problems related to interpretability, scalability, and efficiency that must be addressed. Furthermore, it is also worth investigating new applications from the perspectives of datasets and methods.


Significance: This paper summarizes existing deep learning research using ECG data from multiple perspectives and highlights existing challenges and problems to identify potential future research directions.

1. Introduction

The electrocardiogram (ECG/EKG) is one of the most commonly used non-invasive diagnostic tools for recording the physiological activities of the heart over a period of time. ECG data can aid in the diagnosis of many cardiovascular abnormalities, such as premature contractions of the atria (PAC) or ventricles (PVC), atrial fibrillation (AF), myocardial infarction (MI), and congestive heart failure (CHF). In recent years, we have witnessed the rapid development of portable ECG monitors in the medical field, such as the Holter monitor [129], and wearable devices in various healthcare areas, such as the Apple Watch. As a result, the amount of ECG data requiring analysis has grown too rapidly for human cardiologists to keep up. Therefore, analyzing ECG data automatically and accurately has become a hot research topic. Additionally, many emerging applications, such as biometric human identification and sleep staging, can be implemented based on ECG data.

Traditionally, automatic ECG analysis has relied on diagnostic golden rules. As shown in the top of Figure 1, this is a two-stage method that requires human experts to engineer useful features based on raw ECG data, which are referred to as “expert features”, and then deploy decision rules or other machine learning methods to generate final results. Expert features can be categorized [69] into statistical features (such as heart rate variability [19], sample entropy [3], and coefficients of variation and density histograms [172]), frequency-domain features [151, 106], and time-domain features (such as the Philips 12 lead ECG Algorithm [139]). In practice, expert features are automatically extracted using computer-based algorithms. However, they are still insufficient because they are limited by data quality and human expert knowledge [157, 161, 50].

Recently, deep learning methods have achieved promising results in many application areas, such as speech recognition, computer vision, and natural language processing [89]. The main advantage of deep learning methods is that they do not require an explicit feature extraction step using human experts, as shown in the bottom of Figure 1. Instead, feature extraction is performed automatically and implicitly by deep learning models based on their powerful data learn-

 sdhong1503@gmail.com (S. Hong); joy_yuxi@pku.edu.cn (Y. Zhou);
sjy1203@pku.edu.cn (J. Shang); cao.xiao@iqvia.com (C. Xiao);
jimeng.sun@gmail.com (J. Sun)
ORCID(s):




Figure 1: Comparisons between traditional methods and deep learning methods.

ing capabilities and flexible processing architectures. Some studies have experimentally demonstrated that deep learning features are more informative than expert features for ECG data [67, 69]. The performance of deep learning methods is also superior to that of traditional methods on many ECG analysis tasks, such as disease detection [30] and sleep staging [42].

Although some papers have reviewed machine learning methods for ECG data [121] (2019), cardiac arrhythmia detection using deep learning [136] (2019), and deep learning methods for ECG data [135] (2018), there have no systematic reviews focusing on deep learning methods, which we consider to be promising methods for mining ECG data. Therefore, we believe it is crucial to conduct a systematic review of existing deep learning methods for ECG data from the perspectives of model architectures and application tasks. Challenges and problems related to the current research status are discussed, which should provide inspiration and insights for future work.

2. Method

2.1. Search Strategy

To conduct a comprehensive review, we searched for papers that deployed deep learning methods (deep neural networks (DNNs)) for ECG data on Google Scholar, PubMed, and the Digital Bibliography & Library Project from January 1st of 2010 to February 29th of 2020.

Inspired by [136], the following general search terms were compiled for each database: ("electrocardiogram" OR "electrocardiology" OR "electrocardiography" OR "ECG" OR "EKG" OR "arrhythmia") AND ("deep learning" OR "deep neural network" OR "deep neural networks" OR "convolutional neural network" OR "cnn" OR "recurrent neural network" OR "rnn" OR "long short term memory" OR "lstm" OR "autoencoder" OR "deep belief network" OR "dbn"). All keywords are case insensitive.

To avoid missing papers that do not explicitly mention these keywords in their titles, we expanded our search to include all fields in each article. It should be noted that many unrelated papers mentioned some of the keywords in their introduction sections or related work sections, which resulted in a large initial set of papers.

2.2. Study Selection

We only included published peer-reviewed papers and excluded preprints. We focused on papers from the following journals/conferences:

- **Medical Information and Biomedical Engineering (MI & BME)** : Circulation, Journal of the American College of Cardiology, Nature Medicine, Nature Biomedical Engineering, American Medical Informatics Association, Journal of American Medical Informatics Association, Journal of American Biomedical Informatics, Transactions on Biomedical Engineering, Computers in Biology and Medicine, Biomedical Signal Procession and Control, Computing in Cardiology, Physiological Measurement, IEEE Journal of Biomedical and Health Informatics, Computer Methods and Programs in Biomedicine, Journal of Electrocardiology, International Conference of the IEEE Engineering in Medicine and Biology Society.
- **Artificial Intelligence and Data Mining (AI & DM)**: Nature Machine Intelligence, ACM SIGKDD International Conference on Knowledge Discovery & Data Mining, AAAI Conference on Artificial Intelligence, International Joint Conference on Artificial Intelligence, Neural Information Processing Systems, IEEE Transactions on Pattern Analysis and Machine Intelligence, International Conference on Acoustics, Speech and Signal Processing, IEEE Transactions on Neural Networks and Learning Systems, IEEE Transactions on Knowledge and Data Engineering, IEEE Transactions on Cybernetics, Neurocomputing, Knowledge-Based System, Expert Systems with Applications, Pattern Recognition Letters.
- **Interdisciplinary Area**: Nature Scientific Reports, PLoS One, IEEE Access.

The process of literature searching and selection is illustrated in Figure 2. It is a four-stage process consisting of identification, screening, eligibility, and inclusion.

The number of papers collected in the identification step is 1,621. After removing duplicates, the number of papers is 1,224. Next, paper eligibility assessment was conducted in coarse-to-fine manner by two independent reviewers: one reviewer screening titles and abstracts, and another reviewer reading full texts. The exclusion criteria are 1) not in English, 2) not focusing on ECG data, 3) not using deep learning methods, and 4) no quantitative evaluations. As a result, 928 papers were excluded by screening and 105 papers were excluded by full text assessment. This left 191 papers among the initial 1,621 papers.

2.3. Data Extraction and Analysis

Each paper was analyzed according to the following three aspects:

- **Task**: the targeted application tasks were (1) disease detection (e.g., specific diseases such as AF, MI, CHF, ST elevation, or general diagnostic arrhythmia), (2) annotation or localization (e.g., QRS complex annotation, P-




Figure 2: Framework for literature searching and selection.

wave annotation, localizing the origin of ventricular activation), (3) sleep staging, (4) biometric human identification, (5) denoising, and (6) others.

- **Model:** deep model architectures include (1) convolutional neural networks (CNNs), (2) recurrent neural networks (RNNs), (3) combinations of CNNs and RNNs (CRNNs), (4) autoencoders (AEs), (5) generative adversarial networks (GANs), (6) fully connected neural networks (FCs), and (6) others. We also determined (7) whether each paper included traditional expert features or integrated expert knowledge when constructing a deep model.
- **Data:** data statistics are (1) the size of the dataset, (2) number of channels (number of electrode leads), (3) duration, (4) annotations, (5) sources, (6) collection year, and (7) number of used papers.

We summarized all papers from the perspectives of models and tasks, as shown in Figure 3. Finally, we discuss the challenges and problems that existing models cannot handle well.

3. Results

We included 191 papers in our survey and analyzed them based on the aspects of tasks, models, and data. An overview of our analysis is presented in Figure 3. General statistics

for these papers are presented in Figure 4. Among the included papers, 108 (approximately 57%) were published after 2019, 112 were published by the medical information and biomedical engineering community, and only 25 (approximately 13%) were published by the artificial intelligence and data mining community. We provide a detailed summary of each paper on our GitHub at <https://github.com/hsd1503/DL-ECG-Review>.

3.1. Task

3.1.1. Disease Detection

The goal of developing a deep learning model for disease detection is to map input ECG data to output disease targets through multiple layers of neural networks [66]. For example, the detection of cardiac arrhythmias (e.g., atrial flutter, supraventricular tachyarrhythmia, and ventricular trigeminy) [57] is one of the most common tasks for deep learning models based on ECG signals. AF detection can be regarded as a special case of cardiac arrhythmia detection, where all non-AF rhythms are grouped together [173, 229]. Additionally, a deep learning technique was introduced to monitor ST changes in ECG data [134]. In [113] and [181], convolutional neural networks were applied to automate the detection of MI and CHF, respectively.

From the perspective of the volume of classification results, multiple modalities (e.g., ECG, transthoracic echocardiogram [8]) can be employed for binary classification tasks (e.g., patients with paroxysmal AF or healthy patients [143]), multi-class classification tasks (e.g., detection of acute cognitive stress [61] and decompensation of patient detection [205]), and multi-task classification tasks (e.g., detection of prevalent hypertension, sleep apnea, and diabetes [174]).

3.1.2. Localization and Annotation

The localization and annotation of specific waves in ECG signals are of great importance for cardiologists attempting to diagnose cardiac diseases, such as AF. For instance, AEs [51] and RNNs [52] have been employed to localize the exit of ventricular tachycardia in 12-lead ECG data automatically. Some studies have focused on localizing of the origins of premature ventricular issues [207] and MI [220].

Most studies that have applied deep learning methods to ECG annotation have focused on using deep learning methods for annotating the fetal QRS complex (detecting Q-waves, R-waves, and S-waves, and calculating heart rate), which is critical for identifying various arrhythmias, in the MIT-BIH arrhythmia dataset [93]. Some studies have used the QT database of PhysioNet [46] to explore other methods for annotating ECG waves, including P-wave [138] and T-wave annotation [10]. Another annotated 12-lead ECG dataset named Lobachevsky University database (LUDB) is provided by [77].

3.1.3. Sleep Staging

Understanding sleep patterns is critical for improving healthcare because sleep is a key aspect of our wellbeing. Sleep disorders can lead to catastrophes in personal medicine or public health [118]. In [97], a sparse AE (SAE) and hidden




Figure 3: Overview of analysis based on the aspects of tasks, models, and data.




Figure 4: General statistics for all papers.

Markov model (HMM) were combined to detect obstructive sleep apnea (OSA) using the PhysioNet challenge 2000 dataset. A CNN has also been used to detect OSA [118].

In addition to OSA detection, CNN-based deep learning architectures have also been employed for the multi-class classification of OSA with hypopnea [176], which is the most common sleep-related breathing disorder, based on single-lead ECG data. Some studies have focused on sleep stage identification outside of OSA detection. For example, a long short-term memory (LSTM) network was employed in [188] to analyze a multi-channel physiological signal dataset (electroencephalogram, electrooculogram, and electromyogram signals), which was collected by the Sleep Disorder Diagnosis Center of Xijing Hospital at the Fourth Military Medical

University.

3.1.4. Human Identification

Based on the rapid development of information technology, body sensor networks are reshaping people's daily lives, particularly in the context of smart health applications. Biometric-based human identification is a promising technology for automatic and accurate individual recognition based on various body sensor data, including heart rate, temperature, and activity. Zhang et al. constructed a CNN-based biometric human identification system, evaluated their system using eight datasets from PhysioNet (CEBSDB, WECG, FANTASIA, NSRDB, STDB, MITDB, AFDB, and VFDB), and achieved state-of-the-art performance using a CNN. Similarly, the PTB diagnostic dataset (549 15 channel ECG records from 290 subjects) [86] and CYBHi dataset (65 subjects between 21.64 and 40.56 y old) [54] were also used to evaluate CNN-based biometric human identification methods.

Some studies have combined CNNs with other approaches. Zhao et al. proposed a novel ECG biometric authentication system that incorporates the generalized S-transformation and CNN techniques. A secure multimodal biometric system using a CNN and Q-Gaussian multi-support vector machine (SVM) based on a different levels of fusion was developed in [54].

Additionally, residual networks have been employed to develop ECG biometric authentication methods that can improve generalization for ECG signals sampled in the differ-

	Disease Detection	Annotation or Localiza- tion	Sleep Staging	Biometric Identification	Denoising	Others
CNN	[80, 82, 212, 113, 1, 67, 201, 5, 191, 153, 105, 43, 81, 143, 196, 192, 211, 7, 41, 47, 102, 216, 100, 137, 200, 141, 167, 78, 168, 128, 195, 154, 18, 75, 159, 31, 62, 189, 71, 63, 193, 169, 95, 94, 61, 21, 134, 103, 164, 8, 57, 98, 69, 130, 178, 224, 160, 227, 13, 16, 88, 190, 58, 170, 72, 131, 177, 59, 55]	[207, 20, 226, 25, 214, 93, 53, 76, 175, 166, 74, 124]	[118, 176, 35]	[219, 225, 54, 26, 29, 86, 221, 65, 101]	[223, 27, 39, 40]	[156, 9, 120, 11, 160, 6, 208, 162]
RNN	[117, 158, 209, 23, 173, 147, 111, 228, 24, 31, 62, 179, 99, 45, 220, 202, 155]	[10, 138, 52]	[188, 35]	N.A.	[144]	[60]
CRNN	[231, 186, 174, 12, 37, 171, 132, 146, 163, 187, 197, 4, 110, 125, 181, 182, 68, 229, 140, 73, 184, 210, 96, 198, 2, 222, 112, 126, 104]	[215]	N.A.	[114]	N.A.	[34, 148, 205, 49, 230, 142]
AE	[36, 194, 179, 218, 210]	[52, 51]	[97]	N.A.	[27, 199]	[44, 213, 84]
GAN	[182, 45, 227]	N.A.	N.A.	N.A.	[180]	[90, 230, 208, 60, 162]
NN with Ex- pert Features	[67, 5, 191, 117, 43, 47, 71, 99, 173, 78, 69, 155, 206, 96, 88, 58, 141, 167, 137]	N.A.	N.A.	[54]	[223]	N.A.
FC & Others	[203, 204, 119, 133, 116, 79, 38, 127, 206]	N.A.	[35]	[92]	N.A.	[217, 85]

Table 1

Summary of papers from the perspectives of models and tasks.

ent environments for similar tasks [29]. In [92], features were extracted using a principal component analysis network (PCANet). Next, a robust Eigen ECG network was applied to the time-frequency representations of ECGs for personal identification. A bidirectional gated recurrent unit (GRU)-based method was also proposed for human identification based on ECG data [114].

3.1.5. Denoising

The ECG signal acquisition process is often accompanied by a large amount of noise, which negatively affects the accuracy of diagnosis, particularly in telemedicine environments. In [40], an encoder-decoder CNN, which is a widely used deep learning technique, was employed for ECG denoising. Similarly, Xiong et al. and Chiang et al. proposed fully-convolutional-network-based denoising AE (DAE) methods for ECG signal denoising. In [91], a bidirectional recurrent DAE was used to perform photoplethysmography feature accentuation for pulse waveform analysis.

Additionally, GANs have been employed to accumulate knowledge regarding the distribution of ECG noise continuously through a minimax game between a generator and discriminator, where the quality of denoised signals was evaluated versus an SVM algorithm [180]. Zhao et al. addressed noise by developing a noise rejection method based on a combination of a modified frequency slice wavelet transform (WT) and CNN.

3.1.6. Others

The CNNs used in other types of studies focused on emotion detection [156], drug assessment [9], data compression [217], transfer learning in ECG classification from human data to horse data [177], etc. Combinations of CNNs and LSTM networks have been used to learn long-term depen-

dencies (e.g., classifying pulsed rhythm or pulseless electrical activity [34], detecting hypoglycemic events in healthy individuals [142], predicting the need for urgent revascularization [49], and classifying driver stress levels [148]). A combination of a CNN and HMM was used to segment ECG data into standard component waveforms and intervals [175].

Additionally, AEs [44] have been used for the reconstruction and analysis of biomedical signals. GANs have been employed for ECG generation [230] and synthesis [90], as well as anomaly beat detection [227]. Some studies have used DNNs to process raw ECG waveform data for future risk prediction (e.g., assessing the risk of future cardiac disease [120], sudden cardiac arrest risk prediction [160], mortality prediction [145], and physiological measures for health prediction [6]).

3.2. Models

3.2.1. CNN

CNNs represent a class of DNNs that are widely applied for image classification, natural language processing, and signal analysis. Such networks can automatically extract hierarchical patterns in data using stacked trainable small filters or kernels, meaning they require relatively little preprocessing compared to handcrafted features. A typical CNN is composed of several convolutional layers followed by a batch normalization layer, nonlinear activation layer, dropout layer, pooling layer, and classification layer (e.g., fully connected layer), as discussed in [57]. In some works, SVMs, boosting classifier trees, and RNNs have been used as alternative fully connected layers to summarize global features in CNNs. CNNs can achieve superior performance and fast computation based on shared-weight architectures and parallelization.

Two types of CNN are commonly used for ECG classification, namely the 1D CNN and 2D CNN. A 1D CNN operates by applying kernels along the temporal dimension of raw ECG data, whereas a 2D CNN typically operates on transformed ECG data, such as distance distribution matrices based on entropy calculations [102], gray-level co-occurrence matrices [169], or combined features, such as morphologies, RR intervals, and beat-to-beat correlations [95]. However, there is some controversy regarding the use of multi-head ECG or time-frequency ECG spectrograms extracted using the WT, fast Fourier transform (FFT), or short-term Fourier transform. Some works, such as [71], have directly applied 2D-CNNs to such spectrograms, but this introduces issues related to varying frequency resolutions, meaning most signal characteristics are reflected by intra-component patterns, rather than inter-component behaviors. To overcome this issue, a shared 1D CNN was adopted in [80, 113]. Similarly, a multi-scale 1D CNN was adopted in [219] for biometric human identification.

Additionally, a 2D CNN can be applied to a one-head ECG signal, which is treated as an image. In such cases, a pre-trained ResNet, DenseNet, or Inception-Net trained on an ImageNet dataset [32] can be fine tuned on an ECG dataset to perform heartbeat disease detection [189] and analyze ST changes [182]. Particularly for localization tasks, such as QRS detection, a fully convolutional network with a large kernel size can be applied to an ECG image to reduce that image's height to one while maintaining an output length equal to the input length to derive a QRS window label [93].

Some advanced techniques, such as an atrous spatial pyramid pooling module, can be used to exploit multi-scale features in ECG data. Additionally, active learning [193] and data augmentation [182, 229] can be incorporated into CNN frameworks to handle imbalance problems and further improve accuracy.

3.2.2. RNN

An RNN is a type of neural network designed to model sequential data, such as time series, event sequences, and natural language. In an RNN, the output from the previous step is used as the input for the current step. By iteratively updating hidden states and memory, an RNN is capable of remembering information in sequential order.

In particular, for ECG data, RNNs are a logical choice for both capturing temporal dependencies and handling inputs of various lengths. GRU/LSTM and bidirectional-LSTM (BiLSTM) are commonly used RNN variants that handle a critical problem called the vanishing gradient, which negatively affects classical RNNs. Two small LSTM networks were employed in [155] to combine raw ECG features and WT features for continuous real-time execution on wearable devices. In [99], an attention mechanism was incorporated into a BiLSTM network to improve performance and interpretability by visualizing attention weights.

3.2.3. CRNN

A CRNN, as the name suggests, combines CNN and RNN modules. This is a preferred architecture for handling long ECG signals with varied sequence lengths and multi-channel inputs. A 1D CNN [62] or 2D CNN [163] is used to extract local features from an ECG sequence. An RNN then summarizes local features along the time dimension to generate global features.

DeepHeart [12] follows the CRNN framework to perform cardiovascular risk prediction for heart rate sequences extracted from ECG data and utilizes an AE model (see Sec. 3.2.4) to initialize model weights to achieve enhanced performance. To provide interpretable diagnosis, MINA [68] incorporates a CRNN with a multi-level attention mechanism with beat-level, rhythm-level, and frequency-level expert features based on medical domain knowledge.

3.2.4. AE

An AE is a type of neural network composed of an encoder module and decoder module for learning embeddings in an unsupervised manner. The goal of an AE is to learn a reduced dimensional representation using the encoder module while the decoder attempts to reconstruct an original input from this reduced representation. There are three commonly used variants of the AE, namely the DAE, SAE, and contractive AE (CAE). DAEs take partially corrupted inputs and are trained to recover original undistorted inputs. SAEs and CAEs utilize different regularization methods, such as KL-divergence and the Frobenius norm of the Jacobian matrix, to learn robust representations.

Stacked DAEs [194], SAEs [213, 218], and CAEs [199] are widely used for ECG denoising purposes because ECG signals are often contaminated by various types of noise, such as baseline wandering, electrode contact noise, and motion artifacts, which may lead to inaccurate interpretations. In practice, the effectiveness of an AE is determined by the choice of encoder and decoder modules. As introduced in Sections 3.2.1, 3.2.2, and 3.2.3, CNNs, RNNs, and CRNNs are typically combined to serve as encoder and decoder modules. The authors of [27] utilized fully convolutional networks as an encoder and decoder while [87] used BiLSTM. To improve classification performance, the authors of [44, 147, 210] simultaneously conducted the reconstruction and classification procedures. For examples, the authors of [210] utilized a 1D CNN AE to first compress large ECG signals with minimum loss, and then fed the compressed signals into an LSTM network to recognize arrhythmias automatically.

3.2.5. GAN

A GAN is a class of neural network framework that was invented by Goodfellow et al. [48]. This type of model consists of two sub-models: a generative model G that captures the data distribution of a training dataset in a latent representation and a discriminative model D that determines the probability that a sample produced by the generator comes from the true data distribution. These two models are trained iteratively to conduct a minimax game.

GAN application has increased rapidly, particularly in areas such as image generation [17] and language generation [107]. Recently, GANs have been applied to tackle the data imbalance challenge in ECG data. For example, the authors of [182] proposed an abnormality detection model for ECG signals based on a CRNN framework and used a GAN composed of multiple 1D CNNs to perform data augmentation. Their model achieved excellent performance for class-imbalanced datasets. The authors of [189] utilized a GAN to perform denoising of ECG data and the authors of [230] proposed a GAN composed of a BiLSTM network (generator) and CNN (discriminator) to generate synthetic ECG data to train a deep learning model. Similarly, a model called PGAN [45] was proposed to perform personalized ECG classification, where subject-specific labeled data is sparse. Specifically, a GAN was optimized using a specialized loss function and trained to generate personalized synthetic ECG signals for different arrhythmias.

3.2.6. NN with Expert Features

ENCASE [67] suggests that expert features can be divided into three categories: 1) statistical features (e.g., count, mean, maximum, and minimum), 2) signal processing features that transform ECG data from the time domain into the frequency domain (e.g., FFT, WT, and Shannon entropy), and 3) medical features based on medical domain knowledge (e.g., features based on P-, Q-, R-, S- and T-waves, sample entropy, and the coefficient of variation and density histograms).

All of these methods can benefit significantly from expert features, although additional effort is required to extract such features compared to raw morphological features. Ensemble methods [67, 71, 191, 141, 167, 137] combine expert features with raw morphological features and incorporate various tree models with DNNs to achieved better results compared to individual models.

3.2.7. FC & Others

Some works have relied on FCs for disease detection and classification [38, 79], particularly for extremely short ECG sequences (e.g., 10 RR intervals) [79]. Stacked restricted Boltzmann machines, which are a type of generative stochastic DNN, are also used to process raw ECG data in combination with beat alignment processing to classify heartbeat types [203].

Other works have borrowed ideas from the computer vision field. For example, U-net [152], which is based on a fully convolutional network and consists of a contracting path and expansive path, is widely used for image segmentation tasks. The authors of [133] proposed a modified U-net to handle various lengths of ECG sequences for classification and R-peak detection. PCANet [22], which is an image classification model based on cascaded principal component analysis, binary hashing, and block-wise histograms, was modified for biometric human identification tasks in a non-stationary ECG noise environment [92]. However, the effectiveness of this method must still be evaluated accord-




Figure 5: Example 15 lead ECG data collected from medical devices. The figure presents 10 s of 15 lead ECG data from an MI patient in the PTB Diagnostic ECG Database.




Figure 6: Example single-lead ECG data collected from healthcare devices. The figure presents 30 s of single-lead ECG data from an AF patient in the PhysioNet Computing in Cardiology Challenge 2017 dataset.

ing to the state-of-the-art baselines discussed above.

3.3. Data

Most of the works identified in this review (150 out of 191) used open-source datasets, which makes it easier to perform follow-up works and reproduction. A summary of the 10 most frequently used open-source databases is provided in Table 2. We list the following parameters for each database, which can be used to classify the databases into further subtypes:

- **Sources.** Most databases were collected from medical devices, but a few were collected from healthcare devices. The biggest difference between such devices is that medical device data typically have more leads than healthcare device data, meaning medical device data are more informative. However, medical device data are also more difficult to collect. Healthcare ECG monitor devices, such as smart hardware and wristbands, are becoming increasingly common.
- **Number of leads.** A standard 12 lead ECG (or even 15-lead ECG) system can observe more abnormalities than a single-lead ECG (similar to lead I in a 12 lead ECG). For example, posterior wall MI can only be detected by chest

Database	Records	Leads	Duration	Annotations	Source	Year	Papers
MIT-BIH Arrhythmia Database ¹	47	2	30 minutes	Beat Level, rhythm level. (annotations are keeping updating, please refer to https://archive.physionet.org/physiobank/annotations.shtml)	Boston's Beth Israel Hospital	1975-1979	54
PhysioNet Computing in Cardiology Challenge 2017 ²	8528 train, 3658 test	1	30 seconds	Rhythm level: normal, AF, other, noise	AliveCor healthcare device	2017	33
PTB Diagnostic ECG Database ³	549	15	Several minutes	Rhythm level: Myocardial infarction, Cardiomyopathy/Heart failure, Bundle branch block, Dysrhythmia, Myocardial hypertrophy, Valvular heart disease, Myocarditis, Miscellaneous, Healthy controls	National Metrology Institute of Germany	1995	16
MIT-BIH Atrial Fibrillation Database ⁴	25	2	10 hours	Rhythm level: AF, atrial flutter (AFL), AV junctional rhythm, and others	Boston's Beth Israel Hospital	1983	8
2018 China Physiological Signal Challenge ⁵	6877 train, 2954 test	12	15 seconds	Rhythm level: AF, I-AVB, LBBB, RBBB, PAC, PVC, STD, STE	11 hospitals	2018	7
QT Database ⁶	105	2	15 minutes	Onset, peak, and end markers for P, QRS, T, and U waves	Compiled from several existing databases	1997	6
MIT-BIH Normal Sinus Rhythm Database ⁷	18	2	24 hours	Beat Level: normal	Boston's Beth Israel Hospital	N.A.	5
St Petersburg IN-CART 12-lead Arrhythmia Database ⁸	75	12	30 minutes	Rhythm level: Acute MI, Transient ischemic attack (angina pectoris), Prior MI, Coronary artery disease with hypertension, Sinus node dysfunction, Supraventricular ectopy, Atrial fibrillation or SVTA, WPW, AV block, Bundle branch block	St. Petersburg Institute of Cardiological Technics	2003	3
MIT-BIH Malignant Ventricular Ectopy Database ⁹	22	2	30 minutes	ventricular tachycardia, ventricular flutter, and ventricular fibrillation	Compiled from two separate databases	1986	3
CU Ventricular Tachyarrhythmia Database ¹⁰	35	1	8 minutes	ventricular tachycardia, ventricular flutter, and ventricular fibrillation	Creighton University Cardiac Center	1986	3

Table 2
Summary of databases.

leads (V1 to V4) and no abnormalities will be detected by a single lead. Examples of 15 lead ECG data from medical devices and single lead ECG data from healthcare devices are presented in Figures 5 and 6, respectively.

- **Duration.** Short-term ECG data (less than several minutes) and long-term ECG data can complement each other. Short-term ECG data is cheaper and easier to collect. Many cardiac diseases can be detected based on short-term ECG data, so such data represent the primary diagnostic tool in outpatient departments. However, long-term ECG can help to detect diseases with intermittent symptoms, such as paroxysmal ventricular fibrillation (VF) and AF.
- **Annotations.** Annotations include ECG measurement annotations (onset, peak, and end markers for P-, QRS-, T-, and U-waves), beat-level annotations (PAC, PVC, etc.), and rhythm-level annotations (covers both beat-level annotations and other diseases such as AF and VF). Annotation requires huge effort by medical experts.

The following databases were used by many of the selected papers:

- The MIT-BIH Arrhythmia Database [123] (54 papers) consists of 48 half-hour ECG records from 47 subjects at Boston's Beth Israel Hospital (now the Beth Israel Deaconess Medical Center). Each ECG data sequence has an 11 bit resolution over a 10 mV range with a sampling frequency of 360 Hz. This dataset is fully annotated with both beat-level and rhythm-level diagnoses.
- The PhysioNet Computing in Cardiology Challenge 2017 dataset [30] (33 papers) contains 8,528 de-identified ECG recordings with durations ranging from 9 s to just over 60 s that were sampled at 300 Hz by an AliveCor healthcare device. Among these recordings, 5154 are normal, 717 recordings are AF, 2,557 recordings are others, and 46 recordings are noise. Additionally, 3,658 test recordings are private for scoring. This dataset was collected by healthcare devices.
- The PTB Diagnostic ECG Database [15] (16 papers) contains 549 15 channel ECG records from 290 subjects. The sampling rate reaches as high as 10 kHz. Among these subjects, 216 have one of eight types of heart disease and 52 are healthy control, while 22 are unknown.
- The MIT-BIH Atrial Fibrillation Database [122] (8 papers) includes 25 10 h long-term 2 lead ECG recordings with a sampling rate of 250 Hz for human subjects with AF (mostly paroxysmal). The original recordings were collected at Boston's Beth Israel Hospital using ambula-

¹<https://physionet.org/content/mitdb/1.0.0/>

²<https://www.physionet.org/content/challenge-2017/1.0.0/>

³<https://physionet.org/content/ptbdb/1.0.0/>

⁴<https://physionet.org/content/afdb/1.0.0/>

⁵<http://2018.icbeb.org/Challenge.html>

⁶<https://physionet.org/content/qtdb/1.0.0/>

⁷<https://physionet.org/content/nsrdb/1.0.0/>

⁸<https://physionet.org/content/incartdb/1.0.0/>

⁹<https://physionet.org/content/vfdb/1.0.0/>

¹⁰<https://physionet.org/content/cudb/1.0.0/>

Method	Model	F_{1N}	F_{1A}	F_{1O}	F_{1P}	F_{1NAOP}	F_{1NAO}
[173]	RNN + Expert Features	0.9030	0.8547	0.7366	0.5622	0.7641	0.8314
[57]	CNN	0.91	0.84	0.74	NA	NA	0.83
[141]	CNN + Expert Features	0.9151	0.8247	0.7437	NA	NA	0.8278
[67]	CRNN + Expert Features	0.9117	0.8128	0.7505	0.5671	0.7605	0.8250
[167]	CNN + Expert Features	0.9142	0.8153	0.7370	NA	NA	0.8222
[231]	CRNN	0.9090	0.8221	0.7319	0.5676	0.7577	0.8210
[187]	CRNN	0.9028	0.8221	0.7324	NA	NA	0.8191
[200]	CNN	0.9031	0.8203	0.7310	0.5251	0.7449	0.8181
[137]	CNN + Expert Features	0.9056	0.8284	0.7204	NA	NA	0.8181

Table 3

Comparison of deep learning methods on the PhysioNet Computing in Cardiology Challenge 2017 dataset. We only include methods with an F_1 score over 0.8 reported for the hidden test set.

tory ECG recorders with a 0.1 to 40 Hz recording bandwidth.

- 2018 The China Physiological Signal Challenge dataset [109] (seven papers) contains 6,877 (3178 female, 3699 male) 12 lead ECG recordings with durations ranging from 6 s to just over 60 s, which were collected at 11 hospitals with a sampling rate of 500 Hz. Among these recordings, 918 are normal, 1,098 recordings are AF, 704 are first-degree atrioventricular block, 207 recordings are left-bundle branch block (LBBB), 1,695 are right-bundle branch block (RBBB), 556 are PAC, 672 recordings are PVC, 825 are ST segment depression, and 202 are ST segment elevation. Additionally, 2,954 test recordings are private for scoring.

A summary of the deep learning methods tested on the PhysioNet Computing in Cardiology Challenge 2017 dataset is provided in Table 3. We only include methods with an F_1 score over 0.8 reported for the hidden test set. One can find the official leaderboards for the PhysioNet Computing in Cardiology Challenge 2017 at <https://physionet.org/content/challenge-2017/1.0.0/>, 2018 China Physiological Signal Challenge at <http://2018.icbeb.org/Challenge.html>, and PhysioNet Computing in Cardiology Challenge 2020 at <https://physionetchallenges.github.io/2020/>.

4. Discussion of Opportunities and Challenges

In this section, we will discuss the current challenges and problems related to deep learning based on ECG data. Additionally, potential opportunities are also identified in the context of these challenges and problems.

4.1. Data Collection

As shown in Table 2, there is no standard regarding collection procedures. Different studies have used various numbers of leads, durations, sources (subject backgrounds), etc. This makes it difficult to compare results between different datasets fairly. Additionally, high-quality data and annotations are difficult to acquire, so many current works are still using the MIT-BIH Arrhythmia Database, which was collected over 40 y ago. The most recent single-lead PhysioNet Computing in Cardiology Challenge 2017 and 12 lead 2018 China Physiological Signal Challenge used high-quality data,

but they both focused on short-term ECG recordings. Researchers would welcome a new high-quality long-term ECG dataset with annotations and such a dataset would certainly inspire new innovative studies.

4.2. Interpretability

Deep learning models are often considered to be black-box models because they typically have many model parameters or complex model architectures, which makes it difficult for a human to understand why a particular result is generated by such a model. This challenge is much more severe in the medical domain because diagnoses without any explanation are not acceptable for medical experts.

There have been a few works focusing on enhancing the interpretability of ECG deep learning methods. For example, some works have [99, 69] explicitly added interpretable expert features to deep learning models that can be used for partial interpretation. Others have used multi-level attention weights [68] or attribute scores [168] to generate salient maps based on raw ECG data. There have also been several works [163, 69] on generating lower-dimensional embeddings using t-distributed stochastic neighbor embeddings [115] to derive interpretable results.

There are two worthwhile research directions regarding interpretability. The first is how to interpret complex deep learning models using relatively simple models. For example, one can first construct a black-box deep learning model for a specific task, and then construct a separate interpretable simple model that matches the deep learning model's predictions, and then interpret prediction results based on the simple model [149, 150]. The second one is how to construct an interpretable deep model directly. For example, when designing a deep model architecture, one can borrow neuron connection concepts from tree-based models [183] or add attention mechanisms to hidden layers [28, 68] because such mechanisms can be more easily understood by humans.

4.3. Efficiency

Because deep models are complex, it is difficult to deploy large models on portable healthcare devices, which is a major obstacle to applying deep learning models in real-world applications. In this context, one promising research direction is the model compression technique. For example, knowledge distillation is commonly used to transform large and powerful models into simpler models with a minor decrease in accuracy [64]. Additionally, one can use quantization, weight sharing, and careful coding of network weights [56] to compress a large model.

4.4. Integration with Traditional Methods

Most existing deep learning models are trained in an end-to-end manner, making them difficult to integrate with traditional expert-feature-based methods after model training is completed [135].

There are two main research directions for tackling this issue. The first is to use existing expert knowledge to design DNN architectures [70]. For example, the authors of [68] proposed guiding multilevel attention weights using expert

features for modeling ECG data. The second is to consider deep models as feature extractors and explicitly extract latent embeddings from deep learning models. To some extent, neural networks with expert features represent a step in this direction. Therefore, one can easily combine expert features with deep features and construct traditional machine learning methods on such features.

4.5. Imbalanced Labels

ECG disease labels are very likely to have very biased distributions because most severe diseases occur rarely, but are very important. It is difficult to train an effective deep learning method with a large number of model parameters using small datasets of disease labels.

There are two main methods for handling this problem. The first is data augmentation, such as data preprocessing using the side-and-cut technique, or generating synthetic training datasets using generative models, such as variational AEs [33] or GANs [48]. The second is to design new loss functions, such as focal loss [108], or new model training schema, such as few-shot learning [185].

For example, the method proposed in [229] uses a skewness-driven dynamic data augmentation technique to balance data distributions. The authors of [227] and [45] deployed GANs to improve classification accuracy and anomaly detection, respectively. The method proposed in [75] eliminates the negative effects of imbalanced data from the perspectives of resampling, data features, and algorithms.

4.6. Multimodal Data

Currently, most works have only considered ECG data for analysis. However, a few works have considered joint analysis with other data sources. For example, the method proposed in [205] predicts intensive care unit patient mortalities based on a combination of interventions, lab tests, vital signs, and ECG data. The authors of [54] designed a multi-modal biometric authentication system using a fusion of ECG and fingerprint data.

Based on the development of medical and healthcare devices, many vital signs, such as temperature, respiratory rate, and blood pressure can be collected simultaneously with ECG data. However, these data are not always synchronized with ECG timelines and their sampling frequencies vary significantly, meaning they can be regarded as multimodal data. There is a potential opportunity to study how to design models that are capable of utilizing such multimodal data simultaneously to improve task performance compared to models trained on any individual modality.

4.7. Emerging Interdisciplinary Studies

Finally, there have been a few innovative interdisciplinary studies, a few of which are listed below. 1) Safe driving intensity and cardiac reaction time assessment based on ECG signals [83]. 2) Emotion detection based on ECG signals [165]. 3) Mammalian ECG analysis [14]. 4) Estimating age and gender based on ECG data [6]. The key to the success of such studies is adequate data support.

5. Conclusion

In this paper, we systematically reviewed existing deep learning (DNN) methods for ECG data from the perspectives of models, data, and tasks. We found that deep learning methods can generally achieve better performance than traditional methods for ECG modeling. However, there are still some unresolved challenges and problems related to these deep learning methods. Our main contributions are twofold. First, we provided a systematic overview of various deep learning methods that can be employed in real applications. Second, we highlighted some potential future research opportunities.

Acknowledgement

This work was partially supported by the National Science Foundation awards IIS-1418511, CCF-1533768 and IIS-1838042, and the National Institute of Health awards NIH R01 1R01NS107291-01 and R56HL138415.

References

- [1] Acharya, U.R., Oh, S.L., Hagiwara, Y., Tan, J.H., Adam, M., Gertych, A., San Tan, R., 2017. A deep convolutional neural network model to classify heartbeats. *Computers in biology and medicine* 89, 389–396.
- [2] Al Rahhal, M.M., Bazi, Y., Almubarak, H., Alajlan, N., Al Zuair, M., 2019. Dense convolutional networks with focal loss and image generation for electrocardiogram classification. *IEEE Access* 7, 182225–182237.
- [3] Alcaraz, R., Abásolo, D., Hornero, R., Rieta, J.J., 2010. Optimal parameters study for sample entropy-based atrial fibrillation organization analysis. *computer methods and programs in biomedicine* 99, 124–132.
- [4] Andersen, R.S., Peimankar, A., Puthusserypady, S., 2019. A deep learning approach for real-time detection of atrial fibrillation. *Expert Systems with Applications* 115, 465–473.
- [5] Andreotti, F., Carr, O., Pimentel, M.A., Mahdi, A., De Vos, M., 2017. Comparing feature-based classifiers and convolutional neural networks to detect arrhythmia from short segments of ecg, in: *2017 Computing in Cardiology (CinC)*, IEEE. pp. 1–4.
- [6] Attia, Z.I., Friedman, P.A., Noseworthy, P.A., Lopez-Jimenez, F., Ladewig, D.J., Satam, G., Pellikka, P.A., Munger, T.M., Asirvatham, S.J., Scott, C.G., et al., 2019a. Age and sex estimation using artificial intelligence from standard 12-lead ecgs. *Circulation: Arrhythmia and Electrophysiology* 12, e007284.
- [7] Attia, Z.I., Kapa, S., Lopez-Jimenez, F., Asirvatham, S.J., Friedman, P.A., Noseworthy, P.A., 2018a. Electrocardiographic screening for atrial fibrillation while in sinus rhythm using deep learning. *Circulation* 138, A15871–A15871.
- [8] Attia, Z.I., Kapa, S., Lopez-Jimenez, F., McKie, P.M., Ladewig, D.J., Satam, G., Pellikka, P.A., Enriquez-Sarano, M., Noseworthy, P.A., Munger, T.M., et al., 2019b. Screening for cardiac contractile dysfunction using an artificial intelligence-enabled electrocardiogram. *Nature medicine* 25, 70.
- [9] Attia, Z.I., Sugrue, A., Asirvatham, S.J., Ackerman, M.J., Kapa, S., Friedman, P.A., Noseworthy, P.A., 2018b. Noninvasive assessment of dofetilide plasma concentration using a deep learning (neural network) analysis of the surface electrocardiogram: A proof of concept study. *PloS one* 13, e0201059.
- [10] Attin, M., Cogliati, A., Duan, Z., 2017. Annotating ecg signals with deep neural networks. *Circulation* 136, A19056–A19056.
- [11] Baalman, S.W., Ramos, L.A., Lopes, R.R., Van Der Stuijt, W., Bleijendaal, H., Brouwer, T.F., Marquering, H.A., Driessen, A.H.,

- Knops, R.E., de Groot, J.R., 2019. A deep learning model to predict outcome after thoracoscopic surgery for atrial fibrillation using single beat electrocardiographic samples. *Circulation* 140, A15889–A15889.
- [12] Ballinger, B., Hsieh, J., Singh, A., Sohoni, N., Wang, J., Tison, G.H., Marcus, G.M., Sanchez, J.M., Maguire, C., Olgin, J.E., et al., 2018. Deepheart: semi-supervised sequence learning for cardiovascular risk prediction, in: *Thirty-Second AAAI Conference on Artificial Intelligence*.
- [13] Baloglu, U.B., Talo, M., Yildirim, O., San Tan, R., Acharya, U.R., 2019. Classification of myocardial infarction with multi-lead ecg signals and deep cnn. *Pattern Recognition Letters* 122, 23–30.
- [14] Behar, J.A., Rosenberg, A.A., Weiser-Bitoun, I., Shemla, O., Alexandrovich, A., Konyukhov, E., Yaniv, Y., 2018. Physiozoo: a novel open access platform for heart rate variability analysis of mammalian electrocardiographic data. *Frontiers in physiology* 9, 1390.
- [15] Bousset, R., Kreisler, D., Schnabel, A., 1995. Nutzung der ekg-signal-datenbank cardiodat der ptb über das internet. *Biomedizinische Technik/Biomedical Engineering* 40, 317–318.
- [16] Brisk, R., Bond, R., Banks, E., Padi, A., Finlay, D., McLaughlin, J., McEneaney, D., 2019. Deep learning to automatically interpret images of the electrocardiogram: Do we need the raw samples? *Journal of electrocardiology* 57, S65.
- [17] Brock, A., Donahue, J., Simonyan, K., 2018. Large scale gan training for high fidelity natural image synthesis. *arXiv preprint arXiv:1809.11096*.
- [18] Cai, W., Chen, Y., Guo, J., Han, B., Shi, Y., Ji, L., Wang, J., Zhang, G., Luo, J., 2019. Accurate detection of atrial fibrillation from 12-lead ecg using deep neural network. *Computers in Biology and Medicine*, 103378.
- [19] Camm, A.J., Malik, M., Bigger, J.T., Breithardt, G., Cerutti, S., Cohen, R.J., Coumel, P., Fallen, E.L., Kennedy, H.L., Kleiger, R., et al., 1996. Heart rate variability: standards of measurement, physiological interpretation and clinical use. task force of the european society of cardiology and the north american society of pacing and electrophysiology.
- [20] Camps, J., Rodríguez, B., Mincholé, A., 2018. Deep learning based qrs multilead delineator in electrocardiogram signals, in: *2018 Computing in Cardiology Conference (CinC)*, IEEE. pp. 1–4.
- [21] Cao, X.C., Yao, B., Chen, B.Q., 2019. Atrial fibrillation detection using an improved multi-scale decomposition enhanced residual convolutional neural network. *IEEE Access* 7, 89152–89161.
- [22] Chan, T.H., Jia, K., Gao, S., Lu, J., Zeng, Z., Ma, Y., 2015. Pcanet: A simple deep learning baseline for image classification? *IEEE transactions on image processing* 24, 5017–5032.
- [23] Chang, Y.C., Wu, S.H., Tseng, L.M., Chao, H.L., Ko, C.H., 2018. Af detection by exploiting the spectral and temporal characteristics of ecg signals with the lstm model, in: *2018 Computing in Cardiology Conference (CinC)*, IEEE. pp. 1–4.
- [24] Chauhan, S., Vig, L., Ahmad, S., 2019. Ecg anomaly class identification using lstm and error profile modeling. *Computers in biology and medicine* 109, 14–21.
- [25] Chen, M., Wang, G., Xie, P., Sang, Z., Lv, T., Zhang, P., Yang, H., 2018. Region aggregation network: Improving convolutional neural network for ecg characteristic detection, in: *2018 40th Annual International Conference of the IEEE Engineering in Medicine and Biology Society (EMBC)*, IEEE. pp. 2559–2562.
- [26] Chen, Y., Chen, W., 2018. Finger ecg based two-phase authentication using 1d convolutional neural networks, in: *2018 40th Annual International Conference of the IEEE Engineering in Medicine and Biology Society (EMBC)*, IEEE. pp. 336–339.
- [27] Chiang, H.T., Hsieh, Y.Y., Fu, S.W., Hung, K.H., Tsao, Y., Chien, S.Y., 2019. Noise reduction in ecg signals using fully convolutional denoising autoencoders. *IEEE Access* 7, 60806–60813.
- [28] Choi, E., Bahadori, M.T., Sun, J., Kulas, J., Schuetz, A., Stewart, W.F., 2016. RETAIN: an interpretable predictive model for healthcare using reverse time attention mechanism, in: *Advances in Neural Information Processing Systems 29: Annual Conference on Neural Information Processing Systems 2016, December 5–10, 2016, Barcelona, Spain*, pp. 3504–3512.
- [29] Chu, Y., Shen, H., Huang, K., 2019. Ecg authentication method based on parallel multi-scale one-dimensional residual network with center and margin loss. *IEEE Access* 7, 51598–51607.
- [30] Clifford, G.D., Liu, C., Moody, B., Li-wei, H.L., Silva, I., Li, Q., Johnson, A., Mark, R.G., 2017. Af classification from a short single lead ecg recording: the physionet/computing in cardiology challenge 2017, in: *2017 Computing in Cardiology (CinC)*, IEEE. pp. 1–4.
- [31] Dang, H., Sun, M., Zhang, G., Qi, X., Zhou, X., Chang, Q., 2019. A novel deep arrhythmia-diagnosis network for atrial fibrillation classification using electrocardiogram signals. *IEEE Access*.
- [32] Deng, J., Dong, W., Socher, R., Li, L.J., Li, K., Fei-Fei, L., 2009. Imagenet: A large-scale hierarchical image database, in: *2009 IEEE conference on computer vision and pattern recognition*, Ieee. pp. 248–255.
- [33] Doersch, C., 2016. Tutorial on variational autoencoders. *arXiv preprint arXiv:1606.05908*.
- [34] Elola, A., Aramendi, E., Irujo, U., Picón, A., Alonso, E., Owens, P., Idris, A., 2018. Deep learning for pulse detection in out-of-hospital cardiac arrest using the ecg, in: *2018 Computing in Cardiology Conference (CinC)*, IEEE. pp. 1–4.
- [35] Erdenebayar, U., Kim, Y.J., Park, J.U., Joo, E.Y., Lee, K.J., 2019. Deep learning approaches for automatic detection of sleep apnea events from an electrocardiogram. *Computer methods and programs in biomedicine* 180, 105001.
- [36] Farhadi, J., Attarodi, G., Dabanloo, N.J., Mohandespoor, M., Es-lamizadeh, M., 2018. Classification of atrial fibrillation using stacked auto encoders neural networks, in: *2018 Computing in Cardiology Conference (CinC)*, IEEE. pp. 1–3.
- [37] Faust, O., Shenfield, A., Kareem, M., San, T.R., Fujita, H., Acharya, U.R., 2018. Automated detection of atrial fibrillation using long short-term memory network with rr interval signals. *Computers in biology and medicine* 102, 327–335.
- [38] Feng, N., Xu, S., Liang, Y., Liu, K., 2019. A probabilistic process neural network and its application in ecg classification. *IEEE Access* 7, 50431–50439.
- [39] Fotiadou, E., Konopczyński, T., Hesser, J., Vullings, R., 2019. Deep convolutional encoder-decoder framework for fetal ecg signal denoising, in: *2019 Computing in Cardiology (CinC)*, IEEE. pp. Page–1.
- [40] Fotiadou, E., Konopczyński, T., Hesser, J.W., Vullings, R., 2020. End-to-end trained cnn encoder-decoder network for fetal ecg signal denoising. *Physiological Measurement*.
- [41] Gadaleta, M., Rossi, M., Steinhilber, S.R., Quer, G., 2018. Deep learning to detect atrial fibrillation from short noisy ecg segments measured with wireless sensors. *Circulation* 138, A16177–A16177.
- [42] Ghassemi, M.M., Moody, B.E., Lehman, L.W.H., Song, C., Li, Q., Sun, H., Mark, R.G., Westover, M.B., Clifford, G.D., 2018. You snooze, you win: the physionet/computing in cardiology challenge 2018, in: *2018 Computing in Cardiology Conference (CinC)*, IEEE. pp. 1–4.
- [43] Ghiasi, S., Abdollahpur, M., Madani, N., Kiani, K., Ghaffari, A., 2017. Atrial fibrillation detection using feature based algorithm and deep convolutional neural network, in: *2017 Computing in Cardiology (CinC)*, IEEE. pp. 1–4.
- [44] Gogna, A., Majumdar, A., Ward, R., 2016. Semi-supervised stacked label consistent autoencoder for reconstruction and analysis of biomedical signals. *IEEE Transactions on Biomedical Engineering* 64, 2196–2205.
- [45] Golany, T., Radinsky, K., 2019. Pgans: Personalized generative adversarial networks for ecg synthesis to improve patient-specific deep ecg classification, in: *Proceedings of the AAAI Conference on Artificial Intelligence*, pp. 557–564.
- [46] Goldberger, A.L., Amaral, L.A., Glass, L., Hausdorff, J.M., Ivanov, P.C., Mark, R.G., Mietus, J.E., Moody, G.B., Peng, C.K., Stanley, H.E., 2000. PhysioBank, physioToolkit, and physionet: components of a new research resource for complex physiologic signals. *Circu-*

- lation 101, e215–e220.
- [47] Golrizkhatami, Z., Acan, A., 2018. Ecg classification using three-level fusion of different feature descriptors. *Expert Systems with Applications* 114, 54–64.
- [48] Goodfellow, I., Pouget-Abadie, J., Mirza, M., Xu, B., Warde-Farley, D., Ozair, S., Courville, A., Bengio, Y., 2014. Generative adversarial nets, in: *Advances in neural information processing systems*, pp. 2672–2680.
- [49] Goto, S., Kimura, M., Katsumata, Y., Goto, S., Kamatani, T., Ichihara, G., Ko, S., Sasaki, J., Fukuda, K., Sano, M., 2019. Artificial intelligence to predict needs for urgent revascularization from 12-leads electrocardiography in emergency patients. *PLoS one* 14, e0210103.
- [50] Guglin, M.E., Thattai, D., 2006. Common errors in computer electrocardiogram interpretation. *International journal of cardiology* 106, 232–237.
- [51] Gyawali, P.K., Chen, S., Liu, H., Horacek, B.M., Sapp, J.L., Wang, L., 2017. Automatic coordinate prediction of the exit of ventricular tachycardia from 12-lead electrocardiogram, in: *2017 Computing in Cardiology (CinC)*, IEEE. pp. 1–4.
- [52] Gyawali, P.K., Horacek, B.M., Sapp, J.L., Wang, L., 2019. Sequential factorized autoencoder for localizing the origin of ventricular activation from 12-lead electrocardiograms. *IEEE Transactions on Biomedical Engineering*.
- [53] Habib, A., Karmakar, C., Yearwood, J., 2019. Impact of ecg dataset diversity on generalization of cnn model for detecting qrs complex. *IEEE access* 7, 93275–93285.
- [54] Hammad, M., Liu, Y., Wang, K., 2018. Multimodal biometric authentication systems using convolution neural network based on different level fusion of ecg and fingerprint. *IEEE Access* 7, 26527–26542.
- [55] Han, C., Shi, L., 2020. MI-resnet: A novel network to detect and locate myocardial infarction using 12 leads ecg. *Computer methods and programs in biomedicine* 185, 105138.
- [56] Han, S., Mao, H., Dally, W.J., 2016. Deep compression: Compressing deep neural network with pruning, trained quantization and huffman coding, in: *4th International Conference on Learning Representations, ICLR 2016, San Juan, Puerto Rico, May 2–4, 2016, Conference Track Proceedings*. URL: <http://arxiv.org/abs/1510.00149>.
- [57] Hannun, A.Y., Rajpurkar, P., Haghighpanahi, M., Tison, G.H., Bourn, C., Turakhia, M.P., Ng, A.Y., 2019. Cardiologist-level arrhythmia detection and classification in ambulatory electrocardiograms using a deep neural network. *Nature medicine* 25, 65.
- [58] Hao, C., Wibowo, S., Majmudar, M., Rajput, K.S., 2019. Spectrotemporal feature based multi-channel convolutional neural network for ecg beat classification, in: *2019 41st Annual International Conference of the IEEE Engineering in Medicine and Biology Society (EMBC)*, IEEE. pp. 5642–5645.
- [59] Hao, P., Gao, X., Li, Z., Zhang, J., Wu, F., Bai, C., 2020. Multi-branch fusion network for myocardial infarction screening from 12-lead ecg images. *Computer Methods and Programs in Biomedicine* 184, 105286.
- [60] Harada, S., Hayashi, H., Uchida, S., 2019. Biosignal generation and latent variable analysis with recurrent generative adversarial networks. *IEEE Access* 7, 144292–144302.
- [61] He, J., Li, K., Liao, X., Zhang, P., Jiang, N., 2019a. Real-time detection of acute cognitive stress using a convolutional neural network from electrocardiographic signal. *IEEE Access* 7, 42710–42717.
- [62] He, R., Liu, Y., Wang, K., Zhao, N., Yuan, Y., Li, Q., Zhang, H., 2019b. Automatic cardiac arrhythmia classification using combination of deep residual network and bidirectional lstm. *IEEE Access* 7, 102119–102135.
- [63] He, W., Wang, G., Hu, J., Li, C., Guo, B., Li, F., 2019c. Simultaneous human health monitoring and time-frequency sparse representation using eeg and ecg signals. *IEEE Access* 7, 85985–85994.
- [64] Hinton, G.E., Vinyals, O., Dean, J., 2015. Distilling the knowledge in a neural network. *CoRR abs/1503.02531*. URL: <http://arxiv.org/abs/1503.02531>, arXiv:1503.02531.
- [65] Hong, P.L., Hsiao, J.Y., Chung, C.H., Feng, Y.M., Wu, S.C., 2019a. Ecg biometric recognition: template-free approaches based on deep learning, in: *2019 41st Annual International Conference of the IEEE Engineering in Medicine and Biology Society (EMBC)*, IEEE. pp. 2633–2636.
- [66] Hong, S., Fu, Z., Zhou, R., Yu, J., Li, Y., Wang, K., Cheng, G., 2020. Cardiollearn: A cloud deep learning service for cardiac disease detection from electrocardiogram, in: *Companion Proceedings of the Web Conference 2020*, pp. 148–152.
- [67] Hong, S., Wu, M., Zhou, Y., Wang, Q., Shang, J., Li, H., Xie, J., 2017. Encase: An ensemble classifier for ecg classification using expert features and deep neural networks, in: *2017 Computing in Cardiology (CinC)*, IEEE. pp. 1–4.
- [68] Hong, S., Xiao, C., Ma, T., Li, H., Sun, J., 2019b. Mina: Multi-level knowledge-guided attention for modeling electrocardiography signals, in: *Twenty-Eighth International Joint Conference on Artificial Intelligence (IJCAI)*, pp. 5888–5894.
- [69] Hong, S., Zhou, Y., Wu, M., Shang, J., Wang, Q., Li, H., Xie, J., 2019c. Combining deep neural networks and engineered features for cardiac arrhythmia detection from ecg recordings. *Physiological measurement* 40, 054009.
- [70] Hu, Z., Ma, X., Liu, Z., Hovy, E.H., Xing, E.P., 2016. Harnessing deep neural networks with logic rules, in: *Proceedings of the 54th Annual Meeting of the Association for Computational Linguistics, ACL 2016, August 7–12, 2016, Berlin, Germany, Volume 1: Long Papers*. URL: <https://www.aclweb.org/anthology/P16-1228/>.
- [71] Huang, J., Chen, B., Yao, B., He, W., 2019. Ecg arrhythmia classification using stft-based spectrogram and convolutional neural network. *IEEE Access* 7, 92871–92880.
- [72] Jalali, A., Lee, M., 2019. Atrial fibrillation prediction with residual network using sensitivity & orthogonality constraints. *IEEE Journal of Biomedical and Health Informatics*.
- [73] Jia, D., Zhao, W., Hu, J., Wang, H., Yan, C., Li, Z., 2019a. Detection of first-degree atrioventricular block on variable-length electrocardiogram via a multimodal deep learning method, in: *2019 Computing in Cardiology (CinC)*, IEEE. pp. Page–1.
- [74] Jia, D., Zhao, W., Li, Z., Hu, J., Yan, C., Wang, H., You, T., 2019b. An electrocardiogram delineator via deep segmentation network, in: *2019 41st Annual International Conference of the IEEE Engineering in Medicine and Biology Society (EMBC)*, IEEE. pp. 1913–1916.
- [75] Jiang, J., Zhang, H., Pi, D., Dai, C., 2019. A novel multi-module neural network system for imbalanced heartbeats classification. *Expert Systems with Applications: X* 1, 100003.
- [76] Jimenez-Perez, G., Alcaine, A., Camara, O., 2019. U-net architecture for the automatic detection and delineation of the electrocardiogram, in: *2019 Computing in Cardiology (CinC)*, IEEE. pp. Page–1.
- [77] Kalyakulina, A.I., Yusipov, I.I., Moskalenko, V.A., Nikolskiy, A.V., Kozlov, A.A., Kosonogov, K.A., Zolotikh, N.Y., Ivanchenko, M.V., 2018. Lu electrocardiography database: a new open-access validation tool for delineation algorithms. *arXiv preprint arXiv:1809.03393*.
- [78] Kamaleswaran, R., Mahajan, R., Akbilgic, O., 2018. A robust deep convolutional neural network for the classification of abnormal cardiac rhythm using single lead electrocardiograms of variable length. *Physiological measurement* 39, 035006.
- [79] Kimura, T., Takatsuki, S., Yamashita, H., Miyama, H., Fujisawa, T., Nakajima, K., Katsumata, Y., Nishiyama, T., Aizawa, Y., Fukuda, K., 2018. A 10-rr-interval-based rhythm classifier using a deep neural network. *Circulation* 138, A12693–A12693.
- [80] Kiranyaz, S., Ince, T., Gabbouj, M., 2015a. Real-time patient-specific ecg classification by 1-d convolutional neural networks. *IEEE Transactions on Biomedical Engineering* 63, 664–675.
- [81] Kiranyaz, S., Ince, T., Gabbouj, M., 2017. Personalized monitoring and advance warning system for cardiac arrhythmias. *Scientific reports* 7, 9270.
- [82] Kiranyaz, S., Ince, T., Hamila, R., Gabbouj, M., 2015b. Convolutional neural networks for patient-specific ecg classification, in: *2015 37th Annual International Conference of the IEEE Engineering in Medicine and Biology Society (EMBC)*, IEEE. pp. 2608–2611.

- [83] Koh, D.W., Lee, S.G., 2019. An evaluation method of safe driving for senior adults using ecg signals. *Sensors* 19, 2828.
- [84] Kuznetsov, V., Moskalenko, V., Zolotykh, N.Y., 2020. Electrocardiogram generation and feature extraction using a variational autoencoder. *arXiv preprint arXiv:2002.00254*.
- [85] Kwon, J.m., Kim, K.H., Jeon, K.H., Lee, S.E., Lee, H.Y., Cho, H.J., Choi, J.O., Jeon, E.S., Kim, M.S., Kim, J.J., et al., 2019. Artificial intelligence algorithm for predicting mortality of patients with acute heart failure. *PloS one* 14.
- [86] Labati, R.D., Muñoz, E., Piuri, V., Sassi, R., Scotti, F., 2019. Deep-ecg: convolutional neural networks for ecg biometric recognition. *Pattern Recognition Letters* 126, 78–85.
- [87] Laguna, P., Mark, R.G., Goldberg, A., Moody, G.B., 1997. A database for evaluation of algorithms for measurement of qt and other waveform intervals in the ecg, in: *Computers in cardiology* 1997, IEEE. pp. 673–676.
- [88] Lai, D., Zhang, X., Bu, Y., Su, Y., Ma, C.S., 2019. An automatic system for real-time identifying atrial fibrillation by using a lightweight convolutional neural network. *IEEE access* 7, 130074–130084.
- [89] LeCun, Y., Bengio, Y., Hinton, G.E., 2015. Deep learning. *Nature* 521, 436–444. URL: <https://doi.org/10.1038/nature14539>, doi:10.1038/nature14539.
- [90] Lee, J., Oh, K., Kim, B., Yoo, S.K., 2019a. Synthesis of electrocardiogram v lead signals from limb lead measurement using r peak aligned generative adversarial network. *IEEE journal of biomedical and health informatics*.
- [91] Lee, J., Sun, S., Yang, S., Sohn, J., Park, J., Lee, S., Kim, H.C., 2018. Bidirectional recurrent auto-encoder for photoplethysmogram denoising. *IEEE journal of biomedical and health informatics*.
- [92] Lee, J.N., Kwak, K.C., 2019. Personal identification using a robust eigen ecg network based on time-frequency representations of ecg signals. *IEEE Access* 7, 48392–48404.
- [93] Lee, J.S., Lee, S.J., Choi, M., Seo, M., Kim, S.W., 2019b. Qrs detection method based on fully convolutional networks for capacitive electrocardiogram. *Expert Systems with Applications* 134, 66–78.
- [94] Li, F., Wu, J., Jia, M., Chen, Z., Pu, Y., 2019a. Automated heartbeat classification exploiting convolutional neural network with channel-wise attention. *IEEE Access*.
- [95] Li, F., Xu, Y., Chen, Z., Liu, Z., 2019b. Automated heartbeat classification using 3-d inputs based on convolutional neural network with multi-fields of view. *IEEE Access* 7, 76295–76304.
- [96] Li, H., Wang, X., Liu, C., Wang, Y., Li, P., Tang, H., Yao, L., Zhang, H., 2019c. Dual-input neural network integrating feature extraction and deep learning for coronary artery disease detection using electrocardiogram and phonocardiogram. *IEEE Access* 7, 146457–146469.
- [97] Li, K., Pan, W., Li, Y., Jiang, Q., Liu, G., 2018a. A method to detect sleep apnea based on deep neural network and hidden markov model using single-lead ecg signal. *Neurocomputing* 294, 94–101.
- [98] Li, Q., Liu, C., Li, Q., Shashikumar, S.P., Nemati, S., Shen, Z., Clifford, G.D., 2019d. Ventricular ectopic beat detection using a wavelet transform and a convolutional neural network. *Physiological measurement* 40, 055002.
- [99] Li, R., Zhang, X., Dai, H., Zhou, B., Wang, Z., 2019e. Interpretability analysis of heartbeat classification based on heartbeat activity’s global sequence features and bilstm-attention neural network. *IEEE Access* 7, 109870–109883.
- [100] Li, Y., Pang, Y., Wang, J., Li, X., 2018b. Patient-specific ecg classification by deeper cnn from generic to dedicated. *Neurocomputing* 314, 336–346.
- [101] Li, Y., Pang, Y., Wang, K., Li, X., 2020a. Toward improving ecg biometric identification using cascaded convolutional neural networks. *Neurocomputing*.
- [102] Li, Y., Zhang, Y., Zhao, L., Zhang, Y., Liu, C., Zhang, L., Zhang, L., Li, Z., Wang, B., Ng, E., et al., 2018c. Combining convolutional neural network and distance distribution matrix for identification of congestive heart failure. *IEEE Access* 6, 39734–39744.
- [103] Li, Z., Feng, X., Wu, Z., Yang, C., Bai, B., Yang, Q., 2019f. Classification of atrial fibrillation recurrence based on a convolution neural network with svm architecture. *IEEE Access* 7, 77849–77856.
- [104] Li, Z., Zhou, D., Wan, L., Li, J., Mou, W., 2020b. Heartbeat classification using deep residual convolutional neural network from 2-lead electrocardiogram. *Journal of Electrocardiology* 58, 105–112.
- [105] Limam, M., Precioso, F., 2017. Atrial fibrillation detection and ecg classification based on convolutional recurrent neural network, in: *2017 Computing in Cardiology (CinC)*, IEEE. pp. 1–4.
- [106] Lin, C.H., 2008. Frequency-domain features for ecg beat discrimination using grey relational analysis-based classifier. *Computers & Mathematics with Applications* 55, 680–690.
- [107] Lin, K., Li, D., He, X., Zhang, Z., Sun, M.T., 2017a. Adversarial ranking for language generation, in: *Advances in Neural Information Processing Systems*, pp. 3155–3165.
- [108] Lin, T., Goyal, P., Girshick, R.B., He, K., Dollár, P., 2017b. Focal loss for dense object detection, in: *IEEE International Conference on Computer Vision, ICCV 2017, Venice, Italy, October 22–29, 2017*, pp. 2999–3007. URL: <https://doi.org/10.1109/ICCV.2017.324>, doi:10.1109/ICCV.2017.324.
- [109] Liu, F., Liu, C., Zhao, L., Zhang, X., Wu, X., Xu, X., Liu, Y., Ma, C., Wei, S., He, Z., et al., 2018. An open access database for evaluating the algorithms of electrocardiogram rhythm and morphology abnormality detection. *Journal of Medical Imaging and Health Informatics* 8, 1368–1373.
- [110] Liu, F., Zhou, X., Cao, J., Wang, Z., Wang, H., Zhang, Y., 2019a. A lstm and cnn based assemble neural network framework for arrhythmias classification, in: *ICASSP 2019–2019 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, IEEE. pp. 1303–1307.
- [111] Liu, M., Kim, Y., 2018. Classification of heart diseases based on ecg signals using long short-term memory, in: *2018 40th Annual International Conference of the IEEE Engineering in Medicine and Biology Society (EMBC)*, IEEE. pp. 2707–2710.
- [112] Liu, W., Wang, F., Huang, Q., Chang, S., Wang, H., He, J., 2019b. Mfb-cbrnn: a hybrid network for mi detection using 12-lead ecgs. *IEEE journal of biomedical and health informatics*.
- [113] Liu, W., Zhang, M., Zhang, Y., Liao, Y., Huang, Q., Chang, S., Wang, H., He, J., 2017. Real-time multilead convolutional neural network for myocardial infarction detection. *IEEE journal of biomedical and health informatics* 22, 1434–1444.
- [114] Lynn, H.M., Pan, S.B., Kim, P., 2019. A deep bidirectional gru network model for biometric electrocardiogram classification based on recurrent neural networks. *IEEE Access* 7, 145395–145405.
- [115] Maaten, L.v.d., Hinton, G., 2008. Visualizing data using t-sne. *Journal of machine learning research* 9, 2579–2605.
- [116] Maidens, J., Slamon, N.B., 2018. Artificial intelligence detects pediatric heart murmurs with cardiologist-level accuracy. *Circulation* 138, A12591–A12591.
- [117] Maknickas, V., Maknickas, A., 2017. Atrial fibrillation classification using qrs complex features and lstm, in: *2017 Computing in Cardiology (CinC)*, IEEE. pp. 1–4.
- [118] Malik, J., Lo, Y.L., Wu, H.t., 2018. Sleep-wake classification via quantifying heart rate variability by convolutional neural network. *Physiological measurement* 39, 085004.
- [119] Mathews, S.M., Kambhmettu, C., Barner, K.E., 2018. A novel application of deep learning for single-lead ecg classification. *Computers in biology and medicine* 99, 53–62.
- [120] Miller, A.C., Obermeyer, Z., Mullainathan, S., 2019. A comparison of patient history-and ekg-based cardiac risk scores. *AMIA Summits on Translational Science Proceedings* 2019, 82.
- [121] Mincholé, A., Camps, J., Lyon, A., Rodríguez, B., 2019. Machine learning in the electrocardiogram. *Journal of electrocardiology*.
- [122] Moody, G., 1983. A new method for detecting atrial fibrillation using rr intervals. *Computers in Cardiology*, 227–230.
- [123] Moody, G.B., Mark, R.G., 2001. The impact of the mit-bih arrhythmia database. *IEEE Engineering in Medicine and Biology Magazine* 20, 45–50.
- [124] Moskalenko, V., Zolotykh, N., Osipov, G., 2020. Deep learning for ecg segmentation, in: *Kryzhanovsky, B., Dunin-Barkowski, W.,*

- Redko, V., Tiumentsev, Y. (Eds.), *Advances in Neural Computation, Machine Learning, and Cognitive Research III*, Springer International Publishing, Cham, pp. 246–254.
- [125] Mousavi, S., Afghah, F., 2019. Inter-and intra-patient ecg heart-beat classification for arrhythmia detection: a sequence to sequence deep learning approach, in: ICASSP 2019-2019 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP), IEEE. pp. 1308–1312.
- [126] Mousavi, S., Fotoohinasab, A., Afghah, F., 2020. Single-modal and multi-modal false arrhythmia alarm reduction using attention-based convolutional and recurrent neural networks. *PloS one* 15, e0226990.
- [127] Mukherjee, A., Choudhury, A.D., Datta, S., Puri, C., Banerjee, R., Singh, R., Ukil, A., Bandyopadhyay, S., Pal, A., Khandelwal, S., 2019. Detection of atrial fibrillation and other abnormal rhythms from ecg using a multi-layer classifier architecture. *Physiological measurement* 40, 054006.
- [128] Nguyen, M.T., Van Nguyen, B., Kim, K., 2018. Deep feature learning for sudden cardiac arrest detection in automated external defibrillators. *Scientific reports* 8, 17196.
- [129] Nikolic, G., Bishop, R., Singh, J., 1982. Sudden death recorded during holter monitoring. *Circulation* 66, 218–225.
- [130] Niu, J., Tang, Y., Sun, Z., Zhang, W., 2019. Inter-patient ecg classification with symbolic representations and multi-perspective convolutional neural networks. *IEEE journal of biomedical and health informatics*.
- [131] Noseworthy, P.A., Attia, Z.I., Brewer, L.C., Hayes, S.N., Yao, X., Kapa, S., Friedman, P.A., Lopez-Jimenez, F., 2020. Assessing and mitigating bias in medical artificial intelligence: The effects of race and ethnicity on a deep learning model for ecg analysis. *Circulation: Arrhythmia and Electrophysiology*.
- [132] Oh, S.L., Ng, E.Y., San Tan, R., Acharya, U.R., 2018. Automated diagnosis of arrhythmia using combination of cnn and lstm techniques with variable length heart beats. *Computers in biology and medicine* 102, 278–287.
- [133] Oh, S.L., Ng, E.Y., San Tan, R., Acharya, U.R., 2019. Automated beat-wise arrhythmia diagnosis using modified u-net on extended electrocardiographic recordings with heterogeneous arrhythmia types. *Computers in biology and medicine* 105, 92–101.
- [134] Park, Y., Yun, I.D., Kang, S.H., 2019. Preprocessing method for performance enhancement in cnn-based stemi detection from 12-lead ecg. *IEEE Access* 7, 99964–99977.
- [135] Parvaneh, S., Rubin, J., 2018. Electrocardiogram monitoring and interpretation: from traditional machine learning to deep learning, and their combination, in: 2018 Computing in Cardiology Conference (CinC), IEEE. pp. 1–4.
- [136] Parvaneh, S., Rubin, J., Babaeizadeh, S., Xu-Wilson, M., 2019. Cardiac arrhythmia detection using deep learning: A review. *Journal of electrocardiology*.
- [137] Parvaneh, S., Rubin, J., Rahman, A., Conroy, B., Babaeizadeh, S., 2018. Analyzing single-lead short ecg recordings using dense convolutional neural networks and feature-based post-processing to detect atrial fibrillation. *Physiological measurement* 39, 084003.
- [138] Peimankar, A., Puthusserypady, S., 2019. An ensemble of deep recurrent neural networks for p-wave detection in electrocardiogram, in: ICASSP 2019-2019 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP), IEEE. pp. 1284–1288.
- [139] Philips, 2003. The Philips 12-Lead Algorithm Physician's Guide. URL: [http://incenter.medical.philips.com/doclib/enc/fetch/2000/4504/577242/577243/577245/577817/577818/12-Lead_Algorithm_Physician_s_Guide_for_Algorithm_Version_PH080A%2C_\(ENG\).pdf%3Fnodeid%3D3325283%26vernum%3D1](http://incenter.medical.philips.com/doclib/enc/fetch/2000/4504/577242/577243/577245/577817/577818/12-Lead_Algorithm_Physician_s_Guide_for_Algorithm_Version_PH080A%2C_(ENG).pdf%3Fnodeid%3D3325283%26vernum%3D1).
- [140] Picon, A., Irusta, U., Álvarez-Gila, A., Aramendi, E., Alonso-Atienza, F., Figuera, C., Ayala, U., Garrote, E., Wik, L., Kramer-Johansen, J., et al., 2019. Mixed convolutional and long short-term memory network for the detection of lethal ventricular arrhythmia. *PloS one* 14, e0216756.
- [141] Plesinger, F., Nejedly, P., Viscor, I., Halamek, J., Jurak, P., 2018. Parallel use of a convolutional neural network and bagged tree ensemble for the classification of holter ecg. *Physiological measurement* 39, 094002.
- [142] Porumb, M., Stranges, S., Pescapè, A., Pecchia, L., 2020. Precision medicine and artificial intelligence: A pilot study on deep learning for hypoglycemic events detection based on ecg. *Scientific Reports* 10, 1–16.
- [143] Pourbabae, B., Roshtkhari, M.J., Khorasani, K., 2017. Deep convolutional neural networks and learning ecg features for screening paroxysmal atrial fibrillation patients. *IEEE Transactions on Systems, Man, and Cybernetics: Systems* 48, 2095–2104.
- [144] Qiu, Y., Xiao, F., Shen, H., 2017. Elimination of power line interference from ecg signals using recurrent neural networks, in: 2017 39th Annual International Conference of the IEEE Engineering in Medicine and Biology Society (EMBC), IEEE. pp. 2296–2299.
- [145] Raghunath, S.M., Ulloa Cerna, A., Jing, L., vanMaanen, D., Stough, J.V., Hartzel, D., Leader, J., Kirchner, H.L., Good, C., Patel, A., et al., 2019. Deep neural networks can predict 1-year mortality directly from ecg signal, even when clinically interpreted as normal. *Circulation* 140, A14425–A14425.
- [146] Rajan, D., Beymer, D., Narayan, G., 2018. Generalization studies of neural network models for cardiac disease detection using limited channel ecg, in: 2018 Computing in Cardiology Conference (CinC), IEEE. pp. 1–4.
- [147] Rajan, D., Thiagarajan, J.J., 2018. A generative modeling approach to limited channel ecg classification, in: 2018 40th Annual International Conference of the IEEE Engineering in Medicine and Biology Society (EMBC), IEEE. pp. 2571–2574.
- [148] Rastgoo, M.N., Nakisa, B., Maire, F., Rakotonirainy, A., Chandran, V., 2019. Automatic driver stress level classification using multimodal deep learning. *Expert Systems with Applications* 138, 112793.
- [149] Ribeiro, M.T., Singh, S., Guestrin, C., 2016. "why should I trust you?": Explaining the predictions of any classifier, in: Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining, San Francisco, CA, USA, August 13–17, 2016, pp. 1135–1144. URL: <https://doi.org/10.1145/2939672.2939778>.
- [150] Ribeiro, M.T., Singh, S., Guestrin, C., 2018. Anchors: High-precision model-agnostic explanations, in: Proceedings of the Thirty-Second AAAI Conference on Artificial Intelligence, (AAAI-18), the 30th innovative Applications of Artificial Intelligence (IAAI-18), and the 8th AAAI Symposium on Educational Advances in Artificial Intelligence (EAAI-18), New Orleans, Louisiana, USA, February 2–7, 2018, pp. 1527–1535. URL: <https://www.aaai.org/ocs/index.php/AAAI/AAAI18/paper/view/16982>.
- [151] Romero, I., Serrano, L., 2001. Ecg frequency domain features extraction: A new characteristic for arrhythmias classification, in: 2001 Conference Proceedings of the 23rd Annual International Conference of the IEEE Engineering in Medicine and Biology Society, IEEE. pp. 2006–2008.
- [152] Ronneberger, O., Fischer, P., Brox, T., 2015. U-net: Convolutional networks for biomedical image segmentation, in: International Conference on Medical image computing and computer-assisted intervention, Springer. pp. 234–241.
- [153] Rubin, J., Parvaneh, S., Rahman, A., Conroy, B., Babaeizadeh, S., 2017. Densely connected convolutional networks and signal quality analysis to detect atrial fibrillation using short single-lead ecg recordings, in: 2017 Computing in Cardiology (CinC), IEEE. pp. 1–4.
- [154] Rubin, J., Parvaneh, S., Rahman, A., Conroy, B., Babaeizadeh, S., 2018. Densely connected convolutional networks for detection of atrial fibrillation from short single-lead ecg recordings. *Journal of electrocardiology* 51, S18–S21.
- [155] Saadatnejad, S., Oveis, M., Hashemi, M., 2019. Lstm-based ecg classification for continuous monitoring on personal wearable devices. *IEEE journal of biomedical and health informatics*.
- [156] Santamaria-Granados, L., Munoz-Organero, M., Ramirez-

- Gonzalez, G., Abdulhay, E., Arunkumar, N., 2018. Using deep convolutional neural network for emotion detection on a physiological signals dataset (amigos). *IEEE Access* 7, 57–67.
- [157] Schl  pfer, J., Wellens, H.J., 2017. Computer-interpreted electrocardiograms: benefits and limitations. *Journal of the American College of Cardiology* 70, 1183–1192.
- [158] Schwab, P., Scebbba, G.C., Zhang, J., Delai, M., Karlen, W., 2017. Beat by beat: Classifying cardiac arrhythmias with recurrent neural networks, in: 2017 Computing in Cardiology (CinC), IEEE. pp. 1–4.
- [159] Sellami, A., Hwang, H., 2019. A robust deep convolutional neural network with batch-weighted loss for heartbeat classification. *Expert Systems with Applications* 122, 75–84.
- [160] Selvalingam, A., Alhusseini, M., Rogers, A.J., Krummen, D.E., Abuzaid, F.M., Zaman, J.A., Baykaner, T., Clopton, P.L., Bailis, P., Zaharia, M., et al., 2019. Developing convolutional neural networks for deep learning of ventricular action potentials to predict risk for ventricular arrhythmias. *Circulation* 140, A14675–A14675.
- [161] Shah, A.P., Rubin, S.A., 2007. Errors in the computerized electrocardiogram interpretation of cardiac rhythm. *Journal of electrocardiology* 40, 385–390.
- [162] Shaker, A.M., Tantawi, M., Shedeed, H.A., Tolba, M.F., 2020. Generalization of convolutional neural networks for ecg classification using generative adversarial networks. *IEEE Access* 8, 35592–35605.
- [163] Shashikumar, S.P., Shah, A.J., Clifford, G.D., Nemati, S., 2018. Detection of paroxysmal atrial fibrillation using attention-based bidirectional recurrent neural networks, in: Proceedings of the 24th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining, ACM. pp. 715–723.
- [164] Shen, Y., Voisin, M., Aliamiri, A., Avati, A., Hannun, A., Ng, A., 2019. Ambulatory atrial fibrillation monitoring using wearable photoplethysmography with deep learning, in: Proceedings of the 25th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining, ACM. pp. 1909–1916.
- [165] Shu, L., Xie, J., Yang, M., Li, Z., Li, Z., Liao, D., Xu, X., Yang, X., 2018. A review of emotion recognition using physiological signals. *Sensors* 18, 2074.
- [166] Smith, S.W., Walsh, B., Grauer, K., Wang, K., Rapin, J., Li, J., Fennell, W., Taboulet, P., 2019. A deep neural network learning algorithm outperforms a conventional algorithm for emergency department electrocardiogram interpretation. *Journal of electrocardiology* 52, 88–95.
- [167] Sodmann, P., Vollmer, M., Nath, N., Kaderali, L., 2018. A convolutional neural network for ecg annotation as the basis for classification of cardiac rhythms. *Physiological measurement* 39, 104005.
- [168] Strodthoff, N., Strodthoff, C., 2018. Detecting and interpreting myocardial infarction using fully convolutional neural networks. *Physiological measurement* .
- [169] Sun, W., Zeng, N., He, Y., 2019. Morphological arrhythmia automated diagnosis method using gray-level co-occurrence matrix enhanced convolutional neural network. *IEEE Access* .
- [170] Tadesse, G.A., Zhu, T., Liu, Y., Zhou, Y., Chen, J., Tian, M., Clifton, D., 2019. Cardiovascular disease diagnosis using cross-domain transfer learning, in: 2019 41st Annual International Conference of the IEEE Engineering in Medicine and Biology Society (EMBC), IEEE. pp. 4262–4265.
- [171] Tan, J.H., Hagiwara, Y., Pang, W., Lim, I., Oh, S.L., Adam, M., San Tan, R., Chen, M., Acharya, U.R., 2018. Application of stacked convolutional and long short-term memory network for accurate identification of cad ecg signals. *Computers in biology and medicine* 94, 19–26.
- [172] Tatenko, K., Glass, L., 2001. Automatic detection of atrial fibrillation using the coefficient of variation and density histograms of rr and δ rr intervals. *Medical and Biological Engineering and Computing* 39, 664–671.
- [173] Teijeiro, T., Garc  a, C.A., Castro, D., F  lix, P., 2018. Abductive reasoning as a basis to reproduce expert criteria in ecg atrial fibrillation identification. *Physiological measurement* 39, 084006.
- [174] Tison, G.H., Singh, A.C., Ohashi, D.A., Hsieh, J.T., Ballinger, B.M., Olgin, J.E., Marcus, G.M., Pletcher, M.J., 2017. Cardiovascular risk stratification using off-the-shelf wearables and a multi-task deep learning algorithm. *Circulation* 136, A21042–A21042.
- [175] Tison, G.H., Zhang, J., Dellinger, F.N., Deo, R.C., 2019. Automated and interpretable patient ecg profiles for disease detection, tracking, and discovery. *Circulation: Cardiovascular Quality and Outcomes* 12, e005289.
- [176] Urtnasan, E., Park, J.U., Lee, K.J., 2018. Multiclass classification of obstructive sleep apnea/hypopnea based on a convolutional neural network from a single-lead electrocardiogram. *Physiological measurement* 39, 065003.
- [177] Van Steenkiste, G., van Loon, G., Crevecoeur, G., 2020. Transfer learning in ecg classification from human to horse using a novel parallel neural network architecture. *Scientific Reports* 10, 1–12.
- [178] Vullings, R., 2019. Fetal electrocardiography and deep learning for prenatal detection of congenital heart disease, in: 2019 Computing in Cardiology (CinC), IEEE. pp. Page–1.
- [179] Wang, E.K., Zhang, X., Pan, L., 2019a. Automatic classification of cad ecg signals with sdac and bidirectional long short-term term network. *IEEE Access* .
- [180] Wang, J., Li, R., Li, R., Li, K., Zeng, H., Xie, G., Liu, L., 2019b. Adversarial de-noising of electrocardiogram. *Neurocomputing* 349, 212–224.
- [181] Wang, L., Zhou, W., Chang, Q., Chen, J., Zhou, X., 2019c. Deep ensemble detection of congestive heart failure using short-term rr intervals. *IEEE Access* .
- [182] Wang, P., Hou, B., Shao, S., Yan, R., 2019d. Ecg arrhythmias detection using auxiliary classifier generative adversarial network and residual network. *IEEE Access* 7, 100910–100922.
- [183] Wang, S., Aggarwal, C.C., Liu, H., 2017. Using a random forest to inspire a neural network and improving on it, in: Proceedings of the 2017 SIAM International Conference on Data Mining, Houston, Texas, USA, April 27–29, 2017., pp. 1–9. URL: <https://doi.org/10.1137/1.9781611974973.1>, doi:10.1137/1.9781611974973.1.
- [184] Wang, Y., Xiao, B., Bi, X., Li, W., Zhang, J., Ma, X., 2019e. Pay attention and watch temporal correlation: A novel 1-d convolutional neural network for ecg record classification, in: 2019 Computing in Cardiology (CinC), IEEE. pp. Page–1.
- [185] Wang, Y., Yao, Q., 2019. Few-shot learning: A survey. *CoRR* abs/1904.05046. URL: <http://arxiv.org/abs/1904.05046>, arXiv:1904.05046.
- [186] Warrick, P., Homs, M.N., 2017. Cardiac arrhythmia detection from ecg combining convolutional and long short-term memory networks, in: 2017 Computing in Cardiology (CinC), IEEE. pp. 1–4.
- [187] Warrick, P.A., Homs, M.N., 2018. Ensembling convolutional and long short-term memory networks for electrocardiogram arrhythmia detection. *Physiological measurement* 39, 114002.
- [188] Wei, Y., Qi, X., Wang, H., Liu, Z., Wang, G., Yan, X., 2019. A multi-class automatic sleep staging method based on long short-term memory network using single-lead electrocardiogram signals. *IEEE Access* 7, 85959–85970.
- [189] Wolf, A., et al., 2019. Early and remote detection of possible heart-beat problems with convolutional neural networks and multipart interactive training. *IEEE Access* .
- [190] Wu, Z., Feng, X., Yang, C., 2019. A deep learning method to detect atrial fibrillation based on continuous wavelet transform, in: 2019 41st Annual International Conference of the IEEE Engineering in Medicine and Biology Society (EMBC), IEEE. pp. 1908–1912.
- [191] Xia, Y., Wulan, N., Wang, K., Zhang, H., 2017. Atrial fibrillation detection using stationary wavelet transform and deep learning, in: 2017 Computing in Cardiology (CinC), IEEE. pp. 1–4.
- [192] Xia, Y., Wulan, N., Wang, K., Zhang, H., 2018a. Detecting atrial fibrillation by deep convolutional neural networks. *Computers in biology and medicine* 93, 84–92.
- [193] Xia, Y., Xie, Y., 2019. A novel wearable electrocardiogram classification system using convolutional neural networks and active learning. *IEEE Access* 7, 7989–8001.
- [194] Xia, Y., Zhang, H., Xu, L., Gao, Z., Zhang, H., Liu, H., Li, S., 2018b.

- An automatic cardiac arrhythmia classification system with wearable electrocardiogram. *IEEE Access* 6, 16529–16538.
- [195] Xiao, R., Xu, Y., Pelter, M.M., Fidler, R., Badilini, F., Mortara, D.W., Hu, X., 2018a. Monitoring significant st changes through deep learning. *Journal of electrocardiology* 51, S78.
- [196] Xiao, R., Xu, Y., Pelter, M.M., Mortara, D.W., Hu, X., 2018b. A deep learning approach to examine ischemic st changes in ambulatory ecg recordings. *AMIA Summits on Translational Science Proceedings* 2018, 256.
- [197] Xie, P., Wang, G., Zhang, C., Chen, M., Yang, H., Lv, T., Sang, Z., Zhang, P., 2018. Bidirectional recurrent neural network and convolutional neural network (bircnn) for ecg beat classification, in: 2018 40th Annual International Conference of the IEEE Engineering in Medicine and Biology Society (EMBC), IEEE. pp. 2555–2558.
- [198] Xie, Q., Tu, S., Wang, G., Lian, Y., Xu, L., 2019. Feature enrichment based convolutional neural network for heartbeat classification from electrocardiogram. *IEEE Access* 7, 153751–153760.
- [199] Xiong, P., Wang, H., Liu, M., Lin, F., Hou, Z., Liu, X., 2016. A stacked contractive denoising auto-encoder for ecg signal denoising. *Physiological measurement* 37, 2214.
- [200] Xiong, Z., Nash, M.P., Cheng, E., Fedorov, V.V., Stiles, M.K., Zhao, J., 2018. Ecg signal classification for the detection of cardiac arrhythmias using a convolutional recurrent neural network. *Physiological measurement* 39, 094006.
- [201] Xiong, Z., Stiles, M.K., Zhao, J., 2017. Robust ecg signal classification for detection of atrial fibrillation using a novel neural network, in: 2017 Computing in Cardiology (CinC), IEEE. pp. 1–4.
- [202] Xu, S., Li, J., Liu, K., Wu, L., 2019a. A parallel gru recurrent network model and its application to multi-channel time-varying signal classification. *IEEE Access* 7, 118739–118748.
- [203] Xu, S.S., Mak, M.W., Cheung, C.C., 2018a. Towards end-to-end ecg classification with raw signal extraction and deep neural networks. *IEEE journal of biomedical and health informatics*.
- [204] Xu, S.S., Mak, M.W., Cheung, C.C., 2019b. I-vector based patient adaptation of deep neural networks for automatic heartbeat classification. *IEEE journal of biomedical and health informatics*.
- [205] Xu, Y., Biswal, S., Deshpande, S.R., Maher, K.O., Sun, J., 2018b. Raim: Recurrent attentive and intensive model of multimodal patient monitoring data, in: Proceedings of the 24th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining, ACM. pp. 2565–2573.
- [206] Yang, T., Gregg, R.E., Babaeizadeh, S., 2020. Detection of strict left bundle branch block by neural network and a method to test detection consistency. *Physiological Measurement*.
- [207] Yang, T., Yu, L., Jin, Q., Wu, L., He, B., 2017. Localization of origins of premature ventricular contraction by means of convolutional neural network from 12-lead ecg. *IEEE Transactions on Biomedical Engineering* 65, 1662–1671.
- [208] Ye, F., Zhu, F., Fu, Y., Shen, B., 2019. Ecg generation with sequence generative adversarial nets optimized by policy gradient. *IEEE Access* 7, 159369–159378.
- [209] Yildirim, Ö., 2018. A novel wavelet sequence based on deep bidirectional lstm network model for ecg signal classification. *Computers in biology and medicine* 96, 189–202.
- [210] Yildirim, O., Baloglu, U.B., Tan, R.S., Ciaccio, E.J., Acharya, U.R., 2019. A new approach for arrhythmia classification using deep coded features and lstm networks. *Computer methods and programs in biomedicine* 176, 121–133.
- [211] Yildirim, Ö., Pławiak, P., Tan, R.S., Acharya, U.R., 2018. Arrhythmia detection using deep convolutional neural network with long duration ecg signals. *Computers in biology and medicine* 102, 411–420.
- [212] Yin, W., Yang, X., Zhang, L., Oki, E., 2016. Ecg monitoring system integrated with ir-uwb radar based on cnn. *IEEE Access* 4, 6344–6351.
- [213] Yin, Z., Zhao, M., Wang, Y., Yang, J., Zhang, J., 2017. Recognition of emotions using multimodal physiological signals and an ensemble deep learning model. *Computer methods and programs in biomedicine* 140, 93–110.
- [214] Yu, R., Gao, Y., Duan, X., Zhu, T., Wang, Z., Jiao, B., 2018. Qrs detection and measurement method of ecg paper based on convolutional neural networks, in: 2018 40th Annual International Conference of the IEEE Engineering in Medicine and Biology Society (EMBC), IEEE. pp. 4636–4639.
- [215] Yuen, B., Dong, X., Lu, T., 2019. Inter-patient cnn-lstm for qrs complex detection in noisy ecg signals. *IEEE Access* 7, 169359–169370.
- [216] Zhai, X., Tin, C., 2018. Automated ecg classification using dual heartbeat coupling based on convolutional neural network. *IEEE Access* 6, 27465–27472.
- [217] Zhang, B., Zhao, J., Chen, X., Wu, J., 2017a. Ecg data compression using a neural network model based on multi-objective optimization. *PLoS one* 12, e0182500.
- [218] Zhang, J., Lin, F., Xiong, P., Du, H., Zhang, H., Liu, M., Hou, Z., Liub, X., 2019a. Automated detection and localization of myocardial infarction with stacked sparse autoencoder and treebagger. *IEEE Access*.
- [219] Zhang, Q., Zhou, D., Zeng, X., 2017b. Heartid: A multiresolution convolutional neural network for ecg-based biometric human identification in smart health applications. *IEEE Access* 5, 11805–11816.
- [220] Zhang, X., Li, R., Dai, H., Liu, Y., Zhou, B., Wang, Z., 2019b. Localization of myocardial infarction with multi-lead bidirectional gated recurrent unit neural network. *IEEE Access* 7, 161152–161166.
- [221] Zhang, Y., Xiao, Z., Guo, Z., Wang, Z., 2019c. Ecg-based personal recognition using a convolutional neural network. *Pattern Recognition Letters* 125, 668–676.
- [222] Zhao, W., Hu, J., Jia, D., Wang, H., Li, Z., Yan, C., You, T., 2019a. Deep learning based patient-specific classification of arrhythmia on ecg signal, in: 2019 41st Annual International Conference of the IEEE Engineering in Medicine and Biology Society (EMBC), IEEE. pp. 1500–1503.
- [223] Zhao, Z., Liu, C., Li, Y., Li, Y., Wang, J., Lin, B.S., Li, J., 2019b. Noise rejection for wearable ecgs using modified frequency slice wavelet transform and convolutional neural networks. *IEEE Access* 7, 34060–34067.
- [224] Zhao, Z., Wang, X., Cai, Z., Li, J., Liu, C., 2019c. Pvc recognition for wearable ecgs using modified frequency slice wavelet transform and convolutional neural network, in: 2019 Computing in Cardiology (CinC), IEEE. pp. 1–4.
- [225] Zhao, Z., Zhang, Y., Deng, Y., Zhang, X., 2018. Ecg authentication system design incorporating a convolutional neural network and generalized s-transformation. *Computers in biology and medicine* 102, 168–179.
- [226] Zhong, W., Liao, L., Guo, X., Wang, G., 2018. A deep learning approach for fetal qrs complex detection. *Physiological measurement* 39, 045004.
- [227] Zhou, B., Liu, S., Hooi, B., Cheng, X., Ye, J., 2019a. Beatgan: anomalous rhythm detection using adversarially generated time series, in: Proceedings of the 28th International Joint Conference on Artificial Intelligence, AAAI Press. pp. 4433–4439.
- [228] Zhou, X., Zhu, X., Nakamura, K., Mahito, N., 2018. Premature ventricular contraction detection from ambulatory ecg using recurrent neural networks, in: 2018 40th Annual International Conference of the IEEE Engineering in Medicine and Biology Society (EMBC), IEEE. pp. 2551–2554.
- [229] Zhou, Y., Hong, S., Shang, J., Wu, M., Wang, Q., Li, H., Xie, J., 2019b. K-margin-based residual-convolution-recurrent neural network for atrial fibrillation detection. *IJCAI*, 6057–6063.
- [230] Zhu, F., Ye, F., Fu, Y., Liu, Q., Shen, B., 2019. Electrocardiogram generation with a bidirectional lstm-cnn generative adversarial network. *Scientific reports* 9, 6734.
- [231] Zihlmann, M., Perekrestenko, D., Tschannen, M., 2017. Convolutional recurrent neural networks for electrocardiogram classification, in: 2017 Computing in Cardiology (CinC), IEEE. pp. 1–4.