
BLAZOR





Contents





How we develop web applications today?

For server-side development, we use programming languages like C#, Java, PHP etc.

For the client-side development we use JavaScript frameworks like Angular, React, Vue etc.

To stay in the business as a developer and remain competitive, it's inevitable we learn both a server-side programming language and a client-side programming language.

But the question is, why should we learn and use 2 different sets of programming languages and frameworks.







Blazor

Blazor is one of the frameworks for the .Net family for web development.

With Blazor we can now build interactive web UIs using C# instead of JavaScript

C# code can be executed both on the server and in the client browser.






How can a browser execute C# code?

Blazor can run C# code directly in the browser, using WebAssembly.


WebAssembly is based on open web standards. So it is a native part of all modern browsers including mobile browsers.





How Create a Blazor App?


The IDE Used for creating Blazor App is Visual Studio.





Blazor Hosting Models

Blazor offers 2 hosting models:









Blazor WebAssembly

Application runs directly in the browser on WebAssembly.

Everything the application needs i.e the compiled application code itself, it's dependencies and the .NET runtime are downloaded to the browser

A Blazor WebAssembly app can run entirely on the client without a connection to the server





Advantages and disadvantages



- Active server connection is not required.
- ☐ Client Resources and Capablities is used.
- Full blown asp.net core web server is not required.
- ☐ Can be hosted on our own webserver, cloud azure or CDN



- The very First request usually takes longer.
- Restricted to the capablities of the browser.
- Capable client hadwae and software is required




Server side hosting Model

Application is executed on the server.

Between the client and the server a SignalR connection is established.

When an event occurs on the client such as a button click for example, the information about the event is sent to the server over the SignalR connection. The server handles the event and for the generated HTML a diff (difference) is calculated. The entire HTML is not sent again to the client, it's only the diff that is sent to the client over the SignalR connection. The browser then updates the UI. Since only the diff is applied to update the UI, the application feels faster and more responsive to the user.





Advantages and disadvantages



- Application loads much faster.
- ☐ can take full advantages of server capablities.
- ☐ All the client needs, to use the app is browser.
- ☐ More secure as the app code is not sent to the client



- Asp.Net core web server is required.
- An active connection t the server is required.
- ☐ Higher latency due to the round trip to the server.
- ☐ Scalablity can be challenge



Blazor project structure

Program.cs:contains the Main() method which is the entry point for both the project types

wwwroot:For both the project types, this folder contains the static files like images, stylesheets etc.

App.razor:This is the root component of the application. It uses the built-in Router component and sets up client-side routing.





Pages folder: This folder contains the _Host razor page and the routable components that make up the Blazor app. The components have the .razor extension.

Shared folder: As the name implies, contains the shared components (MainLayout componen (MainLayout.razor), NavMenu component (NavMenu.razor))

_Imports.razor:contains the common namespaces so we do not have to include them in every razor component.





wwwroot/index.html:This is the root page in a Blazor WebAssembly project and is implemented as an html page.

Startup.cs:it contains the applications's startup logic.
ConfigureServices - Configures the applications DI i.e dependency injection services.
Configure - Configures the app's request processing pipeline.

Pages/_Host.cshtml:This is the root page of the application and is specified by calling MapFallbackToPage("/_Host") method. It is implemented as a razor page.





Data folder (Blazor Server):Contains code files related to the sample WeatherForecast service

appsettings.json (Blazor Server):uses this file to store the Configuration settings.





ASP.NET Core razor components

Components are the fundamental building blocks of a Blazor application.

They can be nested, reused, and if implemented properly, can even be shared across multiple projects.

Component files have the extension .razor

Component names cannot start with a lowercase character





Razor component example

```
Project Build
                                      Debug
                                             Test Analyze
                                                           Tools Extensions Window

Search 

▼

                                                                                                         HireMeNow-BlazorApp
                                  Debug - Any CPU
JobListComponent.razor* → X ListJob.razor
                                                                                   NavMenu.razor
                                                                                                    ProviderListComponent1.razor
                                                       Sheduledinter...mponent.razor
            wcayour Jobcomponentrayour
           @inject IJobService Jobservices
           <h2 align="center" color="#3487bf">All Jobs</h2>
            @*Listing Jobs*@
         @foreach(var jobs in Joblist)
                             <ListJob job="@jobs"></ListJob>
    11
            </div>
    16
          □@code {
    17
               List<Job> Joblist;
               protected override void OnInitialized()
    18
                    Joblist = Jobservices.GetJobs();
                                  Anuvind, 20 days ago | 1 author, 1 change | 4
```



Componet is combination of two things:



HTML markup which defines the user interface of the component i.e the look and feel.



C# code which defines the processing logic

Component is rendered by giving path in the @page directive

