Kingston DDR3/3L DRAM for embedded applications

Kingston on-board DRAM is designed to meet the needs of embedded applications and offers a low-voltage option for lower power consumption.

DDR3/3L Part Numbers and Specifications

30nm DDR3/3L Part Number	Capacity	Description	Package Size	Configuration (words x bits)	Speed	VDD, VDDQ	Operating Temperature
D1216ECMDXGJD	2Gb	96 ball FBGA DDR3/3L I-Temp	7.5x13.5x1.2	128Mx16	1866 Mbps	1.35V	0°C ~ +95°C
D2568ECMDPGJD	2Gb	78 ball FBGA DDR3/3L I-Temp	7.5x13.5x1.2	256Mx8	1866 Mbps	1.35V	0°C ~ +95°C
D2516ECMDXGJD	4Gb	96 ball FBGA DDR3L	7.5x13.5x1.2	256Mx16	1866 Mbps	1.35V*	0°C ~ +95°C
D5128ECMDPGJD	4Gb	78 ball FBGA DDR3L	7.5x10.6x1.2	512Mx8	1866 Mbps	1.35V*	0°C ~ +95°C
D2516ECMDXGME	4Gb	96 ball FBGA DDR3L	7.5x13.5x1.2	256Mx16	2133 Mbps	1.35V*	0°C ~ +95°C

^{*}Backward compatible to 1.5V VDD, VDDQ

Key Features

- Double-data-rate architecture: two data transfers per clock cycle
- The high-speed data transfer is realized by the 8 bits prefetch pipelined architecture
- Bi-directional differential data strobe (DOS and /DQS) is transmitted/received with data for capturing data at the receiver
- DOS is edge-aligned with data for READS; center-aligned with data for WRITES
- Differential clock inputs (CK and /CK)
- DLL aligns DQ and DOS transitions with CK transitions
- Commands entered on each positive CK edge; data and data mask referenced to both edges of DQS
- · Data mask (DM) for write data
- Posted /CAS by programmable additive latency for better command and data bus efficiency
- · On-Die Termination (ODD for better signal quality
 - Synchronous ODT
 - Dynamic CDT
 - Asynchronous ODT
- Multi Purpose Register (MPR) for pre-defined pattern read out
- · ZQ calibration for DO drive and ODT
- Programmable Partial Array Self-Refresh (PASR)
- RESET pin for Power-up sequence and reset function
- SRT range: Normal/extended
- · Programmable Output driver impedance control

Kingston DDR3/3L





