REVISIONS					
DISPOSITION= 1.REWORK 2.SCRAP 3.USE AS IS 4.RECORD CHANGE					
REV	DESCRIPTION	ECN NO	DISP.	DATE	APVD

ROTARY FEEDBACK HOUSING

SHIELD
GREEN
WHITE
BROWN

SH G W B — SH R W B

BLACK No.1
WHITE No.1
BLACK No.2

ACTUATOR JUNCTION BOX

STEP MOTOR

HEATER/
THERMOSTAT

ON: 60°F
OFF: 80°F

MOTOR
THERMOSTAT

SPARE SPARE SPARE GRN/YEL BROWN BROWN RED/BLK RED GRN/BLK GREEN YELLOW YELLOW

RED/BLK RED GRN/BLK GREEN YELLOW YELLOW

電氣室

CONTROL SIGNAL
INPUT
4-20 mA DC

ANALOG OUTPUT

現場遠端控制箱

Open
Close
Remote
Auto

ANALOG INPUT

4-20 mA
POSITION FEEDBACK

250 Ω typ.

RED
WHITE
BLACK
SHIELD

1 4-20mA Surge Suppressor 3
2 4

MOTOR DRIVER

DIGITAL I/O

CPU BOARD

TB1
+15V
FB1+
FB1-
FB2+
FB2-
CS+
CS-
+15V
ACC+
ACC-
SLC+
SLC-

CONTACT IN/
RELAY OUT BOARD

TB3, MAIN CONTACTS
OPEN PWROUT CLOSE CLOSE PWRRTN OPEN

TB1, AUX CONTACTS
OPEN PWROUT CLOSE CLOSE PWRRTN OPEN

LED "ON" when Open Signal is present O = Open Input D12
LED "ON" when Close Signal is present C = Close Input D13
LED "ON" when Manual Signal is present M = Manual Input D10

TB6, REMOTE AUTO/MAN
OPEN PWROUT CLOSE CLOSE PWRRTN OPEN PWROUT MAN MAN PWRRTN

TB5
RELAY 1 RELAY 2

TB4
LOOP INT. RTN LOOP EXT. RTN LOOP OUT

上下限定位
DIGITAL INPUT x 2

MOTOR POWER

AC POWER DISTRIBUTION

F2[+24V 1/4 AMP]
F1[TRIPLE 1/4 AMP]
F7[HEATER 2.0 AMP]
F5[FAIL SOLENOID 2.0 AMP]
F3[CONTACT 1.0 AMP]
F4[TRIP SOLENOID 5.0 AMP]

TB4
Grn/Yel Brown Brown Blue Blue N/C N/C Shield Green Grn/Blk Red Red/Blk
Gnd Heater Solenoid Hi-Speed Solenoid Stepper Motor

SHIELD

Control
Enclosure

TRANSIENT
SURPPRESSOR

EMI/RFI
SURPPRESSOR

PE
N
L

FUSE
Europe:
B-Pump 6 Amp,
TYPE aM,
10X38mm

North America:
B-Pump 5 Amp,
Class CC,
13/32" x 1 1/2"

YELLOW/GRN
YELLOW

MAIN POWER INPUT(5)
120 VAC 50/60 Hz
B-Pump 4.0 Amps MAX.
(500 VA source required)

AC POWER WIRING
PROVIDED BY END-USER

AC110V POWER

UNLESS OTHERWISE SPECIFIED									
TEMPLATE NO.	REVISION	DATE	DIMENSIONS ARE IN INCHES				CONTRACT No.		品洲科技貿易有限公司
REXA_B_H_CERT	A	020402	X ±1.00	XX ±.50	XXX ±.25	ANGLES ±2°	98CIU2212		
1) BREAK ALL SHARP EDGES .015 2) O-RING GROOVES 63 FINISH OR BETTER 3) INSIDE CORNER RADII TO BE .030 MAX			MATERIAL N/A				PREP DDP	1/25/10	三階煉焦廠 PECS大風車風扇 速度控制電油壓驅動器接線圖
THIS DRAWING AND ALL INFORMATION HEREIN IS THE PROPERTY OF REXA CORPORATION. IT IS CONFIDENTIAL AND MUST NOT BE MADE PUBLIC OR COPIED AND IS SUBJECT TO RETURN UPON DEMAND.			FINISH NONE				CHKR		
							APVD		
							APVD		
							MACHINE SURFACE N/A	RAW STOCK N/A	SIZE B / NUMBER P9901F02 / REV 0
									SCALE NONE / SHEET 1 OF 1