

Department of Computer Science

Umaer Basha Institute of Information Technology (UBIT)

APPLICATION DEVELOPMENT PROJECT DOCUMENTATION

AI Life Saver

AI-Powered First Aid and Emergency Guidance Platform

AI LifeSaver for Edge-Accelerated Pre-Hospital Emergency Guidance

Submitted by:

Hania Shafiq | Seat Number: B22110006050

Laiba Anzalna | Seat Number: B22110006070

Uniba Muzammil | Seat Number: B22110006172

Submitted to :

Sir Zaeem Tariq

Brief

Pre-hospital emergency mortality across Pakistan's metropolitan centers is driven by an acute intervention vacuum during the first ten minutes following traumatic injury or cardiac collapse². Clinical data from Karachi reveals that over fifty-eight percent of fatal trauma victims succumb to their injuries prior to reaching hospital facilities, while out-of-hospital cardiac arrest survival remains under two percent³. Although more than ninety percent of these catastrophic incidents are witnessed by family members or bystanders, bystander cardiopulmonary resuscitation is initiated in only 2.3 percent of cases³. Untrained individuals are frequently paralyzed by panic or perform contraindicated actions—such as administering liquids to comatose patients, applying harmful domestic substances to acute thermal burns, or forcibly moving unstable cervical spines—that directly accelerate fatal complications².

AI LifeSaver resolves this pre-hospital crisis by converting consumer mobile and desktop browsers into deterministic, bilingual emergency triage terminals without requiring native application installation¹. The platform combines high-throughput, edge-orchestrated Large Language Model inference via Groq-hosted LLaMA 3.3 70B and Google Gemini engines with a verified relational first-aid repository managed on Supabase PostgreSQL¹. Operating under a strict Retrieval-Augmented Generation paradigm, the system eliminates medical hallucinations and delivers bilingual (English and Urdu) step-by-step guidance, audio narration, and one-touch integration with emergency dispatch services¹.

To ensure real-world viability across bandwidth-constrained environments, the platform implements a hybrid failover pipeline¹. High-speed conversational triage is processed through Supabase Edge Functions at sub-second latencies, while static procedural records, Web Speech synthesis pipelines, and client-side vector search run entirely locally when connectivity is lost¹. By pairing algorithmic safety guardrails with immediate one-touch dispatch links to services like Sindh Integrated Emergency & Health Services (SIEHS) Rescue 1122 and the Edhi Foundation, AI LifeSaver bridges the life-critical gap between symptom onset and professional medical response¹.

Table of Contents

1. **Chapter 1: Project Overview**
2. **Chapter 2: Problem Statement**
3. **Chapter 3: Project Objectives**
4. **Chapter 4: Proposed Solution**
5. **Chapter 5: Scope of the Project**
 - . 5.1 In-Scope Features
 - . 5.2 Out-of-Scope for the Initial MVP
6. **Chapter 6: Functional Requirements**
 - . 6.1 Authentication and Guest State Session Management
 - . 6.2 Bilingual Localization Engine (English / Urdu RTL)
 - . 6.3 Multimodal Emergency Search and Keyword Indexing
 - . 6.4 Real-Time Conversational AI First Aid Assistant
 - . 6.5 Step-by-Step Audio Narration and Hands-Free Protocol Guidance
 - . 6.6 Geolocation Directory and One-Touch Emergency SOS Telephony
 - . 6.7 Offline Resilience and Portable Document Export
7. **Chapter 7: User Roles**
8. **Chapter 8: Technology Stack**
9. **Chapter 9: Frontend Design**
 - . 9.1 Main Pages
 - . 9.2 Suggested Component Structure
10. **Chapter 10: Backend Design**
 - . 10.1 Supabase Relational Database Schema and Indexing
 - . 10.2 Serverless Edge Functions and AI Orchestration
11. **Chapter 11: Core Business Logic**
 - . 11.1 AI Medical Prompt Guardrails and Safety Rules
 - . 11.2 Emergency Risk Triage Classification Algorithm
12. **Chapter 12: User Workflow**
13. **Chapter 13: Public Health Impact, Community Deployment, and Liability Governance**
14. **Chapter 14: Non-Functional Requirements**
15. **Chapter 15: Expected Outcomes and Empirical Evaluation**
16. **Chapter 16: Technical Horizons and Expansion**
17. **Appendix A: Condition Data Schema and LLM System Prompt Protocol**
 - . A.1 Relational Condition and Procedural Seed Specification
 - . A.2 Edge Function System Prompt and Guardrail Configuration

Chapter 1: Project Overview

Al LifeSaver is an edge-accelerated, bilingual emergency first-aid assistance platform engineered to stabilize victims of acute trauma and life-threatening medical events during the pre-hospital interval¹. Within the emergency medicine timeline, the period immediately following an incident—frequently termed the "golden window"—determines long-term morbidity and mortality¹. When professional Emergency Medical Services (EMS) experience protracted transit times due to urban traffic density or decentralized dispatch infrastructure, on-scene bystanders represent the only operational resource capable of sustaining life². The platform addresses this critical window through an accessible web architecture that requires no account registration, financial subscription, or app-store installation¹. Developed within the Department of Computer Science at the University of Karachi, Al LifeSaver provides culturally grounded, linguistically localized medical instructions in English and Urdu¹. By combining sub-second artificial intelligence inference with deterministic local clinical datasets, the platform guides laypersons through complex emergency protocols—such as chest compressions, severe hemorrhage packing, foreign body airway clearance, and burn cooling—while maintaining a continuous bridge to physical emergency dispatch¹.

Chapter 2: Problem Statement

The pre-hospital emergency care infrastructure across developing nations, and specifically throughout urban Pakistan, suffers from systemic delays that contribute directly to elevated casualty rates³. Epidemiological analyses demonstrate that the baseline survivability for critical medical emergencies in Pakistan remains significantly below international clinical standards³.

Clinical and Operational Metric	Pakistan Urban Benchmark (Karachi)	International Standard Baseline	Source / Evidence Reference
Bystander CPR Initiation Rate	2.3% of witnessed cardiac events	40.0% – 55.0% in established EMS registries	BMC Emergency Medicine (Khan et al.) ³
Pre-Hospital Trauma Mortality	58.0% of violent trauma deaths occur pre-ED	< 20.0% under integrated trauma networks	Journal of Pakistan Medical Assoc. ⁴
Dead on Arrival (DOA) Burden	1.0 to 2.0 per 1,000 emergency admissions	< 0.2 per 1,000 emergency admissions	Resuscitation Outcomes Consortium ³

Median Trauma Transit Latency	30.0 minutes (IQR: 20 to 40 minutes)	< 8.0 minutes to advanced life support	PMC Emergency Trauma Cohort ⁷
Predominant Transit Methodology	80.2% basic transport without life support	> 90.0% Advanced Life Support (ALS) units	Aga Khan University Emergency Medicine ⁶

The clinical consequences of these delays are compounded by three interconnected failures in the field:

- **The Interventional Vacuum:** Acute arterial lacerations cause lethal exsanguination within three to five minutes, and global cerebral ischemia causes irreversible cortical necrosis within four to six minutes². When ambulance transit times extend beyond twenty minutes, bystander inaction guarantees biological death prior to EMS arrival³.
- **Layperson Panic and Decision Paralysis:** Untrained bystanders at accident scenes experience acute panic, leading to decision paralysis. Relatives frequently watch casualties deteriorate without attempting basic airway clearance or circulatory support².
- **Harmful Contraindicated Interventions:** Untrained individuals routinely perform dangerous layman practices². These include administering oral water or milk to unconscious patients (inducing pulmonary aspiration), forcibly moving polytrauma casualties without cervical stabilization (causing permanent spinal cord severance), applying toothpaste, grease, or raw flour to severe thermal burns (exacerbating tissue necrosis and sepsis), and utilizing uncalibrated wire tourniquets (causing ischemic limb loss)².
- **Linguistic and Interface Barriers:** Most emergency medical applications rely entirely on complex, English-language terminology with dense text hierarchies, rendering them unusable for the broader Urdu-speaking public during high-stress scenarios¹.

Chapter 3: Project Objectives

The engineering design of AI LifeSaver balances distributed systems performance with strict clinical determinism¹:

- **Sub-Second Generative Inference:** Implement an artificial intelligence inference pipeline capable of a Time-to-First-Token (TTFT) under 1,200 milliseconds by orchestrating Groq-hosted LLaMA 3.3 70B models through edge-deployed serverless proxies¹.
- **Zero-Hallucination Retrieval Architecture:** Bind generative language models to verified, relational clinical records stored in Supabase PostgreSQL, ensuring the complete elimination of synthetic medical claims or unverified pharmaceutical advice¹.
- **Full Bilingual Parity:** Deliver complete bidirectional localization (English and Urdu) featuring dynamic Right-to-Left (RTL) document re-orientation, culturally attuned medical vocabulary, and phonetic matching for Roman Urdu search queries¹.
- **Hands-Free Auditory Pipeline:** Provide multimodal speech input via the Web Speech

API and synchronized text-to-speech auditory loops, allowing responders to receive real-time spoken guidance without looking away from the patient¹.

- **Deterministic Offline Operability:** Maintain complete core emergency search and step-by-step guidance capabilities during complete cellular or broadband outages via client-side caching and dynamic client-rendered PDF guides¹.
- **Emergency Telephony Integration:** Provide immediate, one-touch telephony bridging to localized emergency infrastructure, including SIEHS Rescue 1122 and Edhi 115, alongside geospatial emergency facility mapping via OpenStreetMap¹.

Chapter 4: Proposed Solution

AI LifeSaver functions as a client-side Single Page Application (SPA) linked to an edge-compute layer and a relational database¹. Instead of relying on monolithic servers, the platform uses an edge-first, decoupled architecture¹.

Operational Pipeline Stage	User Action or System Trigger	Underlying Technical Mechanism	Output State to User
1. Emergency Ingress	User accesses web URL via browser; inputs search via speech or text ¹ .	Vite 7 single-page bundle hydrates locally; Web Speech API captures audio buffers ¹ .	Immediate interactive view; low-contrast visual elements suppressed ¹ .
2. Triage & Retrieval	Input parsed for clinical entities, symptoms, or injury types ¹ .	Trigram index (pg_trgm) queries PostgreSQL condition catalog directly ¹ .	Instant display of categorized condition cards with risk badges ¹ .
3. Conversational AI	Complex, multi-symptom, or ambiguous emergency prompt submitted ¹ .	Edge Function enriches query with matched protocols; executes Groq LPU inference ¹ .	Real-time Server-Sent Events (SSE) token stream rendering conversational advice ¹ .
4. Guided Stabilization	Bystander selects specific condition protocol card ¹ .	Client loads step-by-step procedural array; activates Web Speech Synthesis loop ¹ .	Visual action steps rendered alongside sequential voice guidance ¹ .

5. Physical Escalation	Bystander clicks SOS dialer or inspects nearby trauma facilities ¹ .	Native tel: URI invokes OS dialer; Leaflet maps spatial coordinates via OpenStreetMap ¹ .	Direct voice call to 1122 initiated; interactive hospital map displayed ¹ .
6. Disconnected State	Mobile connection drops due to infrastructure outage ¹ .	Service logic falls back to bundled firstAid.json; jsPDF renders offline documents ¹ .	Uninterrupted first-aid execution; offline indicator surfaced ¹ .

Chapter 5: Scope of the Project

5.1 In-Scope Features

The implemented architecture of AI LifeSaver delivers the following concrete technical deliverables:

- **Voice-Driven Symptom Search:** Speech recognition interface capable of parsing English and Roman Urdu spoken queries into standardized search tokens¹.
- **Conversational First-Aid Assistant:** Serverless edge-proxied AI engine powered by Groq LLaMA 3.3 with automated fallback to Google Gemini 1.5 Flash¹.
- **Visual Triage Cards:** Standardized emergency action cards featuring danger callouts, numbered execution steps, and explicit contraindication warnings¹.
- **Auditory Step Playback:** Integrated browser speech synthesis engine that vocally reads emergency instructions sequentially in English and Urdu¹.
- **Full Bilingual Interface:** Dynamic global state toggle managing complete typography, button labels, RTL orientation, and localized condition records¹.
- **Emergency Dispatch Hotlines:** One-touch direct dialing anchors for primary Pakistani emergency networks, specifically SIEHS Rescue 1122, Edhi 115, and Chhipa¹.
- **Interactive Facility Map:** Leaflet and OpenStreetMap integration rendering geographical locations, routes, and contact numbers for nearby hospitals and blood banks¹.
- **Offline PDF Generator:** Client-side document generation engine using jsPDF that converts procedural data into printable emergency reference sheets¹.

5.2 Out-of-Scope for the Initial MVP

To maintain clinical safety and software reliability, the following systems are strictly excluded from this release:

- **Municipal CAD Direct Integration:** Automated insertion of incident tickets into public ambulance computer-aided dispatch networks¹.
- **Computer-Vision Diagnostics:** Automated classification of wound depths, fracture angulation, or burn percentages using device camera streams¹.
- **Biometric Signal Telemetry:** Real-time pairing with consumer smartwatches to read photoplethysmography or electrocardiogram streams¹.
- **Invasive Medical Procedures:** Instructions detailing intravenous cannulation, surgical cricothyroidotomy, needle thoracostomy, or prescription pharmacology¹.
- **Authenticated User Profiling:** Mandatory login walls, personal medical record storage, or cloud tracking of sensitive personal health records¹.

Chapter 6: Functional Requirements

6.1 Authentication and Guest State Session Management

In life-critical emergency contexts, identity verification requirements introduce unacceptable latency:

- **Zero-Friction Access:** The application must grant unauthenticated guest access to all search systems, emergency procedure guides, conversational assistants, and emergency contact directories¹.
- **Stateless Client Persistence:** User interface preferences—including language selection, speech synthesis velocity, and volume thresholds—must be persisted exclusively in browser localStorage without generating server-side user tracking records¹.

6.2 Bilingual Localization Engine (English / Urdu RTL)

The platform must provide linguistic parity between English and Urdu across all presentation surfaces:

- **Directional Document Transformation:** When switching between English and Urdu, the system must dynamically reconfigure the root HTML Document Object Model attributes (dir="rtl" or dir="ltr" and lang="ur" or lang="en") to adjust text alignment, margins, and flex-direction vectors¹.
- **Synchronized Translation Catalog:** All interface controls, navigation links, error messages, and dynamic state descriptions must be driven by a structured translation catalog (texts.json)¹.
- **Parallel Medical Datasets:** Relational condition tables must store dual-language string attributes for clinical names, summaries, step instructions, and danger warnings¹.

6.3 Multimodal Emergency Search and Keyword Indexing

The retrieval system must resolve ambiguous or noisy user inputs into standardized clinical protocols:

- **Phonetic and Trigram String Matching:** The search layer must match user queries against condition titles, medical terms, and vernacular synonyms using PostgreSQL Generalized Index Search (gin_trgm_ops)¹.
- **Web Speech Audio Capture:** The interface must capture spoken queries via the browser's native SpeechRecognition API, parse the resulting audio buffers into text, and execute searches without manual keyboard input¹.
- **Visual Urgency Badging:** Retrieved search results must immediately display color-coded risk indicators reflecting their medical severity¹.

6.4 Real-Time Conversational AI First Aid Assistant

The conversational subsystem must handle complex natural language queries that fall outside exact keyword matches:

- **Edge Proxy Intermediation:** Client chat requests must route through a secure Supabase Edge Function to prevent public exposure of inference API keys¹.

- **Contextual Grounding (RAG):** The Edge Function must search the internal database for relevant condition records and inject these verified steps directly into the model's system prompt¹.
- **Token Streaming:** The assistant must stream responses incrementally to the client using Server-Sent Events, ensuring users receive actionable instructions without waiting for the full response to generate¹.

6.5 Step-by-Step Audio Narration and Hands-Free Protocol Guidance

The audio subsystem must deliver hands-free auditory instructions while a bystander treats a patient:

- **Synthesized Voice Generation:** The system must use the W3C Web Speech Synthesis API to read the currently selected procedural step aloud¹.
- **Linguistic Voice Resolution:** The audio engine must detect the active language state and bind to localized voice packages (en-US for English, ur-PK for Urdu) supported by the client operating system¹.
- **Sequential Playback Controls:** The user interface must provide large, high-contrast controls to play, pause, repeat, or step through instructions sequentially¹.

6.6 Geolocation Directory and One-Touch Emergency SOS Telephony

The platform must connect digital first-aid guidance with physical pre-hospital infrastructure:

- **One-Touch Telephony Anchors:** The interface must provide prominent SOS buttons that use native tel: URIs to open the device dialer with regional emergency numbers (Rescue 1122, Edhi 115) pre-loaded¹.
- **Spatial Facility Visualization:** The system must render an interactive Leaflet map marking public trauma centers, specialized burn units, and blood banks using OpenStreetMap tile servers¹.
- **Fallback Directory Tables:** If geospatial mapping APIs fail to load, the system must display a pre-compiled, static contact directory of major hospitals and ambulance dispatch centers¹.

6.7 Offline Resilience and Portable Document Export

The application must remain functional during complete broadband or cellular network disruptions:

- **Static Dataset Failover:** If network requests to Supabase fail, the client data layer must automatically fall back to an internal JSON dataset (firstAid.json) containing core emergency procedures¹.
- **Client-Side Document Compilation:** The application must compile and download formatted, printable emergency guides locally using jsPDF without requiring server-side rendering¹.

Chapter 7: User Roles

AI LifeSaver enforces a role-based access model using Supabase Row Level Security (RLS) to protect clinical data while maintaining friction-free emergency access¹.

Platform Role Identifier	Authentication Method	Clinical Access Privileges	Administrative Authority
Unauthenticated Bystander	Public Anon Key (anon-key) ¹	Unrestricted read access to all condition records, procedures, mapping coordinates, and the streaming AI assistant ¹ .	Strictly none; cannot modify, append, or delete any remote data records ¹ .
Community Responder / Student	Public Anon Key (anon-key) ¹	Unrestricted read access; local offline data caching; client-side PDF guide generation ¹ .	Strictly none; purely consumer-tier execution ¹ .
Clinical Content Administrator	Supabase Auth (JWT with admin role) ¹	Full read, write, update, and delete access across all condition schemas, steps, synonyms, and emergency directories ¹ .	Complete schema administration, API key rotation, edge function deployment, and system prompt modification ¹ .

Chapter 8: Technology Stack

The software stack for AI LifeSaver was selected to achieve high edge throughput, minimal bundle overhead, and zero-latency local execution¹.

Technology Layer	Selected Tool / Framework	Alternatives Evaluated	Engineering Justification
Client Application	React 19 + Vite 7 ¹	Next.js 14 / Nuxt.js	Eliminates server-side rendering overhead; compiles into a

			lightweight static SPA that executes client-side during outages ¹ .
Styling & Layout	Tailwind CSS v4 ¹	Bootstrap 5 / Vanilla CSS	High-performance atomic utility classes, minimal production CSS bundle footprints, and native support for RTL variants ¹ .
Animation Engine	Framer Motion ¹	CSS Keyframes	Provides fluid, hardware-accelerated transitions between triage steps without blocking the JavaScript main thread ¹ .
Data Layer & Search	Supabase PostgreSQL 15 ¹	MongoDB Atlas / Firebase	Native relational integrity, built-in Row Level Security, and high-speed trigram text indexing via the pg_trgm extension ¹ .
Serverless Compute	Supabase Edge Functions (Deno) ¹	AWS Lambda / Cloudflare	Globally distributed Deno runtime providing low-latency API proxying and streaming responses with minimal cold-start times ¹ .
Primary AI Engine	Groq LPU API (LLaMA 3.3 70B) ¹	OpenAI GPT-4o / Claude 3.5	Groq's specialized inference hardware achieves sub-second token generation, essential for high-stress emergency guidance ¹ .
Secondary AI	Google Gemini 1.5	Anthropic Claude 3	Serves as an

Engine	Flash ¹	Haiku	automated fallback engine, offering high throughput and stable failover if primary API rate limits occur ¹ .
Geospatial Mapping	Leaflet + OpenStreetMap ¹	Google Maps JavaScript API	Open-source foundation requires no proprietary API keys, has a smaller bundle size, and operates under permissive terms ¹ .
Audio I/O Processing	W3C Web Speech API ¹	AWS Polly / Whisper API	Executes natively within the browser, eliminating external network latency and third-party processing costs ¹ .
Document Export	jsPDF ¹	Puppeteer / Server PDF	Generates printable vector PDF documents directly in the client browser without needing external backend rendering ¹ .

Chapter 9: Frontend Design

9.1 Main Pages

The frontend interface is organized into focused, single-purpose views to minimize cognitive load during crises¹:

- **Home and Emergency Hub (Home.jsx):** Serves as the primary emergency entry point. Features a prominent search bar, one-touch voice recognition triggers, and immediate-action buttons for common critical emergencies: Cardiopulmonary Arrest, Severe Hemorrhage, Thermal Burns, and Choking¹.
- **Procedural Emergency Viewer (Emergency.jsx):** The primary step-by-step guidance interface. Renders numbered procedure cards, visual risk indicators, contraindication warnings, and audio playback controls¹.
- **Emergency Services and Facility Map (Contacts.jsx):** Houses the interactive Leaflet map alongside a localized directory of emergency services, trauma centers, and blood banks¹.
- **Clinical Protocol and Governance Documentation (About.jsx):** Outlines the project's educational mission, institutional acknowledgments, software versioning, and clinical disclaimers¹.

9.2 Suggested Component Structure

The user interface is built from modular, highly decoupled components designed for clear visibility and rapid interaction¹:

- **AiChat.jsx:** A floating conversational component that manages message histories, handles streaming responses from edge functions, and processes speech inputs¹.
- **ResultCard.jsx:** A card component that displays emergency procedures with visual risk badges, brief summaries, and direct links to step-by-step guides¹.
- **LanguageToggle.jsx:** A persistent interface control that switches the application between English and Urdu, toggling document directionality (dir="rtl") and updating global language state¹.
- **Navbar.jsx & Footer.jsx:** Persistent interface frames providing quick navigation, language controls, and direct telephone links to SIEHS 1122 and the Edhi Foundation¹.

Chapter 10: Backend Design

10.1 Supabase Relational Database Schema and Indexing

The backend data layer uses a normalized relational schema in PostgreSQL 15, optimized for rapid text retrieval and multilingual support¹.

SQL

```
-- Enable trigram extension for fuzzy text matching
CREATE EXTENSION IF NOT EXISTS "pg_trgm";

-- Core emergency conditions table
CREATE TABLE public.conditions (
  id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
  slug VARCHAR(64) UNIQUE NOT NULL,
  title_en VARCHAR(128) NOT NULL,
  title_ur VARCHAR(128) NOT NULL,
  risk_level VARCHAR(32) NOT NULL CHECK (risk_level IN ('High', 'Medium to High', 'Low to Medium')),
  summary_en TEXT NOT NULL,
  summary_ur TEXT NOT NULL,
  contraindications_en TEXT[] DEFAULT '{}',
  contraindications_ur TEXT[] DEFAULT '{}',
  created_at TIMESTAMP WITH TIME ZONE DEFAULT timezone('utc'::text, now()) NOT NULL
);

-- Normalized procedural steps table
CREATE TABLE public.condition_steps (
  id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
  condition_id UUID NOT NULL REFERENCES public.conditions(id) ON DELETE CASCADE,
  step_number INT NOT NULL,
  instruction_en TEXT NOT NULL,
  instruction_ur TEXT NOT NULL,
  warning_en TEXT,
  warning_ur TEXT,
  CONSTRAINT unique_condition_step UNIQUE (condition_id, step_number)
);

-- Multilingual search synonyms table
CREATE TABLE public.condition_synonyms (
  id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
```

```

condition_id UUID NOT NULL REFERENCES public.conditions(id) ON DELETE CASCADE,
synonym VARCHAR(128) NOT NULL,
language VARCHAR(8) NOT NULL CHECK (language IN ('en', 'ur', 'roman_ur'))
);

-- Emergency contact directory table
CREATE TABLE public.emergency_contacts (
  id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
  service_name VARCHAR(128) NOT NULL,
  phone_number VARCHAR(32) NOT NULL,
  jurisdiction VARCHAR(64) NOT NULL,
  latitude DOUBLE PRECISION,
  longitude DOUBLE PRECISION
);

-- Trigram indexing for high-speed fuzzy search
CREATE INDEX idx_conditions_title_trgm_en ON public.conditions USING gin (title_en
gin_trgm_ops);
CREATE INDEX idx_conditions_title_trgm_ur ON public.conditions USING gin (title_ur
gin_trgm_ops);
CREATE INDEX idx_synonyms_trgm ON public.condition_synonyms USING gin (synonym
gin_trgm_ops);

-- Configure Row Level Security (RLS)
ALTER TABLE public.conditions ENABLE ROW LEVEL SECURITY;
ALTER TABLE public.condition_steps ENABLE ROW LEVEL SECURITY;
ALTER TABLE public.condition_synonyms ENABLE ROW LEVEL SECURITY;
ALTER TABLE public.emergency_contacts ENABLE ROW LEVEL SECURITY;

CREATE POLICY "Allow Public Read Access on Conditions" ON public.conditions FOR SELECT
USING (true);
CREATE POLICY "Allow Public Read Access on Steps" ON public.condition_steps FOR
SELECT USING (true);
CREATE POLICY "Allow Public Read Access on Synonyms" ON public.condition_synonyms
FOR SELECT USING (true);
CREATE POLICY "Allow Public Read Access on Contacts" ON public.emergency_contacts
FOR SELECT USING (true);

```

10.2 Serverless Edge Functions and AI Orchestration

Dynamic conversational triage is managed by a TypeScript Edge Function (ai-first-aid/index.ts) hosted on Supabase's edge network¹. The function coordinates security, database grounding, and model failover¹:

Pipeline Stage	Subsystem / Actor	Concrete Operational Mechanics
Request Ingress	Deno Edge Runtime	Validates HTTP POST requests, applies CORS headers, and verifies JSON payload schemas ¹ .
Query Expansion	PostgreSQL Client	Matches user input against condition_synonyms to extract matching verified clinical steps ¹ .
Context Assembly	Edge Logic Layer	Injects matched clinical procedures and safety guardrails into the LLaMA 3.3 system prompt ¹ .
Primary Inference	Groq LPU Client	Executes inference against llama-3.3-70b-versatile with temperature: 0.1 and a 512-token limit ¹ .
Automated Failover	Exception Router	Redirects requests to Google Gemini 1.5 Flash if Groq returns HTTP 429 or 5xx errors ¹ .
Egress Streaming	Server-Sent Events (SSE)	Streams generated text tokens directly to the client interface for progressive rendering ¹ .

Chapter 11: Core Business Logic

11.1 AI Medical Prompt Guardrails and Safety Rules

To ensure clinical safety and prevent harmful advice, the conversational assistant runs under strict prompt guardrails¹:

- **Mandatory Emergency Service Activation:** The model must open high-risk guidance by instructing the user to contact local emergency services (Rescue 1122 or Edhi 115)¹.
- **Strict Domain Limitation:** If a user query is not directly related to emergency first aid, physical injury, or acute medical stabilization, the model must refuse to answer and redirect the user¹.
- **Prohibition of Invasive Procedures:** The model is strictly forbidden from suggesting prescription medications, invasive surgical techniques, or advanced clinical interventions¹.
- **Explicit Contraindication Highlighting:** The model must explicitly warn against harmful layman practices for the identified condition (such as applying ice to burns or offering water to unconscious patients)².
- **Enforced Brevity and Formatting:** Instructions must be structured as numbered, sequential steps beginning with clear action verbs¹.
- **Automatic Linguistic Adaptation:** The system must detect whether the user is querying in English or Urdu and generate responses in the matching language¹.

11.2 Emergency Risk Triage Classification Algorithm

Incoming medical inquiries are categorized into standardized risk tiers to help users quickly assess situation severity¹:

Risk Tier Category	Clinical Determination Criteria	Example Conditions	Platform Action and Safety Protocol
High Risk (Red)	Immediate threat to life; risk of rapid fatal deterioration within minutes ² .	Cardiac arrest, severe arterial hemorrhage, complete airway obstruction ² .	Displays prominent red warnings, surfaces immediate 1122 calling buttons, and presents stabilization steps ¹ .
Medium to High Risk (Orange)	Severe injury or illness requiring urgent medical evaluation; breathing remains intact ² .	Second-degree thermal burns, compound fractures, acute heat exhaustion ¹ .	Surfaces critical contraindication warnings and displays directions to the nearest emergency

			facility ¹ .
Low to Medium Risk (Yellow)	Stable injuries without systemic compromise; condition can be managed with standard on-scene first aid ¹ .	Minor lacerations, superficial first-degree burns, joint sprains ¹ .	Provides standard first-aid steps and guidance on when to seek formal medical evaluation ¹ .

Chapter 12: User Workflow

The platform defines structured, step-by-step procedures for stabilizing patients during common critical emergencies¹:

Emergency Scenario	Clinical Assessment & Entry Trigger	Primary Physical Interventions	Prohibited Actions (Contraindications)	Target Resolution State
Out-of-Hospital Cardiac Arrest	Victim is unresponsive with absent or abnormal (agonal) breathing ² .	Place on a firm, flat surface. Begin continuous chest compressions at 100–120 BPM at a depth of 5–6 cm. Maintain a 30:2 compression-to-ventilation ratio if trained ² .	Do NOT place pillows under the head. Do NOT delay compressions to check for pulses repeatedly ² .	Perfusion maintained until EMS arrives or spontaneous circulation returns ² .
Thermal Burns and Scalds	Direct exposure to thermal energy, steam, or hot liquids with localized tissue damage ¹ .	Cool the burned area immediately under cool, gently running tap water for 10 to 20 minutes. Cover loosely with a clean,	Do NOT apply ice, butter, cooking oil, toothpaste, or raw flour. Do NOT burst intact blisters ¹ .	Thermal transfer arrested; burn surface protected from secondary infection ¹ .

		sterile dressing ¹ .		
Severe Traumatic Hemorrhage	Copious, spurting, or rapidly pooling blood from an open wound ² .	Apply firm, continuous direct pressure to the wound using a clean cloth or sterile dressing. Elevate the injured site above heart level if no fracture is suspected ² .	Do NOT remove blood-soaked dressings (layer fresh dressings on top). Do NOT use wire tourniquets ² .	Hemorrhage managed and stabilized for emergency transport ² .
Foreign Body Airway Obstruction	Sudden inability to speak, silent coughing, cyanosis, universal choking sign ² .	Alternate between 5 firm back blows between the shoulder blades and 5 abdominal thrusts (Heimlich maneuver) just above the navel ² .	Do NOT perform blind finger sweeps in the mouth. Do NOT administer water or liquids to drink ² .	Airway cleared; victim breathes normally or transitions to CPR if unresponsiveness occurs ² .

Chapter 13: Public Health Impact, Community Deployment, and Liability Governance

AI LifeSaver addresses longstanding structural challenges in pre-hospital emergency care across developing economies, particularly within high-density urban areas like Karachi³. In Pakistan, pre-hospital systems have historically faced significant resource limitations, with public ambulance networks frequently augmented by philanthropic fleets that operate primarily on a transport-first basis⁶.

The platform supports community-level emergency response across several key settings:

- **Academic Campuses and Educational Facilities:** Equips non-medical faculty, administrative staff, and students with guided, interactive emergency tools to improve campus safety¹.
- **Households and Families:** Provides families with clear, accessible instructions for managing common household emergencies, including childhood choking, scalds, and domestic falls¹.
- **Community Groups and Disaster Relief:** Serves as a digital support tool for

non-governmental organizations conducting first-aid training across underserved communities¹.

To ensure safe adoption, the platform operates within clear legal and operational boundaries:

- **Educational Purpose:** The system functions as an informational reference tool to guide first aid before professional help arrives, explicitly stating it does not provide formal clinical diagnoses¹.
- **Good Samaritan Protections:** The application's instructions align with basic first-aid principles, encouraging bystanders to act in good faith to stabilize casualties without attempting advanced or invasive medical procedures².
- **Telephony Integration:** By prominently displaying regional emergency numbers (SIEHS 1122, Edhi 115) across all views, the platform reinforces that bystander care is a bridge to, not a replacement for, professional emergency services¹.

Chapter 14: Non-Functional Requirements

To ensure dependable performance during emergency situations, AI LifeSaver targets specific technical and accessibility benchmarks¹:

Quality Metric	Performance Target	Architectural Implementation
Inference Latency (TTFT)	< on standard 4G connections	Groq LPU hardware running LLaMA 3.3 70B with Server-Sent Events token streaming ¹ .
Search Retrieval Latency	< query round-trip	PostgreSQL Generalized Index Search (gin_trgm_ops) over condition tables and synonyms ¹ .
System Availability	99.9% operational uptime	Globally distributed Supabase Edge Functions with automatic failover between Groq and Gemini ¹ .
Offline Operability	100% availability of core procedures	Client-side caching using bundled static datasets (firstAid.json) and local PDF rendering via jsPDF ¹ .
Data Privacy & Security	Zero Protected Health	Stateless guest architecture; no personal identity tracking or

	Information stored	remote conversation logs ¹ .
Accessibility Compliance	WCAG 2.1 Level AA conformance	High-contrast visual themes, readable typography for English and Urdu, and screen-reader accessible controls ¹ .

15. Expected Outcomes and Empirical Evaluation

Validation tests demonstrate that AI LifeSaver achieves significant performance and reliability improvements over traditional web architectures¹:

Evaluated System Metric	Traditional Cloud Architecture	AI LifeSaver System Configuration	Measured Impact / Improvement
Time-to-First-Token (TTFT)	3,450 ms (Standard Cloud API)	840 ms (Groq LPU Edge Pipeline)	75.6% reduction in response latency ¹ .
Search Retrieval Duration	850 ms (Unindexed string scan)	112 ms (PostgreSQL GIN trigram index)	86.8% improvement in search speed ¹ .
Initial Production Bundle	> (Standard bundle)	412 KB (Vite 7 code-split bundle)	85.2% reduction in initial payload ¹ .
Offline Procedure Availability	0.0% (Complete interface loss)	100.0% (via firstAid.json cache)	Complete offline procedural availability ¹ .
Medical Hallucination Rate	14.2% (Unconstrained LLM baseline)	< (Under RAG system guardrails)	High clinical output reliability ¹ .

Chapter 16: Technical Horizons and Expansion

- **Computer-Vision Injury Assessment:** Integrating on-device image classification models (via TensorFlow.js) to assist bystanders in categorizing burn depths and wound severity using their smartphone cameras¹.
- **Direct Emergency Dispatch Integration:** Developing automated Webhook connections with municipal dispatch centers, like SIEHS 1122, to share caller coordinates and preliminary triage data automatically¹.
- **Peer-to-Peer Mesh Distribution:** Using WebRTC data channels to enable peer-to-peer distribution of emergency guides between mobile devices during municipal network disruptions¹.

Through its combination of low-latency edge computing, clinical guardrails, and bilingual accessibility, AI LifeSaver provides a practical, scalable framework for reducing pre-hospital mortality in communities where emergency resources are most constrained¹.

Appendix A: Condition Data Schema and LLM System Prompt Protocol

A.1 Relational Condition and Procedural Seed Specification

The following SQL seed file illustrates the bilingual schema used to store standardized conditions in the database, including procedural steps and contraindication warnings¹:

SQL

-- Seed record for acute thermal burns

```
INSERT INTO public.conditions (  
  slug, title_en, title_ur, risk_level,  
  summary_en, summary_ur,  
  contraindications_en, contraindications_ur  
) VALUES (  
  'burns',  
  'Thermal Burns and Scalds',  
  'جھلسنا اور جلنا',  
  'Medium to High',  
  'Immediate cooling and protection for thermal burns and scald injuries.',  
  'حرارت یا گرم مائع سے جانے کی صورت میں فوری ٹھنڈا کرنے اور محفوظ رکھنے کے اقدامات',  
  ARRAY[  
    'Do NOT apply ice or freezing water',  
    'Do NOT apply butter, toothpaste, cooking oil, or flour',  
    'Do NOT burst blisters or tear stuck clothing'  
  ],  
  ARRAY[  
    'برف یا انتہائی ٹھنڈا پانی مت لگائیں',  
    'مکھن، توتھ پیسٹ، تیل یا آٹا مت لگائیں',  
    'چھالوں کو مت پھوڑیں اور چپکے ہوئے کپڑے مت کھینچیں'  
  ]  
)
```

-- Associate procedural steps with the burn record

```
INSERT INTO public.condition_steps (condition_id, step_number, instruction_en,  
  instruction_ur, warning_en, warning_ur)  
VALUES  
(  
  (SELECT id FROM public.conditions WHERE slug = 'burns'),  
  1,
```

```

'Cool the burn immediately under cool, gently running tap water for 10 to 20 minutes.',
'فوراً جلنے والی جگہ پر 10 سے 20 منٹ کے لیے ٹھنڈا (نل کا) پانی بہائیں۔',
'Use cool running water, not ice or freezing water.',
'پانی نارمل ٹھنڈا ہونا چاہیے، برف کا پانی ہرگز استعمال نہ کریں۔'
),
(
(SELECT id FROM public.conditions WHERE slug = 'burns'),
2,
'Carefully remove rings, watches, jewelry, or loose clothing near the burn before swelling begins.',
'سوجن شروع ہونے سے پہلے جلی ہوئی جگہ کے قریب موجود انگوٹھیاں، گھڑی یا تنگ کپڑے احتیاط سے اتار لیں۔',
'Do not pull clothing that is stuck directly to the burn.',
'اگر کپڑا جلد سے چپک گیا ہو تو اسے زبردستی مت کھینچیں۔'
),
(
(SELECT id FROM public.conditions WHERE slug = 'burns'),
3,
'Cover the burn loosely with a clean, dry, sterile dressing or clean plastic wrap.',
'جلی ہوئی جگہ پر صاف، خشک اور جراثیم سے پاک پٹی یا پلاسٹک کی شیٹ ڈھیلی کر کے لپیٹیں۔',
'Do not wrap tightly to avoid constricting tissue as swelling develops.',
'پٹی کو زیادہ سخت مت باندھیں تاکہ سوجن کی صورت میں دباؤ نہ آئے۔'
);

```

A.2 Edge Function System Prompt and Guardrail Configuration

The Supabase Edge Function ([ai-first-aid/index.ts](#)) enforces the following clinical guardrails, emergency dispatch links, and formatting rules¹:

TypeScript

```

export const EMERGENCY_AI_SYSTEM_PROMPT = `
You are the AI LifeSaver Emergency Medical Assistant, engineered strictly for bystander first aid and trauma triage.

OPERATIONAL INVARIANTS:
1. EMERGENCY SERVICES ACTIVATION: You must begin every critical response by explicitly instructing the user to call regional emergency services: Rescue 1122 (Pakistan SIEHS / Punjab Rescue) or Edhi 115.
2. ABSOLUTE MEDICAL RELEVANCE GUARDRAIL: You must evaluate every input. If the query is NOT strictly related to emergency first aid, physical injury, trauma, or urgent medical stabilization, you must REFUSE to answer. State clearly: "I only provide emergency first-aid assistance. Please consult a professional for other inquiries."
3. ZERO GENERATIVE HALLUCINATIONS: Never suggest prescription medications, surgical techniques, or invasive medical procedures. Limit all instructions to standard Basic Life Support (BLS), wound stabilization, and safe patient positioning.
4. CONTRAINDICATION HIGHLIGHTING: Always state what NOT to do for the identified emergency condition (e.g., forbidding fluids for unconscious individuals, forbidding ice on burns).
5. ACTIONABLE STRUCTURE: Structure instructions as numbered, sequential steps. Begin each step with a clear action verb. Use bold formatting for critical safety notices.
6. BILINGUAL CAPABILITY: Detect the language of the prompt (English or Urdu). Respond in the matching language. When responding in Urdu, use natural,

```

accessible vernacular terminology suitable for emergency comprehension.\n`;

The technical implementation of AI LifeSaver demonstrates that modern web standards, edge computing, and open-weight language models can work together to address long-standing challenges in pre-hospital emergency care¹. By keeping bundle sizes small, providing bilingual support, and enforcing strict clinical guardrails, the platform offers an accessible, reliable tool to help bystanders stabilize casualties during the critical first minutes of medical emergencies¹. *This is for informational purposes only. For medical advice or diagnosis, consult a professional.*