The Lookout Board

Information Gathering under Epistemic and Classical Planning,
with One Robot, Four Lookouts and a Status Board

Haniel Ulises

Epistemic Robotics

13 October 2026

A robot must know whether a zone is blocked. It can see the zone through four windows, one from each of four lookouts, but a screen closes every window except one, and which one is open is not known. A status board beside the robot's start shows it: slot k is lit exactly when the view from lookout k is clear. Nothing in the goal mentions the board. We prove that the domain has no conformant plan, that the policy of depth six Aletheia returns reads the board, goes to the lookout it shows lit and goes to the last lookout unread when three slots are dark, and that no classical planner reads the board: not a planner over the classical model, in which reading achieves nothing a goal needs; not one over a knowledge-level compilation under any determinization of its outcomes, since the board is a detour; and not hindsight optimisation, under which sensing has no value. On the roadmap of the hall the policy drives 8.47 m on average over the eight worlds and 12.15 m at worst; replanning from the nearest lookout drives 13.91 m and 24.66 m; the conformant tour 24.66 m always. In Gazebo, 32 paired seeds under each formulation measure it: every run of every formulation ended knowing the zone, backed by the map; the policy read the board in 32 of 32 runs and the classical ones in none; mean mission time was 48.0 s for the policy, 77.4 s for replanning and 134.0 s for the tour, and the policy's worst 66.6 s against 137.1 s and 137.4 s.

Contents

1 Scope 2

2 Environment 2

3 Domain 3

4 The policy and the absence of a conformant plan 3

5 Classical planning and the value of information 4

6 Route lengths per formulation 5

7 Planning cost as a function of the number of lookouts 5

8 Paired evaluation over 32 seeds 5

9 Recorded runs 6

10 Changes on four defects 7

11 Limitations 7

1 Scope

The comparison of epistemic and classical planning is usually made where the classical planner is handicapped: given a sequence to commit to, or denied the observations the epistemic planner gets. This report makes it where the classical side is at its strongest. The classical planner is POPF [6], with every action of the epistemic domain in its model, the duration of every drive taken from the roadmap the robot drives, and looks that end as soon as the map decides the zone or shows the window screened; in one formulation it replans after every look from where the robot stands, with the lookouts already found screened removed. What it is not given is a model of what the robot will know.

The scenario is built so that this is the one thing that matters. Reading the board achieves nothing the goal asks for; it only changes what the robot knows, and through that, where it should go. An epistemic planner sees the change, because its states are what the robot knows. A classical planner does not, and the propositions of Section 5 show that no determinization of the sensing outcomes, and no sampling of worlds, makes it see it.

2 Environment




Figure 1: The hall, 9.2 by 9.2 m. The zone, a 0.8 m square, stands in the middle of a walled room with a window in each wall; each window opens onto an embrasure, a channel 0.8 m deep between two side walls, and lookout k stands in front of embrasure k. The blue bars are where a screen stands; all but one do. The board is a panel against the west wall with four slots before it, and the robot reads it from 0.7 m off its start. Dashed: the roadmap the drive node plans over.

The embrasures make a view of the zone a property of standing at a lookout: a robot passing along the corridor sees the side walls of an embrasure and nothing of the room. A screen, when it stands, closes its window from inside the embrasure, so a robot at a screened lookout sees the screen and not the zone. The robot is a TurtleBot3 Burger with its laser's range set to 8 m (the LDS-01 reaches 3.5 m, too short to see across the room), mapping with slam_toolbox. Eight worlds, one

per open lookout and per zone, blocked by a crate or clear; seed s takes world $(s-1) \bmod 8$ and perturbs the start by up to 0.1 m and 10°.

Before any simulator run, `tools/check_views.py` casts the laser over a rasterised floor in every world and checks that each observation means what the domain says: from lookout k the zone is decided exactly when the view from k is clear, and the window reads blocked exactly when it is not; at the board the lit slot reads blocked and the other three clear; and no route the robot drives between two places decides the zone in passing.

3 Domain

One agent, $r1$. Atoms: *blocked-z*; *clear-1*, …, *clear-4*, the view from lookout k is clear; and where the robot stands, *at-board* and *at-*l_k. Actions, as event models [1], planned over as in [2]:

action	kind	precondition	events
goto-board, goto-lk	public ontic	not already there	there, and nowhere else
read-k	sensing	*at-board*	lit where *clear-*k, dark where $\neg$*clear-*k
check-k	sensing	*at-*l_k	clear where *clear-*k, screened where $\neg$*clear-*k
look-k	sensing	*at-*$l_k \wedge K_{r1}$ *clear-*k	blocked where *blocked-z*, free where $\neg$*blocked-z*

The sensing actions are semi-private. The initial model has eight worlds, all designated, with $r1$'s relation universal and the frame S5: exactly one of *clear-1*, …, *clear-4* holds, which is therefore common knowledge, and *blocked-z* either way. The goal is Kw_{r1} *blocked-z*. Nothing in it, and nothing in any precondition, mentions the board.

The sensing events carry no condition that the robot not yet know the answer, which such domains usually have to keep a planner from looking twice. On the robot every slot of the board resolves at once, and the epistemic state applies each observation as soon as its event is applicable; with that condition, the dark slots applied first would make the lit one known by elimination and its read inapplicable, and the executor would refuse the very action the policy runs next. Without it, reading what is already known changes nothing, and the planner still never does it.

4 The policy and the absence of a conformant plan

Proposition 1 (No conformant plan)**.** No sequence of the domain's actions is applicable in all eight worlds and leaves Kw_{r1} *blocked-z* true in all of them.

Proof. Only the looks' events differ on *blocked-z*, so such a sequence contains a look; take the first, look-k. Its precondition must hold in the state reached from every world, in particular from one where $\neg$*clear-*k, and no action changes *clear-*k; in an S5 model K_{r1}*clear-*k implies *clear-*k, so it fails there. □

Proposition 2 (The policy)**.** The policy

$$\text{goto-board};\ \text{read-1};\ \begin{cases} \text{lit}: & \text{goto-l1};\ \text{look-1} \\ \text{dark}: & \text{read-2};\ \begin{cases} \text{lit}: & \text{goto-l2};\ \text{look-2} \\ \text{dark}: & \text{read-3};\ \begin{cases} \text{lit}: & \text{goto-l3};\ \text{look-3} \\ \text{dark}: & \text{goto-l4};\ \text{look-4} \end{cases} \end{cases} \end{cases}$$

is applicable in all eight worlds, reaches Kw_{r1} *blocked-z* in all of them, drives to exactly one lookout, the open one, and has depth 6.

Proof. At the board, read-k lit leaves designated the two worlds where *clear-k*, in which K_{r1} *clear-k* holds, so after goto-lk look-k is applicable. If slots 1, 2 and 3 are dark, the designated worlds are the two where $\neg$*clear-1* $\wedge \neg$*clear-2* $\wedge \neg$*clear-3*, and since exactly one view is clear, *clear-4* holds in both: K_{r1} *clear-4* without reading slot 4. Each look's events split the designated worlds by *blocked-z*. The longest branch is goto-board, three reads, a drive and a look. □

Aletheia returns exactly this policy, by AO* in 20 050 expansions, and its validator checks all eight leaves. The policy that checks the lookouts in turn, the only alternative the domain offers, has depth 8. Aletheia minimises depth, the number of actions on the longest branch, and not distance; on this hall the two agree, and Section 6 gives the distances.

5 Classical planning and the value of information

Proposition 3 (The classical model)**.** In the classical model the robot executes, read_slot achieves nothing any precondition or goal uses. So no plan that is minimal under removal of actions contains it, and POPF never returned one.

Proof. The effect of read_slot, *read*, occurs in no precondition and in neither goal, the zone known or every lookout looked from, and the action deletes nothing. Removing every occurrence from a valid plan leaves it valid and shorter. Over the batch, POPF returned 80 plans to the replanner, and none contained read_slot. □

The classical model is the strongest one a classical planner can be given only if a model of knowledge would not help it. It would, as far as the preconditions go: the usual compilation of knowledge into a classical problem [3] has fluents for what is known, and a look needing K *clear-k* becomes a look needing a fluent *known-clear-k*, which read-k lit and check-k clear achieve. What such a planner still has to do is choose an outcome for each sensing action, since it plans sequences, and the two ways of doing that do not change the result.

Proposition 4 (Determinization)**.** Under any determinization that lets the planner choose each sensing action's outcome, as FF-Replan's all-outcomes determinization does [4], the cheapest plan does not visit the board.

Proof. The board is a spur off the start, so $d(\mathit{board}, x) = d(s, \mathit{board}) + d(s, x)$ for every place x. A plan through the board reaches some lookout k known clear at cost at least $2\,d(s, \mathit{board}) + d(s, l_k)$ plus a read; the plan that drives to l_k, checks the view and chooses the outcome clear reaches the same state at $d(s, l_k)$ plus a check, which is cheaper since the two sensing actions take the same time. After a failure the robot is at a lookout l, and by the triangle inequality $d(l, \mathit{board}) + d(\mathit{board}, l_k) \geq d(l, l_k) + 2\,d(s, \mathit{board})$. □

Proposition 5 (Hindsight)**.** Hindsight optimisation [5], which samples worlds and values each action by the cost of the optimal plan in each sample as though the sample were known, gives every sensing action a value no better than not sensing, and so never reads the board.

Proof. In a sampled world the optimal continuation is a plan in a fully known world, in which a sensing action changes nothing and costs time. Each action's value is a mean of such continuations, and reading only adds its own cost to each. □

A planner that does choose to read the board must value what the robot will know after reading it, in each of the worlds it cannot yet tell apart. That is a planner over states of knowledge, which is what an epistemic planner is.

6 Route lengths per formulation

The roadmap's shortest routes, in metres, give each formulation's drive in each world exactly, before a robot moves.

open lookout	1	2	3	4	mean	worst
policy: start, board, l_c	12.03	12.15	4.92	4.79	**8.47**	**12.15**
replanning: l_4, l_3, l_2, l_1 until open	24.66	17.42	10.18	3.35	13.91	24.66
conformant: the tour l_4, l_3, l_2, l_1	24.66	24.66	24.66	24.66	24.66	24.66

Table 1: Route lengths over the roadmap.

The replanner's order is POPF's: the nearest lookout by route time, lookout 4, then from each failure the nearest not yet tried. The conformant tour is the shortest of the twenty-four orders, lookout 4, 3, 2, 1; POPF's own tour for the same goal was longer, 193 s of driving against 155 s, and the baseline is given the shorter. The policy pays 1.44 m for the board in every world and saves a tour of the room in three of four.

7 Planning cost as a function of the number of lookouts

n	worlds	actions	strategy	depth (board / in turn)	first move	expansions	seconds
2	4	9	AO*	4 (4 / 4)	lookout 1	58	0.00
3	6	13	AO*	5 (5 / 6)	the board	1497	0.01
4	8	17	AO*	6 (6 / 8)	the board	20050	0.14
5	10	21	AO*	7 (7 / 10)	the board	318380	2.48
6	12	25	replan	12 (8 / 12)	lookout 1	17	5.00
6	12	25	AO* alone	8 (8 / 12)	the board	5832186	46.97
7	14	29	replan	14 (9 / 14)	lookout 1	20	5.00
7	14	29	AO* alone: no policy within the budget				900
8	16	33	replan	16 (10 / 16)	lookout 1	23	5.00

Table 2: Aletheia on the domain with n lookouts, exactly one of them open: the grounded size, the strategy its selection policy settled on, the policy's depth against $n + 2$ for reading the board and $2n$ for checking the lookouts in turn, and the wall-clock time.

With three to five lookouts, AO*, which Aletheia's selection policy picks, returns the policy that reads the board, of depth $n + 2$, against $2n$ for checking the lookouts in turn; with two the depths tie and it checks. Its search grows by an order of magnitude per lookout. From six lookouts the selection policy gives AO* a few seconds and then falls back on replanning, which determinizes the sensing outcomes and returns the policy that checks the lookouts in turn, of depth $2n$: the classical planner's policy, and it does not read the board, as a determinizing planner never does. Given the whole budget alone, AO* finds the board-first policy for six lookouts in 47 s and 5.8 million expansions, and for seven does not finish in 900 s. Reading the board is what a planner over states of knowledge finds; finding it is what such a planner pays for.

8 Paired evaluation over 32 seeds

Each seed fixes the world and the start, and is run under all three formulations side by side, so the comparison is paired. Times are simulated seconds from the order to the end of the mission; distances come from the robot's odometry, which the simulator reports in the world frame.

	backed	read the board	mean time	worst time	mean driven	worst driven
epistemic policy	32/32	32/32	48.0 s	66.6 s	8.1 m	12.0 m
classical replanning	32/32	0/32	77.4 s	137.1 s	13.9 m	24.8 m
conformant tour	32/32	0/32	134.0 s	137.4 s	24.6 m	24.9 m

Table 3: The batch, per formulation.

world	epistemic	replanning	conformant
lookout 1, zone clear	64.5 s, 11.4 m	136.4 s, 24.6 m	135.1 s, 24.6 m
lookout 1, zone blocked	63.9 s, 11.4 m	136.3 s, 24.6 m	134.8 s, 24.7 m
lookout 2, zone clear	66.0 s, 11.8 m	97.1 s, 17.4 m	134.8 s, 24.7 m
lookout 2, zone blocked	65.2 s, 11.7 m	97.3 s, 17.5 m	134.6 s, 24.7 m
lookout 3, zone clear	32.2 s, 4.7 m	57.3 s, 10.2 m	135.3 s, 24.6 m
lookout 3, zone blocked	30.9 s, 4.7 m	56.5 s, 10.1 m	133.0 s, 24.6 m
lookout 4, zone clear	31.1 s, 4.3 m	19.3 s, 3.5 m	132.6 s, 24.7 m
lookout 4, zone blocked	30.8 s, 4.3 m	18.4 s, 3.4 m	131.0 s, 24.6 m

Table 4: By world: median time and distance; each world met 4 times.

Every run of every formulation ended knowing the zone, and the map backed it in all 96. The policy read the board in all 32 of its runs, and neither classical formulation read it once. Paired by seed against replanning, the policy was faster in 24 seeds and slower in 8 (exact sign test, $p = 0.007$); the Hodges–Lehmann estimate of what it saves is 29.6 s and 5.6 m. It was slower only in the worlds where the open lookout is the replanner's first, by at most 12.7 s, the price of the board. Against the conformant tour it was faster in 32 of 32 seeds, by 86.0 s.

9 Recorded runs

Four takes, recorded one at a time with the launch unchanged and headless: a Gazebo client and RViz on a virtual display, the world held paused until both had drawn, and the Gazebo camera cut on the executor's own actions. Seed 1, where the open view is lookout 1's, the farthest from the start and the replanner's last, under all three formulations; and the policy on seed 8, where lookout 4 is open and the zone blocked, and the policy goes to lookout 4 with slot 4 unread. The film ends with seed 1's policy and replanner side by side by simulated time since the order.




Figure 2: The film at the board on seed 1, held. Left, RViz: the map, with the board's slots outlined in the colour the map gives them, slot 1 red (a post stands in it, so it is lit) and the others green, and the robot's trail from the start. Right, Gazebo: the robot before the board and slot 1's post. Under both: the policy with read-1 running, the observation, and what the robot knows: K_{r1} *clear-1* from the board, and $K_{r1}\neg$*clear-j* for the other three by elimination.

10 Changes on four defects

Knowledge guard on sensing events. The first domain had each sensing event require that the robot not yet know its answer. It planned the same policy, but on the robot it could not run, as the domain section explains, and the condition was removed. The planner's policy did not change.

POPF and a negative precondition. With the look written as requiring *(not (screened ?l))*, POPF dumped core while building its lookup tables. The classical domain writes it positively, *open_ view*, which the problem asserts for every lookout not yet found screened.

Shared scratch directory in domain validation. PlanSys2's domain expert checks the domain with a POPF instance of its own, whose scratch directory defaults to `/tmp`. Runs started side by side read each other's half-written `check_domain.pddl`, and two runs of the batch failed to start with "PDDL syntax error". The launch now gives the domain expert the run's own directory, the batch starts each run a few seconds apart, and the failed runs were run again; their first attempts are kept.

Dangling parameter reference in the action nodes. Both action nodes first iterated directly over the string array of a parameter, a reference into a temporary that the loop outlived, and aborted with `std::length_error` at start. They copy the list first.

11 Limitations

- Cost-aware epistemic planning. Aletheia minimises the policy's depth. Were the board far away, a policy of least depth could still read it and drive further than checking the nearest lookout; this hall does not test that.

- A planner over beliefs that is not epistemic in name. A POMDP solver, or a contingent planner over belief states, values the board for the same reason the epistemic planner does; the comparison here is with classical planning.
- A hand-written rule. "Read the board first" would do as well here and needs no planner; the point is that the epistemic planner finds it from the domain, and would not on a hall where the board told it nothing.
- More than one robot, and sensing that can be wrong. The laser's noise is 0.01 m and every region decided correctly in every run.

References

[1] A. Baltag, L. S. Moss and S. Solecki. The logic of public announcements, common knowledge, and private suspicions. *Proceedings of TARK VII*, 43–56, 1998.

[2] T. Bolander and M. B. Andersen. Epistemic planning for single- and multi-agent systems. *Journal of Applied Non-Classical Logics* 21(1):9–34, 2011.

[3] H. Palacios and H. Geffner. Compiling uncertainty away in conformant planning problems with bounded width. *Journal of Artificial Intelligence Research* 35:623–675, 2009.

[4] S. Yoon, A. Fern and R. Givan. FF-Replan: a baseline for probabilistic planning. *Proceedings of ICAPS*, 352–359, 2007.

[5] S. Yoon, A. Fern, R. Givan and S. Kambhampati. Probabilistic planning via determinization in hindsight. *Proceedings of AAAI*, 1010–1016, 2008.

[6] A. J. Coles, A. I. Coles, M. Fox and D. Long. Forward-chaining partial-order planning. *Proceedings of ICAPS*, 42–49, 2010.