

# Copyright Notice

These slides are distributed under the Creative Commons License.

[DeepLearning.AI](#) makes these slides available for educational purposes. You may not use or distribute these slides for commercial purposes. You may make copies of these slides and use or distribute them for educational purposes as long as you cite [DeepLearning.AI](#) as the source of the slides.

For the rest of the details of the license, see

<https://creativecommons.org/licenses/by-sa/2.0/legalcode>

# Input to a Deep Neural Network

**tf.data** makes input pipelines in TensorFlow to be

- Fast
- Flexible
- Easy-to-use

# Basic mechanics

Data sources

```
tf.data.Datase  
t
```

...

```
tf.data.Datase  
t
```

```
tf.data.Datase  
t
```

Transformations



```
map(func)  
batch(size)  
...
```

```
tf.data.Dataset
```

# Basic mechanics

Data sources

```
tf.data.Dataset  
    t
```

...

```
tf.data.Dataset  
    t
```

```
tf.data.Dataset  
    t
```

Transformations



```
map(func)  
batch(size)  
...
```

```
tf.data.Dataset
```

# Basic mechanics

Data sources

```
tf.data.Dataset  
    t
```

...

```
tf.data.Dataset  
    t
```

```
tf.data.Dataset  
    t
```

Transformations



```
tf.data.Dataset
```

```
map(func)
```

```
batch(size)
```

...

# Using an iterator to navigate

```
dataset = tf.data.Dataset.from_tensor_slices([1, 2, 3, 4])  
it = iter(dataset)
```

```
>>> while True:  
    try:  
        print(next(it))  
    except StopIteration as e:  
        break
```

```
tf.Tensor(1, shape=(), dtype=int32)  
tf.Tensor(2, shape=(), dtype=int32)  
tf.Tensor(3, shape=(), dtype=int32)  
tf.Tensor(4, shape=(), dtype=int32)
```

# Loading numpy arrays (from\_tensor\_slices)

```
(x_train, y_train), (x_test, y_test) = tf.keras.datasets.cifar10.load_data()
```

```
dataset = tf.data.Dataset.from_tensor_slices((x_train, y_train))
```

```
>>> for image, label in tfds.as_numpy(dataset.take(2)):
```

```
    print(image.shape, label)
```

```
(32, 32, 3) [6]
```

```
(32, 32, 3) [9]
```

First	Last	Addr	Phone	Gender	Age	
Jane	Smith	123 Anywhere	555 555 5555	1	3	



First	Last	Addr	Phone	Gender	Age	
Jane	Smith	123 Anywhere	555 555 5555	1	3	


Index	Description
0	Male
1	Female
2	Nonbinary
3	Trans
4	Unassigned
...	...

First	Last	Addr	Phone	Gender	Age	
Jane	Smith	123 Anywhere	555 555 5555	1	3	

Index	Description
0	Male
1	Female
2	Nonbinary
3	Trans
4	Unassigned
...	...

Index	Description
0	Infant
1	Child
2	Teen
3	Young Adult
4	Adult
...	...

# Primer on Feature Columns



<https://archive.ics.uci.edu/ml/datasets/iris>



sepal_length	sepal_width	petal_length	petal_width	species
5.1	3.5	1.4	0.2	Iris-setosa
4.9	3	1.4	0.2	Iris-setosa
4.7	3.2	1.3	0.2	Iris-setosa
4.6	3.1	1.5	0.2	Iris-setosa
5	3.6	1.4	0.2	Iris-setosa
5.4	3.9	1.7	0.4	Iris-setosa
4.6	3.4	1.4	0.3	Iris-setosa
5	3.4	1.5	0.2	Iris-setosa
4.4	2.9	1.4	0.2	Iris-setosa
4.9	3.1	1.5	0.1	Iris-setosa
5.4	3.7	1.5	0.2	Iris-setosa
4.8	3.4	1.6	0.2	Iris-setosa
4.8	3	1.4	0.1	Iris-setosa
4.3	3	1.1	0.1	Iris-setosa
5.8	4	1.2	0.2	Iris-setosa
5.7	4.4	1.5	0.4	Iris-setosa
5.4	3.9	1.3	0.4	Iris-setosa

# Numeric column

The Iris dataset has all numeric data as its input features:

- SepalLength
- SepalWidth
- PetalLength
- PetalWidth

# Specifying data types

```
# Defaults to a tf.float32 scalar.
```

```
numeric_feature_column = tf.feature_column.numeric_column(key="SepalLength")
```


```
# Represent a tf.float64 scalar.
```

[illegible]

# Shapes for different numeric data

[illegible][illegible]

# Bucketized column



Date Range	Represented as...
< 1960	[1, 0, 0, 0]
>= 1960 but < 1980	[0, 1, 0, 0]
>= 1980 but < 2000	[0, 0, 1, 0]
>= 2000	[0, 0, 0, 1]



# Bucketizing features


```
# First, convert the raw input to a numeric column.
```

```
numeric_feature_column = tf.feature_column.numeric_column("Year")
```

```
# Then, bucketize the numeric column on the years 1960, 1980, and 2000.
```

```
bucketized_feature_column = tf.feature_column.bucketized_column(  
    source_column = numeric_feature_column,  
    boundaries = [1960, 1980, 2000])
```

# Categorical identity column




# Categorizing identity features

```
identity_feature_column = tf.feature_column.categorical_column_with_identity(  
    key='my_feature_b',  
    num_buckets=4) # Values [0, 4]
```

```
def input_fn():  
    ...  
    return ({ 'my_feature_a':[7, 9, 5, 2], 'my_feature_b':[3, 1, 2, 2] },  
            [Label_values])
```

# Categorical vocabulary column



# Creating a categorical vocab column

From a vocabulary list

```
vocabulary_feature_column = tf.feature_column.categorical_column_with_vocabulary_list(  
    key=feature_name,  
    vocabulary_list=["kitchenware", "electronics", "sports"])
```

From a vocabulary file

```
vocabulary_feature_column = tf.feature_column.categorical_column_with_vocabulary_file(  
    key=feature_name,  
    vocabulary_file="product_class.txt",  
    vocabulary_size=3)
```

# Creating a categorical vocab column

From a vocabulary list


```
vocabulary_feature_column = tf.feature_column.categorical_column_with_vocabulary_list(  
    key=feature_name,  
    vocabulary_list=["kitchenware", "electronics", "sports"])
```

From a vocabulary file

```
vocabulary_feature_column = tf.feature_column.categorical_column_with_vocabulary_file(  
    key=feature_name,  
    vocabulary_file="product_class.txt",  
    vocabulary_size=3)
```

# Hashed column

$\text{hash}(\text{raw\_feature}) \% \text{hash\_bucket\_size}$



# Hashed column

```
hashed_feature_column = tf.feature_column.categorical_column_with_hash_bucket(  
    key="some_feature",  
    hash_bucket_size=100) # The number of categories
```



# Crossed column

```
# Bucketize the latitude and longitude using the `edges`

latitude_bucket_fc = tf.feature_column.bucketized_column(
    tf.feature_column.numeric_column('latitude'),
    list(atlanta.latitude.edges))

longitude_bucket_fc = tf.feature_column.bucketized_column(
    tf.feature_column.numeric_column('longitude'),
    list(atlanta.longitude.edges))

# Cross the bucketized columns, using 5000 hash bins.


crossed_lat_lon_fc = tf.feature_column.crossed_column(
    [latitude_bucket_fc, longitude_bucket_fc], 5000)
```

# Crossed column

```
# Bucketize the latitude and longitude using the `edges`  
  
latitude_bucket_fc = tf.feature_column.bucketized_column(  
    tf.feature_column.numeric_column('latitude'),  
    list(atlanta.latitude.edges))  
  
longitude_bucket_fc = tf.feature_column.bucketized_column(  
    tf.feature_column.numeric_column('longitude'),  
    list(atlanta.longitude.edges))
```

```
# Cross the bucketized columns, using 5000 hash bins.  
  
crossed_lat_lon_fc = tf.feature_column.crossed_column(  
    [latitude_bucket_fc, longitude_bucket_fc], 5000)
```

# Embedding column



# Natural Language Processing

Course 3 of the deeplearning.ai  
TensorFlow Specialization



deeplearning.ai



TensorFlow

# Embedding column

```
embedding_dimensions = number_of_categories**0.25  
  
categorical_column = ... # Create any categorical column  
  
# Represent the categorical column as an embedding column.  
# This means creating an embedding vector lookup table with one element for each  
category.  
  
embedding_column = tf.feature_column.embedding_column(  
    categorical_column=categorical_column,  
    dimension=embedding_dimensions)
```

# Embedding column

```
embedding_dimensions = number_of_categories**0.25  
categorical_column = ... # Create any categorical column
```

```
# Represent the categorical column as an embedding column.
```

```
# This means creating an embedding vector lookup table with one element for each  
category.
```

```
embedding_column = tf.feature_column.embedding_column(  
    categorical_column=categorical_column,  
    dimension=embedding_dimensions)
```

# Embedding column

```
embedding_dimensions = number_of_categories**0.25

categorical_column = ... # Create any categorical column

# Represent the categorical column as an embedding column.

# This means creating an embedding vector lookup table with one element for each
category.

embedding_column = tf.feature_column.embedding_column(
    categorical_column=categorical_column,
    dimension=embedding_dimensions)
```

# Data sources

Numpy

DataFrames

Images

CSV and Text

TFRecords

Generators



## # Download dataset

```
DATA_URL = 'https://storage.googleapis.com/tensorflow/tf-keras-datasets/mnist.npz'  
path = tf.keras.utils.get_file('mnist.npz', DATA_URL)
```

## # Extract train and test examples

```
with np.load(path) as data:  
    train_examples = data['x_train']  
    train_labels = data['y_train']  
    test_examples = data['x_test']
```

## # Create train and test datasets out of the examples

```
train_dataset = tf.data.Dataset.from_tensor_slices((train_examples, train_labels))  
test_dataset = tf.data.Dataset.from_tensor_slices(test_examples)
```

```
for feat, targ in train_dataset.take(2):
```

```
    print ('Features shape: {}, Target: {}'.format(feat.shape, targ))
```

```
Features shape: (28, 28), Target: 5
```

```
Features shape: (28, 28), Target: 0
```

```
csv_file = tf.keras.utils.get_file('heart.csv', 'https://storage.googleapis.com/applied-dl/heart.csv')
df = pd.read_csv(csv_file)
df.head()
```

	age	sex	cp	trestbps	chol	fbs	restecg	thalach	exang	oldpeak	slope	ca	thal	target
0	63	1	1	145	233	1	2	150	0	2.3	3	0	fixed	0
1	67	1	4	160	286	0	2	108	1	1.5	2	3	normal	1
2	67	1	4	120	229	0	2	129	1	2.6	2	2	reversible	0
3	37	1	3	130	250	0	0	187	0	3.5	3	0	normal	0
4	41	0	2	130	204	0	2	172	0	1.4	1	0	normal	0

```
df['thal'] = pd.Categorical(df['thal'])  
df['thal'] = df.thal.cat.codes  
df.head()
```

	age	sex	cp	trestbps	chol	fbs	restecg	thalach	exang	oldpeak	slope	ca	thal	target
0	63	1	1	145	233	1	2	150	0	2.3	3	0	2	0
1	67	1	4	160	286	0	2	108	1	1.5	2	3	3	1
2	67	1	4	120	229	0	2	129	1	2.6	2	2	4	0
3	37	1	3	130	250	0	0	187	0	3.5	3	0	3	0
4	41	0	2	130	204	0	2	172	0	1.4	1	0	3	0

```
target = df.pop('target')  
dataset = tf.data.Dataset.from_tensor_slices((df.values, target.values))
```

```
>>> for feat, targ in dataset.take(5):  
    print('Features: {}, Target: {}'.format(feat, targ))
```

```
Features: [ 63.    1.    1.  145.  233.    1.    2.  150.    0.    2.3   3.    0.    2. ], Target: 0  
Features: [ 67.    1.    4.  160.  286.    0.    2.  108.    1.    1.5   2.    3.    3. ], Target: 1  
Features: [ 67.    1.    4.  120.  229.    0.    2.  129.    1.    2.6   2.    2.    4. ], Target: 0  
Features: [ 37.    1.    3.  130.  250.    0.    0.  187.    0.    3.5   3.    0.    3. ], Target: 0  
Features: [ 41.    0.    2.  130.  204.    0.    2.  172.    0.    1.4   1.    0.    3. ], Target: 0
```

```
import pathlib
```

```
DATA_URL =  
'https://storage.googleapis.com/download.tensorflow.org/example_images/flower_photos.tgz'  
data_root_orig = tf.keras.utils.get_file(origin=DATA_URL,  
                                           fname='flower_photos', untar=True)  
data_root = pathlib.Path(data_root_orig)
```

```
label_names = sorted(item.name for item in data_root.glob('*/*') if item.is_dir())  
>>> label_names  
['daisy', 'dandelion', 'roses', 'sunflowers', 'tulips']
```



Extract



flower\_photos.tgz



Location:

/flower\_photos/

Name	▲	Size	Type	Modified
tulips		55.1 MB	Folder	10 February 2016, 12:52
sunflowers		54.9 MB	Folder	10 February 2016, 12:52
roses		39.7 MB	Folder	10 February 2016, 12:52
dandelion		48.3 MB	Folder	10 February 2016, 12:52
daisy		34.3 MB	Folder	10 February 2016, 12:52
LICENSE.txt		418.0 kB	plain text do...	08 February 2016, 18:59

```
import pathlib

DATA_URL =
'https://storage.googleapis.com/download.tensorflow.org/example_images/flower_photos.tgz'
data_root_orig = tf.keras.utils.get_file(origin=DATA_URL,
                                         fname='flower_photos', untar=True)
data_root = pathlib.Path(data_root_orig)

label_names = sorted(item.name for item in data_root.glob('*/*') if item.is_dir())
>>> label_names
['daisy', 'dandelion', 'roses', 'sunflowers', 'tulips']
```

```
import random
import IPython.display as display

all_image_paths = list(data_root.glob('*/*'))
all_image_paths = [str(path) for path in all_image_paths]
random.shuffle(all_image_paths)

image_count = len(all_image_paths)
image_count

image_path = random.choice(all_image_paths)
display.display(display.Image(image_path))
```





```
TRAIN_DATA_URL = "https://storage.googleapis.com/tf-datasets/titanic/train.csv"
```

```
train_file_path = tf.keras.utils.get_file("train.csv", TRAIN_DATA_URL)
```

```
df = pd.read_csv(train_file_path, sep=',')
```

```
df.head()
```

	survived	sex	age	n_siblings_spouses	parch	fare	class	deck	embark_town	alone
0	0	male	22.0	1	0	7.2500	Third	unknown	Southampton	n
1	1	female	38.0	1	0	71.2833	First	C	Cherbourg	n
2	1	female	26.0	0	0	7.9250	Third	unknown	Southampton	y
3	1	female	35.0	1	0	53.1000	First	C	Southampton	n
4	0	male	28.0	0	0	8.4583	Third	unknown	Queenstown	y

```
TRAIN_DATA_URL = "https://storage.googleapis.com/tf-datasets/titanic/train.csv"
train_file_path = tf.keras.utils.get_file("train.csv", TRAIN_DATA_URL)

df = pd.read_csv(train_file_path, sep=',')
df.head()
```

	survived	sex	age	n_siblings_spouses	parch	fare	class	deck	embark_town	alone
0	0	male	22.0	1	0	7.2500	Third	unknown	Southampton	n
1	1	female	38.0	1	0	71.2833	First	C	Cherbourg	n
2	1	female	26.0	0	0	7.9250	Third	unknown	Southampton	y
3	1	female	35.0	1	0	53.1000	First	C	Southampton	n
4	0	male	28.0	0	0	8.4583	Third	unknown	Queenstown	y

```
NUMERIC_FEATURES = ['age', 'n_siblings_spouses', 'parch', 'fare']  
dense_df = df[NUMERIC_FEATURES]  
dense_df.head()
```

	age	n_siblings_spouses	parch	fare
0	22.0	1	0	7.2500
1	38.0	1	0	71.2833
2	26.0	0	0	7.9250
3	35.0	1	0	53.1000

```
numeric_columns = []  
for feature in NUMERIC_FEATURES:  
    num_col = tf.feature_column.numeric_column(feature)  
    numeric_columns.append(tf.feature_column.indicator_column(num_col))
```

```
>>> numeric_columns  
[IndicatorColumn(categorical_column=NumericColumn(key='age', shape=(1,),  
default_value=None, dtype=tf.float32, normalizer_fn=None)),  
 IndicatorColumn(categorical_column=NumericColumn(key='n_siblings_spouses', shape=(1,),  
default_value=None, dtype=tf.float32, normalizer_fn=None)),  
 IndicatorColumn(categorical_column=NumericColumn(key='parch', shape=(1,),  
default_value=None, dtype=tf.float32, normalizer_fn=None)),  
 IndicatorColumn(categorical_column=NumericColumn(key='fare', shape=(1,),  
default_value=None, dtype=tf.float32, normalizer_fn=None))]
```

```
numeric_columns = []  
for feature in NUMERIC_FEATURES:  
    num_col = tf.feature_column.numeric_column(feature)  
    numeric_columns.append(tf.feature_column.indicator_column(num_col))
```

```
>>> numeric_columns  
[IndicatorColumn(categorical_column=NumericColumn(key='age', shape=(1,),  
default_value=None, dtype=tf.float32, normalizer_fn=None)),  
 IndicatorColumn(categorical_column=NumericColumn(key='n_siblings_spouses', shape=(1,),  
default_value=None, dtype=tf.float32, normalizer_fn=None)),  
 IndicatorColumn(categorical_column=NumericColumn(key='parch', shape=(1,),  
default_value=None, dtype=tf.float32, normalizer_fn=None)),  
 IndicatorColumn(categorical_column=NumericColumn(key='fare', shape=(1,),  
default_value=None, dtype=tf.float32, normalizer_fn=None))]
```

```
numeric_columns = []  
for feature in NUMERIC_FEATURES:  
    num_col = tf.feature_column.numeric_column(feature)  
    numeric_columns.append(tf.feature_column.indicator_column(num_col))
```

```
>>> numeric_columns  
[IndicatorColumn(categorical_column=NumericColumn(key='age', shape=(1,),  
default_value=None, dtype=tf.float32, normalizer_fn=None)),  
 IndicatorColumn(categorical_column=NumericColumn(key='n_siblings_spouses', shape=(1,),  
default_value=None, dtype=tf.float32, normalizer_fn=None)),  
 IndicatorColumn(categorical_column=NumericColumn(key='parch', shape=(1,),  
default_value=None, dtype=tf.float32, normalizer_fn=None)),  
 IndicatorColumn(categorical_column=NumericColumn(key='fare', shape=(1,),  
default_value=None, dtype=tf.float32, normalizer_fn=None))]
```

```
numeric_columns = []  
for feature in NUMERIC_FEATURES:  
    num_col = tf.feature_column.numeric_column(feature)  
    numeric_columns.append(tf.feature_column.indicator_column(num_col))
```

```
>>> numeric_columns
```

```
[IndicatorColumn(categorical_column=NumericColumn(key='age', shape=(1,),  
default_value=None, dtype=tf.float32, normalizer_fn=None)),  
 IndicatorColumn(categorical_column=NumericColumn(key='n_siblings_spouses', shape=(1,),  
default_value=None, dtype=tf.float32, normalizer_fn=None)),  
 IndicatorColumn(categorical_column=NumericColumn(key='parch', shape=(1,),  
default_value=None, dtype=tf.float32, normalizer_fn=None)),  
 IndicatorColumn(categorical_column=NumericColumn(key='fare', shape=(1,),  
default_value=None, dtype=tf.float32, normalizer_fn=None))]
```

```
>>> numeric_columns  
[IndicatorColumn(categorical_column=NumericColumn(key='age',  
shape=(1,), default_value=None, dtype=tf.float32,  
normalizer_fn=None)),  
...]
```



```
CATEGORIES = {  
    'sex': ['male', 'female'],  
    'class': ['First', 'Second', 'Third'],  
    'deck': ['A', 'B', 'C', 'D', 'E', 'F', 'G', 'H', 'I', 'J'],  
    'embark_town': ['Cherbourg', 'Southampton', 'Queenstown'],  
    'alone': ['y', 'n']  
}
```

```
cat_df = df[list(CATEGORIES.keys())]  
cat_df.head()
```

```
cat_df = df[list(CATEGORIES.keys())]  
cat_df.head()
```

```
CATEGORIES = {  
    'sex': ['male', 'female'],  
    'class' : ['First', 'Second', 'Third'],  
    'deck' : ['A', 'B', 'C', 'D', 'E', 'F', 'G', 'H', 'I', 'J'],  
    'embark_town' : ['Cherbourg', 'Southampton', 'Queenstown'],  
    'alone' : ['y', 'n']  
}
```

	sex	class	deck	embark_town	alone
0	male	Third	unknown	Southampton	n
1	female	First	C	Cherbourg	n
2	female	Third	unknown	Southampton	y
3	female	First	C	Southampton	n
4	male	Third	unknown	Queenstown	y

```
categorical_columns = []  
for feature, vocab in CATEGORIES.items():  
    cat_col = tf.feature_column.categorical_column_with_vocabulary_list(  
        key=feature, vocabulary_list=vocab)  
    categorical_columns.append(tf.feature_column.indicator_column(cat_col))
```

```
categorical_columns = []  
for feature, vocab in CATEGORIES.items():  
    cat_col = tf.feature_column.categorical_column_with_vocabulary_list(  
        key=feature, vocabulary_list=vocab)  
    categorical_columns.append(tf.feature_column.indicator_column(cat_col))
```

```
categorical_columns = []  
for feature, vocab in CATEGORIES.items():  
    cat_col = tf.feature_column.categorical_column_with_vocabulary_list(  
        key=feature, vocabulary_list=vocab)  
    categorical_columns.append(tf.feature_column.indicator_column(cat_col))
```

```
>>> categorical_columns
[IndicatorColumn(categorical_column=VocabularyListCategoricalColumn(key='sex', vocabulary_list=('male', 'female'),
dtype=tf.string, default_value=-1, num_oov_buckets=0)),

IndicatorColumn(categorical_column=VocabularyListCategoricalColumn(key='class', vocabulary_list=('First', 'Second',
'Third'), dtype=tf.string, default_value=-1,
num_oov_buckets=0)),
...
```

```
>>> categorical_columns  
[IndicatorColumn(categorical_column=VocabularyListCategoricalColumn(key='sex', vocabulary_list=('male', 'female'),  
dtype=tf.string, default_value=-1, num_oov_buckets=0)),
```

```
IndicatorColumn(categorical_column=VocabularyListCategoricalColumn(key='class', vocabulary_list=('First', 'Second',  
'Third'), dtype=tf.string, default_value=-1,  
num_oov_buckets=0)),
```

```
...
```

```
DIRECTORY_URL =
```

```
'https://storage.googleapis.com/download.tensorflow.org/data/ill  
iad/'
```

```
FILE_NAME = 'cowper.txt'
```



1 Achilles sing, O Goddess! Peleus' son;  
2 His wrath pernicious, who ten thousand woes  
3 Caused to Achaia's host, sent many a soul  
4 Illustrious into Ades premature,  
5 And Heroes gave (so stood the will of Jove)  
6 To dogs and to all ravening fowls a prey,  
7 When fierce dispute had separated once  
8 The noble Chief Achilles from the son  
9 Of Atreus, Agamemnon, King of men.  
10 Who them to strife impell'd? What power divine?  
11 Latona's son and Jove's. For he, incensed  
12 Against the King, a foul contagion raised

```
file_path = tf.keras.utils.get_file(name,  
                                     origin=DIRECTORY_URL + FILE_NAME)  
  
lines_dataset = tf.data.TextLineDataset(file_path)
```

```
>>> for text_data in tfds.as_numpy(lines_dataset.take(3)):  
    print(text_data.decode('utf-8'))
```

Achilles sing, O Goddess! Peleus' son;  
His wrath pernicious, who ten thousand woes  
Caused to Achaia's host, sent many a soul

```
filenames = [tf_record_filename]
raw_dataset = tf.data.TFRecordDataset(filenames)

feature_description = {
    'feature1': tf.io.FixedLenFeature(), tf.string),
    'feature2': tf.io.FixedLenFeature(), tf.int64)
}

for raw_record in raw_dataset.take(1):
    example = tf.io.parse_single_example(raw_record, feature_description)
    print(example)
```

```
filenames = [tf_record_filename]
raw_dataset = tf.data.TFRecordDataset(filenames)
```

```
feature_description = {
    'feature1': tf.io.FixedLenFeature(), tf.string),
    'feature2': tf.io.FixedLenFeature(), tf.int64)
}
```

```
for raw_record in raw_dataset.take(1):
    example = tf.io.parse_single_example(raw_record, feature_description)
    print(example)
```

```
filenames = [tf_record_filename]
raw_dataset = tf.data.TFRecordDataset(filenames)
```

```
feature_description = {
    'feature1': tf.io.FixedLenFeature((), tf.string),
    'feature2': tf.io.FixedLenFeature((), tf.int64)
}
```

```
for raw_record in raw_dataset.take(1):
    example = tf.io.parse_single_example(raw_record, feature_description)
    print(example)
```

```
filenames = [tf_record_filename]
raw_dataset = tf.data.TFRecordDataset(filenames)

feature_description = {
    'feature1': tf.io.FixedLenFeature(), tf.string),
    'feature2': tf.io.FixedLenFeature(), tf.int64)
}

for raw_record in raw_dataset.take(1):
    example = tf.io.parse_single_example(raw_record, feature_description)
    print(example)
```

# Convolutional Neural Networks in TensorFlow

TensorFlow Specialization




deeplearning.ai



TensorFlow






```
def make_generator():  
    train_datagen = tf.keras.preprocessing.image.ImageDataGenerator(rescale=1. / 255,  
                                                                    rotation_range=20, zoom_range=[0.8, 1.2])  
  
    train_generator = train_datagen.flow_from_directory(catsdogs,  
                                                       target_size=(224, 224), class_mode='categorical', batch_size=32)  
  
    return train_generator  
  
train_generator = tf.data.Dataset.from_generator(  
    make_generator, (tf.float32, tf.uint8))
```


```
def make_generator():  
    train_datagen = tf.keras.preprocessing.image.ImageDataGenerator(rescale=1. / 255,  
                                                                    rotation_range=20, zoom_range=[0.8, 1.2])  
  
    train_generator = train_datagen.flow_from_directory(catsdogs,  
                                                       target_size=(224, 224), class_mode='categorical', batch_size=32)  
  
    return train_generator  
  
train_generator = tf.data.Dataset.from_generator(  
    make_generator, (tf.float32, tf.uint8))
```

```
def make_generator():  
    train_datagen = tf.keras.preprocessing.image.ImageDataGenerator(rescale=1. / 255,  
                                                                    rotation_range=20, zoom_range=[0.8, 1.2])  
  
    train_generator = train_datagen.flow_from_directory(catsdogs,  
                                                       target_size=(224, 224), class_mode='categorical', batch_size=32)  
  
    return train_generator  
  
train_generator = tf.data.Dataset.from_generator(  
    make_generator, (tf.float32, tf.uint8))
```


# Datasets




# Datasets



# Datasets




# Datasets





# Datasets



```
# Fetch the numpy dataset
```

```
DATA_URL =
```

```
'https://storage.googleapis.com/tensorflow/tf-keras-datasets/mnist.npz'
```

```
path = tf.keras.utils.get_file('mnist.npz', DATA_URL)
```

```
# Extract train, test sets
```

```
with np.load(path) as data:
```

```
    train_examples = data['x_train']
```

```
    train_labels = data['y_train']
```

```
    test_examples = data['x_test']
```

```
    test_labels = data['y_test']
```

```
# Load them with tf.data
```

```
train_dataset = tf.data.Dataset.from_tensor_slices((train_examples, train_labels))
```

```
test_dataset = tf.data.Dataset.from_tensor_slices((test_examples, test_labels))
```

```
# Apply transformations like batch, shuffle to the dataset
```

```
train_dataset = train_dataset.shuffle(100).batch(64)
```

```
test_dataset = test_dataset.batch(64)
```

```
X, y = next(iter(train_dataset))  
input_shape = X.numpy().shape[1:]
```

```
# Create a simple sequential model comprising of a Dense layer
```

```
model = tf.keras.Sequential([  
    tf.keras.layers.Flatten(input_shape=input_shape),  
    ...  
    tf.keras.layers.Dense(10, activation='softmax')])
```

```
model.compile(optimizer=tf.keras.optimizers.RMSprop(), loss=...,  
metrics=...])
```

```
# Train the model
```

```
model.fit(train_dataset, epochs=10)
```

```
X, y = next(iter(train_dataset))  
input_shape = X.numpy().shape[1:]
```

```
# Create a simple sequential model comprising of a Dense layer  
model = tf.keras.Sequential([  
    tf.keras.layers.Flatten(input_shape=input_shape),  
    ...  
    tf.keras.layers.Dense(10, activation='softmax')])
```

```
model.compile(optimizer=tf.keras.optimizers.RMSprop(), loss=...,  
metrics=...])
```

```
# Train the model  
model.fit(train_dataset, epochs=10)
```

```
csv_file = tf.keras.utils.get_file('heart.csv',  
    'https://storage.googleapis.com/applied-dl/heart.csv')
```

```
df = pd.read_csv(csv_file)  
df['thal'] = pd.Categorical(df['thal'])  
df['thal'] = df.thal.cat.codes
```

```
target = df.pop('target')
```

```
csv_file = tf.keras.utils.get_file('heart.csv', 'https://storage.googleapis.com/applied-dl/heart.csv')
```

```
df = pd.read_csv(csv_file)
```

```
df['thal'] = pd.Categorical(df['thal'])
```

```
df['thal'] = df.thal.cat.codes
```

```
target = df.pop('target')
```

	age	sex	cp	trestbps	chol	fbs	restecg	thalach	exang	oldpeak	slope	ca	thal
0	63	1	1	145	233	1	2	150	0	2.3	3	0	fixed
1	67	1	4	160	286	0	2	108	1	1.5	2	3	normal
2	67	1	4	120	229	0	2	129	1	2.6	2	2	reversible

```
dataset = tf.data.Dataset.from_tensor_slices((df.values, target.values))
train_dataset = dataset.shuffle(len(df)).batch(32)

model = tf.keras.Sequential([
    tf.keras.layers.Dense(10, activation='relu'),
    tf.keras.layers.Dense(10, activation='relu'),
    tf.keras.layers.Dense(1, activation='sigmoid')
])
model.compile(optimizer='adam',
              loss='binary_crossentropy',
              metrics=['accuracy'])

model.fit(train_dataset, epochs=15)
```



```
dict_slices = tf.data.Dataset.from_tensor_slices((df.to_dict('list'),  
                                                  target.values)).batch(16)
```

```
>>> for features, target in tfds.as_numpy(dict_slices.take(1)):  
    for (feature, value), label in zip(features.items(), target):  
        print('{} = {} \t Label = {}'.format(feature, value, label))
```

```
age   = [63 67 67 37 41 56 62 57 63 53 57 56 56 44 52 57]      Label = 0  
sex   = [1 1 1 1 0 1 0 0 1 1 1 0 1 1 1 1]      Label = 1  
cp    = [1 4 4 3 2 2 4 4 4 4 4 2 3 2 3 3]      Label = 0  
trestbps = [145 160 120 130 130 120 140 120 130 140 140 140 130 120 172 150]      Label = 0  
chol   = [233 286 229 250 204 236 268 354 254 203 192 294 256 263 199 168]      Label = 0  
...
```

```
dict_slices = tf.data.Dataset.from_tensor_slices((df.to_dict('list'),  
                                                  target.values)).batch(16)
```

```
>>> for features, target in tfds.as_numpy(dict_slices.take(1)):  
    for (feature, value), label in zip(features.items(), target):  
        print('{} = {} \t Label = {}'.format(feature, value, label))  
  
age = [63 67 67 37 41 56 62 57 63 53 57 56 56 44 52 57]      Label = 0  
sex = [1 1 1 1 0 1 0 0 1 1 1 0 1 1 1 1]      Label = 1  
cp = [1 4 4 3 2 2 4 4 4 4 4 2 3 2 3 3]      Label = 0  
trestbps = [145 160 120 130 130 120 140 120 130 140 140 140 130 120 172 150]      Label = 0  
chol = [233 286 229 250 204 236 268 354 254 203 192 294 256 263 199 168]      Label = 0  
...
```

```
# Constructing the inputs for all the dense features
inputs = {key: tf.keras.layers.Input(shape=(), name=key) for key in df.keys()}
x = tf.stack(list(inputs.values()), axis=-1)
x = tf.keras.layers.Dense(10, activation='relu')(x)

# The single output denoting the target's probability
output = tf.keras.layers.Dense(1, activation='sigmoid')(x)

model = tf.keras.Model(inputs=inputs, outputs=output)
model.compile(optimizer='adam',
              loss='binary_crossentropy',
              metrics=['accuracy'])

model.fit(dict_slices, epochs=15)
```

```
# Constructing the inputs for all the dense features
inputs = {key: tf.keras.layers.Input(shape=(), name=key) for key in df.keys()}
x = tf.stack(list(inputs.values()), axis=-1)
x = tf.keras.layers.Dense(10, activation='relu')(x)

# The single output denoting the target's probability
output = tf.keras.layers.Dense(1, activation='sigmoid')(x)

model = tf.keras.Model(inputs=inputs, outputs=output)
model.compile(optimizer='adam',
              loss='binary_crossentropy',
              metrics=['accuracy'])

model.fit(dict_slices, epochs=15)
```

```
DATA_URL = '[insert URL here]'\n\ndata_root_orig = tf.keras.utils.get_file(origin=DATA_URL,\n                                         fname='flower_photos', untar=True)\n\ndata_root = pathlib.Path(data_root_orig)\n\n# Load all the file paths in the directory\nall_image_paths = list(data_root.glob('*/*'))\nall_image_paths = [str(path) for path in all_image_paths]\n\n# Gather the list of labels and create a labelmap\nlabel_names = sorted(item.name for item in data_root.glob('*/*') if item.is_dir())\nlabel_to_index = dict((name, index) for index, name in enumerate(label_names))\n\n# Use the label map to fetch all categorical labels\nall_image_labels = [label_to_index[pathlib.Path(path).parent.name]\n                    for path in all_image_paths]
```

```
DATA_URL = '[insert URL here]'\ndata_root_orig = tf.keras.utils.get_file(origin=DATA_URL,\n                                          fname='flower_photos', untar=True)\ndata_root = pathlib.Path(data_root_orig)\n\n# Load all the file paths in the directory\nall_image_paths = list(data_root.glob('*/*'))\nall_image_paths = [str(path) for path in all_image_paths]\n\n# Gather the list of labels and create a labelmap\nlabel_names = sorted(item.name for item in data_root.glob('*/*') if item.is_dir())\nlabel_to_index = dict((name, index) for index, name in enumerate(label_names))\n\n# Use the label map to fetch all categorical labels\nall_image_labels = [label_to_index[pathlib.Path(path).parent.name]\n                    for path in all_image_paths]
```

```
DATA_URL = '[insert URL here]'
data_root_orig = tf.keras.utils.get_file(origin=DATA_URL,
                                          fname='flower_photos', untar=True)
data_root = pathlib.Path(data_root_orig)

# Load all the file paths in the directory
all_image_paths = list(data_root.glob('*/*'))
all_image_paths = [str(path) for path in all_image_paths]

# Gather the list of labels and create a labelmap
label_names = sorted(item.name for item in data_root.glob('*/*') if item.is_dir())
label_to_index = dict((name, index) for index, name in enumerate(label_names))

# Use the label map to fetch all categorical labels
all_image_labels = [label_to_index[pathlib.Path(path).parent.name]
                    for path in all_image_paths]
```

```
DATA_URL = '[insert URL here]'
data_root_orig = tf.keras.utils.get_file(origin=DATA_URL,
                                          fname='flower_photos', untar=True)
data_root = pathlib.Path(data_root_orig)

# Load all the file paths in the directory
all_image_paths = list(data_root.glob('*/*'))
all_image_paths = [str(path) for path in all_image_paths]

# Gather the list of labels and create a labelmap
label_names = sorted(item.name for item in data_root.glob('*/*') if item.is_dir())
label_to_index = dict((name, index) for index, name in enumerate(label_names))

# Use the label map to fetch all categorical labels
all_image_labels = [label_to_index[pathlib.Path(path).parent.name]
                    for path in all_image_paths]
```



```
path_ds = tf.data.Dataset.from_tensor_slices(all_image_paths)
label_ds = tf.data.Dataset.from_tensor_slices(all_image_labels)
```

```
def preprocess_image(path):
    image = tf.io.read_file(path)
    image = tf.image.decode_jpeg(image, channels=3)
    image = tf.image.resize(image, [192, 192])
    image /= 255.0 # normalize to [0,1] range
    return image
```

```
image_ds = path_ds.map(preprocess_image)
image_label_ds = tf.data.Dataset.zip((image_ds, label_ds))
```

```
path_ds = tf.data.Dataset.from_tensor_slices(all_image_paths)
label_ds = tf.data.Dataset.from_tensor_slices(all_image_labels)
```

```
def preprocess_image(path):
    image = tf.io.read_file(path)
    image = tf.image.decode_jpeg(image, channels=3)
    image = tf.image.resize(image, [192, 192])
    image /= 255.0 # normalize to [0,1] range
    return image
```

```
image_ds = path_ds.map(preprocess_image)
image_label_ds = tf.data.Dataset.zip((image_ds, label_ds))
```

```
path_ds = tf.data.Dataset.from_tensor_slices(all_image_paths)
label_ds = tf.data.Dataset.from_tensor_slices(all_image_labels)
```

```
def preprocess_image(path):
    image = tf.io.read_file(path)
    image = tf.image.decode_jpeg(image, channels=3)
    image = tf.image.resize(image, [192, 192])
    image /= 255.0 # normalize to [0,1] range
    return image
```

```
image_ds = path_ds.map(preprocess_image)
image_label_ds = tf.data.Dataset.zip((image_ds, label_ds))
```

```
path_ds = tf.data.Dataset.from_tensor_slices(all_image_paths)
label_ds = tf.data.Dataset.from_tensor_slices(all_image_labels)
```

```
def preprocess_image(path):
    image = tf.io.read_file(path)
    image = tf.image.decode_jpeg(image, channels=3)
    image = tf.image.resize(image, [192, 192])
    image /= 255.0 # normalize to [0,1] range
    return image
```

```
image_ds = path_ds.map(preprocess_image)
image_label_ds = tf.data.Dataset.zip((image_ds, label_ds))
```

```
BATCH_SIZE = 32
ds = image_label_ds.shuffle(
    buffer_size=len(all_image_paths)).repeat().batch(BATCH_SIZE)

steps_per_epoch=tf.math.ceil(len(all_image_paths) / BATCH_SIZE).numpy()

model.fit(ds, epochs=1, steps_per_epoch=steps_per_epoch)
```

```
train_file_path = tf.keras.utils.get_file(
    "train.csv", "https://storage.googleapis.com/tf-datasets/titanic/train.csv")
test_file_path = tf.keras.utils.get_file(
    "Eval.csv", "https://storage.googleapis.com/tf-datasets/titanic/eval.csv")

def get_dataset(file_path, **kwargs):
    dataset = tf.data.experimental.make_csv_dataset(
        file_path,
        batch_size=5, # Artificially small to make examples easier to show.
        label_name='survived',
        na_value="?",
        num_epochs=1,
        ignore_errors=True,
        **kwargs)
    return dataset

raw_train_data = get_dataset(train_file_path)
raw_test_data = get_dataset(test_file_path)
```

```
train_file_path = tf.keras.utils.get_file(
    "train.csv", "https://storage.googleapis.com/tf-datasets/titanic/train.csv")
test_file_path = tf.keras.utils.get_file(
    "Eval.csv", "https://storage.googleapis.com/tf-datasets/titanic/eval.csv")

def get_dataset(file_path, **kwargs):
    dataset = tf.data.experimental.make_csv_dataset(
        file_path,
        batch_size=5, # Artificially small to make examples easier to show.
        label_name='survived',
        na_value="?",
        num_epochs=1,
        ignore_errors=True,
        **kwargs)
    return dataset

raw_train_data = get_dataset(train_file_path)
raw_test_data = get_dataset(test_file_path)
```

```
train_file_path = tf.keras.utils.get_file(
    "train.csv", "https://storage.googleapis.com/tf-datasets/titanic/train.csv")
test_file_path = tf.keras.utils.get_file(
    "Eval.csv", "https://storage.googleapis.com/tf-datasets/titanic/eval.csv")

def get_dataset(file_path, **kwargs):
    dataset = tf.data.experimental.make_csv_dataset(
        file_path,
        batch_size=5, # Artificially small to make examples easier to show.
        label_name='survived',
        na_value="?",
        num_epochs=1,
        ignore_errors=True,
        **kwargs)
    return dataset

raw_train_data = get_dataset(train_file_path)
raw_test_data = get_dataset(test_file_path)
```



```
def show_batch(dataset):  
    for batch, label in dataset.take(1):  
        for key, value in batch.items():  
            print("{:20s}: {}".format(key, value.numpy()))  
  
>>> show_batch(get_dataset(train_file_path))  
sex                : [b'female' b'female' b'female' b'male' b'male']  
age                : [40. 28. 52. 50. 34.]  
n_siblings_spouses : [0 0 1 0 1]  
parch             : [0 0 0 0 0]  
fare              : [13.      7.75   78.2667 13.      21.      ]  
class             : [b'Second' b'Third' b'First' b'Second' b'Second']  
deck              : [b'unknown' b'unknown' b'D' b'unknown' b'unknown']  
embark_town       : [b'Southampton' b'Queenstown' b'Cherbourg' b'Southampton' ...]  
alone            : [b'y' b'y' b'n' b'y' b'n']
```

```
CSV_COLUMNS = ['survived', 'sex', 'age', 'n_siblings_spouses', 'parch', 'fare',  
'class', 'deck', 'embark_town', 'alone']
```

```
temp_dataset = get_dataset(train_file_path, column_names=CSV_COLUMNS)
```

```
>>> show_batch(temp_dataset)
```

```
sex          : [b'female' b'male' b'male' b'male' b'male']  
age          : [15. 29. 49. 35. 22.]  
n_siblings_spouses : [1 1 1 0 0]  
parch        : [0 0 1 0 0]  
fare         : [ 14.4542  21.      110.8833   7.125    7.125 ]  
class        : [b'Third' b'Second' b'First' b'Third' b'Third']  
deck         : [b'unknown' b'unknown' b'C' b'unknown' b'unknown']  
embark_town  : [b'Cherbourg' b'Southampton' b'Cherbourg' b'Southampton'..]  
alone        : [b'n' b'n' b'n' b'y' b'y']
```

```
SELECT_COLUMNS = ['survived', 'age', 'n_siblings_spouses', 'class', 'deck', 'alone']  
temp_dataset = get_dataset(train_file_path, select_columns=SELECT_COLUMNS)
```

```
>>> show_batch(temp_dataset)  
age           : [60. 34. 28. 40. 28.]  
n_siblings_spouses : [1 1 1 0 0]  
class         : [b'Second' b'Third' b'Third' b'First' b'Third']  
deck          : [b'unknown' b'unknown' b'unknown' b'B' b'unknown']  
alone         : [b'n' b'n' b'n' b'y' b'y']
```

```
SELECT_COLUMNS = ['survived', 'age', 'n_siblings_spouses', 'parch', 'fare']
```

```
DEFAULTS = [0, 0.0, 0.0, 0.0, 0.0]
```

```
temp_dataset = get_dataset(train_file_path,  
                           select_columns=SELECT_COLUMNS,  
                           column_defaults=DEFAULTS)
```

```
# Function that will pack together all the columns:
```

```
def pack(features, label):
```

```
    return tf.stack(list(features.values()), axis=-1), label
```

```
packed_dataset = temp_dataset.map(pack)
```

```
SELECT_COLUMNS = ['survived', 'age', 'n_siblings_spouses', 'parch', 'fare']
```

```
DEFAULTS = [0, 0.0, 0.0, 0.0, 0.0]
```

```
temp_dataset = get_dataset(train_file_path,  
                           select_columns=SELECT_COLUMNS,  
                           column_defaults=DEFAULTS)
```

```
# Function that will pack together all the columns:
```

```
def pack(features, label):
```

```
    return tf.stack(list(features.values()), axis=-1), label
```

```
packed_dataset = temp_dataset.map(pack)
```

```
NUMERIC_FEATURES = ['age', 'n_siblings_spouses', 'parch', 'fare']
```

```
class PackNumericFeatures(object):  
    def __init__(self, names):  
        self.names = names  
  
    def __call__(self, features, labels):  
        numeric_features = [features.pop(name) for name in self.names]  
        numeric_features = [tf.cast(feats, tf.float32)  
                             for feats in numeric_features]  
        numeric_features = tf.stack(numeric_features, axis=-1)  
        features['numeric'] = numeric_features  
  
        return features, labels  
  
packed_train_data = raw_train_data.map(  
    PackNumericFeatures(NUMERIC_FEATURES))  
packed_test_data = raw_test_data.map(  
    PackNumericFeatures(NUMERIC_FEATURES))
```

```
NUMERIC_FEATURES = ['age', 'n_siblings_spouses', 'parch', 'fare']
```

```
class PackNumericFeatures(object):  
    def __init__(self, names):  
        self.names = names  
  
    def __call__(self, features, labels):  
        numeric_features = [features.pop(name) for name in self.names]  
        numeric_features = [tf.cast(feats, tf.float32)  
                            for feats in numeric_features]  
        numeric_features = tf.stack(numeric_features, axis=-1)  
        features['numeric'] = numeric_features  
  
        return features, labels  
  
packed_train_data = raw_train_data.map(  
    PackNumericFeatures(NUMERIC_FEATURES))  
packed_test_data = raw_test_data.map(  
    PackNumericFeatures(NUMERIC_FEATURES))
```

```
NUMERIC_FEATURES = ['age', 'n_siblings_spouses', 'parch', 'fare']
```

```
class PackNumericFeatures(object):  
    def __init__(self, names):  
        self.names = names  
  
    def __call__(self, features, labels):  
        numeric_features = [features.pop(name) for name in self.names]  
        numeric_features = [tf.cast(feats, tf.float32)  
                             for feats in numeric_features]  
        numeric_features = tf.stack(numeric_features, axis=-1)  
        features['numeric'] = numeric_features  
  
        return features, labels  
  
packed_train_data = raw_train_data.map(  
    PackNumericFeatures(NUMERIC_FEATURES))  
packed_test_data = raw_test_data.map(  
    PackNumericFeatures(NUMERIC_FEATURES))
```



```
>>> show_batch(packed_train_data)
sex          : [b'male' b'male' ...]
class        : [b'First' b'Third' ...]
deck         : [b'unknown' b'unknown' ...]
embark_town  : [b'Cherbourg' b'Southampton' ...]
alone        : [b'n' b'y' ...]
numeric      : [[28.      1.  ...]
                 [49.      0.  ...]
                 [27.      0.  ...]
                 [0.83     0.  ...]
                 [28.      0.  ...]]
```

```
NUMERIC_FEATURES = ['age', 'n_siblings_spouses', 'parch', 'fare']
```

```
def normalize_numeric_data(data, mean, std):  
    # Center the data  
    return (data-mean)/std
```

```
desc = pd.read_csv(train_file_path)[NUMERIC_FEATURES].describe()
```

```
MEAN, STD = np.array(desc.T['mean']), np.array(desc.T['std'])
```

```
normalizer = functools.partial(normalize_numeric_data,  
                                mean=MEAN,  
                                std=STD)
```

```
numeric_column = tf.feature_column.numeric_column(  
    'numeric',  
    normalizer_fn=normalizer,  
    shape=[len(NUMERIC_FEATURES)])
```

```
NUMERIC_FEATURES = ['age', 'n_siblings_spouses', 'parch', 'fare']
```

```
def normalize_numeric_data(data, mean, std):  
    # Center the data  
    return (data-mean)/std
```

```
desc = pd.read_csv(train_file_path)[NUMERIC_FEATURES].describe()
```

```
MEAN, STD = np.array(desc.T['mean']), np.array(desc.T['std'])
```

```
normalizer = functools.partial(normalize_numeric_data,  
                                mean=MEAN,  
                                std=STD)
```

```
numeric_column = tf.feature_column.numeric_column(  
    'numeric',  
    normalizer_fn=normalizer,  
    shape=[len(NUMERIC_FEATURES)])
```

```
NUMERIC_FEATURES = ['age', 'n_siblings_spouses', 'parch', 'fare']
```

```
def normalize_numeric_data(data, mean, std):  
    # Center the data  
    return (data-mean)/std
```

```
desc = pd.read_csv(train_file_path)[NUMERIC_FEATURES].describe()
```

```
MEAN, STD = np.array(desc.T['mean']), np.array(desc.T['std'])
```

```
normalizer = functools.partial(normalize_numeric_data,  
                                mean=MEAN,  
                                std=STD)
```

```
numeric_column = tf.feature_column.numeric_column(  
    'numeric',  
    normalizer_fn=normalizer,  
    shape=[len(NUMERIC_FEATURES)])
```

```
NUMERIC_FEATURES = ['age', 'n_siblings_spouses', 'parch', 'fare']
```

```
def normalize_numeric_data(data, mean, std):  
    # Center the data  
    return (data-mean)/std
```

```
desc = pd.read_csv(train_file_path)[NUMERIC_FEATURES].describe()
```

```
MEAN, STD = np.array(desc.T['mean']), np.array(desc.T['std'])
```

```
normalizer = functools.partial(normalize_numeric_data,  
                                mean=MEAN,  
                                std=STD)
```

```
numeric_column = tf.feature_column.numeric_column(  
    'numeric',  
    normalizer_fn=normalizer,  
    shape=[len(NUMERIC_FEATURES)])
```

```
CATEGORIES = {  
    'sex': ['male', 'female'],  
    'class' : ['First', 'Second', 'Third'],  
    'deck' : ['A', 'B', 'C', 'D', 'E', 'F', 'G', 'H', 'I', 'J'],  
    'embark_town' : ['Cherbourg', 'Southampton', 'Queenstown'],  
    'alone' : ['y', 'n']  
}
```

```
cat_feature_col = tf.feature_column.categorical_column_with_vocabulary_list(  
    key='class',  
    vocabulary_list=['First', 'Second', 'Third'])
```

```
categorical_column = tf.feature_column.indicator_column(cat_feature_col)
```

```
dense_features= tf.keras.layers.DenseFeatures(categorical_columns+numeric_columns)
```

```
model = tf.keras.Sequential([  
    dense_features,  
    tf.keras.layers.Dense(128, activation='relu'),  
    tf.keras.layers.Dense(128, activation='relu'),  
    tf.keras.layers.Dense(1, activation='sigmoid'),  
])
```

```
model.compile(  
    loss='binary_crossentropy',  
    optimizer='adam',  
    metrics=[ 'accuracy' ])
```

```
model.fit(packed_train_data, epochs=20)
```

```
dense_features= tf.keras.layers.DenseFeatures(categorical_columns+numeric_columns)
```

```
model = tf.keras.Sequential([  
    dense_features,  
    tf.keras.layers.Dense(128, activation='relu'),  
    tf.keras.layers.Dense(128, activation='relu'),  
    tf.keras.layers.Dense(1, activation='sigmoid'),  
])
```

```
model.compile(  
    loss='binary_crossentropy',  
    optimizer='adam',  
    metrics=[ 'accuracy' ])
```

```
model.fit(packed_train_data, epochs=20)
```



```
dense_features= tf.keras.layers.DenseFeatures(categorical_columns+numeric_columns)

model = tf.keras.Sequential([
    dense_features,
    tf.keras.layers.Dense(128, activation='relu'),
    tf.keras.layers.Dense(128, activation='relu'),
    tf.keras.layers.Dense(1, activation='sigmoid'),
])

model.compile(
    loss='binary_crossentropy',
    optimizer='adam',
    metrics=[ 'accuracy' ])

model.fit(packed_train_data, epochs=20)
```

```
DIRECTORY_URL = 'https://storage.googleapis.com/download.tensorflow.org/data/illiad/'
FILE_NAMES = ['cowper.txt', 'derby.txt', 'butler.txt']

def labeler(example, index):
    return example, tf.cast(index, tf.int64)

labeled_data_sets = []
for i, file_name in enumerate(FILE_NAMES):
    file_path = tf.keras.utils.get_file(name, origin=DIRECTORY_URL+file_name)
    lines_dataset = tf.data.TextLineDataset(file_path)
    labeled_dataset = lines_dataset.map(lambda ex: labeler(ex, i))
    labeled_data_sets.append(labeled_dataset)
```

```
DIRECTORY_URL = 'https://storage.googleapis.com/download.tensorflow.org/data/illiad/'
FILE_NAMES = ['cowper.txt', 'derby.txt', 'butler.txt']

def labeler(example, index):
    return example, tf.cast(index, tf.int64)

labeled_data_sets = []
for i, file_name in enumerate(FILE_NAMES):
    file_path = tf.keras.utils.get_file(name, origin=DIRECTORY_URL+file_name)
    lines_dataset = tf.data.TextLineDataset(file_path)
    labeled_dataset = lines_dataset.map(lambda ex: labeler(ex, i))
    labeled_data_sets.append(labeled_dataset)
```

```
dataset = labeled_data_sets[0]
for labeled_dataset in labeled_data_sets[1:]:
    dataset = dataset.concatenate(labeled_dataset)

dataset = dataset.shuffle(buffer_size=50000)

>>> for ex in dataset.take(5):
        print(ex[0].numpy(), ex[1].numpy())
b"Eight barbed arrows have I shot e'en now," 1
b'In thy own band; the Achaians shall for him,' 0
b"Upon their well-mann'd ships, should Heaven vouchsafe" 1
b'He shall not cozen me! Of him, enough!' 1
b'Turns flying, marks him with a steadfast eye,' 0
```

```
tokenizer = tfds.features.text.Tokenizer()

vocabulary_set = set()
for text_tensor, _ in all_labeled_data:
    some_tokens = tokenizer.tokenize(text_tensor.numpy())
    vocabulary_set.update(some_tokens)

vocab_size = len(vocabulary_set)
>>> vocab_size
17178
```

<https://www.coursera.org/learn/natural-language-processing-tensorflow>

Browse > Data Science > Machine Learning

Offered By

This course is part of the **TensorFlow in Practice Specialization**



# Sequences, Time Series and Prediction

★★★★★ 4.6 580 ratings • 98 reviews

**Enroll for Free**

Starts Oct 08

Financial aid available

**10,372** already enrolled!

```
# Show one of the labeled data
```

```
original_text = next(iter(all_labeled_data))[0].numpy()
```

```
# Create an text encoder with a fixed vocabulary set
```

```
encoder = tfds.features.text.TokenTextEncoder(vocabulary_set)
```

```
# Encode an example
```

```
encoded_text = encoder.encode(original_text)
```

```
Original text  b"As honour's meed, the mighty monarch gave."
```

```
Encoded text  [16814, 4289, 11591, 15925, 177, 10357, 11207, 16715]
```

```
def encode(text_tensor, label):  
    encoded_text = encoder.encode(text_tensor.numpy())  
    return encoded_text, label  
  
def encode_map_fn(text, label):  
    return tf.py_function(encode, inp=[text, label],  
                           Tout=(tf.int64, tf.int64))  
  
all_encoded_data = all_labeled_data.map(encode_map_fn)
```



```
BUFFER_SIZE = 50000
```

```
BATCH_SIZE = 64
```

```
TAKE_SIZE = 5000
```

```
train_data = all_encoded_data.skip(TAKE_SIZE).shuffle(BUFFER_SIZE)
```

```
train_data = train_data.padded_batch(BATCH_SIZE, padded_shapes=([-1], []))
```

```
test_data = all_encoded_data.take(TAKE_SIZE)
```

```
test_data = test_data.padded_batch(BATCH_SIZE, padded_shapes=([-1], []))
```

```
model = tf.keras.Sequential([
    tf.keras.layers.Embedding(vocab_size, 64),
    tf.keras.layers.Bidirectional(tf.keras.layers.LSTM(64)),
    tf.keras.Sequential([
        tf.keras.layers.Dense(units, activation='relu') for units in [64, 64]
    ]),
    tf.keras.layers.Dense(3, activation='softmax')
])

model.compile(optimizer='adam',
              loss='sparse_categorical_crossentropy',
              metrics=['accuracy'])

model.fit(train_data, epochs=3)
```