

grant_type
string | (string | null)
pattern: ^password\$

☐ Send empty value

username * required
string

password * required
string(\$password)

scope
string

☒ Send empty value

client_id
string | (string | null)

☐ Send empty value

client_secret
string | (string | null)(\$password)

☐ Send empty value

Execute

Clear

```
curl -X 'POST' \
  'http://127.0.0.1:8000/login' \
  -H 'accept: application/json' \
  -H 'Content-Type: application/x-www-form-urlencoded' \
  -d 'grant_type=password&username=101&password=abc123&scope=&client_id=string&client_secret=*****'
```

Request URL

http://127.0.0.1:8000/login

Server response

Code Details

200

Response body

```
{
  "access_token": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJzdWIiOiIxMDEiLCJyb2x1Ijoic3R1ZGVudCJ9.NHqwkDLPBiq5BFQ1ikmdowvL0jbLUMdHm4aRQGwK1zI",
  "token_type": "bearer"
}
```



Download

Response headers

```
content-length: 162
content-type: application/json
date: Tue, 15 Sep 2026 07:32:22 GMT
server: uvicorn
```

Responses

Code	Description	Links
200	Successful Response	No links

Media type

application/json

Controls Accept header.

Example Value | Schema

```
curl -X 'GET' \
  'http://127.0.0.1:8000/profile' \
  -H 'accept: application/json' \
  -H 'Authorization: Bearer eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJzdWIiOiIxMDEiLCJyb2x1Ijoic3R1ZGVudCJ9.NHqwkDLPB1Q5BFQ11KmdoWVLOjblUMdHm4aRQ6MCIzI'
```

Request URL

http://127.0.0.1:8000/profile

Server response

Code	Details
200	Response body <pre>{ "message": "Welcome to your profile", "user_id": "101", "role": "student" }</pre> Response headers <pre>content-length: 70 content-type: application/json date: Tue, 15 Sep 2026 07:34:21 GMT server: uvicorn</pre>

Responses

Code	Description	Links
200	Successful Response	No links

Media type

application/json

Controls Accept header.

Example Value | Schema

Available authorizations

Scopes are used to grant an application different levels of access to data on behalf of the end user. Each API may declare one or more scopes. API requires the following scopes. Select which ones you want to grant to Swagger UI.

OAuth2PasswordBearer (OAuth2, password)

Token URL: login
Flow: password

username:

password:

Client credentials location:

Authorization header

client_id:

client_secret:

Authorize Close

http://127.0.0.1:8000/profile

Server response

Code	Details
401 <i>Undocumented</i>	Error: Unauthorized Response body <pre>{ "detail": "Not authenticated" }</pre> Response headers <pre>content-length: 30 content-type: application/json date: Tue, 15 Sep 2026 07:35:28 GMT server: uvicorn www-authenticate: Bearer</pre>

Responses

Code	Description	Links
200	Successful Response	No links

Media type

application/json

Controls Accept header.

Example Value | Schema

"string"

http://127.0.0.1:8000/login \n
-H 'accept: application/json' \n
-H 'Content-Type: application/x-www-form-urlencoded' \n
-d 'grant_type=password&username=101&password=sdmnsdmnsdmns&scope=&client_id=string&client_secret=*****'

Request URL

http://127.0.0.1:8000/login

Server response

Code	Details
401 <i>Undocumented</i>	Error: Unauthorized Response body <pre>{ "detail": "Invalid username or password" }</pre> Response headers <pre>content-length: 41 content-type: application/json date: Tue, 15 Sep 2026 07:36:03 GMT server: uvicorn</pre>

Responses

Code	Description	Links
200	Successful Response	No links

Media type

application/json

Controls Accept header.

Example Value | Schema