

# Keras

In this module we will introduce Keras (<https://keras.io/>), a high level API for Neural Networks.

To be specific

- we will mostly restrict ourselves to the Keras Sequential model
- this will greatly simplify your learning and coding
- it will restrict the type of Deep Learning programs that you can write
  - but not a meaningful restriction for the simple programs that you will write in this course

After we introduce the high level Keras API

- we will review the history of Deep Learning programming to see how we got here
- this will give you greater insight into what Keras does "under the covers"
  - appreciate history
  - aid your diagnostics

**Note:**

The code snippets in this notebook are *fragments* of a larger [notebook](#) ([DNN TensorFlow example.ipynb](#)).

- are illustrative: will not actually execute in this notebook but will in the complete notebook

Confusion warning:

- There are two similar *but different* packages that implement Keras
  - one built into TensorFlow (the one we will use)
  - a separate project

TL;DR

YES

- `import tensorflow as tf`  
    `tf.keras.layers.Dense(...)`
- `from tensorflow import keras`  
    `keras.layers.Dense(...)`

NO

- `import keras`  
    `keras.layers.Dense( ... )`

If you want to know the details, visit this [notebook](#)  
([Tensorflow Keras Archaeology.ipynb#tensorflow.keras-vs-keras-\(Confusion-alert\)](#))

# The Keras Sequential Model

Reference: [Getting started with the Keras Sequential Model \(https://keras.io/getting-started/sequential-model-guide/\)](https://keras.io/getting-started/sequential-model-guide/).

Keras has two programming models

- Sequential
- Functional

We will start with the Sequential model

The Sequential model allows you to build Neural Networks (NN) that are composed of a *sequence* of layers

- just like our cartoon
- a very prevalent paradigm

This will likely be sufficient in your initial studies

- but it restricts the architecture of the Neural Networks that you can build
- use the Functional API for full generality
  - but it might appear more complicated

Let's jump into some code.

Some old friends, in new clothing:



```
import tensorflow as tf from tensorflow.keras.models import Model, Sequential from tensorflow.keras
import layers # Regression reg_model = Sequential([ layers.Dense(1, activation=None,
input_dim=x.shape[1]) ]) reg_model.compile(optimizer='rmsprop', loss='mse') reg_model.fit(x, y,
nb_epoch=10, validation_data=(x_val, y_val ))
```

- A model uses the Sequential architecture
- A sequence (implemented as an array) of layers
  - Single element array
  - Consisting of a Dense (Fully connected) layer
    - with 1 output
    - No activation
    - Implements Regression
- Loss is mse

```
# Classification
class_model = Sequential([ layers.Dense(1, activation="sigmoid", input_dim=x.shape[1]) ])
class_model.compile(optimizer='rmsprop', loss='binary_crossentropy')
class_model.fit(x, y, nb_epoch=10, validation_data=(x_val, y_val))
```

- A model uses the `Sequential` architecture
- A sequence (implemented as an array) of layers
  - Single element array
  - Consisting of a `Dense` (Fully connected) layer
    - with 1 output: binary classification
    - sigmoid activation
    - Implements Classification
- Loss is `binary_crossentropy`

## TL;DR

- Both examples are a single layer
  - Dense, with 1 unit ("neuron")
- Regression example
  - No activation
  - MSE loss
- Binary classification example
  - Sigmoid activation
  - Binary cross entropy loss

Hopefully you get the idea.

Let's explore a slightly more complicated model.

```
import tensorflow as tf from tensorflow.keras.models import Model, Sequential from tensorflow.keras
import layers mnist_model = Sequential([ layers.Dense(n_hidden_1, activation=tf.nn.relu, name="hidden1",
input_shape=(input_size,)), layers.Dense(n_hidden_2, activation=tf.nn.relu, name="hidden2")
layers.Dense(output_size,activation=tf.nn.softmax, name="outputs") ])
```

- A model uses the Sequential architecture
- A sequence (implemented as an array) of layers
  - 3 layers (3 element array)
    - 2 Dense layers
      - with varying number of outputs: n\_hidden\_1,n\_hidden\_2
      - relu activation
    - A Dense layer implementing Multinomial Classification
      - number of outputs equal to number of classes
      - softmax activation



- The first two layers "transform" the input
- The "head" layer implements Multinomial Classification

To use the model, you first need to "compile" it

```
metrics = [ "acc" ] mnist_model.compile(optimizer='adam', loss='sparse_categorical_crossentropy',  
metrics=metrics)
```

"Compiling" is quite significant as we will demonstrate later

- For now: *it is where you define the Loss function*

Next, just as in `sklearn`: you "fit" the model to the training data.

```
history = mnist_model.fit(X_train, y_train, epochs=n_epochs, batch_size=batch_size, validation_data=(X_valid, y_valid), shuffle=True)
```

Once the model is fit, you can predict, just like `sklearn`.

Here we evaluate the model on the Test dataset.

```
test_loss, test_accuracy = mnist_model.evaluate(X_test, y_test) print("Test dataset: loss={tl:5.4f}, accuracy={ta:5.4f}".format(tl=test_loss, ta=test_accuracy))
```

The idea is quite simple

- Keras Sequential implements an `sklearn`-like API
  - define a model
  - fit the model
  - predict

We have glossed over a lot of details

- What does each layer do ?
- Why do we need to "compile" ?
  - and why does it need an optimizer ?



## The Keras Functional Model

- More verbose than Sequential
- Also more flexible
  - you can define more complex computation graphs (multiple inputs/outputs, shared layers)

```
from keras.layers import Input, Dense from keras.models import Model # This returns a tensor inputs =  
Input(shape=(784,)) # a layer instance is callable on a tensor, and returns a tensor x = Dense(32,  
activation='relu')(inputs) predictions = Dense(10, activation='softmax')(x) # This creates a model that  
includes # the Input layer and Dense layers model = Model(inputs=inputs, outputs=predictions)
```

## Highlights:

- Manually invoke a single layer at a time
  - Passing as input the output of the prior layer.
- You must define an `Input` layer (placeholder for the input/define its shape)
  - `Sequential` uses the `input_shape=` parameter to the first layer
- You "wrap" the graph into a "model" by a `Model` statement
  - looks like a function definition
    - names the input and output formal parameters
  - a `Model` acts just like a layer (but with internals that you create)

```
model.compile(optimizer='rmsprop', loss='categorical_crossentropy', metrics=['accuracy']) model.fit(data, labels) # starts training
```

As a beginner, you will probably exclusively use the Sequential model.

Keep the Functional API in the back of your mind.

# Let's code !

Lets see a working notebook.

Two options

- Run on your local machine: [DNN Tensorflow example Notebook local \(DNN TensorFlow example.ipynb\)](#) (local)
  - Tensorflow version 2+ only !
- Run on Google Colab: [DNN Tensorflow example Notebook from github \(https://colab.research.google.com/github/kenperry-public/ML\\_Spring\\_2022/blob/master/DNN\\_TensorFlow\\_example.ipynb\)](#) (Colab)

```
In [1]: print("Done")
```

Done